

INTERNATIONAL STANDARD

IEC
60191-6

Second edition
2004-09

Mechanical standardization of semiconductor devices –

Part 6: General rules for the preparation of outline drawings of surface mounted semiconductor device packages



Reference number
IEC 60191-6:2004(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC
60191-6

Second edition
2004-09

Mechanical standardization of semiconductor devices –

Part 6: General rules for the preparation of outline drawings of surface mounted semiconductor device packages

© IEC 2004 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

W

For price, see current catalogue

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Definitions	5
4 Design rules	7
5 Dimensions to be specified	7
6 Notes	7
Annex A (informative) Illustration of the rules.....	11
A.1 Gull-wing lead package with two parallel rows of terminals (SQP, TSQP Type 2).....	13
A.2 Gull-wing lead package with two parallel rows of terminals (TSQP Type 1).....	16
A.3 Gull-wing lead package with one row of terminals on each of four sides (QFP)	19
A.4 J-bent lead package with two parallel rows of terminals (SOJ)	22
A.5 Folded lead package with one row of terminals on each of four sides (QFJ).....	25
A.6 Leadless package	29
A.7-1 Ball grid array package (BGA) Type 1	32
A.7-2 Ball grid array package (BGA) Type 2	35
Annex B (informative) Optional table format.....	38
Figure 1 – Illustrations of terminal projection zone	12
Figure 2 – Isometric view of an example of gauge.....	12

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MECHANICAL STANDARDIZATION
OF SEMICONDUCTOR DEVICES –****Part 6: General rules for the preparation of outline drawings of
surface mounted semiconductor device packages**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60191-6 has been prepared by subcommittee 47D: Mechanical standardization of semiconductor devices, of IEC technical committee 47: Semiconductor devices.

This second edition of IEC 60191-6 cancels and replaces the first edition, published in 1990 and its amendment 1 (1999), and constitutes a technical revision. This includes the following significant changes with respect to the previous edition: improvement of the geometrical drawing format and addition of the examples of the drawing of major packages.

The text of this standard is based on the following documents:

FDIS	Report on voting
47D/584/FDIS	47D/587/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

Withdrawn
IECNORM.COM: Click to view the full PDF of IEC 60191-6:2004

MECHANICAL STANDARDIZATION OF SEMICONDUCTOR DEVICES –

Part 6: General rules for the preparation of outline drawings of surface mounted semiconductor device packages

1 Scope

This part of IEC 60191 gives general rules for the preparation of outlines drawings of surface-mounted semiconductor devices. It supplements IEC 60191-1 and 60191-3. It covers all surface-mounted devices-discrete semiconductors as well as integrated circuits classified as form E in Clause 3 of IEC 60191-4.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60191-1:1966, *Mechanical standardization of semiconductor devices – Part 1: Preparation of drawings of semiconductor devices*

IEC 60191-3:1999, *Mechanical standardization of semiconductor devices – Part 3: General rules for the preparation of outline drawings of integrated circuits*

IEC 60191-4:1999, *Mechanical standardization of semiconductor devices – Part 4: Coding system and classification into forms of package outlines for semiconductor devices*

ISO 1101:1983, *Technical drawings – Geometrical tolerancing – Tolerancing of form, orientation, location and run-out – Generalities, definitions, symbols, indications on drawings*

3 Definitions

For the purposes of this document, the following definitions apply.

3.1

seating plane

plane which designates the plane of contact of the package, including any stand-off, with the surface on which it will be mounted

NOTE This plane is often used as the reference plane.

3.2

reference plane

plane parallel to the seating plane at a distance A_3 above seating plane (does not apply to leadless package)

The distance A_3 is known as the reference plane distance. It determines the terminal projection zone (see Figure 1).

NOTE This distance is a theoretical dimension which is not related to any feature of the package. Its value is chosen for each package so the length of terminal projection zone L_p is a good approximation of the terminal length used for mounting, e.g. the length of the part of the terminal that is soldered to the substrate.

3.3

terminal position area

maximum area on the seating plane within which the terminal projection zone is located, taking into account the maximum values of L_p and b_p

The surface of the terminal position area is equal to $l_1 \times b_3$ with, generally

$$l_1 = L_p \text{ max.} + (HD_{\text{max}} - HD_{\text{min}})/2$$

$$= L_p \text{ max.} + (HE_{\text{max}} - HE_{\text{min}})/2$$

$$\text{and } b_3 = b_p \text{ max.} + x$$

Checking can be carried out by means of an appropriate gauge (see Figure 2).

3.4

pattern of terminal position areas

group of all terminal position areas of a leaded package or folded lead package in the seating plane

For a leadless package, it is the projection of its metallized pads or terminals on the seating plane.

The true positions of the centres of the terminal position areas are located on a grid with as modulus

$$e / e_D \quad \text{or} \quad e / e_E$$

The pattern of terminal position areas does not include tolerances stemming from mounting substrates (printed board) design and placement machine accuracy.

3.5

coplanarity of terminals

the requirement for coplanarity of terminals is given in a tolerance frame showing the ISO symbol for profile of a surface, the tolerance value y and the reference to the seating plane

Where the part of the terminal intended for soldering is a flat zone of defined dimension $b \times l$, with nominal position on the seating plane – e.g. pads of leadless packages – then the requirement for coplanarity of terminals is strictly the ISO requirement for flatness applied to these zones.

In all the other cases, the requirement for coplanarity of terminals is clarified by note.

3.6

datum

theoretically, the exact geometrical reference is established for controlling the tolerance zone when specifying a geometrical tolerance as a related feature

NOTE Datum S should be established by seating plane.

4 Design rules

The outline drawing of a surface-mounted semiconductor device package shall comprise in the given sequence

- the drawing (strictly speaking);
- the tables of dimensions;
- the notes to the tables and the drawings;
- the indication of supporting countries;
- the codification.

The drawing shall conform with the general rules for drawings laid down in IEC 60191-1 sections 1 and 2, as well as with the specific definitions of Clause 3 above.

The following Clauses 5 and 6 give, respectively, the tables of dimensions to be specified and the notes to be called, where relevant. Supplementary dimensions and notes may be added when required.

The codification of package outlines shall be in accordance with IEC 60191-4.

5 Dimensions to be specified

Crosses in Tables 1 and 2 indicate where values have to be specified. In the auxiliary right-hand column, a code indicates for which outline families each dimension is generally relevant, as follows:

L: leaded packages	packages with gull-wing leads	for example; QFP, SOP, TSOP
F: folded lead packages	packages with J-bent leads	for example; QFJ, SOJ
P: leadless packages	packages with no leads	for example; QFN
B: ball grid array packages	packages with ball leads	for example; BGA

6 Notes

Notes referred to in the tables and in the drawings appear after Table 2; in the auxiliary right-hand column, a code indicates for which outline families each note is generally relevant (with the same code as in Clause 5).

For each particular outline package or package family, the applicable notes shall be numbered sequentially from 1 in the order in the tables and then on the drawing.

Table 1 – Dimensions to be specified for Group 1

Group 1 - Group 1 includes dimensions and numerals associated with mounting of packages and kinds of packages. The dimensions and numerals belonging to the group mean values guaranteed to users and imply that mechanical compatibility of mounting of packages can be recognized.

Ref.	Min.	Nom.	Max.	Notes
n	-	x	-	2
nD	-	x	-	3
nE	-	x	-	3
A	-	-	x	
A1	x	-	x	
A2	-	x	-	
A3	-	x(*)	-	4
bp	x	-	x	4
Øbp	x	[x]	x	4
Øb	x	-	x	4
C	x	-	x	
D	x	x	x	4
E	x	x	x	4
e	-	x(*)	-	4
f	-	-	x	
HD	x	x	x	4
HE	x	x	x	4
h	x	-	x	
k	x	-	x	
k1	x	-	x	
Lp	x	-	x	4
t	-	-	x	
v	-	-	x	
w	-	-	x	
x	-	-	x	
x1	-	-	x	
y	-	-	x	
y1	-	-	x	
θ	x	-	x	

Concerned family

LFPB
LFP
LFP
LFPB
LFB
LF
LF
LFP
B
B
LF
LFPB
LFPB
LFPB
LF
LF
LF
F
P
P
LFP
LF
B
B
LFPB
B
LFPB
B
L


Table 2 – Dimensions to be specified for Group 2

Group 2 - Group 2 includes dimensions that do not belong to Group 1, but are associated with the fabrication of packages and dimensions of terminal position areas. The group is to achieve its own original purpose as an industry standard. The group belongs to the dimensions and numerals of external shapes of packages useful for design and manufacture and the dimensions of terminal position areas that can be referenced to in fabrications of mounting boards. Therefore, external dimensions of a package shall have nominal design values specified thereto.

Ref.	Min.	Nom.	Max.	Notes
b1	-	x	-	
b2	x	-	x	
b3	-	-	[x]	4
c1	-	x	-	
eD	-	x	-	4
eE	-	x	-	4
L	-	x	-	
L1	-	x	-	
L2	-	x	-	
l1	-	-	[x]	4
Sd	-	x	-	
SE	-	x	-	
Zd	-	x	-	
ZE	-	x	-	
G1D	-	x	-	
G1E	-	x	-	
h	-	x	-	

Concerned family

LF
F
LFPB
LF
FP
FP
LF
F
F
LFP
B
B
LFPB
LFPB
L
L
F

Notes to the tables	
1 All dimensions are in millimetres. 2 n refers to the total number of terminal positions. 3 n_D refers to the number of terminal positions on one side of the package in the direction of dimension D. n_E refers to the number of terminal positions on one side of the package in the direction of dimension E. 4 Check of the dimensions and positions of package terminal is validly performed when it is ensured that these terminal fit with the pattern of terminal position areas. This can be carried out by means of an appropriate gauge. (*) Means true geometrical position. [] Values given within square brackets are calculated values. 5 Zone of a visible index on the top face. 6 Terminal number designation shall be in accordance with annex C of IEC60191-3.  Means in this drawing that the distance from the seating plane to the nearest point of each terminal should not exceed y mm.  Means projected tolerance zone (see ISO 1101, clause 11). 7 Length of terminal pad number 1 shall be visibly greater than the length of the other terminal pads. 8 Index corner. 9 Seating plane S is defined by the spherical crowns of the solder balls. 10 Dimension ob is measured at the maximum solder ball diameter, parallel to seating plane S. 11 The thickness $A2$ of the package body, exclusive of the lid or encapsulation and ball height. 12 Stand-off $A1$ is optional, but when present they should be located on the ball matrix diagonals.	LFPB LF P F B

Annex A (informative)

Illustration of the rules

The above rules are illustrated by examples of application to several package families:

- gull-wing lead package with two parallel rows of terminals (SOP, TSOP, Type 2) (see A.1);
 - gull-wing lead package with two parallel rows of terminals (TSOP Type 1) (see A.2);
 - gull-wing lead package with one row of terminals on each of four sides (see A.3);
 - J-bend lead package with two parallel rows of terminals (see A.4);
 - folded lead package with one row of terminals on each of four sides (see A.5);
 - leadless package (see A.6);
 - ball grid array package (see A.7.1, A.7.2).
-




Figure 1a – Illustrations of terminal projection zone (a)





Figure 1b – Illustrations of terminal projection zone (b)

Figure 1 – Illustrations of terminal projection zone



IEC 669/04

Figure 2 – Isometric view of an example of gauge

A.1 Gull-wing lead package with two parallel rows of terminals (SOP, TSOP Type 2)




Figure 1a




Figure 1b




Figure 1c – Lead section




Figure 1d





Figure 2 – Pattern of terminal position areas



Date:

Group 1 - Group 1 includes dimensions and numerals associated with mounting of packages and kinds of packages. The dimensions and numerals belonging to the group mean values guaranteed to users and imply that mechanical compatibility of mounting of packages can be recognized.


Ref.	Min.	Nom.	Max.	Notes
n	-	x	-	2
A	-	-	x	
A1	x	-	x	
A2	-	x	-	
A3	-	x(*)	-	3
bp	x	-	x	3
c	x	-	x	
D	x	x	x	
E	x	x	x	
e	-	x(*)	-	3
HE	x	x	x	3
Lp	x	-	x	3
x	-	-	x	
y	-	-	x	
θ	x	-	x	3

Group 2 - Group 2 includes dimensions that do not belong to Group 1, but are associated with the fabrication of packages and dimensions of terminal position areas. The group is to achieve its own original purpose as an industry standard. The group belongs to the dimensions and numerals of external shapes of packages useful for design and manufacture and the dimensions of terminal position areas that can be referenced to in fabrications of mounting boards. Therefore, external dimensions of a package shall have nominal design values specified thereto.

Ref.	Min.	Nom.	Max.	Notes
b1	-	x	-	
b3	-	-	x	3
c1	-	x	-	
L	-	x	-	
L1	-	x	-	
l1	-	-	x	3
(ZD)	-	x	-	
G1E	-	x	-	

NOTES

- (*) Means true geometrical position.
- [] Values given within square brackets are calculated values.
- Ⓟ Means projected tolerance zone (see ISO 1101, Clause 11).



Means in this drawing that the distance from the seating plane to the nearest point of each terminal should not exceed y mm.

- 1 All dimensions are in millimetres.
- 2 n refers to the total number of terminal positions.
- 3 Verification of the dimensions and positions of package terminal is validly performed when it is ensured that these terminal fit with the pattern of terminal position areas. This can be carried out by means of an appropriate gauge.

A.2 Gull-wing lead package with two parallel rows of terminals (TSOP Type 1)




Figure 1a




Figure 1b




Figure 1c – Lead section




Figure 1d





Figure 2 – Pattern of terminal position areas



Date:

Group 1 - Group 1 includes dimensions and numerals associated with the mounting of packages and kinds of packages. The dimensions and numerals belonging to the group means values guaranteed to users and imply that mechanical compatibility of mounting of packages can be recognized.


Ref.	Min.	Nom.	Max.	Notes
n	-	x	-	2
A	-	-	x	
A1	x	-	x	
A2	-	x	-	
A3	-	x(*)	-	3
bp	x	-	x	3
c	x	-	x	
D	x	x	x	
E	x	x	x	
e	-	x(*)	-	3
Hd	x	x	x	3
Lp	x	-	x	3
x	-	-	x	
y	-	-	x	
θ	x		x	

Group 2 - Group 2 includes dimensions that do not belong to Group 1, but are associated with the fabrication of packages and dimensions of terminal position areas. The group is to achieve its own original purpose as an industry standard. The group belongs to the dimensions and numerals of external shapes of packages useful for design and manufacture and the dimensions of terminal position areas that can be referenced to in fabrications of mounting boards. Therefore, external dimensions of a package shall have nominal design values specified thereto.

Ref.	Min.	Nom.	Max.	Notes
b1	-	x	-	
b3	-	-	x	3
c1	-	x	-	
eD	-	x	-	3
L	-	x	-	
l1	-	-	x	3
(ZE)	-	x	-	
G1D	-	x	-	

NOTES

- (*) Means true geometrical position.
- [] Values given within square brackets are calculated values.
- Ⓟ Means projected tolerance zone (see ISO 1101, Clause 11).



Means in this drawing that the distance from the seating plane to the nearest point of each terminal should not exceed y mm.

- 1 All dimensions are in millimetres.
- 2 n refers to the total number of terminal positions.
- 3 Verification of the dimensions and positions of package terminal is validly performed when it is ensured that these terminal fit with the pattern of terminal position areas. This can be carried out by means of an appropriate gauge.

IECNORM.COM: Click to view the full PDF of IEC 60191-6:2004
 Withdrawing

A.3 Gull-wing lead package with one row of terminals on each of four sides (QFP)




Figure 1a

IEC 680/04




Figure 1b

IEC 681/04




Figure 1c – Lead section

IEC 682/04




Figure 1d

IEC 683/04





Figure 2 – Pattern of terminal position areas

IEC 684/04



Date:

Group 1 – Group 1 includes dimensions and numerals associated with the mounting of packages and kinds of packages. The dimensions and numerals belonging to the group mean values guaranteed to users and imply that mechanical compatibility of mounting of packages can be recognized.

Ref.	Min.	Nom.	Max.	Notes
n	-	x	-	2
nD	-	x	-	3
nE	-	x	-	3
A	-	-	x	
A1	x	-	x	
A2	-	x	-	
A3	-	x(*)	-	4
bp	x	-	x	4
c	x	-	x	
D	x	x	x	
E	x	x	x	
e	-	x(*)	-	4
f	-	-	x	
HD	x	x	x	4
HE	x	x	x	4
Lp	x	-	x	4
x	-	-	x	
y	-	-	x	
θ	x	-	x	

Group 2 - Group 2 includes dimensions that do not belong to Group 1, but are associated with the fabrication of packages and dimensions of terminal position areas. The group is to achieve its own original purpose as an industry standard. The group belongs to the dimensions and numerals of external shapes of packages useful for design and manufacture and the dimensions of terminal position areas that can be referenced to in fabrications of mounting boards. Therefore, external dimensions of a package shall have nominal design values specified thereto.


Ref.	Min.	Nom.	Max.	Notes
b1	-	x	-	
b3	-	-	x	4
c1	-	x	-	
L	-	x	-	
L1	-	x	-	
l1	-	-	x	4
(Z _D)	-	x	-	
(Z _E)	-	x	-	
G1D	-	x	-	
G1E	-	x	-	

NOTES

(*) Means true geometrical position.

[] Values given within square brackets are calculated values.

Ⓟ Means projected tolerance zone (see ISO 1101, Clause 11).



Means in this drawing that the distance from the seating plane to the nearest point of each terminal should not exceed y mm.

1 All dimensions are in millimetres.

2 n refers to the total number of terminal positions.

3 n_D refers to the number of terminal positions on one side of the package in the direction of dimension D.

n_E refers to the number of terminal positions on one side of the package in the direction of dimension E.

4 Verification of the dimensions and positions of package terminal is validly performed when it is ensured that these terminal fit with the pattern of terminal position areas. This can be carried out by means of an appropriate gauge.

A.4 J- bend lead package with two parallel rows of terminals (SOJ)




Figure 1a




Figure 1b




Figure 1c




Figure 1d

Figure 1e




Figure 1f





Figure 2 – Pattern of terminal position areas



Date:

Group 1 - Group 1 includes dimensions and numerals associated with the mounting of packages and kinds of packages. The dimensions and numerals belonging to the group mean values guaranteed to users and imply that mechanical compatibility of mounting of packages can be recognized.


Ref.	Min.	Nom.	Max.	Notes
n	-	x	-	2
A	-	-	x	
A1	x	-	x	
A2	-	x	-	
A3	-	x(*)	-	3
bp	x	-	x	3
b2	x	-	x	
c	x	-	x	
D	x	x	x	
E	x	x	x	
e	-	x(*)	-	3
HE	x	x	x	
Lp	x	-	x	3
t	-	-	x	
x	-	-	x	
y	-	-	x	

Group 2 - Group 2 includes dimensions that do not belong to Group 1, but are associated with the fabrication of packages and dimensions of terminal position areas. The group is to achieve its own original purpose as an industry standard. The group belongs to the dimensions and numerals of external shapes of packages useful for design and manufacture and the dimensions of terminal position areas that can be referenced to in fabrications of mounting boards. Therefore, external dimensions of a package shall have nominal design values specified thereto.

Ref.	Min.	Nom.	Max.	Degrees	Notes
b1	-	x	-		
b3	-	-	x		3
c1	-	x	-		
eE	-	x	-		3
L	-	x	-		
L1	-	x	-		
L2	-	x	-		
I1	-	-	x		3
(ZD)	-	x	-		

NOTES

- (*) Means true geometrical position.
- [] Values given within square brackets are calculated values.
- Ⓟ Means projected tolerance zone (see ISO 1101, Clause 11).



Means in this drawing that the distance from the seating plane to the nearest point of each terminal should not exceed y mm.

- 1 All dimensions are in millimetres.
- 2 n refers to the total number of terminal positions.
- 3 Verification of the dimensions and positions of package terminal is validly performed when it is ensured that these terminal fit with the pattern of terminal position areas. This can be carried out by means of an appropriate gauge.

IECNORM.COM: Click to view the full PDF of IEC 60191-6:2004
 Withdrawing

A.5 Folded lead package with one row of terminals on each of four sides (QFJ)




Figure 1a




Figure 1b





Figure 1c

IEC 694/04



Date:




Figure 1d




Figure 1e




Figure 1f





Figure 2 – Pattern of terminal position areas



Date:

Group 1 - Group 1 includes dimensions and numerals associated with the mounting of packages and kinds of packages. The dimensions and numerals belonging to the group mean values guaranteed to users and imply that mechanical compatibility of mounting of packages can be recognized.


Ref.	Min.	Nom.	Max.	Notes
n	-	x	-	2
nD	-	x	-	3
nE	-	x	-	3
A	-	-	x	
A1	x	-	x	
A2	-	x	-	
A3	-	x(*)	-	4
bp	x	-	x	4
c	x	-	x	
D	x	x	x	
E	x	x	x	
e	-	x(*)	-	4
HD	x	x	x	
HE	x	x	x	
Lp	x	-	x	4
t	-	-	x	
x	-	-	x	
y	-	-	x	

Group 2 – Group 2 includes dimensions that do not belong to Group 1, but are associated with the fabrication of packages and dimensions of terminal position areas. The group is to achieve its own original purpose as an industry standard. The group belongs to the dimensions and numerals of external shapes of packages useful for design and manufacture and the dimensions of terminal position areas that can be referenced to in fabrications of mounting boards. Therefore, external dimensions of a package shall have nominal design values specified thereto.

Ref.	Min.	Nom.	Max.	Notes
b1	-	x	-	
b2	x	-	x	
b3	-	-	x	4
c1	-	x	-	
eD	-	x	-	4
eE	-	x	-	4
L	-	x	-	
L1	-	x	-	
L2	-	x	-	
l1	-	-	x	4
h	-	x	-	
(ZD)	-	x	-	
(ZE)	-	x	-	


NOTES

- (*) Means true geometrical position.
- [] Values given within square brackets are calculated values.
- (P) Means projected tolerance zone (see ISO 1101, Clause 11).

 Means in this drawing that the distance from the seating plane to the nearest point of each terminal should not exceed y mm.


- 1 The millimetre (inch) dimensions are derived from the original inch (millimetre) dimensions.
- 2 n refers to the total number of terminal positions.
- 3 n_D refers to the number of terminal positions on one side of the package in the direction of dimension D.
 n_E refers to the number of terminal positions on one side of the package in the direction of dimension E.
- 4 Verification of the dimensions and positions of package terminal is validly performed when it is ensured that these terminal fit with the pattern of terminal position areas. This can be carried out by means of an appropriate gauge.

A.6 Leadless package




IEC 699/04

Figure 1a




IEC 700/04

Figure 1b




IEC 701/04

Figure 1c



IEC 702/04

Figure 2 – Pattern of terminal position areas



Date:

Group 1 - Group 1 includes dimensions and numerals associated with the mounting of packages and kinds of packages. The dimensions and numerals belonging to the group mean values guaranteed to users and imply that mechanical compatibility of mounting of packages can be recognized.

Ref.	Min.	Nom.	Max.	Notes
n	-	x	-	2
nD	-	x	-	3
nE	-	x	-	3
A	-	-	x	
bp	x	-	x	4
D	x	x	x	
E	x	x	x	
e	-	x(*)	-	4
Lp	x	-	x	4
w	-	-	x	
x	-	-	x	
y	-	-	x	


Group 2 - Group 2 includes dimensions that do not belong to Group 1, but are associated with the fabrication of packages and dimensions of terminal position areas. The group is to achieve its own original purpose as an industry standard. The group belongs to the dimensions and numerals of external shapes of packages useful for design and manufacture and the dimensions of terminal position areas that can be referenced to in fabrications of mounting boards. Therefore, external dimensions of a package shall have nominal design values specified thereto.

Ref.	Min.	Nom.	Max.	Notes
b3	-	-	x	4
eD	x-	x	-	4
eE	-	x	-	4
k	x	-	x	
k1	x	-	x	
l1	-	-	x	4
(Zb)	-	x	-	
(ZE)	-	x	-	

NOTES

(*) Means true geometrical position.

[] Values given within square brackets are calculated values.



Means in this drawing that the distance from the seating plane to the nearest point of each terminal should not exceed y mm.

1 All dimensions are in millimetres.

2 n refers to the total number of terminal positions.

3 n_D refers to the number of terminal positions on one side of the package in the direction of dimension D.

n_E refers to the number of terminal positions on one side of the package in the direction of dimension E.

4 Verification of the dimensions and positions of package terminal is validly performed when it is ensured that these terminal fit with the pattern of terminal position areas. This can be carried out by means of an appropriate gauge.

5 Length of terminal pad number 1 shall be visibly greater than the length of the other terminal pads.