

INTERNATIONAL STANDARD



**Household and similar electrical appliances – Safety –
Part 2-11: Particular requirements for tumble dryers**

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IECNORM.COM : Click to view the full PDF IEC 60352-1:2019 RLV



IEC 60335-2-11

Edition 8.0 2019-04
REDLINE VERSION

INTERNATIONAL STANDARD



**Household and similar electrical appliances – Safety –
Part 2-11: Particular requirements for tumble dryers**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 13.120; 97.060

ISBN 978-2-8322-6850-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	4
INTRODUCTION	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	9
4 General requirement	10
5 General conditions for the tests	10
6 Classification	10
7 Marking and instructions	10
8 Protection against access to live parts	12
9 Starting of motor-operated appliances	12
10 Power input and current	12
11 Heating	12
12 Void	14
13 Leakage current and electric strength at operating temperature	14
14 Transient overvoltages	14
15 Moisture resistance	14
16 Leakage current and electric strength	15
17 Overload protection of transformers and associated circuits	15
18 Endurance	15
19 Abnormal operation	15
20 Stability and mechanical hazards	16
21 Mechanical strength	18
22 Construction	18
23 Internal wiring	19
24 Components	20
25 Supply connection and external flexible cords	20
26 Terminals for external conductors	20
27 Provision for earthing	20
28 Screws and connections	20
29 Clearances, creepage distances and solid insulation	20
30 Resistance to heat and fire	20
31 Resistance to rusting	21
32 Radiation, toxicity and similar hazards	21
Annexes	22
Annex R (normative) Software evaluation	22
~~Annex AA (normative) Rinsing agent~~	~~24~~
Annex ~~BB~~ AA (normative) Tumble dryers that use a refrigerating system incorporating sealed motor-compressors for carrying out the drying process	24
Annex BB (normative) Equipment protection by type of protection "n"	32
~~Annex CC (normative) Non-sparking "n" electrical apparatus~~	~~32~~

Bibliography.....	35
Figure 101 – Probe for measuring surface temperatures	21
Table 101 – Maximum temperature rises for accessible external surfaces under normal operating conditions with the door closed	13
Table 201 – Maximum temperatures for motor-compressors	27
Table 202 – Refrigerant flammability parameters	30

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 2-11: Particular requirements for tumble dryers

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

International Standard IEC 60335-2-11 has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

This eighth edition cancels and replaces the seventh edition published in 2008, Amendment 1:2012 and Amendment 2:2015. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the seventh edition:

- aligns the text with IEC 60335-1, Ed 5, and its Amendments 1 and 2;
- some notes have been converted to normative text (7.12, 7.12.1, 11.3, 19.101, AA.5.2);
- more detailed test specifications have been given in 11.3 and 15.2;
- specific requirements have been added in 3.1.9, 3.6.101, 7.12, 11.7, 19.1, and Clause 22 to cover appliances with steam generators;
- specific requirements have been added in 22.108 to cover programmable electronic circuits;
- Annex AA has been deleted, because it is covered by Part 1 and the remaining annexes have been renumbered.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
61/5786/FDIS	61/5803/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60335 series, under the general title: *Household and similar electrical appliances – Safety*, can be found on the IEC website.

This part 2 is to be used in conjunction with the latest edition of IEC 60335-1 and its amendments. It was established on the basis of the fifth edition (2010) of that standard.

NOTE 1 When "Part 1" is mentioned in this standard, it refers to IEC 60335-1.

This part 2 supplements or modifies the corresponding clauses in IEC 60335-1, so as to convert that publication into the IEC standard: Safety requirements for tumble dryers.

When a particular subclause of Part 1 is not mentioned in this part 2, that subclause applies as far as is reasonable. When this standard states "addition", "modification" or "replacement", the relevant text in Part 1 is to be adapted accordingly.

NOTE 2 The following numbering system is used:

- subclauses, tables and figures that are numbered starting from 101 are additional to those in Part 1;
- unless notes are in a new subclause or involve notes in Part 1, they are numbered starting from 101, including those in a replaced clause or subclause;
- additional annexes are lettered AA, BB, etc.

NOTE 3 The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type*;
- notes: in small roman type.

Words in **bold** in the text are defined in Clause 3. When a definition concerns an adjective, the adjective and the associated noun are also in bold.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

NOTE 4 The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 12 months or later than 36 months from the date of publication.

The following differences exist in the countries indicated below.

- 3.1.9: The textile material has different dimensions (USA).
- 6.2: Tumble dryers are not required to be IPX4 (USA).
- 7.12: Actual articles of clothing can be specified instead and warnings are required to be marked on the appliance regarding the use of chemicals for cleaning (USA).
- 11.2: The test condition is different (USA).
- 11.7: This test is continued until steady conditions are established and different criteria are used to determine when steady conditions are reached (USA).
- 19.4: The test is different (USA).
- 19.9: A running overload test is carried out on automatically controlled tumble dryers (USA).
- 20.102: When considering accessibility to rotating drums, the maximum drum volume is 60 dm³ and the maximum door opening is 200 mm (USA).
- 20.103: This test is different (USA).
- 22.104: The test is different (USA).
- 27.1: Earthing terminals and contacts are allowed to be electrically connected to the neutral conductor of a tumble dryer (USA).

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

It has been assumed in the drafting of this International Standard that the execution of its provisions is entrusted to appropriately qualified and experienced persons.

This standard recognizes the internationally accepted level of protection against hazards such as electrical, mechanical, thermal, fire and radiation of appliances when operated as in normal use taking into account the manufacturer's instructions. It also covers abnormal situations that can be expected in practice and takes into account the way in which electromagnetic phenomena can affect the safe operation of appliances.

This standard takes into account the requirements of IEC 60364 as far as possible so that there is compatibility with the wiring rules when the appliance is connected to the supply mains. However, national wiring rules may differ.

If an appliance within the scope of this standard also incorporates functions that are covered by another part 2 of IEC 60335, the relevant part 2 is applied to each function separately, as far as is reasonable. If applicable, the influence of one function on the other is taken into account.

When a part 2 standard does not include additional requirements to cover hazards dealt with in Part 1, Part 1 applies.

NOTE 1 This means that the technical committees responsible for the part 2 standards have determined that it is not necessary to specify particular requirements for the appliance in question over and above the general requirements.

This standard is a product family standard dealing with the safety of appliances and takes precedence over horizontal and generic standards covering the same subject.

NOTE 2 Horizontal and generic standards covering a hazard are not applicable since they have been taken into consideration when developing the general and particular requirements for the IEC 60335 series of standards. For example, in the case of temperature requirements for surfaces on many appliances, generic standards, such as ISO 13732-1 for hot surfaces, are not applicable in addition to Part 1 or part 2 standards.

An appliance that complies with the text of this standard will not necessarily be considered to comply with the safety principles of the standard if, when examined and tested, it is found to have other features which impair the level of safety covered by these requirements.

An appliance employing materials or having forms of construction differing from those detailed in the requirements of this standard may be examined and tested according to the intent of the requirements and, if found to be substantially equivalent, may be considered to comply with the standard.

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 2-11: Particular requirements for tumble dryers

1 Scope

This clause of Part 1 is replaced by the following.

This International Standard deals with the safety of electric **tumble dryers** intended for household and similar purposes, their **rated voltage** being not more than 250 V for single-phase appliances and 480 V for other appliances.

NOTE 101 This standard applies to the drying function of washing machines having a drying cycle.

This standard also deals with the safety of **tumble dryers** that use a refrigerating system, incorporating sealed motor-compressors, for drying textile material. These appliances may use **flammable refrigerants**. Additional requirements for these appliances are given in Annex ~~BB~~ AA.

Appliances not intended for normal household use but which nevertheless may be a source of danger to the public, such as appliances intended to be used by laymen in shops, in light industry and on farms are within the scope of this standard.

NOTE 102 Examples of such appliances are **tumble dryers** for communal use in blocks of flats or in launderettes.

As far as is practicable, this standard deals with the common hazards presented by appliances that are encountered by all persons ~~in and around the home.~~

However, in general, it does not take into account

- persons (including children) whose
 - physical, sensory or mental capabilities; or
 - lack of experience and knowledgeprevents them from using the appliance safely without supervision or instruction;
- children playing with the appliance.

NOTE 103 Attention is drawn to the fact that

- for appliances intended to be used in vehicles or on board ships or aircraft, additional requirements may be necessary;
- in many countries, additional requirements are specified by the national health authorities, the national authorities responsible for the protection of labour, the national water supply authorities, ~~the national authorities responsible for transportation and the national authorities for buildings.~~

NOTE 104 This standard does not apply to

- appliances intended exclusively for industrial purposes;
- appliances intended to be used in locations where special conditions prevail, such as the presence of a corrosive or explosive atmosphere (dust, vapour or gas);
- ~~appliances incorporating steam generating devices in which steam is produced at a pressure exceeding 50 kPa.~~

2 Normative references

This clause of Part 1 is applicable except as follows.

Addition:

~~ISO 3864-1, Graphical symbols – Safety colours and safety signs – Part 1: Design principles for safety signs in workplaces and public areas~~

IEC 60584-1, Thermocouples – Part 1: EMF specifications and tolerances

3 Terms and definitions

This clause of Part 1 is applicable except as follows.

3.1 Definitions relating to physical characteristics

Replacement:

3.1.9

normal operation

operation of the appliance under the following conditions:

The appliance is operated filled with textile material having a mass in the dry condition equal to the maximum load stated in the instructions.

The textile material consists of pre-washed double-hemmed cotton sheets having dimensions approximately 70 cm × 70 cm and a specific mass between 140 g/m² and 175 g/m² in the dry condition. The textile material is soaked with water having a temperature of 25 °C ± 5 °C and a mass equal to that of the textile material.

If the drying function can automatically follow the washing function in a washing machine, the appliance is not separately loaded. The appliance is operated with the maximum quantity of textile material stated in the instructions for the combined washing-drying cycle.

Note 101 to entry: Cotton having a water content not exceeding 10 % is considered to be in the dry condition. Cotton conditioned for 24 h in still air, having a temperature of 20 °C ± 2 °C, a relative humidity between 60 % and 70 % and a pressure between 860 mbar and 1 060 mbar, will contain approximately 7 % water.

A **steam generator** intended to be filled by hand is filled according to the instructions, water being added to maintain the steam generation.

A **steam generator** intended to be filled automatically is connected to the water mains.

3.5 Definitions relating to types of appliances

3.5.101

tumble dryer

appliance in which textile material is dried by tumbling in a rotating drum through which heated air is blown

3.5.102

condensation-type tumble dryer

tumble dryer in which the air used for the drying process is dehumidified by cooling

3.6 Definitions relating to parts of an appliance

3.6.101

steam generator

device in which steam is produced at a pressure not exceeding 50 kPa and in which the pressure drops to atmospheric pressure when the steam is not supplied

3.8 Definitions relating to miscellaneous matters

3.8.101

cool down period

final part of the **tumble dryer** cycle where the drum is continuously rotated with reduced power to the heating element and with air circulation in order to reduce the possibility of spontaneous combustion of the clothes load

Note 1 to entry: Continuous rotation does not mean rotation in same direction if the intended operation is to reverse direction in normal use.

4 General requirement

This clause of Part 1 is applicable.

5 General conditions for the tests

This clause of Part 1 is applicable.

6 Classification

This clause of Part 1 is applicable except as follows.

6.2 Addition:

Appliances shall be at least IPX4.

7 Marking and instructions

This clause of Part 1 is applicable except as follows.

7.1 Addition:

The appliance shall be marked with symbol ISO 7000-0790 (2004-01) or with the substance of the following:

Read the instructions

~~7.6 Addition:~~



~~[symbol IEC 60417-5041 (2002-10)] — caution, hot surface~~

7.10 Addition:

If the **off position** is only indicated by letters, the word "off" shall be used.

7.12 Addition:

The instructions ~~for use~~ shall state

- the maximum mass of dry textile material in kilograms to be used in the appliance;
- that the tumble dryer is not to be used if industrial chemicals have been used for cleaning;
- that the lint trap has to be cleaned frequently, if applicable;

- that lint must not to be allowed to accumulate around the tumble dryer (not applicable for appliances intended to be vented to the exterior of the building);
- that adequate ventilation has to be provided to avoid the back flow of gases into the room from appliances burning other fuels, including open fires

~~NOTE 101~~ (this instruction is not required if the **tumble dryer** discharges the air into the room).

If ~~symbols IEC 60417-5041 (2002-10)~~ or symbol ISO 7000-0790 (2004-01) ~~are~~ is used, ~~their~~ its meaning shall be explained.

The instructions shall include the substance of the following.

- Do not dry unwashed items in the tumble dryer.
- Items that have been soiled with substances such as cooking oil, acetone, alcohol, petrol, kerosene, spot removers, turpentine, waxes and wax removers should be washed in hot water with an extra amount of detergent before being dried in the tumble dryer.
- Items such as foam rubber (latex foam), shower caps, waterproof textiles, rubber backed articles and clothes or pillows fitted with foam rubber pads should not be dried in the tumble dryer.
- Fabric softeners, or similar products, should be used as specified by the fabric softener instructions.
- ~~– The final part of a tumble dryer cycle occurs without heat (cool down cycle) to ensure that the items are left at a temperature that ensures that the items will not be damaged.~~
- Remove all objects from pockets such as lighters and matches.
- Fill steam generators only with liquids specified by the manufacturer.

The instructions shall include the substance of the following warning:

WARNING: Never stop a tumble dryer before the end of the drying cycle unless all items are quickly removed and spread out so that the heat is dissipated.

The instructions for appliances for which the air temperature exceeds 55 °C during the drying cycle, shall include the substance of the following warning:

WARNING: The appliance must not be supplied through an external switching device, such as a timer, or connected to a circuit that is regularly switched on and off by a utility.

7.12.1 Addition:

The ~~installation~~ instructions shall state that

- for appliances with ventilation openings in the base, a carpet must not obstruct the openings;
- exhaust air must not be discharged into a flue that is used for exhausting fumes from appliances burning gas or other fuels

~~NOTE 101~~ (this instruction is not required if the **tumble dryer** discharges the air into the room);

- the appliance must not be installed behind a lockable door, a sliding door or a door with a hinge on the opposite side to that of the tumble dryer, in such a way that a full opening of the tumble dryer door is restricted.

If the ~~installation~~ instructions state that the **tumble dryer** can be placed on top of a washing machine, they shall state which washing machines are suitable. Instructions shall be given for the assembly of the **tumble dryer** and washing machine. The instructions shall state how to obtain any fixing attachments required, unless they are supplied with the appliance.

7.14 Addition:

The height of ~~symbols IEC 60417-5041 (2002-10)~~ and symbol ISO 7000-0790 (2004-01) shall be at least 15 mm.

~~Compliance is checked by measurement.~~

7.15 Addition:

Symbol ISO 7000-0790 (2004-01), or the marking “Read the instructions”, shall be readily visible when the appliance is installed as in normal use.

~~7.101 The rear surface, other than that of fixed appliances, shall be marked with symbol IEC 60417-5041 (2002-10) if its temperature rise exceeds the limits specified in 11.8 for accessible front surfaces.~~

~~The layout of symbol IEC 60417-5041 (2002-10) shall be in accordance with the rules for a warning sign in ISO 3864-1.~~

~~Compliance is checked by inspection.~~

8 Protection against access to live parts

This clause of Part 1 is applicable.

9 Starting of motor-operated appliances

This clause of Part 1 is not applicable.

10 Power input and current

This clause of Part 1 is applicable.

11 Heating

This clause of Part 1 is applicable except as follows.

11.2 Addition:

Lint traps are cleaned and then 50 % of the area of the filter is blocked.

11.3 Addition:

~~Temperature rises of the accessible front surface are measured using the probe of Figure 101. Where the external accessible surfaces are suitably flat and access permits, then the test probe of Figure 101 is used to measure the temperature rises of external accessible surfaces specified in Table 101. The probe is applied with a force of $4\text{ N} \pm 1\text{ N}$ to the surface in such a way that the best possible contact between the probe and the surface is ensured. The measurement is performed after a contact period of 30 s.~~

~~NOTE 101 The probe may be held in place using a laboratory stand clamp or similar device. Any measuring instrument giving the same results as the probe may be used.~~

11.7 Replacement:

Appliances incorporating a timer, a humidity sensing control or other time-limiting control are operated in cycles. Each cycle comprises an operating period having a duration equal to the maximum time that can be provided by the control and a rest period of 4 min during which the appliance is reloaded.

The test may be ended if the temperature rise of any part does not exceed the value determined during the preceding cycle by more than 8 K.

Appliances having a combined washing-drying cycle are operated with the drying programme resulting in the highest temperature rise.

*Appliances with a **steam generator** are operated with that steam mode resulting in the highest temperature rise.*

Other appliances are operated continuously until steady conditions are established.

11.8 Addition:

~~*The temperature rises of the accessible front surface shall not exceed the following values:*~~

~~<i>— metal and painted metal parts</i>~~	~~<i>60 K</i>~~
~~<i>— vitreous-enamelled metal parts</i>~~	~~<i>65 K</i>~~
~~<i>— glass and ceramic parts</i>~~	~~<i>65 K</i>~~
~~<i>— plastic parts having a thickness exceeding 0,3 mm</i>~~	~~<i>80 K</i>~~

~~*The temperature rise limit of 80 K also applies to plastic material having a metal finish of thickness less than 0,1 mm. When the thickness of the plastic coating does not exceed 0,3 mm, the temperature rise limits of the supporting material apply.*~~

During the test, the temperature rises are monitored continuously and shall not exceed the values shown in Table 3 and Table 101.

Table 101 – Maximum temperature rises for accessible external surfaces under normal operating conditions with the door closed

Surface ^c	Temperature rise ^e K		
	Surfaces of appliances situated not more than 850 mm above the floor after installation		Surfaces situated more than 850 mm above the floor after installation ^d
	Front surfaces	Other surfaces ^d	
Bare metal	38	42	42
Coated metal ^a	42	49	49
Glass and ceramic	51	56	56
Plastic and plastic coating > 0,4 mm ^b	58	62	62
^a Metal is considered coated when a coating having a minimum thickness of 90 µm made by enamel or non-substantially plastic coating is used. ^b The temperature rise limit applies also for plastic material having a metal finish of thickness less than 0,1 mm. ^c When the thickness of plastic coating does not exceed 0,4 mm, the temperature rise limits of coated metal or glass and ceramic apply. ^d If these values are exceeded, the test is allowed to be repeated with the appliance moved away from the test corner side wall. The test is repeated for 1 cycle. ^e Temperature rises are not measured on – the underside of appliances intended to be used on a working surface or floor where these surfaces are inaccessible to a 75 mm diameter probe having a hemispherical end applied with a force not exceeding 1 N; – the rear surface of appliances where these surfaces are inaccessible to a 75 mm diameter probe having a hemispherical end applied with a force not exceeding 1 N.			

The temperature rises are measured with the door closed.

The exhaust temperature of the air from the drum, measured at the first lint filter after the air passes the clothes load, shall be measured for the purposes of 22.105.

12 Void

13 Leakage current and electric strength at operating temperature

This clause of Part 1 is applicable except as follows.

13.2 Modification:

For **stationary class I appliances**, the leakage current shall not exceed 3,5 mA, or 1 mA/kW rated power input with a limit of 5 mA, whichever is higher.

14 Transient overvoltages

This clause of Part 1 is applicable.

15 Moisture resistance

This clause of Part 1 is applicable except as follows.

15.2 Modification:

*The test is carried out with the drum filled with wet textile material as specified for **normal operation**, the mass of the water, however, being approximately 1,5 times the mass of the dry textile material.*

*Appliances intended to be connected to the water mains are operated with the outlet of the condensation circuit blocked. The inlet valve is held open and the filling continued for 1 min after first evidence of overflow or for 5 min after a **protective device** operates to stop the flow. Doors are opened but interlocks are not forced.*

For all appliances, 0,5 l of ~~water containing approximately 1 % NaCl and 0,6 % of rinsing agent, as specified in Annex AA~~, the solution is rapidly poured over the top of the appliance, so that the spillage solution flows over the surfaces of the appliance that incorporate controls, the controls being placed in the on position. The controls are then operated through their working range, this operation being repeated after a period of 5 min.

*The appliance shall then withstand the electric strength test of 16.3 and inspection shall show that there is no trace of water on insulation that could result in a reduction of **clearances** or **creepage distances** below the values specified in Clause 29.*

16 Leakage current and electric strength

This clause of Part 1 is applicable except as follows.

16.2 Modification:

*For **stationary class I combined appliances**, the leakage current shall not exceed 1 mA, or 1 mA/kW **rated power input** with a limit of 5 mA, whichever is higher.*

17 Overload protection of transformers and associated circuits

This clause of Part 1 is applicable.

18 Endurance

This clause of Part 1 is not applicable.

19 Abnormal operation

This clause of Part 1 is applicable except as follows.

19.1 Modification:

Instead of being subjected to the tests of 19.2 and 19.3, appliances are subjected to the tests of 19.101 and 19.102, as applicable.

Addition:

If operation without water is a more unfavourable condition for appliances connected to the water mains, the tests are carried out with the water valve closed. This valve is not closed after the appliance has started to operate.

*The **steam generator** is operated without water.*

19.4 Replacement:

*The appliance is operated under the conditions specified in Clause 11 but with dry textile material. Controls that limit the temperature during the test of Clause 11 and all **self-resetting thermal cut-outs** that protect the heating elements are short-circuited simultaneously. The test is terminated at the end of the maximum period allowed by a timer.*

For condensation-type tumble dryers, the test is repeated, but with 75 % of the air outlet of the condenser blocked. The test is then carried out again with the air outlet fully blocked.

19.9 ~~Not applicable~~

Addition:

*The running overload test is carried out on appliances that have overload **protective devices** incorporating **electronic circuits** to protect the windings of the drum motor. However, the test is not carried out if the **protective device** senses the winding temperature directly.*

19.13 Addition:

The textile material shall not ignite and shall show no charring or glowing.

NOTE 101 Light-brown colouring of the textile material or slight emission of smoke is ignored.

19.101 *The appliance is operated under the conditions specified in Clause 11 but with dry textile material and the drum belt removed. The duration of the test is 90 min or for the maximum period allowed by a timer.*

If air circulation is likely to be prevented due to a fault condition, the test is repeated but with the drum belt in position and with the air circulation stopped.

NOTE ~~Care should~~ *shall to be taken to ensure that the textile material is tumbling properly by reducing the load if necessary.*

If both ~~of~~ these conditions are likely to occur simultaneously, the tests are combined.

19.102 *Appliances that permit test probe C of IEC 61032 to gain access to spaces containing **live parts** located below holes in the drum are tested for short circuit conditions. The short circuit is applied at the most unfavourable place between **live parts** and between **live parts** and other metal parts, if such a short circuit can be made by a pin having a diameter of approximately 1 mm and any length up to 50 mm. The appliance is operated as specified in Clause 11 but with dry textile material.*

19.103 *There shall be no risk of fire due to textile material coming into contact with a lamp cover.*

Compliance is checked by the following test.

*Ten layers of cheesecloth are placed over the lamp cover. The appliance is supplied at **rated voltage** with the door open until steady conditions are established. The temperature rise of the cover shall not exceed 150 K.*

20 Stability and mechanical hazards

This clause of Part 1 is applicable except as follows.

20.1 Modification:

The test with the angle of inclination increased to 15 ° is not carried out.

20.101 It shall not be possible to open the door while the appliance is operating unless an interlock is provided that disconnects the motor before the door opening exceeds 75 mm. It shall not be possible to start the motor while the door opening exceeds 75 mm. ~~For appliances with a door opening having a dimension exceeding 200 mm and a drum having a volume exceeding 60 dm³, it shall not be possible to start the motor until a separate means which controls the movement of the drum is operated manually.~~

*Compliance is checked by inspection, by measurement and by manual test, the appliance being supplied at **rated voltage** and operating under **normal operation**.*

If means to prevent the door opening incorporates a coil or similar component to lock the door in the closed position, the component is energized and de-energized 6 000 times, six times a minute or at the rate imposed by the construction of the appliance if this is lower.

The locking means and its components shall be fit for further use.

NOTE The door is opened and closed during the test if this is necessary for the mechanical operation of the interlock.

20.102 For appliances with a door opening having a dimension exceeding 200 mm and a drum having a volume exceeding 60 dm³, it shall be possible to open the door from the inside with a force not exceeding 70 N.

~~This requirement does not apply to washing machines having a drying function.~~

Compliance is checked by inspection, by measurement and by applying a force of 70 N perpendicular to the plane of the door at a point furthest from the hinges.

If the appliance is supplied with a decorative door, the test is carried out with this door closed.

NOTE The force ~~may~~ can be applied to the outside of the door.

20.103 Appliances with horizontally hinged doors shall have adequate stability when the open door is subjected to a load. This requirement is not applicable to **built-in appliances** or **fixed appliances**.

*Compliance is checked by the following test that is carried out with the **tumble dryer** placed on a horizontal surface, even if it can be stacked on top of a washing machine.*

The empty appliance is placed on a horizontal surface and a mass of 23 kg applied to the centre of the open door. The appliance shall not tilt and the door and hinges shall not be damaged to such an extent that compliance with this standard is impaired.

20.104 For appliances having a door on a vertical surface with an opening exceeding 200 mm and a drum having a volume exceeding 60 dm³, it shall not be possible to start the drum motor after closing the door until a separate means which controls the movement of the drum is operated manually.

NOTE The volume can be calculated from the maximum depth and the maximum inner diameter of the drum.

Compliance is checked by the following test.

*The appliance is supplied at **rated voltage**, and the door is opened and then closed.*

*If compliance relies on the operation of an **electronic circuit**, the test is repeated under the following conditions applied separately:*

- the fault conditions in a) to g) of 19.11.2 are applied one at a time to the **electronic circuit**;*
- the electromagnetic phenomena tests of 19.11.4.2 and 19.11.4.5 are applied to the appliance.*

The drum motor shall not start.

*If the **electronic circuit** is programmable, the software shall contain measures to control the fault/error conditions specified in Table R.1 and is evaluated in accordance with the relevant requirements of Annex R.*

21 Mechanical strength

This clause of Part 1 is applicable.

22 Construction

This clause of Part 1 is applicable except as follows.

22.101 Heating elements shall be located or guarded so that they cannot be contacted by textile material.

Compliance is checked by inspection.

22.102 Interlocks shall be constructed so that unexpected operation of the appliance is unlikely to occur while the door is open.

Compliance is checked by inspection and by attempting to release the interlock by means of test probe B of IEC 61032.

22.103 If the instructions state that the **tumble dryer** can be placed on top of a washing machine, this shall be possible without the **tumble dryer** tilting or falling.

Compliance is checked by inspection and by the following tests.

*The washing machine and **tumble dryer** are assembled together in accordance with the instructions.*

*The combination is placed in the most unfavourable orientation on a surface that is inclined at 5 ° to the horizontal. Each appliance is supplied at **rated voltage** and operated under **normal operation** in turn and then together.*

The empty combination is placed on a horizontal surface and a horizontal force of 150 N is applied to the upper edge of the combination with the doors closed.

*The ~~appliances~~ combination shall not tilt and the **tumble dryer** shall not fall off the washing machine.*

22.104 The operation of ~~an overheat~~ **protective devices** for the heating circuit shall not disable the **cool down** ~~cycle period~~, if any.

Compliance is checked during the tests of Clause 19.

22.105 In order to reduce the risk of spontaneous combustion of the clothes load, the drying cycle shall conclude with a **cool down period** to reduce the temperature of the normal clothes load to a suitable value.

This requirement is not applicable to appliances having a drying cycle air temperature not exceeding 55 °C.

Compliance is checked by the following test.

The appliance is operated under the conditions in Clause 11 and the exhaust temperature of the air from the drum shall be measured at the first lint filter after the air passes the clothes load in the drum.

*At end of the **cool down period**, the air temperature shall not exceed 55 °C.*

22.106 Steam generators shall be vented to the atmosphere. The aperture shall be at least 5 mm in diameter or at least 20 mm² in area with a minimum dimension of 3 mm.

Compliance is checked by inspection and by measurement.

22.107 Appliances with a **steam generator** shall be constructed in such a way that there is no spillage of water or sudden jets of steam or hot water likely to expose the user to a hazard when the appliance is used in accordance with the instructions.

If jets of steam or liquids are emitted through **protective devices**, the electrical insulation shall not be affected or the user exposed to a hazard.

Compliance is checked by inspection during the tests of Clause 11 and Clause 19.

22.108 For appliances that are controlled by **programmable electronic circuits** that limit the number of heating elements and motors from being energized at the same time, simultaneous activation of any combination of heating elements and motors shall not render the appliance unsafe.

Compliance is checked by the following test.

- *the fault/error conditions specified in Table R.1 are applied and evaluated in accordance with the relevant requirements of Annex R; or*
- *the appliance is operated under the conditions of Clause 11 while being supplied at **rated voltage**, the **programmable electronic circuits** being modified to allow simultaneous activation of all heaters and motors under their control.*

Under these conditions, compliance with 19.13 shall be fulfilled.

23 Internal wiring

This clause of Part 1 is applicable except as follows.

23.101 The insulation and sheath of internal wiring for the supply of magnetic valves and similar components incorporated in external hoses shall be at least equivalent to light polyvinyl chloride sheathed flexible cord (code designation 60227 IEC 52).

Compliance is checked by inspection.

NOTE The mechanical characteristics specified in IEC 60227 are not checked.

24 Components

This clause of Part 1 is applicable except as follows.

24.1.4 Addition:

The number of cycles of operation for programmers is 3 000.

24.101 Thermal cut-outs incorporated in **tumble dryers** for compliance with 19.4 shall not be **self-resetting thermal cut-outs**.

Compliance is checked by inspection.

25 Supply connection and external flexible cords

This clause of Part 1 is applicable.

26 Terminals for external conductors

This clause of Part 1 is applicable.

27 Provision for earthing

This clause of Part 1 is applicable.

28 Screws and connections

This clause of Part 1 is applicable.

29 Clearances, creepage distances and solid insulation

This clause of Part 1 is applicable except as follows.

29.2 Addition:

The microenvironment is pollution degree 3, and the insulation shall have a CTI of not less than 250, unless the insulation is enclosed or located so that it is unlikely to be exposed to pollution due to condensation produced by the appliance during normal use.

The requirement for a minimum CTI value of 250 is not applicable to **functional insulation** if the **working voltage** does not exceed 50 V.

30 Resistance to heat and fire

This clause of Part 1 is applicable except as follows.

30.2.2 Not applicable.

30.101 Non-metallic materials in close proximity to heating elements and on which lint could accumulate shall be resistant to spread of fire. This requirement also applies to parts on which burning lint could fall.

Compliance is checked by subjecting non-metallic surfaces located within 75 mm of the heating element to the needle-flame test of Annex E. The test is also applied to surfaces located directly below the heating element. However, parts shielded by a barrier that meets the needle-flame test are not tested.

NOTE It is considered that burning lint ~~will not~~ cannot fall through a barrier with openings having a dimension less than 3 mm.

The needle-flame test is not carried out on


- *material classified as V-0 or V-1 according to IEC 60695-11-10, provided that the test sample was no thicker than the relevant part;*
- *rotating parts of fans;*
- *small parts as defined in IEC 60695-2-11.*

31 Resistance to rusting

This clause of Part 1 is applicable.

32 Radiation, toxicity and similar hazards

This clause of Part 1 is applicable.



Key

- A adhesive
- B thermocouple wires 0,3 mm diameter to IEC 60584-1 Type K (chrome alumel)
- C handle arrangement permitting a contact force of $4\text{ N} \pm 1\text{ N}$
- D polycarbonate tube: inside diameter 3 mm, outside diameter 5 mm
- E tinned copper disc: 5 mm diameter, 0,5 mm thick with flat contact face

NOTE ~~The contact face of the disc is flat.~~

Figure 101 – Probe for measuring surface temperatures

Annexes

The annexes of Part 1 are applicable except as follows.

Annex R (normative)

Software evaluation

R.2.2.5 *Modification:*

For **programmable electronic circuits** with functions requiring software incorporating measures to control the fault/error conditions specified in Table R.1, detection of a fault/error shall occur before compliance with Clause 19, 20.104 and 22.108 is impaired.

R.2.2.9 *Modification:*

The software and safety-related hardware under its control shall be initialized and shall terminate before compliance with Clause 19, 20.104 and 22.108 is impaired.

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

Annex AA **(normative)**

Rinsing agent

~~Any commercially available rinsing agent may be used, but if there is any doubt with regards to the test results, the composition of the rinsing agent shall be as follows:~~

Substance	Parts by mass %
Plurafac LF 221 ¹⁾	15,0
Cumene sulfonate (40 % solution)	11,5
Citric acid (anhydrous)	3,0
Deionized water	70,5

~~The rinsing agent has the following properties:~~

~~— viscosity, 17 mPa s;~~

~~— pH, 2,2 (1 % in water).~~

~~NOTE The composition of the rinsing agent is extracted from IEC 60436.~~

~~1) Plurafac LF 221 is the trade name of a product supplied by BASF. This information is given for the convenience of users of this document and does not constitute an endorsement by IEC of the product named.~~

Annex ~~BB~~ AA (normative)

Tumble dryers that use a refrigerating system incorporating sealed motor-compressors for carrying out the drying process

The following modifications to this standard are applicable for **tumble dryers** that use a refrigerating system incorporating sealed motor-compressors.

NOTE Additional subclauses, notes and tables in this annex are numbered starting with 201.

AA.2 Normative references

Addition:

IEC 60068-2-6, *Environmental testing – Part 2: Tests – Test Fc: Vibration (sinusoidal)*

~~IEC 60079-4A, Electrical apparatus for explosive gas atmospheres – Part 4: Method of test for ignition temperature – First supplement~~

~~IEC 60079-15:2005, Electrical apparatus for explosive gas atmospheres – Part 15: Construction, test and marking of type of protection “n” electrical apparatus~~

~~IEC/TR 60079-20:1996, Electrical apparatus for explosive gas atmospheres – Part 20: Data for flammable gases and vapours, relating to the use of electrical apparatus~~

IEC 60079-15:2010, *Explosive atmospheres – Part 15: Equipment protection by type of protection “n”*

IEC 60335-2-34:2012, *Household and similar electrical appliances – Safety – Part 2-34: Particular requirements for motor-compressors*

IEC 60335-2-34:2012/AMD1:2015

IEC 60335-2-34:2012/AMD2:2016²

ISO/IEC 80079-20-1, *Explosive atmospheres – Part 20-1: Material characteristics for gas and vapour classification – Test methods and data*

ISO 817, *Refrigerants – Designation ~~system~~ and safety classification*

~~ISO 5149, Mechanical refrigerating systems used for cooling and heating – Safety requirements~~

ISO 5149-1, *Refrigerating systems and heat pumps – Safety and environmental requirements – Part 1: Definitions, classification and selection criteria*

ISO 7010:2011, *Graphical symbols – Safety colours and safety signs – Registered safety signs*

² There exists a consolidated edition 5.2:2016 that includes edition 5:2012 and its Amendment 1:2015 and Amendment 2:2016.

AA.3 Terms and definitions

AA.3.8.201

flammable refrigerant

refrigerant with a flammability classification ~~of group 2 or 3~~ A2L, A2 or A3 in accordance with ~~ISO 5149~~ ISO 817

Note 1 to entry: For refrigerant blends that have more than one flammability classification, the most unfavourable classification is taken for the purposes of this definition.

AA.4 General requirement

Addition:

NOTE 201 The use of **flammable refrigerants** involves additional hazards that are not associated with appliances using non-flammable refrigerants.

This standard addresses the hazards due to ignition of **flammable refrigerant** by potential ignition sources associated with the appliance.

The hazard due to ignition of **flammable refrigerant** by an external potential ignition source associated with the environment in which the appliance is installed is compensated by the low probability of ignition.

AA.5 General conditions for the tests

AA.5.2 Addition:

At least one additional specially prepared sample is required for the tests of 22.202.

NOTE 201 Unless the motor-compressor conforms to IEC 60335-2-34, at least one additional specially prepared sample ~~may~~ can be required for the test of 19.1.

NOTE 202 At least one additional sample of the fan motor and its thermal motor protector ~~may~~ can be required for the test of 19.1.

NOTE 203 The test of 22.7 ~~may~~ can be performed on separate samples.

~~NOTE 204~~ Due to the potentially hazardous nature of the tests of AA.22.202 and AA.22.204, special precautions ~~may need to~~ shall be taken when performing the tests.

AA.5.7 Addition:

The tests specified in Clauses 10, 11 and 13 are carried out at an ambient temperature of 23 °C ± 2 °C.

AA.6 Classification

AA.6.1 Modification:

Tumble dryers using **flammable refrigerants** shall be class I.

AA.7 Marking and instructions

AA.7.1 Addition:

Appliances shall also be marked with:

- the total mass of the refrigerant;

- for a single component refrigerant, at least one of the following:
 - the chemical name;
 - the chemical formula;
 - the refrigerant number;
- for a blended refrigerant, at least one of the following:
 - the chemical name and nominal proportion of each of the components;
 - the chemical formula and nominal proportion of each of the components;
 - the refrigerant number and nominal proportion of each of the components;
 - the refrigerant number of the refrigerant blend.

If refrigerant numbers are used, they shall be as specified in ISO 817.

The appliance shall also be marked with the mass of the refrigerant for each separate refrigerant circuit.

Appliances that use **flammable refrigerants** shall be marked with ~~the symbol indicating “caution, risk of fire”~~ Warning sign ISO 7010-W021 (2011-06).

AA.7.6 Addition:



~~caution, risk of fire~~



[Warning sign ISO 7010-W021 (2011-06)]

Warning; Flammable material, risk of fire

AA.7.12 Addition:

If ~~the symbol indicating “caution, risk of fire”~~ Warning sign ISO 7010-W021 (2011-06) is used, its meaning shall be explained.

For appliances that use **flammable refrigerants**, the instructions shall include information pertaining to the installation, handling, servicing and disposal of the appliance.

The instructions shall also include the substance of the following:

WARNING: In the appliance enclosure or in the built-in structure, keep ventilation openings clear of obstruction.

WARNING: Do not damage the refrigerant circuit.

NOTE 201 This warning is only necessary if parts of the refrigerant circuit are accessible to the user.

AA.7.14 Addition:

The perpendicular height of the triangle of ~~the symbol indicating “caution, risk of fire”~~ Warning sign ISO 7010-W021 (2011-06) shall be at least 15 mm.

AA.7.15 Addition:

The marking of the type of **flammable refrigerant** and ~~the symbol indicating “caution, risk of fire”~~ Warning sign ISO 7010-W021 (2011-06) shall be visible when gaining access to the motor-compressors.

AA.11 Heating

AA.11.8 Addition:

During the test, **protective devices other than self-resetting thermal motor-protectors** for motor-compressors shall not operate. When steady conditions are established, **self-resetting thermal motor-protectors** for motor-compressors shall not operate.

The temperatures of windings and housing of motor-compressors shall not exceed the values specified in Table 201 and the temperature rise of all other components associated with the motor-compressor shall not exceed the values given in Table 3.

Table 201 – Maximum temperatures for motor-compressors

Part of the motor-compressor	Temperature °C
Windings with	
– synthetic insulation	140
– cellulose insulation or the like	130
Housing	150

The entry in Table 3 relating to the temperature rise of the external enclosure of **motor-operated appliances** is applicable to all appliances covered by this standard. However, it is not applicable to those parts of the external enclosure that

- for **built-in appliances**, are not **accessible** after installation in accordance with the instructions ~~for installation~~;
- for other appliances, are on that part of the appliance that according to the instructions ~~for installation~~, is intended to be placed against a wall with a free distance not exceeding 75 mm.

AA.19 Abnormal operation

AA.19.1 Addition:

Motor-compressors not complying with IEC 60335-2-34 are subjected to the tests specified in IEC 60335-2-34:2012, 19.101 and 19.102, and shall also comply with 19.104 of that standard.

NOTE 201 For any given type of motor-compressor, this test is performed only once.

AA.19.7 Addition:

This test does not apply to motor-compressors.

AA.21 Mechanical strength

AA.21.201 Appliances using **flammable refrigerants** shall withstand the effects of vibration.

The appliance is fastened in its normal position of use to a vibration generator, in accordance with IEC 60068-2-6, by means of straps around the enclosure. The type of vibration is sinusoidal, the direction is vertical and the severity is as follows:

- *duration* 30 min;
- *acceleration* 5 m/s²;
- *frequencies* 100 Hz or 120 Hz depending on the **rated frequency** of the appliance (50 Hz or 60 Hz).

After the test, the appliance shall show no damage affecting safety; in particular, no connections or parts the loosening of which may impair safety shall have loosened. No leakage shall occur when checked according to AA.22.7.

AA.22 Construction

AA.22.7 Addition:

Appliances, including the motor-compressor, shall withstand:

- a pressure of 3,5 times the saturated vapour pressure of the refrigerant at 70 °C for the relevant refrigerant for parts exposed to high-side pressure;
- a pressure of 5 times the saturated vapour pressure of the refrigerant at 25 °C for parts exposed only to low-side pressure.

However, appliances, including the motor-compressor, using **flammable refrigerants** shall withstand

- a pressure of 3,0 times the adjusted value of the **protection device** for parts exposed to high-side pressure;
- a pressure of 5 times the saturated vapour pressure of the refrigerant at 25 °C for parts exposed only to low-side pressure.

NOTE 201 All pressures are gauge pressures.

Compliance is checked by the following test.

The appropriate part of the appliance under test is subjected to a pressure that is gradually increased hydraulically until the required test pressure is reached. This pressure is maintained for 1 min. The part under test shall show no leakage.

AA.22.201 For **tumble dryers** that use **flammable refrigerants** in their refrigerant system, the mass of refrigerant shall not exceed 150 g in each separate refrigerant circuit.

Compliance is checked by inspection.

AA.22.202 For **tumble dryers** that use **flammable refrigerants**, any electrical component located inside the appliance, that during **normal operation** or abnormal operation produces sparks or arcs and luminaries, shall be tested and found at least to comply with the requirements in Annex ~~CC~~ BB for group IIA gases or the refrigerant used.

This requirement does not apply to

- **non-self-resetting protective devices** necessary for compliance with Clause 19, even if they produce arcs or sparks during operation; nor to
- **intentionally weak parts** that become permanently open-circuited during the tests of Clause 19, even if they produce arcs or sparks during operation.

Refrigerant leakage into the appliance enclosure shall not result in an explosive atmosphere outside the appliance in areas where electrical components that produce arcs and sparks during **normal operation** or abnormal operation are mounted, when doors or lids remain closed or when opening or closing doors or lids, unless these components have been tested and found at least to comply with the requirements in Annex-~~CC~~ **BB**, for group IIA gases or the refrigerant used.

This requirement does not apply to

- **non-self-resetting protective devices** necessary for compliance with Clause 19, even if they produce arcs or sparks during operation; nor to
- **intentionally weak parts** that become permanently open-circuited during the tests of Clause 19 even if they produce arcs or sparks during operation.

NOTE 1 Separate components, such as **thermostats**, that contain less than 0,5 g of **flammable gas**, are not considered liable to cause a fire or explosion hazard in the event of a leakage from the component itself.

NOTE 2 Other types of protection for electrical apparatus used in potentially explosive atmospheres covered by the IEC 60079 series are also acceptable.

Compliance is checked by inspection, by the appropriate tests of IEC 60079-15 and by the following test.

NOTE 3 The tests called up by Annex-~~CC~~ **BB**-~~may~~ can be carried out using the stoichiometric concentration of the refrigerant used. However, apparatus that has been independently tested and found to comply with Annex-~~CC~~ **BB** using the gas specified for group IIA need not be tested.

NOTE 4 Irrespective of the requirement given in 5.4.1 of IEC 60079-15, surface temperature limits are specified in AA.22.203.

The gas bottle is kept at a temperature of

- $32\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$ for leakage simulation on low-side pressure circuits;
- $70\text{ }^{\circ}\text{C} \pm 1\text{ }^{\circ}\text{C}$ for leakage simulation on high-side pressure circuits.

NOTE 5 The quantity of gas injected ~~should~~ can preferably be measured by weighing the bottle.

*The test is performed in a draught-free location with the appliance switched off or operated under conditions of **normal operation** at **rated voltage**, whichever gives the more unfavourable result.*

During a test in which the appliance is operated, gas injection is started at the same time as the appliance is first switched on.

The test is carried out twice and is repeated a third time if one of the first tests gives more than 40 % of the lower explosive limit.

Through an appropriate orifice, 80 % of the nominal refrigerant charge $\pm 1,5\text{ g}$, in the vapour state, is injected into the appliance enclosure in a time not exceeding 10 min. The orifice is then closed. The injection shall be as close as possible to the most critical points of the appliances.

NOTE 6 Examples are soldered joints.

The test has to be carried out while the door or lid is closed.

For appliances fitted with fan motors, the test is done with the most unfavourable combination of motor operation.

The concentration of leaked refrigerant is measured every 30 s from the beginning of the test, at positions as close as possible to electrical components. However, it is not measured at the positions of

- **non-self-resetting protective devices** necessary for compliance with Clause 19, even if they produce arcs or sparks during operation;
- **intentionally weak parts** that become permanently open-circuited during the tests of Clause 19, even if they produce arcs or sparks during operation.

The concentration values are recorded for a period of 15 min after a sustained decrease is observed.

The measured value shall not exceed 75 % of the lower explosive limit of the refrigerant as specified in Table 202, and shall not exceed 50 % of the lower explosive limit of the refrigerant as specified in Table 202 for a period exceeding 5 min.

The above test is repeated, and the door or lid is opened at a uniform rate in a time of between 1 s to 2 s to an angle of 90 ° or to the maximum possible, whichever is less. The concentration shall be the highest when the door or lid is opened.

AA.22.203 Temperatures on surfaces that may be exposed to leakage of **flammable refrigerants** shall not exceed the **auto-ignition** temperature of the refrigerant, as specified in Table 202, reduced by 100 K.

Compliance is checked by measuring the appropriate surface temperatures during the tests specified in Clauses 11 and 19.

Table 202 – Refrigerant flammability parameters

Refrigerant number	Refrigerant name	Refrigerant formula	Refrigerant auto-ignition temperature ^{a, c} °C	Refrigerant lower explosive limit ^{b, c, d, e} %V/V
R50	Methane	CH ₄	537 600	4,4
R290	Propane	CH ₃ CH ₂ CH ₃	470 450	1,7
R600	n-Butane	CH ₃ CH ₂ CH ₂ CH ₃	372	1,4
R600a	Isobutane	CH(CH ₃) ₃	494 460	1,8 1,3
^a Values for other flammable refrigerants can be obtained from IEC 60079-4A and IEC 60079-20 IEC 80079-20-1 or ISO 5149-1 . ^b Values for other flammable refrigerants can be obtained from IEC 60079-20 and ISO 5149 IEC 80079-20-1 and ISO 817 . ^c IEC 60079-20 ISO/IEC 80079-20-1 is the reference standard. ISO 5149-1 and ISO 817 may be used if the required data is not contained in IEC 60079-20 IEC 80079-20-1 . ^d Concentration of refrigerant in dry air. ^e In some standards, the term “flammability limit” is used for “explosive limit”.				

AA.22.204 For **tumble dryers** that use **flammable refrigerants**, a pressure responsive electrical cut-out is required for expansion valve refrigerant systems.

NOTE A capillary system is considered to be fail safe. In this case, an additional safety device is not required.

The pressure cut-out is allowed to be a **self-resetting type**. It shall not operate under the conditions of Clause 11. However during the test of 19.4, 75 % of the lint-trap is blocked and under this condition of abnormal use, the pressure cut-out is allowed to operate.

Compliance is checked by inspection during the tests of Clause 11 and 19.4.

AA.22.205 For **tumble dryers** that use **flammable refrigerants**, the insulation resistance between the drum and the enclosure and between the enclosure and the drive motor rotor shaft shall be sufficiently low so as to avoid a build-up of electrostatic charge.

Compliance is checked by measuring the insulation resistance between the drum and the enclosure and between the enclosure and the drive motor rotor shaft, with a DC voltage of approximately 500 V applied. The measurement is made 1 min after application of the voltage.

The insulation resistance shall not exceed 1 MΩ.

AA.22.206 For **tumble dryers** that use **flammable refrigerants**, only factory sealed connections shall be used in the refrigerant circuit.

NOTE Factory sealed connections are connections in the refrigerant circuit that have been sealed tight by welding, brazing or similar permanent connection during the manufacturing process.

Compliance is checked by inspection.

AA.24 Components

AA.24.1 Addition:

Motor-compressors are not required to be separately tested in accordance with IEC 60335-2-34, nor are they required to meet the requirements of IEC 60335-2-34, if they meet the requirements of this standard.

AA.24.1.4 Addition:

For appliances using a refrigerant system, the number of cycles is as follows:

– self-resetting thermal cut-outs that may influence the test results of 19.101 and that are not short-circuited during the test of 19.101	10 000
– thermostats that control the motor-compressor	30 000
– motor-compressor starting relays	30 000
– automatic thermal motor-protectors for motor-compressors of the hermetic type	2 000
– manual reset thermal motor-protectors for motor-compressors of the hermetic type	50
– other automatic thermal motor-protectors	2 000
– other manual reset thermal motor protectors	30
– self-resetting pressure cut-outs (only required on appliances using flammable refrigerants)	1 000
– manual reset pressure cut-outs (only required on appliances using flammable refrigerants)	300

Annex BB (normative)

Equipment protection by type of protection "n"

The following clauses of IEC 60079-15 are applicable as modified below.

11 Supplementary requirements for non-sparking luminaires

All of the subclauses of Clause 11 are applicable, except 11.2.4.1, 11.2.4.5, 11.2.5, 11.2.6, 11.2.7, 11.3.4, 11.3.5, 11.3.6 and 11.4.

16 General supplementary requirements for equipment producing arcs, sparks or hot surfaces

Clause 16 is applicable.

17 Supplementary requirements for enclosed-break devices and non-incendive components producing arcs, sparks or hot surfaces

Clause 17 is applicable.

18 Supplementary requirements for hermetically sealed devices producing arcs, sparks or hot surfaces

Clause 18 is applicable.

19 Supplementary requirements for sealed devices producing arcs, sparks or hot surfaces

All of the subclauses of Clause 19 are applicable, except 19.1 and 19.6, which are replaced by the following.

19.1 Non-metallic materials

Seals are tested using 22.5. However if the device is tested in the appliance, then 22.5.1 and 22.5.2 are not applicable. After the tests of Clause 19 in IEC 60335-2-11, by inspection, no damage that could impair the type of protection shall be evident.

19.6 Type tests

The type tests described in 22.5 shall be performed where relevant.

20 Supplementary requirements for restricted-breathing enclosures protecting equipment producing arcs, sparks or hot surfaces

Clause 20 is applicable.

~~Annex CC~~ (normative)

~~Non-sparking “n” electrical apparatus~~

~~Where reference is made to IEC 60079-15, the following clauses are applicable, as modified below.~~

~~26 General supplementary requirements for apparatus producing arcs, sparks or hot surfaces~~

~~This clause is applicable.~~

~~27 Supplementary requirements for enclosed break devices and non-incendive components producing arcs, sparks or hot surfaces~~

~~This clause is applicable.~~

~~28 Supplementary requirements for hermetically sealed devices producing arcs, sparks or hot surfaces~~

~~This clause is applicable.~~

~~29 Supplementary requirements for sealed devices or encapsulated devices producing arcs, sparks or hot surfaces~~

~~This clause is applicable, except as follows.~~

~~29.1 Non-metallic materials~~

~~Replacement:~~

~~Seals are tested using 33.5. However, if the device is tested in the appliance, then 33.5.1 and 33.5.2 are not applicable. However, after the tests of Clause 19 in IEC 60335-2-11, by inspection, no damage of the encapsulation that could impair the type of protection shall be evident, such as cracks in the resin or exposure of encapsulated parts.~~

~~29.8 Type tests~~

~~Replacement:~~

~~The type tests described in 33.5 shall be performed where relevant.~~

~~30 Supplementary requirements for energy-limited apparatus and circuits producing arcs, sparks or hot surfaces~~

~~This clause is applicable, except as follows.~~

~~Subclauses 30.5, 30.6 and 30.10 are not applicable.~~

~~31 Supplementary requirements for restricted-breathing enclosures protecting apparatus producing arcs, sparks or hot surfaces~~

~~This clause is applicable, except as follows.~~

~~**31.6 Maintenance considerations**~~

~~*Replacement:*~~

~~Restricted-breathing enclosures shall be type tested, including the cable entry devices.~~

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

Bibliography

The bibliography of Part 1 is applicable except as follows.

Addition:

IEC 60079 (all parts), *Explosive atmospheres*

~~IEC 60436, *Electric dishwashers for household use — Methods for measuring the performance*~~

~~IEC 60584-1, *Thermocouples — Part 1: Reference tables*~~

~~ISO 13732-1, *Ergonomics of the thermal environment — Methods for the assessment of human responses to contact with surfaces — Part 1: Hot surfaces*~~

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Household and similar electrical appliances – Safety –
Part 2-11: Particular requirements for tumble dryers**

**Appareils électrodomestiques et analogues – Sécurité –
Partie 2-11: Exigences particulières pour les sèche-linge à tambour**

CONTENTS

FOREWORD	4
INTRODUCTION	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	9
4 General requirement	10
5 General conditions for the tests	10
6 Classification	10
7 Marking and instructions	10
8 Protection against access to live parts	11
9 Starting of motor-operated appliances	12
10 Power input and current	12
11 Heating	12
12 Void	13
13 Leakage current and electric strength at operating temperature	13
14 Transient overvoltages	13
15 Moisture resistance	13
16 Leakage current and electric strength	14
17 Overload protection of transformers and associated circuits	14
18 Endurance	14
19 Abnormal operation	14
20 Stability and mechanical hazards	15
21 Mechanical strength	17
22 Construction	17
23 Internal wiring	18
24 Components	18
25 Supply connection and external flexible cords	19
26 Terminals for external conductors	19
27 Provision for earthing	19
28 Screws and connections	19
29 Clearances, creepage distances and solid insulation	19
30 Resistance to heat and fire	19
31 Resistance to rusting	20
32 Radiation, toxicity and similar hazards	20
Annexes	21
Annex R (normative) Software evaluation	22
Annex AA (normative) Tumble dryers that use a refrigerating system incorporating sealed motor-compressors for carrying out the drying process	23
Annex BB (normative) Equipment protection by type of protection "n"	31
Bibliography	32

Figure 101 – Probe for measuring surface temperatures	20
---	----

Table 101 – Maximum temperature rises for accessible external surfaces under normal operating conditions with the door closed	13
---	----

Table 201 – Maximum temperatures for motor-compressors	26
--	----

Table 202 – Refrigerant flammability parameters	29
---	----

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –**Part 2-11: Particular requirements for tumble dryers****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60335-2-11 has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

This eighth edition cancels and replaces the seventh edition published in 2008, Amendment 1:2012 and Amendment 2:2015. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the seventh edition:

- aligns the text with IEC 60335-1, Ed 5, and its Amendments 1 and 2;
- some notes have been converted to normative text (7.12, 7.12.1, 11.3, 19.101, AA.5.2);
- more detailed test specifications have been given in 11.3 and 15.2;
- specific requirements have been added in 3.1.9, 3.6.101, 7.12, 11.7, 19.1, and Clause 22 to cover appliances with steam generators;

- specific requirements have been added in 22.108 to cover programmable electronic circuits;
- Annex AA has been deleted, because it is covered by Part 1 and the remaining annexes have been renumbered.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
61/5786/FDIS	61/5803/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60335 series, under the general title: *Household and similar electrical appliances – Safety*, can be found on the IEC website.

This part 2 is to be used in conjunction with the latest edition of IEC 60335-1 and its amendments. It was established on the basis of the fifth edition (2010) of that standard.

NOTE 1 When "Part 1" is mentioned in this standard, it refers to IEC 60335-1.

This part 2 supplements or modifies the corresponding clauses in IEC 60335-1, so as to convert that publication into the IEC standard: Safety requirements for tumble dryers.

When a particular subclause of Part 1 is not mentioned in this part 2, that subclause applies as far as is reasonable. When this standard states "addition", "modification" or "replacement", the relevant text in Part 1 is to be adapted accordingly.

NOTE 2 The following numbering system is used:

- subclauses, tables and figures that are numbered starting from 101 are additional to those in Part 1;
- unless notes are in a new subclause or involve notes in Part 1, they are numbered starting from 101, including those in a replaced clause or subclause;
- additional annexes are lettered AA, BB, etc.

NOTE 3 The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type;*
- notes: in small roman type.

Words in **bold** in the text are defined in Clause 3. When a definition concerns an adjective, the adjective and the associated noun are also in bold.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

NOTE 4 The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this publication be adopted for implementation nationally not earlier than 12 months or later than 36 months from the date of publication.

The following differences exist in the countries indicated below.

- 3.1.9: The textile material has different dimensions (USA).
- 6.2: Tumble dryers are not required to be IPX4 (USA).
- 7.12: Actual articles of clothing can be specified instead and warnings are required to be marked on the appliance regarding the use of chemicals for cleaning (USA).
- 11.2: The test condition is different (USA).
- 11.7: This test is continued until steady conditions are established and different criteria are used to determine when steady conditions are reached (USA).
- 19.4: The test is different (USA).
- 19.9: A running overload test is carried out on automatically controlled tumble dryers (USA).
- 20.102: When considering accessibility to rotating drums, the maximum drum volume is 60 dm³ and the maximum door opening is 200 mm (USA).
- 20.103: This test is different (USA).
- 22.104: The test is different (USA).
- 27.1: Earthing terminals and contacts are allowed to be electrically connected to the neutral conductor of a tumble dryer (USA).

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

INTRODUCTION

It has been assumed in the drafting of this International Standard that the execution of its provisions is entrusted to appropriately qualified and experienced persons.

This standard recognizes the internationally accepted level of protection against hazards such as electrical, mechanical, thermal, fire and radiation of appliances when operated as in normal use taking into account the manufacturer's instructions. It also covers abnormal situations that can be expected in practice and takes into account the way in which electromagnetic phenomena can affect the safe operation of appliances.

This standard takes into account the requirements of IEC 60364 as far as possible so that there is compatibility with the wiring rules when the appliance is connected to the supply mains. However, national wiring rules may differ.

If an appliance within the scope of this standard also incorporates functions that are covered by another part 2 of IEC 60335, the relevant part 2 is applied to each function separately, as far as is reasonable. If applicable, the influence of one function on the other is taken into account.

When a part 2 standard does not include additional requirements to cover hazards dealt with in Part 1, Part 1 applies.

NOTE 1 This means that the technical committees responsible for the part 2 standards have determined that it is not necessary to specify particular requirements for the appliance in question over and above the general requirements.

This standard is a product family standard dealing with the safety of appliances and takes precedence over horizontal and generic standards covering the same subject.

NOTE 2 Horizontal and generic standards covering a hazard are not applicable since they have been taken into consideration when developing the general and particular requirements for the IEC 60335 series of standards. For example, in the case of temperature requirements for surfaces on many appliances, generic standards, such as ISO 13732-1 for hot surfaces, are not applicable in addition to Part 1 or part 2 standards.

An appliance that complies with the text of this standard will not necessarily be considered to comply with the safety principles of the standard if, when examined and tested, it is found to have other features which impair the level of safety covered by these requirements.

An appliance employing materials or having forms of construction differing from those detailed in the requirements of this standard may be examined and tested according to the intent of the requirements and, if found to be substantially equivalent, may be considered to comply with the standard.

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 2-11: Particular requirements for tumble dryers

1 Scope

This clause of Part 1 is replaced by the following.

This International Standard deals with the safety of electric **tumble dryers** intended for household and similar purposes, their **rated voltage** being not more than 250 V for single-phase appliances and 480 V for other appliances.

NOTE 101 This standard applies to the drying function of washing machines having a drying cycle.

This standard also deals with the safety of **tumble dryers** that use a refrigerating system, incorporating sealed motor-compressors, for drying textile material. These appliances may use **flammable refrigerants**. Additional requirements for these appliances are given in Annex AA.

Appliances not intended for normal household use but which nevertheless may be a source of danger to the public, such as appliances intended to be used by laymen in shops, in light industry and on farms are within the scope of this standard.

NOTE 102 Examples of such appliances are **tumble dryers** for communal use in blocks of flats or in launderettes.

As far as is practicable, this standard deals with the common hazards presented by appliances that are encountered by all persons.

However, in general, it does not take into account

- persons (including children) whose
 - physical, sensory or mental capabilities; or
 - lack of experience and knowledgeprevents them from using the appliance safely without supervision or instruction;
- children playing with the appliance.

NOTE 103 Attention is drawn to the fact that

- for appliances intended to be used in vehicles or on board ships or aircraft, additional requirements may be necessary;
- in many countries, additional requirements are specified by the national health authorities, the national authorities responsible for the protection of labour, the national water supply authorities,

NOTE 104 This standard does not apply to

- appliances intended exclusively for industrial purposes;
- appliances intended to be used in locations where special conditions prevail, such as the presence of a corrosive or explosive atmosphere (dust, vapour or gas);
- appliances incorporating steam generating devices in which steam is produced at a pressure exceeding 50 kPa.

2 Normative references

This clause of Part 1 is applicable except as follows.

Addition:

3 Terms and definitions

This clause of Part 1 is applicable except as follows.

3.1 Definitions relating to physical characteristics

Replacement:

3.1.9

normal operation

operation of the appliance under the following conditions:

The appliance is operated filled with textile material having a mass in the dry condition equal to the maximum load stated in the instructions.

The textile material consists of pre-washed double-hemmed cotton sheets having dimensions approximately 70 cm × 70 cm and a specific mass between 140 g/m² and 175 g/m² in the dry condition. The textile material is soaked with water having a temperature of 25 °C ± 5 °C and a mass equal to that of the textile material.

If the drying function can automatically follow the washing function in a washing machine, the appliance is not separately loaded. The appliance is operated with the maximum quantity of textile material stated in the instructions for the combined washing-drying cycle.

Note 101 to entry: Cotton having a water content not exceeding 10 % is considered to be in the dry condition. Cotton conditioned for 24 h in still air, having a temperature of 20 °C ± 2 °C, a relative humidity between 60 % and 70 % and a pressure between 860 mbar and 1 060 mbar, will contain approximately 7 % water.

A **steam generator** intended to be filled by hand is filled according to the instructions, water being added to maintain the steam generation.

A **steam generator** intended to be filled automatically is connected to the water mains.

3.5 Definitions relating to types of appliances

3.5.101

tumble dryer

appliance in which textile material is dried by tumbling in a rotating drum through which heated air is blown

3.5.102

condensation-type tumble dryer

tumble dryer in which the air used for the drying process is dehumidified by cooling

3.6 Definitions relating to parts of an appliance

3.6.101

steam generator

device in which steam is produced at a pressure not exceeding 50 kPa and in which the pressure drops to atmospheric pressure when the steam is not supplied

3.8 Definitions relating to miscellaneous matters

3.8.101

cool down period

final part of the **tumble dryer** cycle where the drum is continuously rotated with reduced power to the heating element and with air circulation in order to reduce the possibility of spontaneous combustion of the clothes load

Note 1 to entry: Continuous rotation does not mean rotation in same direction if the intended operation is to reverse direction in normal use.

4 General requirement

This clause of Part 1 is applicable.

5 General conditions for the tests

This clause of Part 1 is applicable.

6 Classification

This clause of Part 1 is applicable except as follows.

6.2 Addition:

Appliances shall be at least IPX4.

7 Marking and instructions

This clause of Part 1 is applicable except as follows.

7.1 Addition:

The appliance shall be marked with symbol ISO 7000-0790 (2004-01) or with the substance of the following:

Read the instructions

7.10 Addition:

If the **off position** is only indicated by letters, the word "off" shall be used.

7.12 Addition:

The instructions shall state

- the maximum mass of dry textile material in kilograms to be used in the appliance;
- that the tumble dryer is not to be used if industrial chemicals have been used for cleaning;
- that the lint trap has to be cleaned frequently, if applicable;
- that lint must not to be allowed to accumulate around the tumble dryer (not applicable for appliances intended to be vented to the exterior of the building);
- that adequate ventilation has to be provided to avoid the back flow of gases into the room from appliances burning other fuels, including open fires (this instruction is not required if the **tumble dryer** discharges the air into the room).

If symbol ISO 7000-0790 (2004-01) is used, its meaning shall be explained.

The instructions shall include the substance of the following.

- Do not dry unwashed items in the tumble dryer.

- Items that have been soiled with substances such as cooking oil, acetone, alcohol, petrol, kerosene, spot removers, turpentine, waxes and wax removers should be washed in hot water with an extra amount of detergent before being dried in the tumble dryer.
- Items such as foam rubber (latex foam), shower caps, waterproof textiles, rubber backed articles and clothes or pillows fitted with foam rubber pads should not be dried in the tumble dryer.
- Fabric softeners, or similar products, should be used as specified by the fabric softener instructions.
- Remove all objects from pockets such as lighters and matches.
- Fill steam generators only with liquids specified by the manufacturer.

The instructions shall include the substance of the following warning:

WARNING: Never stop a tumble dryer before the end of the drying cycle unless all items are quickly removed and spread out so that the heat is dissipated.

The instructions for appliances for which the air temperature exceeds 55 °C during the drying cycle, shall include the substance of the following warning:

WARNING: The appliance must not be supplied through an external switching device, such as a timer, or connected to a circuit that is regularly switched on and off by a utility.

7.12.1 Addition:

The instructions shall state that

- for appliances with ventilation openings in the base, a carpet must not obstruct the openings;
- exhaust air must not be discharged into a flue that is used for exhausting fumes from appliances burning gas or other fuels (this instruction is not required if the **tumble dryer** discharges the air into the room);
- the appliance must not be installed behind a lockable door, a sliding door or a door with a hinge on the opposite side to that of the tumble dryer, in such a way that a full opening of the tumble dryer door is restricted.

If the instructions state that the **tumble dryer** can be placed on top of a washing machine, they shall state which washing machines are suitable. Instructions shall be given for the assembly of the **tumble dryer** and washing machine. The instructions shall state how to obtain any fixing attachments required, unless they are supplied with the appliance.

7.14 Addition:

The height of symbol ISO 7000-0790 (2004-01) shall be at least 15 mm.

7.15 Addition:

Symbol ISO 7000-0790 (2004-01), or the marking “Read the instructions”, shall be readily visible when the appliance is installed as in normal use.

8 Protection against access to live parts

This clause of Part 1 is applicable.

9 Starting of motor-operated appliances

This clause of Part 1 is not applicable.

10 Power input and current

This clause of Part 1 is applicable.

11 Heating

This clause of Part 1 is applicable except as follows.

11.2 Addition:

Lint traps are cleaned and then 50 % of the area of the filter is blocked.

11.3 Addition:

*Where the external **accessible surfaces** are suitably flat and access permits, then the test probe of Figure 101 is used to measure the temperature rises of external **accessible surfaces** specified in Table 101. The probe is applied with a force of $4\text{ N} \pm 1\text{ N}$ to the surface in such a way that the best possible contact between the probe and the surface is ensured. The measurement is performed after a contact period of 30 s.*

The probe may be held in place using a laboratory stand clamp or similar device. Any measuring instrument giving the same results as the probe may be used.

11.7 Replacement:

Appliances incorporating a timer, a humidity sensing control or other time-limiting control are operated in cycles. Each cycle comprises an operating period having a duration equal to the maximum time that can be provided by the control and a rest period of 4 min during which the appliance is reloaded.

The test may be ended if the temperature rise of any part does not exceed the value determined during the preceding cycle by more than 8 K.

Appliances having a combined washing-drying cycle are operated with the drying programme resulting in the highest temperature rise.

*Appliances with a **steam generator** are operated with that steam mode resulting in the highest temperature rise.*

Other appliances are operated continuously until steady conditions are established.

11.8 Addition:

During the test, the temperature rises are monitored continuously and shall not exceed the values shown in Table 3 and Table 101.

Table 101 – Maximum temperature rises for accessible external surfaces under normal operating conditions with the door closed

Surface ^c	Temperature rise ^e K		
	Surfaces of appliances situated not more than 850 mm above the floor after installation		Surfaces situated more than 850 mm above the floor after installation ^d
	Front surfaces	Other surfaces ^d	
Bare metal	38	42	42
Coated metal ^a	42	49	49
Glass and ceramic	51	56	56
Plastic and plastic coating > 0,4 mm ^b	58	62	62
^a Metal is considered coated when a coating having a minimum thickness of 90 µm made by enamel or non-substantially plastic coating is used. ^b The temperature rise limit applies also for plastic material having a metal finish of thickness less than 0,1 mm. ^c When the thickness of plastic coating does not exceed 0,4 mm, the temperature rise limits of coated metal or glass and ceramic apply. ^d If these values are exceeded, the test is allowed to be repeated with the appliance moved away from the test corner side wall. The test is repeated for 1 cycle. ^e Temperature rises are not measured on – the underside of appliances intended to be used on a working surface or floor where these surfaces are inaccessible to a 75 mm diameter probe having a hemispherical end applied with a force not exceeding 1 N; – the rear surface of appliances where these surfaces are inaccessible to a 75 mm diameter probe having a hemispherical end applied with a force not exceeding 1 N.			

The temperature rises are measured with the door closed.

The exhaust temperature of the air from the drum, measured at the first lint filter after the air passes the clothes load, shall be measured for the purposes of 22.105.

12 Void

13 Leakage current and electric strength at operating temperature

This clause of Part 1 is applicable except as follows.

13.2 Modification:

For **stationary class I appliances**, the leakage current shall not exceed 3,5 mA, or 1 mA/kW rated power input with a limit of 5 mA, whichever is higher.

14 Transient overvoltages

This clause of Part 1 is applicable.

15 Moisture resistance

This clause of Part 1 is applicable except as follows.

15.2 Modification:

*The test is carried out with the drum filled with wet textile material as specified for **normal operation**, the mass of the water, however, being approximately 1,5 times the mass of the dry textile material.*

*Appliances intended to be connected to the water mains are operated with the outlet of the condensation circuit blocked. The inlet valve is held open and the filling continued for 1 min after first evidence of overflow or for 5 min after a **protective device** operates to stop the flow. Doors are opened but interlocks are not forced.*

For all appliances, 0,5 l of the solution is rapidly poured over the top of the appliance so that the spillage solution flows over the surfaces of the appliance that incorporate controls, the controls being placed in the on position. The controls are then operated through their working range, this operation being repeated after a period of 5 min.

*The appliance shall then withstand the electric strength test of 16.3 and inspection shall show that there is no trace of water on insulation that could result in a reduction of **clearances** or **creepage distances** below the values specified in Clause 29.*

16 Leakage current and electric strength

This clause of Part 1 is applicable except as follows.

16.2 Modification:

*For **stationary class I combined appliances**, the leakage current shall not exceed 1 mA, or 1 mA/kW **rated power input** with a limit of 5 mA, whichever is higher.*

17 Overload protection of transformers and associated circuits

This clause of Part 1 is applicable.

18 Endurance

This clause of Part 1 is not applicable.

19 Abnormal operation

This clause of Part 1 is applicable except as follows.

19.1 Modification:

Instead of being subjected to the tests of 19.2 and 19.3, appliances are subjected to the tests of 19.101 and 19.102, as applicable.

Addition:

If operation without water is a more unfavourable condition for appliances connected to the water mains, the tests are carried out with the water valve closed. This valve is not closed after the appliance has started to operate.

*The **steam generator** is operated without water.*

19.4 Replacement:

*The appliance is operated under the conditions specified in Clause 11 but with dry textile material. Controls that limit the temperature during the test of Clause 11 and all **self-resetting thermal cut-outs** that protect the heating elements are short-circuited simultaneously. The test is terminated at the end of the maximum period allowed by a timer.*

For condensation-type tumble dryers, the test is repeated, but with 75 % of the air outlet of the condenser blocked. The test is then carried out again with the air outlet fully blocked.

19.9 Addition:

*The running overload test is carried out on appliances that have overload **protective devices** incorporating **electronic circuits** to protect the windings of the drum motor. However, the test is not carried out if the **protective device** senses the winding temperature directly.*

19.13 Addition:

The textile material shall not ignite and shall show no charring or glowing.

NOTE 101 Light-brown colouring of the textile material or slight emission of smoke is ignored.

19.101 *The appliance is operated under the conditions specified in Clause 11 but with dry textile material and the drum belt removed. The duration of the test is 90 min or for the maximum period allowed by a timer.*

If air circulation is likely to be prevented due to a fault condition, the test is repeated but with the drum belt in position and with the air circulation stopped. Care shall to be taken to ensure that the textile material is tumbling properly by reducing the load if necessary.

If both these conditions are likely to occur simultaneously, the tests are combined.

19.102 *Appliances that permit test probe C of IEC 61032 to gain access to spaces containing **live parts** located below holes in the drum are tested for short circuit conditions. The short circuit is applied at the most unfavourable place between **live parts** and between **live parts** and other metal parts, if such a short circuit can be made by a pin having a diameter of approximately 1 mm and any length up to 50 mm. The appliance is operated as specified in Clause 11 but with dry textile material.*

19.103 *There shall be no risk of fire due to textile material coming into contact with a lamp cover.*

Compliance is checked by the following test.

*Ten layers of cheesecloth are placed over the lamp cover. The appliance is supplied at **rated voltage** with the door open until steady conditions are established. The temperature rise of the cover shall not exceed 150 K.*

20 Stability and mechanical hazards

This clause of Part 1 is applicable except as follows.

20.1 Modification:

The test with the angle of inclination increased to 15 ° is not carried out.

20.101 It shall not be possible to open the door while the appliance is operating unless an interlock is provided that disconnects the motor before the door opening exceeds 75 mm. It shall not be possible to start the motor while the door opening exceeds 75 mm.

*Compliance is checked by inspection, by measurement and by manual test, the appliance being supplied at **rated voltage** and operating under **normal operation**.*

If means to prevent the door opening incorporates a coil or similar component to lock the door in the closed position, the component is energized and de-energized 6 000 times, six times a minute or at the rate imposed by the construction of the appliance if this is lower.

The locking means and its components shall be fit for further use.

NOTE The door is opened and closed during the test if this is necessary for the mechanical operation of the interlock.

20.102 For appliances with a door opening having a dimension exceeding 200 mm and a drum having a volume exceeding 60 dm³, it shall be possible to open the door from the inside with a force not exceeding 70 N.

Compliance is checked by inspection, by measurement and by applying a force of 70 N perpendicular to the plane of the door at a point furthest from the hinges.

If the appliance is supplied with a decorative door, the test is carried out with this door closed.

NOTE The force can be applied to the outside of the door.

20.103 Appliances with horizontally hinged doors shall have adequate stability when the open door is subjected to a load. This requirement is not applicable to **built-in appliances** or **fixed appliances**.

*Compliance is checked by the following test that is carried out with the **tumble dryer** placed on a horizontal surface, even if it can be stacked on top of a washing machine.*

The empty appliance is placed on a horizontal surface and a mass of 23 kg applied to the centre of the open door. The appliance shall not tilt and the door and hinges shall not be damaged to such an extent that compliance with this standard is impaired.

20.104 For appliances having a door on a vertical surface with an opening exceeding 200 mm and a drum having a volume exceeding 60 dm³, it shall not be possible to start the drum motor after closing the door until a separate means which controls the movement of the drum is operated manually.

NOTE The volume can be calculated from the maximum depth and the maximum inner diameter of the drum.

Compliance is checked by the following test.

*The appliance is supplied at **rated voltage**, and the door is opened and then closed.*

*If compliance relies on the operation of an **electronic circuit**, the test is repeated under the following conditions applied separately:*

- *the fault conditions in a) to g) of 19.11.2 are applied one at a time to the **electronic circuit**;*
- *the electromagnetic phenomena tests of 19.11.4.2 and 19.11.4.5 are applied to the appliance.*

The drum motor shall not start.

*If the **electronic circuit** is programmable, the software shall contain measures to control the fault/error conditions specified in Table R.1 and is evaluated in accordance with the relevant requirements of Annex R.*

21 Mechanical strength

This clause of Part 1 is applicable.

22 Construction

This clause of Part 1 is applicable except as follows.

22.101 Heating elements shall be located or guarded so that they cannot be contacted by textile material.

Compliance is checked by inspection.

22.102 Interlocks shall be constructed so that unexpected operation of the appliance is unlikely to occur while the door is open.

Compliance is checked by inspection and by attempting to release the interlock by means of test probe B of IEC 61032.

22.103 If the instructions state that the **tumble dryer** can be placed on top of a washing machine, this shall be possible without the **tumble dryer** tilting or falling.

Compliance is checked by inspection and by the following tests.

*The washing machine and **tumble dryer** are assembled together in accordance with the instructions.*

*The combination is placed in the most unfavourable orientation on a surface that is inclined at 5 ° to the horizontal. Each appliance is supplied at **rated voltage** and operated under **normal operation** in turn and then together.*

The empty combination is placed on a horizontal surface and a horizontal force of 150 N is applied to the upper edge of the combination with the doors closed.

*The combination shall not tilt and the **tumble dryer** shall not fall off the washing machine.*

22.104 The operation of **protective devices** for the heating circuit shall not disable the **cool down period**, if any.

Compliance is checked during the tests of Clause 19.

22.105 In order to reduce the risk of spontaneous combustion of the clothes load, the drying cycle shall conclude with a **cool down period** to reduce the temperature of the normal clothes load to a suitable value.

This requirement is not applicable to appliances having a drying cycle air temperature not exceeding 55 °C.

Compliance is checked by the following test.

The appliance is operated under the conditions in Clause 11 and the exhaust temperature of the air from the drum shall be measured at the first lint filter after the air passes the clothes load in the drum.

*At end of the **cool down period**, the air temperature shall not exceed 55 °C.*

22.106 Steam generators shall be vented to the atmosphere. The aperture shall be at least 5 mm in diameter or at least 20 mm² in area with a minimum dimension of 3 mm.

Compliance is checked by inspection and by measurement.

22.107 Appliances with a **steam generator** shall be constructed in such a way that there is no spillage of water or sudden jets of steam or hot water likely to expose the user to a hazard when the appliance is used in accordance with the instructions.

If jets of steam or liquids are emitted through **protective devices**, the electrical insulation shall not be affected or the user exposed to a hazard.

Compliance is checked by inspection during the tests of Clause 11 and Clause 19.

22.108 For appliances that are controlled by **programmable electronic circuits** that limit the number of heating elements and motors from being energized at the same time, simultaneous activation of any combination of heating elements and motors shall not render the appliance unsafe.

Compliance is checked by the following test.

- *the fault/error conditions specified in Table R.1 are applied and evaluated in accordance with the relevant requirements of Annex R; or*
- *the appliance is operated under the conditions of Clause 11 while being supplied at **rated voltage**, the **programmable electronic circuits** being modified to allow simultaneous activation of all heaters and motors under their control.*

Under these conditions, compliance with 19.13 shall be fulfilled.

23 Internal wiring

This clause of Part 1 is applicable except as follows.

23.101 The insulation and sheath of internal wiring for the supply of magnetic valves and similar components incorporated in external hoses shall be at least equivalent to light polyvinyl chloride sheathed flexible cord (code designation 60227 IEC 52).

Compliance is checked by inspection.

NOTE The mechanical characteristics specified in IEC 60227 are not checked.

24 Components

This clause of Part 1 is applicable except as follows.

24.1.4 Addition:

The number of cycles of operation for programmers is 3 000.

24.101 Thermal cut-outs incorporated in **tumble dryers** for compliance with 19.4 shall not be **self-resetting thermal cut-outs**.

Compliance is checked by inspection.

25 Supply connection and external flexible cords

This clause of Part 1 is applicable.

26 Terminals for external conductors

This clause of Part 1 is applicable.

27 Provision for earthing

This clause of Part 1 is applicable.

28 Screws and connections

This clause of Part 1 is applicable.

29 Clearances, creepage distances and solid insulation

This clause of Part 1 is applicable except as follows.

29.2 Addition:

The microenvironment is pollution degree 3, and the insulation shall have a CTI of not less than 250, unless the insulation is enclosed or located so that it is unlikely to be exposed to pollution due to condensation produced by the appliance during normal use.

The requirement for a minimum CTI value of 250 is not applicable to **functional insulation** if the **working voltage** does not exceed 50 V.

30 Resistance to heat and fire

This clause of Part 1 is applicable except as follows.

30.2.2 Not applicable.

30.101 Non-metallic materials in close proximity to heating elements and on which lint could accumulate shall be resistant to spread of fire. This requirement also applies to parts on which burning lint could fall.

Compliance is checked by subjecting non-metallic surfaces located within 75 mm of the heating element to the needle-flame test of Annex E. The test is also applied to surfaces located directly below the heating element. However, parts shielded by a barrier that meets the needle-flame test are not tested.

NOTE It is considered that burning lint cannot fall through a barrier with openings having a dimension less than 3 mm.

The needle-flame test is not carried out on


- material classified as V-0 or V-1 according to IEC 60695-11-10, provided that the test sample was no thicker than the relevant part;
- rotating parts of fans;
- small parts as defined in IEC 60695-2-11.

31 Resistance to rusting

This clause of Part 1 is applicable.

32 Radiation, toxicity and similar hazards

This clause of Part 1 is applicable.



Key

- A adhesive
- B thermocouple wires 0,3 mm diameter to IEC 60584-1 Type K (chrome alumel)
- C handle arrangement permitting a contact force of $4\text{ N} \pm 1\text{ N}$
- D polycarbonate tube: inside diameter 3 mm, outside diameter 5 mm
- E tinned copper disc: 5 mm diameter, 0,5 mm thick with flat contact face

Figure 101 – Probe for measuring surface temperatures

Annexes

The annexes of Part 1 are applicable except as follows.

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

Annex R (normative)

Software evaluation

R.2.2.5 *Modification:*

For **programmable electronic circuits** with functions requiring software incorporating measures to control the fault/error conditions specified in Table R.1, detection of a fault/error shall occur before compliance with Clause 19, 20.104 and 22.108 is impaired.

R.2.2.9 *Modification:*

The software and safety-related hardware under its control shall be initialized and shall terminate before compliance with Clause 19, 20.104 and 22.108 is impaired.

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

Annex AA (normative)

Tumble dryers that use a refrigerating system incorporating sealed motor-compressors for carrying out the drying process

The following modifications to this standard are applicable for **tumble dryers** that use a refrigerating system incorporating sealed motor-compressors.

NOTE Additional subclauses, notes and tables in this annex are numbered starting with 201.

AA.2 Normative references

Addition:

IEC 60068-2-6, *Environmental testing – Part 2: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60079-15:2010, *Explosive atmospheres – Part 15: Equipment protection by type of protection "n"*

IEC 60335-2-34:2012, *Household and similar electrical appliances – Safety – Part 2-34: Particular requirements for motor-compressors*

IEC 60335-2-34:2012/AMD1:2015

IEC 60335-2-34:2012/AMD2:2016¹

ISO/IEC 80079-20-1, *Explosive atmospheres – Part 20-1: Material characteristics for gas and vapour classification – Test methods and data*

ISO 817, *Refrigerants – Designation and safety classification*

ISO 5149-1, *Refrigerating systems and heat pumps – Safety and environmental requirements – Part 1: Definitions, classification and selection criteria*

ISO 7010:2011, *Graphical symbols – Safety colours and safety signs – Registered safety signs*

AA.3 Terms and definitions

AA.3.8.201

flammable refrigerant

refrigerant with a flammability classification A2L, A2 or A3 in accordance with ISO 817

Note 1 to entry: For refrigerant blends that have more than one flammability classification, the most unfavourable classification is taken for the purposes of this definition.

AA.4 General requirement

NOTE 201 The use of **flammable refrigerants** involves additional hazards that are not associated with appliances using non-flammable refrigerants.

This standard addresses the hazards due to ignition of **flammable refrigerant** by potential ignition sources associated with the appliance.

¹ There exists a consolidated edition 5.2:2016 that includes edition 5:2012 and its Amendment 1:2015 and Amendment 2:2016.

The hazard due to ignition of **flammable refrigerant** by an external potential ignition source associated with the environment in which the appliance is installed is compensated by the low probability of ignition.

AA.5 General conditions for the tests

AA.5.2 Addition:

At least one additional specially prepared sample is required for the tests of 22.202.

NOTE 201 Unless the motor-compressor conforms to IEC 60335-2-34, at least one additional specially prepared sample can be required for the test of 19.1.

NOTE 202 At least one additional sample of the fan motor and its thermal motor protector can be required for the test of 19.1.

NOTE 203 The test of 22.7 can be performed on separate samples.

Due to the potentially hazardous nature of the tests of AA.22.202 and AA.22.204, special precautions shall be taken when performing the tests.

AA.5.7 Addition:

The tests specified in Clauses 10, 11 and 13 are carried out at an ambient temperature of $23\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$.

AA.6 Classification

AA.6.1 Modification:

Tumble dryers using **flammable refrigerants** shall be **class I**.

AA.7 Marking and instructions

AA.7.1 Addition:

Appliances shall also be marked with:

- the total mass of the refrigerant;
- for a single component refrigerant, at least one of the following:
 - the chemical name;
 - the chemical formula;
 - the refrigerant number;
- for a blended refrigerant, at least one of the following:
 - the chemical name and nominal proportion of each of the components;
 - the chemical formula and nominal proportion of each of the components;
 - the refrigerant number and nominal proportion of each of the components;
 - the refrigerant number of the refrigerant blend.

If refrigerant numbers are used, they shall be as specified in ISO 817.

The appliance shall also be marked with the mass of the refrigerant for each separate refrigerant circuit.

Appliances that use **flammable refrigerants** shall be marked with Warning sign ISO 7010-W021 (2011-06).

AA.7.6 Addition:



[Warning sign ISO 7010-W021 (2011-06)]

Warning; Flammable material, risk of fire

AA.7.12 Addition:

If Warning sign ISO 7010-W021 (2011-06) is used, its meaning shall be explained.

For appliances that use **flammable refrigerants**, the instructions shall include information pertaining to the installation, handling, servicing and disposal of the appliance.

The instructions shall also include the substance of the following:

WARNING: In the appliance enclosure or in the built-in structure, keep ventilation openings clear of obstruction.

WARNING: Do not damage the refrigerant circuit.

NOTE 201 This warning is only necessary if parts of the refrigerant circuit are accessible to the user.

AA.7.14 Addition:

The perpendicular height of the triangle of Warning sign ISO 7010-W021 (2011-06) shall be at least 15 mm.

AA.7.15 Addition:

The marking of the type of **flammable refrigerant** and Warning sign ISO 7010-W021 (2011-06) shall be visible when gaining access to the motor-compressors.

AA.11 Heating

AA.11.8 Addition:

*During the test, **protective devices** other than **self-resetting thermal motor-protectors** for motor-compressors shall not operate. When steady conditions are established, **self-resetting thermal motor-protectors** for motor-compressors shall not operate.*

The temperatures of windings and housing of motor-compressors shall not exceed the values specified in Table 201 and the temperature rise of all other components associated with the motor-compressor shall not exceed the values given in Table 3.

Table 201 – Maximum temperatures for motor-compressors

Part of the motor-compressor	Temperature °C
Windings with	
– synthetic insulation	140
– cellulose insulation or the like	130
Housing	150

The entry in Table 3 relating to the temperature rise of the external enclosure of **motor-operated appliances** is applicable to all appliances covered by this standard. However, it is not applicable to those parts of the external enclosure that

- for **built-in appliances**, are not **accessible** after installation in accordance with the instructions;
- for other appliances, are on that part of the appliance that according to the instructions, is intended to be placed against a wall with a free distance not exceeding 75 mm.

AA.19 Abnormal operation

AA.19.1 Addition:

Motor-compressors not complying with IEC 60335-2-34 are subjected to the tests specified in IEC 60335-2-34:2012, 19.101 and 19.102, and shall also comply with 19.104 of that standard.

NOTE 201 For any given type of motor-compressor, this test is performed only once.

AA.19.7 Addition:

This test does not apply to motor-compressors.

AA.21 Mechanical strength

AA.21.201 Appliances using **flammable refrigerants** shall withstand the effects of vibration.

The appliance is fastened in its normal position of use to a vibration generator, in accordance with IEC 60068-2-6, by means of straps around the enclosure. The type of vibration is sinusoidal, the direction is vertical and the severity is as follows:

- duration 30 min;
- acceleration 5 m/s²;
- frequencies 100 Hz or 120 Hz depending on the **rated frequency** of the appliance (50 Hz or 60 Hz).

After the test, the appliance shall show no damage affecting safety; in particular, no connections or parts the loosening of which may impair safety shall have loosened. No leakage shall occur when checked according to AA.22.7.

AA.22 Construction

AA.22.7 Addition:

Appliances, including the motor-compressor, shall withstand:

- a pressure of 3,5 times the saturated vapour pressure of the refrigerant at 70 °C for the relevant refrigerant for parts exposed to high-side pressure;
- a pressure of 5 times the saturated vapour pressure of the refrigerant at 25 °C for parts exposed only to low-side pressure.

However, appliances, including the motor-compressor, using **flammable refrigerants** shall withstand

- a pressure of 3,0 times the adjusted value of the **protection device** for parts exposed to high-side pressure;
- a pressure of 5 times the saturated vapour pressure of the refrigerant at 25 °C for parts exposed only to low-side pressure.

NOTE 201 All pressures are gauge pressures.

Compliance is checked by the following test.

The appropriate part of the appliance under test is subjected to a pressure that is gradually increased hydraulically until the required test pressure is reached. This pressure is maintained for 1 min. The part under test shall show no leakage.

AA.22.201 For **tumble dryers** that use **flammable refrigerants** in their refrigerant system, the mass of refrigerant shall not exceed 150 g in each separate refrigerant circuit.

Compliance is checked by inspection.

AA.22.202 For **tumble dryers** that use **flammable refrigerants**, any electrical component located inside the appliance, that during **normal operation** or abnormal operation produces sparks or arcs and luminaries, shall be tested and found at least to comply with the requirements in Annex BB for group IIA gases or the refrigerant used.

This requirement does not apply to

- **non-self-resetting protective devices** necessary for compliance with Clause 19, even if they produce arcs or sparks during operation; nor to
- **intentionally weak parts** that become permanently open-circuited during the tests of Clause 19, even if they produce arcs or sparks during operation.

Refrigerant leakage into the appliance enclosure shall not result in an explosive atmosphere outside the appliance in areas where electrical components that produce arcs and sparks during **normal operation** or abnormal operation are mounted, when doors or lids remain closed or when opening or closing doors or lids, unless these components have been tested and found at least to comply with the requirements in Annex BB, for group IIA gases or the refrigerant used.

This requirement does not apply to

- **non-self-resetting protective devices** necessary for compliance with Clause 19, even if they produce arcs or sparks during operation; nor to
- **intentionally weak parts** that become permanently open-circuited during the tests of Clause 19 even if they produce arcs or sparks during operation.

NOTE 1 Separate components, such as **thermostats**, that contain less than 0,5 g of **flammable gas**, are not considered liable to cause a fire or explosion hazard in the event of a leakage from the component itself.

NOTE 2 Other types of protection for electrical apparatus used in potentially explosive atmospheres covered by the IEC 60079 series are also acceptable.

Compliance is checked by inspection, by the appropriate tests of IEC 60079-15 and by the following test.

NOTE 3 The tests called up by Annex BB can be carried out using the stoichiometric concentration of the refrigerant used. However, apparatus that has been independently tested and found to comply with Annex BB using the gas specified for group IIA need not be tested.

NOTE 4 Irrespective of the requirement given in 5.1 of IEC 60079-15, surface temperature limits are specified in AA.22.203.

The gas bottle is kept at a temperature of

- 32 °C ± 1 °C for leakage simulation on low-side pressure circuits;
- 70 °C ± 1 °C for leakage simulation on high-side pressure circuits.

NOTE 5 The quantity of gas injected can preferably be measured by weighing the bottle.

*The test is performed in a draught-free location with the appliance switched off or operated under conditions of **normal operation at rated voltage**, whichever gives the more unfavourable result.*

During a test in which the appliance is operated, gas injection is started at the same time as the appliance is first switched on.

The test is carried out twice and is repeated a third time if one of the first tests gives more than 40 % of the lower explosive limit.

Through an appropriate orifice, 80 % of the nominal refrigerant charge ± 1,5 g, in the vapour state, is injected into the appliance enclosure in a time not exceeding 10 min. The orifice is then closed. The injection shall be as close as possible to the most critical points of the appliances.

NOTE 6 Examples are soldered joints.

The test has to be carried out while the door or lid is closed.

For appliances fitted with fan motors, the test is done with the most unfavourable combination of motor operation.

The concentration of leaked refrigerant is measured every 30 s from the beginning of the test, at positions as close as possible to electrical components. However, it is not measured at the positions of

- **non-self-resetting protective devices** necessary for compliance with Clause 19, even if they produce arcs or sparks during operation;
- **intentionally weak parts** that become permanently open-circuited during the tests of Clause 19, even if they produce arcs or sparks during operation.

The concentration values are recorded for a period of 15 min after a sustained decrease is observed.

The measured value shall not exceed 75 % of the lower explosive limit of the refrigerant as specified in Table 202, and shall not exceed 50 % of the lower explosive limit of the refrigerant as specified in Table 202 for a period exceeding 5 min.

The above test is repeated, and the door or lid is opened at a uniform rate in a time of between 1 s to 2 s to an angle of 90 ° or to the maximum possible, whichever is less. The concentration shall be the highest when the door or lid is opened.

AA.22.203 Temperatures on surfaces that may be exposed to leakage of **flammable refrigerants** shall not exceed the auto-ignition temperature of the refrigerant, as specified in Table 202, reduced by 100 K.

Compliance is checked by measuring the appropriate surface temperatures during the tests specified in Clauses 11 and 19.

Table 202 – Refrigerant flammability parameters

Refrigerant number	Refrigerant name	Refrigerant formula	Refrigerant auto-ignition temperature ^{a, c} °C	Refrigerant lower explosive limit ^{b, c, d, e} %V/V
R50	Methane	CH ₄	600	4,4
R290	Propane	CH ₃ CH ₂ CH ₃	450	1,7
R600	n-Butane	CH ₃ CH ₂ CH ₂ CH ₃	372	1,4
R600a	Isobutane	CH(CH ₃) ₃	460	1,3
^a Values for other flammable refrigerants can be obtained from IEC 80079-20-1 or ISO 5149-1. ^b Values for other flammable refrigerants can be obtained from IEC 80079-20-1 and ISO 817. ^c ISO/IEC 80079-20-1 is the reference standard. ISO 5149-1 and ISO 817 may be used if the required data is not contained in IEC 80079-20-1. ^d Concentration of refrigerant in dry air. ^e In some standards, the term “flammability limit” is used for “explosive limit”.				

AA.22.204 For **tumble dryers** that use **flammable refrigerants**, a pressure responsive electrical cut-out is required for expansion valve refrigerant systems.

NOTE A capillary system is considered to be fail safe. In this case, an additional safety device is not required.

The pressure cut-out is allowed to be a **self-resetting type**. It shall not operate under the conditions of Clause 11. However during the test of 19.4, 75 % of the lint-trap is blocked and under this condition of abnormal use, the pressure cut-out is allowed to operate.

Compliance is checked by inspection during the tests of Clause 11 and 19.4.

AA.22.205 For **tumble dryers** that use **flammable refrigerants**, the insulation resistance between the drum and the enclosure and between the enclosure and the drive motor rotor shaft shall be sufficiently low so as to avoid a build-up of electrostatic charge.

Compliance is checked by measuring the insulation resistance between the drum and the enclosure and between the enclosure and the drive motor rotor shaft, with a DC voltage of approximately 500 V applied. The measurement is made 1 min after application of the voltage.

The insulation resistance shall not exceed 1 MΩ.

AA.22.206 For **tumble dryers** that use **flammable refrigerants**, only factory sealed connections shall be used in the refrigerant circuit.

NOTE Factory sealed connections are connections in the refrigerant circuit that have been sealed tight by welding, brazing or similar permanent connection during the manufacturing process.

Compliance is checked by inspection.

AA.24 Components

AA.24.1 Addition:

Motor-compressors are not required to be separately tested in accordance with IEC 60335-2-34, nor are they required to meet the requirements of IEC 60335-2-34, if they meet the requirements of this standard.

AA.24.1.4 Addition:

For appliances using a refrigerant system, the number of cycles is as follows:

– self-resetting thermal cut-outs that may influence the test results of 19.101 and that are not short-circuited during the test of 19.101	10 000
– thermostats that control the motor-compressor	30 000
– motor-compressor starting relays	30 000
– automatic thermal motor-protectors for motor-compressors of the hermetic type	2 000
– manual reset thermal motor-protectors for motor-compressors of the hermetic type	50
– other automatic thermal motor-protectors	2 000
– other manual reset thermal motor protectors	30
– self-resetting pressure cut-outs (only required on appliances using flammable refrigerants)	1 000
– manual reset pressure cut-outs (only required on appliances using flammable refrigerants)	300

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

Annex BB (normative)

Equipment protection by type of protection "n"

The following clauses of IEC 60079-15 are applicable as modified below.

11 Supplementary requirements for non-sparking luminaires

All of the subclauses of Clause 11 are applicable, except 11.2.4.1, 11.2.4.5, 11.2.5, 11.2.6, 11.2.7, 11.3.4, 11.3.5, 11.3.6 and 11.4.

16 General supplementary requirements for equipment producing arcs, sparks or hot surfaces

Clause 16 is applicable.

17 Supplementary requirements for enclosed-break devices and non-incendive components producing arcs, sparks or hot surfaces

Clause 17 is applicable.

18 Supplementary requirements for hermetically sealed devices producing arcs, sparks or hot surfaces

Clause 18 is applicable.

19 Supplementary requirements for sealed devices producing arcs, sparks or hot surfaces

All of the subclauses of Clause 19 are applicable, except 19.1 and 19.6, which are replaced by the following.

19.1 Non-metallic materials

Seals are tested using 22.5. However if the device is tested in the appliance, then 22.5.1 and 22.5.2 are not applicable. After the tests of Clause 19 in IEC 60335-2-11, by inspection, no damage that could impair the type of protection shall be evident.

19.6 Type tests

The type tests described in 22.5 shall be performed where relevant.

20 Supplementary requirements for restricted-breathing enclosures protecting equipment producing arcs, sparks or hot surfaces

Clause 20 is applicable.

Bibliography

The bibliography of Part 1 is applicable except as follows.

Addition:

IEC 60079 (all parts), *Explosive atmospheres*

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

SOMMAIRE

AVANT-PROPOS	36
INTRODUCTION	39
1 Domaine d'application	40
2 Références normatives	41
3 Termes et définitions	41
4 Exigences générales	42
5 Conditions générales d'essais	42
6 Classification	42
7 Marquage et instructions	42
8 Protection contre l'accès aux parties actives	44
9 Démarrage des appareils à moteur	44
10 Puissance et courant	44
11 Échauffements	44
12 Vide	46
13 Courant de fuite et rigidité diélectrique à la température de régime	46
14 Surtensions transitoires	46
15 Résistance à l'humidité	46
16 Courant de fuite et rigidité diélectrique	46
17 Protection contre la surcharge des transformateurs et des circuits associés	47
18 Endurance	47
19 Fonctionnement anormal	47
20 Stabilité et dangers mécaniques	48
21 Résistance mécanique	49
22 Construction	49
23 Conducteurs internes	51
24 Composants	51
25 Raccordement au réseau et câbles souples extérieurs	51
26 Bornes pour conducteurs externes	52
27 Dispositions en vue de la mise à la terre	52
28 Vis et connexions	52
29 Distances dans l'air, lignes de fuite et isolation solide	52
30 Résistance à la chaleur et au feu	52
31 Protection contre la rouille	53
32 Rayonnement, toxicité et dangers analogues	53
Annexes	54
Annexe R (normative) Évaluation des logiciels	55
Annexe AA (normative) Sèche-linge à tambour utilisant comme procédé de séchage un système de réfrigération à motocompresseurs hermétiques	56
Annexe BB (normative) Protection des appareils par mode de protection «n»	65
Bibliographie	66

Figure 101 – Calibre pour le mesurage des températures de surface 53

Tableau 101 – Échauffements maximaux pour les surfaces accessibles externes dans des conditions de fonctionnement normal avec la porte fermée..... 45

Tableau 201 – Températures maximales pour les motocompresseurs 59

Tableau 202 – Paramètres d'inflammabilité des fluides frigorigènes..... 62

IECNORM.COM : Click to view the full PDF of IEC 60335-2-11:2019 RLV

COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

APPAREILS ÉLECTRODOMESTIQUES ET ANALOGUES – SÉCURITÉ –**Partie 2-11: Exigences particulières pour les sèche-linge à tambour****AVANT-PROPOS**

- 1) La Commission Électrotechnique Internationale (IEC) est une organisation mondiale de normalisation composée de l'ensemble des comités électrotechniques nationaux (Comités nationaux de l'IEC). L'IEC a pour objet de favoriser la coopération internationale pour toutes les questions de normalisation dans les domaines de l'électricité et de l'électronique. À cet effet, l'IEC – entre autres activités – publie des Normes internationales, des Spécifications techniques, des Rapports techniques, des Spécifications accessibles au public (PAS) et des Guides (ci-après dénommés "Publication(s) de l'IEC"). Leur élaboration est confiée à des comités d'études, aux travaux desquels tout Comité national intéressé par le sujet traité peut participer. Les organisations internationales, gouvernementales et non gouvernementales, en liaison avec l'IEC, participent également aux travaux. L'IEC collabore étroitement avec l'Organisation Internationale de Normalisation (ISO), selon des conditions fixées par accord entre les deux organisations.
- 2) Les décisions ou accords officiels de l'IEC concernant les questions techniques représentent, dans la mesure du possible, un accord international sur les sujets étudiés, étant donné que les Comités nationaux de l'IEC intéressés sont représentés dans chaque comité d'études.
- 3) Les Publications de l'IEC se présentent sous la forme de recommandations internationales et sont agréées comme telles par les Comités nationaux de l'IEC. Tous les efforts raisonnables sont entrepris afin que l'IEC s'assure de l'exactitude du contenu technique de ses publications; l'IEC ne peut pas être tenue responsable de l'éventuelle mauvaise utilisation ou interprétation qui en est faite par un quelconque utilisateur final.
- 4) Dans le but d'encourager l'uniformité internationale, les Comités nationaux de l'IEC s'engagent, dans toute la mesure possible, à appliquer de façon transparente les Publications de l'IEC dans leurs publications nationales et régionales. Toutes divergences entre toutes Publications de l'IEC et toutes publications nationales ou régionales correspondantes doivent être indiquées en termes clairs dans ces dernières.
- 5) L'IEC elle-même ne fournit aucune attestation de conformité. Des organismes de certification indépendants fournissent des services d'évaluation de conformité et, dans certains secteurs, accèdent aux marques de conformité de l'IEC. L'IEC n'est responsable d'aucun des services effectués par les organismes de certification indépendants.
- 6) Tous les utilisateurs doivent s'assurer qu'ils sont en possession de la dernière édition de cette publication.
- 7) Aucune responsabilité ne doit être imputée à l'IEC, à ses administrateurs, employés, auxiliaires ou mandataires, y compris ses experts particuliers et les membres de ses comités d'études et des Comités nationaux de l'IEC, pour tout préjudice causé en cas de dommages corporels et matériels, ou de tout autre dommage de quelque nature que ce soit, directe ou indirecte, ou pour supporter les coûts (y compris les frais de justice) et les dépenses découlant de la publication ou de l'utilisation de cette Publication de l'IEC ou de toute autre Publication de l'IEC, ou au crédit qui lui est accordé.
- 8) L'attention est attirée sur les références normatives citées dans cette publication. L'utilisation de publications référencées est obligatoire pour une application correcte de la présente publication.
- 9) L'attention est attirée sur le fait que certains des éléments de la présente Publication de l'IEC peuvent faire l'objet de droits de brevet. L'IEC ne saurait être tenue pour responsable de ne pas avoir identifié de tels droits de brevets et de ne pas avoir signalé leur existence.

La Norme internationale IEC 60335-2-11 a été établie par le comité d'études 61 de l'IEC: Sécurité des appareils électrodomestiques et analogues.

Cette huitième édition annule et remplace la septième édition parue en 2008, l'Amendement 1:2012 et l'Amendement 2:2015. Cette édition constitue une révision technique.

Cette édition inclut les modifications techniques majeures suivantes par rapport à la septième édition:

- alignement du texte sur l'IEC 60335-1, Éd. 5, et ses Amendements 1 et 2;
- conversion de certaines notes en texte normatif (7.12, 7.12.1, 11.3, 19.101, AA.5.2);
- modalités d'essai plus amplement détaillées en 11.3 et en 15.2;

- ajout d'exigences spécifiques en 3.1.9, 3.6.101, 7.12, 11.7, 19.1 et à l'Article 22 pour couvrir les appareils à générateurs de vapeur;
- ajout d'exigences spécifiques en 22.108 pour couvrir les circuits électroniques programmables;
- suppression de l'Annexe AA puisque son contenu est couvert par la Partie 1, et renumérotation des annexes restantes.

Le texte de cette Norme internationale est issu des documents suivants:

FDIS	Rapport de vote
61/5786/FDIS	61/5803/RVD

Le rapport de vote indiqué dans le tableau ci-dessus donne toute information sur le vote ayant abouti à l'approbation de la présente Norme internationale.

Ce document a été rédigé selon les Directives ISO/IEC, Partie 2.

Une liste de toutes les parties de la série IEC 60335, publiées sous le titre général: *Appareils électrodomestiques et analogues – Sécurité*, peut être consultée sur le site web de l'IEC.

La présente partie 2 doit être utilisée conjointement avec la dernière édition de l'IEC 60335-1 et ses amendements. Elle a été établie sur la base de la cinquième édition (2010) de cette norme.

NOTE 1 L'expression «Partie 1» utilisée dans la présente norme fait référence à l'IEC 60335-1.

La présente partie 2 complète ou modifie les articles correspondants de l'IEC 60335-1 de façon à transformer cette publication en norme IEC: Exigences de sécurité pour les sèche-linge à tambour.

Lorsqu'un paragraphe particulier de la Partie 1 n'est pas mentionné dans la présente partie 2, ce paragraphe s'applique pour autant que cela soit raisonnable. Lorsque la présente norme indique «addition», «modification» ou «remplacement», le texte correspondant de la Partie 1 doit être adapté en conséquence.

NOTE 2 Le système de numérotation suivant est utilisé:

- paragraphes, tableaux et figures: ceux qui sont numérotés à partir de 101 sont complémentaires à ceux de la Partie 1;
- notes: à l'exception de celles qui sont dans un nouveau paragraphe ou de celles qui concernent des notes de la Partie 1, les notes sont numérotées à partir de 101, y compris celles des articles ou paragraphes qui sont remplacés;
- les annexes supplémentaires sont appelées AA, BB, etc.

NOTE 3 Les caractères d'imprimerie suivants sont utilisés:

- exigences: caractères romains;
- *modalités d'essais: caractères italiques;*
- notes: petits caractères romains.

Les mots en **gras** dans le texte sont définis à l'Article 3. Lorsqu'une définition concerne un adjectif, l'adjectif et le nom associé figurent également en gras.

Le comité a décidé que le contenu de ce document ne sera pas modifié avant la date de stabilité indiquée sur le site web de l'IEC sous «<http://webstore.iec.ch>» dans les données relatives au document recherché. À cette date, le document sera

- reconduit,
- supprimé,
- remplacé par une édition révisée, ou
- amendé.

NOTE 4 L'attention des Comités nationaux est attirée sur le fait que les fabricants d'appareils et les organismes d'essai peuvent avoir besoin d'une période transitoire après la publication d'une nouvelle publication IEC, ou d'une publication amendée ou révisée, pour fabriquer des produits conformes aux nouvelles exigences et pour adapter leurs équipements aux nouveaux essais ou aux essais révisés.

Le comité recommande que le contenu de cette publication soit entériné au niveau national au plus tôt 12 mois et au plus tard 36 mois après la date de publication.

Les différences suivantes existent dans les pays indiqués ci-après.

- 3.1.9: Le linge a des dimensions différentes (USA).
- 6.2: Il n'est pas exigé que les sèche-linge à tambour soient IPX4 (USA).
- 7.12: La masse de linge peut être remplacée par un nombre de pièces de linge et le marquage d'une mise en garde sur l'appareil concernant l'emploi de produits chimiques pour le nettoyage est exigé (USA).
- 11.2: Les conditions d'essai sont différentes (USA).
- 11.7: L'essai est poursuivi jusqu'à établissement des conditions de régime et des critères différents sont utilisés pour déterminer le moment auquel les conditions de régime sont atteintes (USA).
- 19.4: L'essai est différent (USA).
- 19.9: Un essai de surcharge est effectué pour les sèche-linge à tambour à commande automatique (USA).
- 20.102: En ce qui concerne l'accessibilité au tambour rotatif, un volume maximal de tambour de 60 dm³ et une dimension maximale de porte de 200 mm sont pris en compte (USA).
- 20.103: Cet essai est différent (USA).
- 22.104: L'essai est différent (USA).
- 27.1: Le raccordement électrique de bornes et de contacts de terre au conducteur neutre d'un sèche-linge à tambour est admis (USA).

IMPORTANT – Le logo "colour inside" qui se trouve sur la page de couverture de cette publication indique qu'elle contient des couleurs qui sont considérées comme utiles à une bonne compréhension de son contenu. Les utilisateurs devraient, par conséquent, imprimer cette publication en utilisant une imprimante couleur.

INTRODUCTION

Il a été considéré en établissant la présente Norme internationale que l'exécution de ses dispositions était confiée à des personnes expérimentées et ayant une qualification appropriée.

La présente norme reconnaît le niveau de protection internationalement accepté contre les dangers électriques, mécaniques, thermiques, liés au feu et au rayonnement des appareils, lorsqu'ils fonctionnent comme en usage normal en tenant compte des instructions du fabricant. Elle couvre également les situations anormales auxquelles on peut s'attendre dans la pratique et prend en considération les phénomènes électromagnétiques qui peuvent affecter le fonctionnement en toute sécurité des appareils.

Cette norme tient compte autant que possible des exigences de l'IEC 60364, de façon à rester compatible avec les règles d'installation quand l'appareil est raccordé au réseau d'alimentation. Cependant, des règles nationales d'installation peuvent être différentes.

Si un appareil relevant du domaine d'application de cette norme comporte également des fonctions qui sont couvertes par une autre partie 2 de l'IEC 60335, la partie 2 correspondante est appliquée à chaque fonction séparément, dans la limite du raisonnable. Si cela est applicable, l'influence d'une fonction sur les autres fonctions est prise en compte.

Lorsqu'une partie 2 ne comporte pas d'exigences complémentaires pour couvrir les dangers traités dans la Partie 1, la Partie 1 s'applique.

NOTE 1 Cela signifie que les comités d'études responsables pour les parties 2 ont déterminé qu'il n'était pas nécessaire de spécifier des exigences particulières pour l'appareil en question en plus des exigences générales.

Cette norme est une norme de famille de produits traitant de la sécurité d'appareils et a préséance sur les normes horizontales et génériques couvrant le même sujet.

NOTE 2 Les normes horizontales et génériques couvrant un danger ne sont pas applicables parce qu'elles ont été prises en considération lorsque les exigences générales et particulières ont été étudiées pour la série de normes IEC 60335. Par exemple, dans le cas des exigences de température de surface pour de nombreux appareils, des normes génériques, comme l'ISO 13732-1 pour les surfaces chaudes, ne sont pas applicables en plus de la Partie 1 ou des parties 2.

Un appareil conforme au texte de la présente norme ne sera pas nécessairement jugé conforme aux principes de sécurité de la norme si, lorsqu'il est examiné et soumis aux essais, il apparaît qu'il présente d'autres caractéristiques qui compromettent le niveau de sécurité visé par ces exigences.

Un appareil utilisant des matériaux ou présentant des modes de construction différents de ceux décrits dans les exigences de cette norme peut être examiné et essayé en fonction de l'objectif poursuivi par ces exigences et, s'il est jugé pratiquement équivalent, il peut être estimé conforme aux principes de sécurité de la norme.

APPAREILS ÉLECTRODOMESTIQUES ET ANALOGUES – SÉCURITÉ –

Partie 2-11: Exigences particulières pour les sèche-linge à tambour

1 Domaine d'application

L'article de la Partie 1 est remplacé par l'article ci-après.

La présente Norme Internationale traite de la sécurité des **sèche-linge à tambour** électriques pour usages domestiques et analogues dont la **tension assignée** n'est pas supérieure à 250 V pour les appareils monophasés et à 480 V pour les autres appareils.

NOTE 101 La présente norme s'applique à la fonction de séchage des machines à laver le linge ayant un cycle de séchage.

La présente norme traite également de la sécurité des **sèche-linge à tambour** utilisant un système de réfrigération à motocompresseurs hermétiques pour sécher le linge. Ces appareils peuvent utiliser des **fluides frigorigènes inflammables**. Des exigences supplémentaires pour ces appareils sont données à l'Annexe AA.

Les appareils non destinés à un usage domestique normal mais qui néanmoins peuvent constituer une source de danger pour le public, tels que les appareils destinés à être utilisés par des usagers non avertis dans des magasins, chez des artisans et dans des fermes, relèvent du domaine d'application de la présente norme.

NOTE 102 Les **sèche-linge à tambour** mis à la disposition commune des usagers dans les immeubles d'habitation ou dans les blanchisseries automatiques sont des exemples de tels appareils.

Dans la mesure du possible, la présente norme traite des dangers ordinaires présentés par les appareils, encourus par toutes les personnes.

Cependant, la présente norme ne tient généralement pas compte

- des personnes (y compris des enfants) dont
 - les capacités physiques, sensorielles ou mentales; ou
 - le manque d'expérience et de connaissanceles empêche(nt) d'utiliser l'appareil en toute sécurité sans surveillance ou instruction;
- de l'utilisation de l'appareil comme jouet par des enfants.

NOTE 103 L'attention est attirée sur le fait que

- pour les appareils destinés à être utilisés dans des véhicules ou à bord de navires ou d'avions, des exigences supplémentaires peuvent être nécessaires;
- dans de nombreux pays, des exigences supplémentaires sont spécifiées par les organismes nationaux de la santé, par les organismes nationaux responsables de la protection des travailleurs et par les organismes nationaux responsables de l'alimentation en eau;

NOTE 104 La présente norme ne s'applique pas

- aux appareils prévus exclusivement pour des usages industriels;
- aux appareils destinés à être utilisés dans des locaux présentant des conditions particulières, telles que la présence d'une atmosphère corrosive ou explosive (poussière, vapeur ou gaz);
- aux appareils équipés de dispositifs générant de la vapeur dans lesquels la vapeur est produite à une pression dépassant 50 kPa.

2 Références normatives

L'article de la Partie 1 est applicable avec les exceptions suivantes.

Addition:

IEC 60584-1, *Couples thermoélectriques – Partie 1: Spécifications et tolérances en matière de FEM*

3 Termes et définitions

L'article de la Partie 1 est applicable avec les exceptions suivantes.

3.1 Définitions relatives aux caractéristiques physiques

Remplacement:

3.1.9

conditions de fonctionnement normal

fonctionnement de l'appareil dans les conditions suivantes:

L'appareil est mis en fonctionnement, le tambour étant chargé de linge dont la masse à sec est égale à la charge maximale indiquée dans les instructions.

Le linge est constitué de pièces de coton décati à double ourlet, de dimensions approximatives 70 cm × 70 cm et de masse spécifique comprise entre 140 g/m² et 175 g/m² à sec. Le linge est imbibé d'eau ayant une température de 25 °C ± 5 °C et une masse égale à celle du linge.

Si la fonction de séchage peut suivre automatiquement la fonction de lavage dans une machine à laver le linge, l'appareil n'est pas chargé séparément. L'appareil est mis en fonctionnement avec la quantité maximale de linge indiquée dans les instructions pour le cycle combiné lavage-séchage.

Note 101 à l'article: Le coton dont la teneur en eau n'est pas supérieure à 10 % est considéré comme sec. Le coton conditionné pendant 24 h en air calme à une température de 20 °C ± 2 °C, avec une humidité relative comprise entre 60 % et 70 % et une pression comprise entre 860 mbar et 1 060 mbar, contient environ 7 % d'eau.

Un **générateur de vapeur** conçu pour être rempli à la main est rempli conformément aux instructions, l'eau étant ajoutée afin de maintenir la production de vapeur.

Un **générateur de vapeur** conçu pour être rempli automatiquement est raccordé au réseau d'alimentation en eau.

3.5 Définitions relatives aux types d'appareils

3.5.101

sèche-linge à tambour

appareil dans lequel le linge est séché en le faisant tourner dans un tambour rotatif à travers lequel de l'air chauffé est soufflé

3.5.102

sèche-linge à tambour à condensation

sèche-linge à tambour dans lequel l'air utilisé pour le séchage est déshumidifié par refroidissement

3.6 Définitions relatives aux parties d'un appareil

3.6.101

générateur de vapeur

dispositif dans lequel de la vapeur est produite à une pression inférieure ou égale à 50 kPa et dans lequel la pression est portée à la pression atmosphérique en l'absence de vapeur

3.8 Définitions relatives à des sujets divers

3.8.101

période de refroidissement

partie finale du cycle d'un **sèche-linge à tambour** pendant laquelle le tambour tourne de manière continue, l'élément chauffant étant à puissance réduite et avec une circulation d'air afin de réduire la possibilité de combustion spontanée de la charge de vêtements

Note 1 à l'article: Une rotation continue ne signifie pas une rotation dans le même sens si le fonctionnement prévoit l'inversion du sens en utilisation normale.

4 Exigences générales

L'article de la Partie 1 est applicable.

5 Conditions générales d'essais

L'article de la Partie 1 est applicable.

6 Classification

L'article de la Partie 1 est applicable avec l'exception suivante.

6.2 *Addition:*

Les appareils doivent être au moins IPX4.

7 Marquage et instructions

L'article de la Partie 1 est applicable avec les exceptions suivantes.

7.1 *Addition:*

L'appareil doit porter le symbole ISO 7000-0790 (2004-01) ou doit comporter, en substance, l'indication suivante:

Lire les instructions

7.10 *Addition:*

Si la **position arrêt** est indiquée uniquement par des lettres, le mot «arrêt» doit être utilisé.

7.12 *Addition:*

Les instructions doivent indiquer

- la masse maximale de linge sec, en kilogrammes, à utiliser avec l'appareil;

- que le sèche-linge à tambour ne doit pas être utilisé si des produits chimiques ont été utilisés pour le nettoyage;
- que le filtre à air doit être nettoyé fréquemment, le cas échéant;
- que l'accumulation de peluche autour du sèche-linge à tambour doit être évitée (non applicable pour les appareils destinés à être raccordés à une ventilation vers l'extérieur de l'immeuble);
- qu'une ventilation appropriée doit être fournie afin d'éviter un refoulement, à l'intérieur de la pièce, de gaz provenant d'appareils brûlant d'autres combustibles, y compris les feux ouverts (cette instruction n'est pas exigée si le **sèche-linge à tambour** évacue l'air à l'intérieur de la pièce).

Si le symbole ISO 7000-0790 (2004-01) est utilisé, sa signification doit être explicitée.

Les instructions doivent comporter, en substance, les indications suivantes.

- Ne pas sécher dans le sèche-linge à tambour des articles non lavés.
- Il convient que les articles qui ont été salis avec des substances telles que l'huile de cuisson, l'acétone, l'alcool, l'essence, le kérosène, les détachants, la térébenthine, la cire et les substances pour retirer la cire soient lavés dans de l'eau chaude avec une quantité supplémentaire de détergent avant d'être séchés dans le sèche-linge à tambour.
- Il convient que les articles comme le caoutchouc mousse (mousse de latex), les bonnets de douche, les textiles étanches, les articles doublés de caoutchouc et les vêtements ou les oreillers comprenant des parties en caoutchouc mousse ne soient pas séchés dans le sèche-linge à tambour.
- Il convient d'utiliser les produits assouplissants ou produits similaires, conformément aux instructions relatives aux produits assouplissants.
- Retirer des poches tous les objets tels que briquets et allumettes.
- Remplir les générateurs de vapeur uniquement avec les liquides spécifiés par le fabricant.

Les instructions doivent comporter, en substance, la mise en garde suivante:

ATTENTION: Ne jamais arrêter un sèche-linge à tambour avant la fin du cycle de séchage, à moins que tous les articles ne soient retirés rapidement et étalés, de telle sorte que la chaleur soit dissipée.

Les instructions des appareils pour lesquels la température de l'air dépasse 55 °C lors du cycle de séchage doivent comporter, en substance, la mise en garde suivante:

ATTENTION: L'appareil ne doit pas être alimenté par l'intermédiaire d'un interrupteur externe, comme une minuterie, ou être connecté à un circuit qui est régulièrement mis sous tension et hors tension par un fournisseur d'électricité.

7.12.1 Addition:

Les instructions doivent indiquer que

- pour les appareils comportant des ouvertures de ventilation à leur base, les ouvertures ne doivent pas être obstruées par un tapis;
- l'air rejeté ne doit pas être évacué dans une évacuation utilisée pour les fumées rejetées provenant des appareils brûlant du gaz ou d'autres combustibles (cette instruction n'est pas exigée si le **sèche-linge à tambour** évacue l'air à l'intérieur de la pièce);
- l'appareil ne doit pas être installé derrière une porte à verrouillage, une porte coulissante ou une porte ayant une charnière du côté opposé à celle du sèche-linge, empêchant ainsi l'ouverture totale du sèche-linge à tambour.

Si les instructions indiquent que le **sèche-linge à tambour** peut être placé sur le dessus d'une machine à laver le linge, elles doivent indiquer les machines à laver le linge qui sont appropriées. Des instructions doivent être données concernant l'assemblage du **sèche-linge à tambour** et de la machine à laver le linge. Les instructions doivent indiquer comment obtenir les dispositifs de fixation exigés, à moins qu'ils ne soient fournis avec l'appareil.

7.14 Addition:

La hauteur du symbole ISO 7000-0790 (2004-01) doit être d'au moins 15 mm.

7.15 Addition:

Le symbole ISO 7000-0790 (2004-01) ou le marquage «Lire les instructions» doit être facilement visible lorsque l'appareil est installé comme en utilisation normale.

8 Protection contre l'accès aux parties actives

L'article de la Partie 1 est applicable.

9 Démarrage des appareils à moteur

L'article de la Partie 1 n'est pas applicable.

10 Puissance et courant

L'article de la Partie 1 est applicable.

11 Échauffements

L'article de la Partie 1 est applicable avec les exceptions suivantes.

11.2 Addition:

Les filtres à air sont nettoyés puis 50 % de la surface du filtre est obturée.

11.3 Addition:

*Lorsque les **surfaces accessibles** externes sont suffisamment planes et que l'accès le permet, le calibre d'essai de la Figure 101 est utilisé pour mesurer les échauffements des **surfaces accessibles** externes spécifiées dans le Tableau 101. Le calibre est appliqué avec une force de $4\text{ N} \pm 1\text{ N}$ à la surface de manière à assurer le meilleur contact possible entre le calibre et la surface. Le mesurage est effectué après une période de contact de 30 s.*

Le calibre peut être maintenu en place à l'aide d'un statif à pince ou d'un dispositif similaire. Tout instrument de mesure donnant les mêmes résultats qu'avec le calibre peut être utilisé.

11.7 Remplacement:

Les appareils comportant une minuterie, un dispositif de commande sensible à l'humidité ou un autre dispositif de commande limiteur de durée sont soumis à des cycles de fonctionnement. Chaque cycle comprend une période de fonctionnement ayant une durée égale au temps maximal que peut fournir le dispositif de commande et une période de repos de 4 min pendant laquelle l'appareil est rechargé.

L'essai peut être terminé si l'échauffement d'aucune partie ne dépasse la valeur déterminée au cours du cycle précédent de plus de 8 K.

Les appareils ayant un cycle combiné lavage-séchage sont mis en fonctionnement avec le programme de séchage conduisant aux échauffements les plus élevés.

Les appareils équipés d'un **générateur de vapeur** sont mis en fonctionnement avec le mode de vapeur conduisant aux échauffements les plus élevés.

Les autres appareils sont mis en fonctionnement continu jusqu'à l'établissement des conditions de régime.

11.8 Addition:

Pendant l'essai, les échauffements sont surveillés en permanence et ne doivent pas dépasser les valeurs présentées dans le Tableau 3 et le Tableau 101.

Tableau 101 – Échauffements maximaux pour les surfaces accessibles externes dans des conditions de fonctionnement normal avec la porte fermée

Surface ^c	Échauffement ^a K		
	Surfaces des appareils situées au maximum à 850 mm du sol après installation		Surfaces situées à plus de 850 mm du sol après installation ^d
	Surfaces frontales	Autres surfaces ^d	
Métal nu	38	42	42
Métal revêtu ^a	42	49	49
Verre et céramique	51	56	56
Plastique et revêtement plastique > 0,4 mm ^b	58	62	62
^a Un métal est considéré comme étant revêtu lorsqu'un revêtement d'une épaisseur minimale de 90 µm en vernis de finition ou un revêtement plastique partiel est utilisé. ^b La limite d'échauffement du plastique s'applique également aux matières plastiques de finition en métal d'épaisseur inférieure à 0,1 mm. ^c Lorsque l'épaisseur du revêtement plastique ne dépasse pas 0,4 mm, les limites d'échauffement du métal revêtu ou du verre et de la céramique s'appliquent. ^d Si ces valeurs sont supérieures, il est admis de répéter l'essai en éloignant l'appareil de la paroi latérale du coin d'essai. L'essai est répété au cours de 1 cycle. ^e Les échauffements ne sont pas mesurés sur les emplacements suivants: – la partie inférieure des appareils destinés à être utilisés sur un plan de travail ou sur le sol inaccessibles à un calibre de 75 mm de diamètre dont l'extrémité est hémisphérique et appliquée à une force ne dépassant pas 1 N; – la surface arrière des appareils inaccessibles à un calibre de 75 mm de diamètre dont l'extrémité est hémisphérique et appliquée à une force ne dépassant pas 1 N.			

Les échauffements sont mesurés avec la porte fermée.

La température de l'air rejeté provenant du tambour, mesurée au niveau du premier filtre à peluches après le passage de l'air dans la charge de vêtements doit être mesurée pour les besoins de 22.105.

12 Vacant

13 Courant de fuite et rigidité diélectrique à la température de régime

L'article de la Partie 1 est applicable avec l'exception suivante.

13.2 Modification:

Pour les **appareils fixes de la classe I**, le courant de fuite ne doit pas dépasser 3,5 mA ou 1 mA/kW de **puissance assignée** avec une limite de 5 mA, suivant la valeur la plus élevée.

14 Surtensions transitoires

L'article de la Partie 1 est applicable.

15 Résistance à l'humidité

L'article de la Partie 1 est applicable avec l'exception suivante.

15.2 Modification:

L'essai est effectué avec le tambour rempli de linge mouillé comme cela est spécifié pour les **conditions de fonctionnement normal**, la masse de l'eau étant toutefois approximativement de 1,5 fois la masse à sec du linge.

Les appareils destinés à être raccordés au réseau d'alimentation en eau sont mis en fonctionnement avec la sortie du circuit de condensation bloquée. La vanne d'entrée est maintenue ouverte et le remplissage est poursuivi pendant 1 min après le début du débordement ou pendant 5 min après qu'un **dispositif de protection** se soit mis en fonctionnement pour arrêter l'arrivée d'eau. Les portes sont ouvertes mais les dispositifs de verrouillage ne sont pas forcés.

Pour tous les appareils, une quantité de 0,5 l de solution est rapidement versée sur le dessus de l'appareil de sorte que la solution de débordement coule sur les surfaces de l'appareil qui comprennent des commandes, les commandes étant mises en position marche. Les commandes sont ensuite mises en fonctionnement sur toute leur plage de service, cette opération étant répétée après 5 min.

L'appareil doit alors satisfaire à l'essai de rigidité diélectrique de 16.3 et l'examen doit montrer qu'il n'y a pas de traces d'eau sur l'isolation pouvant entraîner une réduction des **distances dans l'air** ou des **lignes de fuite** au-dessous des valeurs spécifiées à l'Article 29.

16 Courant de fuite et rigidité diélectrique

L'article de la Partie 1 est applicable avec l'exception suivante.

16.2 Modification:

Pour les **appareils fixes de la classe I combinés**, le courant de fuite ne doit pas dépasser 1 mA ou 1 mA/kW de **puissance assignée** avec une limite de 5 mA, suivant la valeur la plus élevée.