

INTERNATIONAL STANDARD

QC 301801

**Fixed capacitors for use in electronic equipment –
Part 13-1: Blank detail specification – Fixed polypropylene film dielectric metal
foil d.c. capacitors – Assessment level E and EZ**

IECNORM.COM : Click to view the full PDF of IEC 60384-13-1:2006



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2006 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

IECNORM.COM : Click to view the full PDF of IEC 60384-12-1:2006

INTERNATIONAL STANDARD

QC 301801

**Fixed capacitors for use in electronic equipment –
Part 13-1: Blank detail specification – Fixed polypropylene film dielectric metal
foil d.c. capacitors – Assessment level E and EZ**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

M

ICS 31.060.30

ISBN 2-8318-8412-8

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –**Part 13-1: Blank detail specification – Fixed polypropylene film dielectric metal foil d.c. capacitors – Assessment level E and EZ**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-13-1 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This second edition cancels and replaces the first edition published in 1991 and constitutes a minor revisions related to tables, figures and references.

The text of this standard is based on the following documents:

FDIS	Report on voting
40/1621/FDIS	40/1644/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The QC number that appears on the front cover of this publication is the specification number in the IEC Quality Assessment System for Electronic Components (IECQ).

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60384 consists of the following parts, under the general title *Fixed capacitors for use in electronic equipment*:

- Part 1: Generic specification
- Part 2: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric d.c. capacitors
- Part 3: Sectional specification: Fixed tantalum chip capacitors
- Part 4: Sectional specification: Aluminium electrolytic capacitors with solid and non-solid electrolyte
- Part 5: Sectional specification: Fixed mica dielectric d.c. capacitors with a rated voltage not exceeding 3000 V – Selection of methods of test and general requirements
- Part 6: Sectional specification: Fixed metallized polycarbonate film dielectric d.c. capacitors
- Part 8: Sectional specification: Fixed capacitors of ceramic dielectric, Class 1
- Part 9: Sectional specification: Fixed capacitors of ceramic dielectric, Class 2
- Part 11: Sectional specification: Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors
- Part 12: Sectional specification: Fixed polycarbonate film dielectric metal foil d.c. capacitors
- Part 13: Sectional specification: Fixed polypropylene film dielectric metal foil d.c. capacitors
- Part 14: Sectional specification: Fixed capacitors for electromagnetic interference suppression and connection to the supply mains
- Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte
- Part 16: Sectional specification: Fixed metallized polypropylene film dielectric d.c. capacitors
- Part 17: Sectional specification: Fixed metallized polypropylene film dielectric a.c. and pulse capacitors
- Part 18: Sectional specification: Fixed aluminium electrolytic chip capacitors with solid electrolyte
- Part 19: Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric chip d.c. capacitors
- Part 20: Sectional specification: Fixed metallized polyphenylene sulfide film dielectric chip d.c. capacitors
- Part 21: Sectional specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 1
- Part 22: Sectional specification: Fixed surface mount multilayer capacitors of ceramic dielectric, Class 2
- Part 23: Sectional specification: Fixed surface mount metallized polyethylene naphthalate film dielectric d.c. capacitors

Part 24: Sectional specification – Surface mount fixed tantalum electrolytic capacitors with conductive polymer solid electrolyte¹

Part 25: Sectional specification – Surface mount fixed aluminium electrolytic capacitors with conductive polymer solid electrolyte¹

All sectional specifications mentioned above do have one or more blank detail specifications being a supplementary document, containing requirements for style, layout and minimum content of detail specifications.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

The contents of the corrigendum of March 2009 have been included in this copy.

¹ To be published.

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 13-1: Blank detail specification – Fixed polypropylene film dielectric metal foil d.c. capacitors – Assessment level E and EZ

Blank detail specification

A blank detail specification is a supplementary document to the sectional specification and contains requirements for style and layout and minimum content of detail specifications. Detail specifications not complying with these requirements may not be considered as being in accordance with IEC specifications nor shall they so be described.

In the preparation of detail specifications the content of 1.4 of the sectional specification shall be taken into account. The numbers between brackets on the first page correspond to the following information which shall be inserted in the position indicated.

Identification of the detail specification

- (1) The "International Electrotechnical Commission" or the National Standards Organization under whose authority the detail specification is drafted.
- (2) The IEC or National Standards number of the detail specification, date of issue and any further information required by the national system.
- (3) The number and issue number of the IEC or national generic specification.
- (4) The IEC number of the blank detail specification.

Identification of the capacitor

- (5) A short description of the type of capacitor.
- (6) Information on typical construction (when applicable).

When the capacitor is not designed for use in printed-board applications, this shall be clearly stated in the detail specification in this position.

- (7) Outline drawing with main dimensions which are of importance for interchangeability and/or reference to the national or international documents for outlines. Alternatively, this drawing may be given in an annex to the detail specification.
- (8) Application or group of applications covered and/or assessment level.

The assessment level(s) to be used in a detail specification shall be selected from the sectional specification, 3.5.4. This implies that one blank detail specification may be used in combination with several assessment levels, provided the grouping of the tests does not change.

- (9) Reference data on the most important properties, to allow comparison between the various capacitor types.

(1)	IEC 60384-13-1-XXX (2) QC 301801-XXX
ELECTRONIC COMPONENTS OF ASSESSED QUALITY IN ACCORDANCE WITH: (3)	IEC 60384-13-1 (4) QC 301801
	FIXED POLYPROPYLENE (5) FILM DIELECTRIC METAL FOIL DC CAPACITORS
Outline drawing: (see Table 1) (...angle projection) (7) (Other shapes are permitted within the dimensions given.)	
	(6)
	Assessment level(s): E (8) Stability class:

Information on the availability of components qualified to this detail specification is given in IEC QC 001005

(9)

1 General data

1.1 Recommended method(s) of mounting

See IEC 60384-13, 1.4.2.

1.2 Dimensions

Table 1 – Case size reference and dimensions

Case size reference	Dimensions (in mm)						
	$\varnothing$	L	H	d			

When there is no case size reference, Table 1 may be omitted and the dimensions shall be given in Table 2, which then becomes Table 1.

The dimensions shall be given as maximum dimensions or as nominal dimensions with a tolerance.

1.3 Ratings and characteristics

Capacitance range (see Table 2)

Tolerance on rated capacitance

Rated voltage (see Table 2)

Category voltage (if applicable) (see Table 2)

Climatic category

Rated temperature

Maximum a.c. voltage (if applicable)

Tangent of loss angle

Insulation resistance

Table 2 – Values of capacitance and of voltage related to case sizes

Rated voltage				
Category voltage ^a				
Nominal capacitance (in pF, nF and/or µF)	Case size	Case size	Case size	Case size
^a If different from the rated voltage.				

1.4 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60410, *Sampling plans and procedures for inspection by attributes*

IEC 60384-1, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

IEC 60384-13, *Fixed capacitors for use in electronic equipment – Part 13: Sectional Specification: Fixed polypropylene film dielectric metal foil d.c. capacitors*

1.5 Marking

The marking of the capacitor and the package shall be in accordance with the requirements of IEC 60384-13, 1.6.

The details of the marking of the component and package shall be given in full in the detail specification.

1.6 Ordering information

Orders for capacitors covered by this specification shall contain, in clear or in coded form, the following minimum information:

- nominal capacitance;
- tolerance on rated capacitance;
- rated d.c. voltage;
- number and issue reference of the detail specification and style reference.

1.7 Certified records of released lots

Required/not required.

1.8 Additional information (not for inspection purposes)

1.9 Additional or increased severities or requirements to those specified in the generic and/or sectional specification

NOTE Additions or increased requirements should be specified only when essential.

Table 3 – Other characteristics

This table is to be used for defining characteristics which are additional to or more severe than those given in the sectional specification.
--

2 Inspection requirements

2.1 Procedures

2.1.1 For qualification approval, the procedures shall be in accordance with the sectional specification, IEC 60384-13, 3.4.

2.1.2 For quality conformance inspection, the test schedule (Table 4) includes sampling, periodicity, severities and requirements. The formation of inspection lots is covered by IEC 60384-13, 3.5.1.

IECNORM.COM : Click to view the full PDF of IEC 60384-13-1:2006

Table 4 – Test schedule for quality conformance inspection

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	IL	E level	EZ level		Performance requirements ^a
				AQL ^c	n	c	
Group A inspection (lot-by-lot) Subgroup A0 4.2.2 Capacitance 4.2.3 Tangent of loss angle 4.2.1 Voltage proof (Test A) 4.2.4 Insulation resistance (Test A)	ND	Frequency : 1 kHz for all capacitance values Method: ... Measuring point 1a Measuring point 1a			100 % ^d		Within specified tolerance As in 4.2.3.2 No breakdown or flashover. Self-healing breakdowns allowed As in 4.2.4.3
Subgroup A1 4.1 Visual examination 4.1 Dimensions (gauging)	ND		S-3	2,5%	^b	0	As in 4.1 Legible marking and as specified in 1.5 of this specification As specified in Table 1 of this specification
Subgroup A2 4.2.1 Voltage proof (Test A) 4.2.2 Capacitance 4.2.3 Tangent of loss angle 4.2.4 Insulation resistance (Test A)	ND	Method: ... Method: ...	S-3	1,0%	^b	0	No breakdown or flashover Within specified tolerance As in 4.2.3.2 As in 4.2.4.2
Group B inspection (lot-by-lot) Subgroup B1 4.5 Solderability 4.14 Solvent resistance of the marking (if applicable)	ND	Without ageing Method: ... Solvent: ... Solvent temperature: ... Method 1 Rubbing material: cotton wool Recovery time: ...	S-3	2,5%	^b	0	Good tinning as evidenced by free flowing of the solder with wetting of the terminations or solder shall flow within ... s, as applicable See detail specification

Table 4 (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Sample size and criterion of acceptability ^c						Performance requirements ^a
			E			EZ			
			<i>p</i>	<i>n</i>	<i>c</i>	<i>p</i>	<i>n</i>	<i>c</i>	
Group C inspection (periodic)									
Subgroup C1A Part of sample of Subgroup C1	D		6	9	1	6	5	0	
4.1 Dimensions (detail)									See detail specification
4.3.1 Initial measurements		Capacitance Tangent of loss angle:							
4.3 Robustness of terminations		Visual examination							No visible damage
4.4 Resistance to soldering heat		Method: Recovery: 1 h to 2 h							
4.4.2 Final measurements		Visual examination Capacitance							No visible damage Legible marking ΔC/C within limit for relevant stability class at upper category temperature as specified in 2.2.4 of the sectional specification and compared to the value measured in 4.3.1
4.13 Component solvent resistance (if applicable)		Solvent: ... Solvent temperature: ... Method 2 Recovery time:							See detail specification
Subgroup C1B Other part of sample of Subgroup C1	D		6	18	1	6	5	0	
4.6.1 Initial measurements		Capacitance Tangent of loss angle:							
4.6 Rapid change of temperature		T _A = Lower category temperature T _B = Upper category temperature Five cycles Duration <i>t</i> = 30 min Visual examination							No visible damage
4.7 Vibration		Method of mounting: see 1.1 of this specification Frequency range: ... Hz to ... Hz Amplitude 0,75 mm or acceleration 100 m/s ² (whichever is the less severe) Total duration: 6 h							

Table 4 (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Sample size and criterion of acceptability ^c						Performance requirements ^a
			E			EZ			
			<i>p</i>	<i>n</i>	<i>c</i>	<i>p</i>	<i>n</i>	<i>c</i>	
4.7.2 Final inspection		Visual examination							No visible damage
		Capacitance							$\Delta C/C$ within limit for relevant stability class at upper category temperature as specified in 2.2.4 of the sectional specification and compared to the value measured in 4.6.1
4.8 Bump (or shock, see 4.9)		Method of mounting: see 1.1 of this specification							
		Number of bumps: ... Acceleration: .. m/s ² Duration of pulse: ... ms							
4.9 Shock (or bump, see 4.8)		Method of mounting: see 1.1 of this specification							
		Acceleration: .. m/s ² Duration of pulse: ... ms							
4.8.3 Final or measurements 4.9.3		Visual examination							No visible damage
		Capacitance							$\Delta C/C$ within limit for relevant stability class at upper category temperature as specified in 2.2.4 of the sectional specification and compared to the value measured in 4.7.2
		Tangent of loss angle							As in 4.2.3.2
Subgroup C1 Combined sample of specimens of Subgroups C1A and C1B	D		6	27	2	6	10	0	
4.10 Climatic sequence									
4.10.2 Dry heat		Temperature: upper category temperature Duration: 16 h							
4.10.3 Damp heat, cyclic, Test Db, first cycle									
4.10.4 Cold		Temperature: lower category temperature Duration: 2 h							
4.10.5 Low air pressure (if required by the detail specification)		Air pressure: 8 kPa Duration: 1 h							
4.10.5.3 Intermediate measurement		Visual examination							No permanent breakdown, flashover or harmful deformation of the case
4.10.6 Damp heat, cyclic, Test Db, remaining cycles		Recovery: 1 h to 2 h							

Table 4 (continued)

Subclause number and test ^a	D or ND _c	Conditions of test ^a	Sample size and criterion of acceptability _c						Performance requirements ^a
			E			EZ			
			<i>p</i>	<i>n</i>	<i>c</i>	<i>p</i>	<i>n</i>	<i>c</i>	
4.10.6.2 Final measurement		Visual examination Capacitance Tangent of loss angle Insulation resistance							No visible damage Legible marking Δ <i>C/C</i> within limit for relevant stability class at 85 °C as specified in 2.2.4 of the sectional specification and compared to the value measured in 4.4.2, 4.8.3 or 4.9.3, as applicable Tan δ ≤ 1,4 times value measured in 4.3.1 or 4.6.1, as applicable ≥50 % of values in 4.2.4.2
Subgroup C2 4.11 Damp heat, steady state 4.11.1 Initial measurements 4.11.3 Final measurement	D	 Capacitance Tangent of loss angle Recovery: 1 h to 2 h Visual examination Capacitance Tangent of loss angle Insulation resistance	6	15	1	6	10	0	 No visible damage Legible marking Δ <i>C/C</i> within limit for relevant stability class at 85 °C as specified in 2.2.4 of the sectional specification and compared to the value measured in 4.11.1 Tan δ ≤ 1,4 times value measured in 4.11.1 ≥ 50 % of values in 4.2.4.2
Subgroup C3 4.12 Endurance 4.12.1 Initial measurement 4.12.5 Final measurement	D	 Duration: ... h Capacitance Tangent of loss angle: Visual examination Capacitance Tangent of loss angle Insulation resistance	3	21	1	6	10	0	 No visible damage Legible marking Δ <i>C/C</i> within limit for relevant stability class at upper category temperature as specified in 2.2.4 of sectional specification and compared to value measured in 4.12.1 Tan δ as in 4.2.3.2 or ≤ 1,4 times value measured in 4.12.1, whichever is the greater ≥50 % of values in 4.2.4.2