

Essais relatifs aux risques du feu –
Partie 11-20: Flammes d'essai –
Méthodes d'essai à la flamme de 500 W

Fire hazard testing –
Part 11-20: Test flames –
500 W flame test methods

CORRIGENDUM 1

Page 10

1 Domaine d'application

Dernier alinéa, au lieu de:

(voir 8.3.7)

lire:

(voir 8.4)

Page 20

8.2.6

Remplacer la première phrase existante par ce qui suit:

Si une seule éprouvette d'un lot de cinq éprouvettes barreaux, pour un traitement donné, ne satisfait pas à tous les critères pour une catégorie, un nouveau lot de cinq éprouvettes barreaux soumises au même conditionnement, doit être essayé. Toutes éprouvettes du second lot doivent satisfaire à tous les critères spécifiés pour la catégorie.

Page 22

Au lieu de:

8.3.7 Classification

lire:

8.4 Classification

Page 11

1 Scope

Last paragraph, instead of:

(see 8.3.7)

read:

(see 8.4)

Page 21

8.2.6

Replace the existing first sentence by the following:

If only one test specimen from a set of five bar test specimens for a given conditioning treatment does not conform to all of the criteria for a category, another set of five bar test specimens, subjected to the same conditioning, shall be tested. All test specimens from the second set shall conform to all of the specified criteria for the category.

Page 23

Instead of:

8.3.7 Classification

read:

8.4 Classification