

INTERNATIONAL STANDARD

**Optical fibre cables –
Part 3-50: Outdoor cables – Family specification for gas pipe cables and
subducts for installation by blowing and/or pulling/dragging in gas pipes**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

**Optical fibre cables –
Part 3-50: Outdoor cables – Family specification for gas pipe cables and
subducts for installation by blowing and/or pulling/dragging in gas pipes**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE



ICS 33.180.10

ISBN 978-2-88910-296-9

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Symbols and abbreviations.....	7
4 Family specification for gas pipe cables and subducts for installation by blowing and/or pulling/dragging in gas pipes (blank detail specification and minimum requirements).....	8
4.1 Construction.....	8
4.1.1 General	8
4.1.2 Subducts	8
4.1.3 Gas pipe cables.....	8
4.2 Optical fibres.....	9
4.2.1 Single-mode dispersion unshifted (B1.1) optical fibre.....	9
4.2.2 Single-mode dispersion shifted (B2) optical fibre.....	9
4.2.3 Single-mode non-zero dispersion (B4) optical fibre.....	10
4.2.4 Single-mode (B6) optical fibre	10
4.2.5 Multimode fibres	10
4.3 High pressure gas pipe cable constructions.....	11
4.3.1 Cable for installation within subducts (previously installed within the high pressure gas pipe).....	11
4.3.2 Cable for direct installation within the high pressure gas pipe	12
4.3.3 Subduct construction	13
4.4 Installation and operating conditions	13
4.4.1 Tests applicable to cables/cable elements	13
4.4.2 Installation conditions	13
4.5 Mechanical and environmental tests.....	14
4.5.1 Subducts	14
4.5.2 Cable for installation within subducts (previously installed into the gas pipe).....	16
4.5.3 Cables for direct installation into the high pressure gas pipe	20
Annex A (informative) Blank detail specification.....	24
Annex B (informative) OF cables for high pressure gas pipes	27
Annex C (informative) Examples of subducts and high pressure gas pipe cables	28
Annex D (informative) Example for installation schemes of cables in high pressure gas pipes (fibre-in-gas).....	30
Figure C.1 – Example of constructions of cables for installation in subducts within gas pipes	28
Figure C.2 – Example of constructions of cables for direct installation into high pressure gas pipes	29
Figure D.1 – Picture of an I/O-port	30
Figure D.2 – Schematic drawing of Figure D.1: installation of OF cable within the gas pipe	30
Figure D.3 – Schematic drawing of the installation of I/O-ports on high pressure PE gas pipes.....	31

Table 1 – Single-mode dispersion unshifted (B1.1) optical fibre	9
Table 2 – Single-mode dispersion shifted (B2) optical fibre	9
Table 3 – Single-mode non-zero dispersion (B4) optical fibre.....	10
Table 4 – Single-mode (B6) optical fibre	10
Table 5 – Characteristics – Cable for installation within subducts	11
Table 6 – Characteristics – Cable for direct installation within the high pressure gas pipe	12
Table 7 – Characteristics – Subduct construction.....	13
Table 8 – Tests applicable to cables/cable elements.....	13
Table 9 – Tests applicable to subducts	14
Table 10 – Tests applicable for OF cables within subducts	16
Table 11 – Tests applicable to direct installed OF cables.....	20
Table A.1 – Cables for subduct installation into the gas pipe.....	24
Table A.2 – Cables for direct installation into the gas pipe	25
Table A.3 – Subduct description	26
Table B.1 – OF cables for high pressure gas pipes	27

Withdrawing
IECNORM.COM : Click to view the full PDF of IEC 60794-3-50:2008

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPTICAL FIBRE CABLES –

**Part 3-50: Outdoor cables –
Family specification for gas pipe cables
and subducts for installation by blowing and/or
pulling/dragging in gas pipes**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60794-3-50 has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

This standard is to be used in conjunction with IEC 60794-1-1 and IEC 60794-1-2, and IEC 60794-3.

The text of this standard is based on the following documents:

FDIS	Report on voting
86A/1231/FDIS	86A/1242/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2

A list of all parts of IEC 60794 series, under the general title *Optical fibre cables*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

Withdrawn
IECNORM.COM : Click to view the full PDF of IEC 60794-3-50:2008

OPTICAL FIBRE CABLES –

Part 3-50: Outdoor cables – Family specification for gas pipe cables and subducts for installation by blowing and/or pulling/dragging in gas pipes

1 Scope

This part of IEC 60794 is a family specification that covers gas pipe cables and subducts for installation by blowing and/or pulling/dragging in high pressure gas pipes (400 mbar to 4 bar). Systems built with components covered by this standard are subject to the requirements of sectional specification IEC 60794-3.

Gas pipe cable and subduct constructions have to meet the different requirements of the gas-companies and/or associations regarding chemical, environmental, operational interactions and in general maintenance conditions.

I/O-ports for the inlet and outlet of the gas pipe cables (and/or subducts) are housing the sealing system assuring the absolute gas tightness preventing any gas leakage due to the installation of the gas pipe cables into the gas pipes.

A table of preferential applications, describing gas pipe cable characteristics versus methods of installation is reported in Annex A for high pressure gas pipe cables.

Clause 4 describes a blank detail specification for gas pipe cables and subducts for installation by blowing and/or pulling/dragging in high pressure gas pipes. It incorporates some minimum requirements.

Detail specifications may be prepared on the basis of this family specification.

The parameters specified in this standard may be affected by measurement uncertainty arising either from measurement errors or calibration errors due to lack of suitable standards. Acceptance criteria should be interpreted with respect to this consideration.

The number of fibres tested is representative of the gas pipe cable and should be agreed between the customer and the supplier.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60304, 1982: *Standard colours for insulation for low-frequency cables and wires*

IEC 60793-1-20, *Optical fibres – Part 1-20: Measurement methods and test procedures – Fibre geometry*

IEC 60793-1-40, *Optical fibres – Part 1-40: Measurement methods and test procedures – Attenuation*

IEC 60793-1-44, *Optical fibres – Part 1-44: Measurement methods and test procedures – Cut-off wavelength*

IEC 60793-2, *Optical fibres – Part 2: Product specifications – General*

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-1-1, *Optical fibre cables – Part 1-1: Generic specification – General*

IEC 60794-1-2, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures*

IEC 60794-3, *Optical fibre cables – Part 3: Sectional specification – Outdoor cables*

IEC 60794-3-10, *Optical fibre cables – Part 3-10: Outdoor cables – Family specification for duct and directly buried optical telecommunication cables*

IEC 60811-1-1, 1993: *Common test methods for insulating and sheathing materials of electric cables and optical cables – Part 1-1: Methods for general application – Measurement of thickness and overall dimensions – Tests for determining the mechanical properties*

IEC 60811-5-1, 1990 *Insulating and sheathing materials of electric and optical cables – Common test methods – Part 5-1: Methods specific to filling compounds – Drop-point – Separation of oil – Lower temperature brittleness – Total acid number – Absence of corrosive components – Permittivity at 23 °C – DC resistivity at 23 °C and 100 °C*

3 Symbols and abbreviations

For the purposes of this document, the following symbols and abbreviations apply.

λ_{cc}	cabled fibre cut-off wavelength
d	nominal outer diameter of the gas pipe optical fibre cable
d_c	nominal outer diameter of the subduct
DS	detail specification
T_O	threshold tensile load below which no attenuation and/or fibre strain increase should occur in the tensile performance test
T_M	the acceptable amount of short-term tensile load that can be applied to the cable without permanent degradation of the characteristics of the fibres in the tensile performance test
T_{A1}	temperature cycling test low-temperature limit according to IEC 60794-1-2, method F1
T_{A2}	temperature cycling test low-temperature limit according to IEC 60794-1-2, method F1
T_{B1}	temperature cycling test high-temperature limit according to IEC 60794-1-2, method F1
T_{B2}	temperature cycling test high-temperature limit according to IEC 60794-1-2, method F1
t_1	temperature cycling dwell time
$n \times d$	a value times cable outer diameter used for bends, mandrels, etc.
PE	polyethylene
I/O-port	input/ output port for guiding the cable into and out of the gas pipe

APL	aluminium/polyethylene laminate
SPL	steel/polyethylene laminate

4 Family specification for gas pipe cables and subducts for installation by blowing and/or pulling/dragging in gas pipes (blank detail specification and minimum requirements)

4.1 Construction

4.1.1 General

In addition to the constructional requirements of sectional specification IEC 60794-3, the following considerations apply to the gas pipe cables and/or subducts.

The gas pipe cables and/or subducts shall be designed and manufactured for an expected operating lifetime of at least 10 years. It shall be possible to install or remove the cable in or from the gas pipe throughout the operational lifetime. The materials in the gas pipe cable and/or as well as accessories including fixing elements, i.e. I/O-ports and subducts shall not present a health hazard within its intended use.

4.1.2 Subducts

In case of use, the subduct with outer nominal diameters ranging from 10 mm to 100 mm shall be able to resist pressure differences needed for installation by blowing and able to withstand the gas pressure within the gas pipe. They shall be circular and the outer and inner surfaces of low coefficient of friction. The material shall withstand all possible chemical attacks by the natural gas itself. Inner- and outer-diameter and overall minimum wall thickness shall be specified.

4.1.3 Gas pipe cables

A gas pipe cable in accordance to this specification should be suitable for installation in high pressure gas pipes by the following installation methods, also applicable for the access gas pipe network:

- blowing and /or pulling into a subduct, previously installed into the high pressure gas pipe between two I/O-ports;
- direct installation into the gas pipe in between two adjacent I/O-ports.

The attenuation of the installed cable at the operational wavelength(s) shall not exceed values agreed between the customer and the supplier.

There shall be no fibre splice in a delivery length unless otherwise agreed by the customer and the supplier.

It shall be possible to identify each individual fibre throughout the length of the gas pipe cable.

4.2 Optical fibres

4.2.1 Single-mode dispersion unshifted (B1.1) optical fibre

Table 1 – Single-mode dispersion unshifted (B1.1) optical fibre

Characteristics (9)	IEC 60794-3 Clause /subclause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Uncabled optical fibre	5	IEC 60793-2-50		
Attenuation coefficient (cabled fibres)	5.2.1	According to DS	IEC 60793-1-40, method A, B or C	
at 1 310 nm at 1 550 nm and at 1 625 nm ¹ .		$\leq 0,40$ dB/km $\leq 0,35$ dB/km $\leq 0,40$ dB/km		
Attenuation discontinuities at 1 310 and 1 550 nm	5.2.2	$\leq 0,10$ dB	IEC 60793-1-40, method C	
Cabled fibre cut-off wavelength	5.3	$\lambda_{cc} < \lambda$ operational	IEC 60793-1-44, method B	
Fibre colouring	5.4	IEC 60304	Visual inspection	
Outer diameter including colouring	8.2.1.1	IEC 60793-2	IEC 60793-1-20, method D	

4.2.2 Single-mode dispersion shifted (B2) optical fibre

Table 2 – Single-mode dispersion shifted (B2) optical fibre

Characteristics (9)	IEC 60794-3 Clause/ subclause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Uncabled optical fibre	5.1	IEC 60793-2		
Attenuation coefficient (cabled fibres)	5.2.1	According to DS	IEC 60793-1-40, method A, B or C	
at 1 550 nm	5.2.1	$\leq 0,35$ dB/km		
Attenuation discontinuities at 1 550 nm	5.2.2	$\leq 0,10$ dB/km	IEC 60793-1-40, method C	
Cabled fibre cut-off wavelength	5.3	$\lambda_{cc} < \lambda$ operational	IEC 60793-1-44, method B	
Fibre colouring	5.4	IEC 60304	Visual inspection	
Outer diameter including colouring	8.2.1.1	IEC 60793-2	IEC 60793-1-20, method D	

¹ Measurements at 1 625 nm are optional.

4.2.3 Single-mode non-zero dispersion (B4) optical fibre

Table 3 – Single-mode non-zero dispersion (B4) optical fibre

Characteristics (9)	IEC 60794-3 Clause/subclause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Uncabled optical fibre	5.1	IEC 60793-2		
Attenuation coefficient (cabled fibres)	5.2.1	According to DS	IEC 60793-1-40, method A, B or C	
at 1 550 nm	5.2.1	$\leq 0,35$ dB/km		
at 1 625 ² nm		$\leq 0,40$ dB/km		
Attenuation discontinuities at 1 550 nm	5.2.2	$\leq 0,10$ dB/km	IEC 60793-1-40, method C	
Cabled fibre cut-off wavelength	5.3	$\lambda_{cc} < \lambda_{\text{operational}}$	IEC 60793-1-44, method B	
Fibre colouring	5.4	IEC 60304	Visual inspection	
Outer diameter including colouring	8.2.1.1	IEC 60793-2	IEC 60793-1-20, method D	

4.2.4 Single-mode (B6) optical fibre

Table 4 – Single-mode (B6) optical fibre

Characteristics (9)	IEC 60794-3 Clause/subclause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Uncabled optical fibre	5.1	IEC 60793-2		
Attenuation coefficient (cabled fibres)	5.2.1	According to DS	IEC 60793-1-40, method A, B or C	
at 1 550 nm	5.2.1	$\leq 0,30$ dB/km		
at 1 625 ³ nm		$\leq 0,40$ dB/km		
Attenuation discontinuities at 1 550 nm	5.2.2	$\leq 0,10$ dB/km	IEC 60793-1-40, method C	
Cabled fibre cut-off wavelength	5.3	$\lambda_{cc} < \lambda_{\text{operational}}$	IEC 60793-1-44, method B	
Fibre colouring	5.4	IEC 60304	Visual inspection	
Outer diameter including colouring	8.2.1.1	IEC 60793-2	IEC 60793-1-20, method D	

4.2.5 Multimode fibres

Under consideration.

² Measurements at 1 625 nm are optional.

³ Measurements at 1 625 nm are optional.

4.3 High pressure gas pipe cable constructions

4.3.1 Cable for installation within subducts (previously installed within the high pressure gas pipe)

Table 5 – Characteristics – Cable for installation within subducts

Characteristics (9)	IEC 60794-3 Clause/subclause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Lay-up	7.2	According to DS	Visual inspection	
Gas pipe cable core	7.3	According to DS		
Filling compound (if used)		According to DS	Either IEC 60794-1-2, method E14, or IEC 60811-5-1, Clause 4 IEC 60811-5-1, Clause 5 IEC 60811-5-1, Clause 8	
Dry blocking compound	7.3	According to DS	Under consideration	
Strength member	7.4	According to DS	Visual inspection	
- central				
- peripheral				
Moisture barrier	7.5	According to DS		
Metallic tapes (if any):				
Outer cable sheath	7.6			
Material				
Minimum sheath thickness		According to DS	IEC 60811-1-1	
Outer cable diameter		According to DS	IEC 60811-1-1	
Optional protection		According to DS		
Sheath marking	7.7			
Configuration, dimensions		According to DS	Visual inspection	
Abrasion resistance		According to DS	IEC 60794-1-2, method E2B	Method 1 Steel needle diameter $d = 1,0 \text{ mm}$ load: 4 N Method 2 with: felt pad consisting of either 1) water soaked wool felt or 2) rayon felt with < 30 % wool Weight: > 450 g
Sheath abrasion	9.2.8	According to DS	IEC 60794-1-2, method E2A	
Gas pipe cable length			Under consideration	

4.3.2 Cable for direct installation within the high pressure gas pipe

Table 6 – Characteristics – Cable for direct installation within the high pressure gas pipe

Characteristics (9)	IEC60794-3 Clause/subclause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Lay-up	7.2	According to DS	Visual inspection	
Gas pipe cable core	7.3	According to DS		
Filling compound (if used)		According to DS	Either IEC 60794-1-2, method E14 or IEC 60811-5-1, Clause 4 IEC 60811-5-1, Clause 5 IEC 60811-5-1, Clause 8	
Dry blocking compound	7.3	According to DS	Under consideration	
Strength member	7.4	According to DS	Visual inspection	
- central				
- peripheral				
Moisture barrier	7.5	According to DS		
Metallic tapes:				
Outer cable sheath	7.6			
Material				
Minimum sheath thickness		According to DS	IEC 60811-1-1	
Outer cable diameter		According to DS	IEC 60811-1-1	
Optional protection		According to DS		
Sheath marking	7.7			
Configuration, dimensions		According to DS	Visual inspection	
Abrasion resistance		According to DS	IEC 60794-1-2, method E2B	Method 1 Steel needle diameter $d = 1,0 \text{ mm}$ load: 4 N Method 2 with: felt pad consisting of either 1) water soaked wool felt or 2) rayon felt with < 30 % wool Weight: > 450 g
Sheath abrasion	9.2.8	According to DS	IEC 60794-1-2, method E2A	
Gas pipe cable length			Under consideration	

4.3.3 Subduct construction

Table 7 – Characteristics – Subduct construction

Characteristics (9)	IEC 60794-3 as applicable Clause/sub-clause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Material(s)				
Subduct inner diameter		According to DS	IEC 60811-1-1	
Subduct outer diameter		According to DS	IEC 60811-1-1	
Subduct (non-metallic)	Under consideration	Under consideration	Under consideration	Under consideration
Inner subduct (if any): subduct wall thickness Inner layer (if any) Outer layer - Total wall thickness				
Subduct length			Under consideration	

4.4 Installation and operating conditions

4.4.1 Tests applicable to cables/cable elements

Table 8 – Tests applicable to cables/cable elements

Characteristics (9)	IEC 60794-3 Clause/sub-clause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
General requirements	8.1	Agreement between customer and supplier		
Tests applicable to loose tubes:				
Bend test	8.2.1.2	According to DS	IEC 60794-1-2, method G1	
Tube kinking	8.2.2.1	According to DS	IEC 60794-1-2, method G7	
Tests applicable to ribbons:				
Dimensions	8.2.3.1	IEC 60794-3, Table 1	IEC 60794-3, 8.2.3.1	
Separability of individual fibres from ribbon	8.2.3.2.1	IEC 60794-3, 7.2.3.2.1 or according to DS	IEC 60794-1-2, method G5 or according to DS	
Ribbon stripping	8.2.3.2.2	According to DS		
Torsion	8.2.3.2.3	According to DS	IEC 60794-1-2, method G6	

4.4.2 Installation conditions

Under consideration.

4.5 Mechanical and environmental tests

4.5.1 Subducts

4.5.1.1 Tests applicable

Tests listed in the following Table 9 are those relevant to IEC 60794-3 as applicable for subducts.

Table 9 – Tests applicable to subducts

Characteristics (9)	IEC 60794-3 Clause/sub- clause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Tensile performance	9.1	According to DS	IEC 60794-1-2, methods E1A and E1B	
Installation capability (selection from the following)	9.2			
bending under tension	9.2.1	According to DS	IEC 60794-1-2, method E18	
repeated bending	9.2.2		IEC 60794-1-2, method E6	
impact	9.2.3	4.5.1.2.4	IEC 60794-1-2, method E4	
kink	9.2.4	According to DS and 4.5.1.2.2	IEC 60794-1-2, method E10	
torsion	9.2.5		IEC 60794-1-2, method E7	
subduct bend	9.3	According to DS	IEC 60794-1-2, method E11	
Crush	9.4	According to DS and 4.6.1.2.3	IEC 60794-1-2, method E3	
Flexibility		4.6.1.2.5		
Ageing	9.6			
finished conduit	9.6.2	Under consideration		
Pressure		According to DS and 4.5.1.2.1		

4.5.1.2 Details of family requirements and test conditions for subducts

Tests shall be selected from those of Table 9 and the following hereinafter described.

4.5.1.2.1 Pressure

a) Family requirements

Under visual examination, without magnification, there shall be no damage to the conduit.

b) Test conditions

Method: under consideration

All conduits shall resist an air pressure of at least ($2,5 \times$ the installation pressure) at a temperature of 20 °C for a period of 30 min.

Additionally, the same performance shall be demonstrated after a sample of conduit has been maintained at 60 °C for a period of 12 weeks.

All conduits shall resist a proof test pressure of at least $(1,3 \times \text{the installation pressure})$ at a temperature of 20 °C for a period of 24 h, after tensile and bending tests.

c) Family requirements

Under visual examination without magnification, there shall be no damage and the diameter shall not change by more than x %.

d) Test conditions

Method:	under consideration
Tube length under tension:	under consideration
Tensile load on tube:	under consideration
Diameter of test pulleys:	under consideration

4.5.1.2.2 Kink

a) Family requirements

Under visual examination, without magnification, there shall be no kink to the conduits.

b) Test conditions

Method:	IEC 60794-1-2, E10
Minimum diameter:	20 times the outer diameter of the conduit

4.5.1.2.3 Crush

a) Family requirements

Under visual examination, without magnification, there shall be no damage to the conduit. There shall be no residual deformation greater than 15 % of the subduct diameter, no splitting or permanent damage after removing load. The imprint of the anvil on the jacket is not considered as mechanical damage.

b) Test conditions

Method:	IEC 60794-1-2, E3
Sample length:	250 mm
load (plate/plate):	$50 \times d_c$ (N) (d_c in mm) or 450 N whichever is lower
Duration time:	60 s
Recovery time:	1 h

4.5.1.2.4 Impact

a) Family requirements

Under visual examination without magnification, there shall be no damage to the subduct. There shall be no residual deformation greater than 15 % of the conduit diameter, no splitting or permanent damage. The imprint of the striking surface on the subduct is not considered mechanical damage.

b) Test conditions

Method:	under consideration
Striking surface radius:	10 mm
Impact energy:	1 J
Recovery time:	1 h
Number of impacts:	one in 3 different places spaced not less than 500 mm apart

4.5.1.2.5 Flexibility

a) Family requirements

The outer and inner diameter of the conduits shall show, under visual examination without magnification, no damage and no reduction of diameter greater than 15 %.

b) Tests conditions

Method: ten turns of the conduit shall be wrapped tightly and secured around a mandrel of diameter 12 times the outer diameter of the conduit itself

Duration: 30 min

4.5.2 Cable for installation within subducts (previously installed into the gas pipe)

4.5.2.1 Tests applicable

Table 10 – Tests applicable for OF cables within subducts

Characteristics (9)	IEC 60794-3 Clause/sub- clause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Tensile performance	9.1	4.5.2.2.1 and according to DS	IEC 60794-1-2, methods E1A and E1B	
Installation capability (selection from the following)	9.2			
bending under tension	9.2.1	According to DS	IEC 60794-1-2, method E18	
repeated bending	9.2.2	4.5.2.2.2	IEC 60794-1-2, method E6	
impact	9.2.3		IEC 60794-1-2, method E4	
kink	9.2.4	According to DS	IEC 60794-1-2, method E10	
torsion blowing	9.2.5	4.5.2.2.3 and according to DS	IEC 60794-1-2, method E7	
Cable bend	9.3	According to DS and 4.5.2.2.4	IEC 60794-1-2, method E11	
Crush	9.4	According to DS and 4.5.2.2.5	IEC 60794-1-2, method E3	
Temperature cycling	9.5	4.5.2.2.7	IEC 60794-1-2, method F1	
Ageing	9.6			
coating adhesion stability	9.6.1	According to DS	IEC 60794-1-2, method E5	
finished cable	9.6.2	Under consideration		
Water penetration	9.7	According to DS	IEC 60794-1-2, method F5B	
Pneumatic resistance	9.8	According to DS (under consideration)	IEC 60794-1-2, method F6	
Induced voltage (for cables with metallic elements)	9.9	Under consideration		

4.5.2.2 Details of family requirements and test conditions for high pressure gas pipe cable tests

The expression of "no change in attenuation" means that any change in measurement value, either positive or negative, within the uncertainty of measurement shall be ignored. The uncertainty of measurement for this standard shall be $< 0,05$ dB for attenuation.

Tests shall be selected from those of Table 10 and the following hereinafter described.

4.5.2.2.1 Tensile performance

a) Family requirements

Under long term tensile load (T_L) the fibre strain shall not exceed 20 % of the fibre proof strain and there shall be no change in attenuation during the test. Under installation load (T_M) the fibre strain shall not exceed 60 % of the fibre proof strain and the attenuation change during test shall be measured and recorded. Other criteria may be agreed between the customer and the supplier.

Under visual examination without magnification, there shall be no damage to the sheath or to the cable elements.

There shall be no change after test in attenuation when measured in the 1 550 nm region or at the operational wavelength when specified by the customer, at room temperature.

b) Test conditions

Method:	IEC 60794-1-2, E1A and E1B
Cable length under tension:	not less than 50 m. Taking into account the measurement accuracy and end effects, shorter lengths may be used by agreement between the customer and the supplier
Fibre length:	finished cable length
Tensile load on cable:	long term tensile load (T_L) and installation load (T_M) Other loads may be applied in accordance with particular user conditions.
Diameter of test pulleys:	1 m but not less than the minimum loaded bending diameter specified for the cable.
T_M :	equivalent to weight of 1 km of gas pipe cable or 50 N whichever is greater
T_L :	equivalent to weight of 500 m of gas pipe cable or 25 N whichever is greater (ffs)

4.5.2.2.2 Repeated bending

a) Family requirements

Under visual examination without magnification, there shall be no damage to the sheath and to the cable elements.

b) Test conditions

Method:	IEC 60794-1-2, E6
Bending radius:	20 d or 30 mm whichever is greater
Load:	adequate to assure uniform contact with the mandrel
Number of cycles:	25
Duration of cycle:	approximately 2 s

4.5.2.2.3 Torsion

a) Family requirements

Under visual examination without magnification, there shall be no damage to the sheath or to the cable elements.

The variation on attenuation for each fibre shall be less than, or equal to, 0,10 dB at 1 550 nm, or at the operational wavelength when specified by the customer.

There shall be no permanent change in attenuation after the test.

b) Test conditions

Method: IEC 60794-1-2, E7

Length under test: 2 m

Number of turns: one half turn (through 180°) over the length of 2 m in each direction

Number of cycles: 5

4.5.2.2.4 Bend

a) Family requirements

There shall be no change in attenuation when measured in the 1 550 nm region or at the operational wavelength when specified by the customer, at room temperature.

The change in attenuation when tested at -30 °C shall be ≤ 0,1 dB if required.

b) Test conditions

Method: IEC 60794-1-2, E11

Diameter of mandrel: ≤ 40 d or 60 mm whichever is greater

Number of turns/helix: 4

Number of cycles: 3

4.5.2.2.5 Crush

a) Family requirements

Immediately after removal of load, there shall be no increase in attenuation when measured in the 1 550 nm region or at the operational wavelength when specified by the customer.

Under visual examination, there shall be no damage to the sheath or to the cable elements after removing load. The imprint of the plate or mandrel on the sheath is not considered mechanical damage.

b) Test conditions

Method: IEC 60794-1-2, E3

Load (plate/plate): 450 N

Duration of load: 1 min

4.5.2.2.6 Impact

a) Family requirements

The cable shall be tested in accordance with IEC 60794-1-2, method E4

b) Test conditions:

Striking surface radius: 10 mm

Impact energy: 1 J with striking surface radius of 10 mm

Number of impacts: one in 3 different places spaced not less than 500 mm apart

Under visual examination without magnification, there shall be no damage to the sheath or to the cable elements. The imprint of the anvil on the sheath is not considered as mechanical damage.

4.5.2.2.7 Temperature cycling

a) Family requirements

During the last cycle, there shall be no change in attenuation between the initial room temperature measurement and T_{A1} or T_{B1} . For 1 625 nm applications, performance criteria shall be mutually agreed upon between the customer and supplier.

During the last cycle, the attenuation change from the room temperature measurement and T_{A2} or T_{B2} shall be $< 0,15$ dB/km at 1 550 nm. For 1 625 nm applications, performance criteria shall be mutually agreed upon between the customer and supplier. On completion of the test, there shall be no change in attenuation.

Definition of a cycle: T_{B2} to T_{A2}

Definition of the last cycle: T_{A2} , T_{A1} , T_{B1} , T_{B2} with a final measurement at room temperature.

b) Test conditions

Sample length: finished cable length of at least 1 000 m.

High temperature, T_{B2} : +60 °C to +70 °C, depending on customer requirements.

High temperature, T_{B1} : +30 °C to +60 °C, depending on customer requirements.

Low temperature, T_{A1} : –10 °C to –15 °C, depending on customer requirements.

Low temperature, T_{A2} : T_{A1} to –40 or –45 °C, depending on customer requirements.

Rate of heating: sufficiently slow that the effect of changing the cooling temperature does not cause temperature shock.

t_1 : temperature cycling test dwell time until a stable temperature is reached

Number of cycles: 2, but additional cycles may be required in accordance with particular customer requirements.

4.5.3 Cables for direct installation into the high pressure gas pipe

4.5.3.1 Tests applicable

Table 11 – Tests applicable to direct installed OF cables

Characteristics (9)	IEC 60794-3 Clause/sub- clause (10)	Family requirements (11)	Test methods (12)	Remarks (13)
Tensile performance	9.1	4.5.3.2.1	IEC 60794-1-2, methods E1A and E1B	
Installation capability (selection from the following)	9.2			
bending under tension	9.2.1	According to DS	IEC 60794-1-2, method E18	
repeated bending	9.2.2	4.5.3.2.2	IEC 60794-1-2, method E6	
impact	9.2.3	4.5.3.2.6	IEC 60794-1-2, method E4	
kink	9.2.4	According to DS	IEC 60794-1-2, method E10	
torsion	9.2.5	4.5.3.2.3	IEC 60794-1-2, method E7	
Cable bend	9.3	According to DS and 4.5.3.2.4	IEC 60794-1-2, method E11	
Crush	9.4	According to DS and 4.5.3.2.5	IEC 60794-1-2, method E3	
Temperature cycling	9.5	According to DS and 4.5.3.2.7	IEC 60794-1-2, method F1	
Ageing	9.6			
coating adhesion stability	9.6.1	According to DS	IEC 60794-1-2, method E5	
finished cable	9.6.2	Under consideration		
Water penetration	9.7	According to DS	IEC 60794-1-2, method F5B	
Pneumatic resistance	9.8	According to DS (under consideration)	IEC 60794-1-2, method F6	
Induced voltage (for cables with metallic elements)	9.9	Under consideration		
Mould growth	Under consideration	Under consideration	Under consideration	

4.5.3.2 Details of family requirements and test conditions for high pressure gas pipe cables

The expression of "no change in attenuation" means that any change in measurement value, either positive or negative, within the uncertainty of measurement shall be ignored. The uncertainty of measurement for this standard shall be < 0,05 dB for attenuation.

Tests shall be selected from those of Table 11 and the following hereinafter described.

4.5.3.2.1 Tensile performance

a) Family requirements

Under long term tensile load (T_L) the fibre strain shall not exceed 20 % of the fibre proof strain and there shall be no change in attenuation during the test. Under installation load (T_M) the fibre strain shall not exceed 60 % of the fibre proof strain and the attenuation change during test shall be measured and recorded. Other criteria may be agreed between the customer and the supplier.

Under visual examination without magnification, there shall be no damage to the sheath or to the cable elements.

There shall be no change after test in attenuation when measured in the 1 550 nm region or at the operational wavelength when specified by the customer, at room temperature.

b) Test conditions

Method:	IEC 60794-1-2, E1A and E1B
Cable length under tension:	not less than 50 m. Taking into account the measurement accuracy and end effects, shorter lengths may be used by agreement between the customer and the supplier
Fibre length:	finished cable length
Tensile load on cable:	long term tensile load (T_L) and installation load (T_M). Other loads may be applied in accordance with particular user conditions
Diameter of test pulleys:	1 m but not less than the minimum loaded bending diameter specified for the cable
T_M :	equivalent to weight of 1 km of gas pipe cable or 50 N whichever is greater
T_L :	equivalent to weight of 500 m of gas pipe cable or 25 N whichever is greater (ffs)

4.5.3.2.2 Repeated bending

a) Family requirements

Under visual examination without magnification, there shall be no damage to the sheath and to the cable elements.

b) Test conditions

Method:	IEC 60794-1-2, E6
Bending radius:	20 d or 30 mm whichever is greater
Load:	adequate to assure uniform contact with the mandrel
Number of cycles:	25
Duration of cycle:	approximately 2 s

4.5.3.2.3 Torsion

a) Family requirements

Under visual examination without magnification, there shall be no damage to the sheath or to the cable elements.

The variation on attenuation for each fibre shall be less than, or equal to, 0,10 dB at 1 550 nm, or at the operational wavelength when specified by the customer.

There shall be no permanent change in attenuation after the test.

b) Test conditions

Method: IEC 60794-1-2, E7
 Length under test: 2 m
 Number of turns: one half turn (through 180°) over the length of 2 m in each direction
 Number of cycles: 5

4.5.3.2.4 Bend

a) Family requirements

There shall be no change in attenuation when measured in the 1 550 nm region or at the operational wavelength when specified by the customer, at room temperature

The change in attenuation when tested at –30 °C shall be ≤ 0,1 dB if required.

b) Test conditions

Method: IEC 60794-1-2, E11
 Diameter of mandrel: ≤ 40 *d* or 60 mm whichever is greater
 Number of turns/helix: 4
 Number of cycles: 3

4.5.3.2.5 Crush

a) Family requirements

Immediately after the removal of load, there shall be no increase in attenuation when measured in the 1 550 nm region or at the operational wavelength when specified by the customer.

Under visual examination, there shall be no damage to the sheath or to the cable elements after removing load. The imprint of the plate or mandrel on the sheath is not considered mechanical damage.

b) Test conditions

Method: IEC 60794-1-2, E3
 Load (plate/plate): 2 500 N
 Duration of load: 1 min

4.5.3.2.6 Impact

a) Family requirements

The cable shall be tested in accordance with IEC 60794-1-2, method E4.

b) Test conditions:

Striking surface radius: 10 mm
 Impact energy: 10 J with striking surface radius of 10 mm
 Number of impacts: one in 3 different places spaced not less than 500 mm apart

Under visual examination without magnification, there shall be no damage to the sheath or to the cable elements. The imprint of the anvil on the sheath is not considered as mechanical damage.

4.5.3.2.7 Temperature cycling

a) Family requirements

During the last cycle, there shall be no change in attenuation between the initial room temperature measurement and T_{A1} or T_{B1} . For 1 625 nm applications, performance criteria shall be mutually agreed upon between the customer and supplier.

During the last cycle, the attenuation change from the room temperature measurement and T_{A2} or T_{B2} shall be $< 0,15$ dB/km at 1 550 nm. For 1 625 nm applications, performance criteria shall be mutually agreed upon between the customer and supplier. On completion of the test, there shall be no change in attenuation.

Definition of a cycle: T_{B2} to T_{A2}

Definition of the last cycle: T_{A2} , T_{A1} , T_{B1} , T_{B2} with a final measurement at room temperature.

b) Test conditions

Sample length: finished cable length of at least 1 000 m

High temperature, T_{B2} : +60 °C to +70 °C, depending on customer requirements

High temperature, T_{B1} : +30 °C to +60 °C, depending on customer requirements

Low temperature, T_{A1} : –10 °C to –15 °C, depending on customer requirements

Low temperature, T_{A2} : T_{A1} to –40 or –45 °C, depending on customer requirements

Rate of heating: sufficiently slow that the effect of changing the cooling temperature does not cause temperature shock

t_1 : temperature cycling test dwell time until a stable temperature is reached

Number of cycles: 2, but additional cycles may be required in accordance with particular customer requirements

Annex A (informative)

Blank detail specification

A.1 Gas pipe cables description

A.1.1 Cable for installation within subducts (previously installed into the gas pipe in between two adjacent I/O-ports)

Such a gas pipe cable has to be blown or pulled into the subduct described in Clause A.2.

Table A.1 – Cables for subduct installation into the gas pipe

(1) Prepared by		(2) Document No.: Issue: Date:
(3) Available from	(4) Generic specifications: Sectional specification:	IEC 60794-1-1 and IEC 60794-1-2 IEC 60794-3
(5) Additional references:		
Construction - Tube – filled Additional armouring - Metallic armouring Outer sheath Marking identification - Customer requirement - Identification of supplier		Additional remarks
(8) Application information:		
Maximum outer diameter (d) Rated maximum tensile load Minimum bending radius for no-load bending Minimum bending radius for rated-load bending Temperature range - Transport and storage - Installation - Operation Delivery length - Typical - Nominal/tolerances		

A.1.2 Cables for direct installation into the gas pipe

Such cables are directly installed into the high pressure gas pipe with the help of a - pressure reduced - gas flow of the natural gas itself and/or compressed air (see Note) using a stabilized parachute within the high pressure gas pipe.

The cable should have a low coefficient of friction with respect to the inner surface of the gas pipe, which consists of steel, cast iron and/or PE.

NOTE Before pressurizing with air, the gas pipe-section has to be inerted by nitrogen.

Table A.2 – Cables for direct installation into the gas pipe

(1) Prepared by		(2) Document No.: Issue: Date:
(3) Available from	(4) Generic specifications: Sectional specification:	IEC 60794-1-1 and IEC 60794-1-2 IEC 60794-3
(5) Additional references:		
Construction Subduct – filled Inner sheath (optional) - Metallic armouring Outer sheath Marking identification - Customer requirement - Identification of supplier		Additional remarks
(8) Application information:		
Maximum outer diameter (d) Rated maximum tensile load Minimum bending radius for no-load bending Minimum bending radius for rated-load bending Temperature range - Transport and storage - Installation - Operation Delivery length - Typical - Nominal/tolerances		

A.2 Subduct description

Such subducts are directly inserted into the inner space of the high pressure gas pipe guided by guide subducts to the bottom of the gas pipe.

Table A.3 – Subduct description

(1) Prepared by		(2) Document No.: Issue: Date:
(3) Available from	(4) Generic specifications: IEC 60794-1-1 and IEC 60794-1-2 Sectional specification: IEC 60794-3 (all as applicable to conduits)	
(5) Additional references:		
All dielectric construction Single layer wall Double layer wall Marking identification Customer requirement Identification of the supplier		
(8) Application information:		
Maximum outer diameter (<i>d</i>) Rated maximum tensile load Minimum bending radius for no-load bending Minimum bending radius for rated load bending Temperature range - transport and storage - installation - operation delivery subduct length - typical - nominal/tolerances		Under consideration