

INTERNATIONAL STANDARD

IEC
61097-2

Second edition
2002-09

**Global maritime distress and safety
system (GMDSS) –**

**Part 2:
COSPAS-SARSAT EPIRB –
Satellite emergency position indicating radio
beacon operating on 406 MHz –
Operational and performance requirements,
methods of testing and required test results**



Reference number
IEC 61097-2:2002(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (http://www.iec.ch/searchpub/cur_fut.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (http://www.iec.ch/online_news/justpub/jp_entry.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC
61097-2

Second edition
2002-09

Global maritime distress and safety system (GMDSS) –

Part 2: COSPAS-SARSAT EPIRB – Satellite emergency position indicating radio beacon operating on 406 MHz – Operational and performance requirements, methods of testing and required test results

© IEC 2002 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

W

For price, see current catalogue

CONTENTS

FOREWORD	4
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Performance requirements	7
3.1 Compliance	7
3.2 General	8
3.3 Operational	8
3.4 Distress function	10
3.5 Float-free arrangements	11
3.6 Environment	11
3.7 Environment for float-free arrangement	12
3.8 Interference – electromagnetic compatibility	12
3.9 Maintenance	12
3.10 Safety precautions	12
3.11 Equipment manuals	13
3.12 Labelling	14
3.13 Installation	14
4 Technical characteristics	15
4.1 Transmitted frequency	15
4.2 Signal and message format	15
4.3 Distress message memory	15
4.4 Beacon identification code	15
4.5 121,5 MHz homing signal	15
4.6 Power source	15
4.7 Antenna characteristics (C/S T.001)	16
5 Methods of testing and required test results	16
5.1 General	16
5.2 General tests	18
5.3 Operational tests	19
5.4 Distress function	21
5.5 Float-free arrangements	22
5.6 Environment	22
5.7 Maintenance	23
5.8 Safety precautions	23
5.9 Equipment manuals	23
5.10 Labelling	23
5.11 Installation	23
5.12 Power source	23
5.13 Environment	24
5.14 Interference testing	26
5.15 Spurious emissions	26
5.16 Compass safe distance	26
5.17 Conducted interference	26

Annex A (normative) Sequence of tests.....	27
A.1 Compulsory sequence of tests	27
A.2 Additional tests	27
Annex B (normative) List of COSPAS-SARSAT tests.....	29
B.1 Power output	29
B.2 Digital message	29
B.3 Digital message generator	29
B.4 Modulation	29
B.5 406 MHz transmitted frequency.....	30
B.6 Spurious emissions (into 50 Ω)	30
B.7 406 MHz VSWR check	30
B.8 Self-test mode	30
B.9 Thermal shock (30 °C change).....	30
B.10 Operating lifetime at minimum temperature.....	31
B.11 Temperature gradient (5 °C/h)	31
B.12 Long-term frequency stability.....	31
B.13 Protection against continuous transmission	31
B.14 Satellite qualitative tests	31
B.15 Antenna characteristics.....	31
B.16 Beacon Coding Software.....	32
B.17 Navigation System.....	32
Annex C (normative) Standard for a manually activated satellite EPIRB without a float-free mechanism.....	33
C.1 Requirements	33
Annex D (normative) Technical standard for 121,5 MHz homing device.....	34
D.1 General	34
D.2 Performance requirements.....	34
D.3 Technical characteristics	34
D.4 Methods of testing and required test results.....	35
Annex E (informative) User experience of COSPAS-SARSAT EPIRB operation	40

INTERNATIONAL ELECTROTECHNICAL COMMISSION

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –**Part 2: COSPAS-SARSAT EPIRB – Satellite emergency position
indicating radio beacon operating on 406 MHz –
Operational and performance requirements,
methods of testing and required test results**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61097-2 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This second edition cancels and replaces the first edition, published in 1994, of which it constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/348/FDIS	80/351/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2007. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

INTRODUCTION

This revision of IEC 61097-2 is due to changes to the Radio Regulations, COSPAS-SARSAT requirements and amendments to the IMO performance standards for 406 MHz Satellite emergency position indicating radio beacons (EPIRBs).

The document has been renumbered and rearranged to comply in certain aspects with ISO/IEC Directives, and the requirements have been regrouped in a more logical order.

IECNORM.COM: Click to view the full PDF of IEC 61097-2:2002

Withd2W

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –

Part 2: COSPAS-SARSAT EPIRB – Satellite emergency position indicating radio beacon operating on 406 MHz – Operational and performance requirements, methods of testing and required test results

1 Scope

This part of IEC 61097 specifies the minimum performance requirements, technical characteristics and type-testing requirements of the satellite emergency position-indicating radio beacon used in the COSPAS-SARSAT satellite system (satellite EPIRB), as required by Regulation IV/7.1.6 of the 1988 amendments to the 1974 International Convention for Safety of Life at Sea (SOLAS), and which is associated with IEC 60945 (General requirements). When a requirement in this standard is different from IEC 60945, the requirement in this standard shall take precedence.

This standard also includes minimum performance standards for a manually activated satellite EPIRB without float-free release mechanism (see annex C).

This standard incorporates the performance standards of IMO Resolutions A.810(19) *Performance Standards for float-free satellite emergency position-indicating radio beacons (EPIRBs) operating on 406 MHz* and A.662(16) *Performance Standards for float-free release and activation arrangements for emergency radio equipment*, the International Telecommunication Union (ITU) Radio Regulations as well as the technical characteristics for such transmitters contained in Recommendation ITU-R M.633 (as amended), and takes account of the general requirements contained in IMO Resolution A.694(17).

All texts of this standard, whose wording is identical to that in the IMO SOLAS Convention 1974 as amended in 1988 and Resolutions A.658(16), A.662(16), A.689(17), A.694(17), A.696(17), A.702(17) and A.810(19) and Recommendation ITU-R M.633 will be printed in italics and the Resolution/Recommendation and paragraph number indicated between brackets.

NOTE 1 Classes of satellite EPIRB's considered in this document are:

- Class 1: Float-free (–40 °C to +55 °C). The float-free release mechanism (A.662(16)) should be capable of operating throughout the temperature range of –40 °C to +65 °C.

This class is not required by IMO Resolutions but may be applied at the discretion of each Administration.

- Class 2: Float-free (–20 °C to +55 °C). The float-free release mechanism (A.662(16)) should be *capable of operating throughout the temperature range of –30 °C to +65 °C*.

NOTE 2 Non-float-free, manually activated satellite EPIRB's in both classes are considered in annex C.

NOTE 3 All classes shall include a 121,5 MHz homing device, described in annex D.

User experience of COSPAS-SARSAT EPIRB operation leading to some clarification of IMO performance standards, and providing some useful information for satellite EPIRB users is included in annex E.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Marine navigation and radiocommunication equipment and systems – General Requirements – Methods of testing and required test results*

IMO Resolution A.658(16):1989, *Use and fitting of retro-reflective materials on life-saving appliances*

IMO Resolution A.662(16):1989, *Performance standards for float-free release and activation arrangements for emergency radio equipments*

IMO Resolution A.689(17):1991, *Testing of life-saving appliances*

IMO Resolution A.694(17):1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A.696(17):1991, *Type approval of satellite emergency position-indicating radio beacons (EPIRBs) operating in the COSPAS-SARSAT system*

IMO Resolution A.702(17):1991, *Radio maintenance guidelines for the global maritime distress and safety system (GMDSS) related to sea areas A3 and A4*

IMO Resolution A.810(19):1995, *Performance standards for float-free satellite emergency position-indicating radio beacons (EPIRBs) operating on 406 MHz*

ITU-R Recommendation M.585 as amended, *Assignment and use of maritime mobile service identities*

ITU-R Recommendation M.633, *Transmission characteristics of a satellite emergency position-indicating radio beacon (satellite EPIRB) system operating through a low polar-orbiting satellite system in the 406 MHz band*

ITU-R Recommendation M.690-1, *Technical characteristics of emergency position indicating radio beacons (EPIRBs) operating on the carrier frequencies of 121,5 MHz and 243 MHz*

COSPAS-SARSAT
C/S T.001, as amended, *Specification for COSPAS-SARSAT 406 MHz distress beacons and*
C/S T.007, as amended, *COSPAS-SARSAT 406 MHz distress beacon type approval standard*
(as applicable to EPIRBs).

IMO Safety of Life at Sea (SOLAS) Convention 1974, as amended. (GMDSS)

3 Performance requirements

3.1 Compliance

(A.810(19)/A.1) *The satellite emergency position-indicating radio beacon (EPIRB) shall, in addition to meeting the requirements of the Radio Regulations, the relevant ITU-R Recommendations and the general requirements set out in resolution A.694(17) comply with the following performance Standard.*

In addition to this performance Standard, the satellite EPIRB shall comply with the requirements of COSPAS-SARSAT documents C/S T.001 and C/S T.007, as amended.

The radio frequency of operation of the equipment shall at all times be within the limits defined by the Radio Regulations.

3.2 General

- a) The satellite EPIRB shall be (IV/7.1.6.3) *ready to be manually released and capable to be carried by one person into a survival craft.*
- b) (A.810(19)/A.2.1) *The satellite EPIRB shall be capable of transmitting a distress alert to a polar orbiting satellite service operating in the 406 MHz band.*
- c) It shall be designed to operate according to this standard when floating in the sea and shall also be capable of operating on board a ship and on a survival craft.
- d) (A.810(19)/A.2.2) *The satellite EPIRB shall be of an automatic float-free type. The equipment, mounting and releasing arrangements shall be reliable and operate satisfactorily under the most extreme conditions likely to be met with at sea.*
- e) (A.662(16)/1) *Float-free release and activation arrangements shall enable the automatic release of the satellite EPIRB from a sinking ship and its automatic activation. Table 1 shows the correct combination of control functions to prevent or enable activation.*

Table 1 – EPIRB control functions

Control position		EPIRB condition		EPIRB-mount or release mechanism status		Transmitter status	
ON	READY	WET*	DRY	OUT	IN	ON	OFF
X		X		X		X	
X		X			X	X	
X			X	X		X	
X			X		X	X	
	X	X		X		X	
	X	X			X		X
	X		X	X			X
	X		X		X		X

* Floating or immersed in water

- f) (A.694(17)/1.2) *Where a unit of equipment provides a facility which is additional to the minimum requirements of this standard, such as an EPFE (Electronic Position-Fixing Equipment) or the possibility of connecting external data, the operation, and as far as is reasonably practicable, the malfunction of such additional facility shall not degrade the performance of the equipment below those minimum standards. The additional facility shall, as a minimum, meet the appropriate requirements of IEC 60945, as applicable. Where such an additional facility exists, it shall not prevent the satellite EPIRB fully conforming to the requirements of this standard during normal combined operation.*
- g) The satellite EPIRB shall be a single integral unit. No part of it shall be detachable without the use of tools.

3.3 Operational

3.3.1 Prevention of inadvertent activation

The satellite EPIRB shall:

- a) (A.810(19)/A.2.3.1) be fitted with adequate means to prevent inadvertent activation and deactivation;
- b) not automatically activate when water washes over it while in its release mechanism. See table 1;
- c) be designed to limit any inadvertent continuous 406 MHz transmission to a maximum of 45 s.

3.3.2 Immersion, buoyancy and drop into water

The satellite EPIRB shall:

- a) (A.810(19)/A.2.3.2) *be so designed that the electrical portions are watertight at a depth of 10 m for at least 5 min. Consideration shall be given to a temperature variation of 45 °C during transitions from the mounted position to immersion. The harmful effects of a marine environment, condensation and water leakage shall not affect the performance of the beacon;*
- b) (A.810(19)/A.2.3.6) *be capable of floating upright in calm water and have positive stability and sufficient buoyancy in all sea conditions;*
- c) (A.810(19)/A.2.3.7) *be capable of being dropped into the water without damage from a height of 20 m.*

3.3.3 Activation

- a) The satellite EPIRB shall (A.810(19)/A.2.3.3) *be automatically activated after floating free or when floating in the water, irrespective of the settings of any control. See table 1.*
- b) The satellite EPIRB shall (A.810(19)/A.2.3.4) *be capable of repetitive manual activation and manual deactivation.*

Manual deactivation shall not prevent automatic activation of the satellite EPIRB when automatically released from its release mechanism or when floating in the water.

- c) The satellite EPIRB shall (A.810(19)/A.2.3.11) *be provided with a low-duty cycle light (of at least effective 0,75 cd) active during darkness or operating continually, and flashing at a rate of 20 to 30 times per minute, with a flash duration of between 10^{-6} s and 10^{-2} s to indicate its position for the nearby survivors and rescue units.*

The light shall be mounted so that it is visible over as great a portion of the upper hemisphere as is practical.

- d) When the satellite EPIRB is manually activated, the low-duty cycle light (see 3.3.3 c)) shall begin flashing within 2 s, in any lighting condition, and no distress signal shall be emitted until at least 47 s and at most 5 min after the satellite EPIRB has been manually activated.
- e) After start of transmission of the distress signal, the operation of low-duty cycle light should be in accordance with 3.3.3 c).
- f) The satellite EPIRB shall (A.810(19)/A.2.3.5) *be provided with means to indicate that signals are being emitted.* If a low-duty cycle light operating in accordance with 3.3.3 c), is not active during daylight, alternative indication during this time shall be provided.
- g) The satellite EPIRB shall (A.810(19)/A.2.3.14) *be provided with a 121,5 MHz beacon primarily for homing by aircraft.*

3.3.4 Self-test

The satellite EPIRB shall (A.810(19)/A.2.3.8) *be capable of being tested, without using the satellite system, to determine that the satellite EPIRB is capable of operating properly.*

When the self-test mode (C/S T.001) is activated, the satellite EPIRB shall emit a single burst which shall always provide the beacon 15 Hex ID. The frame synchronization pattern shall be "011010000" (i.e. the last eight bits are complemented so that this test burst will not be processed by the satellite equipment and the burst duration shall be 440 ms or 520 ms).

For location protocol beacons, the content of the encoded position data field of the self-test message should be the default values specified in (C/S T.001). Successful completion of the test shall be indicated. Activation of the test facility shall reset automatically. Any transmission in the self-test mode shall be limited to one burst. If the 121,5 MHz auxiliary radio-locating device signal is transmitted during the self-test, it should not exceed 3 audio sweeps or 1 second, whichever is greater.

3.3.5 Colour and retro-reflecting material

The satellite EPIRB shall (A.810(19)/A.2.3.9) *be of highly visible yellow/orange colour and be fitted with retro-reflecting material.*

A band of retro-reflective material, at least 25 mm wide, encircling that part of the satellite EPIRB's body which is normally protruding above the water-line, shall be acceptable.

The retro-reflective material shall also meet the performance requirements of IMO Resolution A.658(16) annex 2.

3.3.6 Lanyard

The satellite EPIRB shall (A.810(19)/A.2.3.10) *be equipped with a buoyant lanyard*, firmly attached to it, suitable for use as a tether for survivors or from a survival craft in the water. It shall *be so arranged as to prevent its being trapped in the ship's structure when floating free.*

The buoyant lanyard shall have a length of 5 m to 8 m. The breaking strength of the lanyard and its attachment to the satellite EPIRB shall be at least five times the weight of the satellite EPIRB.

3.3.7 Exposure to the marine environment

The satellite EPIRB shall *not* (A.810(19)/A.2.3.12), including the labelling, *be unduly affected by sea water or oil or both; and (A.810(19)/A.2.3.13) be resistant to deterioration in prolonged exposure to sunlight.*

3.3.8 Ergonomics

The satellite EPIRB shall have all controls of sufficient size for simple and satisfactory operation and also be capable of being operated by a person wearing an immersion suit as defined in the IMO Lifesaving Appliance Code (Resolution MSC.48(66)), section 2.3.

3.3.9 Indication of previous activation

The satellite EPIRB shall be provided with means to indicate that the satellite EPIRB has been previously activated, to advise the users of a possible reduction of the required battery capacity. These means shall not be capable of reset by the user.

For example, manual activation of the satellite EPIRB shall require the breaking of a seal, which shall not be replaceable by the user. This seal shall not be broken when using the self-test facility.

3.4 Distress function

(A.810(19)/A.3.1) *When the satellite EPIRB is manually operated a distress alert shall be initiated only by means of a dedicated distress alert activator. See table 1.*

The dedicated activator shall:

- a) (A.810(19)/A.3.2.1) *be clearly identified; and*
- b) (A.810(19)/A.3.2.2) *be protected against inadvertent operation.*

(A.810(19)/A.3.3) *Manual distress alert initiation shall require at least two independent actions neither of which on its own shall activate the satellite EPIRB.*

The following actions shall not be counted as one of the two independent actions required to activate the EPIRB

- breaking a seal provided to comply with 3.3.9;
- manual removal from the bracket; or
- inversion.

(A.810(19)/A.3.4) *The satellite EPIRB shall not be automatically activated after being manually removed from the release mechanism. (Dry EPIRB condition.)*

3.5 Float-free arrangements

3.5.1 General

The float-free arrangement shall:

- a) (A.662(16)/2.1) *be designed so that the release mechanism shall operate before reaching a water depth of 4 m in any orientation. Any hydrostatic release unit used in the float-free release mechanism shall comply with IMO Lifesaving Appliance Code (Resolution MSC.48(66)) paragraph 4.1.6.3.*
- b) (A.662(16)/2.4) *be constructed to prevent release when seas wash over the unit.*
- c) have its release mechanism fitted with adequate means to prevent its inadvertent activation. See table 1.
- d) (A.662(16)/2.3) *be constructed of non-corrosive compatible materials, so as to prevent deterioration which may cause any malfunction of the unit. Galvanizing or other forms of metallic coating on parts of the float-free release mechanism shall not be accepted.*
- e) (A.662(16)/2.5) including the labelling, *not be unduly affected by seawater or oil or prolonged exposure to sunlight.*

3.5.2 External power or data connection

(A.662(16)/3) *For the satellite EPIRB requiring external power or data connection, or both, the means of connection shall not inhibit the release from the release mechanism or activation of the satellite EPIRB.*

3.5.3 Ability to check the automatic release

(A.662(16)/4) *With the exception of single-use hydrostatic units, it shall be possible to assess the proper functioning of the automatic release mechanism by a simple method without activation of the satellite EPIRB.*

3.5.4 Manual release

(A.662(16)/5) *It shall be possible to release the satellite EPIRB manually from the float-free mechanism, without tools.*

3.6 Environment

(A.810(19)/A.2.5) *The satellite EPIRB shall be so designed as to operate under any of the following environmental conditions:*

3.6.1 Temperature and icing

- a) Ambient temperatures of $-40\text{ }^{\circ}\text{C}$ to $+55\text{ }^{\circ}\text{C}$ for class 1.
- b) Ambient temperatures of $-20\text{ }^{\circ}\text{C}$ to $+55\text{ }^{\circ}\text{C}$ for class 2.
- c) Icing.

3.6.2 Wind speed

(A.810(19)/A.2.5.3) *Relative wind speeds up to 100 knots (52 m/s).*

3.6.3 Stowage

After stowage at temperatures between –40 °C and +70 °C for class 1 and between –30 °C and +70 °C for class 2.

3.6.4 Shock and vibration

(A.810(19)/A.2.6.2) *Be capable, while mounted on board, of operating properly over the ranges of shock and vibration and other environmental conditions normally encountered above deck on sea-going vessels.*

3.7 Environment for float-free arrangement

The float-free arrangement shall:

- a) (A.662(16)/2.2) *be capable of operating throughout the temperature range of –40 °C to +65 °C for class 1 and –30 °C to +65 °C for class 2.*
- b) (A.662(16)/2.6) *be capable of operating properly after exposure to shock and vibration and other severe environmental conditions encountered above deck on seagoing vessels.*
- c) (A.662(16)/2.7) *if the ship navigates in areas where icing may be expected, be so designed as to minimize the formation of ice and prevent its effects from hindering the release of the satellite EPIRB as far as practicable.*

3.8 Interference – electromagnetic compatibility

(A.694/6.1) *All reasonable and practicable steps shall be taken to ensure electromagnetic compatibility between the equipment concerned and other radiocommunication and navigational equipment carried on board in compliance with the relevant requirements of chapters III, IV and V of the SOLAS Convention.*

Refer to the appropriate clauses of IEC 60945 for the requirements.

3.9 Maintenance

(A.702(17)/3.2) *It should be recognized that, despite the use of other methods, some reliance on shore-based maintenance to ensure the availability of the functional requirements of the GMDSS will always be necessary.*

As defined in 3.2 g), the satellite EPIRB is a single integral unit, which is not suited for on-board repairs.

As a consequence, the equipment shall be so constructed that it is readily accessible for inspection and testing purposes only.

3.10 Safety precautions

All practicable steps shall be taken to ensure that the equipment is in accordance with the appropriate clauses of IEC 60945.

In addition, the battery shall not release toxic or corrosive products outside the satellite EPIRB during or subsequent to storage at temperatures between –55 °C and +75 °C, and:

- a) during a full or partial discharge at any rate up to and including an external short circuit;

- b) during a charge or forced discharge of a cell or cells by another cell or cells within the battery;
- c) after a full or partial discharge.

The satellite EPIRB shall include measures to protect the batteries from reversal of polarity, shorting, and the effects of self-heating, cell-to-cell charging, and forced discharging.

Moreover, care shall be taken that the satellite EPIRB and specially the battery shall not be hazardous to any person handling, using or performing manufacturer approved servicing of the device or to any vehicle or equipment in which it is transported, housed or installed under any of the conditions specified in this standard.

3.11 Equipment manuals

Adequate information, as needed to comply with 3.9 and 3.13, shall be provided to enable the equipment to be properly stowed, installed, operated and tested.

The information supplied with the EPIRB should include pictorial operating instructions on a waterproof placard, suitable for mounting on a bulkhead. Numerals may be used to indicate the order of the illustrated operations, but words should not be used as part of the instructions.

The equipment manual shall also include:

- an overview of the COSPAS-SARSAT system;
- instructions for registration, registration renewal and a discussion on the importance of accurate registration;
- battery information including replacement instructions, battery type, and safety information regarding battery use and disposal;
- an instruction to replace the battery after EPIRB is operated for any purpose other than a test;
- the minimum operating life-time and operating and storage temperatures;
- the purpose of the lanyard and precaution against using it to secure EPIRB to ship;
- a recommendation against attempting to operate inside life raft or under any similar cover or canopy;
- the servicing and/or replacement of any hydrostatic release unit and any associated components subject to ageing, such as release rods;
- manufacturer recommendations, if any, on periodic functional testing, possibly in connection with battery replacement;
- a note to keep the original EPIRB packaging, since it may be needed if the EPIRB has to be shipped for servicing. UN requirements for shipping some batteries as hazardous goods require certain packaging standards and labelling;
- warranty information;
- a warning to the effect that the Satellite EPIRB shall not be operated except in an emergency;
- a warning against installation near strong magnetic fields, if that might activate the EPIRB;
- a recommendation to mounting the EPIRB as high as possible, especially on small vessels. This will help ensure operation of the hydrostatic float-free release unit, in the event the vessel capsizes without sinking;
- a recommendation to limit self-testing to the minimum necessary to ensure confidence in the operation of the EPIRB;
- for EPIRBs which emit a 121,5 MHz signal during self-test, a warning to limit testing to the first five minutes of the hour;

- if appropriate a list of approved external position fixing devices for those EPIRBs accepting external navigation inputs.

The equipment manual shall include information explaining the necessity to report satellite EPIRB false alarms by the most expedient means to the nearest search and rescue authorities. The information that should be reported includes the satellite EPIRB 15-Hex ID; date, time, duration and cause of activation; and location at time of deactivation.

3.12 Labelling

3.12.1 Equipment labelling

The label shall be placed on the satellite EPIRB itself and on its container, if any, as needed.

(A.810(19)/A.4) *In addition to the items specified in IMO Resolution A.694(17) 6.3 and 9 (see appropriate clauses of IEC 60945) on general requirements, the following shall be clearly indicated on the exterior of the equipment:*

- a) (A.810(19)/A.4.1) *Brief operating instructions* at least in English, to enable manual activation, deactivation and self-test (see 3.3.4);
- b) a warning to the effect that the satellite EPIRB shall not be operated except in an emergency;
- c) type designation and class (see clause 1, note) as specified by the manufacturer, type of battery and (A.810(19)/A.4.2) *expiry date for the primary battery used* (see 4.6). Means shall be provided to change this date when the battery is replaced;
- d) the name of the ship and beacon identification data:
 - 1) (A.810(19)/A.4.3) *the identity code programmed into the transmitter* of the satellite EPIRB (i.e. hexadecimal representation of bits 26 to 85 of the digital message, as described in C/S 1.001), together with the call sign or mmSI of the ship as required by the Administration and the MID;
 - 2) country (i.e. name of country as programmed in the MID).

3.12.2 Float-free arrangement labelling

(A.662(16)/2.9) *The float-free arrangement shall carry a label or labels indicating clearly at least in English:*

- a) *the operating instructions for manual release;*
- b) the type designation;
- c) the satellite EPIRB class;
- d) the maintenance and/or replacement date for the release mechanism, if applicable.

If this label or labels are not readily visible in the installed arrangement, they shall be provided in addition, for installation close to the float-free arrangement. These instructions may in addition be shown in pictorial form.

3.13 Installation

The equipment manual shall contain instructions to ensure that *the installed satellite EPIRB* shall:

- a) (IV/7.1.6.2) *be installed in an easily accessible position.*
- b) (A.694(17)/2) *be installed in such a manner that it is capable of meeting the requirements of this standard.*
- c) (A.810(19)/A.2.6.1) *have local manual activation; remote activation may also be provided from the navigating bridge, while the device is installed in the float-free mounting.*

- d) (A.810(19)/A.2.6.3) *release itself and float-free before reaching a water depth of 4 m at a list or trim of any angle.*
- e) (A.662(16)/2.8) *be mounted in such a way that, after being released, it is not obstructed by the structure of the sinking ship.*

4 Technical characteristics

4.1 Transmitted frequency

The satellite EPIRB distress alerting signal shall be transmitted on a frequency in the 406 MHz band as specified in C/S T.001.

4.2 Signal and message format

(A.810(19)/B.1) *The technical characteristics of the transmitted signal and the message format shall be in accordance with the requirements of the COSPAS-SARSAT System document C/S T.001.*

4.3 Distress message memory

(A.810(19)/B.2) *Provisions shall be included for storing the fixed portion of the distress message in the satellite EPIRB using non-volatile memory.*

4.4 Beacon identification code

(A.810(19)/B.3) *A unique beacon identification code shall be made part of all messages.*

This identification code shall include a 3-digit code for the country in which the beacon is registered, followed by either:

- a) *the trailing 6 digits of the ship station identity in accordance ITU-R Recommendation M.585 as amended or*
- b) *a unique serial number; or*
- c) *a radio call sign.*

Preference is given to method a).

4.5 121,5 MHz homing signal

(A.810(19)/B.4) *The 121,5 MHz homing signal shall:*

- a) *have a continuous duty cycle except that it may be interrupted for up to a maximum of 2 s during the transmission of the 406 MHz signal;*
- b) *with the exception of the sweep direction, meet the technical characteristics from ITU-R Recommendation M.690-1. The sweep may either be upward or downward.*

4.6 Power source

4.6.1 General

(A.810(19)/A.2.4) *The battery shall have sufficient capacity to operate the satellite EPIRB for an uninterrupted period of at least 48 h, under the extreme operating temperature conditions corresponding to the class of the satellite EPIRB.*

The satellite EPIRB shall be designed so that the electronic and electrical components are not damaged in the event of a leaking battery.

4.6.2 Battery life and expiry date

The life of the battery as defined by its expiry date shall be at least three years.

The expiry date of the battery shall be the battery manufacturing date plus no more than half the useful life of the battery.

The useful life of the battery is defined as the period of time after the date of battery manufacture that the battery will continue to meet the input power requirements of the satellite EPIRB.

To define the useful life of the battery, the following losses at the temperature of $+20\text{ }^{\circ}\text{C} \pm 5\text{ }^{\circ}\text{C}$ shall be included:

- a) self-testing, as recommended by the manufacturer or as required by the Administration, whichever is more demanding;
- b) self-discharge of the battery;
- c) stand-by loads.

4.6.3 Expiry date indication

The satellite EPIRB shall be clearly and durably marked with the battery expiry date (see 3.12.1 c)).

4.6.4 Reverse polarity protection

It shall not be possible to connect the battery with the polarity reversed.

4.7 Antenna characteristics (C/S T.001)

The antenna shall have the following characteristics.

- *Elevation:* 5° to 60°
- *Pattern:* hemispherical
- *Polarization:* circular (RHCP) or linear
- *Gain (vertical plane):* between -3 dBi and 4 dBi over 90 % of the above region
- *Gain variation (azimuth plane):* $<3\text{ dB}$

5 Methods of testing and required test results

5.1 General

5.1.1 COSPAS-SARSAT type approval

The requirements of this clause are in addition to the COSPAS-SARSAT requirements for type approval, as per COSPAS-SARSAT documents C/S T.001 and T.007, as amended. Tests shall be normally carried out at test sites accepted by the type approval authority. The manufacturer shall, unless otherwise agreed, set up the equipment and ensure it is operating normally before testing commences. If the test site accepted by the type approval authority is also an accepted COSPAS-SARSAT test facility, both series of tests may be combined.

The COSPAS-SARSAT tests consist of the following:

- a) electrical and functional tests at constant temperatures (minimum, normal test conditions and maximum);
- b) thermal shock test;

- c) operating lifetime at minimum temperatures;
- d) frequency stability test with temperature gradient;
- e) satellite qualitative tests;
- f) antenna tests;
- g) beacon coding software;
- h) navigation system.

(See annex B for details.)

5.1.2 Power supply

Electrical power shall be supplied during performance tests normally by the batteries which form a part of the equipment. For type-approval tests, a minimum of three sets of batteries shall be submitted.

5.1.3 Warm-up period

The requirements of this standard shall be met (C/S T.004) after a maximum warm-up period of 15 min.

5.1.4 Instructions

Adequate information shall be provided to enable the equipment to be properly set up, maintained and operated during the type testing.

5.1.5 Additional facilities

(See 3.2 f))

If the equipment contains any additional facilities such as an EPFE (Electronic Position Fixing Equipment) or the possibility of connecting external data, they shall be operational for the duration of all tests, except if specified otherwise.

5.1.6 Audible and visual indications

During testing, all audible and visual indications including the low-duty cycle light shall be operational.

5.1.7 Preparation of satellite EPIRB for type-approval testing

For the purpose of performance testing, the satellite EPIRB shall be specially programmed to transmit data bursts encoded using (C/S T.007) the test protocol of appropriate type and format, when the satellite EPIRB is activated:

Evidence of compliance with all the requirements of this subclause shall be submitted by the manufacturer before testing commences.

(C/S T.007- 4.3 test units) The satellite EPIRB shall be configured so that the antenna port can be connected to the test equipment by a coaxial cable terminated by a 50 Ω load. The configuration of the antenna port can be prepared by the manufacturer before the first test or before test of the list of tests A.1.14 given in annex A. All tests up to A.1.14, except test A.1.10 shall be performed with the antenna in place. (See annex A for the required sequence of tests.) Test A.1.10 is to be performed with the beacon operating into 50 Ω load.

All homing devices shall be prepared for test transmission as required by the national authority. Care shall be taken not to transmit distress signals on distress and safety frequencies, for example, by frequency offset.

5.1.8 Test conditions

Tests shall be carried out under normal test conditions, unless otherwise stated.

5.1.8.1 Normal test conditions

Normal temperature and humidity conditions for tests shall be any convenient combination of temperature and humidity within the following ranges:

Temperature:	+15 °C to +35 °C
Relative humidity:	20 % to 75 %

5.1.8.2 Extreme test conditions

For tests at extreme temperatures, measurements shall be made in accordance with the procedure specified in IEC 60945.

Applicable temperature ranges:

For class 1:	–40 °C to +55 °C
For class 2:	–20 °C to +55 °C

5.1.9 Test sequence

All tests shall be performed on a single equipment, configured as indicated in 5.1.7. The tests shall be carried out in the order defined in annex A of this standard. Alternatively, one equipment configured as indicated in 5.1.7 may be used for tests A.1.1 to A.1.14 of annex A and another or other ones for tests A.2.1 to A.2.6.

5.1.10 Performance check

For the purpose of this standard, a performance check consists in activating the satellite EPIRB (see 5.1.7) and checking the integrity of the complete digital message within 15 min, as defined in 4.2.

5.2 General tests

(See 3.2)

The requirements of clause 3.2 a) shall be verified by inspection.

The requirements of clause 3.2 b) are considered verified by successful completion of the COSPAS-SARSAT type approval tests specified in annex B.

The requirements of clause 3.2 c) are considered verified by successful completion of all tests in annex A.

5.2.1 Tests for float-free arrangements

(See 3.2 d) and 3.2 e))

The satellite EPIRB installed in the automatic release mechanism shall be submerged in water, at normal temperature for all tests. The water temperature shall be noted. The following tests may be performed in any sequence.

The test at normal temperature shall be performed six times with the equipment rotated each time as follows:

- normal mounting position (as defined in the equipment manual, see 3.11);
- rolling 90° to starboard;
- rolling 90° to port;
- pitching 90° bow down;
- pitching 90° stern down;
- upside-down position.

The satellite EPIRB shall be automatically released and float-free of the mounting before reaching, at any orientation, a depth of 4 m or, at a water pressure equivalent to that depth, namely 40 kPa.

The test at the extreme temperatures shall be performed in the normal mounting position(s) only, as defined in the equipment manuals.

NOTE Where the tests required at extreme temperatures cannot be carried out within the environmental chamber, other methods may be used which approximate the required conditions.

(See 3.6.1 a)) Any climatic control devices provided in the equipment may be switched on before or during the test.

The inspection test as described in 5.13 shall be effected after each release from the satellite EPIRB from its float-free mechanism.

The performance check as described in 5.1.10 shall be carried out after each series of releases and at each specified temperature.

5.3 Operational tests

The requirements of clause 3.3 shall be verified as follows.

5.3.1 Prevention of inadvertent activation

- a) (3.3.1 a)) By inspection
- b) (3.3.1 b)) Tests are included in 5.5.1.1
- c) (3.3.1 c)) By inspection

5.3.2 Immersion, buoyancy and drop into water

5.3.2.1 Immersion test

(See 3.3.2 a))

The test is included in 5.13.4 and 5.13.8.

5.3.2.2 Buoyancy test

(See 3.3.2 b))

With the antenna deployed in its normal operating position, the satellite EPIRB shall, when rotated to a horizontal position about any axis, be submerged in fresh water just below the surface, and when released pass through an upright position within 2 s.

NOTE Fresh water is defined as normal domestic tap water.

In calm fresh water, the satellite EPIRB shall float upright with the base of the antenna a minimum of 40 mm above the water-line.

The reserve buoyancy of the satellite EPIRB shall be at least 5 % when determined by one of the following methods:

- a) the complete unit shall be submerged and the buoyant force shall be measured with a scale. The buoyant force shall be divided by the weight of the unit. The result shall be at least 1,05;
- b) the location of the water-line shall be determined on the floating satellite EPIRB. The calculated or measured volume of the unit above the water-level shall be divided by the calculated or measured volume below the water-level. The result shall be at least 1,05.

5.3.2.3 Drop test

(See 3.3.2 c))

The test is included in 5.13.5.

5.3.3 Activation

5.3.3.1 Test for salt water activation

(See 3.3.3 a))

The satellite EPIRB shall be floated in a 0,1 % salt solution and shall activate irrespective of the settings of any control. The test will be repeated for any combination of settings of controls.

The salt used for the test shall be sodium chloride (NaCl) containing, when dry, not more than 0,1 % sodium iodide and 0,03 % total impurities.

The salt solution concentration shall be $(0,1 \pm 0,01)$ % by weight.

The solution shall be prepared by dissolving $(1 \pm 0,1)$ parts by weight of salt in 1 000 parts by weight of distilled or demineralized water.

This test may be combined with the test in 5.2.1.

5.3.3.2 Test for repetitive manual activation and deactivation

(See 3.3.3 b))

By inspection.

5.3.3.3 Test of low-duty cycle light

(See 3.3.3 c))

The effective luminous intensity and flash rate shall be checked at the normal temperature and at the extreme temperatures. The effective luminous intensity shall be defined by the following formula as indicated in IMO Resolution A.689(17) – Testing of life-saving appliances, 10.2.2:

$$\frac{\int_{t_1}^{t_2} i \cdot dt}{0,2 + (t_2 - t_1)}$$

where

i is the instantaneous intensity;

0,2 is the Blondel-Rey constant;

$t_2 - t_1$ are the time limits of integration in seconds.

The effective luminous intensity shall be at least 0,75 cd. The flash rate shall be 20 to 30 times per minute.

NOTE Where the tests required at extreme temperature cannot be carried out within the environmental chamber, other methods may be used which approximate the required conditions.

5.3.3.4 Tests for subclauses 3.3.3 d) to 3.3.3 g)

By inspection.

5.3.4 Self-test

(See 3.3.4)

The self-test mode of the satellite EPIRB shall be activated. The digital message generated shall be in accordance with the requirements of 3.3.4 (self-test *frame synchronization*).

The automatic reset of the test facility and the indication of the self-test mode shall be checked by inspection.

5.3.5 Colour and retro-reflecting material

(See 3.3.5)

By inspection of the fitting and of evidence of compliance with IMO Resolution A.658(16) for the performance requirements of the retro-reflecting material.

5.3.6 Lanyard

(See 3.3.6)

By inspection of evidence submitted by the manufacturer that the lanyard meets the specified requirements.

5.3.7 Exposure to marine environment

(See 3.3.7)

By inspection of the evidence submitted by the manufacturer that the materials used, including any coloured external coating, are unlikely to be affected adversely by seawater or oil or prolonged exposure to sunlight.

5.3.8 Ergonomics

(See 3.3.8)

By inspection.

5.3.9 Indication of previous activation

(See 3.3.9)

By inspection of the evidence submitted by the manufacturer and of the satellite EPIRB.

5.4 Distress function

(See 3.4)

The requirements of clause 3.4 shall be verified as follows

By inspection and by checking that the items listed in 3.4 as those items not counted as one of the two independent actions required to activate the EPIRB, do not cause activation on their own and that two independent actions are required to activate the EPIRB.

If appropriate remove the EPIRB from the bracket and ensure that it is not activated by this action.

5.5 Float-free arrangements

(See 3.5)

5.5.1 General

The requirements of 3.5.1 a) shall be verified during 5.2.1.

5.5.1.1 Test to prevent release when sea water washes over the unit

(See 3.5.1 b), 3.5.1 c) and 3.3.1 b))

The unit consisting of the satellite EPIRB and its release mechanism installed in its bracket, if any, shall be mounted, on a suitable test fixture, successively in each method intended for mounting on a ship, as described in the equipment manual. A stream from a hose shall be directed at the unit for a period of 5 min. The nozzle of the hose shall have a nominal diameter of 63,5 mm and a water-delivery rate of approximately 2 300 l of water per minute. The end of the nozzle shall be 3,50 m away from the satellite EPIRB and 1,50 m above the base of the antenna. The nozzle or the unit shall be moved during the test, so that water strikes the satellite EPIRB in an arc of at least 180° perpendicular to the normal mounting position of the unit.

The satellite EPIRB shall not release from its bracket nor shall it automatically activate as a result of the water from the hose stream.

5.5.1.2 Construction materials

(See 3.5.1 d) and 3.5.1 e))

By inspection of the evidence submitted by the manufacturer that the materials used, including any coloured external coating, are unlikely to cause any malfunction of the unit.

By inspection, including the labelling, of evidence submitted by the manufacturer that the materials used are unlikely to be duly affected by seawater or oil or prolonged exposure to sunlight.

5.5.2 External power or data connection

(See 3.5.2)

By inspection during 5.2.1.

5.5.3 Ability to check the automatic release

(See 3.5.3)

By inspection.

5.5.4 Manual release

(See 3.5.4)

By inspection.

5.6 Environment

(See 3.6)

5.6.1 Icing

If the manufacturer declares conformance with 3.6.1c) and 3.7c) by successful completion of 5.2.1 at the extreme temperature, and by inspection of the equipment manual to confirm fitting of heaters, or suitable alternatives, to the float-free arrangement.

5.6.2 Wind speed

By inspection of the evidence submitted by the manufacturer, and by successful completion of 5.5.1.1.

5.7 Maintenance

(See 3.9)

By inspection of the equipment manuals (see 5.9).

5.8 Safety precautions

(See 3.10)

By inspection of the evidence submitted by the manufacturer that the satellite EPIRB and the battery shall function safely under the conditions stated in 3.10.

5.9 Equipment manuals

(See 3.11)

By inspection.

5.10 Labelling

5.10.1 Equipment labelling

(See 3.12.1)

By inspection.

5.10.2 Float-free arrangement labelling

(See 3.12.2)

By inspection.

5.11 Installation

(See 3.13)

By inspection of the equipment manuals and, if provided, by activation of the satellite EPIRB from the remote system, set up according to manufacturer's instructions.

5.12 Power source

(See 4.6)

5.12.1 Battery capacity and low-temperature test

Using a fresh battery pack, the satellite EPIRB shall be activated (at the ambient temperature) for a period of time as stated by the manufacturer to be equivalent to the loss of battery capacity due to self-testing, stand-by loads as well as battery-pack self-discharge during the useful life of the battery pack (as defined in 4.6.2). The manufacturer shall substantiate the method used to determine this time.

The satellite EPIRB shall be placed in a chamber of normal room temperature. Then the temperature shall be reduced to and maintained at $-40\text{ °C} \pm 3\text{ °C}$ for class 1 or $-30\text{ °C} \pm 3\text{ °C}$ for class 2 equipment for a period of 10 h or some such period as may be determined by the type approval authority.

Any climatic control device provided in the equipment may be switched on and for class 2 equipment the chamber heated to $-20\text{ °C} \pm 3\text{ °C}$, at the conclusion of the period specified in the subclause above. The action of the climatic control device and for class 2 equipment, the heating of the chamber shall be completed within 20 min.

The equipment shall be activated 30 min after the end of the period specified in the subclause above and shall then be kept working continuously for a period of 48 h. The temperature of the chamber shall be maintained as specified in the clause above for the whole of the period of 48 h.

The equipment shall be subjected to the test as specified in C/S T.007, annex A, A.2.3 (Operating lifetime at minimum temperature) at intervals of not more than 6 h and at the end of the period of 48 h.

The satellite EPIRB shall meet the requirements of C/S T.007, annex A, A.2.3 (-40 °C for class 1 and -20 °C for class 2) for 48 h.

This test may be combined with the test as described in C/S T.007, annex A, A.2.3 (see annex A.1.14).

5.12.2 Expiry date indication

By inspection.

5.12.3 Reverse polarity protection

By inspection.

5.13 Environment

Environmental tests are intended to assess the suitability of the construction of the equipment for its intended physical conditions of use.

After each environmental test, the equipment shall be inspected for any mechanical deterioration and/or for water penetration.

Before commencing the first environmental test and after each environmental test, a performance check shall be made (see 5.1.10).

The following tests shall be made under environmental conditions as detailed in IEC 60945. All these tests, except 5.13.5, Drop test into water, shall be performed with the satellite EPIRB installed in the release mechanism.

5.13.1 Dry heat cycle, of IEC 60945

(See 3.6.1, 3.6.3 and 3.7 a))

The performance check shall be replaced by the test required by C/S T.007, annex A, A.2.1 (Electrical and functional tests at constant temperature).

5.13.2 Damp heat cycle, of IEC 60945

(See 3.6.1, 3.6.3 and 3.7 a))

5.13.3 Low-temperature cycle

This test is covered by successful completion of the test in 5.12.

5.13.4 Thermal shock test, of IEC 60945

(See 3.3.2 a))

NOTE This test is different to the thermal shock test required by C/S T.007, annex A, A.2.2, *Thermal shock test*.

Subject to a satisfactory performance check, the opening of the satellite EPIRB to check for water ingress may be delayed until the completion of all tests.

5.13.5 Drop test into water, of IEC 60945

(See 3.3.2 c))

The three drops shall be initiated from a different orientation, namely antenna vertically up, antenna vertically down and antenna horizontal.

Subject to a satisfactory performance check, the opening of the satellite EPIRB to check for water ingress may be delayed until the completion of all tests.

5.13.6 Vibration test, of IEC 60945

(See 3.6.4, 3.7 b))

The performance check as in IEC 60945 shall be carried out at the completion of the vibration test.

5.13.7 Ruggedness test

(See 3.6.4, 3.7 b))

The ruggedness test is conducted to give a measure of confidence that the equipment will meet service conditions. The satellite EPIRB shall be secured to the testing equipment through its normal attachments or mounting intended for use in service conditions and mounted in the normal operating position(s). Additional straps or other holding means shall not be used.

The satellite EPIRB shall be subjected to the ruggedness test according to the following profile:

Peak acceleration:	98 m/s ² ± 10 %
Pulse duration:	16 ms or 20 ms ± 10 %
Wave shape:	Half-cycle sinewave
Test axis:	Vertical
Number of bumps:	4 000

5.13.8 Immersion test, of IEC 60945

(See 3.3.2 a))

Subject to a satisfactory performance check, the opening of the satellite EPIRB to check for water ingress may be delayed until the completion of all tests.

If the satellite EPIRB is equipped with a battery compartment, which allows for user's replacement of the battery, the test shall be repeated with the battery compartment open to ensure that there is no water ingress.

Alternatively, tests may be carried out at a water pressure equivalent to a depth of 10 m, or 100 kPa.

This test may be combined with the test in 5.13.4.

5.13.9 Corrosion test, of IEC 60945

(See 3.3.7 and 3.5.1 d))

5.14 Interference testing

(See 3.8)

All these tests shall be performed with the satellite EPIRB installed in the release mechanism.

5.15 Spurious emissions

The measurement shall be performed only between bursts.

The measurements shall be made at the transmitter output at 50 Ω using a receiver or a spectrum analyzer with its bandwidth set to 120 kHz or its nearest setting, over the following frequency bands:

156 MHz to 174 MHz, 1 525 MHz to 1 545 MHz

No signal level within these bands shall exceed 25 μ W.

This test may be combined with the test required by C/S T.007, annex A, A.3.2.2.4 (annex A.1.14).

5.16 Compass safe distance

The test will be in accordance with IEC 60945 with the satellite EPIRB not activated.

5.17 Conducted interference

If there is a connection between the ship's power system and the satellite EPIRB or its release mechanism, the equipment shall, in addition, be tested to the appropriate clauses of IEC 60945.

Annex A (normative)

Sequence of tests

The following environmental and operational tests shall be conducted in the sequence as stated here below. All tests shall be performed on a single unit as defined in 5.1.7.

Alternatively, all tests numbered A.1.1 to A.1.14 shall be performed on the unit defined in 5.1.7 and all tests numbered A.2.1 to A.2.6 shall be performed on one or more other unit(s) as defined in 5.1.9. These tests numbered A.2.1 to A.2.6 may be carried out independently in any sequence.

Tests marked "x" may be performed in the indicated sequence or moved in the sequence and combined with the related COSPAS-SARSAT tests (A.1.14).

A performance check (see 5.1.10) shall be performed before the first test and during or after each test.

A.1 Compulsory sequence of tests

- A.1.1 Message format and homing devices (see 5.1.7)
- x A.1.2 Dry heat test (see 5.13.1 of this standard and IEC 60945)
- A.1.3 Damp heat test (see 5.13.2 of this standard and IEC 60945)
- A.1.4 Vibration test (see 5.13.6 of this standard and IEC 60945)
- A.1.5 Ruggedness test (see 5.13.7)
- A.1.6 Corrosion test (see 5.13.9 of this standard and IEC 60945)
- A.1.7 Drop test into water (see IEC 60945 as modified in this standard, 5.13.5)
- A.1.8 Thermal shock test (see 5.13.4 of this standard and IEC 60945)
- A.1.9 Immersion test (see 5.13.8 of this standard and IEC 60945)
- x A.1.10 Spurious emission (see 5.15)
- A.1.11 Conducted interference test (if applicable) (see 5.17 of this standard and IEC 60945)
- A.1.12 Signal light test (see 5.3.3.3)
- A.1.13 Battery capacity and low-temperature test (see 5.12.1)
- A.1.14 COSPAS-SARSAT type-approval test procedure

A.2 Additional tests

A.2.1 Test of operational requirements

Subclauses of this part:

5.3.1, 5.3.3.2, 5.3.3.4, 5.3.4, 5.3.5, 5.3.6, 5.3.7, 5.3.8, 5.4, 5.5.1.1, 5.5.1.2, 5.5.2, 5.5.3, 5.5.4, 5.12.2, 5.12.3

A.2.2 Automatic release mechanism and automatic activation test for class 1 and class 2 satellite EPIRB's (5.2.1).

This test may be combined with the test required in 5.13.4.

A.2.3 Stability and buoyancy test (see 5.3.2.2).

A.2.4 Float-free activation test (see 5.3.3.1).

A.2.5 Safety (see 5.8 of this standard and IEC 60945).

A.2.6 Compass safe-distance test (see 5.16 of this standard and IEC 60945).

IECNORM.COM: Click to view the full PDF of IEC 61097-2:2002

Withd2W

Annex B

(normative)

List of COSPAS-SARSAT tests

(as defined in COSPAS-SARSAT document C/S T.007, as amended)

This standard calls up all the requirements of COSPAS-SARSAT type-approval tests without modification

The list of measurements indicated hereunder is given for reference only. The latest issue of C/S T.007 shall be used.

The COSPAS SARSAT type approval is a requirement of this standard (see 3.1 and 5.1.1).

Parameters to be measured during tests

B.1 Power output

- Transmitter power output
- Power output rise time
- Power output 1 ms before burst

B.2 Digital message

- Bit synchronization
- Frame synchronization
- Format flag
- Protocol flag
- Identification / position data
- BCH code
- Emergency code/national use/supplementary data
- Additional data/BCH (if applicable)
- Position error (if applicable)

B.3 Digital message generator

- Repetition rate
- Bit rate
- Total transmission time
- Unmodulated carrier
- First burst delay

B.4 Modulation

- Biphase-L
- Rise time
- Fall time
- Phase deviation: positive
- Phase deviation: negative
- Symmetry measurement

B.5 406 MHz transmitted frequency

- Nominal value
- Short-term stability
- Medium-term stability:
 - slope
 - residual frequency variation

B.6 Spurious emissions (into 50 Ω)

- in-band (406,0 MHz to 406,1 MHz)

B.7 406 MHz VSWR check

After open circuit, short circuit, then while VSWR is 3:1, measure:

- Nominal transmitted frequency

Modulation:

- Rise time
- Fall time
- Phase deviation: positive
- Phase deviation: negative
- Symmetry measurement
- Digital message

B.8 Self-test mode

- Frame synchronization
- Format flag
- Single radiated burst
- Default position data (if applicable)
- Description provided
- Design data provided on protection from repetitive self-test mode transmissions
- Single burst verification
- Provides for beacon 15 Hex ID

B.9 Thermal shock (30 °C change)

- Soak temperature
- Measurement temperature

The following parameters are to be met within 15 min of beacon turn-on and maintained for 2 h:

- Transmitted frequency
- Nominal value
- Short-term stability

- Medium-term stability:
 - slope
 - residual frequency variation
- Transmitter power output
- Digital message

B.10 Operating lifetime at minimum temperature

- Duration
- Transmitted frequency
- Nominal value
- Short-term stability
- Medium-term stability:
 - slope
 - residual frequency variation
- Transmitter power output
- Digital message

B.11 Temperature gradient (5 °C/h)

- Transmitted frequency
- Nominal value
- Short-term stability
- Medium-term stability:
 - slope
 - residual frequency variation
- Transmitter power output
- Digital message

B.12 Long-term frequency stability

B.13 Protection against continuous transmission

B.14 Satellite qualitative tests

B.15 Antenna characteristics

- Polarization
- ERP_{max} EOL
- ERP_{min} EOL
- Azimuth gain variation at 40° elevation angle

B.16 Beacon coding software

- Sample message provided for each coding option of the applicable coding protocol types
- Sample messages provided, if applicable, with encoded positions at least 5 km apart for each applicable coding protocol type
- Sample self-test message provided for each coding option of the applicable coding protocol types

B.17 Navigation system

- Position data default values
- Position acquisition time
- Encoded position data update interval
- Position data input update interval (as applicable)
- Delta offset:
 - positive direction
 - negative direction
 - over-range to 2 times coarse resolution
- Last valid position:
 - retained after navigation input lost
 - cleared when beacon reactivated
- Design data provided on protection against beacon degradation due to navigation device, interface or signal failure or malfunction

Annex C

(normative)

Standard for a manually activated satellite EPIRB without a float-free mechanism

C.1 Requirements

A non-float-free satellite EPIRB shall meet all the requirements of this standard with the exception of the following subclauses and replacement text:

3.2d), 3.2e)

3.3.3a), The satellite EPIRB shall be designed to activate when manually released from its mounting bracket and floating in the water. Table 1 shows the correct combination of control functions to prevent or enable activation.

3.5.1, 3.5.2, 3.5.3, 3.5.4

3.7, 3.12.2, 3.13c), 3.13d), 3.13e)