

INTERNATIONAL STANDARD

**Multicore and symmetrical pair/quad cables for digital communications –
Part 11: Symmetrical single pair cables with transmission characteristics
up to 600 MHz – Horizontal floor wiring – Sectional specification**

IECNORM.COM : Click to view the full PDF of IEC 61156-11:2019



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2019 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IECNORM.COM : Click to view the full text of IEC 60456-11:2019

INTERNATIONAL STANDARD

**Multicore and symmetrical pair/quad cables for digital communications –
Part 11: Symmetrical single pair cables with transmission characteristics
up to 600 MHz – Horizontal floor wiring – Sectional specification**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.20

ISBN 978-2-8322-6678-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	8
4 Installation considerations	8
4.1 General remarks	8
4.2 Bending radius of installed cable.....	8
4.3 Climatic conditions.....	8
5 Materials and cable construction	8
5.1 General remarks	8
5.2 Cable construction	9
5.3 Conductor	9
5.4 Insulation	9
5.5 Cable element.....	9
5.6 Screening of the cable element.....	9
5.7 Cable make-up.....	9
5.8 Screening of the cable core	9
5.9 Sheath	9
5.10 Identification	10
5.11 Finished cable	10
6 Characteristics and requirements	10
6.1 General remarks	10
6.2 Electrical characteristics and tests	10
6.2.1 Conductor resistance.....	10
6.2.2 Resistance unbalance.....	10
6.2.3 Dielectric strength.....	11
6.2.4 Insulation resistance.....	11
6.2.5 Mutual capacitance.....	11
6.2.6 Capacitance unbalance	11
6.2.7 Transfer impedance.....	11
6.2.8 Coupling attenuation.....	11
6.2.9 Current-carrying capacity.....	12
6.3 Transmission characteristics.....	12
6.3.1 Velocity of propagation (phase velocity).....	12
6.3.2 Phase delay and differential delay (delay skew).....	12
6.3.3 Attenuation (α).....	12
6.3.4 Unbalance attenuation (<i>TCL</i> and <i>EL TCL</i>).....	13
6.3.5 Alien (exogenous) near-end crosstalk (<i>PS ANEXT</i>)	13
6.3.6 Alien (exogenous) far-end crosstalk (<i>PS AACR-F</i>).....	14
6.3.7 Alien (exogenous) crosstalk of bundled cables	14
6.3.8 Impedance.....	14
6.3.9 Return loss (<i>RL</i>).....	14
6.4 Mechanical and dimensional characteristics and requirements.....	15
6.4.1 Dimensional requirements	15
6.4.2 Elongation at break of the conductor.....	15
6.4.3 Tensile strength of the insulation	15

6.4.4	Elongation at break of the insulation	15
6.4.5	Adhesion of the insulation to the conductor.....	15
6.4.6	Elongation at break of the sheath	15
6.4.7	Tensile strength of the sheath.....	15
6.4.8	Crush test of the cable.....	15
6.4.9	Impact test of the cable	15
6.4.10	Bending under tension	16
6.4.11	Repeated bending of the cable	16
6.4.12	Tensile performance of the cable.....	16
6.4.13	Shock-test requirements of the cable	16
6.4.14	Bump-test requirements of the cable	16
6.4.15	Vibration-test requirements of a cable	16
6.5	Environmental characteristics	16
6.5.1	Shrinkage of the insulation	16
6.5.2	Wrapping test of the insulation after thermal ageing	16
6.5.3	Bending test of insulation at low temperature.....	16
6.5.4	Elongation at break of the sheath after ageing.....	16
6.5.5	Tensile strength of the sheath after ageing	16
6.5.6	Sheath pressure test at high temperature	16
6.5.7	Cold bend test of the cable	17
6.5.8	Heat shock test.....	17
6.5.9	Damp heat steady state	17
6.5.10	Solar radiation	17
6.5.11	Solvents and contaminating fluids.....	17
6.5.12	Salt mist and sulphur dioxide.....	17
6.5.13	Water immersion	17
6.5.14	Hygroscopicity	17
6.5.15	Wicking.....	17
6.5.16	Flame propagation characteristics of a single cable	17
6.5.17	Flame propagation characteristics of bunched cables	17
6.5.18	Halogen gas evolution	17
6.5.19	Smoke generation.....	18
6.5.20	Toxic gas emission	18
6.5.21	Integrated fire test method for cables in environmental air handling spaces.....	18
7	Bundled cable requirements	18
7.1	General.....	18
7.2	Single pairs sharing one sheath	18
7.2.1	General	18
7.2.2	Near-end crosstalk (<i>NEXT</i>).....	18
7.2.3	Attenuation to crosstalk ratio far-end (<i>PS ACR-F</i>)	19
Annex A (informative)	Blank Detail Specification	20
Bibliography		25
Table 1	– Transfer impedance	11
Table 2	– Coupling attenuation	12
Table 3	– Attenuation equation constants	13
Table 4	– <i>TCL</i> requirements	13

Table 5 – <i>EL TCTL</i> requirements	13
Table 6 – <i>PS ANEXT</i> requirements	14
Table 7 – <i>PS AACR-F</i> requirements	14
Table 8 – <i>RL</i> requirements	15
Table 9 – <i>NEXT</i> and <i>PS NEXT</i> requirements	18
Table 10 – <i>ACR-F</i> and <i>PS ACR-F</i> requirements	19

IECNORM.COM : Click to view the full PDF of IEC 61156-11:2019

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD
CABLES FOR DIGITAL COMMUNICATIONS –****Part 11: Symmetrical single pair cables with
transmission characteristics up to 600 MHz –
Horizontal floor wiring – Sectional specification****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61156-11 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
46C/1118/FDIS	46C/1123/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IECNORM.COM : Click to view the full PDF of IEC 61156-11:2019

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 11: Symmetrical single pair cables with transmission characteristics up to 600 MHz – Horizontal floor wiring – Sectional specification

1 Scope

This part of IEC 61156 describes cables intended to be used for transmission of 1 Gbps over a single twisted pair for office, home and industrial application. An example of existing application is 1000BASE-T1, see ISO/IEC TR 11801-9906¹. The transmission characteristics of these cables are specified up to a frequency of 600 MHz and at a temperature of 20 °C. The cable type recognised is intended to be used for shielded channels with a nominal length of 40 m. Possible designs are U/FTP, X/UTP and X/FTP, where X stands for F, S or SF. A blank detail specification can be found in Annex A.

These cables can comprise more than one pair in the event that several systems are operated in parallel. In this case, refer to Clause 7 of this document.

The cables covered by this document are intended to operate with voltages and currents normally encountered in communication systems. While these cables are not intended to be used in conjunction with low impedance sources, for example, the electric power supplies of public utility mains, they are intended to be used to support the delivery of low-voltage remote powering applications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60708:2005, *Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath*

IEC 61156-1:2007, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*
IEC 61156-1:2007/AMD1:2009²

IEC 61156-5:2009, *Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification*

IEC 62153-4-3:2013, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

¹ Under consideration.

² A consolidated version of this publication exists, comprising IEC 61156-1:2007 and IEC 61156-1:2007/AMD1:2009.

IEC 62153-4-5:2006, *Metallic communication cables test methods – Part 4-5: Electromagnetic compatibility (EMC) – Coupling or screening attenuation – Absorbing clamp method*

IEC 62153-4-9:2018, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

ISO/IEC TS 29125:2017, *Information technology – Telecommunications cabling requirements for remote powering of terminal equipment*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61156-1:2007 and in IEC 61156-1:2007/AMD1:2009 apply.

ISO and IEC maintain terminological databases for use in standardisation at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Installation considerations

4.1 General remarks

Installation area considerations are defined in Clause 4 of IEC 61156-1:2007. Other areas may be considered.

4.2 Bending radius of installed cable

The minimum bending radius of the cable shall be equal to or less than 4 times the outside diameter of the cable unless otherwise specified.

4.3 Climatic conditions

Under static conditions, the cable shall operate at least in the temperature range of the environment from $-20\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$.

The attenuation increase due to the elevated operating temperature (temperature of the environment) is described in 6.3.3.2.

In the case of application of remote powering, the maximum temperature of the conductor shall not exceed the maximum operation temperature under static conditions in order to maintain the integrity of the dielectric material performance which is aligned to environmental temperature range.

Extended temperature ranges are permitted and may be specified in the relevant detail specification.

5 Materials and cable construction

5.1 General remarks

For the purposes of this document, the requirements of Clause 5 of IEC 61156-5:2009 apply.

The choice of materials and cable construction shall be suitable for the intended application and installation of the cable and in line with the requirements of IEC 61156-1. Particular care shall be taken to meet any requirements for EMC and fire performance (such as burning properties, smoke generation, evolution of halogen gas).

5.2 Cable construction

The cable construction shall be in accordance with the details and dimensions given in the relevant detail specification.

5.3 Conductor

The conductor shall be a solid annealed copper conductor in accordance with 5.2.1 of IEC 61156-1:2007 and should have a nominal diameter between 0,4 mm and 0,65 mm. A conductor diameter of up to 1,0 mm may be used.

5.4 Insulation

The conductor shall be insulated with a suitable material. Examples of suitable materials are:

- polyolefin;
- fluoropolymer;
- low-smoke zero-halogen thermoplastic material.

The colour code shall be in accordance with IEC 60708 if not specified differently in the relevant detail specification.

5.5 Cable element

The cable element shall be a pair and shall be twisted. The entire cable may comprise more than one cable element, see 6.3.5 and Clause 7.

5.6 Screening of the cable element

The screen for the cable element shall be in accordance with 5.2.3.2 of IEC 61156-1:2007.

5.7 Cable make-up

Spacers may be used in the cable elements and to separate cable elements. The cable elements and their screens, if they are screened, may be covered by an intermediate jacket. This jacket shall be in accordance with 5.9 of this document. The core of the cable may be wrapped with a protective layer of non-hygroscopic and non-wicking material.

5.8 Screening of the cable core

A screen for the cable core shall be provided. The screen shall be in accordance with 5.2.5 of IEC 61156-1:2007.

5.9 Sheath

The sheath material shall consist of a suitable material. Examples of suitable materials are:

- polyolefin;
- PVC;
- fluoropolymer;
- low-smoke zero-halogen thermoplastic material.

The sheath shall be continuous, having a thickness as uniform as possible. A non-metallic ripcord may be provided. When provided, the ripcord shall be non-hygroscopic and non-wicking.

The colour of the sheath is not specified but it should be specified in the relevant detail specification.

5.10 Identification

Each length of cable shall be identified as to the supplier and, when required, a traceability code, using one of the following methods:

- appropriately coloured threads or tapes;
- with a printed tape;
- printing on the cable core wrapping;
- marking on the sheath.

Additional markings, such as length marking, are permitted. If used, such markings shall refer to this document.

5.11 Finished cable

The finished cable shall be adequately protected for storage and shipment.

6 Characteristics and requirements

6.1 General remarks

Clause 6 lists the characteristics and minimum requirements of a cable complying with this document. Test methods shall be in accordance with IEC 61156-1:2007 and IEC 61156-1:2007/AMD1:2009, Clause 6, except for the length of the cable under test which shall be as specified in Clause 6 of this document.

The computed requirements in dB, rounded to one decimal place, shall be used to determine compliance.

The tests for electrical characteristics in accordance with 6.2 shall be carried out on a cable length of not less than 100 m, unless otherwise specified.

The tests for transmission characteristics in accordance with 6.3 shall be carried out on a cable length of 100 m, unless otherwise specified.

6.2 Electrical characteristics and tests

6.2.1 Conductor resistance

The maximum conductor resistance at or corrected to 20 °C shall not exceed 145 Ω /km.

6.2.2 Resistance unbalance

6.2.2.1 Resistance unbalance within a pair

The resistance unbalance shall not exceed 2,0 %.

6.2.2.2 Resistance unbalance between pairs

If applicable, the pair-to-pair resistance unbalance shall not exceed 5,0 %.

6.2.3 Dielectric strength

There shall be no failures when a test is performed on conductor/conductor and, where screen(s) are present, a conductor/screen with 1,0 kV DC for 1 min or, alternatively, with 2,5 kV DC for 2 s. An AC voltage may be used. The AC voltage levels in these cases shall be 0,7 kV AC for 1 min or alternatively 1,7 kV AC for 2 s.

6.2.4 Insulation resistance

The test shall be performed on:

- conductor/conductor;
- conductor/screen.

The minimum insulation resistance at or corrected to 20 °C shall be not less than 5 GΩ·km.

6.2.5 Mutual capacitance

The mutual capacitance is not specified but may be indicated in the relevant detail specification.

6.2.6 Capacitance unbalance

The maximum capacitance unbalance pair to ground shall not exceed 1 200 pF/km at a frequency of 800 Hz or 1 000 Hz.

6.2.7 Transfer impedance

Two grades of performance are recognised for transfer impedance. The transfer impedance measured in accordance with IEC 62153-4-3 shall not exceed the values of at least one grade shown in Table 1.

Table 1 – Transfer impedance

Frequency range MHz	Maximum surface transfer impedance mΩ/m	
	Grade 1	Grade 2
1 to 10	$Z_t \leq 15f^{-0,176}$	$Z_t \leq 50f^{0,301}$
10 to 30	$Z_t \leq 10 \frac{f}{10}$	$Z_t \leq 23,392f^{0,631}$
Where f is the frequency in MHz.		

6.2.8 Coupling attenuation

Four performance types for coupling attenuation are recognised. Coupling attenuation shall be measured using either the absorbing clamp method (IEC 62153-4-5) or the triaxial method for screened cables (IEC 62153-4-9). When measured using one of these methods, the coupling attenuation in the frequency range from $f = 30$ MHz to 1 000 MHz shall meet the requirements of Type I, Type Ib or Type II indicated in Table 2.

Table 2 – Coupling attenuation

Coupling attenuation type	Frequency range MHz	Coupling attenuation dB
Type I	30 to 100	≥ 85
	100 to 1 000	$\geq 85 - 20 \log_{10}(f/100)$; f in MHz
Type Ib	30 to 100	≥ 70
	100 to 1 000	$\geq 70 - 20 \log_{10}(f/100)$; f in MHz
Type II	30 to 100	≥ 55
	100 to 1 000	$\geq 55 - 20 \log_{10}(f/100)$; f in MHz

6.2.9 Current-carrying capacity

The maximum current-carrying capacity is installation dependent and therefore not specified but may be indicated in the relevant detail specification. Further guidance with respect to current-carrying capacity is provided by ISO/IEC TS 29125:2017.

6.3 Transmission characteristics

6.3.1 Velocity of propagation (phase velocity)

The requirements are not specified but may be indicated in the relevant detail specification.

6.3.2 Phase delay and differential delay (delay skew)

6.3.2.1 Phase delay

The phase delay, τ , shall not exceed the value obtained from Equation (1) in the frequency range from 1 MHz to 600 MHz.

$$\tau = 534 + \frac{36}{\sqrt{f}} \quad (1)$$

where

τ is the phase delay in ns/100 m;

f is the frequency in MHz.

6.3.2.2 Differential delay (delay skew)

If applicable, the maximum delay skew between any two pairs, when measured at $(20 \pm 3)^\circ\text{C}$, shall not exceed 25 ns/100 m in the frequency range from 1 MHz to 600 MHz.

6.3.3 Attenuation (α)

6.3.3.1 Attenuation at 20 °C operating temperature

The maximum attenuation, α , of any pair in the frequency range indicated in Table 3 shall not exceed the value obtained from Equation (2).

$$\alpha = a\sqrt{f} + bf + c/\sqrt{f} \quad (2)$$

where

α is the attenuation expressed in dB/100 m;

a, b, c are constants indicated in Table 3;

f is the frequency expressed in MHz.

Table 3 – Attenuation equation constants

Frequency range MHz	Constants		
	a	b	c
1 to 600	1,8	0,005	0,25

6.3.3.2 Attenuation at elevated operating temperature

The increase of the maximum attenuation from Equation (2) due to elevated environmental temperature above 20 °C is obtained by calculation as follows:

- for screened cables: 0,2 %/°C in the temperature range 20 °C to 60 °C.

In the event of application of remote powering, the actual conductor temperature should be considered in order to calculate the attenuation increase. If an extended environmental temperature range is specified (see 4.3), the temperature coefficients given in this paragraph might not be applicable. The method provided in IEC 61156-1 should be used to determine temperature coefficients in this case.

6.3.4 Unbalance attenuation (TCL and $EL\ TCTL$)

The minimum near-end unbalance attenuation (transverse conversion loss or TCL) shall not be less than the value obtained from Table 4.

Table 4 – TCL requirements

Frequency range MHz	TCL dB
1 to 600	$50 - 15 \log_{10}(f)$; f in MHz; 40 dB maximum

The minimum equal-level far-end unbalance attenuation (equal-level transverse conversion transfer loss or $EL\ TCTL$) shall not be less than the value obtained from Table 5.

Table 5 – $EL\ TCTL$ requirements

Frequency range MHz	$EL\ TCTL$ dB
1 to 600	$40 - 20 \log_{10}(f)$; f in MHz; 5 dB minimum

For calculation of $EL\ TCTL$, the $TCTL$ and the attenuation measurement of the test specimen with the same length as defined in 6.1 shall be used.

6.3.5 Alien (exogenous) near-end crosstalk ($PS\ ANEXT$)

The $PS\ ANEXT$ (power-sum alien near-end crosstalk) of the cable when tested in accordance with 6.3.7.1 of IEC 61156-1:2007 shall be not less than the values obtained from Table 6.

Table 6 – *PS ANEXT* requirements

Frequency range MHz	<i>PS ANEXT</i> dB
1 to 100	67
100 to 600	67

For screened cables meeting the requirements of 6.2.7 and 6.2.8 (minimum Type Ib) *ANEXT* is proven by design.

6.3.6 Alien (exogenous) far-end crosstalk (*PS AACR-F*)

The *PS AACR-F* (power-sum alien attenuation to crosstalk ratio far-end) of the cable when tested in accordance with 6.3.8 of IEC 61156-1:2007 shall not be less than the values obtained from Table 7.

Table 7 – *PS AACR-F* requirements

Frequency range MHz	<i>PS AACR-F</i> dB
1 to 600	$103 - 20 \log_{10}(f)$; f in MHz

If *AFEXT* up to 600 MHz is greater than 90 dB, the *AACR-F* may not be calculated.

For calculation of *AACR-F*, the *AFEXT* and the attenuation measurement of the test specimen with a length as specified in 6.1 shall be used.

For those frequencies where the calculated limit value of *PS AACR-F* is greater than 80 dB, the requirement shall be 80 dB.

For screened cables meeting the requirements in accordance with 6.2.7 and 6.2.8 (minimum Type Ib), *AFEXT* is proven by design.

6.3.7 Alien (exogenous) crosstalk of bundled cables

The relevant requirements of this document – especially those of 6.3.5 and 6.3.6 – apply; see also Clause 7 of this document.

6.3.8 Impedance

The fitted or mean characteristic impedance measured in accordance with 6.3.10.2 or 6.3.10.3 of IEC 61156-1:2007/AMD1:2009 shall be $100 \Omega \pm 5 \Omega$ at 100 MHz. A measurement of the input impedance is not sufficient to ensure return loss limits.

Recommendations contained in IEC TR 61156-1-2 and in IEC TR 61156-1-5 for improvement of measurement uncertainty may be considered.

6.3.9 Return loss (*RL*)

The minimum return loss of any pair in the frequency range indicated in Table 8 shall not be less than the values in Table 8.

Table 8 – *RL* requirements

Frequency range MHz	<i>RL</i> dB
1 to 10	$20 + 5 \log_{10}(f)$; f in MHz
10 to 20	25
20 to 600	$25 - 7 \log_{10}(f/20)$; f in MHz 17,3 dB minimum

When using a balun-less measurement technique, the corresponding descriptions of IEC TR 61156-1-2 may be considered. Recommendations contained in IEC TR 61156-1-5 for improvement of measurement uncertainty by correction technique may be considered.

6.4 Mechanical and dimensional characteristics and requirements

6.4.1 Dimensional requirements

The overall diameter of insulation, the nominal thickness of the sheath and the maximum overall diameter of the sheath are not specified, but shall be indicated in the relevant detail specification.

6.4.2 Elongation at break of the conductor

The minimum elongation of the conductor shall be not less than 8 %.

6.4.3 Tensile strength of the insulation

The tensile strength of the insulation is not specified, but may be indicated in the relevant detail specification.

6.4.4 Elongation at break of the insulation

The minimum value of the elongation at break of the insulation shall be not less than 100 %.

6.4.5 Adhesion of the insulation to the conductor

The adhesion of the insulation to the conductor is not specified, but may be indicated in the relevant detail specification.

6.4.6 Elongation at break of the sheath

The minimum value of the elongation at break of any sheath shall be not less than 100 %.

6.4.7 Tensile strength of the sheath

The minimum tensile strength of any sheath shall be not less than 9 MPa.

6.4.8 Crush test of the cable

The crush resistance of the cable is not specified but may be indicated in the relevant detail specification.

6.4.9 Impact test of the cable

The impact resistance of the cable is not specified but may be indicated in the relevant detail specification.

6.4.10 Bending under tension

The bending performance of the cable is not specified but may be indicated in the relevant detail specification.

6.4.11 Repeated bending of the cable

Not applicable.

6.4.12 Tensile performance of the cable

The tensile strength of the cable is not specified but may be indicated in the relevant detail specification.

6.4.13 Shock-test requirements of the cable

Not applicable.

6.4.14 Bump-test requirements of the cable

Not applicable.

6.4.15 Vibration-test requirements of a cable

Not applicable.

6.5 Environmental characteristics

6.5.1 Shrinkage of the insulation

When tested at $(100 \pm 2) ^\circ\text{C}$ for 1 h, the shrinkage of the insulation shall not exceed 5 %. The length of the sample shall be 150 mm, and the shrink-back shall be measured as the sum from both ends.

6.5.2 Wrapping test of the insulation after thermal ageing

Not applicable.

6.5.3 Bending test of insulation at low temperature

The bending test of the insulated conductor shall be carried out at $(-20 \pm 2) ^\circ\text{C}$. The mandrel diameter shall be 6 mm. There shall be no cracks in the insulation.

6.5.4 Elongation at break of the sheath after ageing

The ageing regime shall be seven days at $(100 \pm 2) ^\circ\text{C}$. The elongation at break after ageing shall not be less than 50 % of the unaged value.

6.5.5 Tensile strength of the sheath after ageing

The ageing regime shall be seven days at $(100 \pm 2) ^\circ\text{C}$. The tensile strength after ageing shall be not less than 70 % of the unaged value.

6.5.6 Sheath pressure test at high temperature

Not applicable.

6.5.7 Cold bend test of the cable

The bending test shall be carried out at $(-20 \pm 2) ^\circ\text{C}$. The mandrel diameter shall be eight times the overall diameter of the cable. There shall be no cracks in the sheath.

6.5.8 Heat shock test

Not applicable.

6.5.9 Damp heat steady state

Not applicable.

6.5.10 Solar radiation

The resistance to solar radiation is not specified but may be specified in the relevant detail specification.

6.5.11 Solvents and contaminating fluids

The resistance to solvents and contaminating fluids is not specified but may be specified in the relevant detail specification.

6.5.12 Salt mist and sulphur dioxide

Not applicable.

6.5.13 Water immersion

Not applicable.

6.5.14 Hygroscopicity

The amount of moisture gained after 3 h shall not exceed 1 % in weight.

6.5.15 Wicking

The test solution shall not wet the filter paper at the end of 6 h.

6.5.16 Flame propagation characteristics of a single cable

If required by local regulations and/or indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1 unless regional or local regulations (e.g. the Construction Products Regulation (CPR) in Europe) apply.

6.5.17 Flame propagation characteristics of bunched cables

If required by local regulations and/or indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1 unless regional or local regulations (e.g. CPR in Europe) apply.

6.5.18 Halogen gas evolution

If required by local regulations and/or indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1 unless regional or local regulations (e.g. CPR in Europe) apply.

6.5.19 Smoke generation

If required by local regulations and/or indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1 unless regional or local regulations (e.g. CPR in Europe) apply.

6.5.20 Toxic gas emission

If required by local regulations and/or indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1 unless regional or local regulations (e.g. CPR in Europe) apply.

6.5.21 Integrated fire test method for cables in environmental air handling spaces

If required by local regulations and/or indicated in the relevant detail specification, the test shall be performed in accordance with IEC 61156-1 unless regional or local regulations (e.g. CPR in Europe) apply.

7 Bundled cable requirements

7.1 General

In bundled cables, break-out cables or cable harnesses, several one-pair cables as described in this document may be bundled. Such arrangements shall be specified in a detail specification agreed on by the manufacturer and the customer. Relevant safety regulations in addition to this document shall be taken into account. The limits for alien crosstalk shall apply for the crosstalk between the one-pair cables as described in this document.

7.2 Single pairs sharing one sheath

7.2.1 General

In the event that several pairs are operating in parallel in a multi-pair cable, the crosstalk between the pairs shall be considered. The most obvious case of four-pair cables is assumed in 7.2 for the requirements of near-end and far-end crosstalk. In the case of a different pair-count, the applicable power-sum requirements in this document for the relevant pair-count shall be met in order to achieve similar noise levels.

7.2.2 Near-end crosstalk (*NEXT*)

The requirements of this subclause apply to four-pair cables only. If applicable, the worst near-end crosstalk shall not be less than the values indicated in Table 9.

Table 9 – *NEXT* and *PS NEXT* requirements

Frequency range MHz	<i>NEXT</i> requirement dB	<i>PS NEXT</i> requirement dB
1 to 600	$111,7 - 15 \log_{10}(f)$; f in MHz	$108,7 - 15 \log_{10}(f)$; f in MHz

For those frequencies where the calculated value of *NEXT* is greater than 78 dB, the requirement shall be 78 dB. For those frequencies where the calculated value of *PS NEXT* is greater than 75 dB, the requirement shall be 75 dB.

7.2.3 Attenuation to crosstalk ratio far-end (*PS ACR-F*)

The requirements of this subclause apply to four-pair cables only. If applicable, the pair-to-pair *ACR-F* in dB for any combination shall be greater than or equal to the value obtained from Table 10.

Table 10 – *ACR-F* and *PS ACR-F* requirements

Frequency range MHz	<i>ACR-F</i> requirement dB	<i>PS ACR-F</i> requirement dB
1 to 600	$99 - 20 \log_{10}(f)$; f in MHz	$96 - 20 \log_{10}(f)$; f in MHz

For calculation of *ACR-F*, the *FEXT* and the attenuation measurement of the test specimen with length as defined in 6.1 shall be used.

For those frequencies where the calculated limit value of *ACR-F* is greater than 78 dB, the requirement shall be 78 dB. For those frequencies where the calculated value of *PS ACR-F* is greater than 75 dB, the requirement shall be 75 dB.

IECNORM.COM : Click to view the full PDF of IEC 61156-11:2019

Annex A (informative)

Blank Detail Specification

The blank detail specification determines the layout and style for detail specifications describing symmetrical single pair cables with transmission characteristics up to 600 MHz. Detail specifications, based on the blank detail specification, may be prepared by a national organization, a manufacturer, or a user. The detail specification shall be written in accordance with the layout of the blank detail specification described here.

This blank detail specification includes additional recommended environmental characteristics and severities, which are derived from the environmental classifications that are specified for cabling for various environments.

NOTE Environmental classifications are presented in ISO/IEC 11801-1 with three levels of severity in four areas: mechanical, ingress, climatic, and electromagnetic; thus, in tabular form, they are referred to as the "MICE table".

The numbers shown in brackets on this and the following pages correspond to the following items of required information, which shall be entered in the spaces provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number, issue number and date of issue.
- [3] Address of the organization from which the document is available.
- [4] Related documents.
- [5] Any other reference to the cable: national reference, trade name, etc.
- [6] A complete description of the cable, which shall include:
 - a) type and number of elements;
 - b) nominal impedance;
 - c) screening;
 - d) application;
 - e) other distinguishing performance characteristics.
- [7] Details of the cable material and construction.
- [8] Special requirements for bending radius or operating temperatures.
- [9] List of cable characteristics, separated into electrical, transmission, mechanical and environmental characteristics.
- [10] Appropriate subclause references to Sectional specification IEC 61156-11.
- [11] Requirements applicable to the relevant cable. The values entered shall meet as a minimum the requirements of Sectional specification IEC 61156-11.
- [12] Comments – Relevant remarks.

[1] Prepared by:		[2] Document: Issue: Date:	
[3] Available from:		[4] Generic specification: IEC 61156-1 Sectional specification: IEC 61156-11 Blank detail specification: IEC 61156-11:2019, Annex A	
[5] Additional references:			
[6] Cable description: a) Type and number of elements: b) Nominal impedance: c) Screening: d) Application: e) Other distinguishing performance characteristics:			
[7] Cable construction:	Subclause		Comments
	5.2	Cable construction:	
	5.3	Conductor description:	
	5.4	Insulation description: Maximum diameter: Colour code of elements:	
	5.5	Cable element:	
	5.6	Screening of the cable element: Tape material Minimum overlap Drain wire Braid wire Braid material	
	5.7	Cable make-up:	
	5.8	Screening of the cable core: Tape material Minimum overlap Drain wire Braid wire Braid material	
	5.9	Sheath Material Nominal thickness Colour Maximum overall diameter Marking Ripcord	
	5.10	Identification	
5.11	Packaging of finished cable		
[8] Minimum bending radius for static bending: Minimum bending radius for dynamic bending: Temperature range for installation:			

Operating temperature range under static conditions: C1: -10 °C to +60 °C C2: -25 °C to +70 °C C3: -40 °C to +70 °C			
[9] Characteristics	[10] Subclause	[11]	Comments
Electrical characteristics	6.2		
Conductor resistance	6.2.1	$\leq \dots \Omega/\text{km}$	
Resistance unbalance	6.2.2		
Resistance unbalance within a pair	6.2.2.1	$\leq \dots \%$	
Resistance unbalance between pairs	6.2.2.2	$\leq \dots \%$	
Dielectric strength			
Conductor/conductor	6.2.3	$\dots \text{ kV (time of application)}$	
Conductor/screen	6.2.3	$\dots \text{ kV (time of application)}$	
Insulation resistance			
Conductor/conductor	6.2.4	$\geq \dots \text{ M}\Omega \cdot \text{km}$	
Conductor/screen	6.2.4	$\geq \dots \text{ M}\Omega \cdot \text{km}$	
Mutual capacitance	6.2.5	$\leq \dots \text{ pF/m}$	
Capacitance unbalance pair to ground	6.2.6	$\leq \dots \text{ pF/m}$	
Transfer impedance	6.2.7		Cable should be according to Grade 1 or Grade 2, if screened.
Coupling attenuation	6.2.8	$\dots \text{ dB}$ Cable type.....	Cable type should be Type I, Ib or II.
Current-carrying capacity	6.2.9	$\dots \text{ mA}$	The current-carrying capacity is dependent on the installation conditions in accordance with ISO/IEC TS 29125.
Transmission characteristics	6.3		
Velocity of propagation	6.3.1		
Phase delay	6.3.2.1	$\leq \dots \text{ ns/m}$	
Differential delay (delay skew)	6.3.2.2	$\leq \dots \text{ ns/m}$	
Attenuation	6.3.3		
General figures	6.3.3.1	$\leq \dots \text{ dB/100 m}$	
Environmental temperature effects	6.3.3.2	$\leq \dots \text{ }^\circ\text{C}$	
Unbalance attenuation near-end (TCL)	6.3.4	$\geq \dots \text{ dB}$	Cable grade shall be identified.
Unbalance attenuation far-end (EL TCTL)	6.3.4	$\geq \dots \text{ dB}$	
Near-end crosstalk	7.2.2, if applicable	$\geq \dots \text{ dB}$	
Attenuation to crosstalk ratio far-end	7.2.3, if applicable	$\geq \dots \text{ dB}$	