

INTERNATIONAL STANDARD

**Multicore and symmetrical pair/quad cables for digital communications –
Part 3-1: Work area wiring – Blank detail specification**

IECNORM.COM : Click to view the full PDF of IEC 61156-3-1:2009



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

IECNORM.COM : Click to view the full PDF of IEC 61156-3-1:2009

INTERNATIONAL STANDARD

**Multicore and symmetrical pair/quad cables for digital communications –
Part 3-1: Work area wiring – Blank detail specification**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE



ICS 33.120.20

ISBN 978-2-88910-421-5

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Guidance for preparation of detail specifications	5
4 Blank detail specification for multicore and symmetrical pair(s)/quad(s) cables for digital communication in horizontal floor wiring	7

IECNORM.COM : Click to view the full PDF of IEC 61156-3-1:2009

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES
FOR DIGITAL COMMUNICATIONS –****Part 3-1: Work area wiring –
Blank detail specification**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61156-3-1 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

This standard is to be read in conjunction with IEC 61156-1: 2002 and IEC 61156-3: 2008.

This third edition cancels and replaces the second edition published in 2003. This edition constitutes a technical revision. The significant global technical change is the alignment with IEC 61156-3: 2008.

The text of this standard is based on the first edition and on the following documents:

FDIS	Report on voting
46C/883/FDIS	46C/891/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61156 series, published under the general title *Multicore and symmetrical pair/quad cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IECNORM.COM : Click to view the full PDF of IEC 61156-3-1:2009

MULTICORE AND SYMMETRICAL PAIR/QUAD CABLES FOR DIGITAL COMMUNICATIONS –

Part 3-1: Work area wiring – Blank detail specification

1 Scope

The application of this blank detail specification relates to multicore and symmetrical pair(s)/quad(s) cables for digital communications in work area wiring.

This blank detail specification determines the layout and style for detail specifications describing multicore and symmetrical pair(s)/quad(s) cables for digital communication in work area wiring. Detail specifications based on the blank detail specification may be prepared by a national standards organization, a manufacturer or a user.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61156-1:2002¹, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 61156-3, *Multicore and symmetrical pair/quad cables for digital communications – Part 3: Work area wiring – Sectional specification*

3 Guidance for preparation of detail specifications

It is necessary to keep the transmission characteristics indicated in the relevant sectional specification for the category number (3 or 5) and the characteristic impedance.

The detail specification shall be written in accordance with the layout of the blank detail specification which forms part of this standard.

NOTE When a characteristic does not apply, then NA (for Not Applicable) should be entered in the appropriate space.

When a characteristic applies but a specific value is not considered necessary, then NS (for Not Specified) should be entered in the appropriate space.

The numbers shown in brackets on this and the following pages correspond to the following items of required information, which should be entered in the spaces provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number, issue number and date of issue.
- [3] Address of the organization from which the document is available.

¹ A more recent version of this standard exists (2007), but as not all of the tests cited herein are addressed by the newer edition, it has been decided that the 2002 edition is to be used.

- [4] Related documents.
- [5] Any other references to the cable, national reference, trade name, etc.
- [6] A complete description of the cable which shall include
 - a) type and number of elements;
 - b) nominal impedance;
 - c) screening;
 - d) application;
 - e) category;
 - f) other distinguishing performance characteristics.

Example: Detail specification for 4-pairs cable without common screen for digital communications in work area wiring category 3.

- [7] Details of the cable materials and construction.
- [8] Special requirements for bending radius or operation temperatures.
- [9] List of cable characteristics. They are separated into electrical, transmission, mechanical and environmental characteristics.
- [10] Appropriate subclause references in both the generic specification IEC 61156-1:2002 and sectional specification IEC 61156-3.
- [11] Requirements applicable for this cable. The values entered shall at a minimum meet the requirements of the sectional specification IEC 61156-3.
- [12] Relevant remarks.

IECNORM.COM : Click to view the full PDF of IEC 61156-3-1:2009

4 Blank detail specification for multicore and symmetrical pair(s)/quad(s) cables for digital communication in horizontal floor wiring

[1] Prepared by:		[2] Document:	
		Issue:	
		Date:	
[3] Available from:	[4] Generic specification: IEC 61156-1: 2002 Sectional specification: IEC 61156-3: 2008 Detail specification: IEC 61156-3-1: 2009		
[5] Additional references:			
[6] Cable description:			
[7] Cable materials and construction	IEC 61156-3: 2008 subclause		comments
	2.2.2	Cable construction	
	2.2.3	Conductor description	
	2.2.4	Insulation description: Nominal thickness Maximum diameter	
	2.2.5	Colour code of elements	
	2.2.6	Number of elements	
	2.2.7	Screening of the element	
	2.2.8	Cable make-up: Number of units Screen of the units Tape material Minimum overlap Protective wrapping(s) of the cable core	

	2.2.9	Screen of the cable core: Tape material Minimum overlap Drain wire Braid wire Braid material Filling factor	
	2.2.10	Sheath: Material Nominal thickness Maximum overall diameter Marking Rip cord	
	2.2.11	Colour of the sheath	
	2.2.12	Identification	
	2.2.13	Packaging of finished cable	

[8]

Minimum bending radius for static bending: mm

Minimum bending radius for dynamic bending: mm

Temperature range (installation/operation): °C

[9] Characteristics	[10] Subclause	[11] Requirements	[12] Comments
Electrical characteristics	3.2		
Conductor resistance	3.2.1	$\leq \dots \Omega/\text{km}$	
Resistance unbalance	3.2.2	$\leq \dots \%$	
Dielectric strength conductor/conductor conductor/screen screen/screen	3.2.3	$\dots \text{ kV}$ $\dots \text{ kV}$ $\dots \text{ kV}$	
Insulation resistance conductor/conductor conductor/screen	3.2.4	$\geq \dots \text{ M}\Omega \cdot \text{km}$ $\geq \dots \text{ M}\Omega \cdot \text{km}$	
Mutual capacitance	3.2.5	$\leq \dots \text{ pF/m}$	
Capacitance unbalance pair/screen	3.2.6	$\leq 1\,700 \text{ pF}/500 \text{ m}$ $\leq \dots \text{ pF}/500 \text{ m}$	
Transfer impedance at 1 MHz 10 MHz 100 MHz	3.2.7	$\leq \dots \text{ m}\Omega/\text{m}$ $\leq \dots \text{ m}\Omega/\text{m}$ $\leq \dots \text{ m}\Omega/\text{m}$	
Transmission characteristics	3.3		
Velocity of propagation (phase velocity) Phase delay Differential phase delay Environmental effects	3.3.1 3.3.1.1 3.3.1.2 3.3.1.2.2	$\geq \dots \text{ km/s}$	
Attenuation at 1 MHz 4 MHz 10 MHz 16 MHz 20 MHz 31,25 MHz 62,5 MHz 100 MHz	3.3.2	$\leq \dots \text{ dB}/100 \text{ m}$ $\leq \dots \text{ dB}/100 \text{ m}$ $\leq \dots \text{ dB}/100 \text{ m}$ $\leq \dots \text{ dB}/100 \text{ m}$ $\leq \dots \text{ dB}/100 \text{ m}$ $\leq \dots \text{ dB}/100 \text{ m}$ $\leq \dots \text{ dB}/100 \text{ m}$ $\leq \dots \text{ dB}/100 \text{ m}$	
Unbalance attenuation near-end (TCL)	3.3.3	$\dots \text{ dB}$	

[9] Characteristics	[10] Subclause	[11] Requirements	[12] Comments
Unbalance attenuation far-end (EL-TCTL)	3.3.3	...dB	
Near-end crosstalk at 1 MHz 4 MHz 10 MHz 16 MHz 20 MHz 31,25 MHz 62,5 MHz 100 MHz	3.3.4	$\geq$ dB $\geq$ dB $\geq$ dB $\geq$ dB $\geq$ dB $\geq$ dB $\geq$ dB $\geq$ dB	
Characteristic impedance	3.3.5	... Ω	
Input impedance 1 MHz / MHz	3.3.5.2	... $\Omega \pm 15 \Omega$	
Function fitted impedance / mean characteristic impedance	3.3.5.3	... Ω	
Structural return loss (SRL)	3.3.6	<... dB	
Mechanical characteristics	3.4		
Dimensional requirements Insulation diameter Sheath thickness Cable diameter	3.4.1	... mm	
Elongation at break of the conductors	3.4.2	$\geq$ %	
Elongation at break of the insulation	3.4.3	$\geq$ %	
Elongation at break of the sheath	3.4.4	$\geq$ %	
Tensile strength of the sheath	3.4.5	$\geq$ MPa	
Crush test of the cable	3.4.6		
Impact test of the cable	3.4.7		
Repeated bending of the cable	3.4.8		
Tensile performance of the cable	3.4.9	 N	