

INTERNATIONAL STANDARD

**Coaxial communication cables –
Part 13-1: Blank detail specification for semi-rigid cables with silicon dioxide
dielectric**

IECNORM.COM : Click to view the full PDF of IEC 61196-13-1:2024



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IECNORM.COM : Click to view the full text of IEC 60619-1:2024

INTERNATIONAL STANDARD

**Coaxial communication cables –
Part 13-1: Blank detail specification for semi-rigid cables with silicon dioxide
dielectric**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 29.060

ISBN 978-2-8322-8315-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Guidance for the preparation of detail specifications	5
5 Blank detail specification	7

IECNORM.COM : Click to view the full PDF of IEC 61196-13-1:2024

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COAXIAL COMMUNICATION CABLES –

**Part 13-1: Blank detail specification for semi-rigid
cables with silicon dioxide dielectric**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61196-13-1 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46A/1662/FDIS	46A/1671/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

This document is to be read in conjunction with IEC 61196-1:2005 and IEC 61196-13:2023.

A list of all parts in the IEC 61196 series, published under the general title *Coaxial communication cables*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IECNORM.COM : Click to view the full PDF of IEC 61196-13-1:2024

COAXIAL COMMUNICATION CABLES –

Part 13-1: Blank detail specification for semi-rigid cables with silicon dioxide dielectric

1 Scope

This part of IEC 61196 applies to coaxial communication cables described in IEC 61196-13. It specifies the requirements of semi-rigid coaxial communication cables with silicon dioxide dielectric and tubular outer conductor. These cables are intended for use in applications demanding the extreme environments as well as the nuclear power plant, oil rig and aircraft engine.

This document determines the layout and style for detail specifications. Detail specifications (DS) can be prepared by a national organization, a manufacturer or a user by entering the details in the blank detail specification.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61196-1:2005, *Coaxial communication cables – Part 1: Generic specification: General, definitions and requirements*

IEC 61196-13:2023, *Coaxial communication cables – Part 13: Sectional specification for semi-rigid cables with silicon dioxide dielectric*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

4 Guidance for the preparation of detail specifications

The detail specification shall be written in accordance with the layout of the blank detail specification, which forms part of this document.

When a characteristic does not apply, then NA (not applicable) should be entered in the appropriate space.

When a characteristic applies but a specific value is not considered necessary, then NS (not specified) should be entered in the appropriate space.

The numbers shown in brackets in this and the following pages correspond to the following items of required information, which should be entered in the space provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number and date of issue.
- [3] Address of the organization from which the document is available.
- [4] Related documents.
- [5] Any other references to the cable, national reference, trade name, etc.
- [6] Complete description of the cable.
- [7] Cable construction.
- [8] Engineering information.
- [9] Parameter or characteristic of the cable.
- [10] Reference to the relevant subclause of the sectional specification.
- [11] Minimum requirements, the values entered shall meet as a minimum the requirements of the sectional specification.
- [12] Remarks.

IECNORM.COM : Click to view the full PDF of IEC 61196-13-1:2024

5 Blank detail specification

Title		
[1] Prepared by:	[2] Document No.:	
	Issue:	
	Date:	
[3] Available from:	[4] Generic specification	IEC 61196-1
	Sectional specification	IEC 61196-13
[5] Additional references:		
References to the different test procedures of Column 9 are given in IEC 61196-13.		
[6] Cable description:		
a) Cable variant b) Material and construction of inner conductor c) Material of dielectric d) Material of outer conductor e) Material of sheath (if any)		
[7] Cable construction		
a) Inner conductor		
Material:		
Construction:		
Diameter (mm) nominal:		
Tolerance (mm): $\pm$...		
b) Dielectric		
Material:		
Diameter (mm) nominal:		
Tolerance (mm) tube: $\pm$...		
c) Outer conductor		
Material:		
Diameter (mm) nominal:		
Tolerance (mm): $\pm$...		
d) Sheath (if any)		
Material		
Minimum thickness (mm)		
Diameter (mm)		
Tolerance (mm): $\pm$...		
[8] Engineering information (reference only)		
a) Operating temperature range, storage temperature range, installation temperature range:		
b) Maximum recommended operating frequency, cut-off frequency:		
c) Nominal characteristic impedance:		
d) Maximum continue working voltage:		
e) Minimum bending radius (static state):		
f) Nominal weight:		
g) Maximum tensile force:		
h) RF peak power (when required):		

[9] Parameter	[10] IEC 61196-13:2023 Subclause	[11] Value	[12] Remarks
Electrical characteristics	8.2		
Inner conductor DC resistance	8.2.1	$\leq \dots \Omega/\text{km}$	
Insulation resistance	8.2.2	$\geq 10^4 \text{ M}\Omega \cdot \text{km}$	
Capacitance	8.2.3	$\leq \dots \text{pF/m}$	The value of typical cable, see IEC 61196-13:2023, Annex A.
Withstand voltage of dielectric	8.2.4	$\dots \text{kV RMS}$	40 Hz to 60 Hz
Propagation velocity ^a	8.2.5	$\geq 70 \% \text{ at } \dots^\circ\text{C}$	The value of typical cable, see IEC 61196-13:2023, Annex A.
Continuity	8.2.6	Inner conductor shall be continuous. Outer conductor shall be continuous.	
Phase stability vs Temperature	8.2.7	$\leq \dots \text{PPM}^1$ Frequency: $\dots \text{GHz}$ Test temperature: $\dots^\circ\text{C}$	A graph should be utilized to depict phase versus temperature change.
Return loss	8.2.8	$\dots \text{MHz} \sim \dots \text{MHz}$ $\geq \dots \text{dB at } \dots^\circ\text{C}$	Specimen length: $\geq 2 \text{ m}$
Attenuation constant	8.2.9	$\dots \text{MHz} \leq \dots \text{dB/m at } 20^\circ\text{C}$	The test method of attenuation for the cable under extreme temperature is for further study, and the value of it can be determined between the manufacturer and the user.
Characteristic impedance	8.2.10	$(\dots \pm \dots) \Omega \text{ at } \dots^\circ\text{C}$	The typical values are 50Ω .
RF average power ^a	8.2.11	$\dots \text{W at } \dots^\circ\text{C}$ Frequency: $\dots \text{GHz}$	The characteristic values should not exceed the range of design values specified in the detail specification.
Screening attenuation ^b	8.2.12	$\geq 110 \text{ dB}$, or specified in the detailed specification.	100 MHz to 3 000 MHz
Environmental characteristics	8.3		
Heat behaviour	8.3.1	After the test, the attenuation and return loss changes shall be in accordance with the relevant detail specification.	Sample preparation: both ends of the specimen should be attached with suitable RF connectors. Temperature of the heating shall be $1\,000^\circ\text{C}$ or specified in the detail specification.
Damp heat	8.3.2	The attenuation change shall be in accordance with the relevant detail specification.	Sample preparation: both ends of the specimen should be attached with suitable RF connectors. Relative humidity: 90 % to 95 % Temperature: 25°C
Gamma irradiation ^a	8.3.3	The attenuation change shall be in accordance with the relevant detail specification.	

¹ PPM stands for parts per million.

[9] Parameter	[10] IEC 61196-13:2023 Subclause	[11] Value	[12] Remarks
Thermal shock	8.3.4	a) The return loss shall be in accordance with the detail specification b) The attenuation change shall be in accordance with the detail specification c) No cracks, flaws or other damage on the cable surface	Length of sample: ... m Low temperature: ... °C ± ... °C High temperature: ... °C ± ... °C Duration: see IEC 61196-13:2023, Annex C or as specified in the detail specification. Cycles: 5 or as specified in the detail specification.
Mechanical characteristics	8.4		
Visual examination	8.4.1	The sheath or outer conductor (when the cable is without sheath) shall be free of rust or cracks.	
Dimensional examination	8.4.2	The requirement shall be specified in the detailed specification.	
Ovality of inner conductor ^b	8.4.3	≤ ... %	
Ovality of sheath ^{b, c}	8.4.4	≤ ... %	
Eccentricity of dielectric ^b	8.4.5	≤ ... %	
Solderability	8.4.6	The surface of tubular outer conductor corresponding to the immersed length shall be correctly tinned.	
Cable bending	8.4.7	a) The attenuation change shall be in accordance with the relevant detail specification. b) The return loss shall be in accordance with the relevant detail specification. c) No physical damage on the cable surface.	Bending radius should be in accordance with the relevant detail specification.
Tensile strength of cable (longitudinal pull) ^a	8.4.8	a) The characteristic impedance: (... ± ...) Ω b) No physical damage on the cable surface.	The maximum tension applied shall be greater than or equal to the cable weight of 100 m or be specified in the detail specification.
^a When required. ^b When applicable ^c Frequencies are not always fixed frequencies and can be a swept over a range.			