

INTERNATIONAL STANDARD

**Fibre optic interconnecting devices and passive components performance
standard –**

**Part 081-2: Non-connectorized single-mode fibre optic middle-scale $1 \times N$ DWDM
devices for category C – Controlled environments**

IECNORM.COM: Click to view the full PDF of IEC 61753-081-2:2009



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

**Fibre optic interconnecting devices and passive components performance
standard –**

**Part 081-2: Non-connectorized single-mode fibre optic middle-scale $1 \times N$ DWDM
devices for category C – Controlled environments**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

R

ICS 33.180.10

ISBN 978-2-88910-556-4

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Terms and definitions	6
4 Test conditions – General.....	6
5 Test report.....	7
6 Reference components.....	7
7 Performance requirements	7
7.1 Dimensions	7
7.2 Test details and requirements	7
Annex A (normative) Sample size, sequencing and grouping requirements	17
Bibliography.....	18
Table 1 – Spectral bands for single-mode systems ^a	7
Table 2 – Test and requirements for type A (Gaussian passband profile).....	8
Table 3 – Test and requirements for type B (Flat-top passband profile).....	11
Table 4 – Environmental test for all types	14
Table A.1 – Sequencing and number of samples for each test	17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE OPTIC INTERCONNECTING DEVICES AND
PASSIVE COMPONENTS PERFORMANCE STANDARD –****Part 081-2: Non-connectorized single-mode fibre optic
middle-scale 1 × N DWDM devices for category C –
Controlled environments**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-081-2 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

This standard cancels and replaces IEC/PAS 61753-081-2 published in 2005. This first edition constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
86B/2863/FDIS	86B/2901/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61753 series, under the general title *Fibre optic interconnecting devices and passive components performance standards*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

Withdrawn
IECNORM.COM: Click to view the full PDF of IEC 61753-081-2:2009

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS PERFORMANCE STANDARD –

Part 081-2: Non-connectorized single-mode fibre optic middle-scale $1 \times N$ DWDM devices for category C – Controlled environments

1 Scope

This part of IEC 61753 contains the minimum initial test and measurement requirements and severities which a fibre optic middle-scale $1 \times N$ ($16 \leq N \leq 64$) DWDM (Dense Wavelength Division Multiplexing) device with channel spacing of 50 GHz, 100 GHz and 200 GHz needs to satisfy in order to be categorized as meeting the requirements of category C-controlled environments. The requirements cover devices with single-mode non-connectorized pigtails and no circuit board. There is also a distinction between small-scale ($N < 16$) and large-scale ($N > 64$) $1 \times N$ DWDM devices for the purpose of this standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – Optical power handling and damage threshold characterization*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat – High temperature endurance*

IEC 61300-2-19, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-19: Tests – Damp heat (steady state)*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for connectors*

IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examinations and measurements – Polarization dependence of attenuation in a single-mode fibre optic device*

IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

IEC 61300-3-20, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-20: Examinations and measurements – Directivity of fibre optic branching devices*

IEC 61300-3-29, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-29: Examinations and measurements – Measurement techniques for characterizing the amplitude of the spectral transfer function of DWDM components*

IEC 61300-3-32, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-32: Examinations and measurements – Polarization mode dispersion measurement for passive optical components*

IEC 61753-021-2, *Fibre optic interconnecting devices and passive components performance standard – Part 021-2 Fibre optic connectors terminated on single mode fibre for category C – Controlled environment*

IEC/PAS 62074-1, *Fibre optic WDM devices – Part 1: Generic specification*

ITU-T Supplement N.39:2003, *Optical system design and engineering considerations*

ITU-T Recommendation G.671:2005, *Transmission characteristics of optical components and subsystems*

ITU-T Recommendation G.692:1998, *Optical interfaces for multichannel systems with optical amplifiers*

ITU-T Recommendation G.694.1:2002, *Spectral grids for WDM applications: DWDM frequency grid*

3 Terms and definitions

For the purposes of this document, the following terms and definitions, as well as those given in IEC/PAS 62074-1, apply.

3.1

middle-scale 1 x N DWDM device

wavelength-selective branching device which performs the function both of a wavelength multiplexer and demultiplexer with DWDM channel spacing of 50 GHz, 100 GHz and 200 GHz and a number of channels (N) equalling 16 ~ 64

4 Test conditions – General

Unless otherwise specified, all test methods shall be in accordance with the IEC 61300 series. DWDM devices used for each test are intended to be previously unstressed new samples but may also be selected from previously used samples, if desired. All measurements shall be carried out at normal room temperature, unless otherwise stated. If the device is provided with an active temperature control, this shall be set at the set-point specified by the manufacturer.

The requirements apply to every combination of input and output port.

All tests are to be carried out to validate performance over the required operating wavelength range. As a result, single or multiple spectral bands may be chosen for the qualification and differing target specifications may be assigned to each spectral band.

The following Table 1 is intended to provide guidance on the wavelength ranges of the various spectral bands. It is not intended for specification. Values of operating wavelength used in performance verification shall be defined in the manufacturer's specification.

Table 1 – Spectral bands for single-mode systems^a

Band	Descriptor	Range (nm)
O-band	Original	1260 to 1360
E-band	Extended	1360 to 1460
S-band	Short wavelength	1460 to 1530
C-band	Conventional	1530 to 1565
L-band	Long wavelength	1565 to 1625
U-band	Ultralong wavelength	1625 to 1675
^a Taken from ITU-T Supplement G sup. 39: Optical system design and engineering considerations (12/2008).		

5 Test report

Fully documented test reports and supporting evidence shall be prepared and be available for inspection as evidence that the tests have been carried out and complied with.

6 Reference components

The testing for these components does not require the use of reference components.

7 Performance requirements

7.1 Dimensions

Dimensions shall comply with either an appropriate IEC interface standard or with those given in appropriate manufacturers drawings, where the IEC interface standard does not exist or cannot be used.

7.2 Test details and requirements

The device is equipped with no circuit-board including a temperature controller. The requirements are given only for pigtailed DWDM devices. For connectorized components, the connector performances shall be in compliance with IEC 61753-021-2.

A minimum length of fibre or cable of 1,5 m per port shall be included in all climatic and environmental tests. The operating wavelengths, unless otherwise specified, shall be in accordance with ITU-T Recommendation G.692 and G.694.1. Where devices with wavelength spaced channels have to be considered, the conversion should refer to vacuum wavelength.

Table 2 – Test and requirements for type A (Gaussian passband profile)

No	Tests	Requirements	Details
1A	Number of channels: N	$16 \leq N \leq 64$	Design information (not test item) Operating wavelength: ITU-T grid or custom design
2A	Channel frequency range	Channel central frequency $\pm 0,125 \times \Delta f$ where Δf is the channel spacing	Information (not test item) IEC 62074-1 Channel central frequency: ITU-T grid or custom design ITU-T Recommendation G.694.1
3A	Insertion loss	Maximum allowable insertion loss over the channel frequency range: 4,8 dB	IEC 61300-3-29, IEC 62074-1 Condition: the insertion loss shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide loss measurement results with accuracy of better than $\pm 0,05$ dB over the operating wavelength range
4A	Channel non-uniformity	Maximum allowable channel non-uniformity of insertion losses: 1,0 dB (Channel n. ≤ 24) 1,5 dB (Channel n. > 24)	IEC 61300-3-29 Condition: the channel non-uniformity shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide loss measurement results with accuracy of better than $\pm 0,05$ dB over the operating wavelength range
5A	1 dB passband width	Minimum allowable 1 dB passband width (centred at the channel frequency): $0,25 \times \Delta f$ where Δf is the channel spacing	IEC 61300-3-29, IEC 62074-1 Condition: the passband width shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m
6A	3 dB passband width	Minimum allowable 3 dB passband width (centred at the channel frequency): $0,5 \times \Delta f$ where Δf is the channel spacing	Details: same as in test 5A

Table 2 (continued)

No	Tests	Requirements	Details
7A	Adjacent channel isolation	Minimum allowable adjacent channel isolation over the channel frequency range: 25 dB	IEC 61300-3-29, IEC 62074-1 The adjacent channel isolation is specified only for demultiplexer Condition: the adjacent channel isolation shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide isolation measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
8A	Non-adjacent channel isolation	Minimum allowable non-adjacent channel isolation over the channel frequency range: 30 dB	IEC 61300-3-29, IEC 62074-1 The non-adjacent channel isolation is specified only for demultiplexer Condition: the non-adjacent channel isolation shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide isolation measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
9A	Total channel isolation	Minimum allowable total channel isolation value: 22 dB (Channel $n \leq 40$) 20 dB (Channel $n > 40$)	IEC 61300-3-29, IEC 62074-1 Condition: the minimum total channel isolation shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide isolation measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
10A	Polarisation dependent loss (PDL)	Maximum allowable PDL over the channel frequency range: 0,4 dB	IEC 61300-3-2, IEC 62074-1 The allowable PDL combination applies to all combination of input and output ports Launch fibre length: $\geq 1,5$ m
11A	Polarisation mode dispersion (PMD)	Maximum allowable PMD over the channel frequency range: 0,5 ps	IEC 61300-3-32, IEC 62074-1 The allowable PMD combination applies to all combination of input and output ports

Table 2 (continued)

No	Tests	Requirements	Details
12A	Chromatic dispersion	Maximum allowable chromatic dispersion over the channel frequency range (absolute value): 20 ps/nm for 100 GHz channel spacing 60 ps/nm for 50 GHz channel spacing	Method: A chromatic dispersion test method is under study in WG4 (Ex. Test method for fibre: IEC 60793-1-42)
13A	Return loss	Minimum allowable return loss: 40 dB	IEC 61300-3-6 Condition: All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement Launch fibre length: $\geq 1,5$ m The test conditions shall provide return loss measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
14A	Directivity	Maximum allowable directivity: - 40 dB	IEC 61300-3-20 Condition: All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement The directivity shall be measured between any pair of input or output ports The test conditions shall provide directivity measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
15A	Optical power handling and damage threshold characterization	+25 dBm	IEC 61300-2-14 Input port: single port

Table 3 – Test and requirements for type B (Flat-top passband profile)

No	Tests	Requirements	Details
1B	Number of channels	$16 \leq \text{Channel n.} \leq 64$	Operating wavelength: ITU-T grid or custom design
2B	Channel frequency range	Channel central frequency $\pm 0.125 \times \Delta f$ where Δf is the channel spacing	IEC 62074-1 Channel central frequency: ITU-T grid or custom design ITU-T Recommendation G.694.1
3B	Insertion loss	Maximum allowable insertion loss over the channel frequency range: 6,0 dB	IEC 61300-3-29, IEC 62074-1 Condition: the insertion loss shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide loss measurement results with accuracy of better than $\pm 0,05$ dB over the operating wavelength range
4B	Channel non-uniformity	Maximum allowable channel non-uniformity of insertion losses: 1,0 dB (Channel n. ≤ 24) 1,5 dB (Channel n. > 24)	IEC 61300-3-29 Condition: the channel non-uniformity shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide loss measurement results with accuracy of better than $\pm 0,05$ dB over the operating wavelength range
5B	1 dB passband width	Minimum allowable 1 dB passband width (centred at the channel frequency): $0,5 \times \Delta f$ where Δf is the channel spacing	IEC 61300-3-29, IEC 62074-1 Condition: the passband width shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m
6B	3 dB passband width	Minimum allowable 3 dB passband width (centred at the channel frequency): $0,5 \times \Delta f$ where Δf is the channel spacing	Details: same as in test 5B

Table 3 (continued)

No	Tests	Requirements	Details
7B	Adjacent channel isolation	Minimum allowable adjacent channel isolation over the channel frequency range: 25 dB	IEC 61300-3-29, IEC 62074-1 The adjacent channel isolation is specified only for demultiplexer Condition: the adjacent channel isolation shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide isolation measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
8B	Non-adjacent channel isolation	Minimum allowable non-adjacent channel isolation over the channel frequency range: 30 dB	IEC 61300-3-29, IEC 62074-1 The non-adjacent channel isolation is specified only for demultiplexer Condition: the non-adjacent channel isolation shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide isolation measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
9B	Total channel isolation	Minimum allowable total channel isolation value: 22 dB (Channel n. ≤ 40) 20 dB (Channel n. > 40)	IEC 61300-3-29, IEC 62074-1 Condition: the minimum total channel isolation shall be determined as the worst case over all states of polarisation Launch fibre length: $\geq 1,5$ m The test conditions shall provide isolation measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
10B	Polarisation dependent loss (PDL)	Maximum allowable PDL over the channel frequency range: 0,4 dB	IEC 61300-3-2, IEC 62074-1 The allowable PDL combination applies to all combination of input and output ports Launch fibre length: $\geq 1,5$ m
11B	Polarisation mode dispersion (PMD)	Maximum allowable PMD over the channel frequency range: 0,5 ps	IEC 61300-3-32, IEC 62074-1 The allowable PMD combination applies to all combination of input and output ports

Table 3 (continued)

No	Tests	Requirements	Details
12B	Chromatic dispersion	Maximum allowable chromatic dispersion over the channel frequency range (absolute value): 40 ps/nm for 100 GHz channel spacing 100 ps/nm for 50 GHz channel spacing	Method: A chromatic dispersion test method is under study in WG4 (Ex. Test method for fibre: IEC 60793-1-42)
13B	Return loss	Minimum allowable return loss: 40 dB	IEC 61300-3-6 Condition: All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement Launch fibre length: $\geq 1,5$ m The test conditions shall provide return loss measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
14B	Directivity	Maximum allowable directivity: -40 dB	IEC 61300-3-20 Condition: All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement The directivity shall be measured between any pair of input or output ports The test conditions shall provide directivity measurement results with accuracy of better than $\pm 0,1$ dB over the operating wavelength range
15B	Optical power handling and damage threshold characterisation	+25 dBm	IEC 61300-2-14 Input port: single port

Table 4 – Environmental test for all types

No	Tests	Requirements	Details
16	Cold	During and on completion of the test the requirement regarding the maximum allowable insertion loss shall be met During and on completion of the test, the insertion loss shall be within $\pm 0,5$ dB with respect to the initial value	IEC 61300-2-17 Temperature: $-10^{\circ}\text{C} \pm 2^{\circ}\text{C}$ Duration of exposure: 96 h Preconditioning procedure: Before test, specimens shall be maintained in room temperature condition for 2 h Specimen shall be optically functioning During the test the Insertion Loss value shall be measured at a maximum interval of 1 h Recovery procedure: After test, specimens shall be maintained in room temperature condition for 2 h
17	High temperature endurance	During and on completion of the test the requirement regarding the maximum allowable Insertion Loss shall be met During and on completion of the test, the Insertion Loss shall be within $\pm 0,5$ dB with respect to the initial value	IEC 61300-2-18 Temperature: $+60^{\circ}\text{C} \pm 2^{\circ}\text{C}$ Humidity is not controlled Duration of exposure: 96 h Preconditioning procedure: Before test, specimens shall be maintained in room temperature condition for 2 h Specimen shall be optically functioning During the test the insertion loss value shall be measured at maximum interval of 1 h during the first 16 h, and thereafter at a maximum interval of 24 h until completion of the test Recovery procedure: After test, specimens shall be maintained in room temperature condition for 2 h
18	Damp heat (steady state)	During and on completion of the test the requirement regarding the maximum allowable insertion loss shall be met During and on completion of the test, the insertion loss shall be within $\pm 0,5$ dB with respect to the initial value	IEC 61300-2-19 Temperature: $+40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ Relative humidity: $93\% \pm 2\%$ Duration of exposure: 96 h Specimen shall be optically functioning During the test the Insertion Loss value shall be measured at a maximum interval of 1 h Preconditioning procedure: Before test, specimens shall be maintained in room temperature condition for 2 h Recovery procedure: After test, specimens shall be maintained in room temperature condition for 2 h

Table 4 (continued)

No	Tests	Requirements	Details
19	Change of temperature	During and on completion of the test the requirement regarding the maximum allowable insertion loss shall be met During and on completion of the test, the insertion loss shall be within $\pm 0,5$ dB with respect to the initial value	IEC 61300-2-22 High temperature:- $+60\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$ Low temperature: $-10\text{ }^{\circ}\text{C} \pm 2\text{ }^{\circ}\text{C}$ Humidity is not controlled Duration at extreme temperatures: 1 h Temperature rate of change: $1\text{ }^{\circ}\text{C}/\text{min}$ Number of cycles: 5 Specimen shall be optically functioning During the test the insertion loss value shall be measured at a maximum interval of 30 min Preconditioning procedure: Before test, specimens shall be maintained in room temperature condition for 2 h Recovery procedure: After test, specimens shall be maintained in room temperature condition for 2 h
20	Vibration (sinusoidal)	During and on completion of the test the requirement regarding the insertion loss shall be met During and on completion of the test, the insertion loss shall be within $\pm 0,5$ dB with respect to the initial value	IEC 61300-2-1 Frequency range: 10 Hz-55 Hz Endurance duration per axis: 0,5 h Number of axes: Three orthogonal Number of sweeps: 15 Vibration amplitude: 0,75 mm Method of mounting: The specimen shall be mounted rigidly to the mounting fixture
21	Fibre/Cable retention	During and on completion of the test the requirement regarding the insertion loss shall be met During and on completion of the test, the insertion loss shall be within $\pm 0,5$ dB with respect to the initial value	IEC 61300-2-4 Magnitude and rate of application of the tensile load: 10 N + 1 N at a speed of 5 N/s for reinforced cables 5 N + 0,5 N at a speed of 0,5 N/s for coated fibres Duration of application of tensile load: 60 s Point of application of tensile load: 0,3 m from the exit point of the fibre / cable from the specimen Method of mounting: The sample shall be rigidly mounted such that the load is only applied to the fibre/cable retention mechanism