

INTERNATIONAL STANDARD

IEC
62122

First edition
2002-03

Methods of measurement for consumer-use digital VTRs – Electronic and mechanical performances

*Méthodes de mesure pour les magnétoscopes
numériques destinés au grand public –
Performances électroniques et mécaniques*



Reference number
IEC 62122:2002(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/catlg-e.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/JP.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC
62122

First edition
2002-03

Methods of measurement for consumer-use digital VTRs – Electronic and mechanical performances

*Méthodes de mesure pour les magnétoscopes
numériques destinés au grand public –
Performances électroniques et mécaniques*

© IEC 2002 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

X

For price, see current catalogue

CONTENTS

FOREWORD.....	7
1 Scope and object.....	8
2 Normative references.....	8
3 Terms and definitions	9
4 Measuring conditions	10
4.1 General	10
4.2 Environmental conditions	10
4.3 Power supply	10
4.4 Test signal.....	10
4.4.1 Video test signal	10
4.4.2 Colour bar signal	11
4.4.3 Video input signal for measuring audio characteristics	11
4.5 Measuring instruments.....	11
4.5.1 Noise meter	11
4.5.2 Audio signal generator	11
4.5.3 Audio level meter	11
4.5.4 Audio mixed frequency oscillator	12
4.5.5 Audio harmonic distortion meter	12
4.6 Video test tape	12
5 Methods of measurement for mechanical characteristics	12
5.1 General	12
5.2 Tape speed	12
5.2.1 Test signal.....	12
5.2.2 Measurement.....	12
5.2.3 Presentation of the results	13
5.3 Flatness of the RF envelope	13
5.3.1 Test signal.....	13
5.3.2 Block diagram.....	13
5.3.3 Measurement.....	13
5.3.4 Presentation of the result	14
5.4 Linearity	14
5.4.1 Test signal.....	14
5.4.2 Measurement.....	14
5.4.3 Presentation of the results	15
5.5 Effective area starting position	15
5.5.1 Test signal.....	15
5.5.2 Measurement.....	15
5.5.3 Presentation of the results	15
5.6 Track displacement measurement by image processing	15
5.6.1 Measurement system.....	15
5.6.2 Image processing technique.....	15
5.6.3 Measuring results	16

6	Video characteristics (analogue input/output)	17
6.1	General	17
6.2	Luminance amplitude frequency response	17
6.2.1	Test signal	17
6.2.2	Block diagram	17
6.2.3	Measurement	17
6.2.4	Presentation of results	18
6.3	Chrominance amplitude frequency response	18
6.3.1	Test signal	18
6.3.2	Block diagram	18
6.3.3	Measurement	18
6.3.4	Presentation of results	18
6.4	Luminance diagonal resolution	19
6.5	Luminance frequency characteristics of diagonal resolution (i)	19
6.6	Luminance frequency characteristics of diagonal resolution (ii)	19
6.7	Luminance non-linear distortion	19
6.8	Luminance waveform distortion (linear distortion)	19
6.9	Chrominance waveform distortion	19
6.9.1	Test signal	19
6.9.2	Block diagram	19
6.9.3	Measurement	19
6.9.4	Presentation of results	20
6.10	Luminance vertical waveform distortion	20
6.11	Chrominance vertical waveform distortion	20
6.12	Automatic Gain Control (AGC) operation	20
6.13	Chrominance to luminance horizontal displacement	20
6.14	Chrominance to luminance vertical displacement	20
6.15	Luminance signal-to-noise ratio	20
6.15.1	General	20
6.15.2	Test signal	21
6.15.3	Block diagram	21
6.15.4	Measurement	21
6.15.5	Presentation of the results	22
6.16	Chrominance signal-to-noise ratio	22
6.16.1	General	22
6.16.2	Test signal	22
6.16.3	Block diagram	22
6.16.4	Measurement	23
6.16.5	Presentation of the results	23
7	Composite signal decoding characteristics (luminance and chrominance separation)	24
7.1	Luminance signal separation (general)	24
7.2	Luminance signal separation at colour change points	24
7.3	Chrominance signal separation	24
7.4	Chrominance signal separation with three dimensional processing	24
7.4.1	Test signal	24
7.4.2	Block diagram	24
7.4.3	Measurement	24
7.4.4	Presentation of results	25

7.5	Luminance signal separation with three dimensional signal processing	25
7.5.1	Test signal	25
7.5.2	Block diagram	25
7.5.3	Measurement	25
7.5.4	Presentation of results	25
8	Audio characteristics (analogue input/output)	25
8.1	General	25
8.2	Audio operational output voltage (with AGC)	26
8.2.1	Test signal	26
8.2.2	Block diagram	26
8.2.3	Measurement	26
8.2.4	Presentation of results	26
8.3	Audio operational input voltage (without AGC)	26
8.3.1	Test signal	26
8.3.2	Block diagram	26
8.3.3	Measurement	26
8.3.4	Presentation of results	26
8.4	Audio maximum output voltage	26
8.4.1	Test signal	26
8.4.2	Block diagram	27
8.4.3	Measurement	27
8.4.4	Presentation of results	27
8.5	Amplitude frequency response	27
8.5.1	Test signal	27
8.5.2	Measurement	27
8.6	Phase difference between channels	27
8.6.1	Test signal	27
8.6.2	Measurement	27
8.6.3	Presentation of results	27
8.7	Signal-to-noise ratio	27
8.8	Dynamic range	27
8.8.1	Test signal	27
8.8.2	Measurement	28
8.8.3	Presentation of results	28
8.9	Harmonic distortion	28
8.10	Inter-modulation distortion	28
8.10.1	Test signal	28
8.10.2	Measurement	28
8.10.3	Presentation of result	28
8.11	Channel separation	28
8.11.1	Test signals	28
8.11.2	Measurement	28
8.11.3	Presentation of results	28
8.12	Wow-flutter	29
8.13	Pitch difference between record and playback	29
8.13.1	Test signal	29
8.13.2	Measurement	29
8.13.3	Presentation of results	29
9	Classification of the characteristics to be specified	29

Annex A (informative) Error rate	44
A.1 Definition	44
A.2 Block diagram	44
A.3 Measurement	44
A.4 Presentation of the results	45
A.5 Example 1	45
A.6 Example 2	45
Bibliography	47
Figure 1 – Basic block diagram of measurement system	30
Figure 2 – Measuring method for track interval	30
Figure 3 – Measuring block diagram for RF envelope flatness	31
Figure 4 – Measuring method for RF envelope flatness	31
Figure 5 – Cross-tape track height for DV format	31
Figure 6 – Cross-tape track height for D-VHS format	32
Figure 7 – Measuring method for linearity	32
Figure 8 – Measuring method for the starting position	32
Figure 9 – Block diagram of the measurement system	33
Figure 10 – Schematic diagram of the image processing technique	34
Figure 11 – Illustration of track displacement distribution (model)	35
Figure 12 – Example of calculation results	35
Figure 13 – Test signal for luminance amplitude frequency response	36
Figure 14 – Measuring block diagram for composite video signal	36
Figure 15 – Measuring block diagram for S video signal	36
Figure 16 – Test signal for chrominance amplitude frequency response	37
Figure 17 – Test signal for luminance non-linear distortion	37
Figure 18 – Test signal for luminance waveform distortion	37
Figure 19 – Test signal for chrominance waveform distortion	38
Figure 20 – Measuring method for chrominance waveform distortion	38
Figure 21 – Composite video test signal for luminance signal-to-noise ratio	39
Figure 22 – S luminance test signal for luminance signal-to-noise ratio	39
Figure 23 – S chrominance test signal for luminance signal-to-noise ratio	39
Figure 24 – Block diagram for composite video input	39
Figure 25 – Block diagram for S video input	40
Figure 26 – Composite video test signal for chrominance signal-to-noise ratio	40
Figure 27 – S luminance test signal for chrominance signal-to-noise ratio	40
Figure 28 – S chrominance test signal for chrominance signal-to-noise ratio	41
Figure 29 – Test signal for 3D chrominance signal separation	41
Figure 30 – Measuring block diagram for chrominance signal separation	41
Figure 31 – Measuring method for 3D chrominance signal separation	42
Figure 32 – Test signal for 3D luminance signal separation	42
Figure 33 – Measuring block diagram for luminance signal separation	42

Figure 34 – Measuring method for 3D luminance signal separation	43
Figure 35 – Block diagram for audio characteristics	43
Figure A 1 – Structure of Data-synchronisation blocks	46
Figure A 2 – Structure of DV format data-synchronisation blocks	46
Figure A 3 – Structure of D-VHS format data-synchronisation blocks	46
Table 1 – Setting of the colour noise meter for luminance measurement	21
Table 2 – Example: white level of test signal (8 bit system)	22
Table 3 – Setting of the colour noise meter for chrominance measurement	23
Table 4– Example: Chrominance level of test signal (8 bit system)	23
Table 5 – Classification of the characteristics to be specified	29

IECNORM.COM : Click to view the full PDF of IEC 62122:2002

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**METHODS OF MEASUREMENT FOR CONSUMER-USE DIGITAL VTRs –
ELECTRONIC AND MECHANICAL PERFORMANCES**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62122 has been prepared by TA 7: Moderate data rate storage media and equipment, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/452/FDIS	100/480/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

Annex A is for information only.

The committee has decided that the contents of this publication will remain unchanged until 2007. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

METHODS OF MEASUREMENT FOR CONSUMER-USE DIGITAL VTRs – ELECTRONIC AND MECHANICAL PERFORMANCES

1 Scope and object

This standard specifies the basic methods of measurement for evaluating the electronic and mechanical performances of consumer-use digital VTRs.

The formats of open reel VTRs, Beta, VHS, and 8 mm VTRs have been standardized. Methods of measurement for these analogue VTRs have been standardized in IEC 61041-1, IEC 61041-2, IEC 61041-3, IEC 61041-4, IEC 61041-5, and IEC 61146-3. Digital VTR 6,35 mm DV format and 12,65 mm D-VHS format have now been brought on the market. The methods of measurement for these consumer-use digital VTRs should be specified and standardized.

With these measurement techniques, some items for the evaluation of performances specific to digital VTRs have also been included.

There are two objectives for the proposed methods of measurement. One is to check the interchangeability and characteristics of the equipment under test which are indispensable to manufacturers, and the other is to evaluate the quality of image and sound, which concerns the customer. The latter is a priority for consumer satisfaction.

Since a consumer can use only general-purpose instruments, any test which needs dismantling of apparatus and requires special instruments is in principle not specified. As error rate is important for digital equipment, an example of a method for measuring error rate is given in annex A.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60094-3:1979, *Magnetic tape sound recording and reproducing systems – Part 3: Methods of measuring the characteristics of recording and reproducing equipment for sound on magnetic tape*

IEC 60386:1972, *Method of measurement of speed fluctuations in sound recording and reproducing equipment*

IEC 60883:1987, *Measuring method for chrominance signal-to-random noise ratio for video tape recorders*

IEC 61041-1:1990, *Non-broadcast video tape recorders – Methods of measurement – Part 1: General, video (NTSC/PAL) and audio (longitudinal) characteristics*

IEC 61041-5:1997, *Non-broadcast video tape recorders – Methods of measurement – Part 5: High-band video tape recorders including those equipped with Y/C video connectors (NTSC/PAL)*

IEC 61834 (all parts), *Recording – Helical-scan digital video cassette recording system using 6,35 mm magnetic tape for consumer use (525-60, 625-50, 1125-60 and 1250-50 systems)*

ITU-R BT.471-1:1986, *Nomenclature and description of colour bar signals*

ITU-R BT.500-10:2000, *Methodology for the subjective assessment of the quality of television pictures*

ITU-R BT.1204:1995, *Measuring methods for digital video equipment with analogue input/output*

3 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

3.1

consumer-use digital VTR

consumer-use video tape recorder using digital recording technology, 6,35 mm to 12,65 mm width videotape and bandwidth compression technology for the image signal. Two tape formats are standardized, as defined in the following two definitions. Although different formats may be introduced in the future, fundamental measuring methods can be adapted to all formats

3.1.1

DV format

6,35 mm helical-scan VTR standardized in IEC 61834

3.1.2

D-VHS format

12,65 mm helical-scan VTR which will be standardized in the near future. Until then, refer to the outline of the D-VHS format in documents [1]¹ and [2]

3.2

ferrofluid development

direct observation of the magnetization on the videotape by the adherence of iron powder to its surface by dipping the tape into a fluid containing powder of fine iron in order to observe the recorded pattern using a microscope

3.3

byte

unit which separates the information series 1 into m bits. m usually consists of 8 bits, but not always

3.4

error rate

ratio of the number of erroneous elements to the total number of elements reproduced and/or transmitted during a given time interval

NOTE 1 The elements may be, for example, digits, code words or blocks.

NOTE 2 "Error ratio" is defined in similar terms as in IEC 704-18-03.

3.5

byte error rate

error rate for a signal constructed from byte units

(number of erroneous byte units)/(total number of elements of byte units)

3.6

MPEG-2 transport stream

MPEG-2 TS

data transmission format standardized by ISO/IEC MPEG (Moving Picture image coding Experts Group)

3.7

three dimensional (3D) signal processing

TV video signal process taken from three viewpoints: the horizontal and vertical directions and the time domain. Generally, it contains the operation processing between the fields or between frames using a field memory or a frame memory

¹ Figures in square brackets refer to the Bibliography.

3.8

audio operational output voltage

standard output voltage specified by the manufacturer for the audio analogue signal interface between equipment when the output terminal is terminated by a specified load impedance

3.9

audio operational input voltage

input voltage specified by the manufacturer to generate the audio operational output voltage at the output terminal

3.10

audio maximum output voltage

maximum audio output voltage that a VTR under test can generate. In this standard, it is the voltage for an output signal of 3 % harmonic distortion, or it can be the voltage just before clipping when the output signal is digitally clipped

4 Measuring conditions

4.1 General

All measurements shall be carried out in the environmental conditions specified by the manufacturer.

If not otherwise stated by the manufacturer or by the format standard, the device under test shall be conditioned for at least 3 h before measurement begins. An adequate warm-up time may be used instead of 3 h conditioning.

The environmental conditions during measurement, at least the temperature and the relative humidity, shall be recorded together with the presentation of the results of the measurements.

4.2 Environmental conditions

The environmental conditions for the measurements shall be:

Ambient temperature: $20^{\circ}\text{C} \pm 1^{\circ}\text{C}$

Relative humidity: $50\% \pm 2\%$

Air pressure: $96\text{ kPa} \pm 10\text{ kPa}$

Ambient temperature can be within a range of 5°C and 35°C , and relative humidity within a range of 45 % and 75 % if these tolerances do not affect the results of measurement. Record the temperature and humidity at the time of measurement along with the results of the measurement.

4.3 Power supply

Use the power supply that conforms to the power requirements for the VTR under test. Voltage regulation shall be $\pm 2,5\%$ or better. The frequency fluctuation shall be $\pm 1\%$ or better and the harmonic content shall be 2 % or less.

4.4 Test signal

Use the test signals specified below for measurement.

4.4.1 Video test signal

Use a video test signal which has a 100 % amplitude level white signal of 4 μs inserted in every horizontal period so that the results of measurement do not include errors caused by disturbance of the video AGC circuitry of the VTR under test. A video test signal which contains

the 100 % level white signal over eight horizontal video periods inserted in every vertical blanking period may be used as an alternative.

4.4.2 Colour bar signal

Use the standard colour bar signal that conforms to the ITU-R BT.471-1 type (b).

4.4.3 Video input signal for measuring audio characteristics

When measuring the audio characteristics for analogue in and analogue out, the colour bar signal of 4.4.2 shall be applied to the VTR and recorded simultaneously with an audio test signal to stabilize the VTR synchronization.

4.5 Measuring instruments

4.5.1 Noise meter

Frequency bandwidth

Luminance:	0,1 kHz to 10 MHz
Chrominance:	3,58 MHz $\pm$ 1,5 MHz (NTSC)
	4,43 MHz $\pm$ 1,5 MHz (PAL)

Cut-off frequency

HPF:	0,1/100 kHz
LPF:	0,5/3,0/4,2/6,0 MHz/TROUGH

Input signal

For luminance S/N:	white signal with superimposed signal (level of 230 mVp-p or less)
For chrominance S/N:	white signal with superimposed single colour signal, modulated carrier

Measuring method

Luminance:	0 dB = 0,714 V (RMS value) for NTSC
	0 dB = 0,700 V (RMS value) for PAL.
Chrominance AM noise:	RMS value of detected AM noise
Chrominance PM noise:	RMS value of detected PM noise

Gated noise position: Not gated until 4 μ s before rising edge of white signal

Output noise signal: Not saturated by the input signals specified above

Input terminal: Composite video input terminal and Y/C separate
signal input terminal such as S Video terminal

4.5.2 Audio signal generator

Frequency range:	4 Hz to 20 kHz in sinusoidal wave form
Output voltage:	Not less than 2 V
Total harmonic distortion:	Less than 0,001 % in the frequency range of 20 Hz to 20 kHz

4.5.3 Audio level meter

This meter shall measure the true root mean square voltage of an a.c. waveform. But an a.c. voltmeter with the scaling of root mean square value that measures the average value of rectified voltage is applicable for the measurements of sinusoidal waveform voltage.

Accuracy: Within ± 2 % in the frequency range of 4 Hz to 20 kHz
 Range: –90 dB(V) to +20 dB(V)

4.5.4 Audio mixed frequency oscillator

This instrument shall generate a waveform of two sinusoidal signals that are mixed in a specific ratio. Total harmonic distortion of each sinusoidal signal shall be less than 0,001 %.

4.5.5 Audio harmonic distortion meter

This meter shall measure residual harmonic and noise components with the exception of the fundamental component.

Indication accuracy: Within ± 3 %
 Minimum measurable value: Less than 0,001 % (The full-scale is 0,01 %)
 Input impedance: More than 100 k Ω

4.6 Video test tape

Use the video test tape which conforms to the video tape specifications of the VTR under test. Record the type of the tape and the name of the manufacturer of the tape with the results of measurement.

5 Methods of measurement for mechanical characteristics

5.1 General

The calibration tape that is prepared by the format supplier can confirm general interchangeability.

The tape pattern of a digital VTR is the same helical-scan system as that used in an analogue VTR, and can be observed by ferrofluid development. Digital VTR has a different tracking system from existing systems and has a high-density recording system. The measuring conditions will be clarified and the means of obtaining high measurement accuracy will be described.

5.2 Tape speed

To obtain the tape speed, observe the magnetization pattern of the tape by a ferrofluid developed tape on which a specified test signal is recorded.

5.2.1 Test signal

- a) For DV format:
 The test signal shall be a sinusoidal waveform whose wavelength is about 1,6 μm on the tape. In the case of the DV format 9 000 min^{-1} system, the frequency is 6 MHz.
- b) For D-VHS format:
 The test signal shall be a MPEG-2 TS.

5.2.2 Measurement

Record the test signal and develop the tape by the ferrofluid development. Then using a microscope, observe the magnetized pattern along the longitudinal line in the middle of the tape for more than 30 mm. Obtain the same azimuth track interval p using the following

equation and referring to figure 2. For the D-VHS format, obtain the CTL pulse pitch p in the same way.

$$p = \frac{l}{n} \quad \text{mm}$$

where

l is the distance of the measurement;

n is the number of the same azimuth tracks (or the number of the CTL pulses) over the distance l .

Use the following equation to obtain the tape speed v :

$$v = \frac{p}{p_r} \times v_r \quad \text{mm/s}$$

where, for the DV format

Reference pitch per 2 tracks	$p_r = 2 \times 10 \times 10^{-3} / \sin(\theta_r)$	mm
Track angle	$\theta_r = 9,1668^\circ$	
Reference speed	$v_r = 18,831/1,001$	mm/s for NTSC
	18,831	mm/s for PAL

For the D-VHS format:

p_r , θ_r , v_r : refer to the D-VHS format.

If the VTR under test can be operated at more than one tape speed, measurements shall be repeated at each of the speeds and the mode used for each test shall be stated.

5.2.3 Presentation of the results

Tape speed: mm/s (mode)

5.3 Flatness of the RF envelope

This is the ratio of the minimum amplitude of the RF envelope at the head amplifier output with respect to the maximum amplitude.

5.3.1 Test signal

- For DV format, the test signal shall be the colour bar signal of 4.4.2.
- For D-VHS format, the test signal shall be a MPEG-2 TS.

5.3.2 Block diagram

See figure 3.

5.3.3 Measurement

Record and reproduce the test signal, and observe the RF signal at the head amplifier output on the oscilloscope. Obtain the maximum amplitude of the RF envelope, $e_{\max}$, and the minimum amplitude, $e_{\min}$ (figure 4).

The flatness of the RF envelope is:

$$\text{Flatness} = \frac{e_{\min}}{e_{\max}} \times 100 \quad \%$$

5.3.4 Presentation of the result

Flatness of the RF envelope: %

5.4 Linearity

This measurement determines the track displacement using the ferrofluid development method, using the cross-tape track measurement technique which has been used for conventional analogue VTRs.

5.4.1 Test signal

- a) For the DV format, the test signal shall be a sinusoidal waveform whose wavelength is about $1,6 \mu\text{m}$ on the tape. In the case of the DV format $9\,000 \text{ min}^{-1}$ system, the frequency is 6 MHz.
- b) For the D-VHS format, the test signal shall be an MPEG-2 TS.

5.4.2 Measurement

Record the test signal and develop the recorded tape by a ferrofluid. Measure the cross-tape track height $h_1, h_2, \dots, h_n$ of the even track from the reference position (see figure 5 for the DV format; figure 6 for the D-VHS format). Obtain each of the track location errors (linearity error) using the following equation.

$$\begin{aligned}\Delta h_1 &= (h_1 - h_r) \cos \theta_r \\ \Delta h_2 &= (h_2 - 2 \times h_r) \cos \theta_r \\ &\vdots \\ \Delta h_n &= (h_n - n \times h_r) \cos \theta_r\end{aligned}$$

where

Δh_n is the track location error, in μm

θ_r is the reference track angle, in $^\circ$

h_r is the reference cross-section track pitch (for 2 tracks)

$$h_r = 2 \times T_p \times \frac{1}{\cos \theta_r} \times \frac{v}{v_r} \mu\text{m}$$

v is the actual tape speed in mm/s

v_r is the reference tape speed in mm/s

For the DV format:

$$\theta_r = 9,1668^\circ$$

$$\begin{aligned}v_r &= 18,831/1,001 \text{ mm/s} && \text{for NTSC} \\ &= 18,831 \text{ mm/s} && \text{for PAL}\end{aligned}$$

$$T_p = 10 \mu\text{m}$$

For the D-VHS format:

θ_r, v_r, T_p : refer to the D-VHS format.

The track location error ($\Delta h_1, \Delta h_2 \dots \Delta h_n$) shall be observed as shown in figure 7 and the peak-to-peak value shall be obtained.

5.4.3 Presentation of the results

Linearity: μm p-p

5.5 Effective area starting position

This is the starting position of the track from the lower edge of the tape.

5.5.1 Test signal

- a) For the DV format, the test signal shall be the colour bar signal of 4.4.2.
- b) For the D-VHS format, the test signal shall be an MPEG-2 TS.

5.5.2 Measurement

Record the test signal and develop the recorded tape by a ferrofluid. Measure the distance from lower edge of the tape to the track starting position, as shown in figure 8.

The track starting position is:

- the front of the ITI signal for the DV format system,
- the front of the sub-code signal for the D-VHS format system.

5.5.3 Presentation of the results

Starting position: mm

5.6 Track displacement measurement by image processing

A new and more reliable technique for measuring track displacement of high-density recorded tape is presented here. An experimental report is given in the paper listed in the bibliography under [3].

5.6.1 Measurement system

Figure 9 shows the block diagram of the measurement system. A tape that has been developed with a ferrofluid is focused on a CCD (charge coupled device) camera through a microscope. The tape is placed on a table that can move in the x and y directions, be rotated, and is illuminated with a light source. The tape is adjusted so that the longitudinal direction of the tape coincides with the x-axis of the table and x-axis of the CCD camera. The microscope magnifies and focuses on the image of the tape so that an effective width of the tape is adjusted to the width of the active image area of the CCD camera. A light from the light source illuminates the tape, and reflection from the surface of the tape goes towards the CCD camera. The CCD camera output is stored in a frame grabber controlled by a computer. The computer calculates the entire image processing, controls the table with a table controller, and transfers the image to the frame grabber and the output to a printer and a monitor.

5.6.2 Image processing technique

The tape of a digital VTR is recorded so that the tracks have the same azimuth angle on every second track. When the tape is illuminated with a light source from a specified direction that depends on the optical set-up of the microscope, the reflection from only the tracks that have the same azimuth angle go into the CCD camera. Every other track is observed brightly, so the image of the tape is a grid of bright and dark stripes (see figure 10 a)).

Figure 10 b) shows a waveform of an intensity distribution cutting out the image on arbitrary x-coordinate of the tape (the origin of the Y-axis is the effective area lower edge). One wavelength is equal to the pitch of two tracks in the direction of the tape's width (y direction). In

this example, the waveform of an intensity distribution does not have a constant wavelength, because some tracks of the tape are displaced.

The Fourier transform of the waveform of the intensity distribution is computed, and Fourier spectra with some harmonics are obtained (see figure 10 c)).

The first harmonic together with its sidebands is extracted from the Fourier spectra, and is subjected to an inverse Fourier transform (see figure 10 d) and e)).

A waveform that is reproduced from inverse Fourier transform has real and imaginary parts without low and high frequency components (see figure 10 f)).

The phase angle $\phi(y)$ of the waveform of the intensity distribution is obtained at each pixel by computing an arctangent of the ratio of the imaginary part to the real part of the reproduced signal (see figure 10 g) and h)).

The differences between the actual phase angle $\phi(y)$ obtained by the process in g) and the calculated theoretical phase angle $\phi_r(y)$, are the displacement values of the track. The theoretical phase angle $\phi_r(y)$;

$$\phi_r(y) = \pi \times y / h_r$$

where h_r is one pitch of the track in the direction of the tape's width (see 5.4.2 and figure 10 i)).

The track displacement $\Delta h(y)$ is obtained for each pixel on an arbitrary x-coordinate of the image as follows;

$$\Delta h(y) = h_r \times (\phi(y) - \phi_r(y)) \times \cos \theta_r / \pi$$

where θ_r is the track angle (see 5.4.2 and figure 10 j)).

Thus, by proceeding from b) to j) in figure 10 for each x-coordinate of the image of the tape, the track displacement is computed for each pixel of the whole image.

This technique gives a two-dimensional displacement distribution of the tracks on the tape with a high measurement accuracy. This has been achieved because it has not been necessary to move the tape in the tape width direction by moving the table, which is the main cause of measurement error of the conventional technique. It also reduces the low and high frequency noises by smoothly translating the track position into the phase angle.

5.6.3 Measuring results

Some images, obtained by taking several images of the tape surface relative to the longitudinal direction of the tape, are subjected to the same image processing technique (see 5.4). The two-dimensional displacement distribution of the tape in the area including one whole track is obtained (see figure 11 a)).

The track displacement distribution in the direction of the tape's width is measured in the same way as the conventional technique (cross-tape track measurement technique), which gives the displacement by cutting out the data from the two-dimensional track displacement distribution (see figure 11 b)).

The track displacement distributions in the longitudinal direction of the track and in the longitudinal direction of the tape are also obtained (see figures 11 c) and d)). These track displacement distributions are not obtainable by using the conventional technique. It is possible to clarify the whole track displacement distribution and time-course changes of the displacement.

Figure 12 shows an example of calculated results for a track displacement distribution of a digital VTR, displayed on a monitor.

6 Video characteristics (analogue input/output)

6.1 General

As for base band analogue input and output, conventional measurement methods (of the analogue type) are available. Measuring instruments for analogue signals can be used in general waveform measurement.

The IEC has standardized the measurement methods for analogue video characteristics as in IEC 61041-1 and IEC 61041-5. Most of the items can be measured using these methods.

The quantization error at the stage of AD conversion has been detailed for broadcast use, and some methods are recommended in ITU-R BT.1204. For consumer VTR, this error appears to be the same as in broadcast VTR. In order to measure a signal-to-noise ratio precisely, it is desirable to apply the method described in ITU-R BT.1204.

A flat signal is used for this noise measurement, and the measured value is different from the one obtained when using a natural picture. To evaluate the noise, which is the difference between the input and output signals including the influence of the compression process, the picture quality measurement method of ITU-R BT.500-10 shall be used.

6.2 Luminance amplitude frequency response

For this measurement, subclause 2.3 of IEC 61041-1, is applicable.

The following test signal shall be used, because the signal bandwidth for digital VTR is wider than that of a conventional VTR.

6.2.1 Test signal

The test signal shall be a sine-wave multiburst signal with or without a chrominance burst according to figure 13.

- a) For composite video input, see figure 13.
- b) For S video input:
 - S luminance signal: use only the luminance portion of the test signal shown in figure 13;
 - S chrominance signal: use only the colour burst of the test signal shown in figure 13.

6.2.2 Block diagram

The block diagram for measurement shall be as follows:

- a) for composite video input, see figure 14;
- b) for S video input, see figure 15.

6.2.3 Measurement

The reference level $V_{\text{ref(a)}}$ shall be 100 % of the amplitude of the 100 % white output picture signal, i.e. from the blanking level to the white level.

The peak-to-peak amplitude $V_{\text{p-p}}$ of each frequency burst of the output signal shall be put in relation with the reference level $V_{\text{ref(a)}}$ to obtain the amplitude/frequency response A :

$$A = 20 \lg \frac{V_{p-p}}{V_{ref(a)}} \text{ dB}$$

6.2.4 Presentation of results

The results of measurement of the composite video signal and the S video signal shall be reported in a table showing the frequency in MHz and A in dB.

6.3 Chrominance amplitude frequency response

This measurement gives the amplitude/frequency response of the chrominance channel.

6.3.1 Test signal

The test signal shall be a 50 % white level superimposed on five frequency bursts having a peak-to-peak amplitude of 100 % with a chrominance burst according to figure 16. The frequencies f_1 to f_4 of the bursts are correlated with the colour sub-carrier frequency f_{sc} as follows.

$$\begin{aligned} f_1 &= f_{sc} - 50 f_h \\ f_2 &= f_{sc} - 25 f_h \\ f_3 &= f_{sc} + 25 f_h \\ f_4 &= f_{sc} + 50 f_h \end{aligned}$$

where f_h is the horizontal line frequency.

- a) For the composite video input, see figure 16.
- b) For the S video input:
 - S luminance signal: use only the luminance portion of the test signal shown in figure 16.
 - S chrominance signal: use only the colour portion of the test signal shown in figure 16.

6.3.2 Block diagram

The block diagram for measurement shall be as follows:

- a) for the composite video input, see figure 14;
- b) for the S video input, see figure 15.

6.3.3 Measurement

The reference level $V_{ref(a)}$ shall be 100 % of the amplitude of the burst, with the frequency f_{sc} measured in the middle of the burst.

The peak-to-peak amplitude V_{p-p} of each frequency burst measured in the middle of the burst shall be put in relation with the reference level $V_{ref(a)}$ to obtain the amplitude/frequency response B :

$$B = 20 \lg \frac{V_{p-p}}{V_{ref(a)}} \text{ dB}$$

6.3.4 Presentation of results

The results of the measurement of the composite video signal and the S video signal shall be reported in a table showing the frequency deviation from f_{sc} in kHz and B in dB.

6.4 Luminance diagonal resolution

Refer to IEC 61041-5, 2.4.

6.5 Luminance frequency characteristics of diagonal resolution (i)

Refer to IEC 61041-5, 2.5.

6.6 Luminance frequency characteristics of diagonal resolution (ii)

Refer to IEC 61041-5, 2.6.

6.7 Luminance non-linear distortion

For this measurement, IEC 61041-1, 2.4 is applicable.

For a VTR equipped with an S video connector, only the luminance portion and only the colour burst portion of the test signal, shown in figure 17, shall be used for this measurement.

6.8 Luminance waveform distortion (linear distortion)

For this measurement, IEC 61041-1, 2.5 is applicable.

For a VTR equipped with an S video connector, a specific portion of the test signal in figure 18 and the luminance output of S video terminal shall be used for this measurement.

- a) For the luminance input at the S video terminal: apply only the luminance signal.
- b) For the chrominance input at the S video terminal: apply only the colour burst signal.

6.9 Chrominance waveform distortion

This measurement defines the waveform distortion of the reproduced envelope of the chrominance signal.

6.9.1 Test signal

The test signal for measurement shall be as follows:

- a) for the composite video input, see figure 19.
- b) for the S video input:
 - S luminance signal: use only the luminance portion of the test signal shown in figure 19.
 - S chrominance signal: use only the colour burst of the test signal shown in figure 19.

6.9.2 Block diagram

The block diagram for measurement shall be as follows:

- a) for the composite video input, see figure 14;
- b) for the S video input, see figure 15.

6.9.3 Measurement

Record and reproduce the test signal as illustrated in figure 19.

Apply the reproduced signal obtained from the composite video output connector or S video output connector to the oscilloscope, and observe the waveform.

Calculate the measurement result using the following formulae in accordance with figure 20, and show results as percentages.

$$\text{Overshoot} = \frac{b}{a} \times 100 (\%)$$

$$\text{Streaking} = \frac{b}{a} \times 100 (\%)$$

$$\text{Smear} = \frac{b}{a} \times 100 (\%)$$

$$\text{Rise time} = t_1$$

$$\text{Fall time} = t_2$$

6.9.4 Presentation of results

Overshoot:	%
Streaking:	%
Smear:	%
Rise time:	s
Fall time:	s

6.10 Luminance vertical waveform distortion

Refer to IEC 61041-5, 2.3.

6.11 Chrominance vertical waveform distortion

Refer to IEC 61041-5, 3.3.

6.12 Automatic Gain Control (AGC) operation

For this measurement, IEC 61041-1, 2.2 is applicable.

For a VTR equipped with an S video connector, a specific portion of the test signal in figure 17 and the luminance output of the S video terminal shall be used for this measurement.

- For the luminance input at the S video terminal: apply only the luminance signal.
- For the chrominance input at the S video terminal: apply only the colour burst signal.

6.13 Chrominance to luminance horizontal displacement

Refer to IEC 61041-1, 3.5.

6.14 Chrominance to luminance vertical displacement

Refer to IEC 61041-5, 3.2.

6.15 Luminance signal-to-noise ratio

6.15.1 General

For this measurement, IEC 61041-5, 2.1 is applicable.

For a digital VTR, the value of S/N may be widely dispersed because of the quantization error. In such a case, both the maximum and the minimum values shall describe the result.

To evaluate the dispersion, it is desirable to take several measurements, whilst changing the white level of the test signal intermittently. The signal-to-noise ratio is measured at each level under equal interval step within quantization step. In practice, it is not easy to follow the above procedure. Repeated measurements for a sufficient period of time by randomly changing the white level gives the maximum/minimum S/N in practice.

6.15.2 Test signal

The test signal shall be as follows:

- a) for the composite video input, see figure 21;
- b) for the S video input, see figures 22 and 23.

6.15.3 Block diagram

The block diagram for the measurements shall be as follows:

- a) for the composite video input, see figure 24;
- b) for the S video input, see figure 25.

6.15.4 Measurement

For a VTR equipped with a composite video connector, the composite video test signal shall be as shown in figure 21.

For a VTR equipped with an S video connector, the S luminance and S chrominance test signal shall be as shown in figures 22 and 23.

Using a colour noise meter according to IEC 60883, measure the signal-to-noise ratio of the luminance signal. The setting for the colour noise meter shall be as follows:

Table 1 – Setting of the colour noise meter for luminance measurement

	Composite video signal	S video signal
HPF	100 kHz	100 kHz
LPF	6 MHz	6 MHz
SC trap	On	Off
Weight	Off	Off

Practical measurement method

- a) Adjust the colour noise meter.
- b) Adjust the test signal to the first input level.
- c) Record and reproduce the test signal and read the colour noise meter.
- d) Change the input level.
- e) Record and reproduce the test signal and read the colour level meter.
- f) Repeat the procedures d) and e) a sufficient number of times.
- g) Find the highest and lowest points, if the S/N ratio is not even.

Table 2 – Example: white level of test signal (8 bit system)

White level	For NTSC	For PAL
40 %	0,286 V	0,280 V
42 %	0,300 V	0,294 V
44 %	0,314 V	0,308 V
46 %	0,328 V	0,322 V
48 %	0,343 V	0,336 V
50 %	0,357 V	0,350 V
52 %	0,371 V	0,364 V
54 %	0,386 V	0,378 V
56 %	0,400 V	0,392 V
58 %	0,414 V	0,406 V
60 %	0,428 V	0,420 V
NOTE 1 White level is incremented by 2 % steps within ± 10 % of the centre level according to IEC 61041-5, 2.1. Where 100 % white level is 0,714 Vp-p for NTSC and 0,700 Vp-p for PAL.		
NOTE 2 The absolute value of the white level is not specified.		

6.15.5 Presentation of the results

Presentation of the results shall be as follows:

- The composite video connector

Luminance S/N:	dB	or	Maximum	dB
			Minimum	dB
- The S video connector

Luminance S/N:	dB	or	Maximum	dB
			Minimum	dB

6.16 Chrominance signal-to-noise ratio

6.16.1 General

For this measurement, IEC 61041-5, 3.1 is applicable.

For a digital VTR, the value of S/N may be widely dispersed because of the quantization error. In such a case, both the maximum and the minimum values shall describe the result.

To evaluate the dispersion, it is desirable to take several measurements whilst changing the chrominance level of the test signal intermittently. The signal-to-noise ratio is measured at each level under equal interval step within quantization step. In practice, it is not easy to follow the above procedure. Repeated measurements for a sufficient period of time by randomly changing the chrominance level gives the maximum/minimum S/N in practice.

6.16.2 Test signal

The test signal for measurement shall be as follows:

- a) for the composite video input, see figure 26;
- b) for the S video input, see figures 27 and 28.

6.16.3 Block diagram

The block diagram for the measurements shall be as follows:

- a) for the composite video input, see figure 24.
- b) for the S video input, see figure 25.

6.16.4 Measurement

Record and reproduce the test signal. Apply the test signal from the composite video output connector or S video output connector to the colour noise meter.

The setting for the colour noise meter shall be as follows:

Table 3 – Setting of the colour noise meter for chrominance measurement

Filter	Cut off frequency
HPF	100 Hz
LPF	500 kHz
NOTE Hue compensation: on (for NTSC only. Set to the optimum position)	

Practical measurement method

- a) Set the colour noise meter.
- b) Adjust the input chrominance level
- c) Record and reproduce the test signal and read the AM and PM noises on the colour noise meter.
- d) Change the input level.
- e) Record and reproduce the test signal and read the AM and PM noises on the colour noise meter.
- f) Repeat the procedures d) and e) a sufficient number of times.
- g) Find the highest point and the lowest point, if the S/N ratio is not regular.

Table 4 – Example: Chrominance level of test signal (8 bit system)

for NTSC		for PAL	
83 %	0,592 Vp-p	90 %	0,630 Vp-p
84 %	0,600 Vp-p	91 %	0,637 Vp-p
85 %	0,607 Vp-p	92 %	0,644 Vp-p
86 %	0,614 Vp-p	93 %	0,651 Vp-p
87 %	0,621 Vp-p	94 %	0,658 Vp-p
88 %	0,628 Vp-p	95 %	0,665 Vp-p
89 %	0,635 Vp-p	96 %	0,672 Vp-p
90 %	0,643 Vp-p	97 %	0,679 Vp-p
91 %	0,650 Vp-p	98 %	0,686 Vp-p
92 %	0,657 Vp-p	99 %	0,693 Vp-p
93 %	0,664 Vp-p	100 %	0,700 Vp-p
NOTE 1 The chrominance level is changed by 1 % (≤ 1 %) steps within ± 5 % ($\leq \pm 10$ %) of the centre level according to IEC 61041-5, 3.1, where 100 % chrominance ($\leq$ white) level is 0,714 Vp-p for NTSC and 0,700 Vp-p for PAL.			
NOTE 2 The absolute value of chrominance (white) level is not specified.			

6.16.5 Presentation of the results

The presentation of the results shall be as follows:

– The composite video:

AM colour S/N:	dB	or	Maximum:	dB
			Minimum:	dB
PM colour S/N:	dB	or	Maximum:	dB
			Minimum:	dB

– The S video:

AM colour S/N:	dB	or	Maximum:	dB
			Minimum:	dB
PM colour S/N:	dB	or	Maximum:	dB
			Minimum:	dB

7 Composite signal decoding characteristics (luminance and chrominance separation)

NOTE This clause is applicable only to the NTSC system.

7.1 Luminance signal separation (general)

Refer to IEC 61041-5, 4.1.

7.2 Luminance signal separation at colour change points

Refer to IEC 61041-5, 4.2.

7.3 Chrominance signal separation

Refer to IEC 61041-5, 4.3.

7.4 Chrominance signal separation with three dimensional processing

This measurement determines the ratio of the luminance signal level to the standard chrominance signal which are mixed in the chrominance signal at the S output terminal when a composite video signal is applied to a three dimensional Y/C separator.

7.4.1 Test signal

The test signal shall be a multiburst signal as shown in figure 29.

The multiburst signal shifts 70 ns in the horizontal direction at every field, and comes back to the original position after 280 ns shift.

7.4.2 Block diagram

Refer to figure 30.

7.4.3 Measurement

Connect the oscilloscope to the S chrominance output connector and set the video tape recorder to record mode. Observe the colour burst and the luminance signal that remain in the S chrominance signal.

Measure the V_b (Vp-p) level of the colour burst and the levels of the residual luminance signal V_y (Vp-p) corresponding to the luminance frequencies of 3,0 MHz, 3,58 MHz, and 4,2 MHz.

Use the following equation to obtain the chrominance signal separation characteristics. Refer to figure 31.

$$\text{Chrominance signal separation} = 20 \lg \left(0,40 \times \frac{V_y}{V_b} \right) \text{ dB}$$

7.4.4 Presentation of results

The presentation of the results shall be as follows.

Chrominance signal separation	at 3,00 MHz	dB
(residual luminance signal level)	at 3,58 MHz	dB
	at 4,20 MHz	dB

7.5 Luminance signal separation with three dimensional signal processing

This measurement determines the ratio of the standard luminance signal level to the chrominance (dot interference) signal, which are mixed in the luminance signal at the S output terminal when the composite video signal is applied to a three dimensional Y/C separator.

7.5.1 Test signal

The test signal shall be a colour-sweep signal as shown in figure 32.

The colour-sweep signal shifts 70 ns in the horizontal direction at every field, and comes back to the original position after a 280 ns shift.

7.5.2 Block diagram

See figure 33 for the block diagram for measurement.

7.5.3 Measurement

Connect the oscilloscope to the S luminance output connector, and set the video tape recorder to record mode. Observe the level of the S luminance signal V_s (Vp-p) and the residual chrominance signal V_c (Vp-p) at the S video output connector.

Use the following equation to obtain the luminance signal separation characteristic. Refer to figure 34.

$$\text{Residual chrominance signal characteristic} = 20 \lg \left(\frac{100}{88} \times \frac{V_c}{V_s} \right) \text{ dB}$$

7.5.4 Presentation of results

The presentation of the results shall be as follows:

Residual chrominance signal characteristic (dot interference):	dB
--	----

8 Audio characteristics (analogue input/output)

8.1 General

The internal audio signal processing of the DV format consists of digital 16 bit linear coding or 12 bit non-linear coding, but in these methods of measurement, only analogue input and output signals through AD/DA converters are used. The general measuring method of an analogue

tape recorder (IEC 60094-3, clause 12) is applicable. A signal level and frequency suitable for the digital VTR shall be specified.

8.2 Audio operational output voltage (with AGC)

8.2.1 Test signal

The test signal shall be a 1 kHz sinusoidal wave.

8.2.2 Block diagram

See figure 35 for the block diagram for measurement.

8.2.3 Measurement

If the VTR under test has an AGC, record the test signal of an operational input level specified by the manufacturer. Reproduce the recorded signal, and measure the output voltage from the output terminal with a specified load impedance.

The measurements shall be made for both audio channels.

8.2.4 Presentation of results

The presentation of the results shall be as follows:

Audio operational output voltage (with AGC): mV

The measurements shall be made for both audio channels.

8.3 Audio operational input voltage (without AGC)

8.3.1 Test signal

The test signal shall be a 1 kHz sinusoidal wave.

8.3.2 Block diagram

See figure 35 for the block diagram for measurement.

8.3.3 Measurement

Adjust the setting of the volume control to the indicated position. Record and reproduce the test signal and measure the input voltage when the reproduced output voltage has to be the operational voltage specified by the manufacturer.

8.3.4 Presentation of results

The presentation of the results shall be as follows:

Audio operational input voltage (without AGC): mV

The measurements shall be made for both audio channels.

8.4 Audio maximum output voltage

8.4.1 Test signal

The test signal shall be a 1 kHz sinusoidal wave.

8.4.2 Block diagram

See figure 35 for the block diagram for measurement.

8.4.3 Measurement

When the VTR under test has an AGC circuit, turn off the AGC and increase the test signal input level gradually, and measure the output level when it has a distortion of 3 %.

If the output signal waveform is observed with an oscilloscope to clip symmetrically, it is also good if a maximum output level is achieved before clipping.

8.4.4 Presentation of results

Maximum output voltage: V

8.5 Amplitude frequency response

8.5.1 Test signal

Use the sinusoidal signals with the specified level of audio operation input voltage and with the following frequencies:

4 Hz, 8 Hz, 20 Hz, 31,5 Hz, 63 Hz, 125 Hz, 250 Hz, 500 Hz, 1 kHz, 2 kHz, 4 kHz, 8 kHz, 10 kHz, 12,5 kHz, 16 kHz, 18 kHz and 20 kHz.

8.5.2 Measurement

Refer to IEC 60094-3, 12.3.1.

It is recommended to turn off the AGC.

8.6 Phase difference between channels

8.6.1 Test signal

For over 44,1 kHz sampling frequency system, use the 20 kHz sinusoidal signal and for 32 kHz sampling system, use 14 kHz.

8.6.2 Measurement

Refer to IEC 60268-3, 14.7.2.

8.6.3 Presentation of results

Phase difference between channels degrees (measuring frequency = kHz).

8.7 Signal-to-noise ratio

Refer to IEC 60094-3, 12.3.2.

The measuring frequency shall be 1 kHz and the input level shall be the specified operational voltage.

8.8 Dynamic range

8.8.1 Test signal

The test signal shall be a 1 kHz sinusoidal wave.

8.8.2 Measurement

Record the test signal so that the output level is 60 dB below the maximum output voltage of 8.4.

Measure the distortion of the reproduced signal by a distortion meter and let the reading A in decibels be an absolute value $|A|$.

$$\text{Dynamic range} = |A| + 60 \text{ dB}$$

The measurement shall be made for both audio channels.

8.8.3 Presentation of results

Dynamic range: dB (channel)

8.9 Harmonic distortion

Refer to IEC 60094-3, 12.3.6.

The test signal shall be a 1 kHz sinusoidal wave of the specified operational voltage.

8.10 Inter-modulation distortion

8.10.1 Test signal

The test signal shall be a mixed frequency signal of 60 Hz and 7 kHz, of a 4:1 amplitude ratio.

8.10.2 Measurement

Record the test signal so that the output level is the maximum output voltage of 8.4.

Measure the reproduced output signal using an inter-modulation distortion meter and observe the spectrum components.

8.10.3 Presentation of result

To be stated as a percentage.

The measurement shall be made for both audio channels.

8.11 Channel separation

8.11.1 Test signals

Test frequencies: 125 Hz, 1 kHz, 4 kHz, 10 kHz and 16 kHz.

Signal level: specified operational voltage.

8.11.2 Measurement

Refer to IEC 60094-3, 12.3.3.

8.11.3 Presentation of results

They shall be presented as a graph or a table of measured channel separation for each frequency.

8.12 Wow-flutter

Refer to IEC 60386.

8.13 Pitch difference between record and playback

8.13.1 Test signal

The test signal shall be a 20 kHz sinusoidal wave.

8.13.2 Measurement

Measure the frequency F_1 of the reproduced 20 kHz signal using a digital frequency counter.

$$\text{Pitch difference} = \frac{F_1 - F_0}{F_0} \times 100 \quad \%$$

where F_0 represents the frequency of the recorded signal.

8.13.3 Presentation of results

To be stated as a percentage.

9 Classification of the characteristics to be specified

The various measurements described in the clauses listed in this standard shall be implemented in accordance with needs of the manufacturer and/or user in order to determine the digital VTR performance. X indicates the important items in table 5. The letter R indicates measurements that may be omitted in assessing the VTR performance.

A = items which are independent of each other and which shall be measured to make a general assessment of a VTR,

B = additional items which may be measured to assess a VTR more precisely,

C = additional items which are less important.

Table 5 – Classification of the characteristics to be specified

Clause/subclause	A	B	C
Mechanical characteristics			
5.2 Tape speed	X		
5.3 Flatness of the RF envelope	X		
5.4 Linearity	X		
5.5 Effective area starting position	X		
5.6 Track displacement measurement by image processing		X	
Video characteristics			
6.2 Luminance amplitude frequency response	X		
6.3 Chrominance amplitude frequency response	X		
6.4 Luminance diagonal resolution		X	
6.5 Luminance frequency characteristics of diagonal resolution (1)		X	
6.6 Luminance frequency characteristics of diagonal resolution (2)		X	
6.7 Luminance non-linear distortion	X		
6.8 Luminance waveform distortion (Linear distortion)	X		
6.9 Chrominance waveform distortion	X		
6.10 Luminance vertical waveform distortion		X	
6.11 Chrominance vertical waveform distortion		X	
6.12 AGC operation	X		
6.13 Chrominance to luminance horizontal displacement	X		
6.14 Chrominance to luminance vertical displacement	X		

Clause/subclause	A	B	C
6.15 Luminance signal-to-noise ratio	X		
6.16 Chrominance signal-to-noise ratio	X		
Composite signal decode characteristics			
7.1 Luminance signal separation (general)	X		
7.2 Luminance signal separation at colour change points	X		
7.3 Chrominance signal separation	X		
7.4 Chrominance signal separation with three dimensional processing			R
7.5 Luminance signal separation with three dimensional signal processing			R
Audio characteristics			
8.2 Audio operational output voltage (with AGC)	X		
8.3 Audio operational input voltage (without AGC)	X		
8.4 Audio maximum output voltage	X		
8.5 Amplitude frequency response	X		
8.6 Phase difference between channels	X		
8.7 Signal-to-noise ratio	X		
8.8 Dynamic range		X	
8.9 Harmonic distortion		X	
8.10 Inter-modulation distortion			R
8.11 Channel separation		X	
8.12 Wow-flutter			R
8.13 Pitch difference between record and playback			R




Figure 1 – Basic block diagram of measurement system




Figure 2 – Measuring method for track interval




Figure 3 – Measuring block diagram for RF envelope flatness




Figure 4 – Measuring method for RF envelope flatness




Figure 5 – Cross-tape track height for DV format




Figure 6 – Cross-tape track height for D-VHS format




Figure 7 – Measuring method for linearity




Figure 8 – Measuring method for the starting position






Figure 9 – Block diagram of the measurement system



IEC 774/02

Figure 10 – Schematic diagram of the image processing technique



IEC 775/02

Figure 11 – Illustration of track displacement distribution (model)




Figure 12 – Example of calculation results

IEC 776/02




Figure 13 – Test signal for luminance amplitude frequency response




Figure 14 – Measuring block diagram for composite video signal




Figure 15 – Measuring block diagram for S video signal




Figure 16 – Test signal for chrominance amplitude frequency response





Figure 17 – Test signal for luminance non-linear distortion



A: 100 %

B: approximately 25 μ s

2T: 0,25 μ s (NTSC)/0,20 μ s (PAL)

Figure 18 – Test signal for luminance waveform distortion






Figure 19 – Test signal for chrominance waveform distortion




$$\text{Amplitude} = \frac{b}{a} \times 100 \%$$

a) Overshoot



$$\text{Amplitude} = \frac{b}{a} \times 100 \%$$


b) Streaking



$$\text{Amplitude} = \frac{b}{a} \times 100 \%$$

$$\text{Fall time} = t_2 \mu\text{s}$$

c) Smear



$$\text{Rise time} = t_1 \mu\text{s},$$

d) Rise and fall time

Figure 20 – Measuring method for chrominance waveform distortion