



INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Secondary cells and batteries containing alkaline or other non-acid electrolytes – Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications –
Part 2: Lithium systems**

**Accumulateurs alcalins et autres accumulateurs à électrolyte non acide –
Exigences de sécurité pour les accumulateurs portables étanches, et pour les batteries qui en sont constituées, destinés à l'utilisation dans des applications portables –
Partie 2: Systèmes au lithium**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.220.30

ISBN 978-2-8322-3910-0

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 Parameter measurement tolerances	10
5 General safety considerations	10
5.1 General.....	10
5.2 Insulation and wiring	11
5.3 Venting	11
5.4 Temperature, voltage and current management	11
5.5 Terminal contacts	11
5.6 Assembly of cells into batteries	12
5.6.1 General	12
5.6.2 Design recommendation	12
5.6.3 Mechanical protection for cells and components of batteries.....	13
5.7 Quality plan	13
5.8 Battery safety components.....	13
6 Type test and sample size	13
7 Specific requirements and tests	14
7.1 Charging procedures for test purposes	14
7.1.1 First procedure	14
7.1.2 Second procedure	14
7.2 Intended use	15
7.2.1 Continuous charging at constant voltage (cells)	15
7.2.2 Case stress at high ambient temperature (battery).....	15
7.3 Reasonably foreseeable misuse.....	15
7.3.1 External short-circuit (cell).....	15
7.3.2 External short-circuit (battery).....	16
7.3.3 Free fall.....	16
7.3.4 Thermal abuse (cells)	16
7.3.5 Crush (cells)	17
7.3.6 Over-charging of battery	17
7.3.7 Forced discharge (cells)	17
7.3.8 Mechanical tests (batteries).....	18
7.3.9 Design evaluation – Forced internal short-circuit (cells)	19
8 Information for safety.....	21
8.1 General.....	21
8.2 Small cell and battery safety information	22
9 Marking	22
9.1 Cell marking.....	22
9.2 Battery marking.....	23
9.3 Caution for ingestion of small cells and batteries	23
9.4 Other information	23
10 Packaging and transport.....	23
Annex A (normative) Charging and discharging range of secondary lithium ion cells for safe use.....	24

A.1	General.....	24
A.2	Safety of lithium ion secondary battery.....	24
A.3	Consideration on charging voltage	24
A.3.1	General	24
A.3.2	Upper limit charging voltage	24
A.4	Consideration of temperature and charging current.....	26
A.4.1	General	26
A.4.2	Recommended temperature range	26
A.4.3	High temperature range	27
A.4.4	Low temperature range	28
A.4.5	Scope of the application of charging current	29
A.4.6	Consideration of discharge	29
A.5	Sample preparation.....	30
A.5.1	General	30
A.5.2	Insertion procedure for nickel particle to generate internal short	30
A.5.3	Disassembly of charged cell	31
A.5.4	Shape of nickel particle	31
A.5.5	Insertion of nickel particle in cylindrical cell	31
A.5.6	Insertion of nickel particle in prismatic cell.....	34
A.6	Experimental procedure of the forced internal short-circuit test	36
A.6.1	Material and tools for preparation of nickel particle	36
A.6.2	Example of a nickel particle preparation procedure	37
A.6.3	Positioning (or placement) of a nickel particle	37
A.6.4	Damaged separator precaution	38
A.6.5	Caution for rewinding separator and electrode	38
A.6.6	Insulation film for preventing short-circuit	39
A.6.7	Caution when disassembling a cell	39
A.6.8	Protective equipment for safety	39
A.6.9	Caution in the case of fire during disassembling	39
A.6.10	Caution for the disassembling process and pressing the electrode core.....	39
A.6.11	Recommended specifications for the pressing device	39
Annex B (informative)	Recommendations to equipment manufacturers and battery assemblers	42
Annex C (informative)	Recommendations to the end-users	43
Annex D (normative)	Measurement of the internal AC resistance for coin cells	44
D.1	General.....	44
D.2	Method	44
Annex E (informative)	Packaging and transport.....	45
Annex F (informative)	Component standards references	46
Bibliography.....		47
Figure 1 – Forced discharge time chart.....		18
Figure 2 – Jig for pressing		21
Figure 3 – Ingestion gauge		22
Figure A.1 – Representation of lithium ion cells operating region for charging.....		25
Figure A.2 – Representation of lithium ion cell operating region for discharging		30
Figure A.3 – Shape of nickel particle.....		31

Figure A.4 – Nickel particle insertion position between positive and negative active material coated area of cylindrical cell	31
Figure A.5 – Nickel particle insertion position between positive aluminium foil and negative active material coated area of cylindrical cell	32
Figure A.6 – Disassembly of cylindrical cell	33
Figure A.7 – Nickel particle insertion position between positive and negative (active material) coated area of prismatic cell.....	34
Figure A.8 – Nickel particle insertion position between positive aluminium foil and negative (active material) coated area of prismatic cell	35
Figure A.9 – Disassembly of prismatic cells	36
Figure A.10 – Dimensions of a completed nickel particle.....	37
Figure A.11 – Positioning of the nickel particle when it cannot be placed in the specified area	38
Figure A.12 – Cylindrical cell	38
Figure A.13 – Distance / time ratio of several types of pressing devices	41
Table 1 – Sample size for type tests	14
Table 2 – Condition of charging procedure.....	15
Table 3 – Conditions for vibration test.....	19
Table 4 – Shock parameters	19
Table 5 – Ambient temperature for cell test.....	20
Table A.1 – Examples of operating region charging parameters	25
Table A.2 – Recommended specifications of a pressing device.....	40
Table F.1 – Component standard references	46

IECNORM.COM : Click to view the full PDF of IEC 62133-2 ed 1.0:2017

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES – SAFETY REQUIREMENTS FOR PORTABLE SEALED SECONDARY CELLS, AND FOR BATTERIES MADE FROM THEM, FOR USE IN PORTABLE APPLICATIONS –

Part 2: Lithium systems

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62133-2 has been prepared by subcommittee 21A: Secondary cells and batteries containing alkaline or other non-acid electrolytes, of IEC technical committee 21: Secondary cells and batteries.

This first edition cancels and replaces the second edition of IEC 62133 published in 2012. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62133:2012:

- separation of nickel systems into a separate Part 1;
- inclusion of coin cell requirements;

- update of assembly of cells into batteries (5.6);
- mechanical tests [vibration, shock] (7.3.8.1, 7.3.8.2);
- insertion of IEC TR 62914 within the Bibliography.

The text of this standard is based on the following documents:

FDIS	Report on voting
21A/620/FDIS	21A/628/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The following different practices of a less permanent nature exist in the countries indicated below.

7.3.9: Design evaluation – Forced internal short-circuit test only applies to Korea, Japan, Switzerland and France.

A list of all parts of the IEC 62133 series, published under the general title *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES – SAFETY REQUIREMENTS FOR PORTABLE SEALED SECONDARY CELLS, AND FOR BATTERIES MADE FROM THEM, FOR USE IN PORTABLE APPLICATIONS –

Part 2: Lithium systems

1 Scope

This part of IEC 62133 specifies requirements and tests for the safe operation of portable sealed secondary lithium cells and batteries containing non-acid electrolyte, under intended use and reasonably foreseeable misuse.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482:2004, *International Electrotechnical Vocabulary – Part 482: Primary and secondary cells and batteries* (available at <http://www.electropedia.org>)

IEC 61960, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary lithium cells and batteries for portable applications*

ISO/IEC Guide 51, *Safety aspects – Guidelines for their inclusion in standards*

SOMMAIRE

AVANT-PROPOS	51
1 Domaine d'application	53
2 Références normatives	53
3 Termes et définitions	53
4 Tolérances de mesure relatives aux paramètres	56
5 Considérations générales de sécurité	57
5.1 Généralités	57
5.2 Isolement et câblage	57
5.3 Échappement de gaz	57
5.4 Gestion de la température, de la tension et du courant	58
5.5 Contacts des bornes	58
5.6 Assemblage des éléments dans les batteries	58
5.6.1 Généralités	58
5.6.2 Recommandation de conception	58
5.6.3 Protection mécanique des éléments et des composants de batteries	59
5.7 Plan qualité	59
5.8 Composants de sécurité de la batterie	59
6 Essai d'homologation et effectif d'échantillon	59
7 Exigences spécifiques et essais	60
7.1 Procédures de charge pour les besoins des essais	60
7.1.1 Première procédure	60
7.1.2 Deuxième procédure	61
7.2 Utilisation prévue	61
7.2.1 Charge continue à tension constante (éléments)	61
7.2.2 Contrainte de moulage du boîtier à température ambiante élevée (batterie)	61
7.3 Utilisation abusive raisonnablement prévisible	62
7.3.1 Court-circuit externe (élément)	62
7.3.2 Court-circuit externe (batterie)	62
7.3.3 Chute libre	62
7.3.4 Température abusive (éléments)	63
7.3.5 Ecrasement (éléments)	63
7.3.6 Surcharge de la batterie	63
7.3.7 Décharge forcée (éléments)	64
7.3.8 Essais mécaniques (batteries)	65
7.3.9 Évaluation de la conception – Court-circuit interne forcé (éléments)	66
8 Informations relatives à la sécurité	68
8.1 Généralités	68
8.2 Informations relatives à la sécurité des éléments et batteries de petite taille	69
9 Marquage	69
9.1 Marquage des éléments	69
9.2 Marquage des batteries	69
9.3 Mise en garde contre l'ingestion des éléments et batteries de petite taille	70
9.4 Autres informations	70
10 Emballage et transport	70

Annexe A (normative) Plage de charge et de décharge des éléments d'accumulateurs lithium ion pour une utilisation en toute sécurité	71
A.1 Généralités	71
A.2 Sécurité des batteries d'accumulateurs lithium ion	71
A.3 Considérations concernant la tension de charge	71
A.3.1 Généralités	71
A.3.2 Limite supérieure de la tension de charge	71
A.4 Considérations relatives à la température et au courant de charge	73
A.4.1 Généralités	73
A.4.2 Plage de températures recommandées	74
A.4.3 Plage de températures élevées	74
A.4.4 Plage de températures basses	75
A.4.5 Domaine d'application du courant de charge	76
A.4.6 Considération relative à la décharge	77
A.5 Préparation de l'échantillon	78
A.5.1 Généralités	78
A.5.2 Procédure d'insertion d'une particule de nickel pour créer un court-circuit interne	78
A.5.3 Démontage de l'élément chargé	78
A.5.4 Forme de la particule de nickel	78
A.5.5 Insertion de la particule de nickel dans l'élément cylindrique	78
A.5.6 Insertion de la particule de nickel dans l'élément parallélépipédique	81
A.6 Procédure expérimentale de l'essai de court-circuit interne forcé	83
A.6.1 Matière et outils pour préparation d'une particule de nickel	83
A.6.2 Exemple de procédure de préparation d'une particule de nickel	84
A.6.3 Positionnement (ou mise en place) d'une particule de nickel	85
A.6.4 Précautions en cas de séparateur endommagé	85
A.6.5 Mise en garde lors du rembobinage du séparateur et de l'électrode	85
A.6.6 Film isolant pour la prévention des court-circuits	86
A.6.7 Mise en garde lors du démontage d'un élément	86
A.6.8 Équipement de protection pour la sécurité	86
A.6.9 Mise en garde en cas de feu lors du démontage	86
A.6.10 Mise en garde lors du processus de démontage et de serrage sous pression du noyau de l'électrode	86
A.6.11 Spécifications recommandées pour le dispositif de pressage	87
Annexe B (informative) Recommandations à l'attention des fabricants d'équipements et assembleurs de batteries	89
Annexe C (informative) Recommandations à l'attention des utilisateurs finaux	90
Annexe D (normative) Mesure de la résistance interne en courant alternatif des éléments boutons	91
D.1 Généralités	91
D.2 Méthode	91
Annexe E (informative) Emballage et transport	92
Annexe F (informative) Références des normes relatives aux composants	93
Bibliographie	94
Figure 1 – Graphique chronologique de la décharge forcée	64
Figure 2 – Gabarit de serrage sous pression	68

Figure 3 – Gabarit d'ingestion	69
Figure A.1 – Représentation de la région de fonctionnement des éléments lithium ion pour la charge.....	72
Figure A.2 – Représentation de la région de fonctionnement d'un élément lithium ion pour la décharge.....	77
Figure A.3 – Forme de la particule de nickel	78
Figure A.4 – Position d'insertion de la particule de nickel entre les zones enduites de matière active positive et négative dans un élément cylindrique.....	79
Figure A.5 – Position d'insertion de la particule de nickel entre la feuille d'aluminium positive et la zone imprégnée de matière active négative de l'élément cylindrique	79
Figure A.6 – Démontage d'un élément cylindrique.....	80
Figure A.7 – Position d'insertion de la particule de nickel entre les zones positive et négative enduites (de matière active) de l'élément parallélépipédique	81
Figure A.8 – Position d'insertion de la particule de nickel entre la feuille d'aluminium positive et la zone enduite (de matière active) négative de l'élément parallélépipédique	82
Figure A.9 – Démontage des éléments parallélépipédiques	83
Figure A.10 – Dimensions de la particule de nickel obtenue.....	84
Figure A.11 – Positionnement de la particule de nickel lorsqu'elle ne peut pas être placée dans la zone spécifiée	85
Figure A.12 – Élément cylindrique	86
Figure A.13 – Rapport distance / durée de plusieurs types de dispositifs de pressage	88
Tableau 1 – Effectif d'échantillon pour essais d'homologation	60
Tableau 2 – Condition de la procédure de charge	61
Tableau 3 – Conditions des essais de vibrations.....	65
Tableau 4 – Paramètres de choc	66
Tableau 5 – Température ambiante pour l'essai d'un élément	66
Tableau A.1 – Exemples de paramètres de charge d'une région de fonctionnement.....	72
Tableau A.2 – Spécifications recommandées pour un dispositif de pressage	87
Tableau F.1 – Références des normes relatives aux composants	93