



IEC 62133

Edition 2.0 2012-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Secondary cells and batteries containing alkaline or other non-acid electrolytes –

Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications

Accumulateurs alcalins et autres accumulateurs à électrolyte non acide –

Exigences de sécurité pour les accumulateurs portables étanches, et pour les batteries qui en sont constituées, destinés à l'utilisation dans des applications portables

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 29.220.30

ISBN 978-2-83220-505-1

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Parameter measurement tolerances	8
5 General safety considerations	8
5.1 General.....	8
5.2 Insulation and wiring	9
5.3 Venting.....	9
5.4 Temperature/voltage/current management	9
5.5 Terminal contacts.....	9
5.6 Assembly of cells into batteries	9
5.6.1 General	9
5.6.2 Design recommendation for lithium systems only.....	10
5.7 Quality plan.....	10
6 Type test conditions	10
7 Specific requirements and tests (nickel systems).....	11
7.1 Charging procedure for test purposes.....	11
7.2 Intended use	12
7.2.1 Continuous low-rate charging (cells).....	12
7.2.2 Vibration.....	12
7.2.3 Moulded case stress at high ambient temperature (batteries)	12
7.2.4 Temperature cycling.....	13
7.3 Reasonably foreseeable misuse	13
7.3.1 Incorrect installation (cells).....	13
7.3.2 External short circuit.....	14
7.3.3 Free fall.....	14
7.3.4 Mechanical shock (crash hazard).....	14
7.3.5 Thermal abuse (cells)	15
7.3.6 Crushing of cells.....	15
7.3.7 Low pressure (cells)	15
7.3.8 Overcharge.....	15
7.3.9 Forced discharge (cells)	16
8 Specific requirements and tests (lithium systems).....	16
8.1 Charging procedures for test purposes	16
8.1.1 First procedure	16
8.1.2 Second procedure	16
8.2 Intended use	17
8.2.1 Continuous charging at constant voltage (cells).....	17
8.2.2 Moulded case stress at high ambient temperature (battery)	17
8.3 Reasonably foreseeable misuse	17
8.3.1 External short circuit (cell).....	17
8.3.2 External short circuit (battery).....	17
8.3.3 Free fall.....	18
8.3.4 Thermal abuse (cells)	18

8.3.5	Crush (cells).....	18
8.3.6	Over-charging of battery	18
8.3.7	Forced discharge (cells)	19
8.3.8	Transport tests	19
8.3.9	Design evaluation – Forced internal short circuit (cells)	19
9	Information for safety.....	21
10	Marking	21
10.1	Cell marking	21
10.2	Battery marking	22
10.3	Other information	22
11	Packaging	22
Annex A (normative)	Charging range of secondary lithium ion cells for safe use	23
Annex B (informative)	Recommendations to equipment manufacturers and battery assemblers	34
Annex C (informative)	Recommendations to the end-users	35
Bibliography		36
Figure 1	– Temperature profile for 7.2.4 – Temperature cycling test.....	13
Figure 2	– Jig for pressing	21
Figure A.1	– Typical of operating region of Li-ion cells with cobalt oxide cathode and carbon anode.....	24
Figure A.2	– Shape of nickel particle.....	28
Figure A.3	– Nickel particle insertion position between positive and negative active material coated area of cylindrical cell	29
Figure A.4	– Nickel particle insertion position between positive aluminum foil and negative active material coated area of cylindrical cell	29
Figure A.5	– Disassembly of cylindrical cell	30
Figure A.6	– Nickel particle insertion position between positive and negative (active material) coated area of prismatic cell.....	31
Figure A.7	– Nickel particle insertion position between positive aluminum foil and negative (active material) coated area of prismatic cell	32
Figure A.8	– Disassembly of prismatic cells	33
Table 1	– Sample size for type tests (nickel systems)	11
Table 2	– Sample size for type tests (lithium systems)	11
Table 3	– Conditions for vibration test.....	12
Table 4	– Condition of charging procedure.....	16
Table 5	– Ambient temperature for cell test ^a	20

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES –

SAFETY REQUIREMENTS FOR PORTABLE SEALED SECONDARY CELLS, AND FOR BATTERIES MADE FROM THEM, FOR USE IN PORTABLE APPLICATIONS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62133 has been prepared by subcommittee 21A: Secondary cells and batteries containing alkaline or other non-acid electrolytes, of IEC technical committee 21: Secondary cells and batteries.

This second edition cancels and replaces the first edition published in 2002. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- update of assembly of cells into batteries (5.5);
- addition of design recommendations for lithium system only (5.6.2);
- separation of nickel systems and lithium systems (Clause 6);

- addition of specific requirements and tests for lithium systems (Clause 8);
- addition of charging of secondary lithium-ion cells for safe use (Annex A).

The text of this standard is based on the following documents:

FDIS	Report on voting
21A/503/FDIS	21A/509/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2

The following difference exists in the countries indicated below:

Subclause 8.3.9: Design evaluation – Forced internal short circuit only applies to Korea, Japan, Switzerland and France.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SECONDARY CELLS AND BATTERIES CONTAINING ALKALINE OR OTHER NON-ACID ELECTROLYTES –

SAFETY REQUIREMENTS FOR PORTABLE SEALED SECONDARY CELLS, AND FOR BATTERIES MADE FROM THEM, FOR USE IN PORTABLE APPLICATIONS

1 Scope

This International Standard specifies requirements and tests for the safe operation of portable sealed secondary cells and batteries (other than button) containing alkaline or other non-acid electrolyte, under intended use and reasonably foreseeable misuse.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482, *International Electrotechnical Vocabulary – Part 482: Primary and secondary cells and batteries*

IEC 61951-1, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Portable sealed rechargeable single cells – Part 1: Nickel-cadmium*

IEC 61951-2, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Portable sealed rechargeable single cells – Part 2: Nickel-metal hydride*

IEC 61960, *Secondary cells and batteries containing alkaline or other non-acid electrolytes – Secondary lithium cells and batteries for portable applications*

ISO/IEC Guide 51, *Safety aspects – Guidelines for their inclusion in standards*

SOMMAIRE

AVANT-PROPOS	40
1 Domaine d'application	42
2 Références normatives	42
3 Termes et définitions	42
4 Tolérances de mesure des paramètres	44
5 Considérations générales de sécurité	44
5.1 Généralités	44
5.2 Isolement et câblage	45
5.3 Échappement de gaz	45
5.4 Gestion de la température, de la tension et du courant	45
5.5 Bornes de contacts	46
5.6 Assemblage des éléments dans les batteries	46
5.6.1 Généralités	46
5.6.2 Recommandations de conception pour les systèmes au lithium seulement	46
5.7 Plan qualité	46
6 Conditions des essais d'homologation	47
7 Exigences spécifiques et essais (systèmes au nickel)	48
7.1 Procédure de charge pour les besoins des essais	48
7.2 Utilisation normale	48
7.2.1 Charge continue à faible régime (éléments)	48
7.2.2 Vibration	48
7.2.3 Contrainte de moulage du boîtier à température ambiante élevée (batteries)	49
7.2.4 Cycles de températures	49
7.3 Utilisation abusive raisonnablement prévisible	50
7.3.1 Installation incorrecte (éléments)	50
7.3.2 Court-circuit externe	50
7.3.3 Chute libre	50
7.3.4 Choc mécanique (danger de collision)	51
7.3.5 Utilisation à température abusive (éléments)	51
7.3.6 Écrasement d'éléments	51
7.3.7 Basse pression (éléments)	52
7.3.8 Surcharge	52
7.3.9 Décharge forcée (éléments)	52
8 Exigences spécifiques et essais (systèmes au lithium)	52
8.1 Procédures de charge pour les besoins des essais	52
8.1.1 Première procédure	52
8.1.2 Deuxième procédure	53
8.2 Utilisation normale	53
8.2.1 Charge continue à tension constante (éléments)	53
8.2.2 Contrainte de moulage du boîtier à température ambiante élevée (batterie)	53
8.3 Utilisation abusive raisonnablement prévisible	54
8.3.1 Court-circuit externe (élément)	54
8.3.2 Court-circuit externe (batterie)	54

8.3.3	Chute libre.....	54
8.3.4	Utilisation à température abusive (éléments)	55
8.3.5	Écrasement (éléments).....	55
8.3.6	Surcharge d'une batterie	55
8.3.7	Décharge forcée (éléments)	56
8.3.8	Essais de transport.....	56
8.3.9	Évaluation de la conception – Court-circuit interne forcé (éléments)	56
9	Information relative à la sécurité.....	58
10	Marquage	59
10.1	Marquage des éléments	59
10.2	Marquage des batteries	59
10.3	Autres informations	59
11	Emballage	59
	Annexe A (normative) Gamme de charge des accumulateurs lithium-ion pour un usage sûr.....	60
	Annexe B (informative) Recommandations aux fabricants de matériel et aux assembleurs de batteries	72
	Annexe C (informative) Recommandations pour les utilisateurs finals	73
	Bibliographie.....	74
	Figure 1 – Profil de température pour 7.2.4 – Essai de cycle de température	50
	Figure 2 – Gabarit de serrage sous pression.....	58
	Figure A.1 – Région de fonctionnement type des éléments Li-ion avec cathode en oxyde de cobalt et anode en carbone.....	61
	Figure A.2 – Forme de la particule de nickel	66
	Figure A.3 – Position d'insertion de la particule de nickel entre les zones enduites de matière active positive et négative dans un élément cylindrique	66
	Figure A.4 – Position d'insertion de la particule de nickel entre la feuille d'aluminium positive et la zone imprégnée de matière active négative de l'élément cylindrique	67
	Figure A.5 – Démontage d'un élément cylindrique.....	68
	Figure A.6 – Position d'insertion de la particule de nickel entre les zones positive et négative enduites (de matière active) de l'élément parallélépipédique	69
	Figure A.7 – Position d'insertion de la particule de nickel entre la feuille d'aluminium positive et la zone enduite (de matière active) négative de l'élément parallélépipédique	70
	Figure A.8 – Démontage d'un élément parallélépipédique	71
	Tableau 1 – Taille des échantillons pour essais d'homologation (systèmes au nickel)	47
	Tableau 2 – Taille des échantillons pour essais d'homologation (systèmes au lithium).....	47
	Tableau 3 – Conditions des essais de vibrations.....	49
	Tableau 4 – Condition de la procédure de charge	53
	Tableau 5 – Température ambiante pour l'essai d'un élément ^a	57