

INTERNATIONAL STANDARD



**Process management for avionics – Atmospheric radiation effects –
Part 5: Assessment of thermal neutron fluxes and single event effects in
avionics systems**

IECNORM.COM : Click to view the full PDF of IEC 62396-5:2014



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2014 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IECNORM.COM : Click to view the full text of IEC 60965:2014

INTERNATIONAL STANDARD



**Process management for avionics – Atmospheric radiation effects –
Part 5: Assessment of thermal neutron fluxes and single event effects in
avionics systems**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

S

ICS 03.100.50; 31.020; 49.060

ISBN 978-2-8322-1821-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Terms and definitions	5
4 Overview of thermal neutron single event rate calculation.....	5
5 Thermal neutron flux inside an airliner.....	7
5.1 Definition of thermal neutron	7
5.2 Overview.....	7
5.3 Background on aircraft measurements	7
5.4 Calculational approach	8
5.5 Processing of in-flight neutron flux data	9
6 Thermal neutron SEU cross-sections	13
6.1 Overview of the issue	13
6.2 Mechanism involved	13
6.3 Thermal neutron SEU cross-sections and Ratio-2	15
7 Recommendation for devices in avionics at the present time.....	17
7.1 General.....	17
7.2 Ratio-1.....	17
7.3 Ratio-2.....	18
7.4 Thermal neutron upset rate	18
8 Determining thermal neutron SEE rates for use in equipment assessments.....	18
8.1 Demonstration of thermal neutron immunity to SEE.....	18
8.1.1 Thermal neutron test.....	18
8.1.2 Absence of boron 10 (B10).....	18
8.2 Determination of thermal neutron SEE where there is no evidence of thermal neutron immunity	19
8.2.1 Results from thermal neutron testing	19
8.2.2 Conservative estimation	19
8.2.3 High voltage devices	19
9 Single event burn out in high voltage devices due to thermal neutrons.....	19
Bibliography	20
Figure 1 – Atmospheric neutron spectra measured in four aircraft.....	10
Figure 2 – Neutron cross-sections for boron-10 including total cross-section (red), total elastic cross-section (green) and (n,α) nuclear capture cross-section (blue).....	15
Table 1 – Tabulation of the various atmospheric neutron measurements used.....	9
Table 2 – Comparison of thermal and high energy neutron fluxes and their ratios.....	11
Table 3 – Calculated neutron fluxes in the Boeing 747 structure	12
Table 4 – SRAM SEU cross-sections induced by thermal and high energy neutrons	16

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**PROCESS MANAGEMENT FOR AVIONICS –
ATMOSPHERIC RADIATION EFFECTS –****Part 5: Assessment of thermal neutron
fluxes and single event effects in avionics systems**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62396-5 has been prepared by IEC technical committee 107: Process management for avionics.

This first edition cancels and replaces the first edition of IEC/TS 62396-5 published in 2008. This edition constitutes a technical revision.

This edition includes the following technical changes with respect to the previous technical specification:

- a) Change to title.
- b) Updated references and bibliography.
- c) Subclause 6.2 expanded to consider smaller geometry devices.

- d) Table 4 neutron cross-sections expanded to add more recent data and the ratio between thermal and high energy neutron cross-section amended to 2,42 from 2,77.
- e) Addition of reference section on thermal neutron high voltage burn out.
- f) New clause on determination of thermal neutron SEE rates for use in equipment assessments.
- g) Document aligned as an IEC standard.

The text of this international standard is based on the following documents:

FDIS	Report on voting
107/237/FDIS	107/242/RVD

Full information on the voting for the approval of this international standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62396 series, published under the general title *Process management for avionics – Atmospheric radiation effects*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

PROCESS MANAGEMENT FOR AVIONICS – ATMOSPHERIC RADIATION EFFECTS –

Part 5: Assessment of thermal neutron fluxes and single event effects in avionics systems

1 Scope

The purpose of this part of IEC 62396 is to provide a more precise definition of the threat that thermal neutrons pose to avionics as a second mechanism for inducing single event upset (SEU) in microelectronics. There are two main points that will be addressed in this part of IEC 62396:

- a) a detailed evaluation of the existing literature on measurements of the thermal flux inside of airliners, and
- b) an enhanced compilation of the thermal neutron SEU cross-section in currently available SRAM devices (more than 20 different devices).

The net result of the reviews of these two different sets of data will be two ratios that are considered to be very important for leading to the ultimate objective of how large a threat is the SEU rate from thermal neutrons compared to the SEU threat from the high energy neutrons ($E > 10$ MeV). The threat from the high energy neutrons has been dealt with extensively in the literature and has been addressed by two standards (IEC 62396-1 in avionics and JESD89A [1]¹ in microelectronics on the ground). Neutrons with $E > 1$ MeV are considered for parts with geometries below 150 nm.

NOTE Reference is made to IEC 62396-1:2012, 5.3.2, for smaller geometry parts below 150 nm which provides the neutron flux for energies above 1 MeV.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62396-1:2012, *Process management for avionics – Atmospheric radiation effects – Part 1: Accommodation of atmospheric radiation effects via single event effects within avionics electronic equipment*

IEC 62396-4, *Process management for avionics – Atmospheric radiation effects – Part 4: Design of high voltage aircraft electronics managing potential single event effects*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62396-1 apply.

4 Overview of thermal neutron single event rate calculation

The two ratios that this part of IEC 62396 considers to be important are:

¹ Numbers in square brackets refer to the Bibliography.

- a) the ratio of the thermal neutron flux inside an airliner relative to the flux of high energy (> 10 MeV) neutrons inside the airliner, and
- b) the ratio of the SEU cross-section due to thermal neutrons relative to that due to high energy neutrons.

These ratios are considered to be important because with them, once the SEU rates are defined from the high energy neutrons for an avionics box, a topic which has been dealt with extensively, such as in IEC 62396-1 and [1], then the additional SEU rate due to thermal neutrons can be obtained with these ratios. Thus, given the SEU rate from high energy neutrons, multiplying this by the two ratios gives the SEU rate from the thermal neutrons. The total SEU rate will be the combination of the SEU rates from both the high energy and thermal neutrons.

The process for calculating the SEU rate from the thermal neutrons is shown in the following set of equations, (1) to (5).

$$\begin{array}{l} \text{SEU rate} \\ \text{(Hi E}^2, \text{ upset/dev}\cdot\text{h)} \end{array} = \phi_{\text{Hi}} (\text{neutron flux} = 6\,000 \text{ n/cm}^2\text{h}) \times \sigma(\text{Hi E, SEU X-Sctn. cm}^2/\text{dev}) \quad (1)$$

$$\begin{array}{l} \text{SEU rate} \\ \text{(thermal neutron,} \\ \text{upset/dev}\cdot\text{h)} \end{array} = \text{SEU rate (Hi E)} \times \frac{\phi_{\text{therm}}(\text{neutron flux})}{\phi_{\text{Hi}}(\text{neutron flux})} \times \frac{\sigma(\text{therm SEU X-Sctn.})}{\sigma(\text{Hi E SEU X-Sctn.})} \quad (2)$$

$$\begin{array}{l} \text{Ratio-1} \end{array} = \frac{\phi_{\text{thermal}}(\text{neutron flux})}{\phi_{\text{Hi}}(\text{neutron flux})} \quad (3)$$

$$\begin{array}{l} \text{Ratio-2} \end{array} = \frac{\sigma(\text{therm SEU X-Sctn.})}{\sigma(\text{Hi E SEU X-Sctn.})} \quad (4)$$

$$\begin{array}{l} \text{SEU rate} \\ \text{(thermal neutron,} \\ \text{upset/dev}\cdot\text{h)} \end{array} = \text{SEU rate (Hi E neutron upset/dev}\cdot\text{h)} \times \text{Ratio-1} \times \text{Ratio-2} \quad (5)$$

The objective of this part of IEC 62396 is to provide the values of Ratio-1, the ratio of the thermal to high energy neutron flux within an airplane, and of Ratio-2, the ratio of the SEU cross-section due to thermal neutrons relative to that due to high energy neutrons. The Ratio-1 should be relatively similar in various types of commercial airliners, but it could vary significantly in other types of aircraft, such as military fighters. However, in the larger type of military aircraft, such as AWACS (Advanced Warning and Command System, E-3, which is based on either a Boeing 707-320-B or 767) and JSTARS (Joint Surveillance Target Attack Radar System, E-8C, which is based on Boeing 707-300 airframe), the ratio should be very similar to that in airliners.

With regard to the ratio of the thermal neutron SEU cross-sections, until recently, not very many such SEU cross-sections were reported in the literature. There were a few, and these were cited in [1]. Due to the data that has recently become available, the number of devices in which the thermal neutron SEU cross-section has been measured has increased significantly. This additional data allows us to have good confidence on the values that have been measured and the resulting average value of the ratio.

² Hi E = High Energy.

5 Thermal neutron flux inside an airliner

5.1 Definition of thermal neutron

Thermal neutrons are so called because although most atmospheric neutrons are produced at high energies following cosmic ray interactions, after a sufficient number of in-elastic collisions with the surrounding medium, the neutron velocity is reduced such that it has approximately the same average kinetic energy as the molecules of the surrounding medium. This energy depends on the temperature of the medium, so it is called thermal energy. The thermal neutrons are therefore in thermal equilibrium with the molecules (or atoms) of the medium in which they are present.

In a medium that has only a small probability of absorbing, rather than scattering, neutrons, the kinetic energies of the thermal neutrons is distributed statistically according to the Maxwell-Boltzmann law. Therefore, based on this Maxwell-Boltzmann distribution, the neutron kinetic energy that corresponds to the most probable velocity is kT , where T is the absolute temperature of the medium and k a constant. For a temperature of 20 °C, room temperature, this is 0,025 eV. This is based on a highly idealized model of elastic collisions between two kinds of particles, nuclei and neutrons, within a gaseous medium, and so there are departures from it in the real world.

Therefore, even though a neutron energy of around 0,025 eV is usually taken to be the definition of thermal neutrons, for purposes of this part of IEC 62396, neutrons with energies < 1 eV will be considered as thermal neutrons. Additional details on this are found in 6.2.

5.2 Overview

In a modern airliner, we know that the thermal neutron flux inside the aircraft should be higher than the thermal neutrons outside of the airplane because of the presence of all of the hydrogenous materials within it (fuel, plastic structures, baggage, people, etc.). The hydrogenous materials “slow down” the high energy neutrons through nuclear collisions, primarily with the hydrogen atoms. After a large number of such interactions, the high energy neutrons (energy > 10 MeV) have had their energy reduced by about seven orders of magnitude. For practical purposes, neutrons with $E < 1$ eV are considered as thermal neutrons. However, the more accurate definition of thermal neutrons is neutrons with energies close to 0,025 eV (equivalent to those at room temperature, hence the term “thermal”). The thermal neutron flux in the atmosphere is relatively low due to absorption by atmospheric molecular nitrogen. By contrast, both calculation and measurement show that the high energy neutron flux inside an aircraft structure is very similar to that in the atmosphere. The presence of the airplane structure and its contents produce far more thermal neutrons inside the aircraft than that are present in the atmosphere just outside the airplane.

5.3 Background on aircraft measurements

The thermal neutron flux inside an airliner is a rather elusive quantity that has not been measured very often despite the fact that hundreds and in fact thousands of ionizing radiation measurements have been and are currently being made inside of aircraft. Firstly, most of the thousands of measurements are of the dose equivalent that passengers and crew accumulate during flight. Although it varies depending on the location of the flight path, in general, the dose equivalent is approximately (50 to 60) % from the high energy neutrons, about (25 to 35) % from electrons and the remainder from other charged particles, mainly protons (10 to 20) %, gamma rays (< 10 %) and muons (< 10 %) [2]. Most of these kinds of instruments measure the combined dose rate from all of the charged particles present in the atmosphere.

Thus, to measure only the neutrons in the atmosphere required a detector system that was sensitive only to neutrons. The early systems that were flown in the 1960s consisted of detectors that were optimized to measure mainly neutrons in the energy range of (1 to 10) MeV. This information was used to develop the simplified Boeing model [3] based on the variation of the (1 to 10) MeV neutron flux with altitude and latitude. The key parameter is not latitude, however, but rigidity. Geomagnetic cut-off rigidity is a measure of the momentum a

charged particle requires in order to penetrate the Earth's magnetic field at a given location. The vertical rigidity cut-off varies mainly with latitude, but there is also a variation due to longitude. Similarly, NASA-LaRC developed a more elaborate model [4] that was also based on the (1 to 10) MeV measurements.

Since that time, there have been more recent flight measurements made with neutron-specific instruments that respond to the entire neutron spectrum. These have been primarily a series of Bonner spheres, a set of instruments with a detector that measures thermal neutrons surrounded by varying thicknesses of moderating material. The moderating material, generally polyethylene, is used to "slow down" the high energy neutrons which constitute most of the neutrons, through nuclear interactions with the hydrogen within it. The larger the sphere of surrounding polyethylene, the more thermal neutrons are produced and the larger the signal by the detector. Careful calibrations are needed of the set of Bonner sphere detectors before a collection of in-flight measurements can be transformed into neutron fluxes within specific energy ranges. This is a painstaking process and therefore is undertaken by a limited number of research groups.

Two such sets of measurements have been made, one by a NASA-Ames group [5], and the other by a Japanese group [6], and these are used in this evaluation. In addition, the most highly regarded set of such measurements [7] were made by P. Goldhagen of the Environmental Measurements Laboratory (formerly part of DOE, now a part of the Homeland Security Administration). Unfortunately, Goldhagen's measurements were made in an ER-2 aircraft.

The ER-2 is drastically different from a modern airliner. Exacerbating the situation even more, the detector that Goldhagen relied upon for the thermal neutron measurement was located in the very tip of the nose of the ER-2 [8]. For all practical purposes, this detector was located in a part of the airplane that is almost indistinguishable from the atmosphere outside of the airplane. Thus, the thermal neutron flux measured by Goldhagen in the ER-2 is too low compared to what is expected within a large airliner. In this case, the main interest lies in Ratio-1, i.e., the ratio between the thermal neutron flux and the high energy ($E > 10$ MeV) neutron flux.

A more recent paper by a group at EADS [9] that used a simpler detector system, again Bonner spheres, but specifically designed to be used in an airliner was examined. Unfortunately, the high energy neutron fluxes from this paper are considered to be far too low to be realistic. Thus, it is believed that the data collected by this detector system and contained in [9] cannot be considered to be accurate enough and consistent enough to be used for our purposes of obtaining a reliable and representative value for Ratio-1.

5.4 Computational approach

There is one paper in the literature [10] that represents a very significant step forward. It is based on applying an elaborate calculational method to a geometry consisting of a large airliner (a Boeing 747) and the atmosphere around it. The gross take-off weight of a large Boeing 747 is close to 450 000 kg (1 million lbs) and the overall internal volume is approximately 850 m³ (30 000 ft³) (based on the cargo capacity of cargo versions of the Boeing 747). The actual size is therefore enormous (length of aircraft is ~76 m (~250 ft) and wingspan of ~69 m (~225 ft) compared to most structures or vehicles that are modelled for purposes of radiation transport calculations. Out of necessity, the calculation had to simplify the true geometry by orders of magnitude in order to be able to develop the model and carry out the calculations in a relatively short time. As a result, the full aircraft is described as being comprised of approximately 30 smaller volumes, into which the different proportions of the full 1 million lbs are distributed, using gross approximations for the various materials (fuel, baggage, aluminium structure, interior, etc.).

Thus, it is unclear how accurate the results of these calculations are, especially for the thermal neutrons. For the high energy neutrons, it is clear that for most locations the neutron flux should be very similar inside the airplane as it is outside the airplane, and that is true in the results of [10], so this serves as a consistency check. However, for the thermal neutrons,

there are no consistency checks. The thermal neutron fluxes are much higher everywhere inside the aircraft compared to outside within the atmosphere, so there is no idea of how accurate a result [10] represents. It may be correct, but it also may be that especially for locations where the electronics are located, a much smaller model, greatly reduced in overall size, but much more detailed in terms of the internal structures and the mass distribution that is used, would be needed to calculate the thermal neutron flux accurately.


Therefore, the results from [10] will be used, but they will also be compared to the measurements from [5] and [6], to obtain Ratio-1. The results from [10] will represent the upper bound and the results from the in-flight measurements will represent a lower bound.

5.5 Processing of in-flight neutron flux data

For the comparison of in-flight measurements data is taken from four groups, [5], [6], [7] and [9], and in addition the calculations from two other groups, [10] and Armstrong [11] are used. First, the measured spectra from the four aircraft measurements are shown in Figure 1, along with the calculated spectrum from [11]. A tabulation of the main features concerning where the measurements were taken and which aircraft were used is given in Table 1.

Table 1 – Tabulation of the various atmospheric neutron measurements used

Researcher	Organization	Detector	Aircraft	Year	Altitude ft (km)	Ref.
Goldhagen	EML	Bonner sphere	ER-2	1997	40 000 (12,2 km)	[7]
Hubert	EADS	7-detect spectrometer	A300	2004	34 800 (10,6 km)	[9]
Hewitt	NASA-Ames	Bonner sphere	C-141	1974	40 600 (12,4 km)	[5]
Nakamura	Tohoku U.	Bonner sphere	DC-8	1985	37 000 (11,3 km)	[6]
Armstrong	ORNL	Calculation	Atmosphere	1973	39 000 (11,9 km)	[11]



Key

- Hewitt NASA Ames 40 000 ft (12,2 km) western USA
- ×— Nakamura, 37 000 ft (11,3 km) over Japan
- ◆— EADS, 34 800 ft (10,6 km) over Atlantic
- Goldhagen, ER-2 40 000 ft (12,2 km) western USA
- ▲— Armstrong calculation 39 000 ft (11,9 km)

Figure 1 – Atmospheric neutron spectra measured in four aircraft

All of the spectra have relatively similar shapes over 11 orders of magnitude, however two of the spectra seem to be lower than the other three, and these are the in-flight measurements by Nakamura over Japan and by the EADS group over the Atlantic. The differential neutron flux spectrum by Nakamura is lower than the others across the entire spectrum. The reason for this is that the measurements were made in an airplane over Japan. The simplified Boeing model of the neutron flux as a function of latitude and longitude is not adequate to deal with this situation. Taking San Jose, CA, as the approximate location for the ER-2 flights, the latitude for San Jose is approximately 37° which is similar to that for Nagoya, Japan, the approximate location for Nakamura's measurements. The earth's magnetic field varies with longitude as well as latitude. Although longitudinal dependence is less acute than latitudinal dependence, the effect is still such that two locations with very similar latitudes can have significantly different vertical rigidity cut-offs. In the case of these two cities, the rigidity cut-off over Nagoya, Japan, is much larger than it is in California, meaning that the cosmic rays are deflected much more over Japan than California and so the atmospheric neutron flux is much lower. Using a recent model by Gordon and Goldhagen for the variation of the atmospheric neutron flux with location [12] that is based on the vertical rigidity cut-off parameter, the net result is that the neutron flux over Japan is a factor of 3 to 4 lower compared to the flux over the western US (factor of 3 compared to San Jose, CA, and factor of 4 for Denver, CO). This is based on altitudes of 37 000 ft (11,3 km) for Nagoya, Japan and 40 000 ft (12,2 km) for the western US locations. The altitude difference accounts for an increase of 24 % in the flux calculated using Annex D of IEC 62396-1:2012. The QARM model [13] can be used to determine the nominal flux at any particular location.

Thus, if the spectrum in Figure 1 was increased by a factor of 3 to 4 to make the measurement over Japan be equivalent to that over the western US, the Nakamura curve would lie right within the NASA-Ames and Goldhagen curves. For this reason, the Nakamura

curve is considered accurate and reliable. The EADS spectrum in Figure 1 is another matter. This measurement was made at 35 000 ft (10,7 km), which represents the lowest altitude of all the in-flight data. Using the model in [12], the spectrum at 35 000 ft (10,7 km), is expected to be lower than that at 40 000 ft (12,2 km) by a factor of 1,5, but this applies over the entire spectrum. As seen in Figure 1, over the (1 to 10) MeV portion of the spectrum, the EADS curve is similar to all of the other curves. However, especially at the highest energies, > 10 MeV, the EADS spectrum is far too low, by about an order of magnitude, so a factor of 1,5 to account for the difference between 35 000 ft (10,7 km) and 40 000 ft (12,2 km) will not improve the situation very much. One of the reasons given in [9] is that the spectrometer was only calibrated up to 20 MeV and therefore data indicated above 20 MeV could not be used as reliable information for the calculation of Ratio-1.

In addition, in looking at Figure 1 carefully and the other three spectra, the two in-flight measurements by Goldhagen and NASA-Ames and the calculated spectrum from Armstrong, there appears to be relatively good agreement except at the higher energies, $E > 10$ MeV. Above 10 MeV, the NASA-Ames spectrum appears to be noticeably too high.

Using the actual spectra shown in Figure 1 in terms of the differential neutron flux, each of them was integrated to obtain the high energy portion of the neutron flux ($E > 10$ MeV) and the thermal neutron portion of the flux ($E < 1$ eV), both in units of $\text{n/cm}^2\text{s}$. In addition, the high energy and thermal neutron fluxes were included as calculated by Armstrong and also as calculated by Dyer-Lei in [10]. The results are shown in Table 2, and the last column of the table contains the ratio of the thermal neutron flux to the high energy ($E > 10$ MeV) neutron flux. This is Ratio-1 that was defined in Equation (3). In two cases, the original results were multiplied by a specified factor to make them applicable to 40 000 ft (12,2 km) altitude over the western US, like the measurements of Goldhagen and NASA-Ames.

Table 2 – Comparison of thermal and high energy neutron fluxes and their ratios

Researcher	Altitude ft (km)	Condition	Neutron flux, Hi E (> 10 MeV) $\text{n/cm}^2\text{s}$	Neutron flux, thermal (< 1 eV) $\text{n/cm}^2\text{s}$	Ratio-1, thermal / Hi E E
Hubert	34 800 (10,6 km)	A300 over Atlantic	0,13	0,063	0,5
Hubert ($\times 1,5$) ^a	34 800 (10,6 km)	A300 over Atlantic	0,19	0,09	0,5
Goldhagen	40 000 (12,2 km)	ER-2, California	0,74	0,18	0,24
NASA Ames	40 600 (12,6 km)	C-141, western US	1,52	0,21	0,14
Nakamura	37 000 (11,3 km)	Over Nagoya, Japan	0,23	0,11	0,49
Nakamura ^b	37 000 (11,3 km)	Over Nagoya, Japan	0,80	0,41	0,49
Armstrong	39 000 (11,9 km)	Calc. -atmosphere	0,94	0,19	0,20
Dyer-Lei	33 000 (10,1 km)	Calc. -atmosphere	0,70	0,15	0,21
Dyer-Lei	33 000 (10,1 km)	Calc, Boeing 747, cockpit	1,0	1,75	1,75
Dyer-Lei	33 000 (10,1 km)	Calc, Boeing 747, window	1,0	1,70	1,70
Goldhagen	Ground	Bonner Sphere	$3,2 \times 10^{-3}$	$2,4 \times 10^{-3}$	0,75
^a Multiplied by factor of 1,5 to make equivalent to altitude of 40 000 ft (12,2 km).					
^b Multiplied by factor of 3,5 (equivalent to location over western US at altitude of 40 000 ft (12,2 km)).					

In looking at Table 2, it is clear that the ratios derived from all of the in-flight measurements are much lower than what was calculated for the cockpit of a Boeing-747 by Dyer-Lei in [10]. The high values of Ratio-1 based on the Dyer-Lei calculations were mentioned in 5.4. In terms of the flight measurements, the data from Hubert and the EADS group, although it gives the highest ratio of all of the in-flight measurements, cannot really be used. It was already

remarked that the high energy portion of this spectrum seems abnormally low, due to the fact that the EADS spectrometer was only calibrated up to 20 MeV. Thus, the Ratio-1 value from the EADS measurements cannot be relied on.

With regard to Goldhagen's measurements in the ER-2, the high energy neutron flux appears to be consistent with other measurements, but the thermal neutron flux may be underestimated due to the location within the aircraft of the detector used for the measurements. This was already discussed in 5.3 and so this results in a value for Ratio-1 that is too low.

The NASA-Ames measurement for the high energy neutron flux appears to be too high. This can be seen in Table 2 and was already commented on above based on looking at the curve for this spectrum in Figure 1. It is not clear why the high energy portion of the spectrum is too high, but the most likely reason is a problem with the data reduction of the entire set of Bonner sphere measurements. It could be that the Bonner sphere detectors were not calibrated carefully enough or that the process for reducing the data, which involves convolution of the Bonner sphere response functions, was not carried out carefully enough. Goldhagen, whose ER-2 data is considered by far to be the best set of in-flight airplane measurements, spent several years in reducing his data before publishing them.

The last set of in-flight measurements is that due to Nakamura. The Ratio-1 that his data gives is 0,5. Table 2 shows that when his values are multiplied by a factor of 3,5 (a value between 3 and 4) to adjust the measurements to a location over the western US and at 40 000 ft (12,2 km), high energy fluxes (that are consistent with what Goldhagen measured and what Armstrong calculated) are obtained. The thermal neutron flux is higher than what Goldhagen measured, but it has been already explained why Goldhagen's thermal neutron flux is too low to be applicable to an airliner. Thus, based on the most applicable set of in-flight measurements, there is a value of the ratio of the thermal to high energy neutron flux within an airplane of 0,5 for civil aircraft; the figure 0,5 is proposed though it is noted there remains significant uncertainty around this figure.

Table 2 also contains the results of the calculations by Dyer-Lei. It was used at the two most appropriate locations for which there are data, the cockpit and the window, and it also included a point outside the airplane. However, neither the cockpit nor the window is a location where most of the avionics are located. It is noted that for the external point, there is relatively good agreement between their results and the calculation of Armstrong. For both internal locations, the cockpit and a window, Ratio-1 is high, a value of 1,75 and 1,7 respectively, much higher than the value of 0,5 that was obtained from the in-flight measurements by Nakamura. Additional calculation work is included in the article by Dyer *et al.* [14] and demonstrates the potential variation in different aircraft locations; the table with Ratio-1 added is reproduced here as Table 3.

Table 3 – Calculated neutron fluxes in the Boeing 747 structure

Calculated neutron fluxes at 10 km, 1 GV cut-off (units = n cm ⁻² s ⁻¹)					
	Cockpit	Mid-fuselage	Fuel tank	Window	External
TOTAL	3,94	3,10	1,17	3,78	4,07
< 1 eV (thermal)	1,80	1,47	0,277	1,73	0,146
1 eV to 1 MeV	0,687	0,444	0,083 3	0,691	2,79
1 MeV to 10 MeV	0,345	0,260	0,073 6	0,280	0,434
10 MeV to 1 000 MeV	1,03	0,860	0,679	0,997	0,696
Neutron flux ratio of < 1 eV to above 10 MeV					
Ratio-1	1,75	1,71	0,408	1,74	0,210

As explained in 5.4, it is not clear how accurate the calculated values are. Our main concern is that out of necessity, the geometric modelling was done on such a gross basis, mixing materials (fuel, baggage, structural members, etc.) within very large volumes within the airplane, that there is a lot of uncertainty as to the accuracy of the final results at much more localized positions. Therefore, it is proposed that an approximate average between the two values of 0,5 and 1,75 be used, which is taken as 1,1, for the value of Ratio-1. However, it could just as easily be taken as 1,0 to simplify matters. Furthermore, based on the calculations, it is certainly possible that there can be some locations in an airliner where Ratio-1 can be as large as 2 or higher.

Table 2 also contains the results of earlier measurements made by Goldhagen at ground level. From this neutron spectrum, the ratio of thermal neutrons to high energy neutrons is 0,75, which is not too different from the value of ratio of 1,1 that was indicated which applies to an airliner. However, it is known that at ground level the thermal neutron flux can vary by a factor of 2 due to local conditions (weather, i.e., rain, bodies of water, nature of the surrounding buildings, etc.).

6 Thermal neutron SEU cross-sections

6.1 Overview of the issue


It has been known for about 25 years that thermal neutrons can cause single event upsets in microelectronics (see [15] for the earliest reference). About ten years later, this topic was again investigated as part of a way to use a nuclear reactor to simulate the SEU environment posed by atmospheric neutrons to avionics [16]. After that, as the feature size of IC technologies continued to decrease, resulting in a continuing decline in the critical charge of devices, the threat of thermal neutrons to induce SEUs in the devices became more of a problem. This thermal neutron threat was recognized as a potential problem for ICs being used in both avionics and ground level applications. However, only within the last ten years have researchers tested devices in both a thermal neutron environment and a high energy neutron/proton environment to allow the two types of SEU cross-sections, due to high energy and thermal neutrons, to be compared. More of this kind of neutron SEU data is currently available and will be utilized in Clause 6.

6.2 Mechanism involved

In larger geometry devices thermal neutrons cause single event upsets because of their interaction with the boron-10 isotope within the IC (glassivation layer over the silicon), rather than with the silicon atoms. About 20 % of naturally occurring boron is B-10, with the remaining 80 % being B-11 which does not interact with the thermal neutrons. The boron is usually present as borophosphosilicate glass, BPSG, which is also used as the dielectric between the metallization layers in the overlayer that covers the silicon transistors.

In more modern devices with smaller feature size and power devices there may be sufficient boron-10 to cause SEE. Boron-10 can be found in IC features such the p-dopant, and although this is at lower atomic concentrations, it may be significant for small geometry and high voltage devices (see Clause 8). In addition, there can be internal IC structures at higher atomic densities ($> 10^{20}$ at/cc), such as in the boron nitride coating applied to tungsten plugs (in 65 nm and 45 nm technology ICs). This presence of boron-10 near the transistors results in SEU rates from the thermal neutrons comparable to the rates from the high energy neutrons [17, 18]. Further, in the 45 nm and 65 nm SRAMs, approximately 20 % to 50 % of all the upsets induced by the thermal neutrons are multiple cell upsets (one neutron upsets more than one cell [17]). Thus, the additional SEU rate in avionics due to thermal neutrons should be accounted for by either increasing the high energy neutron SEU rate by an appropriate factor (Clause 7), or by demonstrating it is small enough to ignore (this will require explicit justification).

The reaction that is responsible for the increased SEU rate due to thermal neutrons is:



This reaction creates two energetic ions, Li-7 and an alpha particle, both of which can deposit enough energy to cause an upset in devices having low critical charges (deposition of the complete 0,84 MeV from the Li-7 ion in silicon leads to 37 fC of charge).

As used by microelectronics manufacturers, the BPSG layers are comprised of (4 to 9) % of boron. The range of the Li-7 and the 1,47 MeV alpha is relatively short, between 2,5 µm and 5 µm, and therefore a significant fraction of the energy deposition will take place in the passivation layer rather than in the adjacent sensitive volume. However, the IC devices also contain boron in much lower concentrations through other constituents on the die (e.g. the p-dopant). Although the target boron in these constituents may be closer to (or within) sensitive volumes than boron in passivation layers, the low concentrations mean that thermal neutron SEU cross-sections are likely to still be orders of magnitude lower than those due to BPSG.

In 5.1, for the purposes of this part of IEC 62396, thermal neutrons were defined as ones with energies of < 1 eV even though the formal definition of a thermal neutron is one having an energy of approximately 0,025 eV. There are practical reasons for this revised definition, for example, the way that calculated and measured neutron fluxes inside an aircraft are displayed, using a finite number of energy groups (see Figure 1).

However, there are also physics considerations. The probability that a neutron will interact with a material is called the neutron cross-section, which is measured in the unit of barns (1 barn = 10⁻²⁴ cm²). The silicon atom has a total neutron cross-section of approximately 2 barns to 3 barns for most of the 10 orders of magnitude of the energy range, 0,01 eV to 100 MeV, with only slight deviations. For boron, it is drastically different; the neutron cross-section increases with decreasing energy because of the behaviour of the cross-section of the B-10 atom with energy (see Figure 2). For natural boron, the total neutron cross-section at 1 eV is ~100 barns (~600 barns for boron-10), but at 100 eV it is only 12 barns and at 0,1 eV it is 400 barns. At an energy as low as 1 eV, the neutron cross-section is 50 times higher in a boron atom compared to that in a silicon atom (and more than 200 times higher for boron-10). Thus it can be said that the presence of boron-10 makes interactions with low energy neutrons far more probable and, crucially, due to the kinetics of the reaction products, this in turn makes significant charge deposition leading to SEU far more likely.

In addition, there is another reason why 1 eV serves very well as the thermal energy cut-off. There are two kinds of thermal neutron facilities that have been used for testing:

- a) one which produces only low energy thermal neutrons, such as a specialized reactor at the National Institute of Standards and Technology, NIST, and
- b) a facility that has neutrons over a broad spectrum of energies, including thermal neutrons.

For the broad spectrum facility, testing for the thermal neutron SEU response is carried out by performing two tests with a microelectronics device. In one test, the device and/or test card is bare, exposed to the beam and the resulting number of upsets are recorded. In the second test, the device is covered with an efficient thermal neutron absorber material, usually a thin foil or sheet of cadmium metal or a boron compound, and the test is repeated. Cadmium is used because it is such a good absorber of thermal neutrons below an energy of ~0,4 eV which is often called the cadmium cut-off (its neutron cross-section changes from 20 barns at 1 eV, 200 barns at 0,5 eV and 7 000 barns at 0,2 eV). Thus, the difference in the response of the device with and without the cadmium is due to the thermal neutrons. The fact that the cadmium cut-off of ~0,4 eV is so close to 1 eV makes the energy of 1 eV a good value for the thermal energy cut-off.




Figure 2 – Neutron cross-sections for boron-10 including total cross-section (red), total elastic cross-section (green) and (n,α) nuclear capture cross-section (blue)

6.3 Thermal neutron SEU cross-sections and Ratio-2

The earliest testing of RAMs with thermal neutrons to induce SEUs [15] was carried out over 25 years ago and the results are not very relevant because the devices are so old and are no longer in use. Nevertheless, the results provide an interesting basis for comparison. Seven SRAMs were tested in the NIST reactor (then called NBS) with a high purity thermal neutron beam and only one of them exhibited upset, the SEU cross-section being $2 \times 10^{-14} \text{ cm}^2/\text{bit}$. In addition [15], eight DRAMs were tested and three of them had upsets induced by the thermal neutrons, but the SEU cross-section was about two orders of magnitude lower compared to the SRAM.

The testing carried out by Sandia in their SPR-III (Sandia Pulsed Reactor) is reported on in [16]. Six SRAMs were tested and in all cases, the SEUs were attributed to the thermal neutrons. The normal neutron spectrum in the central cavity at the SPR-III reactor was modified by using polyethylene around the cavity to produce additional thermal neutrons. Based on the data provided in [16], the thermal neutron SEU cross-sections for the six SRAMs are in the range of $6 \times 10^{-15} \text{ cm}^2/\text{bit}$ to $6 \times 10^{-14} \text{ cm}^2/\text{bit}$. It is unclear whether additional devices were tested that did not exhibit SEUs due to the thermal neutrons.

There has been more recent testing (see Table 4), performed on SRAMs in which SEUs have been induced by both thermal neutrons and high energy ($> 10 \text{ MeV}$) neutrons. These are the data of greatest interest because it enables us to tabulate Ratio-2, the ratio of the SEU cross-section due to thermal neutrons relative to that due to high energy neutrons. In Table 4, these data were compiled and it was noted that the testing was performed at diverse facilities, with the only requirement being that the data contain the results of measurements of neutron-induced SEU cross-sections caused by both high energy and thermal neutrons. In some cases, the high energy SEU measurements were made by using a high energy proton beam rather than a high energy neutron source. In most cases, the thermal neutron contribution was obtained as the result of two measurements, with and without a thermal neutron absorber surrounding the device or test card being exposed to the neutrons.

The last row contains the average for all of the measurements; however, it includes only the data in which a non-zero thermal neutron SEU cross-section was measured. Thus, the two Hitachi parts that had no response to thermal neutrons (rows 3 and 4 in the table) were not included in the averaging process. When all the ratios were combined and averaged, the value of Ratio-2 is 2,8 with a worst case of value of Ratio-2 of 6. All of the data in Table 4 is for SRAMs. (In conjunction with a high value of Ratio-1 this gives a possible thermal neutron SEU rate that is more than an order of magnitude higher than the fast neutron rate.) It is likely to also apply to other kinds of devices, but almost all of the devices that have been tested for SEU susceptibility with thermal neutrons are SRAMs.

Another important factor that comes out of the data in Table 4 is how likely it is for a SRAM to be susceptible to SEUs from thermal neutrons. Reference [18] tested six SRAMs and four of them were susceptible to thermal neutrons inducing SEUs, thus 67 % were susceptible to thermal neutron SEU. In [20], a total of 14 SRAMs were tested and of these 8, or 57 %, were susceptible to SEUs from thermal neutrons and in [21] three of the five, or 60 % of the SRAMs tested, were susceptible to SEUs from thermal neutrons. References [19] and [20] are the two studies in the open literature with the largest number of devices tested for susceptibility to thermal neutron induced upsets. In combination, they lead to the conclusion that an average of 60 % of currently available SRAMs is susceptible to SEUs from thermal neutrons. This percentage figure will potentially increase for SRAMs with feature sizes 100 nm and below (see 6.2).

It has been recognized that major microelectronics vendors are aware of the problem of thermal neutrons inducing upsets in their devices, and have committed to eliminate this problem by removing the use of BPSG in the IC fabrication process where it can lead to SEUs from the thermal neutrons. Another option for the IC vendors is to use 100 % B-11 rather than naturally occurring boron in the BPSG. Furthermore, smaller IC vendors may not follow the larger companies in eliminating the B10 from their fabrication processes. However the major IC vendors proceed, the changes they make will affect future devices, making it likely that most such devices will not be susceptible to SEUs from thermal neutrons. However, as shown in Table 4, currently, for devices that are likely to be used in avionics systems at the present time the assumption has to be that at least half, about 60 %, of all SRAM devices are sensitive to thermal neutrons causing upsets.

Table 4 – SRAM SEU cross-sections induced by thermal and high energy neutrons

Device	Manufacturer	Date code /feature size (microns)	Ref.	Year of ref.	Hi E SEU cross-section cm ² /bit	Thermal neutron SEU cross-section cm ² /bit	Ratio-2, thermal / Hi E SEU cross-section
TC554161AFT	Toshiba	N A / N A	[22]	2002	$7,3 \times 10^{-15}$	$1,15 \times 10^{-14}$	1,57
N/A	N/A	N/A/0,18	[23]	2004	$2,90 \times 10^{-14}$	$1,12 \times 10^{-13}$	3,86
HM628512ALP-7	Hitachi	9809/0,5	[19]	2004	$6,0 \times 10^{-14}$	0	0,00
HM628512BLP-7	Hitachi	9925/0,35	[19]	2004	$4,5 \times 10^{-14}$	0	0,00
TC54001FL	Toshiba	9827/0,5	[19]	2004	$8,20 \times 10^{-15}$	$8,70 \times 10^{-15}$	1,06
TC54001AF	Toshiba	9929/0,4	[19]	2004	$7,50 \times 10^{-15}$	$2,70 \times 10^{-15}$	0,36
M5M5408AFP	Mitsubishi	9839/0,4	[19]	2004	$1,88 \times 10^{-13}$	$1,80 \times 10^{-13}$	0,96
KM684000BLP	Samsung	9844/0,4	[19]	2004	$6,90 \times 10^{-14}$	$2,10 \times 10^{-13}$	3,04
CY62147V18LL	Cypress	0036/0,25	[20]	2005	$3,00 \times 10^{-14}$	$1,80 \times 10^{-13}$	6,0
K6F1616U6A	Samsung	0208/0,25	[20]	2005	$1,00 \times 10^{-14}$	$2,00 \times 10^{-14}$	2,0
M5MY416CW	Mitsubishi	N/A/0,18	[20]	2005	$4,00 \times 10^{-14}$	$2,40 \times 10^{-13}$	6,0

Device	Manufacturer	Date code /feature size (microns)	Ref.	Year of ref.	Hi E SEU cross-section cm^2/bit	Thermal neutron SEU cross-section cm^2/bit	Ratio-2, thermal / Hi E SEU cross-section
CY62147CV33LL	Cypress	0225/0,16	[20]	2005	$4,00 \times 10^{-14}$	$1,80 \times 10^{-13}$	4,5
CY62157DV18LL	Cypress	0311/0,13	[20]	2005	$4,00 \times 10^{-14}$	$3,00 \times 10^{-14}$	0,8
HM62V16512LB	Hitachi	0251/0,13	[20]	2005	$2,50 \times 10^{-14}$	$2,50 \times 10^{-14}$	1,0
HM62V162100LB	Hitachi	0328/0,13	[20]	2005	$3,00 \times 10^{-14}$	$1,10 \times 10^{-13}$	3,7
K6X4016C3F	Samsung	0307/0,13	[20]	2005	$5,00 \times 10^{-15}$	$1,0 \times 10^{-14}$	2,0
8 other devices	Various	2002-03/0,13 to 0,25	[20]	2005	10^{-14} to 10^{-13}	0	0
CY7C1360A	Cypress	0231/0,25	[21]	2003	$3,07 \times 10^{-14}$	$5,1 \times 10^{-14}$	1,7
IBM0436A81	IBM	0139/0,25	[21]	2003	$4,85 \times 10^{-14}$	$2,41 \times 10^{-13}$	5,0
MCM69P737	Motorola	9823/0,4	[21]	2003	$6,66 \times 10^{-15}$	$1,62 \times 10^{-14}$	2,4
K7B803625M	Samsung	0019/?	[21]	2003	$1,20 \times 10^{-15}$	0	0
K7A803600M	Samsung	0016/?	[21]	2003	$1,24 \times 10^{-15}$	0	0
K6F8016U6BEF	Samsung	0,13	[24]	2004	$4,8 \times 10^{-16}$	$1,9 \times 10^{-16}$	0,4
TC55W800FT	Toshiba	0,22	[24]	2004	-	$7,1 \times 10^{-14}$	N/A
HM62V8512C	Hitachi	0,18	[24]	2004	$1,6 \times 10^{-15}$	$2,8 \times 10^{-16}$	0,175
EM128C08	Nanoamp	0,18	[24]	2004	$1,1 \times 10^{-16}$	$6,9 \times 10^{-17}$	0,63
Average -unweighted all non zero data							2,36

NOTE The high energy neutron SEU cross-section is based on the best data available in the reference, with priority being given to neutron measurements (WNR or TRIUMF) and then high energy proton measurements.

7 Recommendation for devices in avionics at the present time

7.1 General

Equation (5) provides a simple way to calculate the SEU rate induced by thermal neutrons within microelectronics used in avionics. It is based on the SEU rate due to high energy neutrons, a topic which has been dealt with extensively, such as in [1], and two ratios, Ratio-1 and Ratio-2. Ratio-1 is the ratio of the thermal to high energy neutron flux within an airplane, and Ratio-2 is the ratio of the SEU cross-section due to thermal neutrons relative to that due to high energy neutrons.

7.2 Ratio-1

In Clause 5, data regarding Ratio-1 were examined. Based on the data given in Table 2, it was proposed that a value of 1,1 be used for Ratio-1. This is an approximate value and it was noted that a value of 1,0 could just as easily be used to simplify matters. It was also noted that, based on the calculations of [10], it is possible that there are some locations within an airliner where Ratio-1 can be as large as 2.

7.3 Ratio-2

In Clause 6, data regarding Ratio-2 were examined. It was noted that it appears likely that within avionics currently being flown a majority of SRAM devices are sensitive to thermal neutrons causing upsets. It is also likely that this applies to other types of devices as well, such as DRAMs and microprocessors. Based on the data given in Table 4, an average value of 2,42 was determined for Ratio-2. This is an approximate value based on averaging data taken on 20 different SRAMs by six different engineering groups.

7.4 Thermal neutron upset rate

Where the device may contain boron-10 in the BPSG and the thermal neutron cross-section is not known so it is recommended that a conservative approach be taken such that the universal value of Ratio-2, applicable to such devices, should be taken as the worst case value 6,0 from Table 4. A less conservative approach using average values is given in [25]. If this worst case value with the value of Ratio-1 above is used, a value of 6,6 ($1,1 \times 6,0 = 6,6$) is obtained. This means that if the SEU rate due to high energy (> 10 MeV) neutrons in a given device has been calculated to be X (such as by using [1]), the SEU rate due to thermal neutrons will be $6,6 X$ and therefore, the total SEU rate will be $7,6 X$, with the thermal neutrons making up about 87 % of the rate and the high energy neutrons 13 %. If the device can be shown not to contain BPSG with boron-10 (such as by a vendor guarantee or independent testing, e.g., by neutron depth profiling (NDP)), the thermal neutrons are unlikely to contribute significantly to the SEU rate for such a device and the total SEU rate will be X .

Specific devices with complete test data will either be susceptible to thermal neutron SEU and thus have a combined total SEU rate (thermal plus high energy), or will not be susceptible, in which case, its total SEU rate will be X .

Based on trends discussed in 6.3, future devices with feature sizes above 100 nm are expected to exhibit much less susceptibility to thermal neutron induced SEU because of the commitment by the major microelectronics vendors to remove the BPSG from their processing. However, that remains to be verified in the future and for devices with feature size of 100 nm and below other factors including p-dopant and boron passivation of tantalum slugs may result in thermal neutron sensitivity [18]. At the present time, the recommendation is that if the SEU rate due to high energy neutrons in a device has been calculated to be X , and the device may potentially contain boron-10 then, the total SEU rate, due to thermal and high energy neutrons, should be treated as $7,6 X$.

8 Determining thermal neutron SEE rates for use in equipment assessments

8.1 Demonstration of thermal neutron immunity to SEE

8.1.1 Thermal neutron test

The immunity of the specific component technology shall have been demonstrated by active application testing with thermal neutrons as referenced in 6.2, no thermal neutron SEE having occurred. This thermal neutron immunity shall be documented either in existing test reports or publications.

8.1.2 Absence of boron 10 (B10)

For components with geometric feature size of greater than 100 nm only, the immunity of the specific component technology can be demonstrated by the component manufacturer documented statement that there is no boron-10 in the device passivation. The user shall retain a copy of the component manufacturer documented statement. For high voltage devices, see 8.2.3.