

INTERNATIONAL STANDARD

Quality evaluation method for the sound field of directional loudspeaker array systems

IECNORM.COM : Click to view the full PDF of IEC 62777:2016



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2016 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IECNORM.COM : Click to view the full text of IEC 60771:2016

INTERNATIONAL STANDARD

Quality evaluation method for the sound field of directional loudspeaker array systems

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.160.50

ISBN 978-2-8322-3136-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references.....	6
3 Terms and definitions	6
4 Personal acoustic zone and sound pressure level.....	7
4.1 Personal acoustic zone	7
4.2 Personal distance between listeners.....	8
4.3 Personal distance between a directional loudspeaker array system and a listener	8
4.4 Average sound pressure level at a personal acoustic zone.....	9
5 Personal acoustic zone index.....	9
5.1 General.....	9
5.2 PAZI-x	10
5.3 PAZI-y	10
5.4 PAZI-xy.....	10
5.5 PAZI-xyz.....	10
6 Measurement of the sound pressure level for a personal acoustic zone	10
6.1 General.....	10
6.2 Characteristics to be specified.....	10
6.3 Method of measurement.....	11
6.3.1 Directional loudspeaker array system	11
6.3.2 Microphone.....	11
6.3.3 Test signals	11
6.3.4 Sound pressure level curves	11
6.4 Test environment condition.....	11
6.4.1 Temperature.....	11
6.4.2 Humidity.....	11
7 Indication of the characteristics to be specified.....	11
Annex A (informative) Example of standard specifications for a personal audio space	13
Bibliography	14
Figure 1 – Personal acoustic zone.....	8
Figure 2 – Personal acoustic zone and sound pressure level	8
Figure 3 – Measuring points of the personal acoustic zone	9
Table 1 – Characteristics to be specified	12
Table A.1 – Personal acoustic zone – Dimensioned example	13

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**QUALITY EVALUATION METHOD FOR THE SOUND FIELD
OF DIRECTIONAL LOUDSPEAKER ARRAY SYSTEMS**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62777 has been prepared by subcommittee technical area 11: Quality for audio, video and multimedia systems, of IEC technical committee technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/2603/FDIS	100/2637/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IECNORM.COM : Click to view the full PDF of IEC 62777:2016

INTRODUCTION

Directional loudspeaker array systems provide focused sound for a person to listen alone without disturbing others. This system is convenient for consumers who want to listen to sound without earphones or headphones.

This system would be widely used in consumer electronics, for example, smart phone or pad, TV, computer, navigator, and game machine. The applicable area for the system could be fitness club, exhibition room, museum, shopping mall, and etc. A simple and easy concept is needed to evaluate the performance of the directional loudspeaker array system for a consumer. It will provide consumers with personalized audio space criteria in order to compare the audio sound field quality between various electronic products that have a directional loudspeaker array system. It is important to specify the quality evaluation method for the personal audio space and the concept of personal audio space.

This standard provides guidelines for general test methods to evaluate the quality of directional loudspeaker array systems.

IECNORM.COM : Click to view the full PDF of IEC 62777:2016

QUALITY EVALUATION METHOD FOR THE SOUND FIELD OF DIRECTIONAL LOUDSPEAKER ARRAY SYSTEMS

1 Scope

This International Standard applies to directional loudspeaker array systems of any kind, and to the parts of which they are composed or which are used as auxiliaries in such systems.

This standard deals with the determination of the performance of directional loudspeaker array systems, the comparison of these system types, and the determination of their proper practical application, by listing the characteristics which are useful for their specification. It specifies uniform measurement methods for these characteristics.

This standard is restricted to a description of the audio space around a person and the relevant method of measurement. It does not consider characteristics of loudspeakers, which are specified in IEC 60268-5.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60268-1, *Sound system equipment – Part 1: General*

IEC 60268-2, *Sound system equipment – Part 2: Explanation of general terms and calculation methods*

IEC 60268-5, *Sound system equipment – Part 5: Loudspeakers*

IEC 61672-1, *Electroacoustics – Sound level meters – Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

personal acoustic zone

PAZ

acoustic space occupied by a person

3.2

personal distance

distance between listeners and a directional loudspeaker array system

3.3

sound pressure level at a personal acoustic zone

P_{ij}

sound pressure level measured at the center of the surface j of the personal acoustic zone i

3.4**average sound pressure level at a personal acoustic zone** P_i

mean value of the sound pressure levels measured at the centers of the surfaces of the personal acoustic zone i

3.5**personal acoustic zone index****PAZI**

ratio of the average sound pressure level of the personal acoustic zone for a listener, to the total average sound pressure levels for listeners around the directional loudspeaker array system located at a specified personal distance

3.6**personal acoustic zone index-x****PAZI-x**

ratio of the average sound pressure level of the personal acoustic zone of a listener in front of the directional loudspeaker array system to the sum of the average sound pressure levels of listeners at the front, the front-right, and the front-left of the system

3.7**personal acoustic zone index-y****PAZI-y**

ratio of the average sound pressure level of the personal acoustic zone of a listener located in front of the directional loudspeaker array system to the sum of the average sound pressure levels of listeners at the front and the rear of the system

3.8**personal acoustic zone index-xy****PAZI-xy**


ratio of the average sound pressure level of the personal acoustic zone of a listener located in front of the directional loudspeaker array system to the sum of the average sound pressure levels of listeners at the front, the front-right, the front-left and the rear of the system

3.9**personal acoustic zone index-xyz****PAZI-xyz**

ratio of the average sound pressure level of the personal acoustic zone of a listener located in front of the directional loudspeaker array system to the sum of the average sound pressure levels of persons at the front, the front-right, the front-left, and the rear, and the front-upper, and the front-lower of the system

4 Personal acoustic zone and sound pressure level**4.1 Personal acoustic zone**

The personal acoustic zone (PAZ) is defined as an acoustic space occupied by a person as shown in Figure 1. The dimensions of the personal acoustic zone are defined as W (width), D (depth), and H (height). Considering the standard size of a person, the dimensions of the personal acoustic zone shall be stated.




IEC

Figure 1 – Personal acoustic zone

4.2 Personal distance between listeners

The personal distance between separate listeners, x and z , shall be defined as the distance between the centres of their personal acoustic zones, see Figure 2. Considering the standard size of a person, the dimension of the personal distance between listeners shall be stated.



IEC

Figure 2 – Personal acoustic zone and sound pressure level

4.3 Personal distance between a directional loudspeaker array system and a listener


The personal distance between a directional loudspeaker array system and a listener, y , shall be defined as a distance from the centre of the directional loudspeaker array system to the

listener in front of the system, as shown in Figure 2. The personal distance shall be specified by the target application area of the directional loudspeaker array system.

4.4 Average sound pressure level at a personal acoustic zone

The sound pressure level, P_{ij} , shall be defined as the sound pressure level measured at the center of the surface j of the personal acoustic zone i . The average sound pressure level of the personal acoustic zone, P_i , shall be the mean value of the sound pressure levels measured at the center of the surfaces of the personal acoustic zone, as shown in Figure 3.

$$P_i = \frac{\sum_{j=1}^6 P_{ij}}{6}$$



IEC

Figure 3 – Measuring points of the personal acoustic zone

The average sound pressure level of the personal acoustic zone, P_i , at the position of listener, as shown in Figure 2, is defined as follows:

- P_F is the average sound pressure level of the personal acoustic zone in front of the directional loudspeaker array system;
- P_L is the average sound pressure level of the personal acoustic zone at the front-left of the directional loudspeaker array system;
- P_R is the average sound pressure level of the personal acoustic zone at the front-right of the directional loudspeaker array system;
- P_B is the average sound pressure level of the personal acoustic zone at the rear of the directional loudspeaker array system;
- P_U is the average sound pressure level of the personal acoustic zone at the front-upper of the directional loudspeaker array system;
- P_D is the average sound pressure level of the personal acoustic zone at the front-lower of the directional loudspeaker array system.

5 Personal acoustic zone index

5.1 General

The personal acoustic zone index provides the ratio of the average sound pressure level of the personal acoustic zone of one listener, to the average sound pressure level of another listener at a specified personal distance.

5.2 PAZI-x

PAZI-x is defined as the ratio of the average sound pressure level of the personal acoustic zone of a listener in front of the directional loudspeaker array system to the sum of the average sound pressure levels of listeners at the front, the front-right, and the front-left of the system. This index means a relative ratio of the average sound pressure level of the listener in front of the directional loudspeaker array system to those of the persons who are at the left side and right side of the listener.

$$PAZI-x = P_F / (P_F + P_R + P_L)$$

5.3 PAZI-y

PAZI-y is the ratio of the average sound pressure level of the personal acoustic zone of a listener located in front of the directional loudspeaker array system to the sum of the average sound pressure levels of listeners at the front and the rear of the system. This index means a relative ratio of the average sound pressure level of a listener in front of the directional loudspeaker array system to that of the person who is at the rear side of the system.

$$PAZI-y = P_F / (P_F + P_B)$$

5.4 PAZI-xy

PAZI-xy is the ratio of the average sound pressure level of the personal acoustic zone of a listener located in front of the directional loudspeaker array system to the sum of the average sound pressure levels of listeners at the front, the front-right, the front-left and the rear of the system. This index means a relative ratio of the average sound pressure level of a listener located in front of the directional loudspeaker array system to the sum of those of the persons who are neighboring the listener in a 2-dimensional plane, as shown in Figure 2.

$$PAZI-xy = P_F / (P_F + P_R + P_L + P_B)$$

5.5 PAZI-xyz

PAZI-xyz is the ratio of the average sound pressure level of the personal acoustic zone of a listener located in front of the directional loudspeaker array system to the sum of the average sound pressure levels of persons at the front, the front-right, the front-left, and the rear, and the front-upper, and the front-lower sides of the system. This index means a relative ratio of the average sound pressure level of a listener located in front of the directional loudspeaker array system to the sum of the average sound pressure levels of the persons who are neighboring the listener in 3-dimensional space.

$$PAZI-xyz = P_F / (P_F + P_R + P_L + P_B + P_U + P_D)$$

6 Measurement of the sound pressure level for a personal acoustic zone

6.1 General

This standard shall be used in conjunction with IEC 60268-1, IEC 60268-2, IEC 60268-5 and IEC 61672-1.

6.2 Characteristics to be specified

The sound pressure level shall be specified as a function of frequency measured under free field condition at a specified constant voltage with sinusoidal signal.

6.3 Method of measurement

6.3.1 Directional loudspeaker array system

The directional loudspeaker array system shall be brought under normal measuring conditions.

6.3.2 Microphone

The measuring microphone shall be positioned in the position specified in 4.4.

6.3.3 Test signals

6.3.3.1 General

Acoustical measurements shall be made under the following measuring signal condition, and be indicated with the results.

6.3.3.2 Sinusoidal signal

The sinusoidal test signal shall not exceed the rated voltage at any frequency. The voltage across the input terminals of the directional loudspeaker array system under test shall be kept constant for all frequencies unless otherwise stated.

6.3.4 Sound pressure level curves

6.3.4.1 General

One or both of the following ways may be chosen for displaying the sound pressure level curves. A family of frequency responses to be used shall be selected for some frequencies or frequency bands according to the application.

6.3.4.2 Curves at stated frequencies

A family of sound pressure level curves at stated frequencies shall be displayed.

6.3.4.3 Curves at stated frequency bands

A family of sound pressure level curves at stated frequency bands shall be displayed.

6.4 Test environment condition

6.4.1 Temperature

The temperature of the test room shall be a standard room temperature ($23\text{ °C} \pm 5\text{ K}$).

6.4.2 Humidity

The humidity in the test room shall be a relative humidity (RH) of 30 % ~ 60 %.

7 Indication of the characteristics to be specified

Data that shall be given by the manufacturer are indicated in Table 1 by an "X". Data that the manufacturer should give are indicated by the letter "R" (recommended).

A = data that shall be specified at stated frequencies;

B = data that shall be specified at a stated frequency range.

This table shall be specified in a document available to buyers before purchase of the directional loudspeaker array system.

Table 1 – Characteristics to be specified

Clauses and subclauses		System	
		A	B
4	Personal acoustic zone and sound pressure level		
4.1	Personal acoustic zone	R	X
4.2	Personal distance between listeners	R	X
4.3	Personal distance between a directional loudspeaker array system and a listener	R	X
4.4	Average sound pressure level of the personal acoustic zone	X	X
5	Personal acoustic zone index		
5.2	PAZI-x	R	X
5.3	PAZI-y	R	X
5.4	PAZI-xy	R	X
5.5	PAZI-xyz	R	X
6	Measurement of the sound pressure level for a personal acoustic zone		
6.4	Test environment condition		
6.4.1	Temperature	R	X
6.4.2	Humidity	R	X

IECNORM.COM : Click to view the full PDF of IEC 62777:2016