

INTERNATIONAL ELECTROTECHNICAL COMMISSION
COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

IEC 62841-1
Edition 1.0 2014-03

**ELECTRIC MOTOR-OPERATED HAND-
HELD TOOLS, TRANSPORTABLE TOOLS
AND LAWN AND GARDEN MACHINERY
– SAFETY –**

Part 1: General requirements

IEC 62841-1
Édition 1.0 2014-03

**OUTILS ÉLECTROPORTATIFS À MOTEUR,
OUTILS PORTABLES ET MACHINES POUR
JARDINS ET PELOUSES – SÉCURITÉ –**

Partie 1: Règles générales

CORRIGENDUM 2

Corrections to the French version appear after the English text.

Les corrections à la version française sont données après le texte anglais.

5 General conditions for the tests

Replace 5.19 with the following:

5.19 *All electrical measurements shall be made with a maximum measurement error of 5 %.*

Instruments for measuring voltage shall have an input resistance of at least 1 M Ω with a maximum parallel capacitance of 150 pF.

Rationale for this corrigendum:

The maximum parallel capacitance for instruments for measuring voltage was increased from 25 pF to 150 pF. A 25 pF maximum parallel capacitance is not typical for voltage measuring equipment, and would require highly specialized and expensive equipment. This was not the intention of TC 116. A maximum value of 150 pF will allow the continued use of voltage measuring equipment currently being used by testing laboratories.