

PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

**Connectors for electrical and electronic equipment – Product requirements –
Part 2-010: Circular connectors – Detail specification for push-pull connectors
with locking mechanism, based on mating interfaces according to
IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 and IEC 61076-2-113**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IECNORM.COM : Click to view the full text of IEC publications
IEC REF: 60376-2-010:2020

PUBLICLY AVAILABLE SPECIFICATION PRE-STANDARD

**Connectors for electrical and electronic equipment – Product requirements –
Part 2-010: Circular connectors – Detail specification for push-pull connectors
with locking mechanism, based on mating interfaces according to
IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 and IEC 61076-2-113**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.220.10

ISBN 978-2-8322-8549-7

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms and definitions	10
4 Technical information	10
4.1 System of levels.....	10
4.1.1 Performance levels	10
4.1.2 Compatibility levels, according to IEC 61076-1	10
4.2 Classification into climatic categories.....	11
4.3 Contact terminations	11
4.4 Available connector codings.....	11
4.5 Ratings	12
4.6 Marking.....	12
4.7 Safety aspects	12
5 Dimensional information	12
5.1 General.....	12
5.2 Survey of styles and variants	12
5.2.1 General	12
5.2.2 Fixed connectors	12
5.2.3 Free connectors.....	19
5.3 Interface dimension	28
5.3.1 Outer push-pull locking: male fixed connector side view	28
5.3.2 Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2	28
5.3.3 Inner push-pull locking: female fixed connector side view and male free connector side view with details for both.....	31
5.4 Gauges	33
6 Characteristics	34
6.1 Classification into climatic category	34
6.2 Electrical characteristics	34
6.2.1 Voltage proof.....	34
6.2.2 Rated voltage – Rated impulse voltage – Pollution degree.....	34
6.2.3 Current-carrying capacity.....	34
6.2.4 Contact resistance	34
6.2.5 Insulation resistance.....	35
6.2.6 Transmission performance.....	35
6.3 Mechanical characteristics	35
6.3.1 Mating interface.....	35
6.3.2 Push-pull locking mechanism.....	36
6.4 Other characteristics	37
6.4.1 Vibration (sinusoidal)	37
6.4.2 Shock	37
6.4.3 Degree of protection provided by enclosures (IP-code).....	37
7 Test schedule	37
7.1 General.....	37
7.2 Test schedule	38

7.2.1	Test group P – Preliminary	38
7.2.2	Test group AP – Dynamic/climatic	38
7.2.3	Test group BP – Mechanical endurance	38
7.2.4	Test group CP – Electrical load	39
7.2.5	Test group DP – Chemical resistivity	39
7.2.6	Test group EP – Connection method tests	39
7.2.7	Test group FP – Electrical transmission requirements	39
Annex A (informative) Diameter of the female connector body		40
Bibliography		41
Figure 1 – Tube insert, male contacts, mounting without thread (thread on tube) and without outer push-pull locking		13
Figure 2 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, square flange front mounting		14
Figure 3 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5		14
Figure 4 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5		15
Figure 5 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5		15
Figure 6 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5		16
Figure 7 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5 and mounting orientation		16
Figure 8 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5		17
Figure 9 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5		17
Figure 10 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5		18
Figure 11 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5 and mounting orientation		18
Figure 12 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5		19
Figure 13 – Rewireable connector, male contacts, straight version, with outer push-pull locking		20
Figure 14 – Rewireable connector, male contacts, angled version, with outer push-pull locking		20
Figure 15 – Non-rewireable connector, male contacts, straight version, with outer push-pull locking		21
Figure 16 – Non-rewireable connector, male contacts, angled version, with outer push-pull locking		22
Figure 17 – Rewireable connector, female contacts, straight version, with outer push-pull locking		22
Figure 18 – Rewireable connector, female contacts, angled version, with outer push-pull locking		23
Figure 19 – Non-rewireable connector, female contacts, straight version, with outer push-pull locking		24

Figure 20 – Non-rewireable connector, female contacts, angled version, with outer push-pull locking.....	25
Figure 21 – Rewireable connector, male contacts, straight version, with inner push-pull locking.....	25
Figure 22 – Rewireable connector, male contacts, angled version, with inner push-pull locking.....	26
Figure 23 – Non-rewireable connector, male contacts, straight version, with inner push-pull locking.....	27
Figure 24 – Non-rewireable connector, male contacts, angled version, with inner push-pull locking.....	27
Figure 25 – Outer push-pull locking: male fixed connector side view.....	28
Figure 26 – Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connector.....	30
Figure 27 – Inner push-pull-locking: female fixed connector side view and male free connector side view with details for both.....	32
Figure A.1 – Diameter of the female connector body.....	40
Table 1 – Available connector codings.....	11
Table 2 – Styles of fixed connectors.....	13
Table 3 – Styles of free connectors.....	19
Table 4 – Dimensions of style JM-OP, Figure 13.....	20
Table 5 – Dimensions of style KM-OP, Figure 14.....	21
Table 6 – Dimensions of style LM-OP, Figure 15.....	21
Table 7 – Dimensions of style MM-OP, Figure 16.....	22
Table 8 – Dimensions of style JF-OP, Figure 17.....	23
Table 9 – Dimensions of style KF-OP, Figure 18.....	23
Table 10 – Dimensions of style LF-OP, Figure 19.....	24
Table 11 – Dimensions of style MF-OP, Figure 20.....	25
Table 12 – Dimensions of style JM-IP, Figure 21.....	26
Table 13 – Dimensions of style KM-IP, Figure 22.....	26
Table 14 – Dimensions of style LM-IP, Figure 23.....	27
Table 15 – Dimensions of style MM-OP, Figure 24.....	27
Table 16 – Dimensions of fixed connector with push-pull housing and male contacts.....	28
Table 17 – Dimensions for Figure 17.....	30
Table 18 – Dimensions for Figure 27.....	33
Table 19 – Climatic category.....	34
Table 20 – Insertion and withdrawal forces for the locking mechanism.....	36
Table 21 – Number of test specimens.....	38
Table 22 – Test group BP.....	39
Table A.1 – Diameter of the female connector body, dimension X.....	40

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CONNECTORS FOR ELECTRICAL AND ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS –

Part 2-010: Circular connectors – Detail specification for push-pull connectors with locking mechanism, based on mating interfaces according to IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 and IEC 61076-2-113

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is an intermediate specification made available to the public and needing a lower level of consensus than an International Standard to be approved by vote (simple majority).

IEC PAS 61076-2-010 has been processed by subcommittee 48B: Electrical connectors, of IEC technical committee 48: Electrical connectors and mechanical structures for electrical and electronic equipment.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
48B/2796/DPAS	48B/2817/RVDPAS

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

An International Standard is under preparation by IEC SC48B, to be published as IEC 61076-2-010 (if approved). This PAS will be withdrawn upon publication of the International Standard.


A list of all parts in the IEC 61076 series, published under the general title *Connectors for electrical and electronic equipment – Product requirements*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

This PAS shall remain valid for an initial maximum period of 2 years starting from the publication date. The validity may be extended for a single period up to a maximum of 2 years, at the end of which it shall be published as another type of normative document, or shall be withdrawn.

IECNORM.COM : Click to view the full PDF of IEC PAS 61076-2-010:2020

INTRODUCTION

IEC SC 48B – Electrical connectors Specification available from: IEC General secretariat or from the addresses shown on the inside cover.	IEC PAS 61076-2-010 Ed. 1
ELECTRONIC COMPONENTS DETAIL SPECIFICATION in accordance with IEC 61076-1	
 IEC	Circular M12 connectors with push-pull locking for power, signal and data transmission Fixed connectors with male and female contacts, mateable with M12 screw or push-pull plugs Free cable connectors with male or female contacts with push-pull or screw locking Rewireable – Non-rewireable Fixed connectors, with front, rear or single hole mounting Straight and right-angled free cable connectors

IECNORM.COM : Click to view the full PDF of IEC PAS 61076-2-010:2020

CONNECTORS FOR ELECTRICAL AND ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS –

Part 2-010: Circular connectors – Detail specification for push-pull connectors with locking mechanism, based on mating interfaces according to IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 and IEC 61076-2-113

1 Scope

This part of IEC 61076 specifies circular connectors with a push-pull locking mechanism of a size derived from and thus being compatible with M12 screw-locking connectors (free connectors with screw-locking according to IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113 are compatible to push-pull fixed interfaces according to this document) and with mating interfaces according to IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113.

NOTE 1 M12 is the dimension of the thread of the screw-locking mechanism of circular connectors with M12 screw-locking.

This document covers both

- 1) power connectors with current ratings up to 16 A and voltage ratings up to 630 V, typically used for power supply and power applications in industrial premises, and
- 2) connectors for data and signal transmission with frequencies up to 500 MHz.

These connectors consist of both, fixed and free connectors, either rewirable or non-rewirable, with M12 push-pull locking as explained above. Male connectors have round contacts from Ø0,6 mm up to Ø1,5 mm. In addition, the push-pull mechanisms consist of two different push-pull designs:

- a) An outer push-pull for male and female fixed connector, where the locking groove is placed onto the outer cylindric surface of the housing. The outer push-pull for female fixed connectors is made for two different types of male connectors. It has locking means for both types on its outer surface.

NOTE 2 For design and dimensions, see 5.3.1 and 5.3.2.

- b) An inner push-pull for female fixed connectors, where the locking means are placed onto the inner cylindric surface of the housing.

NOTE 3 For design and dimensions, see 5.3.3.

The different codings provided by IEC 61076-2 and mentioned within this document, prevent the mating of accordingly coded male or female connectors to any other similarly sized interfaces, covered by other standards and the cross-mating between the different codings provided by IEC 61076-2.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-581, *International Electrotechnical Vocabulary (IEV) – Part 581: Electromechanical components for electronic equipment* (available at <http://www.electropedia.org>)

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 60512-2-1, *Connectors for electronic equipment – Tests and measurements – Part 2-1: Electrical continuity and contact resistance tests – Test 2a: Contact resistance – Millivolt level method*

IEC 60512-3-1, *Connectors for electronic equipment – Tests and measurements – Part 3-1: Insulation tests – Test 3a: Insulation resistance*

IEC 60512-4-1, *Connectors for electronic equipment – Tests and measurements – Part 4-1: Voltage stress tests – Test 4a: Voltage proof*

IEC 60512-5-1, *Connectors for electronic equipment – Tests and measurements – Part 5-1: Current-carrying capacity tests – Test 5a: Temperature rise*

IEC 60512-6-3, *Connectors for electronic equipment – Tests and measurements – Part 6-3: Dynamic stress tests – Test 6c: Shock*

IEC 60512-6-4, *Connectors for electronic equipment – Tests and measurements – Part 6-4: Dynamic stress tests – Test 6d: Vibration (sinusoidal)*

IEC 60512-9-1, *Connectors for electronic equipment – Tests and measurements – Part 9-1: Endurance tests – Test 9a: Mechanical operation*

IEC 60512-13-1, *Connectors for electronic equipment – Tests and measurements – Part 13-1: Mechanical operation tests – Test 13a: Engaging and separating forces*

IEC 60512-13-2, *Connectors for electronic equipment – Tests and measurements – Part 13-2: Mechanical operation tests – Test 13b: Insertion and withdrawal forces*

IEC 60512-13-5, *Connectors for electronic equipment – Tests and measurements – Part 13-5: Mechanical operation tests – Test 13e: Polarizing and keying method*

IEC 60512-15-6, *Connectors for electronic equipment – Tests and measurements – Part 15-6: Connector tests (mechanical) – Test 15f: Effectiveness of connector coupling devices*

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

IEC 60603-7:2008, *Connectors for electronic equipment – Part 7: Detail specification for 8-way, unshielded, free and fixed connectors*

IEC 60664-1, *Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests*

IEC 60998-2-1:2002, *Connecting devices for low-voltage circuits for household and similar purposes – Part 2-1: Particular requirements for connecting devices as separate entities with screw-type clamping units*

IEC 61076-1:2006, *Connectors for electronic equipment – Product requirements – Part 1: Generic specification*

IEC 61076-2-101, *Connectors for electronic equipment – Product requirements – Part 2-101: Circular connectors – Detail specification for M12 connectors with screw-locking*

IEC 61076-2-109, *Connectors for electronic equipment – Product requirements – Part 2-109: Circular connectors – Detail specification for connectors with M12x1 screw-locking, for data transmission frequencies up to 500 MHz*

IEC 61076-2-111, *Connectors for electrical and electronic equipment – Product requirements – Part 2-111: Circular connectors – Detail specification for power connectors with M12 screw-locking*

IEC 61076-2-113, *Connectors for electronic equipment – Product requirements – Part 2-113: Circular connectors – Detail specification for connectors with M12 screw-locking, with power and signal contacts for data transmission with frequencies up to 100 MHz*

IEC 61984, *Connectors – Safety requirements and tests*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-581 shall apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

mounting orientation

circular mounting position of the connector in relation to the polarization of the mating interface.

Note 1 to entry: Where the free connector has an angled cable entry (as opposed to a straight cable entry), the angle between the entry direction and the polarization keyway should be specified.

4 Technical information

4.1 System of levels

4.1.1 Performance levels

Performance levels for these connectors (mating cycles for the mating interface only) are specified in the applicable standard, either IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113. The same performance level (number of cycles of mechanical operations, i.e. one locking and one unlocking operation) shall apply to the specific complete connector with the push-pull locking described herein.

A qualification of the push-pull locking mechanism for the highest performance level shall cover the qualifications for all lower performance levels required by the various mating interfaces, which are not subject to re-qualification for all those aspects already covered in the relevant IEC standards mentioned above.

4.1.2 Compatibility levels, according to IEC 61076-1

The connectors according to this document are intermateable according to IEC 61076-1.

4.2 Classification into climatic categories

For the classifications of the connectors into climatic categories in accordance with the general rules given in IEC 60068-1, see the applicable standard, either IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113.

The qualification of the push-pull locking interface for the most demanding climatic category (lowest LCT, highest UCT, highest number of days of damp heat, steady state) will cover all less demanding climatic categories established for the mating interfaces described in the above-mentioned IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113.

4.3 Contact terminations

The contact terminations shall be of the following types: screw, crimp, insulation piercing, insulation displacement, press-in or solder according to the applicable standard for the mating interface (either IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113).

4.4 Available connector codings

The available codings are shown in Table 1.

Table 1 – Available connector codings

Coding	Type	Reference
A	5-way	IEC 61076-2-101
	8-way	
	12-way	
	17-way	
B	5-way	
C	3-way	
	4-way	
	5-way	
	6-way	
D	4-way	
P	5-way	
H	8-way	IEC 61076-2-109
X	8-way	
F (for outer push-pull)	5-way	IEC 61076-2-111
K	5-way	
L	5-way	
	4-way	
M	6-way	
S	4-way	
T	4-way	
Type 1	6-way	IEC 61076-2-113
Type 2	8-way	
Type 3	6-way	
Type 4	8-way	

4.5 Ratings

Rated voltages and currents are specified in IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113, respectively.

4.6 Marking

The marking of the connector and the package shall be in accordance with 2.7 of IEC 61076-1:2006.

4.7 Safety aspects

For safety aspects IEC 61984 shall be considered unless otherwise specified in the applicable standard for the mating interface (either IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113).

5 Dimensional information

5.1 General

Throughout this document the dimensions are in mm. The drawings are shown in the first angle projection. The shape of the connectors may deviate from those given in the following drawings if the specified dimensions are not influenced. See Annex A for recommended dimensions for the female connector body diameter.

Missing dimensions shall be chosen according to common characteristics and intended use.

5.2 Survey of styles and variants

5.2.1 General

For all connector styles with cables, the length of the cable or wire shall be agreed between manufacturer and user.

The interface dimensions of the free cable connectors shall be chosen according to the common characteristics of the fixed connector styles.

For reliable intermateability, the dimensions of the free connector body as detailed in IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113 shall be met for the free connector body with screw or push-pull locking.

5.2.2 Fixed connectors

5.2.2.1 General


Table 2 shows the styles of fixed connectors.

Table 2 – Styles of fixed connectors

Style	Description
AM-OP	Tube insert, male contacts, mounting without thread (thread on tube) and without outer push-pull locking
DM-OP	Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, square flange front mounting
EM-OP	Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5
FM-OP	Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5
EF-OP	Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5
FF-OP	Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5
GF-OP	Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5 and mounting orientation
IF-OP	Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5
EF-IP	Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5
FF-IP	Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5
GF-IP	Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5 and mounting orientation
IF-IP	Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5

5.2.2.2 Style AM-OP

Figure 1 shows a tube insert, male contacts, mounting without thread (thread on tube) and without outer push-pull locking.



IEC

Figure 1 – Tube insert, male contacts, mounting without thread (thread on tube) and without outer push-pull locking

5.2.2.3 Style DM-OP

Figure 2 shows a fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, square flange front mounting.




Figure 2 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, square flange front mounting

5.2.2.4 Style EM-OP

Figure 3 shows a fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5.




Figure 3 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5

5.2.2.5 Style FM-OP

Figure 4 shows a fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5.




Figure 4 – Fixed connector, male contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5

5.2.2.6 Style EF-OP

Figure 5 shows a fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5.




Figure 5 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5

5.2.2.7 Style FF-OP

Figure 6 shows a fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5.




Figure 6 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5

5.2.2.8 Style GF-OP

Figure 7 shows a fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, a single hole front mounting thread M16 × 1,5 and mounting orientation.




Figure 7 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5 and mounting orientation

5.2.2.9 Style IF-OP

Figure 8 shows a fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5.




Figure 8 – Fixed connector, female contacts, mounting with thread M12 × 1 and outer push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5

5.2.2.10 Style EF-IP

Figure 9 shows a fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5.




Figure 9 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5

5.2.2.11 Style FF-IP

Figure 10 shows a fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5.




Figure 10 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M20 × 1,5

5.2.2.12 Style GF-IP

Figure 11 shows a fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, a single hole front mounting thread M16 × 1,5 and mounting orientation.




Figure 11 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole front mounting thread M16 × 1,5 and mounting orientation

5.2.2.13 Style IF-IP

Figure 12 shows a fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5.




Figure 12 – Fixed connector, female contacts, mounting with thread M12 × 1 and inner push-pull locking, with wire ends, single hole rear mounting thread M16 × 1,5

5.2.3 Free connectors

5.2.3.1 General


Table 3 shows the styles of free connectors.

Table 3 – Styles of free connectors

Style	Description
JM-OP	Rewireable connector, male contacts, straight version, with outer push-pull locking
KM-OP	Rewireable connector, male contacts, angled version, with outer push-pull locking
LM-OP	Non-rewireable connector, male contacts, straight version, with outer push-pull locking
MM-OP	Non-rewireable connector, male contacts, angled version, with outer push-pull locking
JF-OP	Rewireable connector, female contacts, straight version, with outer push-pull locking
KF-OP	Rewireable connector, female contacts, straight version, with outer push-pull locking
LF-OP	Non-rewireable connector, female contacts, angled version, with outer push-pull locking
MF-OP	Non-rewireable connector, female contacts, angled version, with outer push-pull locking
JM-IP	Rewireable connector, male contacts, straight version, with inner push-pull locking
KM-IP	Rewireable connector, male contacts, angled version, with inner push-pull locking
LM-IP	Non-rewireable connector, male contacts, straight version with inner push-pull locking
MM-IP	Non-rewireable connector, male contacts, angled version, with inner push-pull locking

5.2.3.2 Style JM-OP

Figure 13 shows a rewireable connector, male contacts, straight version, with outer push-pull locking. Table 4 shows the dimensions of style JM-OP.



^a Cable outlet alternatively inside.

^b Cable outlet diameter range upon agreement.

Figure 13 – Rewireable connector, male contacts, straight version, with outer push-pull locking


Table 4 – Dimensions of style JM-OP, Figure 13

Dimensions in millimetres

Coding	L1 max.	ØD max.
A, B, C, D, P	65	22
X, H	65	22
F, K, L, M	70	25
S, T	70	23
Type 1 to 4	65	22

5.2.3.3 Style KM-OP

Figure 14 shows a rewireable connector, male contacts, angled version, with outer push-pull locking. Table 5 shows the dimensions of style KM-OP.



^a Cable outlet alternatively inside.

^b Cable outlet diameter range upon agreement.

Figure 14 – Rewireable connector, male contacts, angled version, with outer push-pull locking


Table 5 – Dimensions of style KM-OP, Figure 14

Dimensions in millimetres

Coding	L1 max.	L2 max.	L3 max.	øD max.
A, B, C, D, P	60,5	11	31,5	22
X, H	60,5	11	31,5	22
F, K, L, M	80	14	40	25
S, T	80	13	40	23
Type 1 to 4	60,5	11	31,5	22

5.2.3.4 Style LM-OP

Figure 15 shows a non-rewireable connector, male contacts, straight version, with outer push-pull locking. Table 6 shows the dimensions of style LM-OP.



IEC

Figure 15 – Non-rewireable connector, male contacts, straight version, with outer push-pull locking**Table 6 – Dimensions of style LM-OP, Figure 15**

Dimensions in millimetres

Coding	L1 max.	øD max.
A, B, C, D, P	55	22
X, H	55	22
F, K, L, M	65	22
S, T	57	22
Type 1 to 4	55	22

5.2.3.5 Style MM-OP

Figure 16 shows a non-rewireable connector, male contacts, angled version, with outer push-pull locking. Table 7 shows the dimensions of style MM-OP.




Figure 16 – Non-rewireable connector, male contacts, angled version, with outer push-pull locking


Table 7 – Dimensions of style MM-OP, Figure 16

Dimensions in millimetres

Coding	L1 max.	L2 max.	L3 max.	ØD max.
A, B, C, D, P	36	7,5	31,5	22
X, H	36	7,5	31,5	22
F, K, L, M	41	9	40	22
S, T	36	8	33,5	22
Type 1 to 4	36	7,5	31,5	22

5.2.3.6 Style JF-OP

Figure 17 shows a rewireable connector, female contacts, straight version, with outer push-pull locking. Table 8 shows the dimensions of style JF-OP.



^a Cable outlet alternatively inside.

^b Cable outlet diameter range upon agreement.

Figure 17 – Rewireable connector, female contacts, straight version, with outer push-pull locking


Table 8 – Dimensions of style JF-OP, Figure 17

Dimensions in millimetres

Coding	L1 max.	øD max.
A, B, C, D, P	65	22
X, H	65	22
F, K, L, M	70	25
S, T	70	23
Type 1 to 4	65	22

5.2.3.7 Style KF-OP

Figure 18 shows a rewirable connector, female contacts, angled version, with outer push-pull locking. Table 9 shows the dimensions of style KF-OP.



^a Cable outlet alternatively inside.

^b Cable outlet diameter range upon agreement.

Figure 18 – Rewirable connector, female contacts, angled version, with outer push-pull locking**Table 9 – Dimensions of style KF-OP, Figure 18**

Dimensions in millimetres

Coding	L1 max.	L2 max.	L3 max.	øD max.
A, B, C, D, P	60,5	11	31,5	22
X, H	60,5	11	31,5	22
F, K, L, M	80	14	40	25
S, T	80	13	40	23
Type 1 to 4	60,5	11	31,5	22

5.2.3.8 Style LF-OP

Figure 19 shows a non-rewireable connector, female contacts, straight version, with outer push-pull locking. Table 10 shows the dimensions of style LF-OP.




Figure 19 – Non-rewireable connector, female contacts, straight version, with outer push-pull locking

Table 10 – Dimensions of style LF-OP, Figure 19

Dimensions in millimetres

Coding	L1 max.	ØD max.
A, B, C, D, P	55	22
X, H	55	22
F, K, L, M	65	22
S, T	57	22
Type 1 to 4	55	22

5.2.3.9 Style MF-OP

Figure 20 shows a non-rewireable connector, with female contacts, angled version, with outer push-pull locking. Table 11 shows the dimensions of style MF-OP.




Figure 20 – Non-rewireable connector, female contacts, angled version, with outer push-pull locking


Table 11 – Dimensions of style MF-OP, Figure 20

Dimensions in millimetres

Coding	L1 max.	L2 max.	L3 max.	ØD max.
A, B, C, D, P	36	7,5	31,5	22
X, H	36	7,5	31,5	22
F, K, L, M	41	9	40	22
S, T	36	8	33,5	22
Type 1 to 4	36	7,5	31,5	22

5.2.3.10 Style JM-IP

Figure 21 shows a rewireable connector, male contacts, angled version, with inner push-pull locking. Table 12 shows the dimensions of style JM-IP.



^a Cable outlet alternatively inside.

^b Cable outlet diameter range upon agreement.

Figure 21 – Rewireable connector, male contacts, straight version, with inner push-pull locking


Table 12 – Dimensions of style JM-IP, Figure 21

Dimensions in millimetres

Coding	L1 max.	øD max.
A, B, C, D, P	65	22
X, H	65	22
K, L, M	70	25
S, T	70	23
Type 1 to 4	65	22

5.2.3.11 Style KM-IP

Figure 22 shows a rewirable connector, male contacts, angled version, with inner push-pull locking. Table 13 shows the dimensions of style KM-IP.



^a Cable outlet alternatively inside.

^b Cable outlet diameter range upon agreement.

Figure 22 – Rewirable connector, male contacts, angled version, with inner push-pull locking

Table 13 – Dimensions of style KM-IP, Figure 22

Dimensions in millimetres

Coding	L1 max.	L2 max.	L3 max.	øD max.
A, B, C, D, P	60,5	11	31,5	22
X, H	60,5	11	31,5	22
K, L, M	80	14	40	25
S, T	80	13	40	23
Type 1 to 4	60,5	11	31,5	22

5.2.3.12 Style LM-IP

Figure 23 shows a non-rewirable connector, male contacts, straight version, with inner push-pull locking. Table 14 shows the dimensions of style LM-IP.




Figure 23 – Non-rewireable connector, male contacts, straight version, with inner push-pull locking

Table 14 – Dimensions of style LM-IP, Figure 23

Dimensions in millimetres

Coding	L1 max.	ØD max.
A, B, C, D, P	55	22
X, H	55	22
K, L, M	65	22
S, T	57	22
Type 1 to 4	55	22

5.2.3.13 Style MM-IP

Figure 24 shows a non-rewireable connector, male contacts, angled version, with inner push-pull locking. Table 15 shows the dimensions of style MM-OP.




Figure 24 – Non-rewireable connector, male contacts, angled version, with inner push-pull locking

Table 15 – Dimensions of style MM-OP, Figure 24

Dimensions in millimetres

Coding	L1 max.	L2 max.	L3 max.	ØD max.
A, B, C, D, P	36	7,5	31,5	22
X, H	36	7,5	31,5	22
K, L, M	41	9	40	22
S, T	36	8	33,5	22
Type 1 to 4	36	7,5	31,5	22

5.3 Interface dimension

5.3.1 Outer push-pull locking: male fixed connector side view

See Figure 25 and Table 16.




Figure 25 – Outer push-pull locking: male fixed connector side view



Table 16 – Dimensions of fixed connector with push-pull housing and male contacts

Dimensions in millimetres

Letter	Minimum	Nominal	Maximum
AA 1)	Ø 10,50	Ø 10,55	Ø 10,60
AB	Ø 10,77	Ø 10,80	Ø 10,83
AC		M12x1	
AD	10		
AE	3,40	3,50	3,60
AF	40°	45°	50°
AG	R0,10		
AH	0,40	0,43	0,46
AI	44°	45°	46°
AJ	R0,10	R0,20	R0,30
AK	20°	25°	30°
AL	Ø 10,27	Ø 10,30	Ø 10,33
AM	1,95	2,00	2,05
AN	2,35	2,40	2,45
Flat areas are allowed.			

5.3.2 Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connectors type 1 and 2

See Figure 26 and Table 17.






Figure 26 – Outer push-pull locking: female fixed connector side view with details and engage-plane definition for male free cable connector

Table 17 – Dimensions for Figure 26

Dimensions in millimetres

Letter	Minimum	Nominal	Maximum
DA	Ø 12,32	Ø 12,35	Ø 12,38
DB	Ø 12,95	Ø 13,00	Ø 13,05
DC	Ø 13,48	Ø 13,50	Ø 13,52
DD	Ø 13,98	Ø 14,00	Ø 14,02
DE	Ø 13,75	Ø 13,80	Ø 13,85
DF		M12x1	
DG	R1,80	R2,00	R2,20
DH	2,85	2,90	2,95
DI	7,65	7,80	7,95
DJ	55°	60°	65°
DK	15°	16°	17°
DL	2,50	2,60	2,70
DM	4,95	5,00	5,05
DN	9,00		
DO	3,85	3,90	3,95
DP	0,70	0,80	0,90
DQ	13°	15°	17°
DR	R0,10	R0,20	R0,30
DS	15°	20°	25°
DT	R0,05	R0,10	R0,15
DU	0,40	0,50	0,60
DV	R0,45	R0,50	R0,55
DW	44°	45°	46°
DX	Ø 13,75	Ø 13,80	
DY	R0,05	R0,10	R0,15

Letter	Minimum	Nominal	Maximum
DZ	0,40	0,50	0,60
DAA	28°	30°	32°
CA	5,50	5,85	6,20
CB	See applicable standard for respective coding		
CD	See applicable standard for respective coding -0,4		
CE			14,50
CF	See applicable standard for respective coding -0,4		
CG			6,80
CH			14,50

5.3.3 Inner push-pull locking: female fixed connector side view and male free connector side view with details for both

See Figure 27 and Table 18.

IECNORM.COM : Click to view the full PDF of IEC PAS 61076-2-010:2020




Figure 27 – Inner push-pull-locking: female fixed connector side view and male free connector side view with details for both

Table 18 – Dimensions for Figure 27

Dimensions in millimetres

Letter	Minimum	Nominal	Maximum
FA		M12x1-6H	
FB	Ø 12,90	Ø 13,00	Ø 13,10
FC	Ø 13,30	Ø 13,35	Ø 13,40
FD	8,20		
FE	2,85	2,90	2,95
FF	0,75	0,80	0,85
FG	55°	60°	65°
FH			R0,20
FI			R0,20
FJ	34°	35°	36°
FK	54°	55°	56°
FL	Ø 12,20	Ø 12,25	Ø 12,30
FM	0,55	0,60	0,65
FN	29°	30°	31°
FO	Ø 12,10	Ø 12,15	Ø 12,20
EA	Ø 10,27	Ø 10,30	Ø 10,33
EB	Ø 10,77	Ø 10,80	Ø 10,83
EC	Ø 11,90	Ø 11,95	Ø 12,00
ED	See applicable standard for respective coding -0,4		
EE	8,00	8,10	8,20
EF	2,65	2,70	2,75
EG	58°	60°	62°
EH	3,40	3,50	3,60
EI	2,35	2,40	2,45
EJ	1,95	2,00	2,05
EK	0,40	0,43	0,46
EL	R0,10		
EM	44°	45°	46°
EN	40°	45°	50°
EO	Ø 10,75	Ø 10,80	Ø 10,85
EP	Ø 10,50	Ø 10,55	Ø 10,60
EQ	20°	25°	30°
ER	R0,10	R0,20	R0,30
ES	See applicable standard for respective coding		

5.4 Gauges

See the applicable standard, either IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113, for sizing gauges and retention force gauges.

6 Characteristics

6.1 Classification into climatic category

Conditions: IEC 60068-1 and Table 19.

Table 19 – Climatic category

Climatic category	Category temperature		Damp heat steady state		Days
	Lower	Upper	Temperature	Relative humidity	
	°C	°C	°C	%	
25/085/-	–25	+85	40	93	-

6.2 Electrical characteristics

6.2.1 Voltage proof

Conditions: IEC 60512-4-1, test 4a.

Standard atmospheric conditions.

Mated connectors.

Voltage proof according to the applicable standard, either IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113.

6.2.2 Rated voltage – Rated impulse voltage – Pollution degree

Conditions: IEC 60664-1.

Rated voltage, rated impulse voltage and pollution degree according to the applicable standard, either IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113.

The permissible rated voltage depends on the application or specified safety requirement. Reductions in creepage or clearance distances may occur due to the printed board or wiring used and shall be duly considered.

6.2.3 Current-carrying capacity

Conditions: IEC 60512-5-1, test 5a.

All contacts, but without PE and FE contacts.

The rated current is referenced in the IEC-document, listed in Table 1.

Values at 40 °C ambient temperature.

For rated current see the applicable standard, either IEC 61076-2-101, IEC 61076-2-109, IEC 61076-2-111 or IEC 61076-2-113.

6.2.4 Contact resistance

Conditions: IEC 60512-2-1, test 2a.

Standard atmospheric conditions