

# PUBLICLY AVAILABLE SPECIFICATION

## PRE-STANDARD

Radio-frequency connectors –  
Part 42: Sectional specification for CQN series quick lock RF coaxial connectors



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00

# PUBLICLY AVAILABLE SPECIFICATION

## PRE-STANDARD

---

**Radio-frequency connectors –  
Part 42: Sectional specification for CQN series quick lock RF coaxial connectors**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

U

ICS 33.120.30

ISBN 978-2-88910-802-2

## CONTENTS

|                                                                       |    |
|-----------------------------------------------------------------------|----|
| FOREWORD.....                                                         | 3  |
| INTRODUCTION.....                                                     | 4  |
| 1 Scope.....                                                          | 5  |
| 2 Normative references .....                                          | 5  |
| 3 Mating face and gauge information .....                             | 5  |
| 3.1 Dimensions-General connectors – Grade 2 .....                     | 5  |
| 3.1.1 Connector with pin-centre contact.....                          | 5  |
| 3.1.2 Connector with socket-centre contact .....                      | 8  |
| 3.2 Gauges .....                                                      | 9  |
| 3.2.1 Gauge pins for socket-centre contact.....                       | 9  |
| 3.2.2 Test procedure .....                                            | 10 |
| 3.3 Dimensions- standard test connectors – Grade 0 .....              | 11 |
| 3.3.1 Connector with pin-centre contact.....                          | 11 |
| 3.3.2 Connector with socket-centre contact .....                      | 13 |
| 4 Quality assessment procedure.....                                   | 14 |
| 4.1 General.....                                                      | 14 |
| 4.2 Rating and characteristics (see Clause 6 of IEC 61169-1) .....    | 14 |
| 4.3 Test schedule and inspection requirements – Acceptance tests..... | 17 |
| 4.3.1 Acceptance tests .....                                          | 17 |
| 4.3.2 Periodic tests .....                                            | 18 |
| 4.4 Procedures.....                                                   | 20 |
| 4.4.1 Quality conformance inspection .....                            | 20 |
| 4.4.2 Qualification approval and its maintenance .....                | 20 |
| 5 Instructions for preparation of detail specifications .....         | 20 |
| 5.1 General.....                                                      | 20 |
| 5.2 Identification of the component.....                              | 20 |
| 5.3 Performance.....                                                  | 20 |
| 5.4 Marking, ordering information and related matters.....            | 21 |
| 5.5 Selection of tests, test conditions and severities.....           | 21 |
| 5.6 Blank detail specification pro-forma for type CQN connector ..... | 22 |
| Figure 1 – Connector with pin-centre contact .....                    | 6  |
| Figure 2 – Connector with socket-centre contact.....                  | 8  |
| Figure 3 – Gauge pins for socket-centre contact .....                 | 9  |
| Figure 4 – Connector with pin-centre contact .....                    | 11 |
| Figure 5 – Connector with socket-centre contact.....                  | 13 |
| Table 1 – Dimensions of connector with pin-centre contact .....       | 7  |
| Table 2 – Dimensions of connector with socket-centre contact.....     | 9  |
| Table 3 – Dimensions of gauge pins for socket-centre contact .....    | 10 |
| Table 4 – Dimensions of connector with pin-centre contact .....       | 12 |
| Table 5 – Dimensions of connector with socket-centre contact.....     | 14 |
| Table 6 – Rating and characteristics .....                            | 15 |
| Table 7 – Acceptance tests .....                                      | 17 |
| Table 8 – Periodic tests .....                                        | 18 |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**RADIO-FREQUENCY CONNECTORS –****Part 42: Sectional specification for CQN series  
quick lock RF coaxial connectors****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC-PAS 61169-42 has been processed by subcommittee 46F: RF and microwave passive components, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

| Draft PAS   | Report on voting |
|-------------|------------------|
| 46F/102/PAS | 46F/113/RVD      |

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single 3-year period, following which it shall be revised to become another type of normative document, or shall be withdrawn.

## INTRODUCTION

International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning IEC 61169-42.

IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from:

US Pat. US7.351.088B1  
CHINA Pat. ZL200620046522.6

The owner of the patents is Mr. Qu jinliang  
Address: Room 302, Gudai road 1266–48, Ghanghai 201102 China (021-54148062).

Shaanxi huada S&T CO., LTD  
Address: No.3 Dianzixijie Electronic Industrial Park, Xi'an P.R China  
HUADA is the trade name of Shaanxi huada S&T CO., LTD.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

## RADIO-FREQUENCY CONNECTORS –

### Part 42: Sectional specification for CQN series quick lock RF coaxial connectors

#### 1 Scope

CQN series quick lock RF coaxial connectors with impedance 50  $\Omega$  are used in microwave, telecommunication, wireless and other fields, connecting with R.F. cables or micro-strips. The operating frequency limit is up to 11 GHz.

This PAS, which is a sectional specification, provides information and rules for the preparation of detail specifications for CQN series R.F. coaxial connectors together with the pro-forma blank detail specification.

It also prescribes mating face dimensions for general connectors-grade 2, dimensional details of standard test connectors-grade 0, gauging information and tests selected from IEC 61169-1, applicable to all detail specifications relating to CQN series connectors.

This specification indicates the recommended performance characteristics to be considered when writing a detail specification and it covers test schedules and inspection requirements for assessment levels M and H.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61169-1:1992, *Radio-frequency connectors – Part 1: Generic specification – General requirements and measuring methods*<sup>1)</sup>

Amendment 1 (1996)

Amendment 2 (1997)

#### 3 Mating face and gauge information

##### 3.1 Dimensions-General connectors – Grade 2


###### 3.1.1 Connector with pin-centre contact

Metric dimension are original dimensions.

All undimensioned pictorial configurations are for reference purpose only.

---

<sup>1)</sup> There exists a consolidated edition 1.2 (1998) that comprises IEC 61169-1, its Amendment 1 and its Amendment 2.




NOTE For dimensions and notes, see Table 1.

**Figure 1 – Connector with pin-centre contact**

**Table 1 – Dimensions of connector with pin-centre contact**

| Ref.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | mm           |       | Notes  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------|--------|
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Min.         | Max.  |        |
| <i>a</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 7,00 nominal |       | Note 4 |
| <i>b</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 9,05         | —     |        |
| <i>c</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 10,05        | —     |        |
| <i>d</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | —            | 19,00 |        |
| <i>e</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | —            | 9,80  | Note 5 |
| <i>f</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 1,60         | 1,68  |        |
| <i>g</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | —            | 7,60  |        |
| <i>h</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 2,72         | 4,00  |        |
| <i>j</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 0,80         | 1,00  |        |
| <i>k</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | —            | —     | Note 4 |
| <i>m</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | —            | 5,30  |        |
| <i>n</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 5,00         | 6,28  |        |
| <i>p</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | —            | 2,40  |        |
| <i>r</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | —            | 4,70  |        |
| <p>NOTE 1 Mechanical and electrical reference plane.</p> <p>NOTE 2 Design and location of the seal ring is optional, but should meet environmental requirements.</p> <p>NOTE 3 Radius or angle, plane part is 0,25 mm max.</p> <p>NOTE 4 Diameters are chosen to obtain a normal impedance of 50 <math>\Omega</math> and meet electrical and mechanical requirements.</p> <p>NOTE 5 Prefix locknut (maximal dimension).</p> <p>NOTE 6 Chamfer.</p> <p>NOTE 7 Design of spring is optional, but should meet mechanical performance requirements.</p> |              |       |        |

### 3.1.2 Connector with socket-centre contact



NOTE For dimensions and notes, see Table 2.

Figure 2 – Connector with socket-centre contact

**Table 2 – Dimensions of connector with socket-centre contact**

| Ref.     | mm           |      | Notes  |
|----------|--------------|------|--------|
|          | Min.         | Max. |        |
| <i>a</i> | 7,00 nominal |      | Note 3 |
| <i>b</i> | 8,30         | 8,50 |        |
| <i>c</i> | 8,70         | 8,90 |        |
| <i>d</i> | 8,90         | 9,00 |        |
| <i>e</i> | —            | 10   |        |
| <i>f</i> | 4,20         | 4,25 |        |
| <i>g</i> | 4,90         | 5,00 |        |
| <i>h</i> | 6,15         | 6,25 |        |
| <i>i</i> | 11,00        | —    |        |
| <i>j</i> | —            | —    | Note 3 |
| <i>k</i> | —            | —    |        |
| <i>m</i> | 5,33         | —    |        |
| <i>n</i> | 1,00         | 1,20 |        |


NOTE 1 Mechanical and electrical reference plane.

NOTE 2 Design of centre contact is optional, but should meet electrical and mechanical requirements.

NOTE 3 Diameters are chosen to obtain a normal impedance of 50  $\Omega$  and meet electrical and mechanical performance requirements.

## 3.2 Gauges

### 3.2.1 Gauge pins for socket-centre contact



NOTE For dimensions and notes, see Table 3.

**Figure 3 – Gauge pins for socket-centre contact**

**Table 3 – Dimensions of gauge pins for socket-centre contact**

| Gauge A<br>Maximum material for sizing purposes                 |       |       | Gauge B<br>Minimum material for measurement<br>of retention force<br>Mass of gauge: 56 g ± 2 g |       |
|-----------------------------------------------------------------|-------|-------|------------------------------------------------------------------------------------------------|-------|
| Ref.                                                            | mm    |       | mm                                                                                             |       |
|                                                                 | Min.  | Max.  | Min.                                                                                           | Max.  |
| <i>a</i>                                                        | 1,680 | 1,685 | 1,595                                                                                          | 1,600 |
| <i>b</i>                                                        | 1,72  | 2,92  | 1,72                                                                                           | 2,92  |
| material: steel, polished, surface roughness: Ra=0,4 µm maximum |       |       |                                                                                                |       |

### 3.2.2 Test procedure

Gauge A shall be inserted into the socket-centre contact three times with a minimum depth of 1,72 mm. This is a sizing operation and should only be carried out when the socket-centre contact is removed from the connector.


After this, gauge B shall be inserted into the socket-centre contact. The contact shall retain the mass of the gauge in a vertical downward position. The test shall also be carried out on connector when the socket-centre contact is not removed.

Additional test:

At the conclusion of the tests and if prescribed in the DS, the force necessary to insert gauge A shall be measured. When this additional test is required, the force required shall not exceed 9,0 N.

### 3.3 Dimensions- standard test connectors – Grade 0

#### 3.3.1 Connector with pin-centre contact




NOTE For dimensions and notes, see Table 4.

**Figure 4 – Connector with pin-centre contact**

**Table 4 – Dimensions of connector with pin-centre contact**

| Ref.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | mm           |       | Notes  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------|--------|
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Min.         | Max.  |        |
| <i>a</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 7,00 nominal |       | Note 4 |
| <i>b</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 9,05         | —     |        |
| <i>c</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 10,05        | —     |        |
| <i>d</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | —            | 19,00 |        |
| <i>e</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | —            | 9,60  | Note 5 |
| <i>f</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 1,64         | 1,66  |        |
| <i>g</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | —            | 7,50  |        |
| <i>h</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 3,00         | 3,80  |        |
| <i>j</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 0,90         | 1,00  |        |
| <i>k</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | —            | —     | Note 4 |
| <i>m</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | —            | 5,30  |        |
| <i>n</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 5,30         | 6,00  |        |
| <i>p</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | —            | 2,30  |        |
| <i>r</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | —            | 4,60  |        |
| <p>NOTE 1 Mechanical and electrical reference plane, surface roughness: <math>R_a = 0,8 \mu\text{m}</math>.</p> <p>NOTE 2 Design and location of the seal ring is optional, but should meet environmental performance requirements.</p> <p>NOTE 3 Radius or angle, plane part is 0,25 mm max.</p> <p>NOTE 4 Diameters are chosen to obtain a characteristic impedance of <math>50 \Omega \pm 0,5 \Omega</math>.</p> <p>NOTE 5 Prefix locknut (maximal dimension).</p> <p>NOTE 6 Chamfer.</p> <p>NOTE 7 Design of spring is optional, but should meet mechanical performance requirements.</p> |              |       |        |

### 3.3.2 Connector with socket-centre contact



NOTE For dimensions and notes, see Table 5.

Figure 5 – Connector with socket-centre contact

**Table 5 – Dimensions of connector with socket-centre contact**

| Ref.                                                                                                                      | mm           |       | Notes  |
|---------------------------------------------------------------------------------------------------------------------------|--------------|-------|--------|
|                                                                                                                           | Min.         | Max.  |        |
| <i>a</i>                                                                                                                  | 7,00 nominal |       | Note 3 |
| <i>b</i>                                                                                                                  | 8,35         | 8,45  |        |
| <i>c</i>                                                                                                                  | 8,75         | 8,85  |        |
| <i>d</i>                                                                                                                  | 8,90         | 8,95  |        |
| <i>e</i>                                                                                                                  | —            | 10,00 |        |
| <i>f</i>                                                                                                                  | 4,20         | 4,25  |        |
| <i>g</i>                                                                                                                  | 4,90         | 4,95  |        |
| <i>h</i>                                                                                                                  | 6,15         | 6,20  |        |
| <i>i</i>                                                                                                                  | 11,00        | —     |        |
| <i>j</i>                                                                                                                  | —            | —     | Note 3 |
| <i>k</i>                                                                                                                  | —            | —     |        |
| <i>m</i>                                                                                                                  | 5,33         |       |        |
| <i>n</i>                                                                                                                  | 1,00         | 1,10  |        |
| NOTE 1 Mechanical and electrical reference plane, surface roughness: Ra=0,8 µm.                                           |              |       |        |
| NOTE 2 Remove flash carefully.                                                                                            |              |       |        |
| NOTE 3 Diameters are chosen to obtain a normal impedance of 50 Ω ± 0,5 Ω and meet electrical and mechanical requirements. |              |       |        |
| NOTE 4 Design of centre contact is optional, but should meet electrical and mechanical requirements.                      |              |       |        |

## 4 Quality assessment procedure

### 4.1 General

The following subclauses provide recommended rating, performance and test conditions to be considered when writing a detail specification. They also provide an appropriate schedule of tests with minimum levels of conformance inspection sampling, together with the pro forma blank detail specification (BDS) and instructions for the preparation of a detail specification.

### 4.2 Rating and characteristics (see Clause 6 of IEC 61169-1)

The values indicated below are recommended for CQN series RF connectors and are given for the writer of the detail specification. They are applicable for the condition when the connectors are fully mated.

Certain tests are listed without any recommended values being given. These tests will usually not be required. When these tests are required, appropriate values shall be entered in the detail specification at the discretion of the specification writer.

### Table 6 – Rating and characteristics

| Rating and characteristics                                  | Test method<br>IEC 61169-1<br>Subclause | Values                                                                  | Remarks deviations<br>from standard<br>test method |
|-------------------------------------------------------------|-----------------------------------------|-------------------------------------------------------------------------|----------------------------------------------------|
| <b>Electrical</b>                                           |                                         |                                                                         |                                                    |
| Nominal impedance                                           |                                         | 50 Ω                                                                    |                                                    |
| Frequency range                                             |                                         | DC to 11GHz                                                             | Or upper frequency<br>limit of cable               |
| Reflection factor <sup>1)</sup>                             | 9.2.1                                   |                                                                         |                                                    |
| General connectors                                          |                                         | DC to 3 GHz                                                             |                                                    |
| - straight styles                                           |                                         | 0,07 max.<br>3 GHz to 6 GHz<br>0,09 max.<br>6 GHz to 11 GHz<br>0,13 max |                                                    |
| - right-angle styles                                        |                                         | See DS                                                                  |                                                    |
| - component mounting styles                                 |                                         | See DS                                                                  |                                                    |
| - solder bucket and PCB mounting styles                     |                                         | See DS                                                                  |                                                    |
| Centre contact resistance <sup>2)</sup>                     | 9.2.3                                   |                                                                         |                                                    |
| - initial                                                   |                                         | ≤1,0 mΩ                                                                 |                                                    |
| - after conditioning                                        |                                         | ≤1,5 mΩ                                                                 |                                                    |
| Outer conductor continuity <sup>2)</sup>                    | 9.2.3                                   |                                                                         |                                                    |
| - initial                                                   |                                         | ≤0,25 mΩ                                                                |                                                    |
| - after conditioning                                        |                                         | ≤1,0 mΩ                                                                 |                                                    |
| Insulation resistance                                       | 9.2.5                                   |                                                                         |                                                    |
| - initial                                                   |                                         | ≥5 000 MΩ                                                               |                                                    |
| - after conditioning                                        |                                         | ≥200 MΩ                                                                 |                                                    |
| Proof voltage at sea-level <sup>3)4)</sup>                  | 9.2.6                                   |                                                                         |                                                    |
| - uncabled styles                                           |                                         | 2 500 V                                                                 |                                                    |
| - semi-rigid 0,141 inch diameter                            |                                         | 1 000 V                                                                 |                                                    |
| - semi-rigid 0,086 inch diameter                            |                                         | 750 V                                                                   |                                                    |
| Proof voltage at 4,4 kPa <sup>3)4)</sup>                    | 9.2.6                                   |                                                                         |                                                    |
| - uncabled styles                                           |                                         | 450 V                                                                   | 4,4 kPa approximately<br>equivalent to 20 km       |
| - semi-rigid 0,141 inch diameter                            |                                         | 450 V                                                                   |                                                    |
| - semi-rigid 0,086 inch diameter                            |                                         | 180 V                                                                   |                                                    |
| Environmental test voltage at sea level <sup>3)4)</sup>     | 9.2.6                                   |                                                                         |                                                    |
| - uncabled styles                                           |                                         | 1 000 V                                                                 |                                                    |
| - semi-rigid 0,141 inch diameter                            |                                         | 1 000 V                                                                 |                                                    |
| - semi-rigid 0,086 inch diameter                            |                                         | 400 V                                                                   |                                                    |
| Environmental test voltage at 4,4 kPa <sup>3)4)</sup>       | 9.2.6                                   |                                                                         |                                                    |
| - uncabled styles                                           |                                         | 200 V                                                                   | 4,4 kPa approximately<br>equivalent to 20 km       |
| - semi-rigid 0,141 inch diameter                            |                                         | 200 V                                                                   |                                                    |
| - semi-rigid 0,086 inch diameter                            |                                         | 90 V                                                                    |                                                    |
| Screening effectiveness (straight style only) <sup>7)</sup> | 9.2.8                                   | ≥90 dB at 1 GHz                                                         |                                                    |
| Passive intermodulation                                     |                                         | See DS                                                                  |                                                    |

| Rating and characteristics                 | Test method<br>IEC 61169-1<br>Subclause | Values                                         | Remarks deviations<br>from standard<br>test method |
|--------------------------------------------|-----------------------------------------|------------------------------------------------|----------------------------------------------------|
| Discharge test (corona effect)             | 9.2.9                                   | See DS                                         | Extinction voltage                                 |
| Mechanical                                 |                                         |                                                |                                                    |
| Gauge retention force (resilient contacts) |                                         |                                                |                                                    |
| - centre                                   | 9.3.4                                   | $\geq 0,56$ N                                  |                                                    |
| Centre contact captivation                 | 9.3.5                                   |                                                | Maximum displacement 0,25 mm in each direction     |
| - axial force                              |                                         | 28 N                                           |                                                    |
| Engagement and separation                  | 9.3.6                                   | $\leq 30$ N                                    | Can be carried out by hand                         |
| Technical tests on cable fixing            |                                         |                                                |                                                    |
| - cable rotation (nutation)                | 9.3.7.2                                 | See DS                                         |                                                    |
| - cable pulling                            | 9.3.8                                   | See DS                                         |                                                    |
| - cable bending                            | 9.3.9                                   | See DS                                         |                                                    |
| - cable torsion                            | 9.3.10                                  | See DS                                         |                                                    |
| Tensile strength of coupling mechanism     | 9.3.11                                  | $\geq 450$ N                                   |                                                    |
| Bending moment                             | 9.3.12                                  | na <sup>6)</sup>                               |                                                    |
| Vibration                                  | 9.3.3                                   | 100 m/s <sup>2</sup><br>10 Hz ~ 2 000 Hz       | 10 g <sub>n</sub>                                  |
| Shock                                      | 9.3.14                                  | 500 m/s <sup>2</sup><br>1/2 sine wave<br>11 ms | 50 g <sub>n</sub>                                  |
| Environmental                              |                                         |                                                |                                                    |
| Climatic category                          | 9.4.2                                   | A 55/125/21<br>B 40/085/21                     |                                                    |
| Sealing non-hermetic                       | 9.4.5.1                                 | $\leq 100$ KPa · cm <sup>3</sup> /h            | 100 kPa ~ 110 kPa differential                     |
| Hermetic                                   | 9.4.5.2                                 | $\leq 10^{-3}$ Pa · cm <sup>3</sup> /s         | 100 kPa ~ 110 kPa differential                     |
| Salt mist                                  | 9.4.6                                   | 48 h spray                                     |                                                    |
| Endurance                                  |                                         |                                                |                                                    |
| Mechanical endurance                       | 9.5                                     | 200 operations                                 |                                                    |
| High temperature endurance <sup>5)</sup>   | 9.6                                     | A: 200 h at 125 °C<br>B: 250 h at 85 °C        |                                                    |

1) These values apply to basic connector. In practice, these may be influenced by the cable used and reference should always be made to the actual values given in the detail specification.

2) Values for a single pair of connectors.

3) Voltages are r.m.s values of a.c. at 40 Hz to 65 Hz, unless otherwise specified.

4) Some cables usable with these connectors have ratings lower than the values given here.

5) For certain connectors, the upper temperature limit is restricted by the cable characteristics. Reference should be made to the relevant cable specification. When semi-rigid and semi-flexible cables are used, the upper temperature is limited to 115 °C maximum.

6) na -not applicable.

7) When interfaces are fully mated.

#### 4.3.1 Acceptance tests

|                                      | Test method<br>IEC 61169-1<br>Subclause | Assessment level M (higher) |     |       |        | Assessment level H (lower) |     |       |        |
|--------------------------------------|-----------------------------------------|-----------------------------|-----|-------|--------|----------------------------|-----|-------|--------|
|                                      |                                         | Test required               | IL  | AQL % | Period | Test required              | IL  | AQL % | Period |
| Group A1                             |                                         |                             |     |       | Lot    |                            |     |       | Lot    |
| Visual examination                   | 9.1.2                                   | a                           | II  | 1,0   |        | a                          | S-3 | 1,5   |        |
| Group B1                             |                                         |                             |     |       |        |                            |     |       |        |
| Outline dimension                    | 9.1.3.1                                 | a                           | S-4 | 0,40  |        | a                          | S-3 | 4,0   |        |
| Mechanical compatibility             | 9.1.3.3                                 | a                           | II  | 1,0   |        | a                          | S-3 | 1,5   |        |
| Engagement and separation            | 9.3.6                                   | a                           | S-4 | 0,40  |        | a                          | S-3 | 1,5   |        |
| Gauge retention (resilient contacts) | 9.3.4                                   | ia                          | II  | 1,0   |        | ia                         | S-3 | 1,5   |        |
| Sealing                              |                                         |                             |     |       |        |                            |     |       |        |
| - non-hermetic                       | 9.4.5.1                                 | ia                          | II  | 0,65  |        | ia                         | S-3 | 1,0   |        |
| - hermetic                           | 9.4.5.2                                 | ia                          | II  | 0,015 |        | ia                         | II  | 0,025 |        |
| Voltage proof                        | 9.2.6                                   | a                           | S-4 | 0,40  | By     | a                          | II  | 4,0   | By     |
| Solderability (d)                    | 9.3.2.1.1                               | ia                          | S-4 | 0,40  |        | ia                         | S-3 | 4,0   |        |
| Insulation resistance                | 9.2.5                                   | a                           | S-4 | 0,40  |        | a                          | S-3 | 4,0   |        |

For symbols, abbreviations and procedures, see the end of Table 8.

### 4.3.2 Periodic tests

There are no group C tests for levels H and M.

**Table 8 – Periodic tests**

|                                                                             | Test method<br>IEC 61169-1<br>Subclause | Assessment level M (higher) |                        |                                                     |            | Assessment level H (lower) |                        |                                                     |            |
|-----------------------------------------------------------------------------|-----------------------------------------|-----------------------------|------------------------|-----------------------------------------------------|------------|----------------------------|------------------------|-----------------------------------------------------|------------|
|                                                                             |                                         | Test<br>required            | Number of<br>specimens | Permitted<br>failures<br>per<br>group <sup>1)</sup> | Period     | Test<br>required           | Number of<br>specimens | Permitted<br>failures<br>per<br>group <sup>1)</sup> | Period     |
| Group D1 (d)<br>Solderability<br>- connector<br>assemblies                  | 9.3.2.1.1                               | ia                          | 6                      | 1                                                   | 3<br>years | ia                         | 3                      | 1                                                   | 3<br>years |
| Resistance to<br>soldering heat                                             | 9.3.2.1.2                               | ia                          |                        |                                                     |            | ia                         |                        |                                                     |            |
| Mechanical<br>tests on cable<br>fixing<br>- cable<br>rotation<br>(nutation) | 9.3.7.2                                 | ia                          |                        |                                                     |            | ia                         |                        |                                                     |            |
| - cable pulling                                                             | 9.3.8                                   | ia                          |                        |                                                     |            | ia                         |                        |                                                     |            |
| - cable<br>bending                                                          | 9.3.9                                   | ia                          |                        |                                                     |            | ia                         |                        |                                                     |            |
| - cable torsion                                                             | 9.3.10                                  | ia                          |                        |                                                     |            | ia                         |                        |                                                     |            |
| Bending<br>moment                                                           | 9.3.12                                  | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Strength of<br>coupling<br>mechanism                                        | 9.3.11                                  | ia                          |                        |                                                     |            | ia                         |                        |                                                     |            |
| Group D2 (d)<br>Contact<br>resistance                                       | 9.2.3                                   | a                           | 6                      | 1                                                   | 3<br>years | a                          | 3                      | 1                                                   | 3<br>years |
| Outer<br>conductor<br>and screen<br>continuity                              | 9.2.3                                   |                             |                        |                                                     |            |                            |                        |                                                     |            |
| Centre<br>conductor<br>continuity                                           | 9.2.3                                   |                             |                        |                                                     |            |                            |                        |                                                     |            |
| Bump                                                                        | 9.3.13                                  | na                          |                        |                                                     |            | na                         |                        |                                                     |            |
| Vibration                                                                   | 9.3.3                                   | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Shock                                                                       | 9.3.14                                  | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Damp heat,<br>steady state                                                  | 9.4.3                                   | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Salt mist                                                                   | 9.4.6                                   | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Group D3<br>Dimensions<br>piece part<br>and materials                       | 9.1.3.2                                 | a                           | 1 <sup>2)</sup>        | 1                                                   | 3<br>years | a                          | 1 <sup>2)</sup>        | 1                                                   | 3<br>years |

|                                                                          | Test method<br>IEC 61169-1<br>Subclause | Assessment level M (higher) |                        |                                                     |            | Assessment level H (lower) |                        |                                                     |            |
|--------------------------------------------------------------------------|-----------------------------------------|-----------------------------|------------------------|-----------------------------------------------------|------------|----------------------------|------------------------|-----------------------------------------------------|------------|
|                                                                          |                                         | Test<br>required            | Number of<br>specimens | Permitted<br>failures<br>per<br>group <sup>1)</sup> | Period     | Test<br>required           | Number of<br>specimens | Permitted<br>failures<br>per<br>group <sup>1)</sup> | Period     |
| Group D4 (d)<br>Mechanical<br>endurance                                  | 9.5                                     | a                           | 6                      | 1                                                   | 3<br>years | a                          | 3                      | 1                                                   | 3<br>years |
| High<br>temperature<br>endurance                                         | 9.6                                     | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Sulphur<br>dioxide                                                       | 9.4.8                                   | na                          |                        |                                                     |            | na                         |                        |                                                     |            |
| Group D5 (d)<br>Reflection<br>factor                                     | 9.2.1                                   | a                           | 6                      | 1                                                   | 3<br>years | a                          | 3                      | 1                                                   | 3<br>years |
| Screening<br>effectiveness                                               | 9.2.8                                   | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Water<br>immersion                                                       | 9.2.7                                   | ia                          |                        |                                                     |            | ia                         |                        |                                                     |            |
| Group D6 (d)<br>Contact<br>captivation                                   | 9.3.5                                   | ia                          | 6                      | 1                                                   | 3<br>years | ia                         | 3                      | 1                                                   | 3<br>years |
| Discharge<br>test (corona<br>effect)                                     | 9.2.9                                   | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Rapid change<br>of temperature                                           | 9.4.4                                   | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Climatic<br>sequence                                                     | 9.4.2                                   | a                           |                        |                                                     |            | a                          |                        |                                                     |            |
| Group D7 (d)<br>Resistance to<br>solvents and<br>contaminating<br>fluids | 9.7                                     | na                          | 1 <sup>3)</sup>        | 1                                                   | 3<br>years | na                         | 1 <sup>3)</sup>        | 1                                                   | 3<br>years |

1) For qualification approval, a total of 2 failures only is permitted for level H and 1 failure only for level M from groups D1 to D7.

2) One set of piece parts for each style and variant unless using common piece parts.

3) Group D7 - number of pairs for each solvent.

#### ABBREVIATIONS:

a - applicable.

na - not applicable.

ia - test required (if technically applicable).

(d) - destructive test -specimens shall not be returned to stock.

IL- inspection level.

AQL- acceptable quality level.

## 4.4 Procedures

### 4.4.1 Quality conformance inspection

This shall consist of test group A1 and B1 on a lot-by-lot basis and test groups D1 to D7 on a periodic basis.

### 4.4.2 Qualification approval and its maintenance

This still consists of three consecutive lots passing test groups A1 and B1 followed by selection of specimens from the lots as appropriate. These specimens shall successfully pass the specified periodic D tests.

## 5 Instructions for preparation of detail specifications

### 5.1 General

Detail specifications (DS) writers shall use the appropriate BDS pro-forma. The following pages comprise the pro-forma BDS dedicated for use with 50  $\Omega$  type CQN connectors. It already contains information relating to

- a) the basic specification number applicable to all the detail specifications covering connector styles of the type covered by the sectional specification;
- b) the connector series designation.

The specification writer should enter the details relating to the connector style/variant(s) to be covered as indicated. The numbers in brackets on the BDS pro-forma correspond to the following indications which shall be given.

### 5.2 Identification of the component

- (5) Enter the following details:

Style: The style designation of the connector including type of fixing and sealing, if applicable.

Attachment: By deletion of the inapplicable options of cable/wire: given for centre and outer conductors.

Special features and markings: As applicable.

- (6) Enter details of assessment level and the climatic category.

- (7) A reproduction of the outline drawing and details of the panel piercing, if applicable. It shall provide the maximum envelope dimensions, also the position of the reference plane and, in the case of a fixed connector, the position of the mounting plane(s) relative to the front face of the connector.

Any maximum panel thickness limitations for fixed connectors shall be stated.

- (8) Particulars of all variants covered by the DS. As appropriate, the information shall include:
  - cable types (or sizes) applicable to each variant;
  - alternative plated or protective finishes;
  - details of alternative mounting flanges having either tapped or plain mounting holes;
  - details of alternative solder spills or solder buckets including, when applicable, those for use with microwave integrated circuit (MIC) components.

### 5.3 Performance

- (9) Performance data listing the most important characteristics of the connector taking into account the recommended values in 4.2 of this specification. Deviations from the minimum requirements shall be clearly indicated. Non-applicable parameters shall be marked 'na'.

#### 5.4 Marking, ordering information and related matters

- (10) Insert marking and ordering information as appropriate, together with details of related documents and any invoked structural similarity.

#### 5.5 Selection of tests, test conditions and severities

- (11) 'na' shall be used to indicate non-applicable tests. All tests marked 'a' by the detail specification writer shall be mandatory.

When using the normal procedure with a dedicated BDS, the letter 'a' – for applicable – shall be entered in the 'test required' column against each of the tests indicated as being mandatory in the test schedule as in 4.3 of this specification. Any additional tests required at the discretion of the specification writer shall also be indicated by an 'a'.

The specification writer shall also indicate, when necessary, details of deviations from the standard test methods and test conditions, including any relevant deviations given in the test schedule of the sectional specification.

The qualification approval and conformance inspection shall be such that the national supervising inspectorate (NSI) shall be satisfied that they are appropriate and in line with those for other connectors within the system providing a reasonably comparable service.

## 5.6 Blank detail specification pro-forma for type CQN connector

The following pages contain the complete BDS pro-forma.

|                                                                                                                                                                |                               |                                                                                                       |                 |                                                                                     |       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------|-------|
| (1)                                                                                                                                                            |                               | Page 1 of 10                                                                                          |                 |  |       |
| ELECTRONIC COMPONENT OF ASSESSED QUALITY IN ACCORDANCE WITH<br>GENERIC SPECIFICATION IEC 61169-1<br>SECTIONAL SPECIFICATION IEC 61169-42<br>NATIONAL REFERENCE |                               | (4) ISSUE<br>.....<br>.....                                                                           |                 |                                                                                     |       |
| (5) Detail specification for<br>Radio frequency coaxial connector of assessed quality                                                                          |                               |                                                                                                       | type <b>CQN</b> |                                                                                     |       |
| Style:.....                                                                                                                                                    |                               | Special features and markings                                                                         |                 |                                                                                     |       |
| Method of cable/wire+ attachment                                                                                                                               |                               | centre conductor – solder/crimp+<br>outer conductor – solder/clamp/crimp +<br>+ delete as appropriate |                 |                                                                                     |       |
| (6) Assessment level.....                                                                                                                                      | Characteristic impedance 50 Ω | Climatic category...../...../...../                                                                   |                 |                                                                                     |       |
| (7) Outline and maximum dimensions                                                                                                                             |                               | Panel piercing and mounting details                                                                   |                 |                                                                                     |       |
| (8) Variants                                                                                                                                                   |                               |                                                                                                       |                 |                                                                                     |       |
| Variant No.                                                                                                                                                    | Description of variant        | 61196 IEC                                                                                             |                 |                                                                                     |       |
| 01.....                                                                                                                                                        | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| .....                                                                                                                                                          | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| .....                                                                                                                                                          | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| .....                                                                                                                                                          | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| .....                                                                                                                                                          | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| .....                                                                                                                                                          | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| .....                                                                                                                                                          | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| .....                                                                                                                                                          | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| .....                                                                                                                                                          | .....                         | .....                                                                                                 | .....           | .....                                                                               | ..... |
| Information about manufacturers who have components qualified to this detail specification is available through IECQ on-line certificate system.               |                               |                                                                                                       |                 |                                                                                     |       |