

TECHNICAL SPECIFICATION



**Marine energy – Wave, tidal and other water current converters –
Part 1: Vocabulary**

IECNORM.COM : Click to view the full PDF of IEC TS 62600-1:2020



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2020 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IECNORM.COM : Click to view the full text of IEC 6182600-1:2020

TECHNICAL SPECIFICATION



**Marine energy – Wave, tidal and other water current converters –
Part 1: Vocabulary**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 27.140

ISBN 978-2-8322-8112-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD	3
INTRODUCTION.....	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
Bibliography.....	17
 Figure 1 – Six degrees of freedom – Floating device	 8
Figure 2 – Six degrees of freedom – Submerged device	8
Figure 3 – Equivalent diameter calculations for various projected capture areas	10
Figure 4 – Principal flow direction	13

IECNORM.COM : Click to view the full PDF of IEC TS 62600-1:2020

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARINE ENERGY – WAVE, TIDAL AND OTHER
WATER CURRENT CONVERTERS –****Part 1: Vocabulary****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a Technical Specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical Specification are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC TS 62600-1 which is a Technical Specification, has been prepared by IEC technical committee 114: Marine energy – Wave, tidal and other water current converters.

This 2nd edition cancels and replaces the 1st edition published in 2011, and its Amendment 1, published in 2019. This edition constitutes a technical revision.

This edition includes the following significant technical changes from the previous edition:

- a) Approximately 45 % of the original terms which were either not in use, used only in a glossary sense, or which are commonly understood and found in other references were removed.
- b) Thirteen (13) terms considered more general than tidal were moved up from IEC TS 62600-200 and added.
- c) Eight (8) terms that were added in Amendment 1 to IEC TS 62600-1 were incorporated alphabetically.
- d) Six (6) additional new terms were added.

The text of this Technical Specification is based on the following documents:

Draft TS	Report on voting
114/330/DTS	114/342/RVDTS

Full information on the voting for the approval of this Technical Specification can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62600 series, published under the general title *Marine energy – Wave, tidal and other water current converters*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This Technical Specification has been developed as a tool for the international marine energy community, to assist in creating clarity and understanding. The wave, tidal and water current energy industry has recently experienced a period of rapid growth and sector development. With this expansion, it became apparent that a document defining the terms used within the sector was required. The aim of this document is to present clear and consistent language that will aid the development of programs, projects, and future standards.

This document lists the terms that the marine energy industry uses. It is an evolving document that will change as new terms and symbols are added. The terminologies herein have been harmonized with IEC 60050 and other IEC documents as far as possible. The document does not constitute a full glossary of terms used in the marine energy community.

IECNORM.COM : Click to view the full PDF of IEC TS 62600-1:2020

MARINE ENERGY – WAVE, TIDAL AND OTHER WATER CURRENT CONVERTERS –

Part 1: Vocabulary

1 Scope

This part of IEC 62600 defines the terms relevant to marine energy. For the purposes of this document, sources of ocean and marine renewable energy are taken to include primarily devices that convert wave, tidal and other water current energy into electrical energy, although other conversion methods, systems and products are included.

Terms relating to conventional dam and tidal barrage, offshore wind, marine biomass, and salinity gradient energy conversion are not included in the scope of this document.

This document is intended to provide uniform terminology to facilitate communication between organizations and individuals in the marine energy industry and those who interact with them.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

annual energy production

estimate of the total energy production of a device during a one-year period obtained by applying the device's power performance characteristics to a relevant energy resource characterization, assuming 100 % availability

Note 1 to entry: Actual annual energy production is unlikely to exceed this estimate.

[SOURCE: IEC 60050-415:1999, 415-05-09, modified – The definition has been revised to be generic by replacing "wind turbine generator system" by "device", and by replacing "the power curve to different reference wind speed frequency distributions at hub height" by "the device's power performance characteristics to a relevant energy resource characterization". For clarity, "obtained" has been added before "by applying". Note 1 to entry has been added.]

3.2

array

<in marine energy> one or more groups of marine energy converters

Note 1 to entry: Array spacing is dictated by hydrodynamic considerations and can be very closely packed so as to constitute a single platform or an arrangement of identical devices.

3.3**availability**, <of an item>

See IEV 192-01-23

3.4**capture width****capture length**<of a wave energy converter> power captured by the **wave energy converter** divided by the **wave power** of the incident wave field**3.5****current energy converter****CEC**

device that converts energy from water currents to electricity or other useful forms of energy

3.6**cut-in water speed****cut-in water velocity**

<of a current energy converter> water speed above which there is power production

Note 1 to entry: The term "cut-in water velocity" is sometimes used in industry, although the concept is in fact a speed.

3.7**cut-out water speed****cut-out water velocity**

<of a current energy converter> water speed above which there is no power production

Note 1 to entry: The term "cut-in water velocity" is sometimes used in industry, although the concept is in fact a speed.

3.8**degrees of freedom, pl**

independent displacements and/or rotations that specify the orientation of a body or system

Note 1 to entry: A marine body can experience three linear and three rotational motions as depicted in Figure 1 and A

B Yaw

E Roll

H Incident energy at zero-degree heading

C Pitch

F Sway

I Seabed

Heave


D Surge

G

Centre of gravity

Figure 2.


Note 2 to entry: The principal axis is parallel to the mean water surface and aligned with the longest, plan form, dimension of the device. The principal axis for a symmetric device will be parallel to the mean water surface and aligned with a chosen direction of interest. The direction of incident energy will be through the centre of gravity and may be at an angle to the principal axis.



Key

- | | | |
|---------|---------|--|
| A Heave | D Surge | G Centre of gravity |
| B Yaw | E Roll | H Incident energy at zero-degree heading |
| C Pitch | F Sway | |

Figure 1 – Six degrees of freedom – Floating device



Key

- | | | |
|---------|---------|--|
| A Heave | D Surge | G Centre of gravity |
| B Yaw | E Roll | H Incident energy at zero-degree heading |
| C Pitch | F Sway | I Seabed |

Figure 2 – Six degrees of freedom – Submerged device

3.8.1**heave**

motion in a direction perpendicular to the mean water surface

3.8.2**pitch**

rotation about the **sway** axis

3.8.3**roll**

rotation about the **surge** axis

3.8.4**surge**

motion parallel to the principal axis

3.8.5**sway**

motion perpendicular to the principal axis and parallel to the mean water surface

3.8.6**yaw**

rotation about the **heave** axis

3.9**directional spreading function**

<of a water wave> normalized distribution of **wave energy**, D , for a given frequency, f , over the angle of incidence, θ

Note 1 to entry: Since $\int_0^{2\pi} D(\theta, f) d\theta = 1$ the **directional spreading function** can be considered to be a probability density function over direction.

3.10**directional wave spectrum**

<of a water wave> distribution of the wave elevation variance density as a function of incident wave frequency and direction

Note 1 to entry: The **directional wave spectrum** is calculated as the product of the **wave spectrum** multiplied with the directional spreading function.

3.11**directionally resolved power**

<of a water wave> sum of all **wave power** components propagating in a specified direction in a given sea state

3.12**energy extraction plane**

<of a current energy converter> plane that is perpendicular to the **principal axis of energy capture** where device rotation or energy conversion nominally occurs

Note 1 to entry: Refer to Figure 4 for a simplified illustration of the energy extraction plane.

Note 2 to entry: For a **tidal energy converter** device with multiple extraction planes, an appropriate upstream energy extraction plane on both ebb and flood tides should be identified.

3.13 energy period

T_e

<of a water wave> characteristic wave period associated with energy propagation expressed as the **group velocity** weighted mean period of the **wave spectrum**

Note 1 to entry: It is numerically equivalent to the period of a monochromatic wave in deep water with wave elevation variance and energy flux equal to a polychromatic sea state.

Note 2 to entry: In accordance with International Association for Hydraulic Research the spectral estimate of the energy period is preferred.

$T_e = \frac{m_{-1}}{m_0}$, where m_{-1} and m_0 are the minus-one and zero spectral moments.


3.14 equivalent diameter

D_E

diameter of a circle with area equal to the device **projected capture area**

Note 1 to entry: The equivalent diameter is generally calculated as:

$D_E = \sqrt{\frac{4A}{\pi}}$, where A is the projected capture area as illustrated in Figure 3.



IEC

Key

A projected capture area h height

D_E equivalent diameter w width

R radius

Figure 3 – Equivalent diameter calculations for various projected capture areas

3.15 free-stream condition

<of a current energy converter> boundary condition description for a **current energy converter** such that its performance is equivalent to that of a **current energy converter** operating in a channel with infinite cross-section

3.16 functional survivability

probability that a device will continue to operate without a forced outage over the stated operational life

3.17 group velocity

<of a water wave> propagation velocity of water wave groups and the wave energy

Note 1 to entry: The **group velocity** of a water wave is the velocity at which the energy associated with the wave disturbance travels in the direction of wave propagation. In deep water using linear wave theory the **group velocity** is one half the **wave phase velocity**. In shallow water the **group velocity** is equal to the **wave phase velocity**.

3.18

hub height

<of a current energy converter> distance from the centroid of a **current energy converter's projected capture area** to the sea floor

3.19

instantaneous availability

See IEV 192-08-01

3.20

low cut-out water speed

low cut-out water velocity

<of a current energy converter> water speed during the decelerating part of the current cycle below which a **tidal energy converter** does not produce power

Note 1 to entry: The term "cut-out water velocity" is sometimes used in industry, although the concept is in fact a speed.

3.21

maintainability, <of an item>

See IEV 192-01-27

3.22

marine current

persistent flow of seawater produced by natural physical processes, including the gravitational pull of celestial bodies

3.23

marine energy converter

MEC

device that converts energy from oceans or other natural bodies of water to electricity or other useful forms of energy

3.24

maximum individual wave height

$H_{\max}$

<of a water wave> statistical measure of the largest individual **wave heights** which can be observed or expected in a given sea state for a stated probability of exceedance

Note 1 to entry: Maximum individual wave height is normally calculated from a Rayleigh distribution for wave heights in deep water for an exceedance probability of one per thousand, for which $H_{\max} = 1,86$ times the significant wave height.

3.25

mean annual wave power

<of a water wave> yearly average of the directionally unresolved **wave power** calculated as an arithmetic mean over all sea states occurring at a given location

Note 1 to entry: Typically **mean annual wave power** is expressed in kilowatts per metre.

3.26

mean zero crossing period

<of a water wave> average time interval between downcrossings of the mean water level during a given sea state

Note 1 to entry: The spectral estimate of the mean zero crossing period, T_{02} , is calculated as

$T_{02} = \sqrt{\frac{m_0}{m_2}}$, where m_0 and m_2 are the zero and second spectral moments.

3.27

metocean

met-ocean

meteorological and oceanographic environment typically described using wind, wave, tidal and other characteristics

3.28

ocean current

large scale and persistent flow of seawater other than **tidal current**

3.29

ocean current energy converter

OCEC

device that converts energy from an **ocean current** to electricity or other useful forms of energy

3.30

ocean thermal energy converter

OTEC

device that converts thermal energy from the ocean to electricity or other useful forms of energy

3.31

power curve

power surface

<of a current energy converter> representation of the power capture as a function of current parameters

3.32

power matrix

tabular description of the power capture as a function of relevant meteorological and oceanographic parameters

3.33

power take-off

PTO

mechanism that converts the motion of the **prime mover** into a useful form of energy such as electricity

3.34

power weighted speed

<of a current energy converter> magnitude of current velocity derived with a weighted function corresponding to the kinetic energy flux through the **projected capture area**

3.35

power weighted velocity

<of a current energy converter> current velocity derived with a weighted function corresponding to the kinetic energy flux through the **projected capture area**

3.36

prime mover

marine energy converter component that interfaces with a resource from which energy is converted

3.37**principal axis of energy capture**

<of a current energy converter> axis parallel to the design orientation or heading of a **current energy converter** passing through the centroid of the **projected capture area**

Note 1 to entry: Figure 4 illustrates a simplified example of the principal axis of energy capture.

3.38**principal flow direction**

<of a current energy converter> primary orientation or heading of the water current

Note 1 to entry: Figure 4 illustrates a simplified example of the principal flow directions.

Note 2 to entry: For tidal energy converters, it is common to introduce two primary flow directions, one defining the primary flood flow, and one defining the primary ebb flow.




Figure 4 – Principal flow direction

3.39**projected capture area**

<of a current energy converter> frontal area perpendicular to the **principal flow direction** of the **current energy converter** components hydrodynamically utilized in energy conversion

3.40**rated power****rated capacity**

maximum continuous electric output power which a device's generator system is designed to achieve under normal operating conditions

Note 1 to entry: The term "rated power" can refer to the output of a single device or an **array**.

[SOURCE: IEC 60050-415:1999, 415-04-03, modified – The definition has been revised to be generic by replacing "wind turbine" by "devices". Note 1 to entry has been added.]

3.41**rated water speed****rated water velocity**

<of a current energy converter> lowest mean flow speed at which the **rated power** of a **current energy converter** is delivered

Note 1 to entry: The term "rated water velocity" is sometimes used in industry, although the concept is in fact a speed.

3.42

reliability, <of an item>

See IEC 192-01-24

3.43

resource assessment

<in marine energy> collection and processing of meteorological and oceanographic data required for determining the performance of a **marine energy converter** or **array**

Note 1 to entry: Resource assessments are conducted in three distinct stages comprising theoretical resource assessment, technical resource assessment, and practical resource assessment.

3.43.1

practical resource

proportion of the **technical resource** that is available after consideration of external constraints

Note 1 to entry: External constraints can include grid accessibility, competing use, environmental sensitivity, etc.

3.43.2

technical resource

proportion of the **theoretical resource** that can be captured using existing technology options without consideration of external constraints

3.43.3

theoretical resource

energy available in the resource

3.44

resource characterization

parameterization of meteorological and oceanographic data to enable determination of the performance of a **marine energy converter** or **array**

3.45

river current

flow of water in an open channel other than **tidal current**

3.46

river energy

energy present in a **river current**

3.47

river energy converter

REC

device that converts energy from a **river current** to electricity or other useful forms of energy

3.48

survivability

<of an item> ability to continue to operate without a failure over the stated operational life

3.49

survival mode

<of a device> operational configuration that improves **survivability** during extreme conditions

3.50**test availability**

ratio of the total number of hours during a test period where all test conditions are met, to the total number of hours of the **test period**

3.51**test period**

period between the first data collection and the last data collection, for the purpose of power performance assessment

3.52**tidal current**

tidal stream

flow of water induced by the gravitational forces of celestial bodies

3.53**tidal energy**

energy present in a **tidal current**

3.54**tidal energy converter****TEC**

device that converts energy from a **tidal current** to electricity or other useful forms of energy

3.55**wave climate**

long-term statistical characterization of the wave properties at a location

Note 1 to entry: Wave climate is a subset of the metocean.

3.56**wave energy**

energy present in surface waves

3.57**wave energy converter****WEC**

device that converts energy from surface waves to electricity or other useful forms of energy

3.58**wave height**

<of a water wave> vertical distance between a consecutive wave trough and wave crest

3.59**wave phase velocity**

<of a water wave> velocity at which the phase of the wave is propagating

Note 1 to entry: The **wave phase velocity** is calculated in terms of the ratio between wave length and period.

Note 2 to entry: As water waves are dispersive, the wave phase velocity varies with period and is not necessarily the same as the **group velocity**.

3.60**wave power****wave energy flux per unit width**

wave energy transport rate per unit width from the sea floor to the surface

Note 1 to entry: Unless otherwise specified, wave power should be understood as omnidirectional, or directionally unresolved.