
**Information technology —
Telecommunications and information
exchange between systems — Near Field
Communication Interface and Protocol -2
(NFCIP-2)**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Interface et protocole -2 en
communication de champ proche (NFCIP-2)*

IECNORM.COM : Click to view the full PDF of ISO/IEC 21481:2005

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

IECNORM.COM : Click to view the full PDF of ISO/IEC 21481:2005

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

| | |
|--|----|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Conformance | 1 |
| 3 Normative references | 1 |
| 4 Terms and definitions | 2 |
| 5 Conventions and notations | 2 |
| 5.1 Names | 2 |
| 6 External RF field threshold value | 2 |
| 7 RF Field detection | 2 |
| 8 Mode selection | 3 |
| 9 RF detection and Initial RF generation | 5 |

IECNORM.COM : Click to view the full PDF of ISO/IEC 21481:2005

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 21481 was prepared by Ecma International (as ECMA-352) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

IECNORM.COM : Click to view the full PDF of ISO/IEC 21481:2005

Introduction

In 2002, Ecma International formed Task Group 19 of Technical Committee 32 to specify Near Field Communication (NFC) signal interfaces and protocols. The NFC devices are wireless closely coupled devices communicating at 13,56 MHz.

Although ISO/IEC 18092 (NFCIP-1), ISO/IEC 14443 and ISO/IEC 15693 standards all specify 13,56 MHz as their working frequency, they specify distinct communication modes. These are defined as NFC, PCD, and VCD communication modes respectively.

This NFCIP-2 Standard specifies the mechanism to detect and select one communication mode out of those three possible communication modes. Furthermore, NFCIP-2 requires that subsequent behaviour be as specified in the standard specifying the selected communication mode.

IECNORM.COM : Click to view the full PDF of ISO/IEC 21481:2005

Information technology — Telecommunications and information exchange between systems — Near Field Communication Interface and Protocol -2 (NFCIP-2)

1 Scope

ISO/IEC 18092, ISO/IEC 14443 and ISO/IEC 15693 standards specify the RF signal interface, initialisation, anti-collision and protocols for wireless interconnection of closely coupled devices and access to contactless integrated circuit cards operating at 13,56 MHz.

This International Standard specifies the communication mode selection mechanism, designed to not disturb any ongoing communication at 13,56 MHz, for devices implementing ISO/IEC 18092 and the reader functionality for integrated circuit cards compliant to ISO/IEC 14443 or ISO/IEC 15693. This International Standard requires implementations to enter the selected communication mode as specified in the respective standard. The communication mode specifications, however, are outside the scope of this NFCIP-2 Standard.

2 Conformance

A conforming implementation complies with all the mandatory clauses in this International Standard.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 18092:2004, *Information technology — Telecommunications and information exchange between systems — Near Field Communication — Interface and Protocol (NFCIP-1)*

ISO/IEC 14443-2:2001, *Identification cards — Contactless integrated circuit(s) cards — Proximity cards — Part 2: Radio frequency power and signal interface*

ISO/IEC 14443-3:2001, *Identification cards — Contactless integrated circuit(s) cards — Proximity cards — Part 3: Initialization and anticollision*

ISO/IEC 14443-4:2001, *Identification cards — Contactless integrated circuit(s) cards — Proximity cards — Part 4: Transmission protocol*

ISO/IEC 15693-1, *Identification cards — Contactless integrated circuit(s) cards — Vicinity cards — Part 1: Physical characteristics*

ISO/IEC 15693-2, *Identification cards — Contactless integrated circuit(s) cards — Vicinity cards — Part 2: Air interface and initialization*

ISO/IEC 15693-3, *Identification cards — Contactless integrated circuit(s) cards — Vicinity cards — Part 3: Anticollision and transmission protocol*

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1
H_{Threshold}
the minimum value of an external RF field that a NFCIP-2 device shall detect to not disturb ongoing communication by ensuring that its own RF field is switched off.

4.2
NFC MODE
the communication as specified in ISO/IEC 18092.

4.3
OPERATING FREQUENCY (fc)
13,56 MHz +/- 7 kHz.

4.4
PCD
Proximity Coupling Device as specified in ISO/IEC 14443.

4.5
PCD MODE
the contactless communication between PCD and PICC as specified in ISO/IEC 14443.

4.6
VCD
Vicinity Coupling Device as specified in ISO/IEC 15693.

4.7
VCD MODE
the contactless communication between VCD and VICC as specified in ISO/IEC 15693.

5 Conventions and notations

5.1 Names

The names of basic elements, e.g. specific fields, are written with a capital initial letter.

6 External RF field threshold value

NFCIP-2 devices shall detect external RF fields at the OPERATING FREQUENCY with a value higher than $H_{\text{THRESHOLD}}$ while performing external RF field detection.

The value of $H_{\text{THRESHOLD}} = 0,1875 \text{ A/m}$.

7 RF Field detection

In order to not disturb any communication on the OPERATING FREQUENCY, an NFCIP-2 device shall not switch on its RF field when it detects an external RF field, as specified in Clause 6.

8 Mode selection

Mode selection specifies the procedure for NFCIP-2 devices to select and subsequently enter one the NFC MODE, or the PCD MODE and VCD MODE.

NFCIP-2 devices shall implement the following functions:

1. Initiator and target as specified in ISO/IEC 18092;
2. PCD as specified in ISO/IEC 14443; and
3. VCD as specified in ISO/IEC 15693.

NFCIP-2 devices shall execute the following sequence:

1. The NFCIP-2 device shall have its RF field switched off.
2. If the NFCIP-2 device detects an external RF field, as specified in Clause 6, it shall select the NFC MODE.
3. If the NFCIP-2 device does not detect an external RF field it shall select the NFC MODE, or the PCD MODE or the VCD MODE.
4. If the NFCIP-2 device has selected the NFC MODE, it shall enter the NFC MODE.
5. NFCIP-2 devices that have selected either the PCD MODE or VCD MODE, shall perform RF detection, Initial RF generation and subsequently enter the selected mode as specified in Clause 9.

Figure 1 illustrates the above procedure.

IECNORM.COM : Click to view the full PDF of ISO/IEC 21481:2005