



**International
Standard**

ISO/IEC 23078-3

**Information technology —
Specification of digital rights
management (DRM) technology for
digital publications —**

**Part 3:
Device key-based protection**

**First edition
2024-06**

IECNORM.COM : Click to view the full PDF of ISO/IEC 23078-3:2024



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Abbreviated terms	4
5 Overview	4
5.1 General	4
5.2 Protecting the publication	5
5.3 Licensing the publication	5
5.4 Reading the publication	6
5.4.1 General	6
5.4.2 Registering a device	6
5.4.3 Acquiring a device key-based license document	6
5.4.4 Decrypting a resource	6
5.5 Licensing workflows	7
5.5.1 General	7
5.5.2 Getting a protected publication	7
5.5.3 Transferring a protected publication	7
5.5.4 Register device certificate and update license document	8
6 License document	9
6.1 General	9
6.2 Content conformance	9
6.3 License information	9
6.3.1 General	9
6.3.2 Encryption (transmitting keys)	9
6.3.3 Links (pointing to external resources)	11
6.3.4 Rights (identifying rights and restrictions)	12
6.3.5 User (identifying the user)	12
6.3.6 Signature (signing the license)	12
6.4 User key	12
6.4.1 General	12
6.4.2 Calculating the user key	12
6.4.3 Hints	12
6.4.4 Requirements for the user key and user passphrase	12
6.5 Signature and public key infrastructure	13
6.5.1 General	13
6.5.2 Certificates	13
6.5.3 Canonical form of the license document	14
6.5.4 Generating the signature	14
6.5.5 Validating the certificate and signature	14
6.6 Device key	14
6.6.1 General	14
6.6.2 Generating the device key	14
6.6.3 Recommendations for the device private key protection	15
7 License status document	15
7.1 General	15
7.2 Content conformance	15
7.3 License status information	15
7.3.1 General	15
7.3.2 Status	15
7.3.3 Updated	15

7.3.4	Links.....	15
7.3.5	Potential rights.....	16
7.3.6	Events.....	16
7.4	Interactions.....	16
7.4.1	General.....	16
7.4.2	Handling errors.....	17
7.4.3	Checking the status of a license.....	17
7.4.4	Registering a device.....	17
7.4.5	Returning a publication.....	19
7.4.6	Renewing a license.....	19
8	Encryption profiles.....	19
8.1	General.....	19
8.2	Encryption profile requirements.....	19
8.3	Basic encryption profile.....	20
9	Integration in EPUB.....	20
10	Reading system behaviours.....	20
10.1	Detecting protected publications.....	20
10.2	License document processing.....	20
10.3	User key processing.....	20
10.4	Signature processing.....	20
10.5	Publication processing.....	20
10.6	Device key processing.....	20
	Annex A (informative) Examples.....	22
	Annex B (informative) Schema of license document.....	24
	Annex C (informative) An extension of the ISO/IEC 23078-3 specification for PDF.....	29
	Bibliography.....	31

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC1, *Information technology*, Subcommittee SC 34, *Document description and processing languages*.

This document cancels and replaces ISO/IEC TS 23078-3:2021, which has been technically revised.

The main changes are as follows:

- [Annex C](#) has been added.

A list of all parts in the ISO/IEC 23078 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

Ever since ebooks have grown in popularity, copyright protection has been an important issue for authors and publishers.

While the distribution of ebooks around the world is mostly based on the open EPUB standard, most ebook retailers are using proprietary technologies to enforce usage constraints on digital publications in order to impede oversharing of copyrighted content. The high level of interoperability and accessibility gained by the use of a standard publishing format is therefore cancelled by the use of proprietary and closed technologies: ebooks are only readable on specific devices or software applications (a retailer "lock-in" syndrome); ebooks cannot be accessed anymore if the ebook distributor which protected the publication goes out of business or if the DRM technology evolves drastically. As a result, users are deprived of any control over their ebooks.

Requirements related to security levels differ depending on which part of the digital publishing market is addressed. In many situations, publishers require a solution which technically enforces the digital rights they provide to their users; most publishers are happy to adopt a DRM solution which guarantees an easy transfer of publications between devices, a certain level of fair-use and provides permanent access to the publications they have acquired. However, in certain use cases, publishers require a stronger protection measure, which limits the capability for users to transfer publications from one device to another.

This document, as a variation of the ISO/IEC 23078-2, is a protection technology for digital publication¹⁾ with which transferring of the publication to multiple devices can be limited in accordance with providers' policies.

1) Although this document is primarily intended for the protection of EPUB publications, it can also protect digital publications in other formats, provided that the publication format supports the encryption of resources and the embedding of a license. This is especially the case for PDF documents contained in a Radium Packaging Format, as presented in [Annex C](#). This is important for owners of large PDF collections, who want to apply the same DRM to their EPUB and PDF collections.

Information technology — Specification of digital rights management (DRM) technology for digital publications —

Part 3: Device key-based protection

1 Scope

This document defines a technical solution for encrypting resources in digital publications (especially EPUB), effectively registering a device certificate to providers and securely delivering decryption keys to reading systems included in licenses tailored to specific devices. This technical solution uses the passphrase-based authentication method defined in ISO/IEC 23078-2 for reading systems to receive the license and access the encrypted resources of such digital publications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 23078-2:2024, *Information Technology — Specification of DRM technology for digital publications—Part 2: User key-based protection*

RFC 5280²⁾, *Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile*, Network Working Group

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

content key

symmetric key used to encrypt and decrypt *publication resources* (3.16)

[SOURCE: ISO/IEC 23078-2:2024, 3.2]

3.2

container

EPUB container

zip-based packaging and distribution format for *EPUB publications* (3.12)

[SOURCE: ISO/IEC 23078-2:2024, 3.4]

2) Available at <https://tools.ietf.org/html/rfc5280>.

3.3

device key

public key in a *device certificate* (3.4) that is used to encrypt the *content key* (3.1)

3.4

device certificate

certificate which is issued for a given *reading system* (3.13) and is signed by the *reading system developer* (3.14)

3.5

device private key

private key embedded securely in a *reading system* (3.13), paired with a *device key* (3.3) and used to decrypt the *content key* (3.1)

3.6

encryption profile

set of encryption algorithms used in a specific *protected publication* (3.9) and associated *license document* (3.8)

[SOURCE: ISO/IEC 23078-2:2024, 3.3]

3.7

license authority

entity which delivers *provider certificates* (3.11) to *content providers* (3.10) and *reading system developer certificates* (3.15) to *reading system* (3.13)

Note 1 to entry: License authority in this document has an additional role to deliver reading system developer certificates.

[SOURCE: ISO/IEC 23078-2:2024, 3.5, modified — Additional role and Note 1 to entry have been added.]

3.8

license document

document which contains references to the various keys, links to related external resources, rights and restrictions that are applied to *protected publication* (3.9), and *user* (3.19) information

[SOURCE: ISO/IEC 23078-2:2024, 3.6]

3.9

protected publication

publication (3.12) in which *resources* (3.16) have been encrypted according to this document

[SOURCE: ISO/IEC 23078-2:2024, 3.10, modified — The preferred term "LCP-protected publication" has been removed.]

3.10

provider

content provider

entity that delivers licenses for *protected publications* (3.9) to *users* (3.19)

[SOURCE: ISO/IEC 23078-2:2024, 3.11, modified — "LCP" before "licenses" has been removed.]

3.11

provider certificate

certificate that is included in the *license document* (3.8) to identify the *content provider* (3.10) and validate the signature of the license document

[SOURCE: ISO/IEC 23078-2:2024, 3.12]

3.12

publication

EPUB publication

logical document entity consisting of a set of interrelated *resources* (3.16) and packaged in an *EPUB container* (3.2)

[SOURCE: ISO/IEC 23078-2:2024, 3.13]

3.13

reading system

system which processes *EPUB publications* (3.12) and presents them to *users* (3.19)

[SOURCE: ISO/IEC 23078-2:2024, 3.14]

3.14

reading system developer developer

EPUB reading system developer

entity which signs the *device certificate* (3.4) associated with a *reading system* (3.13)

3.15

reading system developer certificate developer certificate

EPUB reading system developer certificate

certificate which is embedded in the *reading system* (3.13) in order to confirm that the *device certificate* (3.4) is valid

3.16

resource

publication resource

content or instructions that contribute to the logic and rendering of an *EPUB publication* (3.12)

[SOURCE: ISO/IEC 23078-2:2024, 3.15]

3.17

root certificate

certificate possessed by the *license authority* (3.7) and embedded in each EPUB *reading system* (3.13) in order to confirm that the *provider certificate* (3.11) or *reading system developer* (3.14) is valid

[SOURCE: ISO/IEC 23078-2:2024, 3.16, modified — "or reading system developer" has been added.]

3.18

status document

license status document

document that contains the current status and possible interactions with a *license document* (3.8), along with historical information

[SOURCE: ISO/IEC 23078-2:2024, 3.17]

3.19

user

individual who consumes an *EPUB publication* (3.12) using an EPUB *reading system* (3.13)

[SOURCE: ISO/IEC 23078-2:2024, 3.18]

3.20

user key

hash value of the *user passphrase* (3.21), used to authenticate a *reading system* (3.13) to be able to access a *protected publication* (3.9)

Note 1 to entry: User key in this document is only used for authentication purpose to access a protection publication.

[SOURCE: ISO/IEC 23078-2:2024, 3.19, modified — The decryption role has been removed; the authentication role and Note 1 to entry have been added.]

3.21

user passphrase

string of text entered by the *user* (3.19) for obtaining access to the *protected publication* (3.9)

[SOURCE: ISO/IEC 23078-2:2024, 3.20]

4 Abbreviated terms

DRM digital rights management

LCP licensed content protection

5 Overview

5.1 General


In order to deliver a publication to users without risk of indiscriminate redistribution, most publication resources are encrypted; and a license document is generated.

The license document can be transmitted outside an EPUB container or be embedded inside it. Following the EPUB 3.3 specification, META-INF/encryption.xml identifies all encrypted publication resources and points to the content key needed to decrypt them. This content key is located inside the license document and is itself encrypted using the device key. The device key is a public key whose paired device private key is present in the device. It is used to decrypt the content key, which in turn is used to decrypt the publication resources.

The license document may also contain links to external resources, information identifying the user, and information about what rights are conveyed to the user and which are not. Rights information may include things like the time during which the license is valid, or whether the publication may be printed or copied, etc. Finally, the license document always includes a digital signature to prevent modification of any of its components.

NOTE This subclause has been modified from ISO/IEC 23078-2:2024, 5.1. The role of user key has been removed and device key has been added.

[Figure 1](#) shows the relationships among the various components of device key-based protection.



NOTE 1 This figure has been modified from ISO/IEC 23078-2:2024, Figure 1. The user key has been removed, and device key has been added.

NOTE 2 The content key is encrypted using the device key and decrypted using the device private key; the mechanism is different in ISO/IEC 23078-2, where the content key is encrypted and decrypted using the user key.

Figure 1 — Protected publication with a license document

5.2 Protecting the publication

ISO/IEC 23078-2:2024, 5.2 shall apply.

5.3 Licensing the publication

After a user has requested a protected publication, the following steps are followed by the content provider to license the protected publication:

- Generate the user key by hashing the user passphrase (as described in 6.4.2). It is assumed that the user and associated user passphrase are already known to the provider.
- Store this user key for future use.
- Encrypt the content key associated with the protected publication using the device key found in the device certificate. The device certificate has been registered by the reading system in advance (as described in 7.4.4).
- Create a device key-based license document (META-INF/license.lcpl) with the following contents:
 - a unique ID for this license;
 - the date the license was issued;
 - the URI that identifies the content provider;
 - the encrypted content key;
 - information relative to the user passphrase and user key;
 - information relative to the device key;

- 7) links to additional information stored outside of the protected publication and license document (optional);
 - 8) information on specific rights being granted to the user (optional);
 - 9) information identifying the user (optional). Some of the fields in this section may be encrypted using the device key.
- e) Generate a digital signature for the license document data and add it to the license document.

There are then two different methods to deliver the license document and protected publication to the user:

- License document included inside the protected publication: The provider adds the license document to the protected publication's container and delivers this to the user.
- License document delivered separately: The provider includes a link to the protected publication in the license document, and then delivers just the license document to the user. The reading system processing the license document downloads the protected publication and adds the license document to the container of the protected publication.

Whichever method is used, the reading system is presented with an EPUB container that includes the protected publication and the license document.

NOTE This subclause has been modified from ISO/IEC 23078-2:2024, 5.3. Step b) and step d) 6) have been added, and user key has been changed with device key in step d) 9).

5.4 Reading the publication

5.4.1 General

In order to decrypt and render a protected publication, the reading system follows the steps specified in [5.4.2](#), [5.4.3](#) and [5.4.4](#).

NOTE This subclause has been extended from ISO/IEC 23078-2:2024, 5.4 into 5.4.1, 5.4.2, 5.4.3 and 5.4.4.

5.4.2 Registering a device

A device registration is mandatory before a device key-based license is obtained. The register link is obtained from a license status document; and this link is specific to the license to be acquired.

Any user who knows the passphrase of a publication can register the device to the provider, get the associated device key-based license document and open the publication, as long as the accumulated number of registrations does not exceed the limit defined by the provider.

5.4.3 Acquiring a device key-based license document

After having successfully registered the device, a reading system is able to acquire a device key-based license document.

5.4.4 Decrypting a resource

After having successfully acquired the device key-based license document, the reading system follows these steps, in a highly secured manner:

- a) Verify the signature for the license document.
- b) Get the device private key associated with the reading system.
- c) Decrypt the content key using the device private key.
- d) Decrypt the protected resources using the content key.

NOTE The acquiring process of the user key in the step b) in the ISO/IEC 23078-2:2024 has been changed to a process for getting the device private key; and the process using the user key in the step c) has been changed to one using the device private key.

5.5 Licensing workflows

5.5.1 General

Device registration is required by this document before a protected publication can be processed by a reading system, which is a difference compared to ISO/IEC 23078-2:2024. Such registration is necessary when a reading system gets a protected publication as well as when a protected publication is transferred from a reading system to another one.

5.5.2 Getting a protected publication

The first time a license document is issued to a user, the provider cannot generate a user-specific device key-based license document because the device is not yet registered for this license and therefore the provider server doesn't know the device key yet.

The provider therefore issues a license document whose content key is encrypted using a device key defined by the provider itself. The reading system does not possess the matching device private key and therefore cannot process this version of the license document. It can still retrieve the license status document, register the device, retrieve an updated license status document and then fetch the device key-based license document tied to the reading system.

The corresponding workflow is illustrated in [Figure 2](#):




Figure 2 — Workflow of licensing for getting a protected publication

5.5.3 Transferring a protected publication

After successfully opening a protected publication on a device, a user may export this protected publication and try to open it on another device. In such a case the second reading system, even if compliant with this document, is not able to decrypt the content key because its device private key does not match the device key of the first device.

Such reading system therefore has to register the new device in order to get a new license document generated with the proper device key information.

The corresponding workflow is illustrated in [Figure 3](#):




Figure 3 — Workflow of licensing for transferring a protected publication

5.5.4 Register device certificate and update license document

The two previous processes share the same registration and license acquisition process between the reading system and the provider:

- The reading system gets a license status document.
- The reading system gets the user key (if it has previously stored it) or generates it by hashing the user passphrase.
- The reading system gets the developer certificate and device certificate (assuming that these have already been generated and installed during the installation of the reading system).
- The reading system registers the device using the register link found in the license status document, with the user key, developer certificate and device certificate as parameters (see [7.4.4](#)).
- The provider server verifies that the user key matches the value associated with the owner of the license. An error is returned if it is not the case.
- The provider validates the device registration, as long as the user key is correct and the limit on the number of allowed registrations has not been reached for the current license. An error is returned if it is not the case.
- The provider returns an updated license status document.
- The reading system requests an updated license document (see [7.3.4.3](#) and [7.4.3](#)).
- The provider server issues a device key-based license document.

The corresponding workflow is illustrated in [Figure 4](#):




Figure 4 — Workflow of registering device certificate and updating license document

6 License document

6.1 General

ISO/IEC 23078-2:2024, 6.1 shall apply.

NOTE [Annex A](#) shows an example of a license document. [Annex B](#) depicts schema of the license.

6.2 Content conformance

ISO/IEC 23078-2:2024, 6.2 shall apply.

6.3 License information

6.3.1 General

ISO/IEC 23078-2:2024, 6.3.1 shall apply.

6.3.2 Encryption (transmitting keys)

6.3.2.1 General

To transmit keys, the encryption object shall contain the profile, content_key, user_key objects and device_key objects in accordance with [6.3.2.5](#).

NOTE This subclause has been modified from ISO/IEC 23078-2:2024, 6.3.2.1. The device key has been added.

6.3.2.2 Profile

The encryption/profile object shall contain the value defined in [Table 1](#).

Table 1 — Profile information in encryption

Name	Value	Format/data type
profile	Identifier for the encryption profile used by this ISO/IEC 23078-3 compliant publication.	URI

NOTE [Table 1](#) has been modified from ISO/IEC 23078-2:2024, Table 2. The value of profile has been changed.

6.3.2.3 Content key

The encryption/content_key object contains the content key (encrypted using the device key) used to encrypt the publication resources. It shall contain the name/value pairs described in [Table 2](#).

Table 2 — Content key information in encryption

Name	Value	Format/data type
encrypted_value	Encrypted content key.	Base 64 encoded octet sequence
algorithm	Algorithm used to encrypt the content key, identified using the URIs defined in W3C XML Encryption. This shall match the content key encryption algorithm named in the encryption Profile identified in encryption/profile.	URI

NOTE This subclause has been modified from ISO/IEC 23078-2:2024, 6.3.2.3. The content key is encrypted using the device key.

6.3.2.4 User key

The encryption/user_key object contains information regarding the user key used to authenticate the user. It shall contain the name/value pairs defined in [Table 3](#).

Table 3 — User key information in encryption

Name	Value	Format/data type
text_hint	Hint to be displayed to the user in order to help him remember the user passphrase.	String
algorithm	Algorithm used to generate the user key from the user passphrase. This URI shall match the user passphrase hash algorithm specified in the encryption profile identified in encryption/profile.	URI

NOTE [Table 3](#) has been modified from ISO/IEC 23078-2:2024, Table 4. The key_check property has been removed.

6.3.2.5 Device key

The encryption/device_key object contains information associated with the device key that is used to encrypt the content key. It shall contain the name/value pairs defined in [Table 4](#).

Table 4 — Device key information in encryption

Name	Value	Format/data type
key_name	DN (Distinguished Name in X.509 as defined in RFC 5280) described in the device certificate, which is used for identifying the paired device private key.	String
key_check	Value of the license document's id field, encrypted using the device key and the same algorithm identified for content key encryption in encryption/content_key/algorithm. This is used to verify that the reading system has the correct device private key.	Base 64 encoded octet sequence

EXAMPLE Encryption information for a license document with content key, user key and device key for this document.


```
{
  "id": "ef15e740-697f-11e3-949a-0800200c9a66",
  "issued": "2013-11-04T01:08:15+01:00",
  "updated": "2014-02-21T09:44:17+01:00",
  "provider": "https://www.imaginaryebookretailer.com",
  "encryption": {
    "profile": "http://iso.org/ISO-23078-3/basic-profile",
    "content_key": {
      "encrypted_value": "/k8RpXqf4E2WEunCp76E8PjhS051NXwAXeTD1ioazYxCRGvHLAck/
KQ3cCh5JxDmCK0nRLyAxs1X0aA3z55boQ==",
      "algorithm": "http://www.w3.org/2001/04/xmlenc#rsa-oaep-mgflp"
    },
    "user_key": {
      "text_hint": "Enter your email address",
      "algorithm": "http://www.w3.org/2001/04/xmlenc#sha256"
    },
    "device_key": {
      "key_name": "CN=$DEVICE_ID, O=EDRLab",
      "key_check": "1jJEjUDipHK3OjGt6kFq7dcOLZuicQFUYwQ+TYkAIWKm6Xv6kpHFhF71OkUK/Owww"
    }
  },
  "links": "...",
  "rights": "...",
  "signature": "..."
}
```

6.3.3 Links (pointing to external resources)

6.3.3.1 General

ISO/IEC 23078-2:2024, 6.3.3.1 shall apply.

6.3.3.2 Link object

ISO/IEC 23078-2:2024, 6.3.3.2 shall apply.

6.3.3.3 Link relationships

Link relationships defined in ISO/IEC 23078-2:2024, 6.3.3.3 are valid in this document. The specificity of this document is that a license document shall have a status link. [Table 5](#) introduces link relationships for each link object which is used for value of rel.

Table 5 — Link relationships of link

Relation	Semantics	Required?
hint	Location where a reading system can redirect a user looking for additional information about the User Passphrase	Yes
publication	Location where the publication associated with the license document can be downloaded	Yes
self	As defined in the IANA registry of link relations: "Conveys an identifier for the link's context"	No
support	Support resources for the user (either a website, an email or a telephone number)	No
status	Location of the license status document associated with the license document	Yes

NOTE [Table 5](#) has been modified from ISO/IEC 23078-2:2024, Table 6. The 'Required?' field has been changed.

EXAMPLE A license document points to a publication, contains the location of the status document and the location of a hint about the user passphrase.

```
{
  "id": "ef15e740-697f-11e3-949a-0800200c9a66",
  "issued": "2013-11-04T01:08:15+01:00",
  "updated": "2014-02-21T09:44:17+01:00",
  "provider": "https://www.imaginaryebookretailer.com",
  "encryption": "...",
  "links": [
```

```
{ "rel": "publication",
  "href": "https://www.example.com/file.epub",
  "type": "application/epub+zip",
  "length": "264929",
  "hash": "8b752f93e5e73a3efff1c706c1c2e267dfc6ec01c382cbe2a6ca9bd57cc8378"
},
{ "rel": "hint",
  "href": "https://www.example.com/passphraseHint?user_id=1234",
  "type": "text/html"
},
{ "rel": "status",
  "href": "https://www.example.com/lsd/4d8f5e99-7f18-7ab8/status",
  "type": "application/vnd.readium.license.status.v1.0+json"
}
],
"rights": "...",
"signature": "..."
}
```

6.3.4 Rights (identifying rights and restrictions)

ISO/IEC 23078-2:2024, 6.3.4 shall apply.

6.3.5 User (identifying the user)

ISO/IEC 23078-2:2024, 6.3.5 shall apply.

6.3.6 Signature (signing the license)

ISO/IEC 23078-2:2024, 6.3.6 shall apply.

6.4 User key

6.4.1 General

This document uses a passphrase model for authenticating a user. The user passphrase can be anything at all: a user-defined password, a content provider-defined password, an e-mail address, a library card number, etc. The user key is defined as a hash of the user passphrase. A user key is sent to the provider server at the time of registration of a device. The content provider verifies the user key using its own copy of the user passphrase information, stored in the provider server.

When the reading system opens a protected publication for the first time, it prompts the user for a passphrase, generates the corresponding user key and stores this information securely for future use.

6.4.2 Calculating the user key

ISO/IEC 23078-2:2024, 6.4.2 shall apply.

6.4.3 Hints

ISO/IEC 23078-2:2024, 6.4.3 shall apply.

6.4.4 Requirements for the user key and user passphrase

ISO/IEC 23078-2:2024, 6.4.4 shall apply.

6.5 Signature and public key infrastructure

6.5.1 General

6.5.1.1 Validity of license document

ISO/IEC 23078-2:2024, 6.5.1 shall apply.

6.5.1.2 Validity of a device certificate

Since this document allows any reading system with a valid device certificate to register the device and get a device key-based license document as long as the user knows the passphrase associated with the license document, it is critical that the provider can verify that the device certificate is authentic and has not been altered.

When requested to register a device, the content provider first validates the developer certificate as well as the device certificate which are sent from the reading system. The validation process is also executed for checking the validity of the certificate chain among the root certificate, developer certificate and device certificate.

To make sure that the developer certificate and the device certificate have not been revoked, the provider also checks a certificate revocation list maintained by the license authority.

NOTE This subclause has been extended from ISO/IEC 23078-2:2024, 6.5.1 into 6.5.1.1 and 6.5.1.2. The general explanation on the validation process of device certificate has been added.

6.5.2 Certificates

6.5.2.1 Provider certificates

ISO/IEC 23078-2:2024, 6.5.2.1 shall apply.

6.5.2.2 Root certificate

ISO/IEC 23078-2:2024, 6.5.2.2 shall apply.

6.5.2.3 Developer certificates

The developer of a reading system shall have a certificate in the [X.509] v3 format, issued and signed by the license authority using the private key paired with the root certificate: this is referred to here as the developer certificate. The subject of the developer certificate should represent the reading system developer.

Reading system developers shall distribute their developer certificates when the reading system is installed.

6.5.2.4 Device certificates

A reading system shall have a certificate in the [X.509] v3 format, issued and signed by the developer of the reading system using the private key paired with its developer certificate: this is referred to here as the device certificate. The subject of the device certificate should represent a reading system; it should not include any user's personal information.

The reading system should obtain a signed device certificate from the reading system developer via a proprietary and secure channel at the time the reading system is installed.

For a device certificate to be considered valid, the developer certificate shall have been valid at the time the device certificate was signed (as indicated by the issued field); and the developer certificate shall not have been revoked.

6.5.3 Canonical form of the license document

ISO/IEC 23078-2:2024, 6.5.3 shall apply.

6.5.4 Generating the signature

ISO/IEC 23078-2:2024, 6.5.4 shall apply.

6.5.5 Validating the certificate and signature

6.5.5.1 Validating the certificate

- a) The reading system shall check the signature of the provider certificate and developer certificate using the root certificate it embeds.
- b) The reading system shall check the signature of the device certificate using the developer certificate.
- c) If a network connection is available, the reading system shall periodically update its certificate revocation list, as defined in RFC 5280.
- d) The reading system shall check that the device certificate, provider certificate, and developer certificate are not revoked, as defined in RFC 5280.
- e) The reading system shall check that the provider certificate has not expired when the license document was last updated.
- f) The reading system shall check that the developer certificate has not expired when the reading system gets the device certificate.

6.5.5.2 Validating the signature

ISO/IEC 23078-2:2024, 6.5.5.2 shall apply.

6.6 Device key

6.6.1 General

To transfer a content key securely from the provider to a reading system using an asymmetric cryptographic key, the provider uses the reading system's public key called the device key, while the reading system uses for decryption the associated private key called as device private key. The key pair is stored in the reading system; and the device certificate, which includes the device key, is sent to the provider before a device key-based license document is acquired.

6.6.2 Generating the device key

A key pair (private and public keys defined in RFC 5280) for a reading system should be generated when the reading system is installed, where the public key is used as device key and the private key is used as device private key. Then the reading system developer shall sign the device key to make a device certificate. No human intervention for authentication between the reading system and reading system developer should be involved for key pair generation and signing.

Here is a possible scenario for key pair generation:

- a) The reading system generates a X.509 key pair during installation.
- b) The reading system sends the public key to the developer and requests signing via a secure channel.
- c) The developer signs the public key with the developer private key.
- d) The developer returns the signed device certificate to the reading system.

6.6.3 Recommendations for the device private key protection

Although it is not an interoperability issue, protection measures applicable to the handling of the device private key and the signing process of the device key are very important in this document. It is recommended to follow the security guidelines outlined below:

- The device private key should be stored in an encrypted form in the reading system.
- The cryptographic algorithm used to protect the device private key should be at least as secure as AES-256, defined in FIPS 197.
- The key used for the encryption of the device private key should be unique for every reading system.
- The key used for the encryption of the device private key should be related to the device H/W information of the reading system, so that a copy of the encrypted device private key cannot work on another device.
- A communication protocol used between the reading system and the reading system developer for certificate signing should be at least as secure as SSL, defined in RFC 6101.
- The encryption algorithm used to protect the device private key and the communication protocol used to retrieve the device certificate should not be open to the public.

7 License status document

7.1 General

This clause defines the status of a DRM license along with the interactions that can affect its status. It also contains a history of the events associated with the license.

The interactions defined in this document aim at supporting lending in public libraries, where a user may have the ability to renew a time-limited loan or return one before it expires. And the register interaction is necessarily used for registering the device certificate of the reading system.

[Annex A](#) shows an example of a license status document.

7.2 Content conformance

ISO/IEC 23078-2:2024, 7.2 shall apply.

7.3 License status information

7.3.1 General

ISO/IEC 23078-2:2024, 7.3.1 shall apply.

7.3.2 Status

ISO/IEC 23078-2:2024, 7.3.2 shall apply.

7.3.3 Updated

ISO/IEC 23078-2:2024, 7.3.3 shall apply.

7.3.4 Links

7.3.4.1 General

ISO/IEC 23078-2:2024, 7.3.4.1 shall apply.

7.3.4.2 Link object

Each link object contained in links supports the keys defined in [Table 6](#).

Table 6 — Object list in link

Name	Value	Format/data type	Required?
href	Link location.	URI or URI template	Yes
rel	Link relationship to the document.	List of well-known relation values, URIs for extensions as defined in 7.3.4.3	Yes
title	Title of the link.	String	No
type	Expected MIME media type value for the external resources.	MIME media type	No, but highly recommended
templated	Indicates that the href is a URI template.	Boolean	No, default value is "false"
profile	Expected profile used to identify the external resource.	URI	No, default value is "http://iso.org/ISO-23078-3/basic-profile"

NOTE [Table 6](#) has been modified from ISO/IEC 23078-2:2024, Table 13. The 'Required?' field of the profile relation has been changed.

7.3.4.3 Link relationships

This document introduces the link relationships defined in [Table 7](#) for each link object which is used for value of rel.

Table 7 — Allowed value list in rel

Relation	Semantics	Templated?	Required?	HTTP verb
license	Location of the license document associated to the status document.	No	Yes	GET
register	Action to register a device.	Yes	Yes	POST
return	Action to return a license.	Yes	No	PUT
renew	Action to renew a license.	Yes	No	PUT

NOTE [Table 7](#) has been modified from ISO/IEC 23078-2:2024, Table 14. The 'Required?' field of the register relation has been changed.

7.3.5 Potential rights

ISO/IEC 23078-2:2024, 7.3.5 shall apply.

7.3.6 Events

ISO/IEC 23078-2:2024, 7.3.6 shall apply.

7.4 Interactions

7.4.1 General

ISO/IEC 23078-2:2024, 7.4.1 shall apply.

7.4.2 Handling errors

ISO/IEC 23078-2:2024, 7.4.2 shall apply.

7.4.3 Checking the status of a license

ISO/IEC 23078-2:2024, 7.4.3 shall apply.

7.4.4 Registering a device

Registration of the device is mandatory for every publication before a device key-based license document can be acquired.

When a reading system opens a license document for the first time and gets access to its associated status document:

- it shall attempt to register the device to the provider using the link exposed in the status document;
- it shall block the user from accessing the publication associated with the license document if the registration fails (the reading system cannot decrypt the protected resource if the registration process is not successful);
- it shall attempt to register itself again if it couldn't do so the first time the license document was opened.

NOTE 1 The requirements for a reading system on registering a device have been modified from ISO/IEC 23078-2:2024, 7.4.4.

During the registration, a reading system shall always send the same unique identifier for a specific device, no matter which status document it interacts with. Any further interaction with a provider should use the same identifier/name. To consider user privacy and assure the unicity of device ids, the client should generate device unique ids using a hash value of the device key. [Table 8](#) defines a HTTP protocol for the register interaction.

Table 8 — HTTP protocol for register interaction

Relation	Semantics	Templated?	Required?	HTTP verb
register	Associate a new device with the license	Yes	Yes	POST
Parameter*	Format	Semantics		Required?
id	Octet sequence	A unique identifier for the device.		Yes
name	String	A human readable name for the device.		Yes
user_key	Base 64 encoded octet sequence	The user key of the publication, derived from the user passphrase. The algorithm for deriving the user key from the user passphrase is specified in the encryption profile identified in encryption/profile in the license document.		Yes
device_certificate	Base 64 encoded DER certificate	The device certificate: an X.509 certificate containing the device key		No (Yes, if the first time)
developer_certificate	Base 64 encoded DER certificate	The reading system developer certificate: an X.509 certificate used for signing the device certificate		No (Yes, if the first time)

NOTE 2 [Table 8](#) has been extended from ISO/IEC 23078-2:2024, Table 18. The user_key, device_certificate and developer_certificate parameters have been added.

All parameters in [Table 8](#) shall be URL encoded.

[Table 9](#) defines the expected behaviour of the server and client on the register interaction.

Table 9 — Expected behaviour of register interaction

Server side behaviour	HTTP status code	Client side behaviour
The server registers the device identified by 'id' if user_key matches the license owner. It then returns an updated status document. The server shall update the timestamp of the status document contained in the status key of the updated object. If the status was previously set to 'ready', it shall be updated by the server to 'active' instead. The server may also add a new event in the events object of the status document.	200	Once the certificate is registered properly, the client may not attempt to register the device again for this license.

NOTE 3 [Table 9](#) has been modified from ISO/IEC 23078-2:2024, Table 19.

[Table 10](#) defines expected failures of server response on the register interaction.

Table 10 — Expected failures of register interaction

Type	HTTP Status Code	Title
https://readium.org/license-status-document/error/registration	400	Your device could not be registered properly.
https://readium.org/license-status-document/error/registration/authentication	403	The user key is incorrect.
https://readium.org/license-status-document/error/registration/limit	403	The number of registrations exceeds the limit.
https://readium.org/license-status-document/error/registration/not-acceptable	406	The request does not include a device_certificate or developer_certificate, or there was no registered device certificate associated with the device id in the server.
https://readium.org/license-status-document/error/server	5xx	An unexpected error has occurred.

NOTE 4 [Table 10](#) has been extended from ISO/IEC 23078-2:2024, Table 20. Two error types equivalent to HTTP status 403 and 406 are added.

Example 1 A simple license with a registration link.

```
{
  "links": [
    {
      "rel": "register",
      "href": "https://example.org/license/aaa-bbbb-ccc/register?id,name,user_key,device_certificate,developer_certificate",
      "type": "application/vnd.readium.license.status.v1.0+json",
      "templated": true
    }
  ]
}
```

Example 2 A sample for a HTTP request body, in which a device registers the device key.

```
POST /license/aaa-bbbb-ccc/register HTTPS/1.1
Host: example.org
```

```
id=B9DA0A331B6A1F1CBE797FB37138586EBB42539C1DCA4FBFD2DD0E68FF59FCC7
&name=eBook%20App%20(Android)
&user_key=qwYXxfNDVt3z0OZyv010mzL37wLYi986zOR7mU5ZGj4%3D
&device_certificate=MIIESTCCAzGgAwIBAgIDAnkyMA0GCSqGSIb3DQEBCwUAMHUxGT AXBgNVBAoTEGNCvCHlyaWdodHMub3Iua3IwGTAxBgNVBAsTEGNCvCHlyaWdodHMub3Iua3IwGTAxBgNVBAMTDURSTSBpbNpZGUgQ0ExJTAjBgNVBC4THFEyQktabXdpVUZvRXdrUEEx3Wn pdwdjdJTMnZVT0WHhcNMTUwNjA4MDUyMDE1Wjc1MRkwFwYDVQQK ExBjb3B5cmlnaHRzLm9yLmtyMRkwFwYDVQQLExBjb3B5cmlnaHRzLm9yLmtyMRYwFAYDVQQDEw1Cb29raW5nU2Vyd mVyMSUwIwYDVQQuExw0L2FQNEpiUS9mMDdzTk5ueFdgT1BoMkKx WEk9MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAul5CkVsQDxxqTkDc4sClfe I2esChMv0bPjJ9pWln3VoBqA6BzEDNYcpnF9Ic5ZdOcBW0egSAiHb2EcDnzT94FH7SryC9 7ia%2F9TqRs2pdHQacL9fCOjCrIsmwZ2RmGevft0oLM1KNhePS1E8nvnt8521DpJWDIGV9 rDIVCWXY6PcylkZY OyXXYJxDa886Vgjpeeg9UKtWTO495aHJdDJ7Iaeokh4bb8CuEI2ro 13HXcWiivTdjC7eNK2UFhyIYecQOIJAV%2FGDjvb LlWnVBuauYqLrWBe3bSeKCDXUGnNwF F14XKBQ7Oojc3ktaDHbdKHz2XsPlpi16ZZVE7F4BgUJwIDAQBo4HhMIHeMAsGA
```


1UdDwQE AwIEsDAMBgNVHRMBAf8EAjAAMB0GA1UdDgQWBbTj9o%2FgltD9%2FTuw02fFaM4%2BHYjV cjCBoQYDVR0jBIG
ZMIGWgBRDYEpmBcJQWgTCQ8vBnOm%2FsglyxaF5pHcWdTEZMBCGA1UEChMQY29weXJpZ2h0cy5vci5rcjEZMBcGA1UEC
MQY29weXJpZ2h0cy5vci5rcjEWMBQGA1UEAxMNRfJNIGluc2lkZSBdQTElMCMGA1UELhMcUTJCS1ptd2lVRm9Fd2tQTHd
aenB2N0lO Y3NVPYIDANhpMA0GCSqGSIB3DQEBcWUAA4IBAQCjVTU2JPcY7l041h6KcM2%2BLKJE9252 %2BfPYk7YzLcx
CT3Zkt44bairKqqHuyNBzCjPLWrHNYaBz%2F5BX1qxyKm6QgFpUDpVBT 2tIDl97%2FmGMiBfCvTxCarKAipSvzj%2Fif
0tZd9n%2BPuBGPznWibQsg2nH77LGRuGJH BG70%2BLmpg%2BT2R2lq2FBOodonMzzmx16judWhOVzmc1bt7ZtdgHohfaL
wyu2yLrmmBy StDlqI7ZBqDg%2BqFXK0OrWc%2F%2BbgESXZ1yiRmCNGIazrHUcqHQFLaVGbzylI9Qmt5l 7zIOuX0N2su
1JGMwB7vg%2F9c7d1YP1l1TNvyMS43tnKmhC77BUcCR
&developer_certificate=MIIESTCCAzGgAwIBAgIDANkyMA0GCSqGSIB3DQEBcWUAMHUx
GTAXBgNVBAoTEGNvchlyaWdodHMub3Iua3IxtGTAXBgNVBAsTEGNvchlyaWdodHMub3Iua3IxFjAUBgNVBAMTDURSTSBpb
nNpZGUGQ0ExJTAjBgNVBC4THFEyQktabXdpVUZvRXdrUEX3 WnpwdjdJTMNzVT0wHhcNMTUwNjA4MDUyMDElWhcNMjQwO
DA5MDUyMDElWjB1MRkwFwYDVQ KEExBjB3B5cm1naHRzLm9yLmtyMRkwFwYDVQLEExBjB3B5cm1naHRzLm9yLmtyMRYwF
AYD VQODEw1Cb29raW5uU2VydMvYMSUwIwYDVQQuExw0L2FQNEpiUS9mMDdzTk5ueFdqT1BoMk kxWEk9MIIBIjANBgkqh
kiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEaUl5CkVsQDxxqTkDc4sCl feI2esChMv0bPjj9pWln3VoBqA6BzEDNYcpnF9Ic5Z
dOcBW0egSAiHb2EcDnzT94FH7Sry C97ia%2F9TqRs2pdHQacL9fCOjCrIsmwZ2RmGevft0oLMlKNhePS1E8nvnt8521Dp
JWDIG V9rDIVCWxzy6PcylkZY0yXXYJxDa886Vgjee9UKtWTO495aHJdDJ7Iaeokh4bb8CuEI2 ro13HXcWiivTdjC7e
NK2UFhyIYecQoiJAV%2FGDjvblLWnVBUauYqLRwBe3bSeKCDXUGn WfF14XKBQ7Oojc3ktaDHbdKmx2XsPlpi16ZZVE7F
4BgUJwIDAQABo4HhMIHeMasGA1UdDw QEAWIEsDAMBgNVHRMBAf8EAjAAMB0GA1UdDgQWBbTj9o%2FgltD9%2FTuw02fFa
M4%2BHY jVcjCBoQYDVR0jBIGZMIGWgBRDYEpmBcJQWgTCQ8vBnOm%2FsglyxaF5pHcWdTEZMBCGA1 UEChMQY29weXJpZ
2h0cy5vci5rcjEZMBcGA1UECXMqY29weXJpZ2h0cy5vci5rcjEWMBQGA1UEAxMNRfJNIGluc2lkZSBdQTElMCMGA1UELh
McUTJCS1ptd2lVRm9Fd2tQTHdaenB2N0 lOY3NVPYIDANhpMA0GCSqGSIB3DQEBcWUAA4IBAQCjVTU2JPcY7l041h6KcM2
%2BLKJE92 52%2BfPYk7YzLcxCT3Zkt44bairKqqHuyNBzCjPLWrHNYaBz%2F5BX1qxyKm6QgFpUDpV BT2tIDl97%2Fm
GMiBfCvTxCarKAipSvzj%2Fif0tZd9n%2BPuBGPznWibQsg2nH77LGRuG JHBG70%2BLmpg%2BT2R2lq2FBOodonMzzmx1
6judWhOVzmc1bt7ZtdgHohfaLwyu2yLrmm ByStDlqI7ZBqDg%2BqFXK0OrWc%2F%2BbgESXZ1yiRmCNGIazrHUcqHQFLa
VGbzylI9Qmt 5l7zIOuX0N2su1JGMwB7vg%2F9c7d1YP1l1TNvyMS43tnKmhC77BUcCR

7.4.5 Returning a publication

ISO/IEC 23078-2:2024, 7.4.5 shall apply.

7.4.6 Renewing a license

ISO/IEC 23078-2:2024, 7.4.6 shall apply.

8 Encryption profiles

8.1 General

In order to maintain maximum flexibility, no specific algorithms are mandated by this document. Instead, the design of both encryption.xml and the license document allow for the identification of encryption algorithms to be discovered by reading systems when presented with a protected publication.

In order to simplify the discovery process, this document defines the notion of encryption profile, which is the set of encryption algorithms used in a specific protected publication and associated license document. Reading systems that implement the algorithms identified in the encryption profile are able to decrypt protected publications encoded using such encryption profile. The identification of the encryption profile in the license document eases the discovery of these requirements by reading systems.

This document defines the basic encryption profile 1.0, composed from a set of associated algorithms extracted from W3C XML Encryption or W3C XML Signature.

Other encryption profiles are (or will be) defined for use in production; these profiles are referenced in the ISO-23078-3 encryption profiles registry. Such profiles may use algorithms which are not directly extracted from W3C XML Encryption or W3C XML Signature.

NOTE This subclause has been modified from ISO/IEC 23078-2:2024, 8.1. Identifier of the specification has been changed as ISO-23078-3.

8.2 Encryption profile requirements

ISO/IEC 23078-2:2024, 8.2 shall apply.

8.3 Basic encryption profile

The basic encryption profile 1.0 for this specification is officially identified by the URI <http://iso.org/ISO-23078-3/basic-profile>.

The algorithms defined in [Table 11](#) are associated to the basic encryption profile 1.0.

Table 11 — Algorithm list for the basic encryption profile 1.0

Encryption target	Algorithm (name)	Algorithm (URI)	Identified in
publication re-sources	AES 256 bits CBC	http://www.w3.org/2001/04/xmlenc#aes256-cbc	encryption.xml
Content key, user fields (if encrypted)	RSA-OAEP	http://www.w3.org/2001/04/xmlenc#rsa-oaep-mgf1p	License document
User Passphrase	SHA-256	http://www.w3.org/2001/04/xmlenc#sha256	License document
Signature	ECDSA with SHA-256	http://www.w3.org/2001/04/xmldsig-more#ecdsa-sha256	License document

NOTE [Table 11](#) has been modified from ISO/IEC 23078-2:2024, Table 28. Encryption algorithms for content key and signature have been changed.

9 Integration in EPUB

ISO/IEC 23078-2:2024, Clause 9 shall apply.

10 Reading system behaviours

10.1 Detecting protected publications

ISO/IEC 23078-2:2024, 10.1 shall apply.

10.2 License document processing

ISO/IEC 23078-2:2024, 10.2 shall apply.

10.3 User key processing

ISO/IEC 23078-2:2024, 10.3 shall apply.

10.4 Signature processing

ISO/IEC 23078-2:2024, 10.4 shall apply.

10.5 Publication processing

ISO/IEC 23078-2:2024, 10.5 shall apply.

10.6 Device key processing

Reading systems shall:

- have a device certificate and a paired device private key;
- have a developer certificate used to verify the device certificate;

- register the device when opening a license document for the first time.

Reading systems should:

- store the device private key in a secure manner;
- get the device private key associated with the value of device_key/key_name property in the license document in a secure manner.

Reading systems shall not:

- transfer the device private key in any form outside of the reading system.

IECNORM.COM : Click to view the full PDF of ISO/IEC 23078-3:2024

Annex A (informative)

Examples

A.1 Example of a license document

In the following example, the license document contains the following information:

- Profile name: <http://iso.org/ISO-23078-3/basic-profile>
- Rights: no print, allowing copy as much as 2048 words at once, with starting and expiration date
- URL of the publication: <https://www.example.com/file.epub>
- URL of the status document: <https://example.org/license/status/aaa-bbbb-ccc>

```
{
  "id": "ef15e740-697f-11e3-949a-0800200c9a66",
  "issued": "2013-11-04T01:08:15+01:00",
  "encryption": {
    "content_key": {
      "algorithm": "http://www.w3.org/2001/04/xmlenc#rsa-oaep-mgf1p",
      "encrypted_value": "/k8RpXqf4E2WEunCp76E8PjhS051NXwAXeTD1ioazYxCRGvHLAck/KQ3cCh5JxDmCK0n
RLyAxs1X0aA3z55boQ=="
    },
    "profile": "http://iso.org/ISO-23078-3/basic-profile",
    "user_key": {
      "algorithm": "http://www.w3.org/2001/04/xmlenc#sha256",
      "text_hint": "Enter your email address"
    },
    "device_key": {
      "key_name": "CN=709e1380-3528-11e5-a2cb-0800200c9a66, O=DRMinside",
      "key_check": "1jJEjUDipHK3OjGt6KfQ7dcOLZuicQFUYwQ+TYkAIWKm6Xv6kpHFhF7LOkUK/Owww"
    }
  },
  "rights": {
    "print": 0,
    "copy": 2048,
    "start": "2020-01-01T00:00:00+01:00",
    "end": "2030-12-31T23:59:59+01:00",
    "https://www.imaginaryebookretailer.com/lcp/rights/tweet": true
  },
  "links": [
    { "rel": "hint",
      "href": "https://www.imaginaryebookretailer.com/lcp/hint",
      "type": "text/html"
    },
    { "rel": "status",
      "href": "https://example.org/license/status/aaa-bbbb-ccc",
      "type": "application/vnd.readium.license.status.v1.0+json"
    },
    { "rel": "publication",
      "href": "https://www.example.com/file.epub",
      "type": "application/epub+zip",
      "length": "264929",
      "hash": "8b752f93e5e73a3efff1c706c1c2e267dfc6ec01c382cbe2a6ca9bd57cc8378"
    }
  ],
  "user": { "id": "d9f298a7-7f34-49e7-8aae-4378ecb1d597" },
  "signature": {
    "algorithm": "http://www.w3.org/2001/04/xmldsig-more#rsa-sha256",
    "certificate": "MIIDEjCCAfoCCQDwMOjkYYOjPjANBgkqhkiG9w0BAQUFADBMLQswCQYDVQQGEwJVUzETMBEG"
```

```

A1UECBMKQ2FsaWZvcn5pYTETMBEGA1UEBxMKRXZlcn13aGVyZTESMBAGA1UEAxMJBG9jYWxob3N0M0B4XDTE0M DEwMjIx
MjYxNloXDTE1MDEwMjIxMjYxNlowSzELMAKGA1UEBhMCVVMxZARBgNVBAGTCkNhbgGmb3JuaWEeEzARBGNVB AcTCkV
2ZXJ5d2hlcmUxUjEjAQBgNVBAMTCWxvY2FsaG9zdDCCASIwDQYJKoZIhvcNAQEBBQADggEPADCCAQoCggEBAAOpCR ECG7i
cpf0H37kuAM7s42oqggBoikoTpo5yapy+s5eFSp8HSsqwhIYgZ4SghNLkj3e652SALav7chyZ2vWvitZycY+aq5 0n5UT
TxDvdwSC5ZNeTycuzVWZALKGhV7VUPEhtWZNm0gruntronNa8l2WS0aF7P5SbhJ65SDQGprFFaYOSyN6550P3kq aAO7
tDddcAlcmuIDRf8tOIIEmkBFklQf+lh+3uRP2wztOTECsMRxX/hIkCe5DRFDK2MuDUyc/iY8IbY0hMFFGw5J7MWOWZL
BOaZHX+Lf5lOYByPbMH7800dda6T+tLYAVzsmJdHJfTaRguCaJvtSXXQUAMCAwEAATANBgkqhkiG9w0BAQUFAA OCAQE
Ai9HIM+FMfqXsRUyOrGxLlw403f3YtAG/ohzt5i8DKiKUG3YAnwRbL/VzXLZaHru7XBC40wmKefKqoA0RHYNeddXgtY/
aXzOlftVp+xirop+D4DwJIbaj8/wHKWYGBucA/VgGY7JeSYYTUSuz2RoYtjPNRELIXN8A+D+nkJ3dxdFQ6jFfVfahN3nCI
gRqRIOTlKaNI39CSHccCaWJ5DeSASLXLPcEjrti/pyDzC4kLF0VjHYlKT7lq5RkM06GeC+7YFvJtAyssM2nqunA2lUgyQH
blq4Ih/dcYOACubtBwW0ITpHz8N7eO+rldtH/BF4yxeWl6p5kGLvuPXNU2lThgA=="
"value": "q/3IInic9c/EaJHyG1Kkqk5v1zlJNsiQBmzx4lykhyD3dA2jg2ZzrOenYU9GxP/xhe5H5Kt2WaJ/
hnt8+GWrExlQOwnNEij5CmIpZ63yRNKnFS5rSRnDMYmQT/fkUYco7BUi7MPPU6OFf4+kaToNWl8m/ZlMxDcS3BznVhSE
KzUNQnl1f2y3sUcXjes7wHbImDc6dRthbL/E+assh5HEqakrDuA4lM8XNfukEYQJnivqhqMLOGM33RnS5nZKrPPK/c2F/
vGjJffSrlX3W3Jlds0/MZ6wtVeKtugR06c56V6+qKsnMLAQJaeOxxBXmbFdAEyplP9irn4D9tQZKqbbMIw=="
}
}

```

A.2 Example of a license status document

In the following example, the status document indicates that the license has been registered for a single device and may be renewed or returned.

```

{
  "id": "234-5435-3453-345354",
  "status": "active",
  "message": "Your license is currently active and has been used on one device.",
  "updated": {
    "license": "2020-08-05T00:00:00Z",
    "status": "2020-08-08T00:00:00Z"
  },
  "links": [
    {
      "rel": "license",
      "href": "https://example.org/license/35d9b2d6",
      "type": "application/vnd.readium.lcp.license.v1.0+json",
      "profile": "http://iso.org/ISO-23078-3/basic-profile"
    },
    {
      "rel": "register",
      "href": "https://example.org/license/35d9b2d6/register?id,name,user_key,device_certificate,developer_certificate",
      "type": "application/vnd.readium.license.status.v1.0+json",
      "templated": true
    },
    {
      "rel": "return",
      "href": "https://example.org/license/35d9b2d6/return?id,name",
      "type": "application/vnd.readium.license.status.v1.0+json",
      "templated": true
    },
    {
      "rel": "renew",
      "href": "https://example.org/license/35d9b2d6/renew?end,id,name",
      "type": "application/vnd.readium.license.status.v1.0+json",
      "templated": true
    }
  ],
  "potential_rights": {
    "end": "2020-09-13T00:00:00Z"
  },
  "events": [
    {
      "type": "register",
      "name": "eBook App (Android)",
      "timestamp": "2016-07-14T00:00:00Z",
      "id": "709e1380-3528-11e5-a2cb-0800200c9a66"
    }
  ]
}

```

Annex B (informative)

Schema of license document

Schema of license document for this document is an extension of the Radium LCP schema.

There are 3 differences, with 1 redefinition and 2 extensions:

- It redefines the encryption/user_key object by removing the encryption/user_key/key_check property.
- It adds a new encryption/device_key object.
- It adds a mandatory status property in the link relationship.

```
{
  "$schema": "http://json-schema.org/draft-07/schema#",
  "title": "ISO/IEC 23078-3 v1.0",
  "description": "Copyright (c) 2020 The Radium Foundation.",
  "description": "Edited by DRM inside, 2016.",
  "description": "Edited by L.Le Meur / EDRLab, 2017.",
  "description": "Edited by H.Gardeur / Feedbooks, 2019.",
  "description": "Edited by T.H. Kim / DRM inside, 2020.",
  "type": "object",
  "properties": {
    "id": {
      "description": "Unique identifier for the License",
      "type": "string"
    },
    "issued": {
      "description": "Date when the license was first issued",
      "type": "string",
      "format": "date-time"
    },
    "provider": {
      "description": "Unique identifier for the Provider",
      "type": "string",
      "format": "uri"
    },
    "updated": {
      "description": "Date when the license was last updated",
      "type": "string",
      "format": "date-time"
    },
    "encryption": {
      "description": "Information related to the encryption of the content",
      "type": "object",
      "properties": {
        "profile": {
          "description": "Identifies the Encryption Profile used by this ISO-23078-3 Publication",
          "type": "string",
          "format": "uri"
        },
        "content_key": {
          "type": "object",
          "properties": {
            "encrypted_value": {
              "description": "Encrypted Content Key",
              "type": "string",
              "contentEncoding": "base64"
            },
            "algorithm": {
              "description": "Algorithm used to encrypt the Content Key",
              "type": "string",

```