
**Telecommunications and
information exchange between
systems — Recursive inter-network
architecture —**

**Part 5:
Incremental enrolment procedures**

*Télécommunications et échange d'information entre systèmes —
Architecture récursive inter-réseaux —*

Partie 5: Procédures d' enrôlement incrémentiel



IECNORM.COM : Click to view the full PDF of ISO/IEC 4396-5:2023



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword.....iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Overview of the procedures 1

5 Detailed specification of the procedures 2

5.1 Common elements 2

5.2 Enrolment 2

5.2.1 General 2

5.2.2 When sent 2

5.2.3 Action upon receipt 2

IECNORM.COM : Click to view the full PDF of ISO/IEC 4396-5:2023

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6 *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC 4396 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Telecommunications and information exchange between systems — Recursive inter-network architecture —

Part 5: Incremental enrolment procedures

1 Scope

This document defines the procedure executed by a Member of a distributed inter-process communication (IPC) facility (DIF) or distributed application facility (DAF) to initialize a new Member as a fully functioning Member. This document defines the procedure for a new Member to enrol when the new Member was recently a Member of the DIF or DAF. This document is defined for use with DIFs, but it can be used equally well by a DAF that wants to assign synonyms with a scope limited to the DAF.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4396-1, *Telecommunications and information exchange between systems — Recursive Inter-Network Architecture — Part 1: Reference Model*

ISO 4396-2, *Telecommunications and information exchange between systems — Recursive inter-network architecture — Part 2: Common application connection establishment procedure (CACEP)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4396-1 and ISO 4396-2 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Overview of the procedures

Enrolment is the procedure by which an IPC-process joins an existing DIF. Enrolment occurs after an IPC-Process establishes an application connection with another IPC-Process, which is a Member of a DIF. Once the CDAP Connection is established this enrolment procedure may proceed.

This procedure is intended to minimize the amount of data to send to the new Member on the assumption that it had been a Member and lost contact with the DIF, either through a crash or failure of the physical media. Other enrolment procedures are possible.

The Member reads the new Member's address. If null or expired, it assigns a new address; otherwise, it assumes the new Member was very recently a Member. The new Member then reads the information it does not have, taking into account how new it is. These parameters characterize the operation of this DIF and can include parameters, e.g. max PDU size, various time-out ranges, ranges of policies. Once complete, the new Member becomes a Member and this triggers a normal resource information base (RIB) update.

5 Detailed specification of the procedures

5.1 Common elements

RIB: The DIF-Allocator has access to the RIB information consistent with the access control policies. This system is a Member of, and is participating in, the directory chain associated with this DIF-Allocator.

5.2 Enrolment

5.2.1 General

Once the CDAP connection is established and the authentication policy is executed successfully which is signalled by receiving a Connect_Response, Enrolment may proceed. It is recognized that several sequences are possible, so other Enrolment procedures are possible. This Enrolment procedure attempts to efficiently include the case of the momentary loss of a Member, e.g. a router crashes and immediately comes back up. There are three types of enrolment information:

- a) static, part of the definition of the DIF;
- b) near static, may change but very infrequently, i.e. the address or adding a new QoS-cube;
- c) dynamic information, e.g. DIF-Allocator, Directory, and routing information.

5.2.2 When sent

Enrolment begins when the CDAP connection is established.

5.2.3 Action upon receipt

The following procedure is used to facilitate an existing Member becoming partitioned and re-joining. The basic idea is that if the Member is out of the DIF for less than the lifetime of an address assignment, the initialization can be shortened. If there are any errors or unexpected occurrences by either process, the process should send an A_Release (with no Response requested) and invoke Deallocate.

The Member sending a positive A_Connect_Response indicates that enrolment may start.

When the New Member receives the A_Connect Response, the new Member copies Current_Address to Saved_Address. sends

—A_Start Enrolment (address, Address_expiration_time, other data about new Member)

The new Member is telling the existing Member what it knows. Primarily this is derived from the address (NULL or not), and the expiration life-time of the address if non-NULL. Since addresses are generally assigned for hours or minutes, tight time synchronization is not required. (Even for DIFs with fast turnover, fairly long assignment times are still prudent.)*

The Member sends

← A_Start_R Enrolment (address (potentially different), Application Process Name, Current_Address, Address_Expiration)

Using the information provided by the new Member, the existing Member sends

← A_Create (zero or more) to initialize the static and near static information required. When finished and the new Member has sent all necessary → A_Create_Rs

the existing Member sends a

← A_Stop Enrolment (Immediate:Boolean)