



**International
Standard**

ISO 10077-2

**Thermal performance of windows,
doors and shutters — Calculation of
thermal transmittance —**

**Part 2:
Numerical method for frames**

AMENDMENT 1

*Performance thermique des fenêtres, portes et fermetures —
Calcul du coefficient de transmission thermique —*

Partie 2: Méthode numérique pour les encadrements

AMENDEMENT 1

**Third edition
2017-06**

**AMENDMENT 1
2024-12**



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 163, *Thermal performance and energy use in the built environment*, Subcommittee SC 2, *Calculation methods*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 89, *Thermal performance of buildings and building components*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

A list of all parts in the ISO 10077 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 10077-2:2017/Amd 1:2024

Thermal performance of windows, doors and shutters — Calculation of thermal transmittance —

Part 2: Numerical method for frames

AMENDMENT 1

6.4.2.4.1

Replace Figure 10 with the following figure and key:




Figure 10 — Examples for slightly ventilated cavities and grooves with small cross section

B.3


Replace the NOTE with the following:

NOTE Currently in this document, there are no choices between methods and the required input data foreseen that are to be kept open for completion as explained in B.1. To satisfy the need for congruence with all other EPB standards and to make explicitly clear that in this document there are no choices kept open, this annex and Annex A are retained.

F.2

Replace Figure F.2 with the following figure and key:

Dimensions in millimetres



Key

- b_f width of the frame
- b_g width of the glazing
- d_g thickness of the glazing

Figure F.2 — Schematic of profile section with glazing installed

H.2

Replace Table H.1 with the following table:

Table H.1 — Boundaries

Key	Surface resistance, R_s $m^2 \cdot K/W$	Temperature, θ $^{\circ}C$
A adiabatic boundary	infinity	—
B external surface resistance	see Annex E	0
C internal surface resistance	see Annex E	20

Add the following key to Figure H.1:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- d EPDM
- e polyamide 6,6 with 25 % glass fibre
- h aluminium^a
- ^a All surfaces have emissivity 0,9 except for Figure H.2.

Add the following key to Figure H.2:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- D emissivity 0,1
- a insulation panel
- d EPDM
- e polyamide 6,6 with 25 % glass fibre
- h aluminium^a
- ^a All surfaces have emissivity 0,9 except for Figure H.2.

Add the following key to Figure H.3:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- d EPDM
- e polyamide 6,6 with 25 % glass fibre
- h aluminium^a
- ^a All surfaces have emissivity 0,9 except for Figure H.2.

Add the following key to Figure H.4:

Key


- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- c PVC
- d EPDM
- g steel

Add the following key to Figure H.5:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- b soft wood
- d EPDM

Replace Figure H.6 with the following figure and key:



Key


- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel

- b soft wood
- d EPDM
- h aluminium

NOTE The projected frame width, b_f , is 89 mm.

Figure H.6 — Roof window frame section and insulation panel

Replace Figure H.7 with the following figure and add the following key:



Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- d EPDM

- h aluminium^a
- i pile weather stripping (polyester mohair)
- k polyamide
- l PU (Polyurethan-Hartschaum)
- ^a All surfaces have emissivity 0,9 except for Figure H.2.

NOTE The projected frame width, b_f , is 95 mm.


Figure H.7 — Sliding window frame section and insulation panel

Add the following key to Figure H.8:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- c PVC
- d EPDM

Replace Figure H.9 with the following figure and add the following key:




Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- c PVC

NOTE The shutter box width, b_{sb} , is 177 mm.

Figure H.9 — Roller shutter box

Replace Figure H.10 with the following figure and add the following key:



Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- c PVC

Figure H.10 — PVC shutter profile

Replace Figure H.11 with the following figure and add the following key:



- A adiabatic boundary
B external surface resistance
C internal surface resistance
b soft wood
d EPDM
f glass
h aluminium^a
m polysulfide
n silica gel (desiccant)
o gas filling
p polyisobutylene
a All surfaces have emissivity 0,9 except for Figure H.2.

NOTE See Figure H.5.

Figure H.11 — Example for the determination of a linear thermal transmittance of a wood frame section and of a glazing with $U_g = 1,3 \text{ W/(m}^2\cdot\text{K)}$ with a conventional glass edge system

H.3

Replace Table H.3 with the following table:

Table H.3 — Calculated thermal conductance L^{2D} and thermal transmittance

Example	L^{2D} W/(m·K)	U_f W/(m ² ·K)
Figure H.1	0,539	3,11
Figure H.2	0,508	2,83
Figure H.3	0,252	1,35
Figure H.4	0,400	1,86
Figure H.5	0,344	1,34
Figure H.6	0,407	2,07
Figure H.7	0,637	4,44
Figure H.8	0,281	1,23
Figure H.9	0,188	1,06
Figure H.10	0,208	3,64
NOTE To avoid rounding errors the values are given to three significant figures.		

I.2

Add the following key to Figure I.1:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- d EPDM
- e polyamide 6,6 with 25 % glass fibre
- h aluminium^a
- ^a All surfaces have emissivity 0,9.

Add the following key to Figure I.2:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- b soft wood
- d EPDM
- h aluminium^a
- ^a All surfaces have emissivity 0,9.

Add the following key to Figure I.3:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- c PVC
- d EPDM
- g steel


Add the following key to Figure I.4:

Key

- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- b soft wood
- d EPDM

Replace Figure I.5 with the following figure:

STANDARDSISO.COM : Click to view the full PDF of ISO 10077-2:2017/Amd 1:2024



Key


- A adiabatic boundary
- B external surface resistance
- C internal surface resistance
- a insulation panel
- b soft wood

- d EPDM
h aluminium^a
a All surfaces have emissivity 0,9.

NOTE The projected frame width, b_f , is 89 mm.

Figure I.5 — Roof window frame section and insulation panel

Replace Figure I.6 with the following figure and add the following key:



Key

- A adiabatic boundary
B external surface resistance
C internal surface resistance
a insulation panel
d EPDM