
**Industrial automation systems and
integration — Product data representation
and exchange —**

Part 203:

**Application protocol: Configuration
controlled design**

AMENDMENT 1

*Systèmes d'automatisation industrielle et intégration — Représentation et
échange de données de produits —*

Partie 203: Protocole d'application: Conception contrôlée de configuration

AMENDEMENT 1



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this Amendment may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to International Standard ISO 10303-203:1994 was prepared by Technical Committee ISO/TC 184, *Industrial automation systems and integration*, Subcommittee SC 4, *Industrial data*.

Introduction

This document amends ISO 10303-203:1994, *Industrial automation systems and integration — Product data representation and exchange — Part 203: Application protocol: Configuration controlled design*. The corrected document supersedes ISO 10303-203:1994.

The purpose of the modifications to the text of ISO 10303-203:1994 is to correct errors in the EXPRESS definitions likely to cause compilation problems and to replace the object identifier for the document and the applicable schema.

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd.1:2000

Industrial automation systems and integration — Product data representation and exchange —

Part 203:

Application protocol: Configuration controlled design

Amendment 1

Modifications to the text of ISO 10303-203:1994

Table of contents, pp. iii-iv, clause 2, p. 3, clause 5.2, pp. 89-242, annex A, pp. 270-400 and index, pp. 482-515

The purpose of these modifications is to correct Express errors that were not detected at the time of publication due to the immaturity of the checking tools at that time. The corrections have been documented in change pages for readability. The following pages replace Clause 2, Clause 5.2, Annex A and the index of ISO 10303-203:1994 in their entirety as well as pages iii and iv of the table of contents. The net affect of these changes in the short listing is:

- corrected `geometric_representation_item_3d` rule
- corrected `assembly_shape` is defined function
- corrected `subtype_mandatory_shape_representation` rule
- corrected `cc_design_date_time_correlation` function
- added USEs from AICs and removed the OLD 203 entities and functions
- added `dummy_gri` constant
- added `dummy_tri` constant
- added `degenerate_toroidal_surface` (per TC2)
- added `approval_person_organization_constraints` (to solve type pruning issue)
- added `approval_date_time_constraints` (to solve type pruning issue)
- removed `cartesian_transformation_opertor_2d` (per tc2)
- removed `offset_curve_2d` (per tc2)
- added `property_definition_representation` (per seds 57)
- added `representation_relationship` (per seds 57)
- added `b_spline_curve` (per seds 57)
- added `b_spline_surface` (per seds 57)
- added `conic` (per seds 57)
- added `point_replica` (per seds 57)
- added `swept_surface` (per seds 57)
- added `oriented_closed_shell` (per seds 57)
- added `path` (per seds 57)
- added `brep_with_voids` (per seds 57)

Since the long listing is generated from the short listing, the best method of presenting the long listing is to republish it as change pages. The index is being reissued to aid in navigation of the revised short and long listings. The clause 2 changes were made so the document references the appropriate 500 series parts.

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

4.1.11 part_identification	14
4.1.12 shape	14
4.1.13 source_control	14
4.1.14 wireframe_with_topology	15
4.2 Application objects	15
4.3 Application assertions	33
5 Application interpreted model	39
5.1 Mapping table	39
5.2 AIM EXPRESS short listing	89
5.2.1 Fundamental concepts and assumptions	97
5.2.2 Configuration controlled design constants	100
5.2.2 Configuration controlled design types	101
5.2.3 Configuration controlled design entities	105
5.2.3 Configuration controlled design imported entity modifications	116
5.2.4 Configuration controlled design rules	131
5.2.5 Configuration controlled design functions	194
6 Conformance requirements	243
6.1 Conformance class 1 entities	244
6.2 Conformance class 1b entities	245
6.3 Conformance class 2 entities	247
6.4 Conformance class 3 entities	250
6.5 Conformance class 4 entities	251
6.6 Conformance class 5 entities	253
6.7 Conformance class 6 entities	254
Annexes	
A AIM EXPRESS expanded listing	270
B AIM short names of entities	401
C Protocol Implementation Conformance Statement (PICS) proforma	412
D Implementation method specific requirements	414
E Information object registration	415
E.1 Document identification	415
E.2 Schema identification	415
E.2.1 config_control_design expanded schema	415
E.2.2 config_control_design short form schema	415
F Application activity model	416
F.1 AAM definitions	417
F.2 AAM Diagrams	420

G Application reference model	423
H AIM EXPRESS-G	431
J AIM EXPRESS listing	471
K Application protocol usage guide	472
K.1 Usage test purposes	472
K.2 Example part	476
L Bibliography	481
Index	482

Figures

Figure F.1 - IDEF0 basic notation	416
Figure F.2 - A0 Manage product development in IDEF0	421
Figure F.3 - A3 Develop product design in IDEF0	422
Figure G.1 - ARM diagram 1 of 7 in IDEF1X	424
Figure G.2 - ARM diagram 2 of 7 in IDEF1X	425
Figure G.3 - ARM diagram 3 of 7 in IDEF1X	426
Figure G.4 - ARM diagram 4 of 7 in IDEF1X	427
Figure G.5 - ARM diagram 5 of 7 in IDEF1X	428
Figure G.6 - ARM diagram 6 of 7 in IDEF1X	429
Figure G.7 - ARM diagram 7 of 7 in IDEF1X	430
Figure H.1 - application context - AIM EXPRESS-G diagram 1 of 39	432
Figure H.2 - product definition - AIM EXPRESS-G diagram 2 of 39	433
Figure H.3 - product category - AIM EXPRESS-G diagram 3 of 39	434
Figure H.4 - property definition - AIM EXPRESS-G diagram 4 of 39	435
Figure H.5 - property representation - AIM EXPRESS-G diagram 5 of 39	436
Figure H.6 - shape representation relationship - AIM EXPRESS-G diagram 6 of 39	437
Figure H.7 - representation - AIM EXPRESS-G diagram 7 of 39	438
Figure H.8 - geometric representation items - AIM EXPRESS-G diagram 8 of 39	439
Figure H.9 - topological representation items AIM EXPRESS-G diagram 9 of 39	440
Figure H.10 - point - AIM EXPRESS-G diagram 10 of 39	441
Figure H.11 - geometric orientation - AIM EXPRESS-G diagram 11 of 39	442
Figure H.12 - curve - AIM EXPRESS-G diagram 12 of 39	443
Figure H.13 - conic - AIM EXPRESS-G diagram 13 of 39	444
Figure H.14 - bounded curves - AIM EXPRESS-G diagram 14 of 39	445
Figure H.15 - surface curve - AIM EXPRESS-G diagram 15 of 39	446
Figure H.16 - b-spline curve - AIM EXPRESS-G diagram 16 of 39	447
Figure H.17 - surface - AIM EXPRESS-G diagram 17 of 39	448

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of the IEC and ISO maintain registers of currently valid International Standards.

ISO 31:1992, *Quantities and units*.

ISO 1000:1992, *SI units and recommendations for the use of their multiples and of certain other units*.

ISO/IEC 8824-1:1998, *Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation*.

ISO 10303-1:1994, *Industrial automation systems and integration - Product data representation and exchange - Part 1: Overview and fundamental principles*.

ISO 10303-11:1994, *Industrial automation systems and integration - Product data representation and exchange - Part 11: Description methods: The EXPRESS language reference manual*.

ISO 10303-21:1994, *Industrial automation systems and integration - Product data representation and exchange - Part 21: Clear text encoding of the exchange structure*.

ISO 10303-31:1994, *Industrial automation systems and integration - Product data representation and exchange - Part 31: Conformance testing methodology and framework: General concepts*.

ISO 10303-41:1994, *Industrial automation systems and integration - Product data representation and exchange - Part 41: Integrated generic resources: Fundamentals of product description and support*.

ISO 10303-42:1994, *Industrial automation systems and integration - Product data representation and exchange - Part 42: Integrated generic resources: Geometric and topological representation*.

ISO 10303-43:1994, *Industrial automation systems and integration - Product data representation and exchange - Part 43: Integrated generic resources: Representation structures*.

ISO 10303-44:1994, *Industrial automation systems and integration - Product data representation and exchange - Part 44: Integrated generic resources: Product structure configuration*.

ISO 10303-501, *Industrial automation systems and integration \ Product data representation and exchange \ Part 501: Application interpreted construct: Edge-based wireframe.*

ISO 10303-502, *Industrial automation systems and integration \ Product data representation and exchange \ Part 502: Application interpreted construct: Shell-based wireframe.*

ISO 10303-507, *Industrial automation systems and integration - Product data representation and exchange \ Part 507: Application interpreted construct: Geometrically bounded surface.*

ISO 10303-509, *Industrial automation systems and integration - Product data representation and exchange \ Part 509: Application interpreted construct: Manifold surface.*

ISO 10303-510, *Industrial automation systems and integration - Product data representation and exchange \ Part 510: Application interpreted construct: Geometrically bounded wireframe.*

ISO 10303-511, *Industrial automation systems and integration - Product data representation and exchange \ Part 511: Application interpreted construct: Topologically bounded surface.*

ISO 10303-512, *Industrial automation systems and integration - Product data representation and exchange \ Part 512: Application interpreted construct: Faceted boundary representation.*

ISO 10303-514, *Industrial automation systems and integration - Product data representation and exchange \ Part 514: Application interpreted construct: Advanced boundary representation.*

This Page Intentionally Left Blank

3 Definitions and abbreviations

For the purposes of this part of ISO 10303, the following definitions and abbreviations apply.

3.1 Terms defined in ISO 10303-1

This part of ISO 10303 makes use of the following terms defined in ISO 10303-1.

- abstract test suite;
- application;
- application activity model;
- application context;
- application interpreted model;
- application object;
- application protocol;
- application reference model;
- assembly;
- component;
- conformance class;
- conformance requirement;
- data;
- data exchange;
- implementation method;
- information;
- integrated resource;
- interpretation;

- 43) product_requires_product_category
- 44) product_requires_version
- 45) product_version_requires_approval
- 46) product_version_requires_person_organization
- 47) product_version_requires_security_classification
- 48) restrict_action_request_status
- 49) restrict_approval_status
- 50) restrict_certification_type
- 51) restrict_contract_type
- 52) restrict_date_time_role
- 53) restrict_document_type
- 54) restrict_person_organization_role
- 55) restrict_product_category_value
- 56) restrict_security_classification_level
- 57) security_classification_optional_date_time
- 58) security_classification_requires_approval
- 59) security_classification_requires_date_time
- 60) security_classification_requires_person_organization
- 61) start_request_requires_approval
- 62) start_request_requires_date_time
- 63) start_request_requires_person_organization
- 64) start_work_requires_approval
- 65) start_work_requires_date_time
- 66) subtype_mandatory_action
- 67) subtype_mandatory_effectivity
- 68) subtype_mandatory_product_context
- 69) subtype_mandatory_product_definition_formation
- 70) subtype_mandatory_product_definition_usage
- 71) subtype_mandatory_representation
- 72) subtype_mandatory_representation_context
- 73) subtype_mandatory_shape_representation
- 74) unique_version_change_order_rule
- 75) versioned_action_request_requires_solution
- 76) versioned_action_request_requires_status

5.2 AIM EXPRESS short listing

This clause specifies the EXPRESS schema that uses elements from the integrated resources and contains the types, entity specializations, rules, and functions that are specific to this part of ISO 10303. This clause also specifies modifications to the textual material for constructs that are imported from the integrated resources. The definitions and EXPRESS provided in the integrated resources for constructs used in the AIM may include select list items and subtypes which are not imported into the AIM. Requirements stated in the

integrated resources which refer to such items and subtypes apply exclusively to those items which are imported into the AIM.

EXPRESS specification:

*)

SCHEMA config_control_design;

USE FROM application_context_schema -- ISO 10303-41

(application_context,
application_protocol_definition,
product_context,
product_definition_context,
product_concept_context);

USE FROM product_definition_schema -- ISO 10303-41

(product,
product_definition,
product_definition_formation,
product_definition_formation_with_specified_source,
product_definition_relationship,
product_category,
product_category_relationship,
product_related_product_category,
product_definition_with_associated_documents);

USE FROM product_structure_schema -- ISO 10303-44

(product_definition_usage,
assembly_component_usage,
next_assembly_usage_occurrence,
promissory_usage_occurrence,
quantified_assembly_component_usage,
specified_higher_usage_occurrence,
assembly_component_usage_substitute,
alternate_product_relationship);

USE FROM configuration_management_schema -- ISO 10303-44

(configuration_item,
configuration_design,
configuration_effectivity);

```
USE FROM product_concept_schema -- ISO 10303-44
    (product_concept);

USE FROM product_property_definition_schema -- ISO 10303-41
    (product_definition_shape,
     property_definition,
     shape_aspect,
     shape_aspect_relationship);

USE FROM product_property_representation_schema -- ISO 10303-41
    (context_dependent_shape_representation,
     property_definition_representation,
     shape_representation,
     shape_representation_relationship,
     shape_definition_representation);

USE FROM representation_schema -- ISO 10303-43
    (functionally_defined_transformation,
     item_defined_transformation,
     global_uncertainty_assigned_context,
     mapped_item,
     representation,
     representation_context,
     parametric_representation_context,
     representation_item,
     representation_map,
     representation_relationship,
     representation_relationship_with_transformation,
     using_representations);

USE FROM geometry_schema -- ISO 10303-42
    (axis1_placement,
     axis2_placement_2d,
     axis2_placement_3d,
     b_spline_curve,
     b_spline_curve_with_knots,
     b_spline_surface,
     b_spline_surface_with_knots,
     bezier_curve,
     bezier_surface,
     boundary_curve,
     cartesian_point,
```

cartesian_transformation_operator_3d,
circle,
composite_curve,
composite_curve_on_surface,
composite_curve_segment,
conic,
conical_surface,
curve,
curve_bounded_surface,
curve_replica,
cylindrical_surface,
degenerate_pcurve,
degenerate_toroidal_surface,
dimension_count,
dimension_of,
direction,
ellipse,
evaluated_degenerate_pcurve,
geometric_representation_context,
geometric_representation_item,
hyperbola,
intersection_curve,
line,
offset_curve_3d,
offset_surface,
outer_boundary_curve,
parabola,
pcurve,
plane,
point,
point_on_curve,
point_on_surface,
point_replica,
polyline,
quasi_uniform_curve,
quasi_uniform_surface,
rational_b_spline_curve,
rational_b_spline_surface,
rectangular_composite_surface,
rectangular_trimmed_surface,
reparametrised_composite_curve_segment,
seam_curve,

```
spherical_surface,  
surface,  
surface_curve,  
surface_of_linear_extrusion,  
surface_of_revolution,  
surface_replica,  
swept_surface,  
toroidal_surface,  
trimmed_curve,  
uniform_curve,  
uniform_surface,  
vector);
```

```
USE FROM topology_schema -- ISO 10303-42
```

```
(closed_shell,  
connected_edge_set,  
connected_face_set,  
edge_curve,  
edge_loop,  
face_bound,  
face_outer_bound,  
face_surface,  
open_shell,  
oriented_closed_shell,  
oriented_face,  
path,  
poly_loop,  
topological_representation_item,  
vertex_loop,  
vertex_point,  
vertex_shell,  
wire_shell);
```

```
USE FROM geometric_model_schema -- ISO 10303-42
```

```
(brep_with_voids,  
edge_based_wireframe_model,  
faceted_brep,  
geometric_curve_set,  
geometric_set,  
manifold_solid_brep,  
shell_based_surface_model,  
shell_based_wireframe_model);
```

```
USE FROM action_schema -- ISO 10303-41
(action,
 action_method,
 action_request_solution,
 action_request_status,
 action_status,
 action_directive,
 directed_action,
 versioned_action_request);

USE FROM certification_schema -- ISO 10303-41
(certification,
 certification_type);

USE FROM approval_schema -- ISO 10303-41
(approval_date_time,
 approval_person_organization,
 approval,
 approval_status,
 approval_relationship);

USE FROM contract_schema -- ISO 10303-41
(contract,
 contract_type);

USE FROM security_classification_schema -- ISO 10303-41
(security_classification,
 security_classification_level);

USE FROM person_organization_schema -- ISO 10303-41
(person_and_organization,
 organization_relationship,
 personal_address,
 organizational_address,
 organizational_project,
 person_and_organization_role);

USE FROM date_time_schema -- ISO 10303-41
(date_and_time,
 date,
 calendar_date,
 ordinal_date,
```

```
week_of_year_and_day_date,  
date_time_role);
```

```
USE FROM document_schema -- ISO 10303-41  
(document_with_class,  
document_usage_constraint,  
document_type,  
document_relationship);
```

```
USE FROM effectivity_schema -- ISO 10303-41  
(effectivity,  
serial_numbered_effectivity,  
dated_effectivity,  
lot_effectivity);
```

```
USE FROM management_resources_schema -- ISO 10303-41  
(approval_assignment,  
certification_assignment,  
contract_assignment,  
date_and_time_assignment,  
person_and_organization_assignment,  
document_reference,  
security_classification_assignment,  
action_assignment,  
action_request_assignment);
```

```
USE FROM measure_schema -- ISO 10303-41  
(measure_value,  
area_measure,  
count_measure,  
descriptive_measure,  
context_dependent_measure,  
parameter_value,  
plane_angle_measure,  
positive_length_measure,  
positive_plane_angle_measure,  
mass_measure,  
solid_angle_measure,  
volume_measure,  
named_unit,  
context_dependent_unit,  
conversion_based_unit,
```

```

    si_unit,
    area_unit,
    length_unit,
    mass_unit,
    plane_angle_unit,
    solid_angle_unit,
    volume_unit,
    measure_with_unit,
    area_measure_with_unit,
    length_measure_with_unit,
    mass_measure_with_unit,
    plane_angle_measure_with_unit,
    solid_angle_measure_with_unit,
    volume_measure_with_unit,
    global_unit_assigned_context);

USE FROM aic_edge_based_wireframe;    -- ISO 10303-501

USE FROM aic_shell_based_wireframe;    -- ISO 10303-502

USE FROM aic_geometrically_bounded_surface;    -- ISO 10303-507

USE FROM aic_manifold_surface;    -- ISO 10303-509

USE FROM aic_geometrically_bounded_wireframe;    -- ISO 10303-510

USE FROM aic_topologically_bounded_surface;    -- ISO 10303-511

USE FROM aic_faceted_brep;    -- ISO 10303-512

USE FROM aic_advanced_brep;    -- ISO 10303-514
(*)

```

NOTE - The schemas referenced above can be found in the following parts of ISO 10303:

application_context_schema	ISO 10303-41
product_definition_schema	ISO 10303-41
product_structure_schema	ISO 10303-44
configuration_management_schema	ISO 10303-44
product_concept_schema	ISO 10303-44
product_property_definition_schema	ISO 10303-41
product_property_representation_schema	ISO 10303-41

representation_schema	ISO 10303-43
geometry_schema	ISO 10303-42
geometric_model_schema	ISO 10303-42
action_schema	ISO 10303-41
certification_schema	ISO 10303-41
approval_schema	ISO 10303-41
contract_schema	ISO 10303-41
security_classification_schema	ISO 10303-41
person_organization_schema	ISO 10303-41
date_time_schema	ISO 10303-41
document_schema	ISO 10303-41
effectivity_schema	ISO 10303-41
management_resources_schema	ISO 10303-41
measure_schema	ISO 10303-41
aic_edge_based_wireframe	ISO 10303-504
aic_shell_based_wireframe	ISO 10303-502
aic_geometrically_bounded_surface	ISO 10303-507
aic_manifold_surface	ISO 10303-509
aic_geometrically_bounded_wireframe	ISO 10303-510
aic_topologically_bounded_surface	ISO 10303-511
aic_faceted_brep	ISO 10303-512
aic_advanced_brep	ISO 10303-514

5.2.1 Fundamental concepts and assumptions

ISO 10303-203 is designed to be used in the configuration control of three dimensional product design data. The fundamental concept of this schema is that the organization controls the configuration of these types of product designs. This schema is not designed to control product designs through drawing control. It is designed to provide a vehicle to control the configuration of the three dimensional design.

5.2.1.1 Relating the shape of a product to its configuration data

The shape of products in this part of ISO 10303 is represented by the **shape_representation** entity. This entity and its subtypes define the geometric and/or topological entities which make up a particular representation type. Each mechanical part or assembly that is of interest will be given by an instance of the **product** entity. Each product will, in turn, have at least one version given by an instance of the **product_definition** entity. Each version may have one or more definitions given by the **product_definition** entity. Each definition may have its shape represented. This is done using the AIM entities by relating the **product_definition** instance to the appropriate **shape_representation** instance. The concept of the shape of a **product_definition** is given by an instance of the entity **product_definition_shape**. That shape of the product is then connected to the **shape_representation** entity by an instance of **shape_definition_representation**. A **shape_definition_representation** inherits attributes from its supertype

property_definition_representation that reference the **shape_representation** entity that contains the geometry and/or topology for the shape of the part and a select type called **characterized_definition**. This type allows for the representation of a **shape_aspect**, **shape_aspect_relationship** or a **characterized_product_definition** which is also a select type. To specify that the property of interest is the shape of the **product_definition**, the **product_definition_shape** subtype of **property_definition** shall be used. The **product_definition_shape** entity is constrained to use the **characterized_product_definition** select type. The **characterized_product_definition** select type allows for the representation of a **product_definition** or a **product_definition_relationship** via a reference through its select list. This reference ensures that the **product_definition_shape** entity will be used to define the shape of a **product_definition**. If the property of interest is an aspect of the shape of the **product_definition** or the relationship between two aspects of the shape of the **product_definition**, the **property_definition** shall be used and its **definition** attribute shall reference an instance of **shape_aspect** or **shape_aspect_relationship**. In order to specify the shape of a product, the **product_definition** entity will be referenced here. The constraint **subtype_mandatory_shape_representation** (see 5.2.5.73) specifies that one of the subtypes of **shape_representation** shall be used to specify the shape of the part. The representation of a **shape_aspect** or **shape_aspect_relationship** may be given by any set of **representation_items**.

5.2.1.2 Relating the shape of a component to the shape of its assembly

There are two methods that may be used to relate a component part's shape to the shape of the assembly part in which it is assembled. The first method consists of defining the shape for each part (component and assembly), and then relating the two shapes and providing the information that defines the orientation of the component part with respect to the assembly part through a transformation. The second method consists of defining the shape for each part (component and assembly), and then incorporating the shape of the component directly in the shape of the assembly. The first method shall be used to relate the shapes that are represented by different representation types. The second method may be used for the incorporation of a components representation into the assembly's representation if the two types are the same.

Both methods employ the **shape_representation** and **product_definition** entities. The first method also employs the **product_definition_relationship**, **shape_representation_relationship** AND **representation_relationship_with_transformation** (an instance of each entity forming a complex entity instance of the two entities with an AND relationship) and **context_dependent_shape_representation** entities. The second method employs the **mapped_item** and **representation_map** entities.

When using the first method to relate the shape of the component to the shape of the assembly, each of the **shape_representation** entities that define the shapes of the component and assembly **product_definitions** is related through references in the **shape_representation_relationship** entity. Orientation information, in this case, will be provided by the formation of a complex instance of the **shape_representation_relationship** AND **representation_relationship_with_transformation** entities. The **representation_relationship_with_transformation** entity references a **transformation** which is a select type allowing the orientation to be defined using an **axis2_placement_3d** entity in each representation for an **item_defined_transformation** or a **cartesian_transformation_operator** entity for a **functionally_defined_transformation**. In addition,

an instance of the **context_dependent_shape_representation** must be given to explicitly relate the **shape_representation_relationship** that defines the relationship of the two shapes to the **product_definition_relationship** that defines the assembly-component relationship between the two **product_definitions**.

When using the second method to relate the shape of the component to the shape of the assembly, the **shape_representation** entity that defines the geometry and/or topology for the component part's shape is referenced by an instance of a **representation_map** entity that is referenced by the **mapping_source** attribute of an instance of the **mapped_item** entity. The attribute **mapped_representation** of the **representation_map** will reference the **shape_representation** subtype that defines the geometric and/or topological representation of the shape. The instance of the **mapped_item** entity is then added to the set of **items** in the **shape_representation** entity that defines the geometry and/or topology for the assembly part.

5.2.1.3 Types of shape representation

This part of ISO 10303 defines eight types of representation for shapes of parts - wireframe representations using edge based and shell based models, wireframe representations that are geometrically bounded, manifold surface models, surface models that are geometrically bounded, faceted boundary representation solid models and boundary representation solid models. Each of these types of representation is self contained meaning that one type may not contain another type. Each of the types is given by a subtype of the **shape_representation** entity. Each subtype contains local rules that govern the types of geometric and/or topological entities that can be used in it. Every **shape_representation** must be one of the subtypes unless it is used as the representation of the shape of an assembly used in method 1 above. In that case, the **shape_representation** instance will contain only **axis2_placement_3d** entities in its set of **items** in order to define the orientation of the components' representations in it. Since the rules in each of the subtypes will conflict with each other, any **shape_representation** that is referenced by a **representation_map** to implement method 2 above must be of the same type as the **shape_representation** that has the **mapped_item** that references that **representation_map** in its set of **items**.

5.2.1.4 Use of global rules

Many of the relationships among different entities in the integrated resource parts of ISO 10303 are specified using the most generic cardinality of zero or more between two related entities. This cardinality means that the relationship is optional or there may be one or more instances of a related entity that is related to a single instance of the relating entity. This part of ISO 10303 uses global rules to constrain that cardinality. In some cases the constraint is made to be one to one, and in some instances at least one. Examples of these rules include **contract_requires_person_organization**, **approval_requires_approval_date_time**, and **certification_requires_approval** for exactly one, and **change_request_requires_person_organization** and **product_requires_version** for one or more.

Global rules are also used to restrict the values of STRING type attributes to be only those that are applicable within the context of configuration controlled 3d design of mechanical parts and assemblies. Examples of these rules are **restrict_approval_status** and **restrict_person_organization_role**.

5.2.1.5 Assignment of units

Units are assigned to the representation of shape on a global basis. This is done by the creation of an instance of the **global_unit_assigned_context**. This entity contains an attribute that allows for a set of units to be assigned to a **representation_context**. Each of the **shape_representation** entities has a context for its representation. If units of measure are desired for a particular instance of **shape_representation**, then that instance shall have a **global_unit_assigned_context** in its **context_of_items** attribute.

5.2.2 Configuration controlled design constants

EXPRESS specification:

```
*)
CONSTANT
( *
```

5.2.2.1 dummy_gri

A **dummy_gri** identifies a **geometric_representation_item** which has a null **name** value for use in constructor functions.

EXPRESS specification:

```
*)
  dummy_gri : geometric_representation_item := representation_item('') ||
    geometric_representation_item();
( *
```

5.2.2.2 dummy_tri

A **dummy_tri** identifies a **topological_representation_item** which has a null **name** value for use in constructor functions.

EXPRESS specification:

```
*)
  dummy_tri : topological_representation_item := representation_item('') ||
    topological_representation_item();
END_CONSTANT;
( *
```

5.2.3 Configuration controlled design types

5.2.3.1 work_item

A **work_item** identifies the **product_definition_formation** that is the result of initial design activity or a modification to a design.

EXPRESS specification:

```
*)  
TYPE work_item = SELECT (product_definition_formation);  
END_TYPE;  
(*
```

5.2.3.2 change_request_item

A **change_request_item** is the **product_definition_formation** of the part that is to be affected by the **change_request**.

EXPRESS specification:

```
*)  
TYPE change_request_item = SELECT (product_definition_formation);  
END_TYPE;  
(*
```

5.2.3.3 start_request_item

A **start_request_item** is the **product_definition_formation** of the part that is to be created by the **start_request**.

EXPRESS specification:

```
*)  
TYPE start_request_item = SELECT (product_definition_formation);  
END_TYPE;  
(*
```

5.2.3.4 certified_item

A **certified_item** applies a **certification** to a part that is supplied by an external organization. The **certification** stipulates that the external organization is qualified to produce the part.

EXPRESS specification:

```

*)
TYPE certified_item = SELECT (supplied_part_relationship);
END_TYPE;
( *

```

5.2.3.5 approved_item

An **approved_item** assigns an **approval** to a **product_definition_formation**, **product_definition**, **planned_effectivity**, **configuration_item**, **security_classification**, **change_request**, **change**, **start_request**, **start_work**, **certification**, or **contract** to indicate the approval status of the selected aspect of the design.

EXPRESS specification:

```

*)
TYPE approved_item = SELECT
  (product_definition_formation,
   product_definition,
   configuration_effectivity,
   configuration_item,
   security_classification,
   change_request,
   change,
   start_request,
   start_work,
   certification,
   contract);
END_TYPE;
( *

```

5.2.3.6 contracted_item

A **contracted_item** associates a particular **product_definition_formation** with a **contract**.

EXPRESS specification:

```

*)
TYPE contracted_item = SELECT (product_definition_formation);
END_TYPE;
( *

```

5.2.3.7 classified_item

A **classified_item** applies **security_classification** to a particular **product_definition_formation** or a relationship between two **product_definitions** for a particular usage.

EXPRESS specification:

```

*)
TYPE classified_item = SELECT
    (product_definition_formation,
     assembly_component_usage);
END_TYPE;
( *

```

5.2.3.8 person_organization_item

A **person_organization_item** assigns a **person_and_organization** to a **change_request**, **start_request**, **approval**, **configuration_item**, **product**, **product_definition_formation**, **product_definition**, **contract**, or **security_classification**. The role for the **person_and_organization** is controlled by the **cc_design_person_and_organization_correlation** function given in 5.2.6.2.

EXPRESS specification:

```

*)
TYPE person_organization_item = SELECT
    (change,
     start_work,
     change_request,
     start_request,
     configuration_item,
     product,
     product_definition_formation,
     product_definition,
     contract,
     security_classification);

```

```
END_TYPE;
```

```
(*
```

5.2.3.9 date_time_item

A **date_time_item** assigns a **date_and_time** to a **product_definition**, **change_request**, **start_request**, **change**, **start_work**, **approval_person_organization**, **contract**, **security_classification**, or **certification**. The role for the **date_and_time** is controlled by the **cc_design_date_time_correlation** function given in 5.2.6.3.

EXPRESS specification:

```
*)
```

```
TYPE date_time_item = SELECT
  (product_definition,
   change_request,
   start_request,
   change,
   start_work,
   approval_person_organization,
   contract,
   security_classification,
   certification);
```

```
END_TYPE;
```

```
(*
```

5.2.3.10 specified_item

A **specified_item** assigns a **specification** to either a **product_definition** or a **shape_aspect**.

EXPRESS specification:

```
*)
```

```
TYPE specified_item = SELECT
  (product_definition,
   shape_aspect);
```

```
END_TYPE;
```

```
(*
```

5.2.4 Configuration controlled design entities

5.2.4.1 Configuration controlled design entity definitions

5.2.4.1.1 mechanical_context

A **mechanical_context** is a **product_context** that is applicable to those products that are mechanical.

NOTE - The use of this entity defines a viewpoint for the context of a product. It is not intended to be a classification or categorization of a type of product. The definition of the **product_context** to be mechanical using this entity is specifying the way that the product acts within the data exchange.

EXAMPLE 21 - A printed circuit assembly is defined in a mechanical context when its physical properties such as shape are of interest, and are defined so that its fit within the assembly in which it used may be specified. Other properties of the printed circuit assembly such as connectivity requirements and functional requirements would not be specified in a mechanical context.

EXPRESS specification:

```
*)
ENTITY mechanical_context
  SUBTYPE OF (product_context);
WHERE
  WR1: SELF.discipline_type = 'mechanical';
END_ENTITY;
(*
```

Formal propositions:

WR1: the **discipline_type** of the **mechanical_context** entity shall contain the value 'mechanical'.

5.2.4.1.2 design_context

A **design_context** is a **product_definition_context** that defines a life cycle stage of design as the frame of reference for **product_definition** entities.

NOTE - A further refinement within the context of design may be made using the **application_context_element** entity.

EXPRESS specification:

```

*)
ENTITY design_context
  SUBTYPE OF (product_definition_context);
WHERE
  WR1: SELF.life_cycle_stage = 'design';
END_ENTITY;
( *

```

Formal propositions:

WR1: the **life_cycle_stage** of the **design_context** entity shall contain the value 'design'.

5.2.4.1.3 design_make_from_relationship

A **design_make_from_relationship** specifies that one **product**'s design has been derived from another **product**'s design. The use of the **design_make_from_relationship** also implies that the physical product resulting from the manufacture of the **relating_product_definition** is to be used as the basis for the manufacture of the **related_product_definition**.

EXPRESS specification:

```

*)
ENTITY design_make_from_relationship
  SUBTYPE OF (product_definition_relationship);
END_ENTITY;
( *

```

Attribute definitions:

SELF\product_definition_relationship.relying_product_definition: the **product_definition** that is the source for the make from relationship.

SELF\product_definition_relationship.related_product_definition: the **product_definition** entity that is created from the source **product_definition**.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **design_make_from_relationship** entity:

— no_shape_for_make_from (See 5.2.5.76).

5.2.4.1.4 supplied_part_relationship

A **supplied_part_relationship** relates the identifications of two **products** and specifies that one is the identification used by the internal design organization and the other is the identification used by a supplier.

EXPRESS specification:

```
*)
ENTITY supplied_part_relationship
  SUBTYPE OF (product_definition_relationship);
END_ENTITY;
( *
```

Attribute definitions:

SELF\product_definition_relationship.relying_product_definition: the **product_definition** that is the design organization's definition and identification of the **product**.

SELF\product_definition_relationship.related_product_definition: the **product_definition** that is definition and identification of the product for the organization which supplies the part or design to the design organization.

Informal propositions:

IP1: The shapes for design organization's definition and the supplying organization's definition shall be equal with respect to form, fit and function.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **supplied_part_relationship** entity:

— no_shape_for_supplied_part (See 5.2.5.77).

5.2.4.1.5 change_request

A **change_request** is a formal notification of a desire for a modification to a particular piece of product data.

EXPRESS specification:

```

*)
ENTITY change_request
  SUBTYPE OF (action_request_assignment);
  items : SET [1:?] OF change_request_item;
END_ENTITY;
( *

```

Attribute definitions:

items: a set of **change_request_items** which identify versions of particular **products** to be changed.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **change_request** entity:

- change_request_requires_approval (See 5.2.5.6);
- change_request_requires_person_organization (See 5.2.5.7);
- change_request_requires_date_time (See 5.2.5.8).

5.2.4.1.6 start_request

A **start_request** is a formal notification of a desire to begin a new design for a **product** or group of **products**.

EXPRESS specification:

```

*)
ENTITY start_request
  SUBTYPE OF (action_request_assignment);
  items : SET [1:?] OF start_request_item;
END_ENTITY;
( *

```

Attribute definitions:

items: a set of **start_request_items** which identify the versions of particular **products**.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **start_request** entity:

- start_request_requires_approval (See 5.2.5.11);
- start_request_requires_person_organization (See 5.2.5.12);
- start_request_requires_date_time (See 5.2.5.13).

5.2.4.1.7 change

A **change** identifies the **change_requests** that have been incorporated into the design and, as a result, have established a new version of the **product**.

EXPRESS specification:

```

*)
ENTITY change
  SUBTYPE OF (action_assignment);
  items : SET [1:?] OF work_item;
END_ENTITY;
( *
```

Attribute definitions:

items: a set of **work_items** which identify versions of particular **products** which were created as a result of the incorporation of the **change**.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **change** entity:

- change_requires_approval (See 5.2.5.9);
- change_requires_date_time (See 5.2.5.10);
- unique_version_change_order_rule (See 5.2.5.19).

5.2.4.1.8 start_work

A **start work** identifies the **start_requests** that have been fulfilled and, as a result, have established a new

version of a **product**.

EXPRESS specification:

```
*)
ENTITY start_work
  SUBTYPE OF (action_assignment);
  items : SET [1:?] OF work_item;
END_ENTITY;
(*
```

Attribute definitions:

items: a set of **work_items** which identify versions of **products** that are to be created as a result of the start of the **work**.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **start_work** entity:

- start_work_requires_approval (See 5.2.5.14);
- start_work_requires_date_time (See 5.2.5.15).

5.2.4.1.9 cc_design_certification

A **cc_design_certification** assigns a **certification** to a **product** that is supplied by an external organization.

EXPRESS specification:

```
*)
ENTITY cc_design_certification
  SUBTYPE OF (certification_assignment);
  items : SET [1:?] OF certified_item;
END_ENTITY;
(*
```

Attribute definitions:

items: a set of **certified_items** which identify **supplied_part_relationship** entities to which the **certification** is being assigned.

5.2.4.1.10 cc_design_approval

A **cc_design_approval** relates an **approval** to a particular piece of product data.

EXPRESS specification:

```
* )  
ENTITY cc_design_approval  
  SUBTYPE OF (approval_assignment);  
  items : SET [1:?] OF approved_item;  
END_ENTITY;  
( *
```

Attribute definitions:

items: a set of **approved_items** which identify the particular **product_definition_formation**, **product_definition**, **planned_effectivity**, **configuration_item**, **security_classification**, **change_request**, **change**, **start_request**, **start_work**, **certification**, or **contract** to which the **approval** applies.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **cc_design_approval** entity:

- change_request_requires_approval (See 5.2.5.6);
- change_requires_approval (See 5.2.5.9);
- start_request_requires_approval (See 5.2.5.11);
- start_work_requires_approval (See 5.2.5.14);
- product_version_requires_approval (See 5.2.5.22);
- product_definition_requires_approval (See 5.2.5.26);
- certification_requires_approval (See 5.2.5.28);
- contract_requires_approval (See 5.2.5.35);
- security_classification_requires_approval (See 5.2.5.38);

— effectivity_requires_approval (See 5.2.5.66);

— configuration_item_requires_approval (See 5.2.5.67).

5.2.4.1.11 cc_design_contract

A **cc_design_contract** relates a **contract** to a **product_definition_formation**.

EXPRESS specification:

```
*)
ENTITY cc_design_contract
  SUBTYPE OF (contract_assignment);
  items : SET [1:?] OF contracted_item;
END_ENTITY;
(*
```

Attribute definitions:

items: a set of **contracted_items** which identify the versions of particular **products** to which the **contract** is assigned.

5.2.4.1.12 cc_design_security_classification

A **cc_design_security_classification** relates a **security_classification** to a particular piece of product data.

EXPRESS specification:

```
*)
ENTITY cc_design_security_classification
  SUBTYPE OF (security_classification_assignment);
  items : SET [1:?] OF classified_item;
END_ENTITY;
(*
```

Attribute definitions:

items: a set of **classified_items** which identify the versions or definition relationships of particular **products** to which the **security_classification** is assigned.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **cc_design_security_classification** entity:

- **product_version_requires_security_classification** (See 5.2.5.24);
- **pdu_requires_security_classification** (See 5.2.5.70).

5.2.4.1.13 cc_design_person_and_organization_assignment

A **cc_design_person_and_organization_assignment** relates a **person_and_organization** to a particular piece of product data.

EXPRESS specification:

```

*)
ENTITY cc_design_person_and_organization_assignment
  SUBTYPE OF (person_and_organization_assignment);
  items : SET [1:?] OF person_organization_item;
WHERE
  WR1: cc_design_person_and_organization_correlation (SELF);
END_ENTITY;
( *

```

Attribute definitions:

items: a set of **person_organization_items** which identify the **change_request**, **start_request**, **configuration_item**, **product**, **product_definition_formation**, **contract**, or **security_classification** to which the **person_and_organization** is related.

Formal propositions:

WR1: The **cc_design_person_and_organization_correlation** function that correlates roles of persons and organizations to elements of product data shall be satisfied. See 5.2.6.2 for the complete definition of the **cc_design_person_and_organization_correlation** function.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **cc_design_person_and_organization_assignment** entity:

- change_request_requires_person_organization (See 5.2.5.7);
- start_request_requires_person_organization (See 5.2.5.12);
- product_requires_person_organization (See 5.2.5.21);
- product_version_requires_person_organization (See 5.2.5.23);
- product_definition_requires_person_organization (See 5.2.5.25);
- contract_requires_person_organization (See 5.2.5.36);
- security_classification_requires_person_organization (See 5.2.5.39);
- configuration_item_requires_person_organization (See 5.2.5.64);

5.2.4.1.14 cc_design_date_and_time_assignment

A **cc_design_date_and_time_assignment** relates a **date_and_time_assignment** to a particular piece of product data.

EXPRESS specification:

```

*)
ENTITY cc_design_date_and_time_assignment
  SUBTYPE OF (date_and_time_assignment);
  items : SET [1:?] OF date_time_item;
WHERE
  WR1: cc_design_date_time_correlation (SELF);
END_ENTITY;
( *
```

Attribute definitions:

items: a set of **date_time_items** which identify the particular **product_definition**, **change_request**, **start_request**, **change**, **start_work**, **contract**, **security_classification**, **change**, **certification** or **approval_person_and_organization** to which the date and time is assigned.

Formal propositions:

WR1: The **cc_design_date_time_correlation** function which correlates roles of dates and times to elements of product data shall be satisfied. See 5.2.6.3 the complete definition of the **cc_design_date_time_correlation** function.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **cc_design_date_and_time_assignment** entity:

- change_request_requires_date_time (See 5.2.5.8);
- change_requires_date_time (See 5.2.5.10);
- start_request_requires_date_time (See 5.2.5.13);
- start_work_requires_date_time (See 5.2.5.15);
- product_definition_requires_date_time (See 5.2.5.27);
- certification_requires_date_time (See 5.2.5.30);
- security_classification_requires_date_time (See 5.2.5.40);
- security_classification_optional_date_time (See 5.2.5.41).

5.2.4.1.15 cc_design_specification_reference

A **cc_design_specification_reference** relates a reference to a specification to a complete definition of a product or to some aspect of its shape.

EXPRESS specification:

```

*)
ENTITY cc_design_specification_reference
  SUBTYPE OF (document_reference);
  items : SET [1:?] OF specified_item;
END_ENTITY;
( *
```

Attribute definitions:

items: a set of **product_definitions** and / or **shape_aspects** to which the **specification_reference** applies.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **cc_design_specification_reference** entity:

— document_to_product_definition (See 5.2.5.46).

5.2.4.2 Configuration controlled design imported entity modifications

5.2.4.2.1 application_context

The base definition of the **application_context** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **application_context** entity:

— application_context_requires_ap_definition (See 5.2.5.1).

5.2.4.2.2 application_protocol_definition

The base definition of the **application_protocol_definition** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **application_protocol_definition** entity:

— application_context_requires_ap_definition (See 5.2.5.1).

5.2.4.2.3 product_context

The base definition of the **product_context** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **product_context** entity:

— subtype_mandatory_product_context (See 5.2.5.2).

5.2.4.2.4 product_definition_context

The base definition of the **product_definition_context** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

The definition of **product_definition_context** is modified as follows:

The **application_context_element** attribute **name** shall be used to modify the **product_definition_context** in order to specify the exact context within design to which the **product_definition** is applicable.

5.2.4.2.5 product_category

The base definition of the **product_category** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

The definition of **product_category** is modified as follows:

In this part of ISO 10303, **product_category** trees are utilized to categorize parts. An intermediate node in the tree may be used to segregate standard parts from non-standard parts. In this case, the **name** attribute for the **product_category** shall be "standard_part".

5.2.4.2.6 product_related_product_category

The base definition of the **product_related_product_category** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **product_related_product_category** entity:

— restrict_product_category_value (See 5.2.5.4);

— product_requires_product_category (See 5.2.5.5).

5.2.4.2.7 product

The base definition of the **product** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **product** entity:

- product_requires_product_category (See 5.2.5.5);
- product_requires_version (See 5.2.5.20);
- product_requires_person_organization (See 5.2.5.21).

5.2.4.2.8 product_definition_formation

The base definition of the **product_definition_formation** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **product_definition_formation** entity:

- product_requires_version (See 5.2.5.20);
- product_version_requires_approval (See 5.2.5.22);
- product_version_requires_person_organization (See 5.2.5.23);
- product_version_requires_security_classification (See 5.2.5.24);
- subtype_mandatory_product_definition_formation (See 5.2.5.50).

5.2.4.2.9 product_definition

The base definition of the **product_definition** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **product_definition** entity:

- design_context_for_property (See 5.2.5.3);
- product_definition_requires_person_organization (See 5.2.5.25);
- product_definition_requires_approval (See 5.2.5.26);
- product_definition_requires_date_time (See 5.2.5.27);
- document_to_product_definition (See 5.2.5.46).

5.2.4.2.10 action_request_status

The base definition of the **action_request_status** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **action_request_status** entity:

- restrict_action_request_status (See 5.2.5.16);
- versioned_action_request_requires_status (See 5.2.5.17).

5.2.4.2.11 versioned_action_request

The base definition of the **versioned_action_request** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **versioned_action_request** entity:

- versioned_action_request_requires_status (See 5.2.5.17);
- versioned_action_request_requires_solution (See 5.2.5.18).

5.2.4.2.12 action_request_solution

The base definition of the **action_request_solution** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **action_request_solution** entity:

- versioned_action_request_requires_solution (See 5.2.5.18).

5.2.4.2.13 certification_type

The base definition of the **certification_type** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **certification_type** entity:

- restrict_certification_type (See 5.2.5.29);
- dependent_instantiable_certification_type (See 5.2.5.62).

5.2.4.2.14 certification

The base definition of the **certification** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **certification** entity:

- certification_requires_approval (See 5.2.5.28);
- certification_requires_date_time (See 5.2.5.30).

5.2.4.2.15 approval_status

The base definition of the **approval_status** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **approval_status** entity:

- restrict_approval_status (See 5.2.5.34);
- dependent_instantiable_approval_status (See 5.2.5.59).

5.2.4.2.16 approval

The base definition of the **approval** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **approval** entity:

- approvals_are_assigned (See 5.2.5.31);
- approval_requires_approval_person_organization (See 5.2.5.32);
- approval_requires_approval_date_time (See 5.2.5.33).

5.2.4.2.17 approval_assignment

The base definition of the **approval_assignment** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **approval_assignment** entity:

- approvals_are_assigned (See 5.2.5.31).

5.2.4.2.18 approval_person_organization

The base definition of the **approval_person_organization** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rules defined in this part of ISO 10303 apply to the **approval_person_organization** entity:

- approval_person_organization_constraints (See 5.2.5.79);
- approval_requires_approval_person_organization (See 5.2.5.32).

5.2.4.2.19 approval_date_time

The base definition of the **approval_date_time** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rules defined in this part of ISO 10303 apply to the **approval_date_time** entity:

- approval_date_time_constraints (See 5.2.5.78);
- approval_requires_approval_date_time (See 5.2.5.33).

5.2.4.2.20 contract_type

The base definition of the **contract_type** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **contract_type** entity:

- restrict_contract_type (See 5.2.5.37);
- dependent_instantiable_contract_type (See 5.2.5.61).

5.2.4.2.21 contract

The base definition of the **contract** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **contract** entity:

- contract_requires_approval (See 5.2.5.35);
- contract_requires_person_organization (See 5.2.5.36).

5.2.4.2.22 security_classification_level

The base definition of the **security_classification_level** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **security_classification_level** entity:

- restrict_security_classification_level (See 5.2.5.42);
- dependent_instantiable_security_classification_level (See 5.2.5.58).

5.2.4.2.23 security_classification

The base definition of the **security_classification** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **security_classification** entity:

- security_classification_requires_approval (See 5.2.5.38);
- security_classification_requires_person_organization (See 5.2.5.39);
- security_classification_requires_date_time (See 5.2.5.40);
- security_classification_optional_date_time (See 5.2.5.41).

5.2.4.2.24 **person_and_organization_role**

The base definition of the **person_and_organization_role** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **person_and_organization_role** entity:

- restrict_person_organization_role (See 5.2.5.43);
- dependent_instantiable_person_and_organization_role (See 5.2.5.56).

5.2.4.2.25 **person**

The base definition of the **person** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Attribute definitions:

The attribute definitions are modified as follows:

id: a means by which the **person** may be identified.

NOTE - The uniqueness of this attribute must be maintained and guaranteed over the entire domain of the data. With a single organization, country or team, this constraint may be easy to satisfy. In situations where global or universal uniqueness is required, the reader is referred to ISO/IEC 8824-1 for guidance on registration of strings for international application uniqueness.

5.2.4.2.26 **date_time_role**

The base definition of the **date_time_role** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **date_time_role** entity:

- restrict_date_time_role (See 5.2.5.44);
- dependent_instantiable_date_time_role (See 5.2.5.55).

5.2.4.2.27 document_type

The base definition of the **document_type** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **document_type** entity:

- restrict_document_type (See 5.2.5.45);
- dependent_instantiable_document_type (See 5.2.5.60).

5.2.4.2.28 measure_with_unit

The base definition of the **measure_with_unit** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **measure_with_unit** entity:

- as_required_quantity (See 5.2.5.47).

5.2.4.2.29 global_unit_assigned_context

The base definition of the **global_unit_assigned_context** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **global_unit_assigned_context** entity:

- global_unit_assignment (See 5.2.5.48).

5.2.4.2.30 action

The base definition of the **action** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **action** entity:

- subtype_mandatory_action (See 5.2.5.49).

5.2.4.2.31 action_directive

The base definition of the **action_directive** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **action_directive** entity:

- dependent_instantiable_action_directive (See 5.2.5.57).

5.2.4.2.32 date

The base definition of the **date** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **date** entity:

- dependent_instantiable_date (See 5.2.5.51).

5.2.4.2.33 representation

The base definition of the **representation** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **representation** entity:

- subtype_mandatory_representation (See 5.2.5.74).

5.2.4.2.34 representation_context

The base definition of the **representation_context** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **representation_context** entity:

— subtype_mandatory_representation_context (See 5.2.5.75).

5.2.4.2.35 shape_representation

The base definition of the **shape_representation** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **shape_representation** entity:

— dependent_instantiable_shape_representation (See 5.2.5.52);

— subtype_mandatory_shape_representation (See 5.2.5.73).

5.2.4.2.36 context_dependent_shape_representation

The base definition of the **context_dependent_shape_representation** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

The definition of **context_dependent_shape_representation** is modified as follows:

In this part of ISO 10303, **context_dependent_shape_representation** shall be used to relate the **next_assembly_usage_occurrence** defining the usage of a component in an assembly to the **shape_representation_relationship** which defines the position and orientation of the component's shape in the shape definition of the assembly.

NOTE - **Context_dependent_shape_representation** may be used to relate shapes of components and assemblies regardless of what type of **shape_representation** is used for each. The **mapped_item** construct may also be used to relate the shapes of components and assemblies, but the use of **mapped_item**, in this part of ISO 10303, requires that the **shape_representation** types be the same.

5.2.4.2.37 **named_unit**

The base definition of the **named_unit** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **named_unit** entity:

— dependent_instantiable_named_unit (See 5.2.5.53).

5.2.4.2.38 **representation_item**

The base definition of the **representation_item** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **representation_item** entity:

— dependent_instantiable_representation_item (See 5.2.5.54).

5.2.4.2.39 **product_definition_usage**

The base definition of the **product_definition_usage** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **product_definition_usage** entity:

— subtype_mandatory_product_definition_usage (See 5.2.5.69).

5.2.4.2.40 **geometric_representation_item**

The base definition of the **geometric_representation_item** entity is given in ISO 10303-42. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **geometric_representation_item** entity:

- **geometric_representation_item_3d** (See 5.2.5.71).

5.2.4.2.41 **parametric_representation_context**

The base definition of the **parametric_representation_context** entity is given in ISO 10303-43. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **parametric_representation_context** entity:

- **dependent_instantiable_parametric_representation_context** (See 5.2.5.72).

5.2.4.2.42 **product_concept**

The base definition of the **product_concept** entity is given in ISO 10303-44. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **product_concept** entity:

- **product_concept_requires_configuration_item** (See 5.2.5.63).

5.2.4.2.43 **configuration_item**

The base definition of the **configuration_item** entity is given in ISO 10303-44. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **configuration_item** entity:

- **product_concept_requires_configuration_item** (See 5.2.5.63);

— configuration_item_requires_person_organization (See 5.2.5.64);

— configuration_item_requires_approval (See 5.2.5.67);

5.2.4.2.44 effectivity

The base definition of the **effectivity** entity is given in ISO 10303-41. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **effectivity** entity:

— subtype_mandatory_effectivity (See 5.2.5.65);

— effectivity_requires_approval (See 5.2.5.66).

5.2.4.2.45 next_assembly_usage_occurrence

The base definition of the **next_assembly_usage_occurrence** entity is given in ISO 10303-44. The following modifications apply to this part of ISO 10303.

Associated global rule:

The following global rule defined in this part of ISO 10303 applies to the **next_assembly_usage_occurrence** entity:

— coordinated_assembly_and_shape (See 5.2.5.68).

5.2.4.2.46 assembly_component_usage

The base definition of the **assembly_component_usage** entity is given in ISO 10303-44. The following modifications apply to this part of ISO 10303.

Associated global rules:

The following global rules defined in this part of ISO 10303 apply to the **assembly_component_usage** entity:

— acu_requires_security_classification (See 5.2.5.70);

5.2.5 Configuration controlled design rules

5.2.5.1 application_context_requires_ap_definition

The **application_context_requires_ap_definition** rule specifies that each instance of **application_context** shall be referenced by exactly one **application_protocol_definition** that specifies this part of ISO 10303.

EXPRESS specification:

```
*)
RULE application_context_requires_ap_definition FOR
  (application_context, application_protocol_definition);
WHERE
  WR1: SIZEOF (QUERY (ac <* application_context |
    NOT (SIZEOF (QUERY (apd <* application_protocol_definition |
      (ac := apd.application)
      AND
      (apd.application_interpreted_model_schema_name =
        'config_control_design')))) = 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

application_context: identifies the set of all instances of **application_context** entities.

application_protocol_definition: identifies the set of all instances of **application_protocol_definition** entities.

Formal propositions:

WR1: For each instance of **application_context**, there shall be exactly one instance of **application_protocol_definition** that references the instance of **application_context** as its **application** with a value of 'config_control_design' as its **application_interpreted_model_schema_name**.

5.2.5.2 subtype_mandatory_product_context

The **subtype_mandatory_product_context** rule specifies the permitted usage of the product context. The **mechanical_context** entity shall be used to define the **discipline_type** of a **product_context**. This usage ensures that the context of the product data communicated represents a mechanical viewpoint of the data.

EXPRESS specification:

```

*)
RULE subtype_mandatory_product_context FOR (product_context);
WHERE
  WR1: SIZEOF ( QUERY (pc <* product_context |
    NOT ('CONFIG_CONTROL_DESIGN.MECHANICAL_CONTEXT' IN TYPEOF(pc)))
    = 0;
END_RULE;
( *

```

Argument definitions:

product_context: identifies the set of all instances of **product_context** entities.

Formal propositions:

WR1: Each instance of **product_context** shall be a **mechanical_context** entity.

5.2.5.3 design_context_for_property

The **design_context_for_property** rule specifies that the only life cycle stage for which properties may be defined in this part of ISO 10303 is that of design. Product structures may be defined using any life cycle stage for the context of a **product_definition**.

EXPRESS specification:

```

*)
RULE design_context_for_property FOR (product_definition);
WHERE
  WR1: SIZEOF (QUERY (pd <* product_definition |
    (SIZEOF (USEDIN (pd, 'CONFIG_CONTROL_DESIGN.' +
      'PROPERTY_DEFINITION.DEFINITION') +
      QUERY (pdr <* USEDIN (pd, 'CONFIG_CONTROL_DESIGN.' +
        'PRODUCT_DEFINITION_RELATIONSHIP.RELATED_PRODUCT_DEFINITION') |
        SIZEOF (USEDIN (pdr, 'CONFIG_CONTROL_DESIGN.PROPERTY_DEFINITION.' +
          'DEFINITION')) >= 1)) >= 1) AND
    (NOT ('CONFIG_CONTROL_DESIGN.DESIGN_CONTEXT' IN
      TYPEOF (pd.frame_of_reference)))))) = 0;
END_RULE;
( *

```

Argument definition:

product_definition: identifies the set of all instances of **product_definition**.

Formal proposition:

WR1: For each instance of **product_definition**, if that instance is referenced as the **definition** attribute of a **property_definition**, or if that instance is the **related_product_definition** in a **product_definition-relationship** instance that is referenced by the **definition** attribute of a **property_definition**, the **frame_of_reference** attribute for that **product_definition** instance must reference a **design_context**.

5.2.5.4 restrict_product_category_value

The **restrict_product_category_value** rule specifies the set of values that a **product_category** which is related to a **product** may contain.

EXPRESS specification:

```
*)
RULE restrict_product_category_value FOR
  (product_related_product_category);
WHERE
  WR1: SIZEOF (QUERY (prpc <*
    product_related_product_category |
    NOT( prpc.name IN ['assembly', 'detail',
      'customer_furnished_equipment', 'inseparable_assembly', 'cast',
      'coined', 'drawn', 'extruded', 'forged', 'formed', 'machined',
      'molded', 'rolled', 'sheared']))) = 0;
END_RULE;
(*
```

Argument definitions:

product_related_product_category: identifies the set of all instances of **product_related_product_category** entities.

Formal propositions:

WR1: The **name** attribute of a **product_related_product_category** shall be either "assembly", "detail", "inseparable_assembly", "customer_furnished_equipment", "cast", "coined", "drawn", "extruded", "forged", "formed", "machined", "molded", "rolled" or "sheared".

Attribute value restriction definitions:

assembly: identifies a part that consists of a collection of other parts which are put together to satisfy a particular function.

detail: identifies a part that exists at the lowest level of the bill of materials structure.

customer_furnished_equipment: identifies a part that has been furnished to the design agency by the customer.

inseparable_assembly: identifies a part that after being put together cannot be dis-assembled without causing physical harm to at least one of the components of the assembly.

cast: identifies a class of parts that are intended to be produced by a manufacturing process in which a liquid form of material is poured into a mold and hardened.

coined: identifies a class of parts that are intended to be produced by a manufacturing process in which a liquid form of material is forced into well confined dies by high pressures which forces the material to fill the shape of the die.

drawn: identifies a class of parts that are intended to be produced by a manufacturing process in which metal is pulled in order to remove material from a raw stock and form an indenture in the material of a defined shape.

extruded: identifies a class of parts that are intended to be produced by a manufacturing process in which material is squeezed by a compressing operation that changes the shape of the raw stock.

forged: identifies a class of parts that are intended to be produced by a manufacturing process in which metal materials are worked into useful shapes under the influence of external force at a high temperature.

formed: identifies a class of parts that are intended to be produced by a manufacturing process in which metal materials are subjected to stresses which change their shape.

machined: identifies a class of parts that are intended to be produced by a manufacturing process which employs a piece of automated equipment.

molded: identifies a class of parts that are intended to be produced by a manufacturing process in which material is heated past its melting point and poured into a mold to form its shape.

rolled: identifies a class of parts that are intended to be produced by a manufacturing process in which material is passed between two rolls in order to reduce it to the thickness equal to the space between the two rolls.

sheared: identifies a class of parts that are intended to be produced by a manufacturing process in which material is cut to alter its shape.

5.2.5.5 product_requires_product_category

The **product_requires_product_category** rule specifies the requirement that each **product** shall be referenced by exactly one **product_related_product_category** which defines whether the product is an "assembly", "inseparable_assembly", "detail" or "customer_furnished_equipment".

NOTE - The **product_requires_product_category** rule constrains the relationship between **product_related_product_category** and **product**. The rule specifies that a **product** must be referenced by exactly one **product_related_product_category** whose value is either "assembly", "inseparable_assembly", "detail" or "customer_furnished_equipment". The rule does not preclude the inclusion of other **product_related_product_category** entity instances with values other than those stated above for the **name** attribute of the **product_related_product_category**. Valid values for the **name** attribute of the **product_related_product_category** entity are defined in the rule **restrict_product_category_value**.

EXPRESS specification:

```
*)
RULE product_requires_product_category FOR
  (product, product_related_product_category);
WHERE
  WR1: SIZEOF (QUERY (prod <* product |
    NOT (SIZEOF (QUERY (prpc <* product_related_product_category |
      (prod IN prpc.products) AND
      (prpc.name IN ['assembly', 'inseparable_assembly', 'detail',
        'customer_furnished_equipment']))) = 1))) = 0;
END_RULE;
(*
```

Argument definitions:

product: identifies the set of all instances of **product** entities.

product_related_product_category: identifies the set of all instances of **product_related_product_category** entities.

Formal propositions:

WR1: For each instance of **product**, there shall be exactly one instance of **product_related_product_category** that contains a **name** attribute that has a value of either "assembly", "inseparable_assembly", "detail" or "customer_furnished_equipment".

5.2.5.6 change_request_requires_approval

The **change_request_requires_approval** rule specifies that each instance of a **change_request** shall be referenced by exactly one **cc_design_approval**. This rule enforces the requirement for each change request to have an approval.

EXPRESS specification:

```

*)
RULE change_request_requires_approval FOR
  (change_request, cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (cr <* change_request |
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
      cr IN ccda.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

change_request: identifies the set of all instances of **change_request** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **change_request**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **change_request** in its set of **items**.

5.2.5.7 change_request_requires_person_organization

The **change_request_requires_person_organization** rule specifies that every **change_request** shall be referenced by at least one **cc_design_person_and_organization_assignment**. This rule specifies the need for every **change_request** to have a recipient who receives the request. The meaning of recipient is found in the **person_and_organization_assignment** entity's **role** attribute.

NOTE - The coordination of the different role values with the assignment of **person_and_organization_assignment** to different entities is specified in the **cc_design_person_and_organization_correlation** function. This function is invoked locally to **cc_design_person_and_organization_assignment**.

EXPRESS specification:

```
*)
RULE change_request_requires_person_organization FOR
  (change_request,
   cc_design_person_and_organization_assignment);
WHERE
  WR1: SIZEOF (QUERY (cr <* change_request |
    NOT (SIZEOF (QUERY (ccpoa <*
      cc_design_person_and_organization_assignment |
        cr IN ccpoa.items )) >= 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

change_request: identifies the set of all instances of **change_request** entities.

cc_design_person_and_organization_assignment: identifies the set of all instances of **cc_design_person_and_organization_assignment** entities.

Formal propositions:

WR1: For each instance of **change_request**, there shall be at least one instance of **cc_design_person_and_organization_assignment** that contains the instance of **change_request** in its set of **items**.

5.2.5.8 change_request_requires_date_time

The **change_request_requires_date_time** rule specifies that each instance of a **change_request** shall be referenced by exactly one **cc_design_date_and_time_assignment**. This rule enforces the requirement for every **change_request** to have a request date indicating the date on which the **change_request** was issued.

NOTE - The coordination of the different role values with the assignment of **date_time_assignment** to different entities is specified in the **cc_design_date_and_time_correlation** function. This function is invoked locally to **cc_design_date_and_time_assignment**.

EXPRESS specification:

```

*)
RULE change_request_requires_date_time FOR
  (change_request, cc_design_date_and_time_assignment);
WHERE
  WR1: SIZEOF (QUERY (cr <* change_request |
    NOT (SIZEOF (QUERY (ccdta <* cc_design_date_and_time_assignment |
      cr IN ccdta.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

change_request: identifies the set of all instances of **change_request** entities.

cc_design_date_and_time_assignment: identifies the set of all instances of **cc_design_date_and_time_assignment** entities.

Formal propositions:

WR1: For each instance of **change_request**, there shall be exactly one instance of **cc_design_date_and_time_assignment** that contains the instance of **change_request** in its set of **items**.

5.2.5.9 change_requires_approval

The **change_requires_approval** rule specifies that each instance of **change** shall be referenced by exactly one instance of **cc_design_approval**. This rule enforces the requirement for every change to have an approval.

EXPRESS specification:

```

*)
RULE change_requires_approval FOR
  (change, cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (chg <* change |
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
      chg IN ccda.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

change: identifies the set of all instances of **change** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **change**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **change** in its set of **items**.

5.2.5.10 change_requires_date_time

The **change_requires_date_time** rule specifies that each instance of a **change** shall be referenced by exactly one **cc_design_date_and_time_assignment**. This rule enforces the requirement for every **change** to have a change date indicating the date on which the **change** is incorporated into the design.

NOTE - The coordination of the different role values with the assignment of **date_time_assignment** to different entities is specified in the **cc_design_date_and_time_correlation** function. This function is invoked locally to **cc_design_date_and_time_assignment**.

EXPRESS specification:

```

*)
RULE change_requires_date_time FOR
  (change, cc_design_date_and_time_assignment);
WHERE
  WR1: SIZEOF (QUERY (chg <* change |
    NOT (SIZEOF (QUERY (ccdta <* cc_design_date_and_time_assignment |
      (chg IN ccdta.items)
      AND (ccdta.role.name = 'start_date')))) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

change: identifies the set of all instances of **change** entities.

cc_design_date_and_time_assignment: identifies the set of all instances of **cc_design_date_and_time_assignment** entities.

Formal propositions:

WR1: For each instance of **change**, there shall be exactly one instance of **cc_design_date_and_time_assignment** that contains the instance of **change** in its set of **items** where the role name is "start_date".

5.2.5.11 start_request_requires_approval

The **start_request_requires_approval** rule specifies that each instance of **start_request** shall be referenced by exactly one instance of **cc_design_approval**. This rule enforces the requirement for every **start_request** to have an approval which authorizes the initiation of a design.

EXPRESS specification:

```

*)
RULE start_request_requires_approval FOR
  (start_request, cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (sr <* start_request |
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
      sr IN ccda.items )) = 1 ))) = 0;
END_RULE;
(*

```

Argument definitions:

start_request: identifies the set of all instances of **start_request** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **start_request**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **start_request** in its set of **items**.

5.2.5.12 start_request_requires_person_organization

The **start_request_requires_person_organization** rule specifies that every **start_request** shall be referenced by at least one **cc_design_person_and_organization_assignment**. This rule specifies the need for every **start_request** to have a recipient who receives the request. The meaning of recipient is found in the **person_and_organization_assignment** entity's **role** attribute.

NOTE - The coordination of the different role values with the assignment of **person_and_organization_assignment** to different entities is specified in the **cc_design_person_and_organization_correlation** function. This function is invoked locally to **cc_design_person_and_organization_assignment**.

EXPRESS specification:

```
*)
RULE start_request_requires_person_organization FOR (start_request,
  cc_design_person_and_organization_assignment);
WHERE
  WR1: SIZEOF (QUERY (sr <* start_request |
    NOT (SIZEOF (QUERY (ccdpoa <*
      cc_design_person_and_organization_assignment |
        sr IN ccdpoa.items )) >= 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

start_request: identifies the set of all instances of **start_request** entities.

cc_design_person_and_organization_assignment: identifies the set of all instances of **cc_design_person_and_organization_assignment** entities.

Formal propositions:

WR1: For each instance of **start_request**, there shall be at least one instance of **cc_design_person_and_organization_assignment** that contains the instance of **start_request** in its set of **items**.

5.2.5.13 start_request_requires_date_time

The **start_request_requires_date_time** rule specifies that each instance of a **start_request** shall be referenced by exactly one **cc_design_date_and_time_assignment**. This rule enforces the requirement for every **start_request** to have a request date indicating the date on which the **start_request** was issued.

NOTE - The coordination of the different role values with the assignment of **date_time_assignment** to different entities is specified in the **cc_design_date_and_time_correlation** function. This function is invoked locally to **cc_design_date_and_time_assignment**.

EXPRESS specification:

```

*)
RULE start_request_requires_date_time FOR
  (start_request, cc_design_date_and_time_assignment);
WHERE
  WR1: SIZEOF (QUERY (sr <* start_request |
    NOT (SIZEOF (QUERY (ccdata <* cc_design_date_and_time_assignment
      sr IN ccdata.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

start_request: identifies the set of all instances of **start_request** entities.

cc_design_date_and_time_assignment: identifies the set of all instances of **cc_design_date_and_time_assignment** entities.

Formal propositions:

WR1: For each instance of **start_request**, there shall be exactly one instance of **cc_design_date_and_time_assignment** that contains the instance of **start_request** in its set of **items**.

5.2.5.14 start_work_requires_approval

The **start_work_requires_approval** rule specifies that each instance of **start_work** shall be referenced by exactly one instance of **cc_design_approval**. This rule enforces the requirement for every design initiation to have an approval.

EXPRESS specification:

```

*)
RULE start_work_requires_approval FOR
  (start_work, cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (sw <* start_work |
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
      sw IN ccda.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

start_work: identifies the set of all instances of **start_work** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **start_work**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **start_work** in its set of **items**.

5.2.5.15 start_work_requires_date_time

The **start_work_requires_date_time** rule specifies that each instance of a **start_work** shall be referenced by exactly one **cc_design_date_and_time_assignment**. This rule enforces the requirement for every **start_work** to have a start date indicating the date on which work on the design is initiated.

NOTE - The coordination of the different role values with the assignment of **date_time_assignment** to different entities is specified in the **cc_design_date_and_time_correlation** function. This function is invoked locally to **cc_design_date_and_time_assignment**.

EXPRESS specification:

```
*)
RULE start_work_requires_date_time FOR
  (start_work, cc_design_date_and_time_assignment);
WHERE
  WR1: SIZEOF (QUERY (sw <* start_work |
    NOT (SIZEOF (QUERY (ccdta <* cc_design_date_and_time_assignment |
      (sw IN ccdta.items)
      AND (ccdta.role.name = 'start_date')))) = 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

start_work: identifies the set of all instances of **start_work** entities.

cc_design_date_and_time_assignment: identifies the set of all instances of **cc_design_date_and_time_assignment** entities.

Formal propositions:

WR1: For each instance of **start_work**, there shall be exactly one instance of **cc_design_date_and_time_assignment** that contains the instance of **start_work** in its set of **items** where the role name is "start_date".

5.2.5.16 restrict_action_request_status

The **restrict_action_request_status** rule specifies the permitted values for the status of a **action_request**.

EXPRESS specification:

```
*)
RULE restrict_action_request_status FOR (action_request_status);
WHERE
    WR1: SIZEOF (QUERY (ars <* action_request_status |
        NOT (ars.status IN ['proposed', 'in_work', 'issued', 'hold']))) = 0;
END_RULE;
(*
```

Argument definitions:

action_request_status: identifies the set of all instances of **action_request_status** entities.

Formal propositions:

WR1: For each instance of the **action_request_status** entity, the status attribute shall have a value of "proposed", "in_work", "issued", or "hold".

Attribute value definitions:

proposed: the **versioned_action_request** has been completed and is awaiting review and authorization.

in_work: the **versioned_action_request** is being developed for possible inclusion in the design.

issued: the **versioned_action_request** has been authorized for inclusion in the design.

hold: the **versioned_action_request** has been reviewed and not authorized to be included in the design.

5.2.5.17 versioned_action_request_requires_status

The **versioned_action_request_requires_status** rule specifies that each instance of **versioned_action_request** shall have exactly one status. The status of a **versioned_action_request** is defined by the **action_request_status** entity.

EXPRESS specification:

```
*)
RULE versioned_action_request_requires_status FOR
  (versioned_action_request, action_request_status);
WHERE
  WR1: SIZEOF (QUERY (ar <* versioned_action_request |
    NOT (SIZEOF (QUERY (ars <* action_request_status |
      ar ::= ars.assigned_request)) = 1))) = 0;
END_RULE;
(*
```

Argument definitions:

versioned_action_request: identifies the set of all instances of **versioned_action_request**.

action_request_status: identifies the set of all instances of **action_request_status**.

Formal proposition:

WR1: For each instance of **versioned_action_request** there shall be exactly one instance of **action_request_status** that contains an **assigned_request** attribute value equal to that instance of **versioned_action_request**.

5.2.5.18 versioned_action_request_requires_solution

The **versioned_action_request_requires_solution** rule specifies that each instance of **versioned_action_request** shall have one or more solutions suggested for it. A solution for a **versioned_action_request** is defined by the **action_request_solution** entity.

EXPRESS specification:

```
*)
RULE versioned_action_request_requires_solution FOR
  (versioned_action_request, action_request_solution);
WHERE
```

```

WR1: SIZEOF (QUERY (ar <* versioned_action_request |
    NOT (SIZEOF (QUERY (ars <* action_request_solution |
        ar ::= ars.request))) >= 1))) = 0;
END_RULE;
( *

```

Argument definitions:

versioned_action_request: identifies the set of all instances of **versioned_action_request**.

action_request_solution: identifies the set of all instances of **action_request_solution**.

Formal proposition:

WR1: For each instance of **versioned_action_request** there shall be exactly one instance of **action_request_solution** that contains a **request** attribute value equal to that instance of **versioned_action_request**.

5.2.5.19 unique_version_change_order_rule

The **unique_version_change_order_rule** calls a function that returns true if a **change** updates more than one **product_definition_formation**, and each updated **product_definition_formation** is a version of a different product. This rule specifies that a single **change** shall not change more than one version of a single **product**, but may change more than one **product_definition_formation** if each **product_definition_formation** references a different **product**.

EXPRESS specification:

```

*)
RULE unique_version_change_order_rule FOR (change);
WHERE
    WR1: SIZEOF (QUERY (c <* change |
        NOT (unique_version_change_order (c.assigned_action)))) = 0;
END_RULE;
( *

```

Argument definitions:

change: identifies the set of all instances of **change** entities.

Formal propositions:

WR1: For each instance of **change**, the **unique_version_change_order** function shall return a value of true.

5.2.5.20 product_requires_version

The **product_requires_version** rule specifies that each instance of **product** shall be referenced by at least one instance of **product_definition_formation**. This rule enforces the requirement for every product to have one or more versions.

EXPRESS specification:

```

*)
RULE product_requires_version FOR (product, product_definition_formation);
WHERE
    WR1: SIZEOF (QUERY (prod <* product |
        NOT (SIZEOF (QUERY (pdf <* product_definition_formation |
            prod ::= pdf.of_product )) >= 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

product: identifies the set of all instances of **product** entities.

product_definition_formation: identifies the set of all instances of **product_definition_formation** entities.

Formal propositions:

WR1: For each instance of **product**, there shall be one or more instances of **product_definition_formation** that contains an **of_product** attribute value equal to that instance of **product**.

5.2.5.21 product_requires_person_organization

The **product_requires_person_organization** rule specifies that each instance of **product** shall be referenced by an instance of **cc_design_person_and_organization_assignment**. This rule enforces the requirement for every product to have a design_owner.

EXPRESS specification:

```

*)
RULE product_requires_person_organization FOR
  (product, cc_design_person_and_organization_assignment);
WHERE
  WR1: SIZEOF (QUERY (prod <* product |
    NOT (SIZEOF (QUERY (ccdpoa <*
      cc_design_person_and_organization_assignment |
        prod IN ccdpoa.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

product: identifies the set of all instances of **product** entities.

cc_design_person_and_organization_assignment: identifies the set of all instances of **cc_design_person_and_organization_assignment** entities.

Formal propositions:

WR1: For each instance of **product**, there shall be an instance of **cc_design_person_and_organization_assignment** that contains an **items** attribute value equal to that instance of **product**.

NOTE - The role which is specified for the **person_and_organization** that is assigned to the **product** is "design_owner". This role association is specified formally in the function defined in 5.2.6.2.

5.2.5.22 product_version_requires_approval

The **product_version_requires_approval** rule specifies that each instance of **product_definition_formation** shall be referenced by exactly one instance of **cc_design_approval**. This rule enforces the requirement for every version of a design to have an approval.

EXPRESS specification:

```

*)
RULE product_version_requires_approval FOR (product_definition_formation,
  cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (pdf <* product_definition_formation |
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |

```

```

        pdf IN ccda.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

product_definition_formation: identifies the set of all instances of **product_definition_formation** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **product_definition_formation**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **product_definition_formation** in its set of **items**.

5.2.5.23 product_version_requires_person_organization

The **product_version_requires_person_organization** rule specifies that every **product_definition_formation** shall be referenced by exactly one **cc_design_person_and_organization_assignment** in the role of creator and one or more **cc_design_person_and_organization_assignment** in the role of either part-supplier or design_supplier. This rule specifies the need for every **product_definition_formation** to have a creator and supplier who are responsible for the creation or delivery of the particular version of the design. The meanings of creator, part_supplier, and design_supplier are found in 5.2.5.43 as part of the definition of the **restrict_person_organization_role** rule.

NOTE - The coordination of the different role values with the assignment of **person_and_organization_assignment** to different entities is specified in the **cc_design_person_and_organization_correlation** function. This function is invoked locally to **cc_design_person_and_organization_assignment**. See the function definition in 5.2.6.2.

EXPRESS specification:

```

*)
RULE product_version_requires_person_organization FOR
    (product_definition_formation,
    cc_design_person_and_organization_assignment);
WHERE
    WR1: SIZEOF (QUERY (pdf <* product_definition_formation |
        NOT (SIZEOF (QUERY (ccdpoa <*
            cc_design_person_and_organization_assignment |
            (pdf IN ccdpoa.items) AND (ccdpoa.role.name = 'creator')))) = 1 )))
        = 0;

```

```

WR2: SIZEOF (QUERY (pdf <* product_definition_formation |
    NOT (SIZEOF (QUERY (ccdpoa <*
    cc_design_person_and_organization_assignment |
    (pdf IN ccdpoa.items) AND
    (ccdpoa.role.name IN ['design_supplier', 'part_supplier']))) >= 1)))
    = 0;
END_RULE;
( *

```

Argument definitions:

product_definition_formation: identifies the set of all instances of **product_definition_formation** entities.

cc_design_person_and_organization_assignment: identifies the set of all instances of **cc_design_person_and_organization_assignment** entities.

Formal propositions:

WR1: For each instance of **product_definition_formation**, there shall be exactly one instance of **cc_design_person_and_organization_assignment** that contains the instance of **product_definition_formation** in its set of **items** and its **role** attribute references a **person_and_organization_role** that has a value of 'creator' in its **name** attribute.

WR2: For each instance of **product_definition_formation**, there shall be at least one instance of **cc_design_person_and_organization_assignment** that contains the instance of **product_definition_formation** in its set of **items** and its **role** attribute references a **person_and_organization_role** that has a value of either 'design_supplier' or 'part_supplier' in its **name** attribute.

5.2.5.24 product_version_requires_security_classification

The **product_version_requires_security_classification** rule specifies that each instance of **product_definition_formation** shall be referenced by exactly one instance of **cc_design_security_classification**. This rule enforces the requirement for every version of a design to have a security classification.

EXPRESS specification:

```

*)
RULE product_version_requires_security_classification FOR
    (product_definition_formation, cc_design_security_classification);
WHERE
    WR1: SIZEOF (QUERY (pdf <* product_definition_formation |
        NOT (SIZEOF (QUERY (ccdsc <* cc_design_security_classification |

```

```

        pdf IN ccdsc.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

product_definition_formation: identifies the set of all instances of **product_definition_formation** entities.

cc_design_security_classification: identifies the set of all instances of **cc_design_security_classification** entities.

Formal propositions:

WR1: For each instance of **product_definition_formation**, there shall be exactly one instance of **cc_design_security_classification** that contains the instance of **product_definition_formation** in its set of items.

5.2.5.25 product_definition_requires_person_organization

The **product_definition_requires_person_organization** rule specifies that every **product_definition** shall be referenced by exactly one **cc_design_person_and_organization_assignment**. This rule specifies the need for every **product_definition** to have a creator who is responsible for the creation of the particular definition of the design. The meaning of creator is found in the **person_and_organization_assignment** entity's **role** attribute.

NOTE - The coordination of the different role values with the assignment of **person_and_organization_assignment** to different entities is specified in the **cc_design_person_and_organization_correlation** function. This function is invoked locally to **cc_design_person_and_organization_assignment**.

EXPRESS specification:

```

*)
RULE product_definition_requires_person_organization FOR
    (product_definition,
    cc_design_person_and_organization_assignment);
WHERE
    WR1: SIZEOF (QUERY (pd <* product_definition |
        NOT (SIZEOF (QUERY (ccdpoa <*
            cc_design_person_and_organization_assignment |
            pd IN ccdpoa.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

product_definition: identifies the set of all instances of **product_definition** entities.

cc_design_person_and_organization_assignment: identifies the set of all instances of **cc_design_person_and_organization_assignment** entities.

Formal propositions:

WR1: For each instance of **product_definition**, exactly one instance of **cc_design_person_and_organization_assignment** shall contain the instance of **product_definition** in its set of items.

5.2.5.26 product_definition_requires_approval

The **product_definition_requires_approval** rule specifies that each instance of **product_definition** shall be referenced by exactly one instance of **cc_design_approval**. This rule enforces the requirement for every definition of a design to have an approval.

EXPRESS specification:

```

*)
RULE product_definition_requires_approval FOR
  (product_definition, cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (pd <* product_definition |
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
      pd IN ccda.items)) = 1 ))) = 0;
END_RULE;
( *
```

Argument definitions:

product_definition: identifies the set of all instances of **product_definition** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **product_definition**, exactly one instance of **cc_design_approval** shall contain the instance of **product_definition** in its set of **items**.

5.2.5.27 product_definition_requires_date_time

The **product_definition_requires_date_time** rule specifies that each instance of a **product_definition** shall be referenced by exactly one **cc_design_date_and_time_assignment**. This rule enforces the requirement for every **product_definition** to have a date indicating the date on which the definition of the product was created.

NOTE - The coordination of the different role values with the assignment of **date_time_assignment** to different entities is specified in the **cc_design_date_and_time_correlation** function. This function is invoked locally to **cc_design_date_and_time_assignment**.

EXPRESS specification:

```

*)
RULE product_definition_requires_date_time FOR
  (product_definition, cc_design_date_and_time_assignment);
WHERE
  WR1: SIZEOF (QUERY (pd <* product_definition |
    NOT (SIZEOF (QUERY (ccdata <* cc_design_date_and_time_assignment |
      pd IN ccdata.items )) = 1))) = 0;
END_RULE;
( *
```

Argument definitions:

product_definition: identifies the set of all instances of **product_definition** entities.

cc_design_date_and_time_assignment: identifies the set of all instances of **cc_design_date_and_time_assignment** entities.

Formal propositions:

WR1: For each instance of **product_definition**, exactly one instance of **cc_design_date_and_time_assignment** shall contain the instance of **product_definition** in its set of **items**.

5.2.5.28 certification_requires_approval

The **certification_requires_approval** rule specifies that each instance of **certification** shall be referenced by exactly one instance of **cc_design_approval**. This rule enforces the requirement for every certification of a supplier of either a design or a part to have an approval.

EXPRESS specification:

```
*)
RULE certification_requires_approval FOR (certification,
    cc_design_approval);
WHERE
    WR1: SIZEOF (QUERY (cert <* certification |
        NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
            cert IN ccda.items )) = 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

certification: identifies the set of all instances of **certification** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **certification**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **certification** its set of **items**.

5.2.5.29 restrict_certification_type

The **restrict_certification_type** rule specifies that **certification** may only be given for either a "part-supplier" or "design_supplier".

EXPRESS specification:

```
*)
RULE restrict_certification_type FOR (certification_type);
WHERE
    WR1: SIZEOF (QUERY (ct <* certification_type |
        NOT (ct.description IN ['design_supplier', 'part_supplier']))) = 0;
```

```
END_RULE;
( *
```

Argument definitions:

certification_type: identifies the set of all instances of **certification_type** entities.

Formal propositions:

WR1: For each instance of **certification_type**, the value of the **kind** attribute shall be "design_supplier" or "part_supplier".

Attribute value definitions:

design_supplier: identifies a supplier of a design for a part.

part_supplier: identifies a supplier of a part.

5.2.5.30 certification_requires_date_time

The **certification_requires_date_time** rule specifies that each instance of a **certification** shall be referenced by exactly one **cc_design_date_and_time_assignment**. This rule enforces the requirement for every **certification** to have a date indicating the date on which the certification is effective.

NOTE - The coordination of the different role values with the assignment of **date_time_assignment** to different entities is specified in the **cc_design_date_and_time_correlation** function. This function is invoked locally to **cc_design_date_and_time_assignment**. See the function definition in 5.2.6.3.

EXPRESS specification:

```
*)
RULE certification_requires_date_time FOR
  (certification, cc_design_date_and_time_assignment);
WHERE
  WR1: SIZEOF (QUERY (cert <* certification |
    NOT (SIZEOF (QUERY (ccdata <* cc_design_date_and_time_assignment |
      cert IN ccdata.items )) = 1 ))) = 0;
END_RULE;
( *
```

Argument definitions:

certification: identifies the set of all instances of **certification** entities.

cc_design_date_and_time_assignment: identifies the set of all instances of **cc_design_date_and_time_assignment** entities.

Formal propositions:

WR1: For each instance of **certification**, exactly one instance of **cc_design_date_and_time_assignment** shall contain the instance of **certification** in its set of **items**.

5.2.5.31 approvals_are_assigned

The **approvals_are_assigned** rule specifies that each instance of **approval** shall be assigned by at least one instance of **approval_assignment** entity.

EXPRESS specification:

```

*)
RULE approvals_are_assigned FOR
  (approval, approval_assignment);
WHERE
  WR1: SIZEOF (QUERY (app <* approval |
    NOT (SIZEOF (QUERY (aa <* approval_assignment |
      app ::= aa.assigned_approval )) >= 1 ))) = 0;
END_RULE;
( *
```

Argument definitions:

approval: identifies the set of all instances of **approval** entities.

approval_assignment: identifies the set of all instances of **approval_assignment** entities.

Formal propositions:

WR1: For each instance of **approval**, there shall be one or more instances of **approval_assignment** which contains the instance of **approval** as its **assigned_approval** attribute.

5.2.5.32 approval_requires_approval_person_organization

The **approval_requires_approval_person_organization** specifies that each instance of **approval** shall have at least one **approval_person_organization** referencing it. This rule enforces the requirement for an approval to be authorized by one or more people within their organizations.

EXPRESS specification:

```
*)
RULE approval_requires_approval_person_organization FOR
    (approval, approval_person_organization);
WHERE
    WR1: SIZEOF (QUERY (app <* approval |
        NOT (SIZEOF (QUERY (apo <* approval_person_organization |
            app ::= apo.authorized_approval )) >= 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

approval: identifies the set of all instances of **approval** entities.

approval_person_organization: identifies the set of all instances of **approval_person_organization** entities.

Formal propositions:

WR1: For each instance of **approval**, there shall be one or more instances of **approval_person_organization** which contains the instance of **approval** as its **authorized_approval** attribute.

5.2.5.33 approval_requires_approval_date_time

The **approval_requires_approval_date_time** rule specifies that each instance of **approval** shall be referenced by exactly one **approval_date_time**. This rule enforces the requirement for every approval to have a date on which the approval obtained its specified status.

EXPRESS specification:

```
*)
RULE approval_requires_approval_date_time FOR (approval,
    approval_date_time);
WHERE
```

```

WR1: SIZEOF (QUERY (app <* approval |
    NOT (SIZEOF (QUERY (adt <* approval_date_time |
        app :=: adt.dated_approval )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

approval: identifies the set of all instances of **approval** entities.

approval_date_time: identifies the set of all instances of **approval_date_time** entities.

Formal propositions:

WR1: For each instance of **approval**, there shall be exactly one instance of **approval_date_time** which contains the instance of **approval** as its **dated_approval** attribute.

5.2.5.34 restrict_approval_status

The **restrict_approval_status** rule specifies that the only values of **approval_status** permitted shall be "approved", "not_yet_approved", "disapproved" or "withdrawn".

EXPRESS specification:

```

*)
RULE restrict_approval_status FOR (approval_status);
WHERE
    WR1: SIZEOF (QUERY (ast <* approval_status |
        NOT (ast.name IN
            ['approved', 'not_yet_approved', 'disapproved', 'withdrawn']))) = 0;
END_RULE;
( *

```

Argument definitions:

approval: identifies the set of all instances of **approval** entities.

Formal propositions:

WR1: For each instance of **approval**, the value of the **status** attribute shall be either "approved", "not_yet_approved", "disapproved" or "withdrawn".

Attribute value definitions:

approved: specifies that the required authorizations have been obtained for a particular role of approval for a piece of product data.

not_yet_approved: specifies that the required authorizations are being awaited for a particular role of approval for a piece of product data.

disapproved: specifies that the required authorizations have been denied for a particular role of approval for a piece of product data.

withdrawn: specifies that the required authorizations have been revoked for a particular role of approval for a piece of product data.

5.2.5.35 contract_requires_approval

The **contract_requires_approval** rule specifies that each instance of **contract** shall be referenced by exactly one instance of **cc_design_approval**. This rule enforces the requirement for every contract under which a design is developed is to have an approval.

EXPRESS specification:

```
*)
RULE contract_requires_approval FOR (contract,
  cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (c <* contract |
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
      c IN ccda.items)) = 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

contract: identifies the set of all instances of **contract** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **contract**, exactly one instance of **cc_design_approval** shall exist which references the instance of **contract** in its set of **items**.

5.2.5.36 contract_requires_person_organization

The **contract_requires_person_organization** rule specifies that every **contract** shall be referenced by exactly one **cc_design_person_and_organization_assignment**. This rule specifies the need for every **contract** to have a contractor who is responsible for the maintenance of information about the contract. The meaning of contractor is found in the **person_and_organization_assignment** entity's **role** attribute.

NOTE - The coordination of the different role values with the assignment of **person_and_organization_assignment** to different entities is specified in the **cc_design_person_and_organization_correlation** function. This function is invoked locally to **cc_design_person_and_organization_assignment**. See the function definition in 5.2.6.2.

EXPRESS specification:

```
*)
RULE contract_requires_person_organization FOR
  (contract, cc_design_person_and_organization_assignment);
WHERE
  WR1: SIZEOF (QUERY (c <* contract |
    NOT (SIZEOF (QUERY (ccdpoa <*
      cc_design_person_and_organization_assignment |
        c IN ccdpoa.items )) = 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

contract: identifies the set of all instances of **contract** entities.

cc_design_person_and_organization_assignment: identifies the set of all instances of **cc_design_person_and_organization_assignment** entities.

Formal propositions:

WR1: For each instance of **contract**, there shall be exactly one instance of **cc_design_person_and_organization_assignment** that contains the instance of **contract** in its set of **items**.

5.2.5.37 restrict_contract_type

The **restrict_contract_type** rule specifies the permitted types of contracts. This rule enforces the requirement for the types of contract to be either "fixed_price" or "cost_plus".

EXPRESS specification:

```

*)
RULE restrict_contract_type FOR (contract_type);
WHERE
    WR1: SIZEOF (QUERY (ct <* contract_type |
        NOT (ct.description IN ['fixed_price', 'cost_plus']))) = 0;
END_RULE;
( *

```

Argument definitions:

contract_type: identifies the set of all instances of **contract_type** entities.

Formal propositions:

WR1: For each instance of **contract_type**, the **kind** attribute shall contain a value of "fixed_price" or "cost_plus".

Attribute value definitions:

fixed_price: identifies a contract under which the remuneration for the performance of the contract has been set.

cost_plus: identifies a contract under which the remuneration for the performance of the contract is a set amount above the cost to the contracting organization.

5.2.5.38 security_classification_requires_approval

The **security_classification_requires_approval** rule specifies that each instance of **security_classification** shall be referenced by exactly one instance of **cc_design_approval**. This rule enforces the requirement for every security classification assigned to a design is to have an approval.

EXPRESS specification:

```

*)
RULE security_classification_requires_approval FOR
    (security_classification, cc_design_approval);
WHERE
    WR1: SIZEOF (QUERY (sc <* security_classification |
        NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
            sc IN ccda.items )) = 1 ))) = 0;

```

```
END_RULE;
( *
```

Argument definitions:

security_classification: identifies the set of all instances of **security_classification** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **security_classification**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **security_classification** in its set of **items**.

5.2.5.39 security_classification_requires_person_organization

The **security_classification_requires_person_organization** rule specifies that every **security_classification** shall be referenced by exactly one **cc_design_person_and_organization_assignment**. This rule specifies the need for every **security_classification** to have a classification officer who is responsible for issuing the security classification. The meaning of classification officer is found in the **person_and_organization_assignment** entity's **role** attribute.

NOTE - The coordination of the different role values with the assignment of **person_and_organization_assignment** to different entities is specified in the **cc_design_person_and_organization_correlation** function. This function is invoked locally to **cc_design_person_and_organization_assignment**. See the function definition in 5.2.6.2.

EXPRESS specification:

```
*)
RULE security_classification_requires_person_organization FOR
  (security_classification,
   cc_design_person_and_organization_assignment);
WHERE
  WR1: SIZEOF (QUERY (sc <* security_classification |
    NOT (SIZEOF (QUERY (ccdpoa <*
      cc_design_person_and_organization_assignment |
        sc IN ccdpoa.items )) = 1 ))) = 0;
END_RULE;
( *
```

Argument definitions:

security_classification: identifies the set of all instances of **security_classification** entities.

cc_design_person_and_organization_assignment: identifies the set of all instances of **cc_design_person_and_organization_assignment** entities.

Formal propositions:

WR1: For each instance of **security_classification**, there shall be exactly one instance of **cc_design_person_and_organization_assignment** that contains the instance of **security_classification** in its set of items.

5.2.5.40 security_classification_requires_date_time

The **security_classification_requires_date_time** rule specifies that each instance of a **security_classification** shall be referenced by exactly one **cc_design_date_and_time_assignment** that has a role of "classification_date". This rule enforces the requirement for every **security_classification** to have a date indicating the date on which the security classification is effective.

NOTE - The coordination of the different role values with the assignment of **date_time_assignment** to different entities is specified in the **cc_design_date_and_time_correlation** function. This function is invoked locally to **cc_design_date_and_time_assignment**. See the function definition in 5.2.6.3.

EXPRESS specification:

```
*)
RULE security_classification_requires_date_time FOR
  (security_classification, cc_design_date_and_time_assignment);
WHERE
  WR1: SIZEOF (QUERY (sc <* security_classification |
    NOT (SIZEOF (QUERY (ccdta <* cc_design_date_and_time_assignment |
      (sc IN ccdta.items) AND
      ('classification_date' = ccdta.role.name)))) = 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

security_classification: identifies the set of all instances of **security_classification** entities.

cc_design_date_and_time_assignment: identifies the set of all instances of **cc_design_date_and_time_assignment** entities.

Formal propositions:

WR1: For each instance of **security_classification**, there shall be exactly one instance of **cc_design_date_and_time_assignment** that contains the instance of **security_classification** in its set of **items** and its **role** attribute references an instance of **date_and_time_role** that has a **name** attribute with the value of "classification_date".

5.2.5.41 security_classification_optional_date_time

The **security_classification_optional_date_time** rule specifies that each instance of a **security_classification** may be referenced by zero or one **cc_design_date_and_time_assignment** that has a role of "declassification_date". This rule enforces the requirement that every **security_classification** may have a date indicating the date on which the security classification expires.

NOTE - The coordination of the different role values with the assignment of **date_time_assignment** to different entities is specified in the **cc_design_date_and_time_correlation** function. This function is invoked locally to **cc_design_date_and_time_assignment**. See the function definition in 5.2.6.3.

EXPRESS specification:

```
*)
RULE security_classification_optional_date_time FOR
  (security_classification, cc_design_date_and_time_assignment);
WHERE
  WR1: SIZEOF (QUERY (sc <* security_classification |
    NOT (SIZEOF (QUERY (ccdta <* cc_design_date_and_time_assignment |
      (sc IN ccdta.items) AND
      ('declassification_date' = ccdta.role.name))) <= 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

security_classification: identifies the set of all instances of **security_classification** entities.

cc_design_date_and_time_assignment: identifies the set of all instances of **cc_design_date_and_time_assignment** entities.

Formal propositions:

WR1: For each instance of **security_classification**, there may be zero or one instance of **cc_design_date_and_time_assignment** that contains the instance of **security_classification** in its set of **items** and its **the_role** attribute references an instance of **date_and_time_role** that has a **name** attribute with the value of "declassification_date".

5.2.5.42 restrict_security_classification_level

The **restrict_security_classification_level** rule specifies the permitted levels of security. This rule enforces the requirement for the levels of security to be "unclassified", "classified", "proprietary", "confidential", "secret", or "top_secret".

EXPRESS specification:

```

*)
RULE restrict_security_classification_level FOR
  (security_classification_level);
WHERE
  WR1: SIZEOF (QUERY (scl <* security_classification_level |
    NOT (scl.name IN ['unclassified', 'classified', 'proprietary',
      'confidential', 'secret', 'top_secret']))) = 0;
END_RULE;
( *

```

Argument definitions:

security_classification_level: identifies the set of all instances of **security_classification_level** entities.

Formal propositions:

WR1: For each instance of **security_classification_level**, the **name** attribute shall contain a value of "unclassified", "classified", "proprietary", "confidential", "secret" or "top_secret".

Attribute value definitions:

unclassified: identifies the classification level for which no security is necessary.

classified: identifies the classification level for which security is necessary, but the classification details are not given.

proprietary: identifies the classification level for which the disclosure of information about the part or the design of the part would risk an organization's market or competitive advantage.

confidential: identifies the classification level for which the disclosure of information about the part or the design of the part would cause damage to national or organizational security.

secret: identifies the classification level for which the disclosure of information about the part or the design of the part would cause serious damage to national or organizational security.

top_secret: identifies the classification level for which the disclosure of information about the part or the design of the part would cause exceptionally grave damage to national or organizational security.

5.2.5.43 restrict_person_organization_role

The **restrict_person_organization_role** rule specifies the permitted roles for **person_and_organization** entities. This rule enforces the requirement for the roles of **person_and_organization** entities to be "request_recipient", "initiator", "part_supplier", "design_supplier", "configuration_manager", "contractor", "classification_officer", "creator" or "design_owner".

EXPRESS specification:

```
*)
RULE restrict_person_organization_role FOR
  (person_and_organization_role);
WHERE
  WR1: SIZEOF (QUERY (por <* person_and_organization_role |
    NOT (por.name IN ['request_recipient', 'initiator', 'part_supplier',
      'design_supplier', 'configuration_manager', 'contractor',
      'classification_officer', 'creator', 'design_owner']))) = 0;
END_RULE;
(*
```

Argument definitions:

person_organization_role: identifies the set of all instances of **person_organization_role** entities.

Formal propositions:

WR1: For each instance of **person_organization_role**, the name attribute shall have a value of "request_recipient", "initiator", "part_supplier", "design_supplier", "configuration_manager", "contractor", "classification_officer", "creator" or "design_owner".

Attribute value definitions:

request_recipient: identifies a person within an organization who is responsible for receiving a **change_request** or **start_request** and taking action based on the request.

initiator: identifies a person within an organization who is responsible for creating the **change_request** or **start_request**.

part_supplier: identifies a person within an organization who is responsible for supplying a part.

design_supplier: identifies a person within an organization who is responsible for supplying the design of a part.

configuration_manager: identifies a person within an organization who is responsible for assigning the configuration information about a design.

contractor: identifies a person within an organization who is responsible for the information pertaining to a contract that applies to a design.

classification_officer: identifies a person within an organization who is responsible for the classification and declassification of parts.

creator: identifies a person within an organization who is responsible for the creation of a particular **product_definition_formation** or **product_definition**.

design_owner: identifies a person within an organization who is responsible for the design of all aspects of a **product**.

5.2.5.44 restrict_date_time_role

The **restrict_date_time_role** rule specifies the permitted roles for **date_and_time** entities. This rule enforces the requirement for the roles of **date_and_time** entities to be "creation_date", "request_date", "release_date", "start_date", "contract_date", "certification_date", "sign_off_date", "classification_date", or "declassification_date".

EXPRESS specification:

*)

```
RULE restrict_date_time_role FOR (date_time_role);
WHERE
```

```
  WR1: SIZEOF (QUERY (dtr <* date_time_role |
    NOT (dtr.name IN ['creation_date', 'request_date', 'release_date',
```

```

        'start_date', 'contract_date', 'certification_date',
        'sign_off_date', 'classification_date',
        'declassification_date']))) = 0;
END_RULE;
( *

```

Argument definitions:

date_time_role: identifies the set of all instances of **date_time_role** entities.

Formal propositions:

WR1: For each instance of **date_time_role**, the name attribute shall have the value of "creation_date", "request_date", "release_date", "start_date", "contract_date", "certification_date", "sign_off_date", "classification_date", or "declassification_date".

Attribute value definitions:

creation_date: identifies the date and time when either a version of a design or a definition of a design comes into existence.

request_date: identifies the date and time given when work is requested for a design.

release_date: identifies the date and time when a design is initially released or a change is incorporated into a design.

start_date: identifies the date and time when work is begun for either a new design or a change to an existing design.

contract_date: identifies the date and time when a contract for a design goes into effect.

certification_date: identifies the date and time when a certification goes into effect.

sign_off_date: identifies the date and time when an authorization was given to an approval.

classification_date: identifies the date and time when a security classification goes into effect.

declassification_date: identifies the date and time when a security classification goes out of effect.

5.2.5.45 restrict_document_type

The **restrict_document_type** rule specifies the permitted types of documents. This rule enforces the requirement for the types of documents to be "material_specification", "process_specification", "design_specification" or "surface_finish_specification".

EXPRESS specification:

```
*)
RULE restrict_document_type FOR (document_type);
WHERE
  WR1: SIZEOF (QUERY (dt <* document_type |
    NOT (dt.product_data_type IN ['material_specification',
      'process_specification', 'design_specification',
      'surface_finish_specification', 'cad_filename', 'drawing']))) = 0;
END_RULE;
(*
```

Argument definitions:

document_type: identifies the set of all instances of **document_type** entities.

Formal propositions:

WR1: For each instance of **document_type**, the **product_data_type** attribute shall have the value of "material_specification", "process_specification", "design_specification", "surface_finish_specification", "cad_filename", or "drawing".

Attribute value definitions:

material_specification: identifies a type of document that specifies properties which are applicable to raw material, mixtures or semi-fabricated material which are used in the fabrication of a part.

process_specification: identifies a type of document that specifies a service to be performed on a product or material.

design_specification: identifies a type of document that sets the design requirements of a part.

surface_finish_specification: identifies a type of document that specifies properties which are applicable to surface textures or protective coatings for either an in process or completed part.

cad_filename: identifies a type of document that is represented electronically as a file from a Computer Aided Design system.

drawing: identifies a type of document that contains the draughting representation of the design for a part or parts.

5.2.5.46 document_to_product_definition

The **document_to_product_definition** rule specifies the permitted association between documents which are grouped together using **document_relationship** and **product_definition** entities. This rule enforces the requirement that only **product_definition** entities may have groups of documents related to them.

EXPRESS specification:

```

*)
RULE document_to_product_definition FOR
  (cc_design_specification_reference);
WHERE
  WR1: SIZEOF (QUERY (sp <* cc_design_specification_reference |
    NOT (((('CONFIG_CONTROL_DESIGN.DOCUMENT_RELATIONSHIP.' +
    'RELATING_DOCUMENT' IN
    ROLESOF (sp\document_reference.assigned_document)) AND
    (SIZEOF (QUERY (it <* sp.items |
    NOT('CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION' IN
    TYPEOF (it)))) = 0)))) = 0)))
  OR
  (NOT ('CONFIG_CONTROL_DESIGN.DOCUMENT_RELATIONSHIP.' +
    'RELATING_DOCUMENT' IN
    ROLESOF (sp\document_reference.assigned_document)))))) = 0;
END_RULE;
( *

```

Argument definitions:

cc_design_specification_reference: identifies the set of all instances of **cc_design_specification_reference** entities.

product_definition: identifies the set of all instances of **product_definition** entities.

Formal propositions:

WR1: For each instance of **cc_design_specification_reference**, if the referenced **document** is used as the **relating_document** in a **document_relationship** then each of the elements in the set of **items** shall be a **product_definition** entity.

5.2.5.47 as_required_quantity

The **as_required_quantity** rule specifies the use of the **descriptive_measure** type in the **measure_with_unit** entity. The value of the **descriptive_measure** STRING type shall always be "as_required". This rule enforces the requirement for the specification of the use of an amount to be as required.

EXPRESS specification:

```

*)
RULE as_required_quantity FOR (measure_with_unit);
WHERE
  WR1: SIZEOF (QUERY (m <* measure_with_unit |
    ('CONFIG_CONTROL_DESIGN.DESCRPTIVE_MEASURE' IN
    TYPEOF (m.value_component)) AND
    (NOT (m.value_component = 'as_required')))) = 0;
END_RULE;
(*

```

Argument definitions:

measure_with_unit: identifies the set of all instances of **measure_with_unit** entities.

Formal propositions:

WR1: For each instance of **measure_with_unit**, if the type of the attribute **value** is **descriptive_measure** then the value of the attribute shall be "as_required".

5.2.5.48 global_unit_assignment

The **global_unit_assignment** rule specifies the units that shall be defined for a **global_unit_assigned_context**. The rule states that every **global_unit_assigned_context** shall have exactly three elements in its set of **units**, and that every **global_unit_assigned_context** shall contain units of length, plane angle and solid angle.

EXPRESS specification:

```

*)
RULE global_unit_assignment FOR (global_unit_assigned_context);
WHERE
  WR1: SIZEOF (QUERY (guac <* global_unit_assigned_context |
    NOT (SIZEOF (guac.units) = 3))) = 0;
  WR2: SIZEOF (QUERY (guac <* global_unit_assigned_context |
    NOT ((SIZEOF (QUERY (u <* guac.units |
      'CONFIG_CONTROL_DESIGN.LENGTH_UNIT' IN TYPEOF (u))) = 1) AND
      (SIZEOF (QUERY (u <* guac.units |
        'CONFIG_CONTROL_DESIGN.PLANE_ANGLE_UNIT' IN TYPEOF (u))) = 1) AND
      (SIZEOF (QUERY (u <* guac.units |
        'CONFIG_CONTROL_DESIGN.SOLID_ANGLE_UNIT' IN TYPEOF (u))) = 1
      )))) = 0;
END_RULE;
(*)

```

Argument definitions:

global_unit_assigned_context: identifies the set of all instances of **global_unit_assigned_context** entities.

Formal propositions:

WR1: For each instance of **global_unit_assigned_context**, the set of **units** shall contain exactly 3 elements.

WR2: For each instance of **global_unit_assigned_context**, the first element of the set of **units** shall be a **length_unit**, the second element of the set of **units** shall be a **plane_angle_unit** and the third element of the set of **units** shall be a **solid_angle_unit**.

5.2.5.49 subtype_mandatory_action

The **subtype_mandatory_action** rule specifies that all **action** entities shall be an **directed_action** entity.

EXPRESS specification:

```

*)
RULE subtype_mandatory_action FOR
  (action);
WHERE
  WR1: SIZEOF (QUERY (act <* action |
    NOT ('CONFIG_CONTROL_DESIGN.DIRECTED_ACTION' IN

```

```

        TYPEOF (act)))) = 0;
END_RULE;
( *

```

Argument definitions:

action: identifies the set of all instances of **action** entities to be constrained.

Formal propositions:

WR1: Each instance of **action** shall be a **directed_action**.

5.2.5.50 subtype_mandatory_product_definition_formation

The **subtype_mandatory_product_definition_formation** rule specifies that all **product_definition_formation** entities shall be **product_definition_formation_with_specified_source** entities.

EXPRESS specification:

```

*)
RULE subtype_mandatory_product_definition_formation FOR
  (product_definition_formation);
WHERE
  WR1: SIZEOF (QUERY (pdf <* product_definition_formation |
    NOT ('CONFIG_CONTROL_DESIGN.' +
      'PRODUCT_DEFINITION_FORMATION_WITH_SPECIFIED_SOURCE' IN
    TYPEOF (pdf)))) = 0;
END_RULE;
( *

```

Argument definitions:

product_definition_formation: identifies the set of all instances of **product_definition_formation** entities to be constrained.

Formal propositions:

WR1: Each instance of **product_definition_formation** shall be a **product_definition_formation_with_specified_source**.

5.2.5.51 dependent_instantiable_date

The **dependent_instantiable_date** rule specifies that all instances of **date** are dependent on the usage to define another entity.

EXPRESS specification:

```
*)
RULE dependent_instantiable_date FOR (date);
WHERE
  WR1: SIZEOF (QUERY (dt <* date |
    NOT (SIZEOF (USEDIN (dt, '')) >= 1))) = 0;
END_RULE;
(*
```

Argument definition:

date: identifies the set of all instances of **date**.

Formal proposition:

WR1: For each instance of **date**, there shall be a reference to the **date** instance from an attribute of another entity.

5.2.5.52 dependent_instantiable_shape_representation

The **dependent_instantiable_shape_representation** rule specifies that all instances of **shape-representation** are dependent on the usage to define another entity.

EXPRESS specification:

```
*)
RULE dependent_instantiable_shape_representation FOR
  (shape_representation);
WHERE
  WR1: SIZEOF (QUERY (sr <* shape_representation |
    NOT (SIZEOF (USEDIN (sr, '')) >= 1))) = 0;
END_RULE;
(*
```

Argument definition:

shape_representation: identifies the set of all instances of **shape_representation**.

Formal proposition:

WR1: For each instance of **shape_representation**, there shall be a reference to the **shape_representation** instance from an attribute of another entity.

5.2.5.53 dependent_instantiable_named_unit

The **dependent_instantiable_named_unit** rule specifies that all instances of **named_unit** are dependent on the usage to define another entity.

EXPRESS specification:

```
*)
RULE dependent_instantiable_named_unit FOR (named_unit);
WHERE
  WR1: SIZEOF (QUERY (nu <* named_unit |
    NOT (SIZEOF (USEDIN (nu, '')) >= 1))) = 0;
END_RULE;
(*
```

Argument definition:

named_unit: identifies the set of all instances of **named_unit**.

Formal proposition:

WR1: For each instance of **named_unit**, there shall be a reference to the **named_unit** instance from an attribute of another entity.

5.2.5.54 dependent_instantiable_representation_item

The **dependent_instantiable_representation_item** rule specifies that all instances of **representation_item** are dependent on the usage to define another entity.

EXPRESS specification:

```
*)
RULE dependent_instantiable_representation_item FOR (representation_item);
```

WHERE

```
WR1: SIZEOF (QUERY (ri <* representation_item |
    NOT (SIZEOF (USEDIN (ri, '')) >= 1))) = 0;
END_RULE;
(*
```

Argument definition:

representation_item: identifies the set of all instances of **representation_item**.

Formal proposition:

WR1: For each instance of **representation_item**, there shall be a reference to the **representation_item** instance from an attribute of another entity.

5.2.5.55 dependent_instantiable_date_time_role

The **dependent_instantiable_date_time_role** rule specifies that all instances of **date_time_role** are dependent on the usage to define another entity.

EXPRESS specification:

```
*)
RULE dependent_instantiable_date_time_role FOR (date_time_role);
WHERE
    WR1: SIZEOF (QUERY (dtr <* date_time_role |
        NOT (SIZEOF (USEDIN (dtr, '')) >= 1))) = 0;
END_RULE;
(*
```

Argument definition:

date_time_role: identifies the set of all instances of **date_time_role**.

Formal proposition:

WR1: For each instance of **date_time_role**, there shall be a reference to the **date_time_role** instance from an attribute of another entity.

5.2.5.56 dependent_instantiable_person_and_organization_role

The **dependent_instantiable_person_and_organization_role** rule specifies that all instances of **person_and_organization_role** are dependent on the usage to define another entity.

EXPRESS specification:

```
*)
RULE dependent_instantiable_person_and_organization_role FOR
  (person_and_organization_role);
WHERE
  WR1: SIZEOF (QUERY (poar <* person_and_organization_role |
    NOT (SIZEOF (USEDIN (poar, '')) >= 1))) = 0;
END_RULE;
(*
```

Argument definition:

person_and_organization_role: identifies the set of all instances of **person_and_organization_role**.

Formal proposition:

WR1: For each instance of **person_and_organization_role**, there shall be a reference to the **person_and_organization_role** instance from an attribute of another entity.

5.2.5.57 dependent_instantiable_action_directive

The **dependent_instantiable_action_directive** rule specifies that all instances of **action_directive** are dependent on the usage to define another entity.

EXPRESS specification:

```
*)
RULE dependent_instantiable_action_directive FOR (action_directive);
WHERE
  WR1: SIZEOF (QUERY (ad <* action_directive |
    NOT (SIZEOF (USEDIN (ad, '')) >= 1))) = 0;
END_RULE;
(*
```

Argument definition:

action_directive: identifies the set of all instances of **action_directive**.

Formal proposition:

WR1: For each instance of **action_directive**, there shall be a reference to the **action_directive** instance from an attribute of another entity.

5.2.5.58 dependent_instantiable_security_classification_level

The **dependent_instantiable_security_classification_level** rule specifies that all instances of **security_classification_level** are dependent on the usage to define another entity.

EXPRESS specification:

```

*)
RULE dependent_instantiable_security_classification_level FOR
  (security_classification_level);
WHERE
  WR1: SIZEOF (QUERY (scl <* security_classification_level |
    NOT (SIZEOF (USEDIN (scl, '')) >= 1))) = 0;
END_RULE;
( *
```

Argument definition:

security_classification_level: identifies the set of all instances of **security_classification_level**.

Formal proposition:

WR1: For each instance of **security_classification_level**, there shall be a reference to the **security_classification_level** instance from an attribute of another entity.

5.2.5.59 dependent_instantiable_approval_status

The **dependent_instantiable_approval_status** rule specifies that all instances of **approval_status** are dependent on the usage to define another entity.

EXPRESS specification:

```

*)
RULE dependent_instantiable_approval_status FOR (approval_status);
WHERE
    WR1: SIZEOF (QUERY (ast <* approval_status |
        NOT (SIZEOF (USEDIN (ast, '')) >= 1))) = 0;
END_RULE;
( *

```

Argument definition:

approval_status: identifies the set of all instances of **approval_status**.

Formal proposition:

WR1: For each instance of **approval_status**, there shall be a reference to the **approval_status** instance from an attribute of another entity.

5.2.5.60 dependent_instantiable_document_type

The **dependent_instantiable_document_type** rule specifies that all instances of **document_type** are dependent on the usage to define another entity.

EXPRESS specification:

```

*)
RULE dependent_instantiable_document_type FOR (document_type);
WHERE
    WR1: SIZEOF (QUERY (dt <* document_type |
        NOT (SIZEOF (USEDIN (dt, '')) >= 1))) = 0;
END_RULE;
( *

```

Argument definition:

document_type: identifies the set of all instances of **document_type**.

Formal proposition:

WR1: For each instance of **document_type**, there shall be a reference to the **document_type** instance from an attribute of another entity.

5.2.5.61 dependent_instantiable_contract_type

The **dependent_instantiable_contract_type** rule specifies that all instances of **contract_type** are dependent on the usage to define another entity.

EXPRESS specification:

```
* )
RULE dependent_instantiable_contract_type FOR (contract_type);
WHERE
  WR1: SIZEOF (QUERY (ct <* contract_type |
    NOT (SIZEOF (USEDIN (ct, '')) >= 1))) = 0;
END_RULE;
( *
```

Argument definition:

contract_type: identifies the set of all instances of **contract_type**.

Formal proposition:

WR1: For each instance of **contract_type**, there shall be a reference to the **contract_type** instance from an attribute of another entity.

5.2.5.62 dependent_instantiable_certification_type

The **dependent_instantiable_certification_type** rule specifies that all instances of **certification_type** are dependent on the usage to define another entity.

EXPRESS specification:

```
* )
RULE dependent_instantiable_certification_type FOR (certification_type);
WHERE
  WR1: SIZEOF (QUERY (ct <* certification_type |
    NOT (SIZEOF (USEDIN (ct, '')) >= 1))) = 0;
END_RULE;
( *
```

Argument definition:

certification_type: identifies the set of all instances of **certification_type**.

Formal proposition:

WR1: For each instance of **certification_type**, there shall be a reference to the **certification_type** instance from an attribute of another entity.

5.2.5.63 product_concept_requires_configuration_item

The **product_concept_requires_configuration_item** rule specifies that every **product_concept** shall be referenced by at least one **configuration_item**. This rule enforces the requirement for every **product_concept** have at least one **configuration_item** in it.

EXPRESS specification:

```

*)
RULE product_concept_requires_configuration_item FOR
  (product_concept, configuration_item);
WHERE
  WR1: SIZEOF (QUERY (pc <* product_concept |
    NOT (SIZEOF (QUERY (ci <* configuration_item |
      pc ::= ci.item_concept))) >=1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

product_concept: identifies the set of all instances of **product_concept** entities.

configuration_item: identifies the set of all instances of **configuration_item** entities.

Formal propositions:

WR1: For each instance of **product_concept**, there shall be at least one instance of **configuration_item** that contains the instance of **product_concept** as the value of its **item_concept** attribute.

5.2.5.64 configuration_item_requires_person_organization

The **configuration_item_requires_person_organization** rule specifies that every **configuration_item** shall be referenced by exactly one **cc_design_person_and_organization_assignment**. This rule specifies the need for every **configuration_item** to have a configuration manager who is responsible for it. The meaning of **configuration_manager** is found in the **person_organization_assignment** entity's **role** attribute.

NOTE - The coordination of the different role values with the assignment of **person_organization_**-

assignment to different entities is specified in the **cc_design_person_and_organization_correlation** function. This function is invoked locally to **cc_design_person_and_organization_assignment**. See the function definition in 5.2.6.2.

EXPRESS specification:

```
*)
RULE configuration_item_requires_person_organization FOR
  (configuration_item,
   cc_design_person_and_organization_assignment);
WHERE
  WR1: SIZEOF (QUERY (ci <* configuration_item |
    NOT (SIZEOF (QUERY (ccdpoa <*
      cc_design_person_and_organization_assignment |
        ci IN ccdpoa.items )) = 1 ))) = 0;
END_RULE;
(*
```

Argument definitions:

configuration_item: identifies the set of all instances of **configuration_item** entities.

cc_design_person_and_organization_assignment: identifies the set of all instances of **cc_design_person_and_organization_assignment** entities.

Formal propositions:

WR1: For each instance of **configuration_item**, there shall be exactly one instance of **cc_design_person_and_organization_assignment** that contains the instance of **configuration_item** in its set of **items**.

5.2.5.65 subtype_mandatory_effectivity

The **subtype_mandatory_effectivity** rule specifies that each instance of the **effectivity** entities shall be a complex entity instance comprised of an instance of one of either **serial_numbered_effectivity**, **dated_effectivity** or **lot_effectivity** entity and an instance of **configuration_effectivity**.

EXPRESS specification:

```
*)
RULE subtype_mandatory_effectivity FOR (effectivity);
WHERE
  WR1: SIZEOF (QUERY (eff <* effectivity |
```

```

NOT ((SIZEOF ([ 'CONFIG_CONTROL_DESIGN.SERIAL_NUMBERED_EFFECTIVITY',
'CONFIG_CONTROL_DESIGN.LOT_EFFECTIVITY',
'CONFIG_CONTROL_DESIGN.DATED_EFFECTIVITY' ] *
  TYPEOF (eff)) = 1) AND
  ('CONFIG_CONTROL_DESIGN.CONFIGURATION_EFFECTIVITY' IN
    TYPEOF(eff)))) = 0;
END_RULE;
( *

```

Argument definitions:

effectivity: identifies the set of all instances of **effectivity** entities.

Formal propositions:

WR1: Each instance of **effectivity** shall be a **serial_numbered_effectivity**, **lot_effectivity** or **dated_effectivity** and a **configuration_effectivity** instance.

5.2.5.66 effectivity_requires_approval

The **effectivity_requires_approval** rule specifies that each instance of a **effectivity** shall be referenced by exactly one **cc_design_approval**. This rule enforces the requirement for each **effectivity** to have an approval.

EXPRESS specification:

```

*)
RULE effectivity_requires_approval FOR
  (effectivity, cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (eff <* effectivity |
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
      eff IN ccda.items )) = 1 ))) = 0;
END_RULE;
( *

```

Argument definitions:

effectivity: identifies the set of all instances of **effectivity** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **effectivity**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **effectivity** in its set of **items**.

5.2.5.67 configuration_item_requires_approval

The **configuration_item_requires_approval** rule specifies that each instance of a **configuration_item** shall be referenced by exactly one **cc_design_approval**. This rule enforces the requirement for each **configuration_item** to have an approval.

EXPRESS specification:

```

*)
RULE configuration_item_requires_approval FOR
  (configuration_item, cc_design_approval);
WHERE
  WR1: SIZEOF (QUERY (ci <* configuration_item
    NOT (SIZEOF (QUERY (ccda <* cc_design_approval |
      ci IN ccda.items )) = 1 ))) = 0;
END_RULE;
( *
```

Argument definitions:

configuration_item: identifies the set of all instances of **configuration_item** entities.

cc_design_approval: identifies the set of all instances of **cc_design_approval** entities.

Formal propositions:

WR1: For each instance of **configuration_item**, there shall be exactly one instance of **cc_design_approval** that contains the instance of **configuration_item** in its set of **items**.

5.2.5.68 coordinated_assembly_and_shape

The **coordinated_assembly_and_shape** rule specifies that the relationship between two **product_definition** entities which are an assembly and a component in a **next_assembly_usage_occurrence** and the relationship between two **shape_representation** entities which contain the representation of the shapes of the assembly and the component in a **shape_representation_relationship** must be explicitly

related through the **context_dependent_shape_representation**. This rule calls the function **assembly_shape_is_defined** which returns true if the assembly relationship and shape relationship are explicitly related.

EXPRESS specification:

```
*)
RULE coordinated_assembly_and_shape FOR
  (next_assembly_usage_occurrence);
WHERE
  WR1: SIZEOF (QUERY (nauo <* next_assembly_usage_occurrence |
    NOT (assembly_shape_is_defined (nauo, 'CONFIG_CONTROL_DESIGN'))))
    = 0;
END_RULE;
( *
```

Argument definitions:

next_assembly_usage_occurrence: identifies the set of all instances of **next_assembly_usage_occurrence** entities.

Formal propositions:

WR1: For each of instance of **next_assembly_usage_occurrence**, the **assembly_shape_is_defined** function shall be true.

5.2.5.69 subtype_mandatory_product_definition_usage

The **subtype_mandatory_product_definition_usage** rule specifies that all **product_definition_usage** entities shall be **assembly_component_usage** entities.

EXPRESS specification:

```
*)
RULE subtype_mandatory_product_definition_usage FOR
  (product_definition_usage);
WHERE
  WR1: SIZEOF (QUERY (pdu <* product_definition_usage |
    NOT ('CONFIG_CONTROL_DESIGN.' +
      'ASSEMBLY_COMPONENT_USAGE' IN TYPEOF (pdu)))) = 0;
END_RULE;
( *
```

Argument definitions:

product_definition_usage: identifies the set of all instances of **product_definition_usage** entities to be constrained.

Formal propositions:

WR1: Each instance of **product_definition_usage** shall be an **assembly_component_usage**.

5.2.5.70 acu_requires_security_classification

The **acu_requires_security_classification** rule specifies that every **assembly_component_usage** shall be referenced by exactly one **cc_design_security_classification**. This rule enforces the requirement for every **product_definition** which is the **related_product_definition** in a **assembly_component_usage** to have a security classification within the context of the **assembly_component_usage**.

EXPRESS specification:

```

*)
RULE acu_requires_security_classification FOR
  (assembly_component_usage,
    cc_design_security_classification);
WHERE
  WR1: SIZEOF (QUERY (acu <* assembly_component_usage |
    NOT (SIZEOF (QUERY (ccdsc <* cc_design_security_classification |
      acu IN ccdsc.items )) = 1 ))) = 0;
END_RULE;
( *
```

Argument definitions:

assembly_component_usage: identifies the set of all instances of **assembly_component_usage** entities to be constrained.

cc_design_security_classification: identifies the set of all instances of **cc_design_security_classification** entities to be constrained.

Formal propositions:

WR1: For each instance of **assembly_component_usage** there shall be exactly one instance of **cc_design_security_classification** that contains the instance of **assembly_component_usage** in its set of **items**.

5.2.5.71 geometric_representation_item_3d

The **geometric_representation_item_3d** rule specifies that every **geometric_representation_item** must be founded within a **geometric_representation_context** that has a dimensionality of 3 except for use in defining the **pcurve** entity. This rule constrains all geometry to be three dimensional. The **pcurve** entity is an exception because it must be founded in a 2 dimensional context which is the parameter space of a surface.

EXPRESS specification:

```

*)
RULE geometric_representation_item_3d FOR
  (geometric_representation_item);
WHERE
  WR1: SIZEOF (QUERY (gri <* geometric_representation_item |
    NOT ((dimension_of (gri) = 3) OR
      (SIZEOF (QUERY (ur <* using_representations(gri) |
        'CONFIG_CONTROL_DESIGN.DEFINITIONAL_REPRESENTATION'
        IN TYPEOF(ur))) > 0)))) = 0;
END_RULE;
( *

```

Argument definitions:

geometric_representation_item: identifies the set of all instances of **geometric_representation_item** entities to be constrained.

Formal propositions:

WR1: For each instance of **geometric_representation_item**, the value of **dim** shall be three or the **geometric_representation_item** shall be used as an item in a **definitional_representation**.

NOTE - The use of the **definitional_representation** is to define points or curves in the parametric space of a surface for use by the **pcurve**.

5.2.5.72 dependent_instantiable_parametric_representation_context

The **dependent_instantiable_parametric_representation_context** rule specifies that all instances of **parametric_representation_context** are dependent on the usage to define another entity.

EXPRESS specification:

```
*)
RULE dependent_instantiable_parametric_representation_context FOR
  (parametric_representation_context);
WHERE
  WR1: SIZEOF (QUERY (prc <* parametric_representation_context |
    NOT (SIZEOF (USEDIN (prc, '')) >= 1))) = 0;
END_RULE;
(*
```

Argument definition:

parametric_representation_context: identifies the set of all instances of **parametric_representation_context**.

Formal proposition:

WR1: For each instance of **parametric_representation_context**, there shall be a reference to the **parametric_representation_context** instance from an attribute of another entity.

5.2.5.73 subtype_mandatory_shape_representation

The **subtype_mandatory_shape_representation** rule requires all **shape_representation** entities to be either **geometrically_bounded_wireframe_shape_representation**, **geometrically_bounded_surface_shape_representation**, **edge_based_wireframe_shape_representation**, **shell_based_wireframe_shape_representation**, **manifold_surface_shape_representation**, **faceted_brep_shape_representation** or **advanced_brep_shape_representation** or contain only **axis2_placement_3d** entities in their respective sets of **items** or be the representation of a **shape_aspect** or a relationship between two **shape_aspects**. The rule defines the constraint that establishes the different types of representations allowed for shapes in this part of ISO 10303.

EXPRESS specification:

```
*)
RULE subtype_mandatory_shape_representation FOR
  (shape_representation);
```

WHERE

```

WR1: SIZEOF (QUERY (sr <* shape_representation |
  NOT ((SIZEOF (['CONFIG_CONTROL_DESIGN.' +
    'ADVANCED_BREP_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.FACETED_BREP_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.MANIFOLD_SURFACE_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.EDGE_BASED_WIREFRAME_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.' +
    'GEOMETRICALLY_BOUNDED_SURFACE_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.' +
    'GEOMETRICALLY_BOUNDED_WIREFRAME_SHAPE_REPRESENTATION']) *
  TYPEOF (sr)) = 1) OR
  (SIZEOF (QUERY (it <* sr\representation.items |
    NOT ('CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D' IN TYPEOF (it))))
  = 0) OR
  (SIZEOF (QUERY (sdr <* QUERY (pdr <* USEDIN (sr,
    'CONFIG_CONTROL_DESIGN.PROPERTY_DEFINITION_REPRESENTATION.' +
    'USED_REPRESENTATION') |
    'CONFIG_CONTROL_DESIGN.SHAPE_DEFINITION_REPRESENTATION' IN
    TYPEOF (pdr)) |
    NOT (SIZEOF (['CONFIG_CONTROL_DESIGN.SHAPE_ASPECT',
    'CONFIG_CONTROL_DESIGN.SHAPE_ASPECT_RELATIONSHIP'] * TYPEOF
    (sdr.definition.definition)) = 1))) = 0))) = 0;
END_RULE;
(*

```

Argument definitions:

shape_representation: identifies the set of all instances of **shape_representation** entities to be constrained.

Formal propositions:

WR1: Each instance of **shape_representation** shall be either a **geometrically_bounded_wireframe_representation**, **geometrically_bounded_surface_representation**, **edge_based_wireframe_representation**, **shell_based_wireframe_representation**, **manifold_surface_with_topology_representation**, **faceted_brep_representation** or **advanced_brep_representation** or contain only **axis2_placement_3d** entities in its set of **items** or be the representation of a **shape_aspect** or **shape_aspect_relationship**.

5.2.5.74 subtype_mandatory_representation

The **subtype_mandatory_representation** rule requires all **representation** entities to be **shape_-representations**.

EXPRESS specification:

```
*)
RULE subtype_mandatory_representation FOR (representation);
WHERE
  WR1: SIZEOF (QUERY (rep <* representation |
    NOT ('CONFIG_CONTROL_DESIGN.SHAPE_REPRESENTATION' IN
      TYPEOF (rep)))) = 0;
END_RULE;
(*
```

Argument definitions:

representation: identifies the set of all instances of **representation** entities to be constrained.

Formal propositions:

WR1: Each instance of **representation** shall be a **shape_representation**.

5.2.5.75 subtype_mandatory_representation_context

The **subtype_mandatory_representation_context** rule requires all **representation_context** entities to be **geometric_representation_contexts**.

EXPRESS specification:

```
*)
RULE subtype_mandatory_representation_context FOR (representation_context);
WHERE
  WR1: SIZEOF (QUERY (rep_cntxt <* representation_context |
    NOT ('CONFIG_CONTROL_DESIGN.GEOMETRIC_REPRESENTATION_CONTEXT' IN
      TYPEOF (rep_cntxt)))) = 0;
END_RULE;
(*
```

Argument definitions:

representation_context: identifies the set of all instances of **representation_context** entities to be constrained.

Formal propositions:

WR1: Each instance of **representation_context** shall be a **geometric_representation_context**.

5.2.5.76 no_shape_for_make_from

The **no_shape_for_make_from** rule ensures that **product_definition_relationship** entities that are **design_make_from_relationship** entities do not have shape defined for them. This rule works by disallowing the use of a **design_make_from_relationship** entity in a **product_definition_shape** entity which establishes the shape of a part or the relative shape of a constituent part in an assembly.

EXPRESS specification:

```

*)
RULE no_shape_for_make_from FOR
  (design_make_from_relationship);
WHERE
  WR1: SIZEOF (QUERY (dmfr <* design_make_from_relationship |
    NOT (SIZEOF (QUERY (pd <* USEDIN (dmfr, 'CONFIG_CONTROL_DESIGN.' +
      'PROPERTY_DEFINITION.DEFINITION') |
      'CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION_SHAPE' IN TYPEOF (pd))) =
    0))) = 0;
END_RULE;
( *
```

Argument definitions:

design_make_from_relationship: identifies all instances of the **design_make_from_relationship** entity that are to be constrained.

Formal propositions:

WR1: No **design_make_from_relationship** entities shall be referenced by the **definition** attribute of a **property_definition** that is a **product_definition_shape**.

5.2.5.77 no_shape_for_supplied_part

The **no_shape_for_supplied_part** rule ensures that **product_definition_relationship** entities that are **supplied_part_relationship** entities do not have shape defined for them. This rule works by disallowing the use of a **supplied_part_relationship** entity in a **product_definition_shape** entity which establishes the shape of a part or the relative shape of a constituent part in an assembly.

EXPRESS specification:

```
*)
RULE no_shape_for_supplied_part FOR
  (supplied_part_relationship);
WHERE
  WR1: SIZEOF (QUERY (spr <* supplied_part_relationship |
    NOT (SIZEOF (QUERY (pd <* USEDIN (spr, 'CONFIG_CONTROL_DESIGN.' +
      'PROPERTY_DEFINITION.DEFINITION') |
      'CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION_SHAPE' IN TYPEOF (pd))) =
    0))) = 0;
END_RULE;
(*
```

Argument definitions:

supplied_part_relationship: identifies all instances of the **supplied_part_relationship** entity that are to be constrained.

Formal propositions:

WR1: No **supplied_part_relationship** entities shall be referenced by the **definition** attribute of a **property_definition** that is a **product_definition_shape**.

5.2.5.78 approval_date_time_constraints

The **approval_date_time_constraints** specifies that each instance of **approval_date_time** shall only reference a **date_and_time** instance. This rule enforces the requirement that dates be specified with a time.

EXPRESS specification:

```
*)
RULE approval_date_time_constraints FOR (approval_date_time);
WHERE
  WR1: SIZEOF (QUERY (adt <* approval_date_time |
```

```

    NOT (SIZEOF (TYPEOF(adtt.date_time) *
    [ 'CONFIG_CONTROL_DESIGN.DATE_AND_TIME' ]) = 1)))=0;
END_RULE;
( *
```

Argument definitions:

approval_date_time: identifies the set of all instances of **approval_date_time** entities.

Formal propositions:

WR1: For each instance of **approval_date_time**, the **date_time** attribute shall reference an instance of **date_and_time**.

5.2.5.79 approval_person_organization_constraints

The **approval_person_organization_constraints** specifies that each instance of **approval_person_organization** shall only reference a **person_and_organization** instance. This rule enforces the requirement that people be specified within an organization.

EXPRESS specification:

```

*)
RULE approval_person_organization_constraints FOR
  (approval_person_organization);
WHERE
  WR1: SIZEOF (QUERY (apo <* approval_person_organization |
    NOT (SIZEOF (TYPEOF(apo.person_organization) *
    [ 'CONFIG_CONTROL_DESIGN.PERSON_AND_ORGANIZATION' ]) = 1)))=0;
END_RULE;
( *
```

Argument definitions:

approval_person_organization: identifies the set of all instances of **approval_person_organization** entities.

Formal propositions:

WR1: For each instance of **approval_person_organization**, the **person_organization** attribute shall reference an instance of **person_and_organization**.

5.2.6 Configuration controlled design functions

5.2.6.1 unique_version_change_order

The **unique_version_change_order** boolean function accepts an **action_execution** as input and returns true if the **ordered_action** invoked by the **action_execution** incorporates **requested_action** entities which reference different **product_definition_formation** entities and those **product_definition_formation** entities reference different **product** entities. This function will return false if the **requested_action** entities reference **product_definition_formation** entities that are incorporated by an **action_execution** and those **product_definition_formation** entities reference the same **product**. This function will be true if a change changes multiple versions of a part, and those versions are versions of different parts. A single change may not change different versions of a single part.

EXPRESS specification:

```
*)
FUNCTION unique_version_change_order (c : action) : BOOLEAN;
  LOCAL
    ords      : action_directive := c\directed_action.directive;
    assign    : SET OF change_request := [];
    versions  : SET OF product_definition_formation := [];
  END_LOCAL;

  -- build the set of change_requests that are the assigned
  -- versioned_action_requests incorporated by the action_directive

  REPEAT i := 1 TO SIZEOF(ords.requests);
    assign := assign + QUERY (ara <* bag_to_set (USEDIN (ords.requests[i],
      'CONFIG_CONTROL_DESIGN.ACTION_REQUEST_ASSIGNMENT.' +
      'ASSIGNED_ACTION_REQUEST')) |
      'CONFIG_CONTROL_DESIGN.CHANGE_REQUEST' IN TYPEOF (ara));
  END_REPEAT;

  -- gather the product_definition_formation that are referenced by the
  -- change_requests

  REPEAT k := 1 TO SIZEOF(assign);
    versions := versions + assign[k].items;
  END_REPEAT;

  -- check that no product_definition_formation reference the same
  -- instance of product
```

```

RETURN (SIZEOF (QUERY (vers <* versions |
    NOT (SIZEOF (QUERY (other_vers <* versions - vers |
        vers.of_product :=: other_vers.of_product))) = 0))) = 0);
END_FUNCTION;
(*

```

Argument definitions:

c: (input) identifies the **directed_action** to be checked.

5.2.6.2 cc_design_person_and_organization_correlation

The **cc_design_person_and_organization_correlation** boolean function returns true if the **name** attribute value of the **person_organization_role** entity is coordinated with the type of entity selected in the **items** of a **cc_design_person_and_organization_assignment** entity.

The function states the following:

- a person and organization assigned to a **change_request** or **start_request** may have the role of "request_recipient";
- a person and organization assigned to a **change_request**, **start_request**, **change**, or **start_work** may have the role of "initiator";
- a person and organization assigned to a **product_definition_formation** or a **product_definition** may have the role of "creator";
- a person and organization assigned to a **product_definition_formation** may have the role of "part_supplier";
- a person and organization assigned to a **product_definition_formation** may have the role of "design_supplier";
- a person and organization assigned to a **product** may have the role of "design_owner";
- a person and organization assigned to a **configuration_item** may have the role of "configuration_manager";
- a person and organization assigned to a **contract** may have the role of "contractor";
- a person and organization assigned to a **security_classification** may have the role of "classification_officer".

EXPRESS specification:

```

*)
FUNCTION cc_design_person_and_organization_correlation
  (e : cc_design_person_and_organization_assignment ) : BOOLEAN;
LOCAL
  po_role : STRING;
END_LOCAL;
  po_role := e\person_and_organization_assignment.role.name;
CASE po_role OF
  'request_recipient'      : IF SIZEOF (e.items) <>
                             SIZEOF (QUERY (x <* e.items |
                             SIZEOF(['CONFIG_CONTROL_DESIGN.' +
                             'CHANGE_REQUEST',
                             'CONFIG_CONTROL_DESIGN.' +
                             'START_REQUEST'] *
                             TYPEOF (x)) = 1))
                             THEN RETURN(FALSE);
                             END_IF;
  'initiator'              : IF SIZEOF (e.items) <>
                             SIZEOF (QUERY (x <* e.items |
                             SIZEOF(['CONFIG_CONTROL_DESIGN.' +
                             'CHANGE_REQUEST',
                             'CONFIG_CONTROL_DESIGN.' +
                             'START_REQUEST',
                             'CONFIG_CONTROL_DESIGN.' +
                             'START_WORK',
                             'CONFIG_CONTROL_DESIGN.' +
                             'CHANGE'] *
                             TYPEOF (x)) = 1))
                             THEN RETURN(FALSE);
                             END_IF;
  'creator'                : IF SIZEOF (e.items) <>
                             SIZEOF (QUERY (x <* e.items |
                             SIZEOF (['CONFIG_CONTROL_DESIGN.' +
                             'PRODUCT_DEFINITION_FORMATION',
                             'CONFIG_CONTROL_DESIGN.' +
                             'PRODUCT_DEFINITION'] *
                             TYPEOF (x)) = 1))
                             THEN RETURN (FALSE);
                             END_IF;
  'part_supplier'          : IF SIZEOF (e.items) <>

```

```

        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'PRODUCT_DEFINITION_FORMATION'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

'design_supplier' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'PRODUCT_DEFINITION_FORMATION'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

'design_owner' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.PRODUCT'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

'configuration_manager' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'CONFIGURATION_ITEM'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

'contractor' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.CONTRACT'
        IN TYPEOF (x))) THEN RETURN(FALSE);
    END_IF;

'classification_officer' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'SECURITY_CLASSIFICATION'
        IN TYPEOF (x))) THEN RETURN(FALSE);
    END_IF;

    OTHERWISE : RETURN(TRUE);
END_CASE;
RETURN (TRUE);
END_FUNCTION;
(*

```

Argument definitions:

e: (input) identifies the **cc_design_person_and_organization_assignment** to be checked.

5.2.6.3 cc_design_date_time_correlation

The **cc_design_date_time_correlation** boolean function returns true if the **name** attribute value of the **date_time_role** entity is coordinated with the type of entity selected in the **items** of the **cc_design_date_and_time_assignment** entity.

The function states the following:

- a date and time assigned to a **product_definition** may have the role of "creation_date";
- a date and time assigned to a **change_request** or **start_request** may have the role of "request_date";
- a date and time assigned to a **change** or a **start_work** may have the role of "release_date";
- a date and time assigned to a **change** or a **start_work** may have the role of "start_date";
- a date and time assigned to an **approval_date_time** may have the role of "sign_off_date";
- a date and time assigned to a **contract** may have the role of "contract_date";
- a date and time assigned to a **certification** may have the role of "certification_date";
- a date and time assigned to a **security_classification** may have the role of "classification_date";
- a date and time assigned to a **security_classification** may have the role of "declassification_date".

EXPRESS specification:

```

*)
FUNCTION cc_design_date_time_correlation
  (e : cc_design_date_and_time_assignment ) : BOOLEAN;
  LOCAL
    dt_role : STRING;
  END_LOCAL;
  dt_role := e\date_and_time_assignment.role.name;

```

```

CASE dt_role OF
  'creation_date'      : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        'CONFIG_CONTROL_DESIGN.' +
                        'PRODUCT_DEFINITION'
                        IN TYPEOF (x)))
                        THEN RETURN(FALSE);
                        END_IF;
  'request_date'      : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        SIZEOF (
                        ['CONFIG_CONTROL_DESIGN.CHANGE_REQUEST',
                        'CONFIG_CONTROL_DESIGN.START_REQUEST'] *
                        TYPEOF (x)) = 1))
                        THEN RETURN(FALSE);
                        END_IF;
  'release_date'      : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        SIZEOF (
                        ['CONFIG_CONTROL_DESIGN.CHANGE',
                        'CONFIG_CONTROL_DESIGN.START_WORK'] *
                        TYPEOF (x)) = 1))
                        THEN RETURN(FALSE);
                        END_IF;
  'start_date'        : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        SIZEOF (
                        ['CONFIG_CONTROL_DESIGN.CHANGE',
                        'CONFIG_CONTROL_DESIGN.START_WORK'] *
                        TYPEOF (x)) = 1))
                        THEN RETURN(FALSE);
                        END_IF;
  'sign_off_date'     : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        'CONFIG_CONTROL_DESIGN.' +
                        'APPROVAL_PERSON_ORGANIZATION'
                        IN TYPEOF (x)))
                        THEN RETURN(FALSE);
                        END_IF;
  'contract_date'     : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        'CONFIG_CONTROL_DESIGN.CONTRACT'

```

```

        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;
'certification_date' : IF SIZEOF (e.items) <>
    SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.CERTIFICATION'
        IN TYPEOF (x)))
    THEN RETURN(FALSE);
    END_IF;
'classification_date' : IF SIZEOF (e.items) <>
    SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'SECURITY_CLASSIFICATION'
        IN TYPEOF (x)))
    THEN RETURN(FALSE);
    END_IF;
'declassification_date' : IF SIZEOF (e.items) <>
    SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'SECURITY_CLASSIFICATION'
        IN TYPEOF (x)))
    THEN RETURN(FALSE);
    END_IF;
    OTHERWISE : RETURN(TRUE);
END_CASE;
RETURN (TRUE);
END_FUNCTION;
( *

```

Argument definitions:

e: (input) identifies the **cc_design_date_and_time_assignment** to be checked.

5.2.6.4 assembly_shape_is_defined

The **assembly_shape_is_defined** function accepts a **next_assembly_usage_occurrence** as input and returns a boolean result. The function will return true if the shape is defined for the **product_definition** which is the **related_product_definition** and the shape is defined for the **product_definition** which is the **relating_product_definition** in the **next_assembly_usage_occurrence**, and the two shapes are related through a **shape_representation_relationship**, and the two relationships are related through **context_dependent_shape_representation**. The function will also return true if the shape of the **related_product_definition** or the **relating_product_definition** is not defined.

The only time this function will return false is when the shapes are defined for the **related_product_definition** and the **relating_product_definition** and related through **shape_representation_relationship**, but the **next_assembly_usage_occurrence** and the **shape_representation_relationship** are not explicitly related through **context_dependent_shape_representation**.

EXPRESS specification:

```

*)
FUNCTION assembly_shape_is_defined(
    assy: next_assembly_usage_occurrence;
    schma: STRING
): BOOLEAN;

LOCAL
    srr_set    : SET OF shape_representation_relationship := [];
    i          : INTEGER;
    j          : INTEGER;
    sdr_set    : SET OF shape_definition_representation := [];
    pr1_set    : SET OF property_definition := [];
    pdrel_set  : SET OF product_definition_relationship := [];
    pr2_set    : SET OF property_definition := [];
END_LOCAL;
pr1_set := bag_to_set(USEDIN(assy.related_product_definition,schma +
    '.PROPERTY_DEFINITION.DEFINITION'));
REPEAT i := 1 TO HIINDEX(pr1_set) BY 1;
    sdr_set := sdr_set + QUERY ( pdr <* USEDIN(pr1_set[i],schma +
        '.PROPERTY_DEFINITION_REPRESENTATION.DEFINITION') | ((schma +
        '.SHAPE_DEFINITION_REPRESENTATION') IN TYPEOF(pdr)) );
END_REPEAT;
pdrel_set := bag_to_set(USEDIN(assy.related_product_definition,schma +
    '.PRODUCT_DEFINITION_RELATIONSHIP.' +
    'RELATED_PRODUCT_DEFINITION'));
REPEAT j := 1 TO HIINDEX(pdrel_set) BY 1;
    pr2_set := pr2_set + USEDIN(pdrel_set[j],schma +
        '.PROPERTY_DEFINITION.DEFINITION');
END_REPEAT;
REPEAT i := 1 TO HIINDEX(pr2_set) BY 1;
    sdr_set := sdr_set + QUERY ( pdr <* USEDIN(pr2_set[i],schma +
        '.PROPERTY_DEFINITION_REPRESENTATION.DEFINITION') | ((schma +
        '.SHAPE_DEFINITION_REPRESENTATION') IN TYPEOF(pdr)) );
END_REPEAT;
IF SIZEOF(sdr_set) > 0 THEN

```

```

REPEAT i := 1 TO HIINDEX(sdr_set) BY 1;
  srr_set := QUERY ( rr <* bag_to_set(USEDIN(sdr_set[i]\
    property_definition_representation.used_representation,schma +
    '.REPRESENTATION_RELATIONSHIP.REP_2')) | ((schma +
    '.SHAPE_REPRESENTATION_RELATIONSHIP') IN TYPEOF(rr)) );
  IF SIZEOF(srr_set) > 0 THEN
    REPEAT j := 1 TO HIINDEX(srr_set) BY 1;
      IF SIZEOF(QUERY ( pdr <* bag_to_set(USEDIN(srr_set[j]\
        representation_relationship.rep_1,schma +
        '.PROPERTY_DEFINITION_REPRESENTATION.USED_REPRESENTATION'))
        | ((schma + '.SHAPE_DEFINITION_REPRESENTATION') IN TYPEOF(
        pdr)) ) * QUERY ( pdr <* bag_to_set(USEDIN(assy.\
        relating_product_definition,schma +
        '.PROPERTY_DEFINITION_REPRESENTATION.DEFINITION')) | ((
        schma + '.SHAPE_DEFINITION_REPRESENTATION')
        IN TYPEOF(pdr)) )) >= 1 THEN
        IF SIZEOF(QUERY ( cdsr <* USEDIN(srr_set[j],schma +
          '.CONTEXT_DEPENDENT_SHAPE_REPRESENTATION.' +
          'REPRESENTATION_RELATION') | (NOT (cdsr\
            context_dependent_shape_representation.
            represented_product_relation\property_definition.
            definition :=: assy))) > 0 THEN RETURN(FALSE);
        END_IF;
      END_IF;
    END_REPEAT;
  END_IF;
END_REPEAT;
END_IF;
RETURN(TRUE);
END_FUNCTION; -- assembly_shape_is_defined
(*)

```

Argument definitions:

assy: (input) identifies the **next_assembly_usage_occurrence** for which the relationships are to be checked.

EXPRESS specification:

```

*)
END_SCHEMA; --config_control_design
(*)

```

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

This Page Intentionally Left Blank

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

This Page Intentionally Left Blank

- solid_angle_measure_with_unit;
- solid_angle_unit;
- solid_model;
- specified_higher_usage_occurrence;
- spherical_surface;
- start_request;
- start_work;
- supplied_part_relationship;
- surface;
- surface_of_linear_extrusion;
- surface_of_revolution;
- swept_surface;
- topological_representation_item;
- uncertainty_measure_with_unit;
- uniform_curve;
- uniform_surface;
- vector;
- versioned_action_request;
- vertex;
- vertex_loop;
- vertex_point;
- volume_measure_with_unit;
- volume_unit;
- week_of_year_and_day_date.

STANDARDSISO.COM : Click to view the full PDF of ISO 10303-203:1994/Amd 1:2000

Annex A (normative)

AIM EXPRESS expanded listing

*)

```
SCHEMA config_control_design;
```

```
CONSTANT
```

```
dummy_gri : geometric_representation_item := representation_item('') ||  
           geometric_representation_item();
```

```
dummy_tri : topological_representation_item := representation_item('')  
           || topological_representation_item();
```

```
END_CONSTANT;
```

```
TYPE ahead_or_behind = ENUMERATION OF
```

```
  (ahead,  
   behind);
```

```
END_TYPE; -- ahead_or_behind
```

```
TYPE approved_item = SELECT
```

```
  (product_definition_formation,  
   product_definition,  
   configuration_effectivity,  
   configuration_item,  
   security_classification,  
   change_request,  
   change,  
   start_request,  
   start_work,  
   certification,  
   contract);
```

```
END_TYPE; -- approved_item
```

```
TYPE area_measure = REAL;
```

```
END_TYPE; -- area_measure
```

```
TYPE axis2_placement = SELECT
```

```
  (axis2_placement_2d,  
   axis2_placement_3d);
```

```
END_TYPE; -- axis2_placement
```

```
TYPE b_spline_curve_form = ENUMERATION OF
  (polyline_form,
   circular_arc,
   elliptic_arc,
   parabolic_arc,
   hyperbolic_arc,
   unspecified);
END_TYPE; -- b_spline_curve_form
```

```
TYPE b_spline_surface_form = ENUMERATION OF
  (plane_surf,
   cylindrical_surf,
   conical_surf,
   spherical_surf,
   toroidal_surf,
   surf_of_revolution,
   ruled_surf,
   generalised_cone,
   quadric_surf,
   surf_of_linear_extrusion,
   unspecified);
END_TYPE; -- b_spline_surface_form
```

```
TYPE boolean_operand = SELECT
  (solid_model);
END_TYPE; -- boolean_operand
```

```
TYPE certified_item = SELECT
  (supplied_part_relationship);
END_TYPE; -- certified_item
```

```
TYPE change_request_item = SELECT
  (product_definition_formation);
END_TYPE; -- change_request_item
```

```
TYPE characterized_definition = SELECT
  (characterized_product_definition,
   shape_definition);
END_TYPE; -- characterized_definition
```

```
TYPE characterized_product_definition = SELECT
  (product_definition,
```

```
product_definition_relationship);  
END_TYPE; -- characterized_product_definition
```

```
TYPE classified_item = SELECT  
  (product_definition_formation,  
   assembly_component_usage);  
END_TYPE; -- classified_item
```

```
TYPE context_dependent_measure = REAL;  
END_TYPE; -- context_dependent_measure
```

```
TYPE contracted_item = SELECT  
  (product_definition_formation);  
END_TYPE; -- contracted_item
```

```
TYPE count_measure = NUMBER;  
END_TYPE; -- count_measure
```

```
TYPE curve_on_surface = SELECT  
  (pcurve,  
   surface_curve,  
   composite_curve_on_surface);  
END_TYPE; -- curve_on_surface
```

```
TYPE date_time_item = SELECT  
  (product_definition,  
   change_request,  
   start_request,  
   change,  
   start_work,  
   approval_person_organization,  
   contract,  
   security_classification,  
   certification);  
END_TYPE; -- date_time_item
```

```
TYPE date_time_select = SELECT  
  (date,  
   local_time,  
   date_and_time);  
END_TYPE; -- date_time_select
```

```
TYPE day_in_month_number = INTEGER;
END_TYPE; -- day_in_month_number

TYPE day_in_week_number = INTEGER;
WHERE
    wr1: ((1 <= SELF) AND (SELF <= 7));
END_TYPE; -- day_in_week_number

TYPE day_in_year_number = INTEGER;
END_TYPE; -- day_in_year_number

TYPE descriptive_measure = STRING;
END_TYPE; -- descriptive_measure

TYPE dimension_count = INTEGER;
WHERE
    wr1: (SELF > 0);
END_TYPE; -- dimension_count

TYPE founded_item_select = SELECT
    (founded_item,
     representation_item);
END_TYPE; -- founded_item_select

TYPE geometric_set_select = SELECT
    (point,
     curve,
     surface);
END_TYPE; -- geometric_set_select

TYPE hour_in_day = INTEGER;
WHERE
    wr1: ((0 <= SELF) AND (SELF < 24));
END_TYPE; -- hour_in_day

TYPE identifier = STRING;
END_TYPE; -- identifier

TYPE knot_type = ENUMERATION OF
    (uniform_knots,
     unspecified,
     quasi_uniform_knots,
```

```

        piecewise_bezier_knots);
END_TYPE; -- knot_type

TYPE label = STRING;
END_TYPE; -- label

TYPE length_measure = REAL;
END_TYPE; -- length_measure

TYPE list_of_reversible_topology_item = LIST [0:?] OF
    reversible_topology_item;
END_TYPE; -- list_of_reversible_topology_item

TYPE mass_measure = REAL;
END_TYPE; -- mass_measure

TYPE measure_value = SELECT
    (length_measure,
     mass_measure,
     plane_angle_measure,
     solid_angle_measure,
     area_measure,
     volume_measure,
     parameter_value,
     context_dependent_measure,
     descriptive_measure,
     positive_length_measure,
     positive_plane_angle_measure,
     count_measure);
END_TYPE; -- measure_value

TYPE minute_in_hour = INTEGER;
WHERE
    wr1: ((0 <= SELF) AND (SELF <= 59));
END_TYPE; -- minute_in_hour

TYPE month_in_year_number = INTEGER;
WHERE
    wr1: ((1 <= SELF) AND (SELF <= 12));
END_TYPE; -- month_in_year_number

```

```
TYPE parameter_value = REAL;  
END_TYPE; -- parameter_value
```

```
TYPE pcurve_or_surface = SELECT  
  (pcurve,  
   surface);  
END_TYPE; -- pcurve_or_surface
```

```
TYPE person_organization_item = SELECT  
  (change,  
   start_work,  
   change_request,  
   start_request,  
   configuration_item,  
   product,  
   product_definition_formation,  
   product_definition,  
   contract,  
   security_classification);  
END_TYPE; -- person_organization_item
```

```
TYPE person_organization_select = SELECT  
  (person,  
   organization,  
   person_and_organization);  
END_TYPE; -- person_organization_select
```

```
TYPE plane_angle_measure = REAL;  
END_TYPE; -- plane_angle_measure
```

```
TYPE positive_length_measure = length_measure;  
WHERE  
  wr1: (SELF > 0);  
END_TYPE; -- positive_length_measure
```

```
TYPE positive_plane_angle_measure = plane_angle_measure;  
WHERE  
  wr1: (SELF > 0);  
END_TYPE; -- positive_plane_angle_measure
```

```
TYPE preferred_surface_curve_representation = ENUMERATION OF  
  (curve_3d,
```

```
    pcurve_s1,
    pcurve_s2);
END_TYPE; -- preferred_surface_curve_representation

TYPE reversible_topology = SELECT
    (reversible_topology_item,
    list_of_reversible_topology_item,
    set_of_reversible_topology_item);
END_TYPE; -- reversible_topology

TYPE reversible_topology_item = SELECT
    (edge,
    path,
    face,
    face_bound,
    closed_shell,
    open_shell);
END_TYPE; -- reversible_topology_item

TYPE second_in_minute = REAL;
WHERE
    wr1: ((0 <= SELF) AND (SELF < 60));
END_TYPE; -- second_in_minute

TYPE set_of_reversible_topology_item = SET [0:?] OF
    reversible_topology_item;
END_TYPE; -- set_of_reversible_topology_item

TYPE shape_definition = SELECT
    (product_definition_shape,
    shape_aspect,
    shape_aspect_relationship);
END_TYPE; -- shape_definition

TYPE shell = SELECT
    (vertex_shell,
    wire_shell,
    open_shell,
    closed_shell);
END_TYPE; -- shell
```

TYPE si_prefix = ENUMERATION OF

(exa,
peta,
tera,
giga,
mega,
kilo,
hecto,
deca,
deci,
centi,
milli,
micro,
nano,
pico,
femto,
atto);

END_TYPE; -- si_prefix

TYPE si_unit_name = ENUMERATION OF

(metre,
gram,
second,
ampere,
kelvin,
mole,
candela,
radian,
steradian,
hertz,
newton,
pascal,
joule,
watt,
coulomb,
volt,
farad,
ohm,
siemens,
weber,
tesla,
henry,

```
        degree_celsius,  
        lumen,  
        lux,  
        becquerel,  
        gray,  
        sievert);  
END_TYPE; -- si_unit_name  
  
TYPE solid_angle_measure = REAL;  
END_TYPE; -- solid_angle_measure  
  
TYPE source = ENUMERATION OF  
    (made,  
     bought,  
     not_known);  
END_TYPE; -- source  
  
TYPE specified_item = SELECT  
    (product_definition,  
     shape_aspect);  
END_TYPE; -- specified_item  
  
TYPE start_request_item = SELECT  
    (product_definition_formation);  
END_TYPE; -- start_request_item  
  
TYPE supported_item = SELECT  
    (action_directive,  
     action,  
     action_method);  
END_TYPE; -- supported_item  
  
TYPE surface_model = SELECT  
    (shell_based_surface_model);  
END_TYPE; -- surface_model  
  
TYPE text = STRING;  
END_TYPE; -- text  
  
TYPE transformation = SELECT  
    (item_defined_transformation,
```

```
        functionally_defined_transformation);
END_TYPE; -- transformation

TYPE transition_code = ENUMERATION OF
    (discontinuous,
     continuous,
     cont_same_gradient,
     cont_same_gradient_same_curvature);
END_TYPE; -- transition_code

TYPE trimming_preference = ENUMERATION OF
    (cartesian,
     parameter,
     unspecified);
END_TYPE; -- trimming_preference

TYPE trimming_select = SELECT
    (cartesian_point,
     parameter_value);
END_TYPE; -- trimming_select

TYPE unit = SELECT
    (named_unit);
END_TYPE; -- unit

TYPE vector_or_direction = SELECT
    (vector,
     direction);
END_TYPE; -- vector_or_direction

TYPE volume_measure = REAL;
END_TYPE; -- volume_measure

TYPE week_in_year_number = INTEGER;
WHERE
    wr1: ((1 <= SELF) AND (SELF <= 53));
END_TYPE; -- week_in_year_number

TYPE wireframe_model = SELECT
    (shell_based_wireframe_model,
     edge_based_wireframe_model);
END_TYPE; -- wireframe_model
```

```
TYPE work_item = SELECT
  (product_definition_formation);
END_TYPE; -- work_item

TYPE year_number = INTEGER;
END_TYPE; -- year_number

ENTITY action;
  name          : label;
  description    : text;
  chosen_method : action_method;
END_ENTITY; -- action

ENTITY action_assignment
  ABSTRACT SUPERTYPE;
  assigned_action : action;
END_ENTITY; -- action_assignment

ENTITY action_directive;
  name          : label;
  description    : text;
  analysis       : text;
  comment        : text;
  requests       : SET [1:?] OF versioned_action_request;
END_ENTITY; -- action_directive

ENTITY action_method;
  name          : label;
  description    : text;
  consequence    : text;
  purpose        : text;
END_ENTITY; -- action_method

ENTITY action_request_assignment
  ABSTRACT SUPERTYPE;
  assigned_action_request : versioned_action_request;
END_ENTITY; -- action_request_assignment

ENTITY action_request_solution;
  method : action_method;
  request : versioned_action_request;
END_ENTITY; -- action_request_solution
```

```

ENTITY action_request_status;
    status          : label;
    assigned_request : versioned_action_request;
END_ENTITY; -- action_request_status

```

```

ENTITY action_status;
    status          : label;
    assigned_action : executed_action;
END_ENTITY; -- action_status

```

```

ENTITY address;
    internal_location      : OPTIONAL label;
    street_number          : OPTIONAL label;
    street                  : OPTIONAL label;
    postal_box              : OPTIONAL label;
    town                    : OPTIONAL label;
    region                  : OPTIONAL label;
    postal_code             : OPTIONAL label;
    country                 : OPTIONAL label;
    facsimile_number        : OPTIONAL label;
    telephone_number        : OPTIONAL label;
    electronic_mail_address : OPTIONAL label;
    telex_number            : OPTIONAL label;

```

WHERE

```

wr1: (EXISTS(internal_location) OR EXISTS(street_number) OR EXISTS(
    street) OR EXISTS(postal_box) OR EXISTS(town) OR EXISTS(
    region) OR EXISTS(postal_code) OR EXISTS(country) OR EXISTS(
    facsimile_number) OR EXISTS(telephone_number) OR EXISTS(
    electronic_mail_address) OR EXISTS(telex_number));

```

END_ENTITY; -- address

```

ENTITY advanced_brep_shape_representation

```

```

    SUBTYPE OF (shape_representation);

```

WHERE

```

wr1: (SIZEOF(QUERY ( it <* SELF.items | (NOT (SIZEOF([
    'CONFIG_CONTROL_DESIGN.MANIFOLD_SOLID_BREP',
    'CONFIG_CONTROL_DESIGN.FACETED_BREP',
    'CONFIG_CONTROL_DESIGN.MAPPED_ITEM',
    'CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D'] * TYPEOF(it)) =
    1)) )) = 0);

```

```

wr2: (SIZEOF(QUERY ( it <* SELF.items | (SIZEOF([
    'CONFIG_CONTROL_DESIGN.MANIFOLD_SOLID_BREP',

```

```

        'CONFIG_CONTROL_DESIGN.MAPPED_ITEM'] * TYPEOF(it)) = 1) )) >
        0);
wr3: (SIZEOF(QUERY ( msb <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.MANIFOLD_SOLID_BREP' IN TYPEOF(it)) )
        | (NOT (SIZEOF(QUERY ( csh <* msb_shells(msb) | (NOT (
        SIZEOF(QUERY ( fcs <* csh\connected_face_set.cfs_faces | (
        NOT ('CONFIG_CONTROL_DESIGN.ADVANCED_FACE'
        IN TYPEOF(fcs))) )) = 0)) )) = 0)) )) = 0);
wr4: (SIZEOF(QUERY ( msb <* QUERY ( it <* items | (
        'CONFIG_CONTROL_DESIGN.MANIFOLD_SOLID_BREP' IN TYPEOF(it)) )
        | ('CONFIG_CONTROL_DESIGN.ORIENTED_CLOSED_SHELL' IN TYPEOF(
        msb\manifold_solid_brep.outer)) )) = 0);
wr5: (SIZEOF(QUERY ( brv <* QUERY ( it <* items | (
        'CONFIG_CONTROL_DESIGN.BREP_WITH_VOIDS' IN TYPEOF(it)) ) | (
        NOT (SIZEOF(QUERY ( csh <* brv\brep_with_voids.voids | csh\
        oriented_closed_shell.orientation )) = 0)) )) = 0);
wr6: (SIZEOF(QUERY ( mi <* QUERY ( it <* items | (
        'CONFIG_CONTROL_DESIGN.MAPPED_ITEM' IN TYPEOF(it)) ) | (NOT
        ('CONFIG_CONTROL_DESIGN.ADVANCED_BREP_SHAPE_REPRESENTATION'
        IN TYPEOF(mi\mapped_item.mapping_source.
        mapped_representation))) )) = 0);
END_ENTITY; -- advanced_brep_shape_representation

ENTITY advanced_face
  SUBTYPE OF (face_surface);
  WHERE
    wr1 : (SIZEOF(['CONFIG_CONTROL_DESIGN.ELEMENTARY_SURFACE',
        'CONFIG_CONTROL_DESIGN.B_SPLINE_SURFACE',
        'CONFIG_CONTROL_DESIGN.SWEPT_SURFACE'] * TYPEOF(
        face_geometry)) = 1);
    wr2 : (SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* bounds | (
        'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
        | (NOT (SIZEOF(QUERY ( oe <* elp_fbnds.bound\path.
        edge_list | (NOT ('CONFIG_CONTROL_DESIGN.EDGE_CURVE' IN
        TYPEOF(oe\oriented_edge.edge_element))) )) = 0)) )) = 0);
    wr3 : (SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* bounds | (
        'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
        | (NOT (SIZEOF(QUERY ( oe <* elp_fbnds.bound\path.
        edge_list | (NOT (SIZEOF(['CONFIG_CONTROL_DESIGN.LINE',
        'CONFIG_CONTROL_DESIGN.CONIC',
        'CONFIG_CONTROL_DESIGN.POLYLINE',
        'CONFIG_CONTROL_DESIGN.SURFACE_CURVE',

```

```

'CONFIG_CONTROL_DESIGN.B_SPLINE_CURVE'] * TYPEOF(oe.
edge_element\edge_curve.edge_geometry)) = 1)) )) = 0)) )) =
0);
wr4 : (SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* bounds | (
'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
| (NOT (SIZEOF(QUERY ( oe <* elp_fbnds.bound\path.
edge_list | (NOT (('CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN
TYPEOF(oe\edge.edge_start)) AND (
'CONFIG_CONTROL_DESIGN.CARTESIAN_POINT' IN TYPEOF(oe\edge.
edge_start\vertex_point.vertex_geometry)) AND (
'CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(oe\edge.
edge_end)) AND ('CONFIG_CONTROL_DESIGN.CARTESIAN_POINT' IN
TYPEOF(oe\edge.edge_end\vertex_point.vertex_geometry)))) ))
= 0)) )) = 0);
wr5 : (SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* bounds | (
'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
| (('CONFIG_CONTROL_DESIGN.ORIENTED_PATH' IN TYPEOF(
elp_fbnds.bound)) )) = 0);
wr6 : ((NOT ('CONFIG_CONTROL_DESIGN.SWEEP_SURFACE' IN TYPEOF(
face_geometry))) OR (SIZEOF(['CONFIG_CONTROL_DESIGN.LINE',
'CONFIG_CONTROL_DESIGN.CONIC',
'CONFIG_CONTROL_DESIGN.POLYLINE',
'CONFIG_CONTROL_DESIGN.B_SPLINE_CURVE'] * TYPEOF(
face_geometry\swept_surface.swept_curve)) = 1));
wr7 : (SIZEOF(QUERY ( vlp_fbnds <* QUERY ( bnds <* bounds | (
'CONFIG_CONTROL_DESIGN.VERTEX_LOOP'
IN TYPEOF(bnds.bound)) )
| (NOT (('CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(
vlp_fbnds\face_bound.bound\vertex_loop.loop_vertex)) AND (
'CONFIG_CONTROL_DESIGN.CARTESIAN_POINT' IN TYPEOF(vlp_fbnds
\face_bound.bound\vertex_loop.loop_vertex\vertex_point.
vertex_geometry)))) )) = 0);
wr8 : (SIZEOF(QUERY ( bnd <* bounds | (NOT (SIZEOF([
'CONFIG_CONTROL_DESIGN.EDGE_LOOP',
'CONFIG_CONTROL_DESIGN.VERTEX_LOOP'] * TYPEOF(bnd.bound)) =
1)) )) = 0);
wr9 : (SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* bounds | (
'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
| (NOT (SIZEOF(QUERY ( oe <* elp_fbnds.bound\path.
edge_list | (('CONFIG_CONTROL_DESIGN.SURFACE_CURVE' IN
TYPEOF(oe\oriented_edge.edge_element\edge_curve.
edge_geometry)) AND (NOT (SIZEOF(QUERY ( sc_ag <* oe.

```

```

        edge_element\edge_curve.edge_geometry\surface_curve.
        associated_geometry | (NOT ('CONFIG_CONTROL_DESIGN.PCURVE'
        IN TYPEOF(sc_ag))) ) = 0))) ) = 0))) ) = 0);
wr10: (((NOT ('CONFIG_CONTROL_DESIGN.SWEPT_SURFACE' IN TYPEOF(
        face_geometry))) OR (NOT ('CONFIG_CONTROL_DESIGN.POLYLINE'
        IN TYPEOF(face_geometry\swept_surface.swept_curve))) OR (
        SIZEOF(face_geometry\swept_surface.swept_curve\polyline.
        points) >= 3)) AND (SIZEOF(QUERY ( elp_fbnds <*
        QUERY ( bnds <* bounds | ('CONFIG_CONTROL_DESIGN.EDGE_LOOP'
        IN TYPEOF(bnds.bound)) ) | (NOT (SIZEOF(QUERY ( oe <*
        elp_fbnds.bound\path.edge_list | ((
        'CONFIG_CONTROL_DESIGN.POLYLINE' IN TYPEOF(oe\oriented_edge
        .edge_element\edge_curve.edge_geometry)) AND (NOT (SIZEOF(
        oe\oriented_edge.edge_element\edge_curve.edge_geometry\
        polyline.points) >= 3))) ) = 0)) ) = 0)));
END_ENTITY; -- advanced_face

ENTITY alternate_product_relationship;
    name      : label;
    definition : text;
    alternate  : product;
    base       : product;
    basis      : text;
UNIQUE
    url : alternate, base;
WHERE
    wr1: (alternate :<>:base);
END_ENTITY; -- alternate_product_relationship

ENTITY application_context;
    application : text;
INVERSE
    context_elements : SET [1:?] OF application_context_element FOR
        frame_of_reference;
END_ENTITY; -- application_context

ENTITY application_context_element
    SUPERTYPE OF (ONEOF (product_context,product_definition_context,
        product_concept_context));
    name      : label;
    frame_of_reference : application_context;
END_ENTITY; -- application_context_element

```

```
ENTITY application_protocol_definition;  
    status : label;  
    application_interpreted_model_schema_name : label;  
    application_protocol_year : year_number;  
    application : application_context;  
END_ENTITY; -- application_protocol_definition
```

```
ENTITY approval;  
    status : approval_status;  
    level : label;  
END_ENTITY; -- approval
```

```
ENTITY approval_assignment  
    ABSTRACT SUPERTYPE;  
    assigned_approval : approval;  
END_ENTITY; -- approval_assignment
```

```
ENTITY approval_date_time;  
    date_time : date_time_select;  
    dated_approval : approval;  
END_ENTITY; -- approval_date_time
```

```
ENTITY approval_person_organization;  
    person_organization : person_organization_select;  
    authorized_approval : approval;  
    role : approval_role;  
END_ENTITY; -- approval_person_organization
```

```
ENTITY approval_relationship;  
    name : label;  
    description : text;  
    relating_approval : approval;  
    related_approval : approval;  
END_ENTITY; -- approval_relationship
```

```
ENTITY approval_role;  
    role : label;  
END_ENTITY; -- approval_role
```

```
ENTITY approval_status;  
    name : label;  
END_ENTITY; -- approval_status
```

```

ENTITY area_measure_with_unit
  SUBTYPE OF (measure_with_unit);
  WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.AREA_UNIT' IN TYPEOF(SELF\
      measure_with_unit.unit_component));
END_ENTITY; -- area_measure_with_unit

ENTITY area_unit
  SUBTYPE OF (named_unit);
  WHERE
    wr1: ((SELF\named_unit.dimensions.length_exponent = 2) AND (SELF\
      named_unit.dimensions.mass_exponent = 0) AND (SELF\
      named_unit.dimensions.time_exponent = 0) AND (SELF\
      named_unit.dimensions.electric_current_exponent = 0) AND (
      SELF\named_unit.dimensions.
      thermodynamic_temperature_exponent = 0) AND (SELF\named_unit
      .dimensions.amount_of_substance_exponent = 0) AND (SELF\
      named_unit.dimensions.luminous_intensity_exponent = 0));
END_ENTITY; -- area_unit

ENTITY assembly_component_usage
  SUPERTYPE OF (ONEOF (next_assembly_usage_occurrence,
    specified_higher_usage_occurrence, promissory_usage_occurrence))
  SUBTYPE OF (product_definition_usage);
  reference_designator : OPTIONAL identifier;
END_ENTITY; -- assembly_component_usage

ENTITY assembly_component_usage_substitute;
  name : label;
  definition : text;
  base : assembly_component_usage;
  substitute : assembly_component_usage;
  UNIQUE
    ur1 : base, substitute;
  WHERE
    wr1: (base.relatng_product_definition == substitute.
      relating_product_definition);
    wr2: (base :<>: substitute);
END_ENTITY; -- assembly_component_usage_substitute

ENTITY axis1_placement
  SUBTYPE OF (placement);

```

```

    axis : OPTIONAL direction;
DERIVE
    z : direction := NVL(normalise(axis),dummy_gri ||
        direction([0,0,1]));
WHERE
    wr1: (SELF\geometric_representation_item.dim = 3);
END_ENTITY; -- axis1_placement

ENTITY axis2_placement_2d
    SUBTYPE OF (placement);
    ref_direction : OPTIONAL direction;
DERIVE
    p : LIST [2:2] OF direction := build_2axes(ref_direction);
WHERE
    wr1: (SELF\geometric_representation_item.dim = 2);
END_ENTITY; -- axis2_placement_2d

ENTITY axis2_placement_3d
    SUBTYPE OF (placement);
    axis          : OPTIONAL direction;
    ref_direction : OPTIONAL direction;
DERIVE
    p : LIST [3:3] OF direction := build_axes(axis,ref_direction);
WHERE
    wr1: (SELF\placement.location.dim = 3);
    wr2: ((NOT EXISTS(axis)) OR (axis.dim = 3));
    wr3: ((NOT EXISTS(ref_direction)) OR (ref_direction.dim = 3));
    wr4: ((NOT EXISTS(axis)) OR (NOT EXISTS(ref_direction)) OR (
        cross_product(axis,ref_direction).magnitude > 0));
END_ENTITY; -- axis2_placement_3d

ENTITY b_spline_curve
    SUPERTYPE OF (ONEOF (uniform_curve,b_spline_curve_with_knots,
        quasi_uniform_curve,bezier_curve) ANDOR rational_b_spline_curve)
    SUBTYPE OF (bounded_curve);
    degree          : INTEGER;
    control_points_list : LIST [2:?] OF cartesian_point;
    curve_form      : b_spline_curve_form;
    closed_curve    : LOGICAL;
    self_intersect   : LOGICAL;
DERIVE
    upper_index_on_control_points : INTEGER := SIZEOF(

```

```

                                control_points_list) - 1;
control_points                  : ARRAY [0:
                                upper_index_on_control_points] OF
                                cartesian_point := list_to_array(
                                control_points_list, 0,
                                upper_index_on_control_points);

WHERE
  wr1: (('CONFIG_CONTROL_DESIGN.UNIFORM_CURVE' IN TYPEOF(SELF)) OR (
        'CONFIG_CONTROL_DESIGN.QUASI_UNIFORM_CURVE' IN TYPEOF(SELF))
        OR ('CONFIG_CONTROL_DESIGN.BEZIER_CURVE' IN TYPEOF(SELF)) OR
        ('CONFIG_CONTROL_DESIGN.B_SPLINE_CURVE_WITH_KNOTS' IN
         TYPEOF(SELF)));
END_ENTITY; -- b_spline_curve

ENTITY b_spline_curve_with_knots
  SUBTYPE OF (b_spline_curve);
  knot_multiplicities : LIST [2:?] OF INTEGER;
  knots               : LIST [2:?] OF parameter_value;
  knot_spec           : knot_type;
  DERIVE
    upper_index_on_knots : INTEGER := SIZEOF(knots);
  WHERE
    wr1: constraints_param_b_spline(degree, upper_index_on_knots,
                                     upper_index_on_control_points, knot_multiplicities, knots);
    wr2: (SIZEOF(knot_multiplicities) = upper_index_on_knots);
END_ENTITY; -- b_spline_curve_with_knots

ENTITY b_spline_surface
  SUPERTYPE OF (ONEOF (b_spline_surface_with_knots, uniform_surface,
                       quasi_uniform_surface, bezier_surface) ANDOR
                rational_b_spline_surface)
  SUBTYPE OF (bounded_surface);
  u_degree      : INTEGER;
  v_degree      : INTEGER;
  control_points_list : LIST [2:?] OF LIST [2:?] OF cartesian_point;
  surface_form   : b_spline_surface_form;
  u_closed       : LOGICAL;
  v_closed       : LOGICAL;
  self_intersect : LOGICAL;
  DERIVE
    u_upper      : INTEGER := SIZEOF(control_points_list) - 1;
    v_upper      : INTEGER := SIZEOF(control_points_list[1]) - 1;

```

```

        control_points : ARRAY [0:u_upper] OF ARRAY [0:v_upper] OF
            cartesian_point := make_array_of_array(
                control_points_list, 0, u_upper, 0, v_upper);
WHERE
    wr1: (('CONFIG_CONTROL_DESIGN.UNIFORM_SURFACE' IN TYPEOF(SELF)) OR (
        'CONFIG_CONTROL_DESIGN.QUASI_UNIFORM_SURFACE' IN
        TYPEOF(SELF))
        OR ('CONFIG_CONTROL_DESIGN.BEZIER_SURFACE' IN TYPEOF(SELF))
        OR ('CONFIG_CONTROL_DESIGN.B_SPLINE_SURFACE_WITH_KNOTS' IN
        TYPEOF(SELF)));
END_ENTITY; -- b_spline_surface

ENTITY b_spline_surface_with_knots
    SUBTYPE OF (b_spline_surface);
    u_multiplicities : LIST [2:?] OF INTEGER;
    v_multiplicities : LIST [2:?] OF INTEGER;
    u_knots           : LIST [2:?] OF parameter_value;
    v_knots           : LIST [2:?] OF parameter_value;
    knot_spec         : knot_type;
DERIVE
    knot_u_upper : INTEGER := SIZEOF(u_knots);
    knot_v_upper : INTEGER := SIZEOF(v_knots);
WHERE
    wr1: constraints_param_b_spline(SELF\b_spline_surface.u_degree,
        knot_u_upper, SELF\b_spline_surface.u_upper, u_multiplicities,
        u_knots);
    wr2: constraints_param_b_spline(SELF\b_spline_surface.v_degree,
        knot_v_upper, SELF\b_spline_surface.v_upper, v_multiplicities,
        v_knots);
    wr3: (SIZEOF(u_multiplicities) = knot_u_upper);
    wr4: (SIZEOF(v_multiplicities) = knot_v_upper);
END_ENTITY; -- b_spline_surface_with_knots

ENTITY bezier_curve
    SUBTYPE OF (b_spline_curve);
END_ENTITY; -- bezier_curve

ENTITY bezier_surface
    SUBTYPE OF (b_spline_surface);
END_ENTITY; -- bezier_surface

```

```

ENTITY boundary_curve
  SUBTYPE OF (composite_curve_on_surface);
  WHERE
    wr1: SELF\composite_curve.closed_curve;
END_ENTITY; -- boundary_curve

ENTITY bounded_curve
  SUPERTYPE OF (ONEOF (polyline,b_spline_curve,trimmed_curve,
    bounded_pcurve,bounded_surface_curve,composite_curve))
  SUBTYPE OF (curve);
END_ENTITY; -- bounded_curve

ENTITY bounded_pcurve
  SUBTYPE OF (pcurve, bounded_curve);
  WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.BOUNDED_CURVE' IN TYPEOF(SELF\pcurve.
      reference_to_curve.items[1]));
END_ENTITY; -- bounded_pcurve

ENTITY bounded_surface
  SUPERTYPE OF (ONEOF (b_spline_surface,rectangular_trimmed_surface,
    curve_bounded_surface,rectangular_composite_surface))
  SUBTYPE OF (surface);
END_ENTITY; -- bounded_surface

ENTITY bounded_surface_curve
  SUBTYPE OF (surface_curve, bounded_curve);
  WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.BOUNDED_CURVE' IN TYPEOF(SELF\
      surface_curve.curve_3d));
END_ENTITY; -- bounded_surface_curve

ENTITY brep_with_voids
  SUBTYPE OF (manifold_solid_brep);
  voids : SET [1:?] OF oriented_closed_shell;
END_ENTITY; -- brep_with_voids

ENTITY calendar_date
  SUBTYPE OF (date);
  day_component      : day_in_month_number;
  month_component    : month_in_year_number;
  WHERE

```

```

        wr1: valid_calendar_date(SELf);
END_ENTITY; -- calendar_date

ENTITY cartesian_point
    SUBTYPE OF (point);
    coordinates : LIST [1:3] OF length_measure;
END_ENTITY; -- cartesian_point

ENTITY cartesian_transformation_operator
    SUPERTYPE OF (cartesian_transformation_operator_3d)
    SUBTYPE OF (geometric_representation_item,
        functionally_defined_transformation);
    axis1      : OPTIONAL direction;
    axis2      : OPTIONAL direction;
    local_origin : cartesian_point;
    scale      : OPTIONAL REAL;
    DERIVE
        scl : REAL := NVL(scale,1);
    WHERE
        wr1: (scl > 0);
END_ENTITY; -- cartesian_transformation_operator

ENTITY cartesian_transformation_operator_3d
    SUBTYPE OF (cartesian_transformation_operator);
    axis3 : OPTIONAL direction;
    DERIVE
        u : LIST [3:3] OF direction := base_axis(3,SELF\
            cartesian_transformation_operator.axis1,SELF\
            cartesian_transformation_operator.axis2,axis3);
    WHERE
        wr1: (SELF\geometric_representation_item.dim = 3);
END_ENTITY; -- cartesian_transformation_operator_3d

ENTITY cc_design_approval
    SUBTYPE OF (approval_assignment);
    items : SET [1:?] OF approved_item;
END_ENTITY; -- cc_design_approval

ENTITY cc_design_certification
    SUBTYPE OF (certification_assignment);
    items : SET [1:?] OF certified_item;
END_ENTITY; -- cc_design_certification

```

```
ENTITY cc_design_contract
  SUBTYPE OF (contract_assignment);
  items : SET [1:?] OF contracted_item;
END_ENTITY; -- cc_design_contract

ENTITY cc_design_date_and_time_assignment
  SUBTYPE OF (date_and_time_assignment);
  items : SET [1:?] OF date_time_item;
  WHERE
    wr1: cc_design_date_time_correlation(SELF);
END_ENTITY; -- cc_design_date_and_time_assignment

ENTITY cc_design_person_and_organization_assignment
  SUBTYPE OF (person_and_organization_assignment);
  items : SET [1:?] OF person_organization_item;
  WHERE
    wr1: cc_design_person_and_organization_correlation(SELF);
END_ENTITY; -- cc_design_person_and_organization_assignment

ENTITY cc_design_security_classification
  SUBTYPE OF (security_classification_assignment);
  items : SET [1:?] OF classified_item;
END_ENTITY; -- cc_design_security_classification

ENTITY cc_design_specification_reference
  SUBTYPE OF (document_reference);
  items : SET [1:?] OF specified_item;
END_ENTITY; -- cc_design_specification_reference

ENTITY certification;
  name      : label;
  purpose   : text;
  kind      : certification_type;
END_ENTITY; -- certification

ENTITY certification_assignment
  ABSTRACT SUPERTYPE;
  assigned_certification : certification;
END_ENTITY; -- certification_assignment
```

```

ENTITY certification_type;
    description : label;
END_ENTITY; -- certification_type

ENTITY change
    SUBTYPE OF (action_assignment);
    items : SET [1:?] OF work_item;
END_ENTITY; -- change

ENTITY change_request
    SUBTYPE OF (action_request_assignment);
    items : SET [1:?] OF change_request_item;
END_ENTITY; -- change_request

ENTITY circle
    SUBTYPE OF (conic);
    radius : positive_length_measure;
END_ENTITY; -- circle

ENTITY closed_shell
    SUBTYPE OF (connected_face_set);
END_ENTITY; -- closed_shell

ENTITY composite_curve
    SUBTYPE OF (bounded_curve);
    segments      : LIST [1:?] OF composite_curve_segment;
    self_intersect : LOGICAL;
    DERIVE
        n_segments      : INTEGER := SIZEOF(segments);
        closed_curve : LOGICAL := segments[n_segments].transition <>
                                discontinuous;
    WHERE
        wr1: (((NOT closed_curve) AND (SIZEOF(QUERY ( temp <* segments | (
                                temp.transition = discontinuous) )) = 1)) OR (closed_curve
                                AND (SIZEOF(QUERY ( temp <* segments | (temp.transition =
                                discontinuous) )) = 0)));
END_ENTITY; -- composite_curve

ENTITY composite_curve_on_surface
    SUPERTYPE OF (boundary_curve)
    SUBTYPE OF (composite_curve);
    DERIVE

```

```

    basis_surface : SET [0:2] OF surface := get_basis_surface(SELF);
WHERE
    wr1: (SIZEOF(basis_surface) > 0);
    wr2: constraints_composite_curve_on_surface(SELF);
END_ENTITY; -- composite_curve_on_surface

ENTITY composite_curve_segment
    SUBTYPE OF (founded_item);
    transition      : transition_code;
    same_sense      : BOOLEAN;
    parent_curve    : curve;
INVERSE
    using_curves    : BAG [1:?] OF composite_curve FOR segments;
WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.BOUNDED_CURVE' IN TYPEOF(parent_curve));
END_ENTITY; -- composite_curve_segment

ENTITY configuration_design;
    configuration    : configuration_item;
    design           : product_definition_formation;
UNIQUE
    url : configuration, design;
END_ENTITY; -- configuration_design

ENTITY configuration_effectivity
    SUBTYPE OF (product_definition_effectivity);
    configuration    : configuration_design;
UNIQUE
    url : configuration, usage, id;
WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION_USAGE' IN TYPEOF(
        SELF\product_definition_effectivity.usage));
END_ENTITY; -- configuration_effectivity

ENTITY configuration_item;
    id              : identifier;
    name            : label;
    description     : OPTIONAL text;
    item_concept    : product_concept;
    purpose         : OPTIONAL label;

```

```
    UNIQUE
      url : id;
END_ENTITY; -- configuration_item

ENTITY conic
  SUPERTYPE OF (ONEOF (circle,ellipse,hyperbola,parabola))
  SUBTYPE OF (curve);
  position : axis2_placement;
END_ENTITY; -- conic

ENTITY conical_surface
  SUBTYPE OF (elementary_surface);
  radius      : length_measure;
  semi_angle : plane_angle_measure;
  WHERE
    wr1: (radius >= 0);
END_ENTITY; -- conical_surface

ENTITY connected_edge_set
  SUBTYPE OF (topological_representation_item);
  ces_edges : SET [1:?] OF edge;
END_ENTITY; -- connected_edge_set

ENTITY connected_face_set
  SUPERTYPE OF (ONEOF (closed_shell,open_shell))
  SUBTYPE OF (topological_representation_item);
  cfs_faces : SET [1:?] OF face;
END_ENTITY; -- connected_face_set

ENTITY context_dependent_shape_representation;
  representation_relation      : shape_representation_relationship;
  represented_product_relation : product_definition_shape;
  WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION_RELATIONSHIP' IN
          TYPEOF(SELF.represented_product_relation.definition));
END_ENTITY; -- context_dependent_shape_representation

ENTITY context_dependent_unit
  SUBTYPE OF (named_unit);
  name : label;
END_ENTITY; -- context_dependent_unit
```

```

ENTITY contract;
    name      : label;
    purpose   : text;
    kind      : contract_type;
END_ENTITY; -- contract

ENTITY contract_assignment
    ABSTRACT SUPERTYPE;
    assigned_contract : contract;
END_ENTITY; -- contract_assignment

ENTITY contract_type;
    description : label;
END_ENTITY; -- contract_type

ENTITY conversion_based_unit
    SUBTYPE OF (named_unit);
    name          : label;
    conversion_factor : measure_with_unit;
END_ENTITY; -- conversion_based_unit

ENTITY coordinated_universal_time_offset;
    hour_offset      : hour_in_day;
    minute_offset    : OPTIONAL minute_in_hour;
    sense            : ahead_or_behind;
END_ENTITY; -- coordinated_universal_time_offset

ENTITY curve
    SUPERTYPE OF (ONEOF (line, conic, pcurve, surface_curve, offset_curve_3d,
        curve_replica))
    SUBTYPE OF (geometric_representation_item);
END_ENTITY; -- curve

ENTITY curve_bounded_surface
    SUBTYPE OF (bounded_surface);
    basis_surface : surface;
    boundaries    : SET [1:?] OF boundary_curve;
    implicit_outer : BOOLEAN;
    WHERE
        wr1: (NOT (implicit_outer AND (
            'CONFIG_CONTROL_DESIGN.OUTER_BOUNDARY_CURVE' IN TYPEOF(
                boundaries))));

```

```

wr2: ((NOT implicit_outer) OR (
    'CONFIG_CONTROL_DESIGN.BOUNDED_SURFACE' IN TYPEOF(
        basis_surface)));
wr3: (SIZEOF(QUERY ( temp <* boundaries | (
    'CONFIG_CONTROL_DESIGN.OUTER_BOUNDARY_CURVE'
    IN TYPEOF(temp)) )) <= 1);
wr4: (SIZEOF(QUERY ( temp <* boundaries | (temp\
    composite_curve_on_surface.basis_surface[1] <> SELF.
    basis_surface) )) = 0);
END_ENTITY; -- curve_bounded_surface

ENTITY curve_replica
    SUBTYPE OF (curve);
    parent_curve      : curve;
    transformation     : cartesian_transformation_operator;
    WHERE
        wr1: (transformation.dim = parent_curve.dim);
        wr2: acyclic_curve_replica(SELF,parent_curve);
END_ENTITY; -- curve_replica

ENTITY cylindrical_surface
    SUBTYPE OF (elementary_surface);
    radius : positive_length_measure;
END_ENTITY; -- cylindrical_surface

ENTITY date
    SUPERTYPE OF (ONEOF (calendar_date,ordinal_date,
        week_of_year_and_day_date));
    year_component : year_number;
END_ENTITY; -- date

ENTITY date_and_time;
    date_component : date;
    time_component : local_time;
END_ENTITY; -- date_and_time

ENTITY date_and_time_assignment
    ABSTRACT SUPERTYPE;
    assigned_date_and_time : date_and_time;
    role                    : date_time_role;
END_ENTITY; -- date_and_time_assignment

```

```
ENTITY date_time_role;
    name : label;
END_ENTITY; -- date_time_role

ENTITY dated_effectivity
    SUBTYPE OF (effectivity);
    effectivity_start_date : date_and_time;
    effectivity_end_date   : OPTIONAL date_and_time;
END_ENTITY; -- dated_effectivity

ENTITY definitional_representation
    SUBTYPE OF (representation);
    WHERE
        wr1: ('CONFIG_CONTROL_DESIGN.PARAMETRIC_REPRESENTATION_CONTEXT' IN
            TYPEOF(SELF\representation.context_of_items));
END_ENTITY; -- definitional_representation

ENTITY degenerate_pcurve
    SUBTYPE OF (point);
    basis_surface      : surface;
    reference_to_curve : definitional_representation;
    WHERE
        wr1: (SIZEOF(reference_to_curve\representation.items) = 1);
        wr2: ('CONFIG_CONTROL_DESIGN.CURVE' IN TYPEOF(reference_to_curve\
            representation.items[1]));
        wr3: (reference_to_curve\representation.items[1]\
            geometric_representation_item.dim = 2);
END_ENTITY; -- degenerate_pcurve

ENTITY degenerate_toroidal_surface
    SUBTYPE OF (toroidal_surface);
    select_outer : BOOLEAN;
    WHERE
        wr1: (major_radius < minor_radius);
END_ENTITY; -- degenerate_toroidal_surface

ENTITY design_context
    SUBTYPE OF (product_definition_context);
    WHERE
        wr1: (SELF.life_cycle_stage = 'design');
END_ENTITY; -- design_context
```

```
ENTITY design_make_from_relationship
  SUBTYPE OF (product_definition_relationship);
END_ENTITY; -- design_make_from_relationship

ENTITY dimensional_exponents;
  length_exponent          : REAL;
  mass_exponent            : REAL;
  time_exponent            : REAL;
  electric_current_exponent : REAL;
  thermodynamic_temperature_exponent : REAL;
  amount_of_substance_exponent : REAL;
  luminous_intensity_exponent : REAL;
END_ENTITY; -- dimensional_exponents

ENTITY directed_action
  SUBTYPE OF (executed_action);
  directive : action_directive;
END_ENTITY; -- directed_action

ENTITY direction
  SUBTYPE OF (geometric_representation_item);
  direction_ratios : LIST [2:3] OF REAL;
  WHERE
    wr1: (SIZEOF(QUERY ( tmp < * direction_ratios | (tmp <> 0) )) > 0);
END_ENTITY; -- direction

ENTITY document;
  id          : identifier;
  name        : label;
  description : text;
  kind        : document_type;
  UNIQUE
    url : id;
END_ENTITY; -- document

ENTITY document_reference
  ABSTRACT SUPERTYPE;
  assigned_document : document;
  source            : label;
END_ENTITY; -- document_reference
```

```

ENTITY document_relationship;
    name          : label;
    description    : text;
    relating_document : document;
    related_document : document;
END_ENTITY; -- document_relationship

ENTITY document_type;
    product_data_type : label;
END_ENTITY; -- document_type

ENTITY document_usage_constraint;
    source          : document;
    subject_element  : label;
    subject_element_value : text;
END_ENTITY; -- document_usage_constraint

ENTITY document_with_class
    SUBTYPE OF (document);
    class : identifier;
END_ENTITY; -- document_with_class

ENTITY edge
    SUPERTYPE OF (ONEOF (edge_curve, oriented_edge))
    SUBTYPE OF (topological_representation_item);
    edge_start : vertex;
    edge_end   : vertex;
END_ENTITY; -- edge

ENTITY edge_based_wireframe_model
    SUBTYPE OF (geometric_representation_item);
    ebwm_boundary : SET [1:?] OF connected_edge_set;
END_ENTITY; -- edge_based_wireframe_model

ENTITY edge_based_wireframe_shape_representation
    SUBTYPE OF (shape_representation);
    WHERE
        wr1: (SIZEOF(QUERY ( it <* SELF.items | (NOT (SIZEOF([
            'CONFIG_CONTROL_DESIGN.EDGE_BASED_WIREFRAME_MODEL',
            'CONFIG_CONTROL_DESIGN.MAPPED_ITEM',
            'CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D'] * TYPEOF(it)) =
            1)) )) = 0);

```

```

wr2: (SIZEOF(QUERY ( it <* SELF.items | (SIZEOF([
    'CONFIG_CONTROL_DESIGN.EDGE_BASED_WIREFRAME_MODEL',
    'CONFIG_CONTROL_DESIGN.MAPPED_ITEM'] * TYPEOF(it)) = 1) ))
    >= 1);

wr3: (SIZEOF(QUERY ( ebwm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.EDGE_BASED_WIREFRAME_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( eb <* ebwm\
    edge_based_wireframe_model.ebwm_boundary | (NOT (SIZEOF(
    QUERY ( edges <* eb.ces_edges | (NOT (
    'CONFIG_CONTROL_DESIGN.EDGE_CURVE' IN TYPEOF(edges))))
    = 0)) )) = 0)) )) = 0);

wr4: (SIZEOF(QUERY ( ebwm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.EDGE_BASED_WIREFRAME_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( eb <* ebwm\
    edge_based_wireframe_model.ebwm_boundary | (NOT (SIZEOF(
    QUERY ( pline_edges <* QUERY ( edges <* eb.ces_edges | (
    'CONFIG_CONTROL_DESIGN.POLYLINE' IN TYPEOF(edges\edge_curve.
    edge_geometry))) ) | (NOT (SIZEOF(pline_edges\edge_curve.
    edge_geometry\polyline.points) > 2)) )) = 0)) )) = 0)) )) =
    0);

wr5: (SIZEOF(QUERY ( ebwm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.EDGE_BASED_WIREFRAME_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( eb <* ebwm\
    edge_based_wireframe_model.ebwm_boundary | (NOT (SIZEOF(
    QUERY ( edges <* eb.ces_edges | (NOT ((
    'CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(edges.
    edge_start)) AND ('CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN
    TYPEOF(edges.edge_end)))) )) = 0)) )) = 0)) )) = 0);

wr6: (SIZEOF(QUERY ( ebwm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.EDGE_BASED_WIREFRAME_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( eb <* ebwm\
    edge_based_wireframe_model.ebwm_boundary | (NOT (SIZEOF(
    QUERY ( edges <* eb.ces_edges | (NOT
    valid_wireframe_edge_curve(edges\edge_curve.edge_geometry))
    )) = 0)) )) = 0)) )) = 0);

wr7: (SIZEOF(QUERY ( ebwm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.EDGE_BASED_WIREFRAME_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( eb <* ebwm\
    edge_based_wireframe_model.ebwm_boundary | (NOT (SIZEOF(
    QUERY ( edges <* eb.ces_edges | (NOT (
    valid_wireframe_vertex_point(edges.edge_start\vertex_point.
    vertex_geometry) AND valid_wireframe_vertex_point(edges.

```

```

        edge_end\vertex_point.vertex_geometry))) )) = 0)) )) = 0))
    )) = 0);
wr8: (SIZEOF(QUERY ( mi <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.MAPPED_ITEM' IN TYPEOF(it)) ) | (NOT
    (('CONFIG_CONTROL_DESIGN.' +
    'EDGE_BASED_WIREFRAME_SHAPE_REPRESENTATION') IN TYPEOF(mi\
    mapped_item.mapping_source.mapped_representation))) )) = 0);
wr9: (SELF.context_of_items\geometric_representation_context.
    coordinate_space_dimension = 3);
END_ENTITY; -- edge_based_wireframe_shape_representation

ENTITY edge_curve
    SUBTYPE OF (edge, geometric_representation_item);
    edge_geometry : curve;
    same_sense    : BOOLEAN;
END_ENTITY; -- edge_curve

ENTITY edge_loop
    SUBTYPE OF (loop, path);
    DERIVE
        ne : INTEGER := SIZEOF(SELF\path.edge_list);
    WHERE
        wr1: (SELF\path.edge_list[1].edge_start :=: SELF\path.edge_list[ne].
            edge_end);
END_ENTITY; -- edge_loop

ENTITY effectivity
    SUPERTYPE OF (ONEOF (serial_numbered_effectivity,dated_effectivity,
        lot_effectivity));
    id : identifier;
END_ENTITY; -- effectivity

ENTITY elementary_surface
    SUPERTYPE OF (ONEOF (plane,cylindrical_surface,conical_surface,
        spherical_surface,toroidal_surface))
    SUBTYPE OF (surface);
    position : axis2_placement_3d;
END_ENTITY; -- elementary_surface

ENTITY ellipse
    SUBTYPE OF (conic);
    semi_axis_1 : positive_length_measure;

```

```

    semi_axis_2 : positive_length_measure;
END_ENTITY; -- ellipse

ENTITY evaluated_degenerate_pcurve
  SUBTYPE OF (degenerate_pcurve);
  equivalent_point : cartesian_point;
END_ENTITY; -- evaluated_degenerate_pcurve

ENTITY executed_action
  SUBTYPE OF (action);
END_ENTITY; -- executed_action

ENTITY face
  SUPERTYPE OF (ONEOF (face_surface, oriented_face))
  SUBTYPE OF (topological_representation_item);
  bounds : SET [1:?] OF face_bound;
  WHERE
    wr1: (NOT mixed_loop_type_set(list_to_set(list_face_loops(SELF))));
    wr2: (SIZEOF(QUERY ( temp <* bounds | (
      'CONFIG_CONTROL_DESIGN.FACE_OUTER_BOUND' IN TYPEOF(temp)) ))
      <= 1);
END_ENTITY; -- face

ENTITY face_bound
  SUBTYPE OF (topological_representation_item);
  bound : loop;
  orientation : BOOLEAN;
END_ENTITY; -- face_bound

ENTITY face_outer_bound
  SUBTYPE OF (face_bound);
END_ENTITY; -- face_outer_bound

ENTITY face_surface
  SUBTYPE OF (face, geometric_representation_item);
  face_geometry : surface;
  same_sense : BOOLEAN;
END_ENTITY; -- face_surface

ENTITY faceted_brep
  SUBTYPE OF (manifold_solid_brep);
END_ENTITY; -- faceted_brep

```

```

ENTITY faceted_brep_shape_representation
  SUBTYPE OF (shape_representation);
  WHERE
    wr1: (SIZEOF(QUERY ( it <* items | (NOT (SIZEOF([
      'CONFIG_CONTROL_DESIGN.FACETED_BREP',
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM',
      'CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D'] * TYPEOF(it)) =
      1)) )) = 0);
    wr2: (SIZEOF(QUERY ( it <* items | (SIZEOF([
      'CONFIG_CONTROL_DESIGN.FACETED_BREP',
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM'] * TYPEOF(it)) = 1) )) >
      0);
    wr3: (SIZEOF(QUERY ( fbrep <* QUERY ( it <* items | (
      'CONFIG_CONTROL_DESIGN.FACETED_BREP' IN TYPEOF(it)) ) | (
      NOT (SIZEOF(QUERY ( csh <* msb_shells(fbrep) | (NOT (SIZEOF(
      QUERY ( fcs <* csh\connected_face_set.cfs_faces | (NOT ((
      'CONFIG_CONTROL_DESIGN.FACE_SURFACE' IN TYPEOF(fcs)) AND (
      'CONFIG_CONTROL_DESIGN.PLANE' IN TYPEOF(fcs\face_surface.
      face_geometry)) AND ('CONFIG_CONTROL_DESIGN.CARTESIAN_POINT'
      IN TYPEOF(fcs\face_surface.face_geometry\elementary_surface.
      position.location)))) )) = 0)) )) = 0)) )) = 0);
    wr4: (SIZEOF(QUERY ( fbrep <* QUERY ( it <* items | (
      'CONFIG_CONTROL_DESIGN.FACETED_BREP' IN TYPEOF(it)) ) | (
      NOT (SIZEOF(QUERY ( csh <* msb_shells(fbrep) | (NOT (SIZEOF(
      QUERY ( fcs <* csh\connected_face_set.cfs_faces | (NOT (
      SIZEOF(QUERY ( bnds <* fcs.bounds | (
      'CONFIG_CONTROL_DESIGN.FACE_OUTER_BOUND' IN TYPEOF(bnds)) ))
      = 1)) )) = 0)) )) = 0)) )) = 0);
    wr5: (SIZEOF(QUERY ( msb <* QUERY ( it <* items | (
      'CONFIG_CONTROL_DESIGN.MANIFOLD_SOLID_BREP' IN TYPEOF(it)) )
      | ('CONFIG_CONTROL_DESIGN.ORIENTED_CLOSED_SHELL' IN TYPEOF(
      msb\manifold_solid_brep.outer)) )) = 0);
    wr6: (SIZEOF(QUERY ( brv <* QUERY ( it <* items | (
      'CONFIG_CONTROL_DESIGN.BREP_WITH_VOIDS' IN TYPEOF(it)) ) | (
      NOT (SIZEOF(QUERY ( csh <* brv\brep_with_voids.voids | csh\
      oriented_closed_shell.orientation )) = 0)) )) = 0);
    wr7: (SIZEOF(QUERY ( mi <* QUERY ( it <* items | (
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM' IN TYPEOF(it)) ) | (NOT
      ('CONFIG_CONTROL_DESIGN.FACETED_BREP_SHAPE_REPRESENTATION'
      IN TYPEOF(mi\mapped_item.mapping_source.
      mapped_representation)))) )) = 0);
  END_ENTITY; -- faceted_brep_shape_representation

```

```

ENTITY founded_item;
END_ENTITY; -- founded_item

ENTITY functionally_defined_transformation;
    name          : label;
    description    : text;
END_ENTITY; -- functionally_defined_transformation

ENTITY geometric_curve_set
    SUBTYPE OF (geometric_set);
    WHERE
        wr1: (SIZEOF(QUERY ( temp <* SELF\geometric_set.elements | (
            'CONFIG_CONTROL_DESIGN.SURFACE' IN TYPEOF(temp)) )) = 0);
END_ENTITY; -- geometric_curve_set

ENTITY geometric_representation_context
    SUBTYPE OF (representation_context);
    coordinate_space_dimension : dimension_count;
END_ENTITY; -- geometric_representation_context

ENTITY geometric_representation_item
    SUPERTYPE OF (ONEOF (point,direction,vector,placement,
        cartesian_transformation_operator,curve,surface,edge_curve,
        face_surface,poly_loop,vertex_point,solid_model,
        shell_based_surface_model,shell_based_wireframe_model,
        edge_based_wireframe_model,geometric_set))
    SUBTYPE OF (representation_item);
    DERIVE
        dim : dimension_count := dimension_of(SELF);
    WHERE
        wr1: (SIZEOF(QUERY ( using_rep <* using_representations(SELF) | (
            NOT (
                'CONFIG_CONTROL_DESIGN.GEOMETRIC_REPRESENTATION_CONTEXT' IN
                TYPEOF(using_rep.context_of_items))) )) = 0);
END_ENTITY; -- geometric_representation_item

ENTITY geometric_set
    SUPERTYPE OF (geometric_curve_set)
    SUBTYPE OF (geometric_representation_item);
    elements : SET [1:?] OF geometric_set_select;
END_ENTITY; -- geometric_set

```

```

ENTITY geometrically_bounded_surface_shape_representation
  SUBTYPE OF (shape_representation);
  WHERE
    wr1: (SIZEOF(QUERY ( it <* SELF.items | (NOT (SIZEOF([
      'CONFIG_CONTROL_DESIGN.GEOMETRIC_SET',
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM',
      'CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D'] * TYPEOF(it)) =
      1)) )) = 0);
    wr2: (SIZEOF(QUERY ( it <* SELF.items | (SIZEOF([
      'CONFIG_CONTROL_DESIGN.GEOMETRIC_SET',
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM'] * TYPEOF(it)) = 1) )) >
      0);
    wr3: (SIZEOF(QUERY ( mi <* QUERY ( it <* SELF.items | (
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM' IN TYPEOF(it)) ) | (NOT
      ((( 'CONFIG_CONTROL_DESIGN.' +
      'GEOMETRICALLY_BOUNDED_SURFACE_SHAPE_REPRESENTATION') IN
      TYPEOF(mi\mapped_item.mapping_source.mapped_representation))
      AND (SIZEOF(QUERY ( mr_it <* mi\mapped_item.mapping_source.
      mapped_representation.items | (
      'CONFIG_CONTROL_DESIGN.GEOMETRIC_SET' IN TYPEOF(mr_it)) )) >
      0))) )) = 0);
    wr4: (SIZEOF(QUERY ( gs <* QUERY ( it <* SELF.items | (
      'CONFIG_CONTROL_DESIGN.GEOMETRIC_SET' IN TYPEOF(it)) ) | (
      NOT (SIZEOF(QUERY ( pnt <* QUERY ( gsel <* gs\geometric_set.
      elements | ('CONFIG_CONTROL_DESIGN.POINT' IN TYPEOF(gsel)) )
      | (NOT gbsf_check_point(pnt)) )) = 0)) )) = 0);
    wr5: (SIZEOF(QUERY ( gs <* QUERY ( it <* SELF.items | (
      'CONFIG_CONTROL_DESIGN.GEOMETRIC_SET' IN TYPEOF(it)) ) | (
      NOT (SIZEOF(QUERY ( cv <* QUERY ( gsel <* gs\geometric_set.
      elements | ('CONFIG_CONTROL_DESIGN.CURVE' IN TYPEOF(gsel)) )
      | (NOT gbsf_check_curve(cv)) )) = 0)) )) = 0);
    wr6: (SIZEOF(QUERY ( gs <* QUERY ( it <* SELF.items | (
      'CONFIG_CONTROL_DESIGN.GEOMETRIC_SET' IN TYPEOF(it)) ) | (
      NOT (SIZEOF(QUERY ( sf <* QUERY ( gsel <* gs\geometric_set.
      elements | ('CONFIG_CONTROL_DESIGN.SURFACE' IN
      TYPEOF(gsel)) ) | (NOT gbsf_check_surface(sf)) ))
      = 0)) )) = 0);
    wr7: (SIZEOF(QUERY ( gs <* QUERY ( it <* SELF.items | (
      'CONFIG_CONTROL_DESIGN.GEOMETRIC_SET' IN TYPEOF(it)) ) | (
      SIZEOF(QUERY ( gsel <* gs\geometric_set.elements | (

```

```

        'CONFIG_CONTROL_DESIGN.SURFACE' IN TYPEOF(gsel)) )) > 0) ))
    > 0);
END_ENTITY; -- geometrically_bounded_surface_shape_representation

ENTITY geometrically_bounded_wireframe_shape_representation
    SUBTYPE OF (shape_representation);
    WHERE
        wr1: (SIZEOF(QUERY ( it <* SELF.items | (NOT (SIZEOF(TYPEOF(it) * [
            'CONFIG_CONTROL_DESIGN.GEOMETRIC_CURVE_SET',
            'CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D',
            'CONFIG_CONTROL_DESIGN.MAPPED_ITEM']) = 1)) )) = 0);
        wr2: (SIZEOF(QUERY ( it <* SELF.items | (SIZEOF(TYPEOF(it) * [
            'CONFIG_CONTROL_DESIGN.GEOMETRIC_CURVE_SET',
            'CONFIG_CONTROL_DESIGN.MAPPED_ITEM']) = 1)) )) >= 1);
        wr3: (SIZEOF(QUERY ( gcs <* QUERY ( it <* SELF.items | (
            'CONFIG_CONTROL_DESIGN.GEOMETRIC_CURVE_SET' IN TYPEOF(it)) )
            | (NOT (SIZEOF(QUERY ( crv <* QUERY ( elem <* gcs\
            geometric_set.elements | ('CONFIG_CONTROL_DESIGN.CURVE' IN
            TYPEOF(elem)) ) | (NOT valid_geometrically_bounded_wf_curve(
            crv)) )) = 0)) )) = 0);
        wr4: (SIZEOF(QUERY ( gcs <* QUERY ( it <* SELF.items | (
            'CONFIG_CONTROL_DESIGN.GEOMETRIC_CURVE_SET' IN TYPEOF(it)) )
            | (NOT (SIZEOF(QUERY ( pnts <* QUERY ( elem <* gcs\
            geometric_set.elements | ('CONFIG_CONTROL_DESIGN.POINT' IN
            TYPEOF(elem)) ) | (NOT valid_geometrically_bounded_wf_point(
            pnts)) )) = 0)) )) = 0);
        wr5: (SIZEOF(QUERY ( gcs <* QUERY ( it <* SELF.items | (
            'CONFIG_CONTROL_DESIGN.GEOMETRIC_CURVE_SET' IN TYPEOF(it)) )
            | (NOT (SIZEOF(QUERY ( cnc <* QUERY ( elem <* gcs\
            geometric_set.elements | ('CONFIG_CONTROL_DESIGN.CONIC' IN
            TYPEOF(elem)) ) | (NOT (
            'CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D' IN TYPEOF(cnc\
            conic.position))) )) = 0)) )) = 0);
        wr6: (SIZEOF(QUERY ( gcs <* QUERY ( it <* SELF.items | (
            'CONFIG_CONTROL_DESIGN.GEOMETRIC_CURVE_SET' IN TYPEOF(it)) )
            | (NOT (SIZEOF(QUERY ( pline <* QUERY ( elem <* gcs\
            geometric_set.elements | ('CONFIG_CONTROL_DESIGN.POLYLINE'
            IN TYPEOF(elem)) ) | (NOT (SIZEOF(pline\polyline.points)
            > 2)) )) = 0)) )) = 0);
        wr7: (SIZEOF(QUERY ( mi <* QUERY ( it <* SELF.items | (
            'CONFIG_CONTROL_DESIGN.MAPPED_ITEM' IN TYPEOF(it)) ) | (NOT
            (('CONFIG_CONTROL_DESIGN.' +

```

```

        'GEOMETRICALLY_BOUNDED_WIREFRAME_SHAPE_REPRESENTATION') IN
        TYPEOF(mi\mapped_item.mapping_source.mapped_representation)
        )) )) = 0);
END_ENTITY; -- geometrically_bounded_wireframe_shape_representation

ENTITY global_uncertainty_assigned_context
    SUBTYPE OF (representation_context);
    uncertainty : SET [1:?] OF uncertainty_measure_with_unit;
END_ENTITY; -- global_uncertainty_assigned_context

ENTITY global_unit_assigned_context
    SUBTYPE OF (representation_context);
    units : SET [1:?] OF unit;
END_ENTITY; -- global_unit_assigned_context

ENTITY hyperbola
    SUBTYPE OF (conic);
    semi_axis      : positive_length_measure;
    semi_imag_axis : positive_length_measure;
END_ENTITY; -- hyperbola

ENTITY intersection_curve
    SUBTYPE OF (surface_curve);
    WHERE
        wr1: (SIZEOF(SELF\surface_curve.associated_geometry) = 2);
        wr2: (associated_surface(SELF\surface_curve.associated_geometry[1])
            <> associated_surface(SELF\surface_curve.associated_geometry
            [2]));
END_ENTITY; -- intersection_curve

ENTITY item_defined_transformation;
    name      : label;
    description : text;
    transform_item_1 : representation_item;
    transform_item_2 : representation_item;
END_ENTITY; -- item_defined_transformation

ENTITY length_measure_with_unit
    SUBTYPE OF (measure_with_unit);
    WHERE
        wr1: ('CONFIG_CONTROL_DESIGN.LENGTH_UNIT' IN TYPEOF(SELF\

```

```

        measure_with_unit.unit_component));
END_ENTITY; -- length_measure_with_unit

ENTITY length_unit
  SUBTYPE OF (named_unit);
  WHERE
    wr1: ((SELF\named_unit.dimensions.length_exponent = 1) AND (SELF\
      named_unit.dimensions.mass_exponent = 0) AND (SELF\
      named_unit.dimensions.time_exponent = 0) AND (SELF\
      named_unit.dimensions.electric_current_exponent = 0) AND (
      SELF\named_unit.dimensions.
      thermodynamic_temperature_exponent = 0) AND (SELF\named_unit
      .dimensions.amount_of_substance_exponent = 0) AND (SELF\
      named_unit.dimensions.luminous_intensity_exponent = 0));
END_ENTITY; -- length_unit

ENTITY line
  SUBTYPE OF (curve);
  pnt : cartesian_point;
  dir : vector;
  WHERE
    wr1: (dir.dim = pnt.dim);
END_ENTITY; -- line

ENTITY local_time;
  hour_component : hour_in_day;
  minute_component : OPTIONAL minute_in_hour;
  second_component : OPTIONAL second_in_minute;
  zone : coordinated_universal_time_offset;
  WHERE
    wr1: valid_time(SELF);
END_ENTITY; -- local_time

ENTITY loop
  SUPERTYPE OF (ONEOF (vertex_loop,edge_loop,poly_loop))
  SUBTYPE OF (topological_representation_item);
END_ENTITY; -- loop

ENTITY lot_effectivity
  SUBTYPE OF (effectivity);
  effectivity_lot_id : identifier;

```

```

    effectivity_lot_size : measure_with_unit;
END_ENTITY; -- lot_effectivity

ENTITY manifold_solid_brep
  SUBTYPE OF (solid_model);
  outer : closed_shell;
END_ENTITY; -- manifold_solid_brep

ENTITY manifold_surface_shape_representation
  SUBTYPE OF (shape_representation);
  WHERE
    wr1 : (SIZEOF(QUERY ( it <* SELF.items | (NOT (SIZEOF([
      'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL',
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM',
      'CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D'] * TYPEOF(it)) =
      1)) )) = 0);
    wr2 : (SIZEOF(QUERY ( it <* SELF.items | (SIZEOF([
      'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL',
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM'] * TYPEOF(it)) = 1)) ))
      > 0);
    wr3 : (SIZEOF(QUERY ( mi <* QUERY ( it <* SELF.items | (
      'CONFIG_CONTROL_DESIGN.MAPPED_ITEM' IN TYPEOF(it)) ) | (
      NOT (('CONFIG_CONTROL_DESIGN.' +
      'MANIFOLD_SURFACE_SHAPE_REPRESENTATION'
      IN TYPEOF(mi\mapped_item.mapping_source.
      mapped_representation)) AND (SIZEOF(QUERY ( mr_it <* mi\
      mapped_item.mapping_source.mapped_representation.items | (
      'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
      TYPEOF(mr_it)) )) > 0))) )) = 0);
    wr4 : (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
      'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
      TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( sh <* sbsm\
      shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF([
      'CONFIG_CONTROL_DESIGN.OPEN_SHELL',
      'CONFIG_CONTROL_DESIGN.ORIENTED_CLOSED_SHELL',
      'CONFIG_CONTROL_DESIGN.CLOSED_SHELL'] * TYPEOF(sh)) = 1))
      )) = 0)) )) = 0);
    wr5 : (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
      'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
      TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
      shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
      QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT (

```

```

        SIZEOF(['CONFIG_CONTROL_DESIGN.FACE_SURFACE',
        'CONFIG_CONTROL_DESIGN.ORIENTED_FACE'] * TYPEOF(fa)) = 1))
        )) = 0)) )) = 0)) )) = 0);
wr6 : (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
        shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
        QUERY ( f_sf <* QUERY ( fa <* cfs\connected_face_set.
        cfs_faces | ('CONFIG_CONTROL_DESIGN.FACE_SURFACE' IN
        TYPEOF(fa)) ) | (NOT ((
        'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(f_sf)) OR (
        SIZEOF(['CONFIG_CONTROL_DESIGN.B_SPLINE_SURFACE',
        'CONFIG_CONTROL_DESIGN.ELEMENTARY_SURFACE',
        'CONFIG_CONTROL_DESIGN.OFFSET_SURFACE',
        'CONFIG_CONTROL_DESIGN.SURFACE_REPLICA',
        'CONFIG_CONTROL_DESIGN.SWEPT_SURFACE'] * TYPEOF(f_sf\
        face_surface.face_geometry)) = 1))) )) = 0)) )) = 0)) )) =
        0);
wr7 : (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
        shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
        QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
        'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR
        msf_surface_check(fa\face_surface.face_geometry))) ))
        = 0)) )) = 0)) )) = 0);
wr8 : (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
        shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
        QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
        'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR (
        SIZEOF(QUERY ( bnds <* fa.bounds | (NOT (SIZEOF([
        'CONFIG_CONTROL_DESIGN.EDGE_LOOP',
        'CONFIG_CONTROL_DESIGN.VERTEX_LOOP'] * TYPEOF(bnds.bound))
        = 1))) )) = 0))) )) = 0)) )) = 0)) )) = 0);
wr9 : (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
        shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
        QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
        'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR (

```

```

        SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* fa.bounds | (
        'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
        | (NOT (SIZEOF(QUERY ( oe <* elp_fbnds\path.edge_list | (
        NOT ('CONFIG_CONTROL_DESIGN.EDGE_CURVE' IN TYPEOF(oe.
        edge_element)))))) = 0)))) = 0)))) = 0))) = 0)) )) = 0)) )) = 0);
wr10: (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
        shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
        QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
        'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR (
        SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* fa.bounds | (
        'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
        | (NOT (SIZEOF(QUERY ( oe_cv <* QUERY ( oe <* elp_fbnds\
        path.edge_list | ('CONFIG_CONTROL_DESIGN.EDGE_CURVE' IN
        TYPEOF(oe.edge_element)) ) | (NOT (SIZEOF([
        'CONFIG_CONTROL_DESIGN.B_SPLINE_CURVE',
        'CONFIG_CONTROL_DESIGN.CONIC',
        'CONFIG_CONTROL_DESIGN.CURVE_REPLICA',
        'CONFIG_CONTROL_DESIGN.LINE',
        'CONFIG_CONTROL_DESIGN.OFFSET_CURVE_3D',
        'CONFIG_CONTROL_DESIGN.PCURVE',
        'CONFIG_CONTROL_DESIGN.POLYLINE',
        'CONFIG_CONTROL_DESIGN.SURFACE_CURVE'] * TYPEOF(oe_cv.
        edge_element\edge_curve.edge_geometry)) = 1)) )) = 0)) )) =
        0))) )) = 0)) )) = 0)) )) = 0);
wr11: (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
        shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
        QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
        'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR (
        SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* fa.bounds | (
        'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
        | (NOT (SIZEOF(QUERY ( oe <* elp_fbnds\path.edge_list | (
        NOT msf_curve_check(oe.edge_element\edge_curve.
        edge_geometry)) )) = 0)) )) = 0))) ))
        = 0)) )) = 0)) )) = 0);
wr12: (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
        shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(

```

```

QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR (
SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* fa.bounds | (
'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
| (NOT (SIZEOF(QUERY ( oe <* elp_fbnds\path.edge_list | (
NOT (('CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(oe.
edge_element.edge_start)) AND (
'CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(oe.
edge_element.edge_end)))) ) = 0)) ) = 0)) ) = 0)) ) =
0)) ) = 0);

wr13: (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR (
SIZEOF(QUERY ( elp_fbnds <* QUERY ( bnds <* fa.bounds | (
'CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN TYPEOF(bnds.bound)) )
| (NOT (SIZEOF(QUERY ( oe <* elp_fbnds\path.edge_list | (
NOT ((SIZEOF(['CONFIG_CONTROL_DESIGN.CARTESIAN_POINT',
'CONFIG_CONTROL_DESIGN.DEGENERATE_PCURVE',
'CONFIG_CONTROL_DESIGN.POINT_ON_CURVE',
'CONFIG_CONTROL_DESIGN.POINT_ON_SURFACE'] * TYPEOF(oe.
edge_element.edge_start\vertex_point.vertex_geometry)) = 1)
AND (SIZEOF(['CONFIG_CONTROL_DESIGN.CARTESIAN_POINT',
'CONFIG_CONTROL_DESIGN.DEGENERATE_PCURVE',
'CONFIG_CONTROL_DESIGN.POINT_ON_CURVE',
'CONFIG_CONTROL_DESIGN.POINT_ON_SURFACE'] * TYPEOF(oe.
edge_element.edge_end\vertex_point.vertex_geometry))
= 1))) ) = 0)) ) = 0))) ) = 0)) ) = 0)) ) = 0);

wr14: (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR (
SIZEOF(QUERY ( vlp_fbnds <* QUERY ( bnds <* fa.bounds | (
'CONFIG_CONTROL_DESIGN.VERTEX_LOOP'
IN TYPEOF(bnds.bound)) )
| (NOT ('CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(
vlp_fbnds\vertex_loop.loop_vertex))) ) = 0))) ) = 0)) ) =
0)) ) = 0);

```

```

wr15: (SIZEOF(QUERY ( sbsm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.SHELL_BASED_SURFACE_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( cfs <* sbsm\
    shell_based_surface_model.sbsm_boundary | (NOT (SIZEOF(
    QUERY ( fa <* cfs\connected_face_set.cfs_faces | (NOT ((
    'CONFIG_CONTROL_DESIGN.ADVANCED_FACE' IN TYPEOF(fa)) OR (
    SIZEOF(QUERY ( vlp_fbnds <* QUERY ( bnds <* fa.bounds | (
    'CONFIG_CONTROL_DESIGN.VERTEX_LOOP'
    IN TYPEOF(bnds.bound)) )
    | (NOT (SIZEOF(['CONFIG_CONTROL_DESIGN.CARTESIAN_POINT',
    'CONFIG_CONTROL_DESIGN.DEGENERATE_PCURVE',
    'CONFIG_CONTROL_DESIGN.POINT_ON_CURVE',
    'CONFIG_CONTROL_DESIGN.POINT_ON_SURFACE'] * TYPEOF(
    vlp_fbnds\vertex_loop.loop_vertex\vertex.point.
    vertex_geometry)) = 1)) )) = 0))) ))
    = 0)) )) = 0)) )) = 0);
END_ENTITY; -- manifold_surface_shape_representation

ENTITY mapped_item
    SUBTYPE OF (representation_item);
    mapping_source : representation_map;
    mapping_target : representation_item;
    WHERE
        wr1: acyclic_mapped_representation(using_representations(SELF),
            [SELF]);
END_ENTITY; -- mapped_item

ENTITY mass_measure_with_unit
    SUBTYPE OF (measure_with_unit);
    WHERE
        wr1: ('CONFIG_CONTROL_DESIGN.MASS_UNIT' IN TYPEOF(SELF\
            measure_with_unit.unit_component));
END_ENTITY; -- mass_measure_with_unit

ENTITY mass_unit
    SUBTYPE OF (named_unit);
    WHERE
        wr1: ((SELF\named_unit.dimensions.length_exponent = 0) AND (SELF\
            named_unit.dimensions.mass_exponent = 1) AND (SELF\
            named_unit.dimensions.time_exponent = 0) AND (SELF\
            named_unit.dimensions.electric_current_exponent = 0) AND (
            SELF\named_unit.dimensions.

```

```

        thermodynamic_temperature_exponent = 0) AND (SELF\named_unit
        .dimensions.amount_of_substance_exponent = 0) AND (SELF\
        named_unit.dimensions.luminous_intensity_exponent = 0));
END_ENTITY; -- mass_unit

ENTITY measure_with_unit
    SUPERTYPE OF (ONEOF (length_measure_with_unit,mass_measure_with_unit,
        plane_angle_measure_with_unit,solid_angle_measure_with_unit,
        area_measure_with_unit,volume_measure_with_unit));
    value_component : measure_value;
    unit_component  : unit;
    WHERE
        wr1: valid_units(SELF);
END_ENTITY; -- measure_with_unit

ENTITY mechanical_context
    SUBTYPE OF (product_context);
    WHERE
        wr1: (SELF.discipline_type = 'mechanical');
END_ENTITY; -- mechanical_context

ENTITY named_unit
    SUPERTYPE OF (ONEOF (si_unit,conversion_based_unit,
        context_dependent_unit) ANDOR ONEOF (length_unit,mass_unit,
        plane_angle_unit,solid_angle_unit,area_unit,volume_unit));
    dimensions : dimensional_exponents;
END_ENTITY; -- named_unit

ENTITY next_assembly_usage_occurrence
    SUBTYPE OF (assembly_component_usage);
END_ENTITY; -- next_assembly_usage_occurrence

ENTITY offset_curve_3d
    SUBTYPE OF (curve);
    basis_curve      : curve;
    distance          : length_measure;
    self_intersect    : LOGICAL;
    ref_direction     : direction;
    WHERE
        wr1: ((basis_curve.dim = 3) AND (ref_direction.dim = 3));
END_ENTITY; -- offset_curve_3d

```

```
ENTITY offset_surface
  SUBTYPE OF (surface);
    basis_surface : surface;
    distance       : length_measure;
    self_intersect : LOGICAL;
END_ENTITY; -- offset_surface

ENTITY open_shell
  SUBTYPE OF (connected_face_set);
END_ENTITY; -- open_shell

ENTITY ordinal_date
  SUBTYPE OF (date);
    day_component : day_in_year_number;
  WHERE
    wr1: (((NOT leap_year(SELF.year_component)) AND (1 <= day_component)
           AND (day_component <= 365)) OR (leap_year(SELF.
           year_component) AND (1 <= day_component) AND (day_component
           <= 366)));
END_ENTITY; -- ordinal_date

ENTITY organization;
  id : OPTIONAL identifier;
  name : label;
  description : text;
END_ENTITY; -- organization

ENTITY organization_relationship;
  name : label;
  description : text;
  relating_organization : organization;
  related_organization : organization;
END_ENTITY; -- organization_relationship

ENTITY organizational_address
  SUBTYPE OF (address);
    organizations : SET [1:?] OF organization;
    description : text;
END_ENTITY; -- organizational_address

ENTITY organizational_project;
  name : label;
```

```

        description          : text;
        responsible_organizations : SET [1:?] OF organization;
END_ENTITY; -- organizational_project

ENTITY oriented_closed_shell
    SUBTYPE OF (closed_shell);
    closed_shell_element : closed_shell;
    orientation          : BOOLEAN;
    DERIVE
        SELF\connected_face_set.cfs_faces : SET [1:?] OF face :=
            conditional_reverse(SELF.orientation,SELF.
                closed_shell_element.cfs_faces);
    WHERE
        wr1: (NOT ('CONFIG_CONTROL_DESIGN.ORIENTED_CLOSED_SHELL' IN TYPEOF(
            SELF.closed_shell_element)));
END_ENTITY; -- oriented_closed_shell

ENTITY oriented_edge
    SUBTYPE OF (edge);
    edge_element : edge;
    orientation  : BOOLEAN;
    DERIVE
        SELF\edge.edge_start : vertex := boolean_choose(SELF.orientation,
            SELF.edge_element.edge_start,SELF.
                edge_element.edge_end);
        SELF\edge.edge_end   : vertex := boolean_choose(SELF.orientation,
            SELF.edge_element.edge_end,SELF.
                edge_element.edge_start);
    WHERE
        wr1: (NOT ('CONFIG_CONTROL_DESIGN.ORIENTED_EDGE' IN TYPEOF(SELF.
            edge_element)));
END_ENTITY; -- oriented_edge

ENTITY oriented_face
    SUBTYPE OF (face);
    face_element : face;
    orientation  : BOOLEAN;
    DERIVE
        SELF\face.bounds : SET [1:?] OF face_bound := conditional_reverse(
            SELF.orientation,SELF.face_element.bounds);
    WHERE
        wr1: (NOT ('CONFIG_CONTROL_DESIGN.ORIENTED_FACE' IN TYPEOF(SELF.

```

```

        face_element))) ;
END_ENTITY; -- oriented_face

ENTITY oriented_open_shell
  SUBTYPE OF (open_shell);
    open_shell_element : open_shell;
    orientation          : BOOLEAN;
  DERIVE
    SELF\connected_face_set.cfs_faces : SET [1:?] OF face :=
                                          conditional_reverse(SELF.
                                          orientation, SELF.
                                          open_shell_element.cfs_faces);
  WHERE
    wr1: (NOT ('CONFIG_CONTROL_DESIGN.ORIENTED_OPEN_SHELL' IN TYPEOF(
      SELF.open_shell_element)));
END_ENTITY; -- oriented_open_shell

ENTITY oriented_path
  SUBTYPE OF (path);
    path_element : path;
    orientation   : BOOLEAN;
  DERIVE
    SELF\path.edge_list : LIST [1:?] OF UNIQUE oriented_edge :=
                                          conditional_reverse(SELF.orientation, SELF.
                                          path_element.edge_list);
  WHERE
    wr1: (NOT ('CONFIG_CONTROL_DESIGN.ORIENTED_PATH' IN TYPEOF(SELF.
      path_element)));
END_ENTITY; -- oriented_path

ENTITY outer_boundary_curve
  SUBTYPE OF (boundary_curve);
END_ENTITY; -- outer_boundary_curve

ENTITY parabola
  SUBTYPE OF (conic);
    focal_dist : length_measure;
  WHERE
    wr1: (focal_dist <> 0);
END_ENTITY; -- parabola

```

```
ENTITY parametric_representation_context
  SUBTYPE OF (representation_context);
END_ENTITY; -- parametric_representation_context

ENTITY path
  SUPERTYPE OF (ONEOF (edge_loop,oriented_path))
  SUBTYPE OF (topological_representation_item);
  edge_list : LIST [1:?] OF UNIQUE oriented_edge;
  WHERE
    wr1: path_head_to_tail(SELF);
END_ENTITY; -- path

ENTITY pcurve
  SUBTYPE OF (curve);
  basis_surface : surface;
  reference_to_curve : definitional_representation;
  WHERE
    wr1: (SIZEOF(reference_to_curve\representation.items) = 1);
    wr2: ('CONFIG_CONTROL_DESIGN.CURVE' IN TYPEOF(reference_to_curve\
      representation.items[1]));
    wr3: (reference_to_curve\representation.items[1]\
      geometric_representation_item.dim = 2);
END_ENTITY; -- pcurve

ENTITY person;
  id : identifier;
  last_name : OPTIONAL label;
  first_name : OPTIONAL label;
  middle_names : OPTIONAL LIST [1:?] OF label;
  prefix_titles : OPTIONAL LIST [1:?] OF label;
  suffix_titles : OPTIONAL LIST [1:?] OF label;
  UNIQUE
    url : id;
  WHERE
    wr1: (EXISTS(last_name) OR EXISTS(first_name));
END_ENTITY; -- person

ENTITY person_and_organization;
  the_person : person;
  the_organization : organization;
END_ENTITY; -- person_and_organization
```

```

ENTITY person_and_organization_assignment
  ABSTRACT SUPERTYPE;
    assigned_person_and_organization : person_and_organization;
    role                             : person_and_organization_role;
END_ENTITY; -- person_and_organization_assignment

ENTITY person_and_organization_role;
  name : label;
END_ENTITY; -- person_and_organization_role

ENTITY personal_address
  SUBTYPE OF (address);
    people      : SET [1:?] OF person;
    description : text;
END_ENTITY; -- personal_address

ENTITY placement
  SUPERTYPE OF (ONEOF (axis1_placement, axis2_placement_2d,
    axis2_placement_3d))
  SUBTYPE OF (geometric_representation_item);
    location : cartesian_point;
END_ENTITY; -- placement

ENTITY plane
  SUBTYPE OF (elementary_surface);
END_ENTITY; -- plane

ENTITY plane_angle_measure_with_unit
  SUBTYPE OF (measure_with_unit);
  WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.PLANE_ANGLE_UNIT' IN TYPEOF(SELF\
      measure_with_unit.unit_component));
END_ENTITY; -- plane_angle_measure_with_unit

ENTITY plane_angle_unit
  SUBTYPE OF (named_unit);
  WHERE
    wr1: ((SELF\named_unit.dimensions.length_exponent = 0) AND (SELF\
      named_unit.dimensions.mass_exponent = 0) AND (SELF\
      named_unit.dimensions.time_exponent = 0) AND (SELF\
      named_unit.dimensions.electric_current_exponent = 0) AND (
      SELF\named_unit.dimensions.

```

```

        thermodynamic_temperature_exponent = 0) AND (SELF\named_unit
        .dimensions.amount_of_substance_exponent = 0) AND (SELF\
        named_unit.dimensions.luminous_intensity_exponent = 0));
END_ENTITY; -- plane_angle_unit

```

```

ENTITY point

```

```

    SUPERTYPE OF (ONEOF (cartesian_point,point_on_curve,point_on_surface,
        point_replica,degenerate_pcurve))

```

```

    SUBTYPE OF (geometric_representation_item);

```

```

END_ENTITY; -- point

```

```

ENTITY point_on_curve

```

```

    SUBTYPE OF (point);

```

```

        basis_curve      : curve;

```

```

        point_parameter  : parameter_value;

```

```

END_ENTITY; -- point_on_curve

```

```

ENTITY point_on_surface

```

```

    SUBTYPE OF (point);

```

```

        basis_surface     : surface;

```

```

        point_parameter_u : parameter_value;

```

```

        point_parameter_v : parameter_value;

```

```

END_ENTITY; -- point_on_surface

```

```

ENTITY point_replica

```

```

    SUBTYPE OF (point);

```

```

        parent_pt        : point;

```

```

        transformation    : cartesian_transformation_operator;

```

```

    WHERE

```

```

        wr1: (transformation.dim = parent_pt.dim);

```

```

        wr2: acyclic_point_replica(SELf,parent_pt);

```

```

END_ENTITY; -- point_replica

```

```

ENTITY poly_loop

```

```

    SUBTYPE OF (loop, geometric_representation_item);

```

```

        polygon : LIST [3:?] OF UNIQUE cartesian_point;

```

```

END_ENTITY; -- poly_loop

```

```

ENTITY polyline

```

```

    SUBTYPE OF (bounded_curve);

```

```

        points : LIST [2:?] OF cartesian_point;

```

```

END_ENTITY; -- polyline

```

```
ENTITY product;
    id                : identifier;
    name              : label;
    description       : text;
    frame_of_reference : SET [1:?] OF product_context;
    UNIQUE
        url : id;
END_ENTITY; -- product

ENTITY product_category;
    name          : label;
    description : OPTIONAL text;
END_ENTITY; -- product_category

ENTITY product_category_relationship;
    name          : label;
    description   : text;
    category      : product_category;
    sub_category  : product_category;
    WHERE
        wr1: acyclic_product_category_relationship(SELF, [SELF.sub_category]);
END_ENTITY; -- product_category_relationship

ENTITY product_concept;
    id                : identifier;
    name              : label;
    description       : text;
    market_context   : product_concept_context;
    UNIQUE
        url : id;
END_ENTITY; -- product_concept

ENTITY product_concept_context
    SUBTYPE OF (application_context_element);
    market_segment_type : label;
END_ENTITY; -- product_concept_context

ENTITY product_context
    SUBTYPE OF (application_context_element);
    discipline_type : label;
END_ENTITY; -- product_context
```

```
ENTITY product_definition;
    id                : identifier;
    description        : text;
    formation          : product_definition_formation;
    frame_of_reference : product_definition_context;
END_ENTITY; -- product_definition

ENTITY product_definition_context
    SUBTYPE OF (application_context_element);
    life_cycle_stage : label;
END_ENTITY; -- product_definition_context

ENTITY product_definition_effectivity
    SUBTYPE OF (effectivity);
    usage : product_definition_relationship;
    UNIQUE
    url : usage, id;
END_ENTITY; -- product_definition_effectivity

ENTITY product_definition_formation;
    id                : identifier;
    description        : text;
    of_product        : product;
    UNIQUE
    url : id, of_product;
END_ENTITY; -- product_definition_formation

ENTITY product_definition_formation_with_specified_source
    SUBTYPE OF (product_definition_formation);
    make_or_buy : source;
END_ENTITY; -- product_definition_formation_with_specified_source

ENTITY product_definition_relationship;
    id                : identifier;
    name              : label;
    description        : text;
    relating_product_definition : product_definition;
    related_product_definition  : product_definition;
END_ENTITY; -- product_definition_relationship

ENTITY product_definition_shape
    SUBTYPE OF (property_definition);
```

```

    UNIQUE
        url : definition;
    WHERE
        wr1: (NOT ('CONFIG_CONTROL_DESIGN.SHAPE_DEFINITION' IN TYPEOF(SELF\
            property_definition.definition)));
END_ENTITY; -- product_definition_shape

ENTITY product_definition_usage
    SUPERTYPE OF (assembly_component_usage)
    SUBTYPE OF (product_definition_relationship);
    UNIQUE
        url : id, relating_product_definition, related_product_definition;
    WHERE
        wr1: acyclic_product_definition_relationship(SELF, [SELF\
            product_definition_relationship.related_product_definition],
            'CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION_USAGE');
END_ENTITY; -- product_definition_usage

ENTITY product_definition_with_associated_documents
    SUBTYPE OF (product_definition);
    documentation_ids : SET [1:?] OF document;
END_ENTITY; -- product_definition_with_associated_documents

ENTITY product_related_product_category
    SUBTYPE OF (product_category);
    products : SET [1:?] OF product;
END_ENTITY; -- product_related_product_category

ENTITY promissory_usage_occurrence
    SUBTYPE OF (assembly_component_usage);
END_ENTITY; -- promissory_usage_occurrence

ENTITY property_definition;
    name : label;
    description : text;
    definition : characterized_definition;
END_ENTITY; -- property_definition

ENTITY property_definition_representation;
    definition : property_definition;
    used_representation : representation;
END_ENTITY; -- property_definition_representation

```

```

ENTITY quantified_assembly_component_usage
  SUBTYPE OF (assembly_component_usage);
    quantity : measure_with_unit;
END_ENTITY; -- quantified_assembly_component_usage

ENTITY quasi_uniform_curve
  SUBTYPE OF (b_spline_curve);
END_ENTITY; -- quasi_uniform_curve

ENTITY quasi_uniform_surface
  SUBTYPE OF (b_spline_surface);
END_ENTITY; -- quasi_uniform_surface

ENTITY rational_b_spline_curve
  SUBTYPE OF (b_spline_curve);
    weights_data : LIST [2:?] OF REAL;
  DERIVE
    weights : ARRAY [0:upper_index_on_control_points] OF REAL :=
      list_to_array(weights_data, 0,
        upper_index_on_control_points);
  WHERE
    wr1: (SIZEOF(weights_data) = SIZEOF(SELF\b_spline_curve.
      control_points_list));
    wr2: curve_weights_positive(SELF);
END_ENTITY; -- rational_b_spline_curve

ENTITY rational_b_spline_surface
  SUBTYPE OF (b_spline_surface);
    weights_data : LIST [2:?] OF LIST [2:?] OF REAL;
  DERIVE
    weights : ARRAY [0:u_upper] OF ARRAY [0:v_upper] OF REAL :=
      make_array_of_array(weights_data, 0, u_upper, 0, v_upper);
  WHERE
    wr1: ((SIZEOF(weights_data) = SIZEOF(SELF\b_spline_surface.
      control_points_list)) AND (SIZEOF(weights_data[1]) = SIZEOF(
      SELF\b_spline_surface.control_points_list[1])));
    wr2: surface_weights_positive(SELF);
END_ENTITY; -- rational_b_spline_surface

ENTITY rectangular_composite_surface
  SUBTYPE OF (bounded_surface);
    segments : LIST [1:?] OF LIST [1:?] OF surface_patch;

```

```

DERIVE
  n_u : INTEGER := SIZEOF(segments);
  n_v : INTEGER := SIZEOF(segments[1]);
WHERE
  wr1: ([ ] = QUERY ( s <* segments | (n_v <> SIZEOF(s)) ));
  wr2: constraints_rectangular_composite_surface(SELF);
END_ENTITY; -- rectangular_composite_surface

ENTITY rectangular_trimmed_surface
  SUBTYPE OF (bounded_surface);
  basis_surface : surface;
  u1             : parameter_value;
  u2             : parameter_value;
  v1             : parameter_value;
  v2             : parameter_value;
  usense         : BOOLEAN;
  vsense         : BOOLEAN;
WHERE
  wr1: (u1 <> u2);
  wr2: (v1 <> v2);
  wr3: (((('CONFIG_CONTROL_DESIGN.ELEMENTARY_SURFACE' IN TYPEOF(
    basis_surface)) AND (NOT ('CONFIG_CONTROL_DESIGN.PLANE' IN
    TYPEOF(basis_surface)))) OR (
    'CONFIG_CONTROL_DESIGN.SURFACE_OF_REVOLUTION' IN TYPEOF(
    basis_surface)) OR (usense = (u2 > u1))));
  wr4: (('CONFIG_CONTROL_DESIGN.SPHERICAL_SURFACE' IN TYPEOF(
    basis_surface)) OR ('CONFIG_CONTROL_DESIGN.TOROIDAL_SURFACE'
    IN TYPEOF(basis_surface)) OR (vsense = (v2 > v1)));
END_ENTITY; -- rectangular_trimmed_surface

ENTITY reparametrised_composite_curve_segment
  SUBTYPE OF (composite_curve_segment);
  param_length : parameter_value;
WHERE
  wr1: (param_length > 0);
END_ENTITY; -- reparametrised_composite_curve_segment

ENTITY representation;
  name           : label;
  items          : SET [1:?] OF representation_item;
  context_of_items : representation_context;
END_ENTITY; -- representation

```

```

ENTITY representation_context;
    context_identifier : identifier;
    context_type       : text;
    INVERSE
        representations_in_context : SET [1:?] OF representation FOR
                                    context_of_items;
END_ENTITY; -- representation_context

ENTITY representation_item;
    name : label;
    WHERE
        wr1: (SIZEOF(using_representations(SELF)) > 0);
END_ENTITY; -- representation_item

ENTITY representation_map;
    mapping_origin      : representation_item;
    mapped_representation : representation;
    INVERSE
        map_usage : SET [1:?] OF mapped_item FOR mapping_source;
    WHERE
        wr1: item_in_context(SELF.mapping_origin, SELF.mapped_representation,
                               context_of_items);
END_ENTITY; -- representation_map

ENTITY representation_relationship;
    name          : label;
    description    : text;
    rep_1          : representation;
    rep_2          : representation;
END_ENTITY; -- representation_relationship

ENTITY representation_relationship_with_transformation
    SUBTYPE OF (representation_relationship);
    transformation_operator : transformation;
    WHERE
        wr1: (SELF\representation_relationship.rep_1.context_of_items :<>:
               SELF\representation_relationship.rep_2.context_of_items);
END_ENTITY; -- representation_relationship_with_transformation

ENTITY seam_curve
    SUBTYPE OF (surface_curve);
    WHERE

```

```

wr1: (SIZEOF(SELF\surface_curve.associated_geometry) = 2);
wr2: (associated_surface(SELF\surface_curve.associated_geometry[1])
      = associated_surface(SELF\surface_curve.associated_geometry[
        2]));
wr3: ('CONFIG_CONTROL_DESIGN.PCURVE' IN TYPEOF(SELF\surface_curve.
      associated_geometry[1]));
wr4: ('CONFIG_CONTROL_DESIGN.PCURVE' IN TYPEOF(SELF\surface_curve.
      associated_geometry[2]));
END_ENTITY; -- seam_curve

```

```

ENTITY security_classification;
    name          : label;
    purpose        : text;
    security_level : security_classification_level;
END_ENTITY; -- security_classification

```

```

ENTITY security_classification_assignment
    ABSTRACT SUPERTYPE;
    assigned_security_classification : security_classification;
END_ENTITY; -- security_classification_assignment

```

```

ENTITY security_classification_level;
    name : label;
END_ENTITY; -- security_classification_level

```

```

ENTITY serial_numbered_effectivity
    SUBTYPE OF (effectivity);
    effectivity_start_id : identifier;
    effectivity_end_id   : OPTIONAL identifier;
END_ENTITY; -- serial_numbered_effectivity

```

```

ENTITY shape_aspect;
    name          : label;
    description    : text;
    of_shape       : product_definition_shape;
    product_definitional : LOGICAL;
END_ENTITY; -- shape_aspect

```

```

ENTITY shape_aspect_relationship;
    name          : label;
    description    : text;
    relating_shape_aspect : shape_aspect;

```

```

        related_shape_aspect : shape_aspect;
END_ENTITY; -- shape_aspect_relationship

ENTITY shape_definition_representation
  SUBTYPE OF (property_definition_representation);
  WHERE
    wr1: (('CONFIG_CONTROL_DESIGN.SHAPE_DEFINITION' IN TYPEOF(SELF.
      definition.definition)) OR (
      'CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION_SHAPE' IN TYPEOF(
      SELF.definition)));
    wr2: ('CONFIG_CONTROL_DESIGN.SHAPE_REPRESENTATION' IN TYPEOF(SELF.
      used_representation));
END_ENTITY; -- shape_definition_representation

ENTITY shape_representation
  SUBTYPE OF (representation);
END_ENTITY; -- shape_representation

ENTITY shape_representation_relationship
  SUBTYPE OF (representation_relationship);
  WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.SHAPE_REPRESENTATION' IN (TYPEOF(SELF\
      representation_relationship.rep_1) + TYPEOF(SELF\
      representation_relationship.rep_2)));
END_ENTITY; -- shape_representation_relationship

ENTITY shell_based_surface_model
  SUBTYPE OF (geometric_representation_item);
  sbsm_boundary : SET [1:?] OF shell;
  WHERE
    wr1: constraints_geometry_shell_based_surface_model(SELF);
END_ENTITY; -- shell_based_surface_model

ENTITY shell_based_wireframe_model
  SUBTYPE OF (geometric_representation_item);
  sbwm_boundary : SET [1:?] OF shell;
  WHERE
    wr1: constraints_geometry_shell_based_wireframe_model(SELF);
END_ENTITY; -- shell_based_wireframe_model

ENTITY shell_based_wireframe_shape_representation
  SUBTYPE OF (shape_representation);

```

WHERE

```

wr1 : (SIZEOF(QUERY ( it <* SELF.items | (NOT (SIZEOF([
    'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL',
    'CONFIG_CONTROL_DESIGN.MAPPED_ITEM',
    'CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D'] * TYPEOF(it)) =
    1)) )) = 0);

wr2 : (SIZEOF(QUERY ( it <* SELF.items | (SIZEOF([
    'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL',
    'CONFIG_CONTROL_DESIGN.MAPPED_ITEM'] * TYPEOF(it)) = 1)) ))
    >= 1);

wr3 : (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( ws <* QUERY ( sb <*
    sbwm\shell_based_wireframe_model.sbwm_boundary | (
    'CONFIG_CONTROL_DESIGN.WIRE_SHELL' IN TYPEOF(sb)) ) | (NOT
    (SIZEOF(QUERY ( eloop <* QUERY ( wsb <* ws\wire_shell.
    wire_shell_extent | ('CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN
    TYPEOF(wsb)) ) | (NOT (SIZEOF(QUERY ( el <* eloop\path.
    edge_list | (NOT ('CONFIG_CONTROL_DESIGN.EDGE_CURVE' IN
    TYPEOF(el.edge_element)))) )) = 0)) ))
    = 0)) )) = 0)) )) = 0);

wr4 : (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( ws <* QUERY ( sb <*
    sbwm\shell_based_wireframe_model.sbwm_boundary | (
    'CONFIG_CONTROL_DESIGN.WIRE_SHELL' IN TYPEOF(sb)) ) | (NOT
    (SIZEOF(QUERY ( eloop <* QUERY ( wsb <* ws\wire_shell.
    wire_shell_extent | ('CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN
    TYPEOF(wsb)) ) | (NOT (SIZEOF(QUERY ( pline_el <*
    QUERY ( el <* eloop\path.edge_list | (
    'CONFIG_CONTROL_DESIGN.POLYLINE' IN TYPEOF(el.edge_element\
    edge_curve.edge_geometry)) ) | (NOT (SIZEOF(pline_el.
    edge_element\edge_curve.edge_geometry\polyline.points)
    > 2)) )) = 0)) )) = 0)) )) = 0)) )) = 0);

wr5 : (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
    'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
    TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( ws <* QUERY ( sb <*
    sbwm\shell_based_wireframe_model.sbwm_boundary | (
    'CONFIG_CONTROL_DESIGN.WIRE_SHELL' IN TYPEOF(sb)) ) | (NOT
    (SIZEOF(QUERY ( eloop <* QUERY ( wsb <* ws\wire_shell.
    wire_shell_extent | ('CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN
    TYPEOF(wsb)) ) | (NOT (SIZEOF(QUERY ( el <* eloop\path.

```

```

edge_list | (NOT valid_wireframe_edge_curve(el.edge_element
\edge_curve.edge_geometry)) )) = 0)) )) = 0)) )) = 0)) )) =
0);

wr6 : (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( ws <* QUERY ( sb <*
sbwm\shell_based_wireframe_model.sbwm_boundary | (
'CONFIG_CONTROL_DESIGN.WIRE_SHELL' IN TYPEOF(sb)) ) | (NOT
(SIZEOF(QUERY ( eloop <* QUERY ( wsb <* ws\wire_shell.
wire_shell_extent | ('CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN
TYPEOF(wsb)) ) | (NOT (SIZEOF(QUERY ( el <* eloop\path.
edge_list | (NOT (('CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN
TYPEOF(el.edge_element.edge_start)) AND (
'CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(el.
edge_element.edge_end)))))) )) = 0)) ))
= 0)) )) = 0)) )) = 0);

wr7 : (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( ws <* QUERY ( sb <*
sbwm\shell_based_wireframe_model.sbwm_boundary | (
'CONFIG_CONTROL_DESIGN.WIRE_SHELL' IN TYPEOF(sb)) ) | (NOT
(SIZEOF(QUERY ( eloop <* QUERY ( wsb <* ws\wire_shell.
wire_shell_extent | ('CONFIG_CONTROL_DESIGN.EDGE_LOOP' IN
TYPEOF(wsb)) ) | (NOT (SIZEOF(QUERY ( el <* eloop\path.
edge_list | (NOT (valid_wireframe_vertex_point(el.
edge_element.edge_start\vertex_point.vertex_geometry) AND
valid_wireframe_vertex_point(el.edge_element.edge_end\
vertex_point.vertex_geometry)))))) )) = 0)) ))
= 0)) )) = 0)) )) = 0);

wr8 : (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( ws <* QUERY ( sb <*
sbwm\shell_based_wireframe_model.sbwm_boundary | (
'CONFIG_CONTROL_DESIGN.WIRE_SHELL' IN TYPEOF(sb)) ) | (NOT
(SIZEOF(QUERY ( vloop <* QUERY ( wsb <* ws\wire_shell.
wire_shell_extent | ('CONFIG_CONTROL_DESIGN.VERTEX_LOOP' IN
TYPEOF(wsb)) ) | (NOT (
'CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(vloop\
vertex_loop.loop_vertex)))))) )) = 0)) )) = 0)) )) = 0);

wr9 : (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( ws <* QUERY ( sb <*

```

```

        sbwm\shell_based_wireframe_model.sbwm_boundary | (
        'CONFIG_CONTROL_DESIGN.WIRE_SHELL' IN TYPEOF(sb)) ) | (NOT
        (SIZEOF(QUERY ( vloop <* QUERY ( wsb <* ws\wire_shell.
        wire_shell_extent | ('CONFIG_CONTROL_DESIGN.VERTEX_LOOP' IN
        TYPEOF(wsb)) ) | (NOT valid_wireframe_vertex_point(vloop\
        vertex_loop.loop_vertex\vertex_point.vertex_geometry)) )) =
        0)) )) = 0)) )) = 0);
wr10: (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( vs <* QUERY ( sb <*
        sbwm\shell_based_wireframe_model.sbwm_boundary | (
        'CONFIG_CONTROL_DESIGN.VERTEX_SHELL' IN TYPEOF(sb)) ) | (
        NOT ('CONFIG_CONTROL_DESIGN.VERTEX_POINT' IN TYPEOF(vs\
        vertex_shell.vertex_shell_extent.loop_vertex))) )) = 0)) ))
        = 0);
wr11: (SIZEOF(QUERY ( sbwm <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.SHELL_BASED_WIREFRAME_MODEL' IN
        TYPEOF(it)) ) | (NOT (SIZEOF(QUERY ( vs <* QUERY ( sb <*
        sbwm\shell_based_wireframe_model.sbwm_boundary | (
        'CONFIG_CONTROL_DESIGN.VERTEX_SHELL' IN TYPEOF(sb)) ) | (
        NOT valid_wireframe_vertex_point(vs\vertex_shell.
        vertex_shell_extent.loop_vertex\vertex_point.
        vertex_geometry)) )) = 0)) )) = 0);
wr12: (SIZEOF(QUERY ( mi <* QUERY ( it <* SELF.items | (
        'CONFIG_CONTROL_DESIGN.MAPPED_ITEM' IN TYPEOF(it)) ) | (
        NOT (('CONFIG_CONTROL_DESIGN.' +
        'SHELL_BASED_WIREFRAME_SHAPE_REPRESENTATION') IN TYPEOF(mi\
        mapped_item.mapping_source.mapped_representation))) ))
        = 0);
wr13: (SELF.context_of_items\geometric_representation_context.
        coordinate_space_dimension = 3);
END_ENTITY; -- shell_based_wireframe_shape_representation

ENTITY si_unit
    SUBTYPE OF (named_unit);
    prefix : OPTIONAL si_prefix;
    name : si_unit_name;
    DERIVE
        SELF\named_unit.dimensions : dimensional_exponents :=
            dimensions_for_si_unit(SELF.name);
END_ENTITY; -- si_unit

```

```

ENTITY solid_angle_measure_with_unit
  SUBTYPE OF (measure_with_unit);
  WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.SOLID_ANGLE_UNIT' IN TYPEOF(SELF\
      measure_with_unit.unit_component));
END_ENTITY; -- solid_angle_measure_with_unit

ENTITY solid_angle_unit
  SUBTYPE OF (named_unit);
  WHERE
    wr1: ((SELF\named_unit.dimensions.length_exponent = 0) AND (SELF\
      named_unit.dimensions.mass_exponent = 0) AND (SELF\
      named_unit.dimensions.time_exponent = 0) AND (SELF\
      named_unit.dimensions.electric_current_exponent = 0) AND (
      SELF\named_unit.dimensions.
      thermodynamic_temperature_exponent = 0) AND (SELF\named_unit
      .dimensions.amount_of_substance_exponent = 0) AND (SELF\
      named_unit.dimensions.luminous_intensity_exponent = 0));
END_ENTITY; -- solid_angle_unit

ENTITY solid_model
  SUPERTYPE OF (manifold_solid_brep)
  SUBTYPE OF (geometric_representation_item);
END_ENTITY; -- solid_model

ENTITY specified_higher_usage_occurrence
  SUBTYPE OF (assembly_component_usage);
  upper_usage : assembly_component_usage;
  next_usage : next_assembly_usage_occurrence;
  UNIQUE
    ur1 : upper_usage, next_usage;
  WHERE
    wr1: (SELF :<>: upper_usage);
    wr2: (SELF\product_definition_relationship.
      relating_product_definition :=: upper_usage.
      relating_product_definition);
    wr3: (SELF\product_definition_relationship.
      related_product_definition :=: next_usage.
      related_product_definition);
    wr4: (upper_usage.related_product_definition :=: next_usage.
      relating_product_definition);
    wr5: (NOT ('CONFIG_CONTROL_DESIGN.PROMISSORY_USAGE_OCCURRENCE' IN

```

```

        TYPEOF(upper_usage)));
END_ENTITY; -- specified_higher_usage_occurrence

ENTITY spherical_surface
    SUBTYPE OF (elementary_surface);
    radius : positive_length_measure;
END_ENTITY; -- spherical_surface

ENTITY start_request
    SUBTYPE OF (action_request_assignment);
    items : SET [1:?] OF start_request_item;
END_ENTITY; -- start_request

ENTITY start_work
    SUBTYPE OF (action_assignment);
    items : SET [1:?] OF work_item;
END_ENTITY; -- start_work

ENTITY supplied_part_relationship
    SUBTYPE OF (product_definition_relationship);
END_ENTITY; -- supplied_part_relationship

ENTITY surface
    SUPERTYPE OF (ONEOF (elementary_surface, swept_surface, bounded_surface,
        offset_surface, surface_replica))
    SUBTYPE OF (geometric_representation_item);
END_ENTITY; -- surface

ENTITY surface_curve
    SUPERTYPE OF (ONEOF (intersection_curve, seam_curve) ANDOR
        bounded_surface_curve)
    SUBTYPE OF (curve);
    curve_3d : curve;
    associated_geometry : LIST [1:2] OF pcurve_or_surface;
    master_representation : preferred_surface_curve_representation;
    DERIVE
        basis_surface : SET [1:2] OF surface := get_basis_surface(SELF);
    WHERE
        wr1: (curve_3d.dim = 3);
        wr2: (('CONFIG_CONTROL_DESIGN.PCURVE' IN TYPEOF(associated_geometry[
            1])) OR (master_representation <> pcurve_s1));
        wr3: (('CONFIG_CONTROL_DESIGN.PCURVE' IN TYPEOF(associated_geometry[

```

```

                2))) OR (master_representation <> pcurve_s2));
        wr4: (NOT ('CONFIG_CONTROL_DESIGN.PCURVE' IN TYPEOF(curve_3d)));
END_ENTITY; -- surface_curve

ENTITY surface_of_linear_extrusion
    SUBTYPE OF (swept_surface);
        extrusion_axis : vector;
END_ENTITY; -- surface_of_linear_extrusion

ENTITY surface_of_revolution
    SUBTYPE OF (swept_surface);
        axis_position : axis1_placement;
    DERIVE
        axis_line : line := dummy_gri || curve() || line(axis_position.
            location,dummy_gri || vector(axis_position.z,1));
END_ENTITY; -- surface_of_revolution

ENTITY surface_patch
    SUBTYPE OF (founded_item);
        parent_surface : bounded_surface;
        u_transition    : transition_code;
        v_transition    : transition_code;
        u_sense         : BOOLEAN;
        v_sense         : BOOLEAN;
    INVERSE
        using_surfaces : BAG [1:?] OF rectangular_composite_surface FOR
            segments;
    WHERE
        wr1: (NOT ('CONFIG_CONTROL_DESIGN.CURVE_BOUNDED_SURFACE' IN TYPEOF(
            parent_surface)));
END_ENTITY; -- surface_patch

ENTITY surface_replica
    SUBTYPE OF (surface);
        parent_surface : surface;
        transformation : cartesian_transformation_operator_3d;
    WHERE
        wr1: acyclic_surface_replica(SELF,parent_surface);
END_ENTITY; -- surface_replica

ENTITY swept_surface
    SUPERTYPE OF (ONEOF (surface_of_linear_extrusion,

```

```

        surface_of_revolution))
    SUBTYPE OF (surface);
        swept_curve : curve;
END_ENTITY; -- swept_surface

ENTITY topological_representation_item
    SUPERTYPE OF (ONEOF (vertex,edge,face_bound,face,vertex_shell,
        wire_shell,connected_edge_set,connected_face_set,loop ANDOR path))
    SUBTYPE OF (representation_item);
END_ENTITY; -- topological_representation_item

ENTITY toroidal_surface
    SUBTYPE OF (elementary_surface);
        major_radius : positive_length_measure;
        minor_radius : positive_length_measure;
END_ENTITY; -- toroidal_surface

ENTITY trimmed_curve
    SUBTYPE OF (bounded_curve);
        basis_curve      : curve;
        trim_1           : SET [1:2] OF trimming_select;
        trim_2           : SET [1:2] OF trimming_select;
        sense_agreement  : BOOLEAN;
        master_representation : trimming_preference;
    WHERE
        wr1: ((HIINDEX(trim_1) = 1) OR (TYPEOF(trim_1[1]) <>
            TYPEOF(trim_1[2])));
        wr2: ((HIINDEX(trim_2) = 1) OR (TYPEOF(trim_2[1]) <>
            TYPEOF(trim_2[2])));
END_ENTITY; -- trimmed_curve

ENTITY uncertainty_measure_with_unit
    SUBTYPE OF (measure_with_unit);
        name      : label;
        description : text;
    WHERE
        wr1: valid_measure_value(SELf\measure_with_unit.value_component);
END_ENTITY; -- uncertainty_measure_with_unit

ENTITY uniform_curve
    SUBTYPE OF (b_spline_curve);
END_ENTITY; -- uniform_curve

```

```
ENTITY uniform_surface
  SUBTYPE OF (b_spline_surface);
END_ENTITY; -- uniform_surface

ENTITY vector
  SUBTYPE OF (geometric_representation_item);
  orientation : direction;
  magnitude   : length_measure;
  WHERE
    wr1: (magnitude >= 0);
END_ENTITY; -- vector

ENTITY versioned_action_request;
  id          : identifier;
  version     : label;
  purpose     : text;
  description : text;
END_ENTITY; -- versioned_action_request

ENTITY vertex
  SUBTYPE OF (topological_representation_item);
END_ENTITY; -- vertex

ENTITY vertex_loop
  SUBTYPE OF (loop);
  loop_vertex : vertex;
END_ENTITY; -- vertex_loop

ENTITY vertex_point
  SUBTYPE OF (vertex, geometric_representation_item);
  vertex_geometry : point;
END_ENTITY; -- vertex_point

ENTITY vertex_shell
  SUBTYPE OF (topological_representation_item);
  vertex_shell_extent : vertex_loop;
END_ENTITY; -- vertex_shell

ENTITY volume_measure_with_unit
  SUBTYPE OF (measure_with_unit);
  WHERE
    wr1: ('CONFIG_CONTROL_DESIGN.VOLUME_UNIT' IN TYPEOF(SEL\
```

```

        measure_with_unit.unit_component));
END_ENTITY; -- volume_measure_with_unit

ENTITY volume_unit
  SUBTYPE OF (named_unit);
  WHERE
    wr1: ((SELF\named_unit.dimensions.length_exponent = 3) AND (SELF\
      named_unit.dimensions.mass_exponent = 0) AND (SELF\
      named_unit.dimensions.time_exponent = 0) AND (SELF\
      named_unit.dimensions.electric_current_exponent = 0) AND (
      SELF\named_unit.dimensions.
      thermodynamic_temperature_exponent = 0) AND (SELF\named_unit
      .dimensions.amount_of_substance_exponent = 0) AND (SELF\
      named_unit.dimensions.luminous_intensity_exponent = 0));
END_ENTITY; -- volume_unit

ENTITY week_of_year_and_day_date
  SUBTYPE OF (date);
  week_component : week_in_year_number;
  day_component  : OPTIONAL day_in_week_number;
END_ENTITY; -- week_of_year_and_day_date

ENTITY wire_shell
  SUBTYPE OF (topological_representation_item);
  wire_shell_extent : SET [1:?] OF loop;
  WHERE
    wr1: (NOT mixed_loop_type_set(wire_shell_extent));
END_ENTITY; -- wire_shell

RULE acu_requires_security_classification FOR (assembly_component_usage,
  cc_design_security_classification);
WHERE
  wr1: (SIZEOF(QUERY ( acu <* assembly_component_usage | (NOT (SIZEOF(
    QUERY ( ccdsc <* cc_design_security_classification | (acu IN
    ccdsc.items) )) = 1)) )) = 0);
END_RULE; -- acu_requires_security_classification

RULE application_context_requires_ap_definition FOR (application_context,
  application_protocol_definition);
WHERE
  wr1: (SIZEOF(QUERY ( ac <* application_context | (NOT (SIZEOF(
    QUERY ( apd <* application_protocol_definition | ((ac ::= apd.

```

```

        application) AND (apd.
        application_interpreted_model_schema_name =
        'config_control_design')) )) = 1)) )) = 0);
END_RULE; -- application_context_requires_ap_definition

RULE approval_date_time_constraints FOR (approval_date_time);
WHERE
    wr1: (SIZEOF(QUERY ( adt <* approval_date_time | (NOT (SIZEOF(TYPEOF(
        adt.date_time) * ['CONFIG_CONTROL_DESIGN.DATE_AND_TIME'])
        = 1)) )) = 0);
END_RULE; -- approval_date_time_constraints

RULE approval_person_organization_constraints FOR (
    approval_person_organization);
WHERE
    wr1: (SIZEOF(QUERY ( apo <* approval_person_organization | (NOT (
        SIZEOF(TYPEOF(apo.person_organization) * [
        'CONFIG_CONTROL_DESIGN.PERSON_AND_ORGANIZATION'])
        = 1)) )) = 0);
END_RULE; -- approval_person_organization_constraints

RULE approval_requires_approval_date_time FOR (approval,
    approval_date_time);
WHERE
    wr1: (SIZEOF(QUERY ( app <* approval | (NOT (SIZEOF(QUERY ( adt <*
        approval_date_time | (app :=: adt.dated_approval) )) = 1)) ))
        = 0);
END_RULE; -- approval_requires_approval_date_time

RULE approval_requires_approval_person_organization FOR (approval,
    approval_person_organization);
WHERE
    wr1: (SIZEOF(QUERY ( app <* approval | (NOT (SIZEOF(QUERY ( apo <*
        approval_person_organization | (app :=: apo.
        authorized_approval) )) >= 1)) )) = 0);
END_RULE; -- approval_requires_approval_person_organization

RULE approvals_are_assigned FOR (approval, approval_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( app <* approval | (NOT (SIZEOF(QUERY ( aa <*
        approval_assignment | (app :=: aa.assigned_approval) ))

```

```

        >= 1)) )) = 0);
END_RULE; -- approvals_are_assigned

RULE as_required_quantity FOR (measure_with_unit);
WHERE
    wr1: (SIZEOF(QUERY ( m <* measure_with_unit | ((
        'CONFIG_CONTROL_DESIGN.DESCRPTIVE_MEASURE' IN TYPEOF(m.
        value_component)) AND (NOT (m.value_component =
        'as_required')))) )) = 0);
END_RULE; -- as_required_quantity

RULE certification_requires_approval FOR (certification,
    cc_design_approval);
WHERE
    wr1: (SIZEOF(QUERY ( cert <* certification | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_approval | (cert IN ccda.items) )) =
        1)) )) = 0);
END_RULE; -- certification_requires_approval

RULE certification_requires_date_time FOR (certification,
    cc_design_date_and_time_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( cert <* certification | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_date_and_time_assignment | (cert IN
        ccda.items) )) = 1)) )) = 0);
END_RULE; -- certification_requires_date_time

RULE change_request_requires_approval FOR (change_request,
    cc_design_approval);
WHERE
    wr1: (SIZEOF(QUERY ( cr <* change_request | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_approval | (cr IN ccda.items) ))
        = 1)) )) = 0);
END_RULE; -- change_request_requires_approval

RULE change_request_requires_date_time FOR (change_request,
    cc_design_date_and_time_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( cr <* change_request | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_date_and_time_assignment | (cr IN
        ccda.items) )) = 1)) )) = 0);
END_RULE; -- change_request_requires_date_time

```

```
RULE change_request_requires_person_organization FOR (change_request,
    cc_design_person_and_organization_assignment);
```

```
WHERE
```

```
    wr1: (SIZEOF(QUERY ( cr <* change_request | (NOT (SIZEOF(
        QUERY ( ccpoa <* cc_design_person_and_organization_assignment
            | (cr IN ccpoa.items) )) >= 1)) )) = 0);
```

```
END_RULE; -- change_request_requires_person_organization
```

```
RULE change_requires_approval FOR (change, cc_design_approval);
```

```
WHERE
```

```
    wr1: (SIZEOF(QUERY ( chg <* change | (NOT (SIZEOF(QUERY ( ccda <*
        cc_design_approval | (chg IN ccda.items) )) = 1)) )) = 0);
```

```
END_RULE; -- change_requires_approval
```

```
RULE change_requires_date_time FOR (change,
    cc_design_date_and_time_assignment);
```

```
WHERE
```

```
    wr1: (SIZEOF(QUERY ( chg <* change | (NOT (SIZEOF(QUERY ( ccdta <*
        cc_design_date_and_time_assignment | ((chg IN ccdta.items) AND
            (ccdta.role.name = 'start_date')) )) = 1)) )) = 0);
```

```
END_RULE; -- change_requires_date_time
```

```
RULE compatible_dimension FOR (cartesian_point, direction,
    representation_context, geometric_representation_context);
```

```
WHERE
```

```
    wr1: (SIZEOF(QUERY ( x <* cartesian_point | (SIZEOF(QUERY ( y <*
        geometric_representation_context | (item_in_context(x,y) AND (
            HIINDEX(x.coordinates) <> y.coordinate_space_dimension)) )) >
            0) )) = 0);
```

```
    wr2: (SIZEOF(QUERY ( x <* direction | (SIZEOF(QUERY ( y <*
        geometric_representation_context | (item_in_context(x,y) AND (
            HIINDEX(x.direction_ratios) <> y.coordinate_space_dimension))
            )) > 0) )) = 0);
```

```
END_RULE; -- compatible_dimension
```

```
RULE configuration_item_requires_approval FOR (configuration_item,
    cc_design_approval);
```

```
WHERE
```

```
    wr1: (SIZEOF(QUERY ( ci <* configuration_item | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_approval | (ci IN ccda.items) ))
            = 1)) )) = 0);
```

```
END_RULE; -- configuration_item_requires_approval
```

```

RULE configuration_item_requires_person_organization FOR (
    configuration_item,
    cc_design_person_and_organization_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( ci <* configuration_item | (NOT (SIZEOF(
        QUERY ( ccdpoa <* cc_design_person_and_organization_assignment
            | (ci IN ccdpoa.items) )) = 1)) )) = 0);
END_RULE; -- configuration_item_requires_person_organization

RULE contract_requires_approval FOR (contract, cc_design_approval);
WHERE
    wr1: (SIZEOF(QUERY ( c <* contract | (NOT (SIZEOF(QUERY ( ccda <*
        cc_design_approval | (c IN ccda.items) )) = 1)) )) = 0);
END_RULE; -- contract_requires_approval

RULE contract_requires_person_organization FOR (contract,
    cc_design_person_and_organization_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( c <* contract | (NOT (SIZEOF(QUERY ( ccdpoa <*
        cc_design_person_and_organization_assignment | (c IN ccdpoa.
            items) )) = 1)) )) = 0);
END_RULE; -- contract_requires_person_organization

RULE coordinated_assembly_and_shape FOR (next_assembly_usage_occurrence);
WHERE
    wr1: (SIZEOF(QUERY ( nauo <* next_assembly_usage_occurrence | (NOT
        assembly_shape_is_defined(nauo, 'CONFIG_CONTROL_DESIGN')) )) =
        0);
END_RULE; -- coordinated_assembly_and_shape

RULE dependent_instantiable_action_directive FOR (action_directive);
WHERE
    wr1: (SIZEOF(QUERY ( ad <* action_directive | (NOT (SIZEOF(USEDIN(ad,
        '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_action_directive

RULE dependent_instantiable_approval_status FOR (approval_status);
WHERE
    wr1: (SIZEOF(QUERY ( ast <* approval_status | (NOT (SIZEOF(USEDIN(ast,
        '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_approval_status

```

```

RULE dependent_instantiable_certification_type FOR (certification_type);
WHERE
    wr1: (SIZEOF(QUERY ( ct <* certification_type | (NOT (SIZEOF(USEDIN(ct,
        '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_certification_type

RULE dependent_instantiable_contract_type FOR (contract_type);
WHERE
    wr1: (SIZEOF(QUERY ( ct <* contract_type | (NOT (SIZEOF(USEDIN(ct, ''))
        >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_contract_type

RULE dependent_instantiable_date FOR (date);
WHERE
    wr1: (SIZEOF(QUERY ( dt <* date | (NOT (SIZEOF(USEDIN(dt, '')) >= 1)) ))
        = 0);
END_RULE; -- dependent_instantiable_date

RULE dependent_instantiable_date_time_role FOR (date_time_role);
WHERE
    wr1: (SIZEOF(QUERY ( dtr <* date_time_role | (NOT (SIZEOF(USEDIN(dtr,
        '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_date_time_role

RULE dependent_instantiable_document_type FOR (document_type);
WHERE
    wr1: (SIZEOF(QUERY ( dt <* document_type | (NOT (SIZEOF(USEDIN(dt, ''))
        >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_document_type

RULE dependent_instantiable_named_unit FOR (named_unit);
WHERE
    wr1: (SIZEOF(QUERY ( nu <* named_unit | (NOT (SIZEOF(USEDIN(nu, '')) >=
        1)) )) = 0);
END_RULE; -- dependent_instantiable_named_unit

RULE dependent_instantiable_parametric_representation_context FOR (
    parametric_representation_context);
WHERE
    wr1: (SIZEOF(QUERY ( prc <* parametric_representation_context | (NOT (
        SIZEOF(USEDIN(prc, '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_parametric_representation_context

```

```

RULE dependent_instantiable_person_and_organization_role FOR (
    person_and_organization_role);
WHERE
    wr1: (SIZEOF(QUERY ( poar <* person_and_organization_role | (NOT (
        SIZEOF(USEDIN(poar, '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_person_and_organization_role

RULE dependent_instantiable_representation_item FOR
    (representation_item);
WHERE
    wr1: (SIZEOF(QUERY ( ri <* representation_item | (NOT (SIZEOF(USEDIN(
        ri, '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_representation_item

RULE dependent_instantiable_security_classification_level FOR (
    security_classification_level);
WHERE
    wr1: (SIZEOF(QUERY ( scl <* security_classification_level | (NOT (
        SIZEOF(USEDIN(scl, '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_security_classification_level

RULE dependent_instantiable_shape_representation FOR (
    shape_representation);
WHERE
    wr1: (SIZEOF(QUERY ( sr <* shape_representation | (NOT (SIZEOF(USEDIN(
        sr, '')) >= 1)) )) = 0);
END_RULE; -- dependent_instantiable_shape_representation

RULE design_context_for_property FOR (product_definition);
WHERE
    wr1: (SIZEOF(QUERY ( pd <* product_definition | ((SIZEOF(USEDIN(pd,
        'CONFIG_CONTROL_DESIGN.' + 'PROPERTY_DEFINITION.DEFINITION') +
        QUERY ( pdr <* USEDIN(pd, 'CONFIG_CONTROL_DESIGN.' +
        'PRODUCT_DEFINITION_RELATIONSHIP.RELATED_PRODUCT_DEFINITION')
        | (SIZEOF(USEDIN(pdr,
        'CONFIG_CONTROL_DESIGN.PROPERTY_DEFINITION.' + 'DEFINITION'))
        >= 1) )) >= 1) AND (NOT (
        'CONFIG_CONTROL_DESIGN.DESIGN_CONTEXT' IN TYPEOF(pd.
        frame_of_reference)))))) = 0);
END_RULE; -- design_context_for_property

```

```

RULE document_to_product_definition FOR (
    cc_design_specification_reference);
WHERE
    wr1: (SIZEOF(QUERY ( sp <* cc_design_specification_reference | (NOT ((
        (('CONFIG_CONTROL_DESIGN.DOCUMENT_RELATIONSHIP.' +
        'RELATING_DOCUMENT') IN ROLESOF(sp\document_reference.
        assigned_document)) AND (SIZEOF(QUERY ( it <* sp.items | (NOT
        ('CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION' IN TYPEOF(it))) ))
        = 0)) OR (NOT (('CONFIG_CONTROL_DESIGN.DOCUMENT_RELATIONSHIP.'
        + 'RELATING_DOCUMENT') IN ROLESOF(sp\document_reference.
        assigned_document))))) )) = 0);
END_RULE; -- document_to_product_definition

RULE effectivity_requires_approval FOR (effectivity, cc_design_approval);
WHERE
    wr1: (SIZEOF(QUERY ( eff <* effectivity | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_approval | (eff IN ccda.items) )) =
        1)) )) = 0);
END_RULE; -- effectivity_requires_approval

RULE geometric_representation_item_3d FOR
    (geometric_representation_item);
WHERE
    wr1: (SIZEOF(QUERY ( gri <* geometric_representation_item | (NOT ((
        dimension_of(gri) = 3) OR (SIZEOF(QUERY ( ur <*
        using_representations(gri) | (
        'CONFIG_CONTROL_DESIGN.DEFINITIONAL_REPRESENTATION' IN TYPEOF(
        ur)) )) > 0))) )) = 0);
END_RULE; -- geometric_representation_item_3d

RULE global_unit_assignment FOR (global_unit_assigned_context);
WHERE
    wr1: (SIZEOF(QUERY ( guac <* global_unit_assigned_context | (NOT (
        SIZEOF(guac.units) = 3)) )) = 0);
    wr2: (SIZEOF(QUERY ( guac <* global_unit_assigned_context | (NOT ((
        SIZEOF(QUERY ( u <* guac.units | (
        'CONFIG_CONTROL_DESIGN.LENGTH_UNIT' IN TYPEOF(u)) )) = 1) AND
        (SIZEOF(QUERY ( u <* guac.units | (
        'CONFIG_CONTROL_DESIGN.PLANE_ANGLE_UNIT' IN TYPEOF(u)) )) = 1)
        AND (SIZEOF(QUERY ( u <* guac.units | (
        'CONFIG_CONTROL_DESIGN.SOLID_ANGLE_UNIT' IN TYPEOF(u)) ))

```

```

        = 1))) )) = 0);
END_RULE; -- global_unit_assignment

RULE no_shape_for_make_from FOR (design_make_from_relationship);
WHERE
    wr1: (SIZEOF(QUERY ( dmfr <* design_make_from_relationship | (NOT (
        SIZEOF(QUERY ( pd <* USEDIN(dmfr, 'CONFIG_CONTROL_DESIGN.' +
        'PROPERTY_DEFINITION.DEFINITION') | (
        'CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION_SHAPE'
        IN TYPEOF(pd)) )) = 0)) )) = 0);
END_RULE; -- no_shape_for_make_from

RULE no_shape_for_supplied_part FOR (supplied_part_relationship);
WHERE
    wr1: (SIZEOF(QUERY ( spr <* supplied_part_relationship | (NOT (SIZEOF(
        QUERY ( pd <* USEDIN(spr, 'CONFIG_CONTROL_DESIGN.' +
        'PROPERTY_DEFINITION.DEFINITION') | (
        'CONFIG_CONTROL_DESIGN.PRODUCT_DEFINITION_SHAPE'
        IN TYPEOF(pd)) )) = 0)) )) = 0);
END_RULE; -- no_shape_for_supplied_part

RULE product_concept_requires_configuration_item FOR (product_concept,
    configuration_item);
WHERE
    wr1: (SIZEOF(QUERY ( pc <* product_concept | (NOT (SIZEOF(
        QUERY ( ci <* configuration_item | (pc ::= ci.item_concept) ))
        >= 1)) )) = 0);
END_RULE; -- product_concept_requires_configuration_item

RULE product_definition_requires_approval FOR (product_definition,
    cc_design_approval);
WHERE
    wr1: (SIZEOF(QUERY ( pd <* product_definition | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_approval | (pd IN ccda.items) ))
        = 1)) )) = 0);
END_RULE; -- product_definition_requires_approval

RULE product_definition_requires_date_time FOR (product_definition,
    cc_design_date_and_time_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( pd <* product_definition | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_date_and_time_assignment | (pd IN

```

```

        ccdta.items) )) = 1)) )) = 0);
END_RULE; -- product_definition_requires_date_time

RULE product_definition_requires_person_organization FOR (
    product_definition,
    cc_design_person_and_organization_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( pd <* product_definition | (NOT (SIZEOF(
        QUERY ( ccdpoa <* cc_design_person_and_organization_assignment
            | (pd IN ccdpoa.items) )) = 1)) )) = 0);
END_RULE; -- product_definition_requires_person_organization

RULE product_requires_person_organization FOR (product,
    cc_design_person_and_organization_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( prod <* product | (NOT (SIZEOF(QUERY ( ccdpoa <*
        cc_design_person_and_organization_assignment | (prod IN ccdpoa
            .items) )) = 1)) )) = 0);
END_RULE; -- product_requires_person_organization

RULE product_requires_product_category FOR (product,
    product_related_product_category);
WHERE
    wr1: (SIZEOF(QUERY ( prod <* product | (NOT (SIZEOF(QUERY ( prpc <*
        product_related_product_category | ((prod IN prpc.products)
        AND (prpc.name IN ['assembly', 'inseparable_assembly', 'detail',
            'customer_furnished_equipment'])) )) = 1)) )) = 0);
END_RULE; -- product_requires_product_category

RULE product_requires_version FOR (product,
    product_definition_formation);
WHERE
    wr1: (SIZEOF(QUERY ( prod <* product | (NOT (SIZEOF(QUERY ( pdf <*
        product_definition_formation | (prod :=: pdf.of_product) )) >=
            1)) )) = 0);
END_RULE; -- product_requires_version

RULE product_version_requires_approval FOR (product_definition_formation,
    cc_design_approval);
WHERE
    wr1: (SIZEOF(QUERY ( pdf <* product_definition_formation | (NOT (
        SIZEOF(QUERY ( ccda <* cc_design_approval |

```

```

        (pdf IN ccda.items) )) = 1)) )) = 0);
END_RULE; -- product_version_requires_approval

RULE product_version_requires_person_organization FOR (
    product_definition_formation,
    cc_design_person_and_organization_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( pdf <* product_definition_formation | (NOT (
        SIZEOF(QUERY ( ccdpoa <*
        cc_design_person_and_organization_assignment | ((pdf IN ccdpoa
        .items) AND (ccdpoa.role.name = 'creator')) )) = 1))) = 0);
    wr2: (SIZEOF(QUERY ( pdf <* product_definition_formation | (NOT (
        SIZEOF(QUERY ( ccdpoa <*
        cc_design_person_and_organization_assignment | ((pdf IN ccdpoa
        .items) AND (ccdpoa.role.name IN ['design_supplier',
        'part_supplier']))) )) >= 1)) )) = 0);
END_RULE; -- product_version_requires_person_organization

RULE product_version_requires_security_classification FOR (
    product_definition_formation,
    cc_design_security_classification);
WHERE
    wr1: (SIZEOF(QUERY ( pdf <* product_definition_formation | (NOT (
        SIZEOF(QUERY ( ccdsc <* cc_design_security_classification | (
        pdf IN ccdsc.items))) )) = 1)) )) = 0);
END_RULE; -- product_version_requires_security_classification

RULE restrict_action_request_status FOR (action_request_status);
WHERE
    wr1: (SIZEOF(QUERY ( ars <* action_request_status | (NOT (ars.status
        IN ['proposed', 'in_work', 'issued', 'hold']))) )) = 0);
END_RULE; -- restrict_action_request_status

RULE restrict_approval_status FOR (approval_status);
WHERE
    wr1: (SIZEOF(QUERY ( ast <* approval_status | (NOT (ast.name IN [
        'approved', 'not_yet_approved', 'disapproved', 'withdrawn']))) ))
        = 0);
END_RULE; -- restrict_approval_status

RULE restrict_certification_type FOR (certification_type);
WHERE

```

```

    wr1: (SIZEOF(QUERY ( ct <* certification_type | (NOT (ct.description
        IN ['design_supplier','part_supplier']))) )) = 0);
END_RULE; -- restrict_certification_type

RULE restrict_contract_type FOR (contract_type);
WHERE
    wr1: (SIZEOF(QUERY ( ct <* contract_type | (NOT (ct.description IN [
        'fixed_price','cost_plus']))) )) = 0);
END_RULE; -- restrict_contract_type

RULE restrict_date_time_role FOR (date_time_role);
WHERE
    wr1: (SIZEOF(QUERY ( dtr <* date_time_role | (NOT (dtr.name IN [
        'creation_date','request_date','release_date','start_date',
        'contract_date','certification_date','sign_off_date',
        'classification_date','declassification_date']))) )) = 0);
END_RULE; -- restrict_date_time_role

RULE restrict_document_type FOR (document_type);
WHERE
    wr1: (SIZEOF(QUERY ( dt <* document_type | (NOT (dt.product_data_type
        IN ['material_specification','process_specification',
        'design_specification','surface_finish_specification',
        'cad_filename','drawing']))) )) = 0);
END_RULE; -- restrict_document_type

RULE restrict_person_organization_role FOR
    (person_and_organization_role);
WHERE
    wr1: (SIZEOF(QUERY ( por <* person_and_organization_role | (NOT (por.
        name IN ['request_recipient','initiator','part_supplier',
        'design_supplier','configuration_manager','contractor',
        'classification_officer','creator','design_owner']))) )) = 0);
END_RULE; -- restrict_person_organization_role

RULE restrict_product_category_value FOR (
    product_related_product_category);
WHERE
    wr1: (SIZEOF(QUERY ( prpc <* product_related_product_category | (NOT (
        prpc.name IN ['assembly','detail',
        'customer_furnished_equipment','inseparable_assembly','cast',
        'coined','drawn','extruded','forged','formed','machined',

```

```

        'molded','rolled','sheared']))) )) = 0);
END_RULE; -- restrict_product_category_value

RULE restrict_security_classification_level FOR (
    security_classification_level);
WHERE
    wr1: (SIZEOF(QUERY ( scl <* security_classification_level | (NOT (scl.
        name IN ['unclassified','classified','proprietary',
        'confidential','secret','top_secret']))) )) = 0);
END_RULE; -- restrict_security_classification_level

RULE security_classification_optional_date_time FOR (
    security_classification, cc_design_date_and_time_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( sc <* security_classification | (NOT (SIZEOF(
        QUERY ( ccdta <* cc_design_date_and_time_assignment | ((sc IN
        ccdta.items) AND ('declassification_date' = ccdta.role.name))
        )) <= 1)) )) = 0);
END_RULE; -- security_classification_optional_date_time

RULE security_classification_requires_approval FOR (
    security_classification, cc_design_approval);
WHERE
    wr1: (SIZEOF(QUERY ( sc <* security_classification | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_approval | (sc IN ccda.items) ))
        = 1)) )) = 0);
END_RULE; -- security_classification_requires_approval

RULE security_classification_requires_date_time FOR (
    security_classification, cc_design_date_and_time_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( sc <* security_classification | (NOT (SIZEOF(
        QUERY ( ccdta <* cc_design_date_and_time_assignment | ((sc IN
        ccdta.items) AND ('classification_date' = ccdta.role.name)) ))
        = 1)) )) = 0);
END_RULE; -- security_classification_requires_date_time

RULE security_classification_requires_person_organization FOR (
    security_classification,
    cc_design_person_and_organization_assignment);
WHERE
    wr1: (SIZEOF(QUERY ( sc <* security_classification | (NOT (SIZEOF(

```

```

        QUERY ( ccdpoa <* cc_design_person_and_organization_assignment
                | (sc IN ccdpoa.items) )) = 1)) )) = 0);
END_RULE; -- security_classification_requires_person_organization

RULE start_request_requires_approval FOR (start_request,
        cc_design_approval);

WHERE
    wr1: (SIZEOF(QUERY ( sr <* start_request | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_approval | (sr IN ccda.items) ))
        = 1)) )) = 0);
END_RULE; -- start_request_requires_approval

RULE start_request_requires_date_time FOR (start_request,
        cc_design_date_and_time_assignment);

WHERE
    wr1: (SIZEOF(QUERY ( sr <* start_request | (NOT (SIZEOF(
        QUERY ( ccda <* cc_design_date_and_time_assignment | (sr IN
        ccda.items) )) = 1)) )) = 0);
END_RULE; -- start_request_requires_date_time

RULE start_request_requires_person_organization FOR (start_request,
        cc_design_person_and_organization_assignment);

WHERE
    wr1: (SIZEOF(QUERY ( sr <* start_request | (NOT (SIZEOF(
        QUERY ( ccdpoa <* cc_design_person_and_organization_assignment
                | (sr IN ccdpoa.items) )) >= 1)) )) = 0);
END_RULE; -- start_request_requires_person_organization

RULE start_work_requires_approval FOR (start_work, cc_design_approval);

WHERE
    wr1: (SIZEOF(QUERY ( sw <* start_work | (NOT (SIZEOF(QUERY ( ccda <*
        cc_design_approval | (sw IN ccda.items) )) = 1)) )) = 0);
END_RULE; -- start_work_requires_approval

RULE start_work_requires_date_time FOR (start_work,
        cc_design_date_and_time_assignment);

WHERE
    wr1: (SIZEOF(QUERY ( sw <* start_work | (NOT (SIZEOF(QUERY ( ccda <*
        cc_design_date_and_time_assignment | ((sw IN ccda.items) AND
        (ccda.role.name = 'start_date')) )) = 1)) )) = 0);
END_RULE; -- start_work_requires_date_time

```

```

RULE subtype_mandatory_action FOR (action);
WHERE
  wr1: (SIZEOF(QUERY ( act <* action | (NOT (
    'CONFIG_CONTROL_DESIGN.DIRECTED_ACTION' IN TYPEOF(act))) )) =
    0);
END_RULE; -- subtype_mandatory_action

RULE subtype_mandatory_effectivity FOR (effectivity);
WHERE
  wr1: (SIZEOF(QUERY ( eff <* effectivity | (NOT ((SIZEOF([
    'CONFIG_CONTROL_DESIGN.SERIAL_NUMBERED_EFFECTIVITY',
    'CONFIG_CONTROL_DESIGN.LOT_EFFECTIVITY',
    'CONFIG_CONTROL_DESIGN.DATED_EFFECTIVITY'] * TYPEOF(eff)) = 1)
    AND ('CONFIG_CONTROL_DESIGN.CONFIGURATION_EFFECTIVITY' IN
    TYPEOF(eff)))) )) = 0);
END_RULE; -- subtype_mandatory_effectivity

RULE subtype_mandatory_product_context FOR (product_context);
WHERE
  wr1: (SIZEOF(QUERY ( pc <* product_context | (NOT (
    'CONFIG_CONTROL_DESIGN.MECHANICAL_CONTEXT' IN TYPEOF(pc))) ))
    = 0);
END_RULE; -- subtype_mandatory_product_context

RULE subtype_mandatory_product_definition_formation FOR (
  product_definition_formation);
WHERE
  wr1: (SIZEOF(QUERY ( pdf <* product_definition_formation | (NOT ((
    'CONFIG_CONTROL_DESIGN.' +
    'PRODUCT_DEFINITION_FORMATION_WITH_SPECIFIED_SOURCE') IN
    TYPEOF(pdf))) )) = 0);
END_RULE; -- subtype_mandatory_product_definition_formation

RULE subtype_mandatory_product_definition_usage FOR (
  product_definition_usage);
WHERE
  wr1: (SIZEOF(QUERY ( pdu <* product_definition_usage | (NOT ((
    'CONFIG_CONTROL_DESIGN.' + 'ASSEMBLY_COMPONENT_USAGE') IN
    TYPEOF(pdu))) )) = 0);
END_RULE; -- subtype_mandatory_product_definition_usage

```

```

RULE subtype_mandatory_representation FOR (representation);
WHERE
  wr1: (SIZEOF(QUERY ( rep <* representation | (NOT (
    'CONFIG_CONTROL_DESIGN.SHAPE_REPRESENTATION' IN TYPEOF(rep)))
  )) = 0);
END_RULE; -- subtype_mandatory_representation

RULE subtype_mandatory_representation_context FOR (
  representation_context);
WHERE
  wr1: (SIZEOF(QUERY ( rep_cntxt <* representation_context | (NOT (
    'CONFIG_CONTROL_DESIGN.GEOMETRIC_REPRESENTATION_CONTEXT' IN
    TYPEOF(rep_cntxt))) )) = 0);
END_RULE; -- subtype_mandatory_representation_context

RULE subtype_mandatory_shape_representation FOR (shape_representation);
WHERE
  wr1: (SIZEOF(QUERY ( sr <* shape_representation | (NOT ((SIZEOF([
    'CONFIG_CONTROL_DESIGN.' +
    'ADVANCED_BREP_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.FACETED_BREP_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.MANIFOLD_SURFACE_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.' +
    'EDGE_BASED_WIREFRAME_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.' +
    'SHELL_BASED_WIREFRAME_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.' +
    'GEOMETRICALLY_BOUNDED_SURFACE_SHAPE_REPRESENTATION',
    'CONFIG_CONTROL_DESIGN.' +
    'GEOMETRICALLY_BOUNDED_WIREFRAME_SHAPE_REPRESENTATION'] *
    TYPEOF(sr)) = 1) OR (SIZEOF(QUERY ( it <* sr\representation.
    items | (NOT ('CONFIG_CONTROL_DESIGN.AXIS2_PLACEMENT_3D' IN
    TYPEOF(it))) )) = 0) OR (SIZEOF(QUERY ( sdr <* QUERY ( pdr <*
    USEDIN(sr,
    'CONFIG_CONTROL_DESIGN.PROPERTY_DEFINITION_REPRESENTATION.' +
    'USED_REPRESENTATION') | (
    'CONFIG_CONTROL_DESIGN.SHAPE_DEFINITION_REPRESENTATION' IN
    TYPEOF(pdr)) ) | (NOT (SIZEOF([
    'CONFIG_CONTROL_DESIGN.SHAPE_ASPECT',
    'CONFIG_CONTROL_DESIGN.SHAPE_ASPECT_RELATIONSHIP'] * TYPEOF(
    sdr.definition.definition)) = 1)) )) = 0))) )) = 0);
END_RULE; -- subtype_mandatory_shape_representation

```

```

RULE unique_version_change_order_rule FOR (change);
WHERE
  wr1: (SIZEOF(QUERY ( c <* change | (NOT unique_version_change_order(c.
    assigned_action)) )) = 0);
END_RULE; -- unique_version_change_order_rule

RULE versioned_action_request_requires_solution FOR (
  versioned_action_request, action_request_solution);
WHERE
  wr1: (SIZEOF(QUERY ( ar <* versioned_action_request | (NOT (SIZEOF(
    QUERY ( ars <* action_request_solution | (ar :=: ars.request)
    )) >= 1)) )) = 0);
END_RULE; -- versioned_action_request_requires_solution

RULE versioned_action_request_requires_status FOR (
  versioned_action_request, action_request_status);
WHERE
  wr1: (SIZEOF(QUERY ( ar <* versioned_action_request | (NOT (SIZEOF(
    QUERY ( ars <* action_request_status | (ar :=: ars.
    assigned_request) )) = 1)) )) = 0);
END_RULE; -- versioned_action_request_requires_status

FUNCTION acyclic_curve_replica(rep: curve_replica;
  parent: curve): BOOLEAN;
  IF NOT ('CONFIG_CONTROL_DESIGN.CURVE_REPLICA' IN TYPEOF(parent)) THEN
    RETURN(TRUE);
  END_IF;
  IF parent :=: rep THEN RETURN(FALSE);
  ELSE
    RETURN(acyclic_curve_replica(rep,parent\curve_replica.parent_curve));
  END_IF;
END_FUNCTION; -- acyclic_curve_replica

FUNCTION acyclic_mapped_representation(parent_set: SET OF representation;
  children_set: SET OF representation_item): BOOLEAN;
  LOCAL
    i : INTEGER;
    x : SET OF representation_item;
    y : SET OF representation_item;
  END_LOCAL;
  x := QUERY ( z <* children_set | ('CONFIG_CONTROL_DESIGN.MAPPED_ITEM'
    IN TYPEOF(z)) );

```

```

IF SIZEOF(x) > 0 THEN
  REPEAT i := 1 TO HIINDEX(x) BY 1;
    IF x[i]\mapped_item.mapping_source.mapped_representation IN
      parent_set THEN RETURN(FALSE);
    END_IF;
    IF NOT acyclic_mapped_representation(parent_set + x[i]\mapped_item.
      .mapping_source.mapped_representation,x[i]\mapped_item.
      mapping_source.mapped_representation.items) THEN
      RETURN(FALSE);
    END_IF;
  END_REPEAT;
END_IF;
x := children_set - x;
IF SIZEOF(x) > 0 THEN
  REPEAT i := 1 TO HIINDEX(x) BY 1;
    y := QUERY ( z <* bag_to_set(USEDIN(x[i],'')) | (
      'CONFIG_CONTROL_DESIGN.REPRESENTATION_ITEM' IN TYPEOF(z)) );
    IF NOT acyclic_mapped_representation(parent_set,y) THEN
      RETURN(FALSE);
    END_IF;
  END_REPEAT;
END_IF;
RETURN(TRUE);
END_FUNCTION; -- acyclic_mapped_representation

FUNCTION acyclic_point_replica(rep: point_replica;
  parent: point): BOOLEAN;
IF NOT ('CONFIG_CONTROL_DESIGN.POINT_REPLICA' IN TYPEOF(parent)) THEN
  RETURN(TRUE);
END_IF;
IF parent ::= rep THEN RETURN(FALSE);
ELSE
  RETURN(acyclic_point_replica(rep,parent\point_replica.parent_pt));
END_IF;
END_FUNCTION; -- acyclic_point_replica

FUNCTION acyclic_product_category_relationship(
  relation: product_category_relationship;
  children: SET OF product_category): LOGICAL;
LOCAL
  i
    : INTEGER;
  x
    : SET OF product_category_relationship;

```

```

    local_children : SET OF product_category;
END_LOCAL;
REPEAT i := 1 TO HIINDEX(children) BY 1;
    IF relation.category :=: children[i] THEN RETURN(FALSE);
    END_IF;
END_REPEAT;
x := bag_to_set(USEDIN(relation.category, 'CONFIG_CONTROL_DESIGN.' +
    'PRODUCT_CATEGORY_RELATIONSHIP.SUB_CATEGORY'));
local_children := children + relation.category;
IF SIZEOF(x) > 0 THEN
    REPEAT i := 1 TO HIINDEX(x) BY 1;
        IF NOT acyclic_product_category_relationship(x[i], local_children)
            THEN RETURN(FALSE);
        END_IF;
    END_REPEAT;
END_IF;
RETURN(TRUE);
END_FUNCTION; -- acyclic_product_category_relationship

FUNCTION acyclic_product_definition_relationship(
    relation: product_definition_relationship;
    relatives: SET [1:?] OF product_definition;
    specific_relation: STRING): LOGICAL;
LOCAL
    x : SET OF product_definition_relationship;
END_LOCAL;
IF relation.relating_product_definition IN relatives THEN
    RETURN(FALSE);
END_IF;
x := QUERY ( pd <* bag_to_set(USEDIN(relation.
    relating_product_definition, 'CONFIG_CONTROL_DESIGN.' +
    'PRODUCT_DEFINITION_RELATIONSHIP.' + 'RELATED_PRODUCT_DEFINITION'))
    | (specific_relation IN TYPEOF(pd)) );
REPEAT i := 1 TO HIINDEX(x) BY 1;
    IF NOT acyclic_product_definition_relationship(x[i], relatives +
        relation.relating_product_definition, specific_relation) THEN
        RETURN(FALSE);
    END_IF;
END_REPEAT;
RETURN(TRUE);
END_FUNCTION; -- acyclic_product_definition_relationship

```

```

FUNCTION acyclic_surface_replica(rep: surface_replica;
                                parent: surface): BOOLEAN;
  IF NOT ('CONFIG_CONTROL_DESIGN.SURFACE_REPLICA' IN TYPEOF(parent))
  THEN
    RETURN(TRUE);
  END_IF;
  IF parent :=: rep THEN RETURN(FALSE);
  ELSE
    RETURN(acyclic_surface_replica(rep,parent\surface_replica.
                                   parent_surface));
  END_IF;
END_FUNCTION; -- acyclic_surface_replica

FUNCTION assembly_shape_is_defined(assy: next_assembly_usage_occurrence;
                                   schma: STRING): BOOLEAN;
  LOCAL
    srr_set    : SET OF shape_representation_relationship := [];
    i          : INTEGER;
    j          : INTEGER;
    sdr_set    : SET OF shape_definition_representation := [];
    pr1_set    : SET OF property_definition := [];
    pdrel_set  : SET OF product_definition_relationship := [];
    pr2_set    : SET OF property_definition := [];
  END_LOCAL;
  pr1_set := bag_to_set(USEDIN(assy.related_product_definition,schma +
                              '.PROPERTY_DEFINITION_DEFINITION'));
  REPEAT i := 1 TO HIINDEX(pr1_set) BY 1;
    sdr_set := sdr_set + QUERY ( pdr <* USEDIN(pr1_set[i],schma +
                              '.PROPERTY_DEFINITION_REPRESENTATION_DEFINITION') | ((schma +
                              '.SHAPE_DEFINITION_REPRESENTATION') IN TYPEOF(pdr)) );
  END_REPEAT;
  pdrel_set := bag_to_set(USEDIN(assy.related_product_definition,schma +
                              '.PRODUCT_DEFINITION_RELATIONSHIP.' +
                              'RELATED_PRODUCT_DEFINITION'));
  REPEAT j := 1 TO HIINDEX(pdrel_set) BY 1;
    pr2_set := pr2_set + USEDIN(pdrel_set[j],schma +
                              '.PROPERTY_DEFINITION_DEFINITION');
  END_REPEAT;
  REPEAT i := 1 TO HIINDEX(pr2_set) BY 1;
    sdr_set := sdr_set + QUERY ( pdr <* USEDIN(pr2_set[i],schma +
                              '.PROPERTY_DEFINITION_REPRESENTATION_DEFINITION') | ((schma +
                              '.SHAPE_DEFINITION_REPRESENTATION') IN TYPEOF(pdr)) );
  END_REPEAT;

```

```

END_REPEAT;
IF SIZEOF(sdr_set) > 0 THEN
  REPEAT i := 1 TO HIINDEX(sdr_set) BY 1;
    srr_set := QUERY ( rr <* bag_to_set(USEDIN(sdr_set[i])\
      property_definition_representation.used_representation,schma +
      '.REPRESENTATION_RELATIONSHIP.REP_2')) | ((schma +
      '.SHAPE_REPRESENTATION_RELATIONSHIP') IN TYPEOF(rr)) );
  IF SIZEOF(srr_set) > 0 THEN
    REPEAT j := 1 TO HIINDEX(srr_set) BY 1;
      IF SIZEOF(QUERY ( pdr <* bag_to_set(USEDIN(srr_set[j])\
        representation_relationship.rep_1,schma +
        '.PROPERTY_DEFINITION_REPRESENTATION.USED_REPRESENTATION'))
        | ((schma + '.SHAPE_DEFINITION_REPRESENTATION') IN TYPEOF(
        pdr)) ) * QUERY ( pdr <* bag_to_set(USEDIN(assy.
        relating_product_definition,schma +
        '.PROPERTY_DEFINITION_REPRESENTATION.DEFINITION')) | ((
        schma + '.SHAPE_DEFINITION_REPRESENTATION') IN
        TYPEOF(pdr)) )) >= 1 THEN
        IF SIZEOF(QUERY ( cdsr <* USEDIN(srr_set[j],schma +
          '.CONTEXT_DEPENDENT_SHAPE_REPRESENTATION.' +
          'REPRESENTATION_RELATION') | (NOT (cdsr\
            context_dependent_shape_representation.
            represented_product_relation\property_definition.
            definition :=: assy)) )) > 0 THEN
          RETURN(FALSE);
        END_IF;
      END_IF;
    END_REPEAT;
  END_IF;
END_REPEAT;
RETURN(TRUE);
END_FUNCTION; -- assembly_shape_is_defined

FUNCTION associated_surface(arg: pcurve_or_surface): surface;
  LOCAL
    surf : surface;
  END_LOCAL;
  IF 'CONFIG_CONTROL_DESIGN.PCURVE' IN TYPEOF(arg) THEN
    surf := arg.basis_surface;
  ELSE
    surf := arg;
  END_IF;

```

```

END_IF;
RETURN(surf);
END_FUNCTION; -- associated_surface

FUNCTION bag_to_set(the_bag: BAG OF GENERIC:intype
  ): SET OF GENERIC:intype;
LOCAL
  i      : INTEGER;
  the_set : SET OF GENERIC:intype := [];
END_LOCAL;
IF SIZEOF(the_bag) > 0 THEN
  REPEAT i := 1 TO HIINDEX(the_bag) BY 1;
    the_set := the_set + the_bag[i];
  END_REPEAT;
END_IF;
RETURN(the_set);
END_FUNCTION; -- bag_to_set

FUNCTION base_axis(dim: INTEGER; axis1, axis2, axis3: direction
  ): LIST [2:3] OF direction;
LOCAL
  u      : LIST [2:3] OF direction;
  d1     : direction;
  d2     : direction;
  factor : REAL;
END_LOCAL;
IF dim = 3 THEN
  d1 := NVL(normalise(axis3), dummy_gri || direction([0,0,1]));
  d2 := first_proj_axis(d1, axis1);
  u := [d2, second_proj_axis(d1, d2, axis2), d1];
ELSE
  IF EXISTS(axis1) THEN
    d1 := normalise(axis1);
    u := [d1, orthogonal_complement(d1)];
    IF EXISTS(axis2) THEN
      factor := dot_product(axis2, u[2]);
      IF factor < 0 THEN
        u[2].direction_ratios[1] := -u[2].direction_ratios[1];
        u[2].direction_ratios[2] := -u[2].direction_ratios[2];
      END_IF;
    END_IF;
  ELSE

```

```

    IF EXISTS(axis2) THEN
        d1 := normalise(axis2);
        u := [orthogonal_complement(d1),d1];
        u[1].direction_ratios[1] := -u[1].direction_ratios[1];
        u[1].direction_ratios[2] := -u[1].direction_ratios[2];
    ELSE
        u := [dummy_gri || direction([1,0]),dummy_gri ||
            direction([0,1])];
    END_IF;
END_IF;
END_IF;
RETURN(u);
END_FUNCTION; -- base_axis

FUNCTION boolean_choose(b: BOOLEAN;
    choice1, choice2: GENERIC:item): GENERIC:item;
    IF b THEN
        RETURN(choice1);
    ELSE
        RETURN(choice2);
    END_IF;
END_FUNCTION; -- boolean_choose

FUNCTION build_2axes(ref_direction: direction): LIST [2:2] OF direction;
    LOCAL
        d : direction := NVL(normalise(ref_direction),dummy_gri ||
            direction([1,0]));
    END_LOCAL;
    RETURN([d,orthogonal_complement(d)]);
END_FUNCTION; -- build_2axes

FUNCTION build_axes(axis, ref_direction: direction
    ): LIST [3:3] OF direction;
    LOCAL
        d1 : direction;
        d2 : direction;
    END_LOCAL;
    d1 := NVL(normalise(axis),dummy_gri || direction([0,0,1]));
    d2 := first_proj_axis(d1,ref_direction);
    RETURN([d2,normalise(cross_product(d1,d2)).orientation,d1]);
END_FUNCTION; -- build_axes

```

```

FUNCTION cc_design_date_time_correlation
  (e : cc_design_date_and_time_assignment ) : BOOLEAN;
LOCAL
  dt_role : STRING;
END_LOCAL;
  dt_role := e\date_and_time_assignment.role.name;
CASE dt_role OF
  'creation_date'      : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        'CONFIG_CONTROL_DESIGN.' +
                        'PRODUCT_DEFINITION'
                        IN TYPEOF (x)))
                        THEN RETURN(FALSE);
                        END_IF;
  'request_date'       : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        SIZEOF (
                        ['CONFIG_CONTROL_DESIGN.CHANGE_REQUEST',
                        'CONFIG_CONTROL_DESIGN.START_REQUEST'] *
                        TYPEOF (x)) = 1))
                        THEN RETURN(FALSE);
                        END_IF;
  'release_date'       : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        SIZEOF (
                        ['CONFIG_CONTROL_DESIGN.CHANGE',
                        'CONFIG_CONTROL_DESIGN.START_WORK'] *
                        TYPEOF (x)) = 1))
                        THEN RETURN(FALSE);
                        END_IF;
  'start_date'         : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        SIZEOF (
                        ['CONFIG_CONTROL_DESIGN.CHANGE',
                        'CONFIG_CONTROL_DESIGN.START_WORK'] *
                        TYPEOF (x)) = 1))
                        THEN RETURN(FALSE);
                        END_IF;
  'sign_off_date'      : IF SIZEOF (e.items) <>
                        SIZEOF (QUERY (x <* e.items |
                        'CONFIG_CONTROL_DESIGN.' +
                        'APPROVAL_PERSON_ORGANIZATION'

```

```

        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

    'contract_date'      : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.CONTRACT'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

    'certification_date' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.CERTIFICATION'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

    'classification_date' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'SECURITY_CLASSIFICATION'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

    'declassification_date' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'SECURITY_CLASSIFICATION'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;

    OTHERWISE : RETURN(TRUE);
END_CASE;
RETURN (TRUE);
END_FUNCTION; -- cc_design_date_time_correlation

FUNCTION cc_design_person_and_organization_correlation
(e : cc_design_person_and_organization_assignment ) : BOOLEAN;
LOCAL
    po_role : STRING;
END_LOCAL;
    po_role := e\person_and_organization_assignment.role.name;
CASE po_role OF
    'request_recipient'      : IF SIZEOF (e.items) <>

```

```

        SIZEOF (QUERY (x <* e.items |
        SIZEOF(['CONFIG_CONTROL_DESIGN.' +
        'CHANGE_REQUEST',
        'CONFIG_CONTROL_DESIGN.' +
        'START_REQUEST'] *
        TYPEOF (x)) = 1))
        THEN RETURN(FALSE);
    END_IF;
'initiator'
: IF SIZEOF (e.items) <>
    SIZEOF (QUERY (x <* e.items |
    SIZEOF(['CONFIG_CONTROL_DESIGN.' +
    'CHANGE_REQUEST',
    'CONFIG_CONTROL_DESIGN.' +
    'START_REQUEST',
    'CONFIG_CONTROL_DESIGN.' +
    'START_WORK',
    'CONFIG_CONTROL_DESIGN.' +
    'CHANGE'] *
    TYPEOF (x)) = 1))
    THEN RETURN(FALSE);
    END_IF;
'creator'
: IF SIZEOF (e.items) <>
    SIZEOF (QUERY (x <* e.items |
    SIZEOF (['CONFIG_CONTROL_DESIGN.' +
    'PRODUCT_DEFINITION_FORMATION',
    'CONFIG_CONTROL_DESIGN.' +
    'PRODUCT_DEFINITION'] *
    TYPEOF (x)) = 1))
    THEN RETURN (FALSE);
    END_IF;
'part_supplier'
: IF SIZEOF (e.items) <>
    SIZEOF (QUERY (x <* e.items |
    'CONFIG_CONTROL_DESIGN.' +
    'PRODUCT_DEFINITION_FORMATION'
    IN TYPEOF (x)))
    THEN RETURN(FALSE);
    END_IF;
'design_supplier'
: IF SIZEOF (e.items) <>
    SIZEOF (QUERY (x <* e.items |
    'CONFIG_CONTROL_DESIGN.' +
    'PRODUCT_DEFINITION_FORMATION'
    IN TYPEOF (x)))

```

```

        THEN RETURN(FALSE);
    END_IF;
'design_owner'      : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.PRODUCT'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;
'configuration_manager' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'CONFIGURATION_ITEM'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;
'contractor'        : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.CONTRACT'
        IN TYPEOF (x)))
        THEN RETURN(FALSE);
    END_IF;
'classification_officer' : IF SIZEOF (e.items) <>
        SIZEOF (QUERY (x <* e.items |
        'CONFIG_CONTROL_DESIGN.' +
        'SECURITY_CLASSIFICATION'
        IN TYPEOF (x))) THEN
        RETURN(FALSE);
    END_IF;

    OTHERWISE : RETURN(TRUE);
END_CASE;
RETURN (TRUE);
END_FUNCTION; -- cc_design_person_and_organization_correlation

FUNCTION closed_shell_reversed(a_shell: closed_shell
): oriented_closed_shell;
LOCAL
    the_reverse : oriented_closed_shell;
END_LOCAL;
IF 'CONFIG_CONTROL_DESIGN.ORIENTED_CLOSED_SHELL' IN TYPEOF(a_shell)
    THEN
        the_reverse := dummy_tri || connected_face_set(a_shell\
            connected_face_set.cfs_faces) || closed_shell() ||

```

```

        oriented_closed_shell(a_shell\oriented_closed_shell.
        closed_shell_element,NOT a_shell\oriented_closed_shell.
        orientation);
ELSE
    the_reverse := dummy_tri || connected_face_set(a_shell\
        connected_face_set.cfs_faces) || closed_shell() ||
        oriented_closed_shell(a_shell,FALSE);
END_IF;
RETURN(the_reverse);
END_FUNCTION; -- closed_shell_reversed

FUNCTION conditional_reverse(p: BOOLEAN;
        an_item: reversible_topology): reversible_topology;
IF p THEN RETURN(an_item);
ELSE
    RETURN(topology_reversed(an_item));
END_IF;
END_FUNCTION; -- conditional_reverse

FUNCTION constraints_composite_curve_on_surface(
        c: composite_curve_on_surface): BOOLEAN;
LOCAL
    n_segments : INTEGER := SIZEOF(c.segments);
END_LOCAL;
REPEAT k := 1 TO n_segments BY 1;
    IF (NOT ('CONFIG_CONTROL_DESIGN.PCURVE' IN TYPEOF(c\composite_curve.
        segments[k].parent_curve))) AND (NOT (
        'CONFIG_CONTROL_DESIGN.SURFACE_CURVE' IN TYPEOF(c\composite_curve
        .segments[k].parent_curve))) AND (NOT (
        'CONFIG_CONTROL_DESIGN.COMPOSITE_CURVE_ON_SURFACE' IN TYPEOF(c\
        composite_curve.segments[k].parent_curve))) THEN
        RETURN(FALSE);
    END_IF;
END_REPEAT;
RETURN(TRUE);
END_FUNCTION; -- constraints_composite_curve_on_surface

FUNCTION constraints_geometry_shell_based_surface_model(
        m: shell_based_surface_model): BOOLEAN;
LOCAL
    result : BOOLEAN := TRUE;
END_LOCAL;

```

```

REPEAT j := 1 TO SIZEOF(m.sbsm_boundary) BY 1;
  IF (NOT ('CONFIG_CONTROL_DESIGN.OPEN_SHELL' IN TYPEOF(m.
    sbsm_boundary[j]))) AND (NOT (
    'CONFIG_CONTROL_DESIGN.CLOSED_SHELL' IN
    TYPEOF(m.sbsm_boundary[j]))) THEN
    result := FALSE;
    RETURN(result);
  END_IF;
END_REPEAT;
RETURN(result);
END_FUNCTION; -- constraints_geometry_shell_based_surface_model

FUNCTION constraints_geometry_shell_based_wireframe_model
  (m: shell_based_wireframe_model): BOOLEAN;
LOCAL
  result : BOOLEAN := TRUE;
END_LOCAL;
REPEAT j := 1 TO SIZEOF(m.sbwm_boundary) BY 1;
  IF (NOT ('CONFIG_CONTROL_DESIGN.WIRE_SHELL' IN TYPEOF(m.
    sbwm_boundary[j]))) AND (NOT (
    'CONFIG_CONTROL_DESIGN.VERTEX_SHELL' IN
    TYPEOF(m.sbwm_boundary[j])))
    THEN result := FALSE;
    RETURN(result);
  END_IF;
END_REPEAT;
RETURN(result);
END_FUNCTION; -- constraints_geometry_shell_based_wireframe_model

FUNCTION constraints_param_b_spline(degree, up_knots, up_cp: INTEGER;
  knot_mult: LIST OF INTEGER;
  knots: LIST OF parameter_value): BOOLEAN;
LOCAL
  k : INTEGER;
  sum : INTEGER;
  result : BOOLEAN := TRUE;
END_LOCAL;
sum := knot_mult[1];
REPEAT i := 2 TO up_knots BY 1;
  sum := sum + knot_mult[i];
END_REPEAT;
IF (degree < 1) OR (up_knots < 2) OR (up_cp < degree) OR (sum <> (

```

```

        degree + up_cp + 2)) THEN result := FALSE;
    RETURN(result);
END_IF;
k := knot_mult[1];
IF (k < 1) OR (k > (degree + 1)) THEN result := FALSE;
    RETURN(result);
END_IF;
REPEAT i := 2 TO up_knots BY 1;
    IF (knot_mult[i] < 1) OR (knots[i] <= knots[i - 1]) THEN
        result := FALSE;
        RETURN(result);
    END_IF;
    k := knot_mult[i];
    IF (i < up_knots) AND (k > degree) THEN
        result := FALSE;
        RETURN(result);
    END_IF;
    IF (i = up_knots) AND (k > (degree + 1)) THEN
        result := FALSE;
        RETURN(result);
    END_IF;
END_REPEAT;
RETURN(result);
END_FUNCTION; -- constraints_param_b_spline

FUNCTION constraints_rectangular_composite_surface(
    s: rectangular_composite_surface): BOOLEAN;
REPEAT i := 1 TO s.n_u BY 1;
    REPEAT j := 1 TO s.n_v BY 1;
        IF NOT (('CONFIG_CONTROL_DESIGN.B_SPLINE_SURFACE' IN TYPEOF(s.
            segments[i][j].parent_surface)) OR (
            'CONFIG_CONTROL_DESIGN.RECTANGULAR_TRIMMED_SURFACE' IN TYPEOF(s.
            segments[i][j].parent_surface))) THEN
            RETURN(FALSE);
        END_IF;
    END_REPEAT;
END_REPEAT;
REPEAT i := 1 TO s.n_u - 1 BY 1;
    REPEAT j := 1 TO s.n_v BY 1;
        IF s.segments[i][j].u_transition = discontinuous THEN
            RETURN(FALSE);
        END_IF;

```

```

    END_REPEAT;
END_REPEAT;
REPEAT i := 1 TO s.n_u BY 1;
    REPEAT j := 1 TO s.n_v - 1 BY 1;
        IF s.segments[i][j].v_transition = discontinuous THEN
            RETURN(FALSE);
        END_IF;
    END_REPEAT;
END_REPEAT;
RETURN(TRUE);
END_FUNCTION; -- constraints_rectangular_composite_surface

FUNCTION cross_product(arg1, arg2: direction): vector;
LOCAL
    v2      : LIST [3:3] OF REAL;
    v1      : LIST [3:3] OF REAL;
    mag     : REAL;
    res     : direction;
    result  : vector;
END_LOCAL;
IF (NOT EXISTS(arg1)) OR (arg1.dim = 2) OR (NOT EXISTS(arg2)) OR (arg2
    .dim = 2) THEN RETURN(?);
ELSE
    BEGIN
        v1 := normalise(arg1).direction_ratios;
        v2 := normalise(arg2).direction_ratios;
        res := dummy_gri | direction([(v1[2] * v2[3]) - (v1[3] * v2[2]), (
            v1[3] * v2[1]) - (v1[1] * v2[3]), (v1[1] * v2[2]) - (v1[2] * v2[
            1])]);
        mag := 0;
        REPEAT i := 1 TO 3 BY 1;
            mag := mag + (res.direction_ratios[i] * res.direction_ratios[i]);
        END_REPEAT;
        IF mag > 0 THEN
            result := dummy_gri || vector(res, SQRT(mag));
        ELSE
            result := dummy_gri || vector(arg1, 0);
        END_IF;
        RETURN(result);
    END;
END_IF;
END_FUNCTION; -- cross_product

```

```

FUNCTION curve_weights_positive(b: rational_b_spline_curve): BOOLEAN;
  LOCAL
    result : BOOLEAN := TRUE;
  END_LOCAL;
  REPEAT i := 0 TO b.upper_index_on_control_points BY 1;
    IF b.weights[i] <= 0 THEN result := FALSE;
      RETURN(result);
    END_IF;
  END_REPEAT;
  RETURN(result);
END_FUNCTION; -- curve_weights_positive

FUNCTION derive_dimensional_exponents(x: unit): dimensional_exponents;
  LOCAL
    i      : INTEGER;
    result : dimensional_exponents := dimensional_exponents(0,0,0,0,0,0,
      0);
  END_LOCAL;
  IF 'CONFIG_CONTROL_DESIGN.DERIVED_UNIT' IN TYPEOF(x) THEN
    REPEAT i := LOINDEX(x.elements) TO HIINDEX(x.elements) BY 1;
      result.length_exponent := result.length_exponent +
        (x.elements[i].
          exponent * x.elements[i].unit.dimensions.length_exponent);
      result.mass_exponent := result.mass_exponent + (x.elements[i].
        exponent * x.elements[i].unit.dimensions.mass_exponent);
      result.time_exponent := result.time_exponent + (x.elements[i].
        exponent * x.elements[i].unit.dimensions.time_exponent);
      result.electric_current_exponent := result.
        electric_current_exponent + (x.elements[i].exponent * x.
          elements[i].unit.dimensions.electric_current_exponent);
      result.thermodynamic_temperature_exponent := result.
        thermodynamic_temperature_exponent + (x.elements[i].exponent *
          x.elements[i].unit.dimensions.
            thermodynamic_temperature_exponent);
      result.amount_of_substance_exponent := result.
        amount_of_substance_exponent + (x.elements[i].exponent * x.
          elements[i].unit.dimensions.amount_of_substance_exponent);
      result.luminous_intensity_exponent := result.
        luminous_intensity_exponent + (x.elements[i].exponent * x.
          elements[i].unit.dimensions.luminous_intensity_exponent);
    END_REPEAT;
  ELSE

```

```

    result := x.dimensions;
END_IF;
RETURN(result);
END_FUNCTION; -- derive_dimensional_exponents

FUNCTION dimension_of(item: geometric_representation_item
    ): dimension_count;
LOCAL
    x : SET OF representation;
    y : representation_context;
END_LOCAL;
x := using_representations(item);
y := x[1].context_of_items;
RETURN(y\geometric_representation_context.coordinate_space_dimension);
END_FUNCTION; -- dimension_of

FUNCTION dimensions_for_si_unit(n: si_unit_name
    ): dimensional_exponents;
CASE n OF
    metre      : RETURN(dimensional_exponents(1,0,0,0,0,0,0));
    gram       : RETURN(dimensional_exponents(0,1,0,0,0,0,0));
    second     : RETURN(dimensional_exponents(0,0,1,0,0,0,0));
    ampere     : RETURN(dimensional_exponents(0,0,0,1,0,0,0));
    kelvin     : RETURN(dimensional_exponents(0,0,0,0,1,0,0));
    mole       : RETURN(dimensional_exponents(0,0,0,0,0,1,0));
    candela    : RETURN(dimensional_exponents(0,0,0,0,0,0,1));
    radian     : RETURN(dimensional_exponents(0,0,0,0,0,0,0));
    steradian  : RETURN(dimensional_exponents(0,0,0,0,0,0,0));
    hertz      : RETURN(dimensional_exponents(0,0,-1,0,0,0,0));
    newton     : RETURN(dimensional_exponents(1,1,-2,0,0,0,0));
    pascal     : RETURN(dimensional_exponents(-1,1,-2,0,0,0,0));
    joule      : RETURN(dimensional_exponents(2,1,-2,0,0,0,0));
    watt       : RETURN(dimensional_exponents(2,1,-3,0,0,0,0));
    coulomb    : RETURN(dimensional_exponents(0,0,1,1,0,0,0));
    volt       : RETURN(dimensional_exponents(2,1,-3,-1,0,0,0));
    farad      : RETURN(dimensional_exponents(-2,-1,4,1,0,0,0));
    ohm        : RETURN(dimensional_exponents(2,1,-3,-2,0,0,0));
    siemens    : RETURN(dimensional_exponents(-2,-1,3,2,0,0,0));
    weber      : RETURN(dimensional_exponents(2,1,-2,-1,0,0,0));
    tesla      : RETURN(dimensional_exponents(0,1,-2,-1,0,0,0));
    henry      : RETURN(dimensional_exponents(2,1,-2,-2,0,0,0));
    degree_celsius : RETURN(dimensional_exponents(0,0,0,0,1,0,0));

```