
**Space systems — Programme
management and quality — Vocabulary**

*Systèmes spatiaux — Management de programme et qualité —
Vocabulaire*

STANDARDSISO.COM : Click to view the full PDF of ISO 10795:2011





COPYRIGHT PROTECTED DOCUMENT

© ISO 2011

The reproduction of the terms and definitions contained in this International Standard is permitted in teaching manuals, instruction booklets, technical publications and journals for strictly educational or implementation purposes. The conditions for such reproduction are: that no modifications are made to the terms and definitions; that such reproduction is not permitted for dictionaries or similar publications offered for sale; and that this International Standard is referenced as the source document.

With the sole exceptions noted above, no other part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
Scope	1
1 Terms and definitions	1
2 Abbreviated terms	33
Bibliography.....	37

STANDARDSISO.COM : Click to view the full PDF of ISO 10795:2011

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10795 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 14, *Space systems and operations*.

STANDARDSISO.COM : Click to view the full PDF of ISO 10795:2011

Introduction

It is intended that this International Standard be applied for the management, engineering, and product assurance in space projects and applications. The definitions in this International Standard specify what is accomplished, rather than how the necessary work is organized and carried out. This allows the application of existing organizational structures and methods where they are effective, and for the structures and methods to evolve as necessary without rewriting the standards. The formulation of this International Standard takes into account the existing International Standard prepared by ISO/TC 176.

STANDARDSISO.COM : Click to view the full PDF of ISO 10795:2011

STANDARDSISO.COM : Click to view the full PDF of ISO 10795:2017

Space systems — Programme management and quality — Vocabulary

Scope

This International Standard provides definitions of all common terms used in the area of space systems and operations. It does not contain terms specific to an individual International Standard in the area of space systems and operations, which are defined in that particular International Standard.

1 Terms and definitions

1.1 Acceptance

1.1.1

acceptance

⟨act⟩ raw, semi-finished or finished substance (gaseous, liquid, solid) of given characteristics from which processing into a **component** (1.43) or **part** (1.153) is undertaken

1.1.2

acceptance

⟨process⟩ part of the verification process, which demonstrates that the **product** (1.162) meets specified acceptance margins

1.2

acceptance criteria

minimum requirements that it is necessary for an item to satisfy for formal acceptance

1.3

accepted risk

hazard that has not been eliminated and for which the residual risk is deemed low enough to continue operation and that has been accepted by project/program management on the basis of documented risk acceptance rationale

1.4

acceptance test

test to determine that a system, subsystem, **component** (1.43), or functional part is capable of meeting performance requirements prescribed in a purchase specification or other **document** (1.81) specifying what constitutes the adequate performance capability for the **item** (1.121) and to demonstrate that the item is free from manufacturing defects

1.5

accident

undesired event arising from operation of any **project** (1.167) or specific **item** (1.121) that results in (a) human death or injury, (b) loss of, or damage to, project hardware, **software** (1.205) or facilities that can then affect the accomplishment of the **mission** (1.140), (c) loss of, or damage to, public or private property, or (d) detrimental effects on the **environment** (1.85)

NOTE Accident and mishap are synonymous.

[EN 13701:2001, 3.2]

1.6

action

task negotiated between two and only two persons, one decision maker and one holder, whose result leads to an expected result as a description of an operation in the formulation of a solution, and is characterized by objectives in terms of cost, quality and due date

1.7

action item

assignment to a designated organization or individual the accomplishment of a defined objective within a specified time frame

1.8

alert

formal notification to users, informing them of a **failure** (1.91) or **nonconformity** (1.144) of an **item** (1.121), already released for use or not, that can also be present on other items already delivered (e.g. items with identical **design** (1.75) concept, **material** (1.135), **component** (1.43) or **process** (1.160))

NOTE An alert can also be raised when a deficiency in a specified **requirement** (1.190) that can affect the fitness for purpose in the defined application has been identified.

[EN 13701:2001, 3.4]

1.9

analysis

verification method utilizing techniques and tools such as math models, compilation similarity assessments, validation of records, etc., to confirm that verification requirements have been satisfied

1.10

anomaly

any gap between a current situation and an expected one

NOTE 1 An anomaly justifies an investigation that can lead to the discovery of a nonconformance, a defect or a "non-lieu" [deviation without impact, e.g. **product** (1.162) peculiarity].

NOTE 2 A deviation may be declared, foreseen or requested.

NOTE 3 An anomaly is often detected in comparison with what seems to be standard or with the expected use.

1.11

applicable document

document (1.81) that contains **provisions** (1.170) which, through reference in the source document, incorporates additional provisions in the source document

NOTE In this context, a provision is an expression that takes the form of a statement, an instruction, a recommendation or a requirement.

1.12

approval

formal agreement by a designated management official to use or apply an **item** (1.121) or proceed with a proposed course of action

NOTE 1 Approvals shall be documented.

NOTE 2 Approval implies that the approving authority has verified that the **item** (1.121) conforms to its **requirements** (1.190).

Adapted from EN 13701:2001, 3.8.

1.13**as-built configuration**

configuration of one **product** (1.162) item identified by its gaps of conformity with respect to its applicable configuration

NOTE 1 The relevant “as-designed configuration” corresponds to the same “part number”.

NOTE 2 “As-built configuration” includes any impacts from technical events, anomalies, repairs, life potential consumption that occurred before the **product** delivery and any potential modifications applied on the **product** but not embodied in the relevant design data file.

1.14**as-built configuration list****ABCL**

reporting instrument defining the “as-built status” for each serial number of a configuration item subject to formal acceptance

NOTE 1 The ABCL shall identify the “as-manufactured” and “as-tested” statuses applicable to a part comprising a configuration item.

NOTE 2 Using the configuration item data list as a reference, any difference between the ABCL and the CIDL shall be documented in the ABCL with reference to the applicable NCR and RFW.

1.15**as-delivered configuration**

as-built configuration at the time of delivery

1.16**as-designed configuration**

current design status at any point of time providing the complete definition of a configuration item

NOTE The starting point of the “as-designed” configuration with regard to the “as-planned” configuration is based on changes the company has approved internally but has not yet incorporated in the design, and on changes already implemented but not yet approved in the “as-planned” configuration.

1.17**as-ordered configuration****contractual configuration**

configuration of a product configuration item, effectively given by its contractual approved changes from the configuration baseline

NOTE At a given moment, a **product** (1.162) may have several applicable configurations.

1.18**as-planned configuration**

planned to be built statement for each configuration item unit being delivered

NOTE The as-planned configuration is composed of the current configuration baseline and any changes that the company has approved internally but has not yet embodied in the current configuration baseline.

1.19**as-qualified configuration**

as-built configuration that was certified to have satisfactorily passed specified qualification tests

1.20**assembly**

combination of **parts** (1.153), **components** (1.43) and units that form a functional entity

NOTE An assembly can be disassembled and retain its capabilities after reassembly.

**1.21
assessment**

systematic process of collecting and analysing data to determine the current status of a **product** (1.162), a **process** (1.160), a **system** (1.221), a person or an **organization** (1.150)

**1.22
audit**

systematic, independent and documented **process** (1.160) for obtaining **audit evidence** (1.26) and evaluating it objectively to determine the extent to which **audit criteria** (1.25) are fulfilled

NOTE Internal audits, sometimes called first-party audits, are conducted by, or on behalf of, the **organization** (1.150) itself for internal purposes and can form the basis of the organization's self-declaration of **conformity** (1.55). External audits include what are generally termed "second-" or "third-party audits". Second-party audits are conducted by parties having an interest in the organization, such as **customers** (1.71), or by other persons on their behalf. Third-party audits are conducted by external independent organizations. Such organizations provide certification or registration of **conformity** (1.55) with **requirements** (1.190) such as those of ISO 1401:1994. When **quality** (1.176) and environmental **management systems** (1.134) are audited together, this is termed "combined audit". When two or more auditing organizations cooperate to audit a single auditee jointly, this is termed "joint audit".

Adapted from ISO 9000:2005, 3.9.1.

**1.23
audit client
organization**

(1.150) or person requesting an **audit** (1.22)

NOTE The audit client may be the auditee or any other **organization** (1.150) that has the regulatory or contractual right to request an audit.

[ISO 9000:2005, 3.9.7]

**1.24
audit conclusion**

outcome of an **audit** (1.22) provided by the audit team after consideration of the audit objectives and all **audit findings** (1.27)

[ISO 9000:2005, 3.9.6]

**1.25
audit criteria**

set of policies, **procedures** (1.159), or **requirements** (1.190) used as a reference

[ISO 9000:2005, 3.9.3]

**1.26
audit evidence**

records (1.184), statements of fact or other information which is relevant to the **audit criteria** (1.25) and verifiable

NOTE Audit evidence can be qualitative or quantitative.

[ISO 9000:2005, 3.9.4]

**1.27
audit findings**

results of the evaluation of the collected **audit evidence** (1.26) against **audit criteria** (1.25)

NOTE Audit findings can indicate either **conformity** (1.55) or **nonconformity** (1.144) with audit criteria, or opportunities for improvement.

[ISO 9000:2005, 3.9.5]

1.28**availability of an item**

ability to be in a state to perform as required, under given conditions, at a given instant, or over a given time interval

NOTE 1 The “given conditions” include the provision of necessary external resources.

NOTE 2 This ability depends on the combined aspects of the reliability and maintainability of the **item** (1.121), and the maintenance support performance or recoverability of the **item** (1.121).

NOTE 3 Availability may be quantified using appropriate measures.

1.29**baseline**

set of information that describes exhaustively a situation at a given instant of time or over a given time interval

[EN 13701:2001, 3.13]

NOTE It is generally used as a reference for comparison with an analysis of subsequent evolutions of the information.

1.30**business agreement**

legally binding agreement, for the supply of goods or services, between two or more actors in the customer-supplier chain

NOTE Business agreements are recorded in a variety of forms, such as

- **contracts** (1.60),
- memoranda of understanding,
- inter-governmental agreements,
- inter-agency agreements,
- partnerships,
- bartering agreements,
- purchase orders.

1.31**calibration**

all the operations for the purpose of determining the values of the **errors** (1.87) and, if necessary, other metrological properties of a measuring instrument

NOTE The metrological use of the term “calibration” is often extended to include operations such as adjustments, scale graduation, etc. This use is deprecated.

[IEC Multilingual Dictionary: 2001 edition]

1.32**catastrophic**

capable of causing death or major system destruction

1.33**certificate of compliance**

signed formal declaration that states that all actions relating to safety and interface verification that the user is required to complete prior to turnover have been accomplished

1.34

certification procedure

written assurance by a third party that a **product** (1.162), **process** (1.160) or service conforms to specified **requirements** (1.190)

1.35

change

official numerically issued alterations to a **document** (1.81) or any portion thereof, usually brought about by changed conditions or more complete information

NOTE 1 Such a correction is not extensive enough to require retying and reprinting of the entire **document** (1.81) and usually consists of an instruction to replace a few pages with those of a later issue. Documents of 10 or fewer pages are revised, not changed.

NOTE 2 "Class 1" ("major" for deviation) are changes that impact the contractual/technical agreement reached between the **project** (1.167) and its customer. It is necessary that such changes be submitted to the customer for review and approval before implementation.

NOTE 3 "Class 2" ("minor" for deviation) are changes that do not impact the customer **contract** (1.60) and that are necessary for the **project** (1.167) and its supply chain to meet the technical/contractual requirements and provisions. Such changes can be implemented after CCB approval.

1.36

change request

document (1.81) containing a call for an adjustment of a system

NOTE 1 It is of great importance in the change management process.

NOTE 2 A change request is declarative (i.e. it states what it is necessary to accomplish) but leaves out how the change should be carried out.

1.37

characteristic

distinguishing feature

NOTE 1 A characteristic can be inherent or assigned.

NOTE 2 A characteristic can be qualitative or quantitative.

NOTE 3 There are various classes of characteristic, such as the following:

- physical (e.g. mechanical, electrical, chemical or biological characteristics);
- sensory (e.g. related to smell, touch, taste, sight, hearing);
- behavioural (e.g. courtesy, honesty, veracity);
- temporal [e.g. punctuality, **reliability** (1.187), **availability** (1.28)];
- ergonomic [e.g. physiological characteristic, or related to human **safety** (1.198)];
- functional (e.g. maximum speed of an aircraft).

[ISO 9000:2005, 3.5.1]

1.38

clean room

clean area controlled according to specified levels

NOTE Levels specified include humidity, temperature, particulates number versus size and volume and chemical contamination.

1.39**common-cause failure**

〈within a system〉 multiple **failures** (1.91) related to a single cause or causal event

NOTE 1 It is generally accepted that the **failures** (1.91) occur simultaneously or within a short time of each other.

NOTE 2 Common-cause failures can also be common-mode failures.

NOTE 3 Common-cause failures reduce the effect of system redundancy.

1.40**common-mode failure**

〈within a system〉 multiple **failures** (1.91) that occur in the same way

NOTE 1 Common-mode failures can have different causes.

NOTE 2 Common-mode failures can also be common-cause failures (1.91).

1.41**common-mode fault**

fault (1.94) of multiple **items** (1.121) that exhibit the same fault mode

[EN 13701:2001, 3.21]

1.42**competence**

demonstrated ability to apply knowledge and skills

NOTE 1 Technical competence is defined by the know-how, such as working practices, special skills ("tours de main"), mastery of technology, etc.

NOTE 2 Cognitive competence is knowledge, such as specific fundamental knowledge, scientific "capital", expertise in a domain, history, etc.

NOTE 3 Methodological competence is defined by the working methods, such as problem solving, manner of decision.

NOTE 4 Experimental competence is the experience related to relations with different interlocutors (e.g. customer relations), to participation, to events, to "personal" actions, etc.

[ISO 9000:2005, 3.9.14]

1.43**component part**

set of materials, assembled according to defined and controlled processes, which cannot be disassembled without destroying its capability and which performs a simple **function** (1.102) that can be evaluated against expected performance requirements

NOTE 1 The term "part" is preferred when referring to purely mechanical devices.

NOTE 2 The term "component" is preferred for EEE devices.

1.44**concession**

permission to use or release a **product** (1.162) that does not conform to specified **requirements** (1.190)

NOTE 1 The concession can impose limitations on the use of the conceded product: a concession is generally limited to the delivery of a **product** (1.162) that has nonconforming characteristics within specified limits for an agreed period of time or quantity of that **product** (1.162).

NOTE 2 The "deviation" is an anterior decision whereas the "waiver" is a posterior decision with respect to production phase.

NOTE 3 A concession is part of the **product** (1.162) as-built configuration and does not affect the configuration baselines.

NOTE 4 The inability to meet the required **product** (1.162) characteristics is documented through the concession after the manufacturing phase.

1.45

configuration

interrelated functional and physical characteristics of a **product** (1.162) (hardware/software) defined in configuration documents subject to configuration management

1.46

configuration baseline

approved status of requirements and design of a **product** (1.162) at project key milestone that serves as reference for activities throughout the **life cycle** (1.128) of the **product** (1.162)

Adapted from ISO 10007:2003, 3.4.

1.47

configuration control

coordinated activities for controlling modifications to a **configuration baseline** (1.46)

NOTE Request for deviations are also considered modifications to a baseline.

1.48

configuration document

document (1.81) that defines the **requirements** (1.190) for **function** (1.102), **design** (1.75), build, production, and **verification** (1.229) for a **configuration item** (1.50)

NOTE For space **standards** (1.215), configuration documents can include documents relating to operation and disposal of the configuration item.

1.49

configuration identification

coordinated activities to establish rules for **configuration item** (1.50) selection, **configuration baseline** (1.46) content definition, and **product** (1.162) and **document** (1.81) identifiers definition

1.50

configuration item

aggregation of hardware, **software** (1.205), processed **materials** (1.135), services or any of its discrete portions, that is designated for **configuration management** (1.52) and treated as a single entity in the configuration management **process** (1.160)

NOTE A configuration item can contain other configuration item(s).

1.51

configuration item data list

CIDL

document (1.81) generated from the central configuration database giving the current design status of a configuration item at a given point of time in sufficient detail and/or providing its complete definition

NOTE A CIDL includes the list of applicable changes not yet incorporated into the baseline documentation and deviations.

1.52

configuration management

activity for establishing and maintaining consistent records of the status of and changes to the performance parameters of a **product** (1.162) and its functional and physical attributes compared to **product** (1.162) design and operational requirements

NOTE Configuration management is applied throughout the entire **life cycle** (1.128) of the **product** (1.162) (i.e. development, production, deployment, operation and disposal).

Adapted from ISO 10007:2003, 3.6.

1.53**configuration status accounting**

formalized recording and reporting of **product** (1.162) characteristics and configuration information, the status of applicable changes and the status of their implementation

Adapted from ISO 10007:2003, 3.7.

1.54**configuration verification**

coordinated activities to determine the conformity of the **configuration item** (1.50) to its **configuration document(s)** (1.48)

1.55**conformity**

conformance (deprecated)

fulfilment of a **requirement** (1.190)

NOTE This definition is consistent with ISO/IEC Guide 2 but differs from it in phrasing to fit into the ISO 9000 concepts.

[ISO 9000:2005, 3.6.1]

1.56**constraint**

characteristic, result or design feature that is made compulsory or has been prohibited for some reason

NOTE 1 Constraints are generally restrictions on the choice of solutions in a **system** (1.221).

NOTE 2 Two kinds of constraints are considered: those that concern solutions and those that concern the use of the system.

EXAMPLE Constraints can come from environmental and operational conditions, law, **standards** (1.215), market demand, investments and means availability, or the organization's policy.

Adapted from EN 1325-1:1997, 3.1.7.

1.57**contamination**

introduction of any undesirable molecular or particulate matter (including microbiological matter) into an **item** (1.121) or into the environment of interest

1.58**contingency procedure**

pre-planned **procedure** (1.159) for execution in response to a departure from specified behavior

[EN 13701:2001, 3.31]

1.59**continual improvement**

recurring activity to increase the ability to fulfil **requirements** (1.190)

NOTE The **process** (1.160) of establishing objectives and finding opportunities for improvement is a continual process through the use of **audit findings** (1.27) and **audit conclusions** (1.24), analysis of data, management reviews or other means and generally leads to **corrective action** (1.63) or **preventive action** (1.158).

[ISO 9000:2005, 3.2.13]

1.60**contract**

legally enforceable business agreement for the supply of goods or services

NOTE A contract is a special case of a business agreement in which payment is associated with the contract conditions.

1.61

contractor

supplier (1.219) in a contractual situation

1.62

correction

action to eliminate a detected **nonconformity** (1.144)

NOTE A correction can be made in conjunction with a **corrective action** (1.63).

EXAMPLE **Rework** (1.193) or regrade.

[ISO 9000:2005, 3.6.6]

1.63

corrective action

action to eliminate the cause of a detected **nonconformity** (1.144) or other undesirable situation

NOTE 1 There can be more than one cause for a nonconformity.

NOTE 2 Corrective action is taken to prevent recurrence whereas **preventive action** (1.158) is taken to prevent occurrence.

NOTE 3 There is a distinction between **correction** (1.62) and corrective action.

[ISO 9000:2005, 3.6.5]

1.64

cost breakdown structure

hierarchical structure that depicts elements of cost

1.65

critical

capable of causing severe injury, severe illness, or major property damage

1.66

critical characteristics

any physical attribute of an article or material that, if defective, can cause loss of life or equipment, or make the article or material non-functional

1.67

critical design review

CDR

review performed prior to fabrication of prototype and after completion of the critical design

NOTE In the review, drawing specifications and test result of the engineering model are evaluated to confirm that the result of the critical design satisfies the requirements of the **contracts** (1.60) and technical specifications to allow proceeding with prototype production phase.

1.68

critical hazard

any hazard that can cause a nondisabling injury, severe occupational illness, loss of an emergency system, or that requires the use of emergency procedures, or involves major damage to one of the following: the launch or servicing vehicle, manned base, an on-orbit life-sustaining function, a ground facility, or any critical support equipment

1.69

critical item

item that can pose a potential threat to the schedule, cost, performance and quality of a **project** (1.167) or programme that is controlled by a specific action plan in order to mitigate emanating risks and to prevent undesirable consequences

NOTE Examples of critical items are:

- an item not qualified or validated for the application in question (or that has previously caused problems that remain unresolved);
- an item difficult to demonstrate design performance;
- an item highly sensitive to the conditions under which it is produced or used (e.g. contamination, radiation);
- an item having the potential to degrade the quality of the **product** (1.162) significantly, and hence the ability of the end-product to accomplish defined mission objectives;
- an item for which major difficulties or uncertainties are expected in the procurement, manufacturing, assembly, inspection, test, handling, storage and transportation that can have the potential to lead to a major degradation in the quality of the **product** (1.162).

1.70

critical path

series of activities that determine the earliest completion of the **project** (1.167)

NOTE As a consequence, delay of any one task belonging to the critical path extends the **project** (1.167) duration.

1.71

customer

organization (1.150), legal entity or person that receives a **product** (1.162) as part of a business agreement

EXAMPLE Consumer, client, end-user, retailer, beneficiary and **purchaser** (1.171).

NOTE 1 A customer can be internal or external to the **organization** (1.150).

NOTE 2 The “customer”, as a physical or moral person for the account of which the programme or **project** (1.167) is realized, also called “owner” or “contracting authority”, is the responsible actor in the acquisition network for defining the requirements (specified in technical and contractual terms) and for the control of the realisation entrusted to a prime contractor in order to respect the contractual objectives in terms of performance, costs and due dates.

1.72

defect

non-fulfilment of a **requirement** (1.190) related to an intended or specified use

NOTE 1 The distinction between the concepts of defect and **nonconformity** (1.144) is important as it has legal connotations, particularly those associated with **product** (1.162) liability issues. Consequently, the term “defect” should be used with extreme caution.

NOTE 2 The use as intended by the **customer** (1.71) can be affected by the nature of the information, such as operating or maintenance instructions, provided by the **supplier** (1.219).

[ISO 9000:2005, 3.6.3]

1.73

dependability

(of an item) ability to perform as and when required

NOTE 1 Dependability characteristics include availability and its inherent or external influencing factors, such as: reliability, fault tolerance, recoverability, integrity, security, maintainability, durability, and maintenance support.

NOTE 2 Dependability is also used descriptively as an umbrella term for the time-related quality characteristics of a **product** (1.162) or service, and it may also be expressed as a grade, degree, confidence or probability of fulfilling a defined set of characteristics.

NOTE 3 Specifications for dependability characteristics typically include the **function** (1.102) the **product** (1.162) is required to perform; the time for which it is required that that performance be sustained; and the conditions of storage, use and maintenance. Requirements for safety, efficiency and economy throughout the **life cycle** (1.128) may also be included.

1.74

derating

designed reduction of stress from the rated value to enhance reliability

1.75

design, noun

⟨result⟩ set of information that defines the **characteristics** (1.37) of a **product** (1.162)

Adapted from EN 13701:2001, 3.44.

1.76

design, noun

⟨activity⟩ **process** (1.160) used to generate the set of information defining the **characteristics** (1.37) of a **product** (1.162)

Adapted from EN 13701:2001, 3.45.

1.77

design review

formal, independent examination of a design to identify shortcomings that could affect the fitness for purpose, reliability, maintainability or maintenance support requirements of the **item** (1.121) concerned

NOTE 1 In this context, “design” includes requirements, specifications, drawings, and supporting documentation.

NOTE 2 Design review is not, by itself, sufficient to ensure the adequacy of the emerging design.

1.78

development

process (1.160) by which the capability to adequately implement a technology or **design** (1.75) is established before manufacture

NOTE This process can include the building of various partial or complete **models** (1.141) of the **products** (1.162) and assessment of their **performance** (1.155).

[EN 13701:2001, 3.47]

1.79

deviation

formal authorization to depart from the originally specified requirements for a **product** (1.162), prior to its production

NOTE 1 “Waiver” is a posterior decision whereas “deviation” is an anterior decision with respect to production phase.

NOTE 2 Permission to use or release a product that does not conform to specified requirements.

1.80

discrepancy

departures from expected performance

NOTE They can be the result of nonconforming hardware and/or software, or conditions occurring in test set-up. These differences from expected performance levels can be momentary, non-repeatable, or permanent.

1.81

document

information and its supporting medium

EXAMPLES **Record** (1.184), **specification** (1.214), procedure document, drawing, report, **standard** (1.215).

NOTE 1 The medium can be paper, magnetic, electronic or optical computer disc, photograph or master sample, or a combination thereof.

NOTE 2 A set of documents, for example specifications and records, is frequently called “documentation”.

NOTE 3 Some **requirements** (1.190) (e.g. the requirement of readability) relate to all types of documents, however there can be different requirements for specifications (e.g. the requirement that they be revision controllable) and records (e.g. the requirement that they be retrievable).

[ISO 9000:2005, 3.7.2]

1.82

documentation

one mode of information communication

NOTE This includes management and technical data current as of a given point in time and may be used to reflect contractor to customer and/or contractor to contractor agreements and procedures. This includes such items as program plans, procedures, specifications, ICDs, reports, technical publications, training documentation.

[SSP 30534]

1.83

EEE component

EEE part

device that performs an electrical, electronic or electromechanical **function** (1.102) and consists of one or more elements so joined together that they cannot normally be disassembled without destroying this capability

[EN 13701:2001, 3.51]

1.84

end item

combination of **parts** (1.153), assemblies, accessories, and/or attachments integrated to form an equipment unit that can accomplish a specific **function** (1.102) when used

NOTE An end item is complete within itself and classified as such for purposes of separate manufacture, procurement, drawings, specification, storage, issue, maintenance, or use.

1.85

environment

natural conditions and induced conditions that constrain the design definitions or operations for end products and their enabling products

NOTE 1 Examples of natural conditions are weather, climate, ocean conditions, terrain, vegetation, dust, light and radiation.

NOTE 2 Examples of induced conditions are electromagnetic interference, heat, vibration, pollution and contamination.

1.86

equipment

unit

integrated set of **parts** (1.153) and **components** (1.43)

NOTE 1 An equipment accomplishes a specific **function** (1.102).

NOTE 2 An equipment is self-contained and classified as such for the purposes of separate manufacture, procurement, drawings, specification, storage, issue, maintenance, or use.

1.87

error

discrepancy between a computed, observed or measured value or condition and the true, specified or theoretically correct value or condition

NOTE An error can be caused by a faulty **item** (1.121), e.g. a computing error made by faulty computer **equipment** (1.86).

[IEC Multilingual Dictionary: 2001 edition]

1.88

estimate at completion

sum of costs incurred up to the cut-off date and the respective **estimate to completion** (1.89)

Adapted from EN 13701:2001, 3.57.

1.89

estimate to completion

estimate of all costs from the cut-off date required to deliver the **product** (1.162), based on work to be completed, and approved anticipated **contract** (1.60) changes

Adapted from EN 13701:2001, 3.58.

1.90

evaluation

systematic process of determining how well individuals, procedures, systems or programs have met formally agreed objectives and requirements

1.91

failure

⟨of an item⟩ loss of ability to perform as required

NOTE 1 When the loss of ability is caused by a pre-existing condition, the failure occurs when a particular set of circumstances is encountered.

NOTE 2 A failure of an **item** (1.121) is an event, as distinct from a fault of an **item**, which is a state.

NOTE 3 Qualifiers may be used to classify failures according to the severity of consequences, such as catastrophic, critical, major, minor, marginal and insignificant, the definitions depending upon the field of application.

1.92

failure mode

fault mode (deprecated in this sense) manner in which **failure** (1.91) occurs

NOTE A failure mode may be defined by the **function** (1.102) lost or the state transition that occurred.

1.93

failure tolerance

attribute of an **item** (1.121) that makes it able to perform a required **function** (1.102) in the presence of certain given sub-item **failures** (1.91)

1.94

fault, noun

state of an **item** (1.121) characterized by inability to perform as required, excluding the inability during preventative maintenance or other planned actions, or due to lack of external resources

NOTE A fault is often the result of a **failure** (1.91) of the **item** (1.121) itself, but can exist without prior **failure** (1.91).

Adapted from IEC Multilingual Dictionary: 2001 edition.

1.95

fault, noun

unplanned occurrence or **defect** (1.72) in an **item** (1.121) that can result in one or more **failures** (1.91) of the **item** (1.121) itself or of other associated **equipment** (1.86)

[IEC Multilingual Dictionary: 2001 edition]

NOTE An **item** (1.121) can contain a sub-element fault, which is a defect that can manifest itself only under certain circumstances. When those circumstances occur, the defect in the sub-element causes the item to fail, resulting in an **error** (1.87). This error can propagate to other items causing them, in turn, to fail. After the **failure** (1.91) occurs, the item as a whole is said to have a fault or to be in a faulty state.

1.96**fault tolerance**

⟨design property of a system⟩ fault masking (deprecated in this sense) ability to continue functioning with certain faults present

NOTE In French, the adjective “fault tolerant” is used in this sense.

1.97**fault tree analysis****FTA**

analysis using logic diagram showing the faults of sub-items, external events, or combinations thereof, that result in a predefined, undesired event

1.98**firmware**

hardware that contains a computer program or data that cannot be changed in its user **environment** (1.85)

NOTE The computer program and data contained in firmware are classified as **software** (1.205); the circuitry containing the computer program and data is classified as hardware.

1.99**flammability**

measure of the ease with which a material is set on fire

1.100**flashpoint**

lowest temperature at which a material gives off flammable vapour that, when mixed with the test atmosphere and exposed to an ignition source, provides a non-self-sustaining flash

1.101**flight operations**

all activities related to the planning, execution and evaluation of the control of the space segment (or subsets thereof) when in orbit

1.102**function**

intended effect of a **system** (1.221), **subsystem** (1.218), **product** (1.162) or **part** (1.153)

Adapted from EN 1325-1:1997, 3.3.1.

1.103**function tree**

hierarchical decomposition of the system performances into **functions** (1.102) and sub-functions that, when all are fulfilled, completes the overall system mission

1.104**functional analysis**

technique of identifying and describing all **functions** (1.102) of a **system** (1.221)

Adapted from EN 1325-1:1997, 3.3.2.

1.105**functional verification**

task of assuring that hardware or software functions as per the design requirements

1.106**ground operations**

all activities related to the planning, execution and evaluation of the control of the ground segment (or subsets thereof) facility

1.107

ground support equipment

GSE

contract (1.60) deliverable equipment (hardware/software) used on the ground to test, transport, access, handle, maintain, measure, calibrate, verify, service and protect flight hardware/software

1.108

ground systems

all ground infrastructure elements that are used to support the preparation activities leading up to mission operations, the conduct of mission operations and all post-operational activities

1.109

hardware

H/W

items of identifiable equipment including piece **parts** (1.153), **components** (1.43), assemblies, subsystems and systems

1.110

hazard

existing or potential condition of an **item** (1.121) that can result in an **accident** (1.5)

NOTE 1 This condition can be associated with the design, fabrication, operation or environment of the item, and has the potential for accidents.

NOTE 2 "Items" can include human beings.

Adapted from ISO 14620-2:2000, 3.9.

1.111

hazard analysis

determination of potential sources of danger, causes, effects, hazard level, and recommended resolution for those conditions found in either the hardware/software system, the person-machine relationship, or both, that can cause loss of personnel capability, loss of system, or loss of life/injury to the public

1.112

hazardous event

occurrence leading to undesired consequences and arising from the triggering by one (or more) initiator events of one (or more) **hazards** (1.110)

1.113

incident

unplanned event that could have been an **accident** (1.5) but was not

[EN 13701:2001, 3.71]

1.114

infrastructure

organization **system** (1.221) of facilities, **equipment** (1.86) and services needed for the operation of an **organization** (1.150)

[ISO 9000:2005, 3.3.3]

1.115

inspection

conformity evaluation by observation and judgement accompanied as appropriate by measurement, testing or gauging

[ISO 9000:2005, 3.8.2]

1.116**integrate logistic support
ILS**

coordinated and interactive set of technical and management tasks whose objectives are the following:

- to express the requirement in logistics support and the environmental constraints of use in the expression of operational requirement;
- to contribute to obtaining a system definition including the support elements:
 - allowing the optimization and maintenance of its effectiveness for all its life time, in consistency with the user resources,
 - allowing total optimization of performance/costs/schedules;
- to realize, set up and to renew the support elements, according to the exploitation and the maintenance requirements

1.117**integration**

process of physically and functionally combining lower-level products (hardware or software) to obtain a particular functional configuration

1.118**interchangeability**

situation when two or more **items** (1.121) possess such functional and physical characteristics as to be equivalent in performance and durability and capable of being exchanged one for another without alteration of the items themselves or adjoining items except for adjustment and without selection for fit or performance

NOTE Functional and physical characteristics that constitute interchangeability are as follows.

- It is necessary that items have the same design envelope and have no use limitations imposed.
- It is necessary that items utilize the same attachments, mountings, or mating surfaces.
- It is necessary that attachments, connectors, wiring, GSE, and tubing be the same to the extent that no rework is required on installation.
- It is necessary that items meet all baseline design requirements for performance. Performance or durability design requirements include the same safety, strength, electrical, mechanical, reliability, maintainability, tolerance, balance and mass requirements.
- It is necessary that items have the same adjustments, testing, operation, and maintenance requirements and the same design to the extent that the same test procedures, specifications, and operating procedures may be utilized.

1.119**interchangeable**

any **item** (1.121) that has identical external form, fit, and **function** (1.102) with another item, allowing its use as a replacement

1.120**interface****I/F**

mechanical, thermal, electrical, or operational common boundary between two elements of a system

1.121**item**

any node of a product breakdown structure

NOTE 1 Any part, **component** (1.43) device, subsystem, functional unit, equipment or system that can be individually considered.

NOTE 2 An item can be considered either as a “product” or a “component” on a “product breakdown structure” of more than two levels of decomposition. Items are designated “products” when described as being decomposed and designated “components” when described as decompositions.

1.122

launch campaign

launch activities that include launcher preparation and final integration, payload processing and integration on the launcher, and launch operations including flight data gathering

1.123

launch operations

all launching related activities taking place after completion of the activities necessary to deliver a fully integrated launcher up to reception of post-flight data

1.124

launch segment

part of a space system that is used to transport space segment element(s) into space

NOTE 1 A launch segment is composed of one or more launch segment elements.

NOTE 2 A launch segment is composed of the integrated launcher and needed facilities for manufacturing, testing and delivering launcher elements.

1.125

launch vehicle

See **launcher** (1.126)

1.126

launcher

system that ensures the transport of a payload into space orbit

1.127

launcher stage

complete element of a launcher that delivers the defined thrust during dedicated phase of the launcher mission

NOTE 1 A launcher stage typically consists of a main propulsion system, a reaction controlled system (sometimes integrated to some extent with the main propulsion system), supporting structure, forward and aft skirts, aerodynamic control and/or stabilized surfaces, a separation system and a destruction system.

NOTE 2 Some of the upper stages are also equipped with an avionics system.

1.128

life cycle

all the phases of acquisition, operation and logistic support of an **item** (1.121) beginning with requirement identification through disposal of the item

1.129

life cycle cost

total cost estimated and eventually incurred in connection with a system during its acquisition, operation, maintenance, and disposal

NOTE Can also be referred to as the total cost of ownership.

Adapted from EN 13701:2001, 3.78.

1.130

lifetime

period over which any of the **item** (1.121) properties are required to be within defined limits

1.131**maintainability**

(of an item) ability to be retained in, or restored to a state in which it can perform as required, under given conditions of use and maintenance

NOTE 1 Given conditions of use may include storage.

NOTE 2 Given conditions of maintenance include the procedures and resources for use.

NOTE 3 Maintainability may be quantified using such measures as mean time to restoration, or the probability of restoration within a specified period of time.

1.132**maintenance**

combination of all technical and administrative actions intended to retain an **item** (1.121) in, or restore it to, a state in which it can perform as required

NOTE Maintenance includes management and supervision activities for support.

1.133**management**

coordinated activities to direct and control an **organization** (1.150)

NOTE In English, the term “management” sometimes refers to people (i.e. a person or group of people) with authority and responsibility for the conduct and control of an organization. When “management” is used in this sense it should always be used with some form of qualifier to avoid confusion with the concept “management” defined above. For example, “management shall” is deprecated, whereas “top management shall” is acceptable.

[ISO 9000:2005, 3.2.6]

1.134**management system**

system (1.221) to establish policy and objectives and to achieve those objectives

NOTE A management system of an **organization** (1.150) can include different management systems, such as a quality management system, a financial management system or an environmental management system.

[ISO 9000:2005, 3.2.2]

1.135**material**

raw, semi-finished or finished purchased item (gaseous, liquid, solid) of given characteristics from which processing into a functional element of the **product** (1.162) is undertaken

[EN 13701:2001, 3.81]

1.136**mean time between failures****MTBF**

expected value of the operating time between **failures** (1.91)

NOTE 1 “Time” is generic, and should be expressed in units appropriate to the **item** (1.121) concerned, e.g. calendar time, operating time, operating cycles, distance run, etc., and the units should always be clearly stated.

NOTE 2 The practice of replacing the “T” with “D” for distance, or “K” for kilometres, etc., is deprecated.

1.137**measurement management system**

set of interrelated or interacting elements necessary to achieve metrological confirmation and continual control of measurement processes

[ISO 9000:2005, 3.10.1]

1.138

measuring equipment

measuring instrument, **software** (1.205), measurement **standard** (1.215), reference **material** (1.135), or auxiliary apparatus or combination thereof necessary to realize a measurement process

[ISO 9000:2005, 3.10.4]

1.139

mechanical part

piece of hardware that is not electrical, electronic or electromechanical, and that performs a simple elementary **function** (1.102) or part of a function in such a way that it can be evaluated as a whole against expected requirements of **performance** (1.155) and cannot be disassembled without destroying this capability

[EN 13701:2001, 3.84]

1.140

mission

specific task, duty or **function** (1.102) defined for accomplishment by a **system** (1.221)

[EN 13701:2001, 3.86]

1.141

model

physical or abstract representation of relevant aspects of an **item** (1.121) or **process** (1.160) that is put forward as a basis for calculations, predictions, or further assessment

[Oxford English Dictionary]

NOTE The term “model” can also be used to identify particular instances of the **product** (1.162), e.g. flight model.

1.142

modification

scheduled replacement of an **item** (1.121) with an item of a different configuration (new or modified)

NOTE This type of maintenance is accomplished during transfer periods for mission and safety items.

1.143

non-conformance

See **nonconformity** (1.144).

1.144

nonconformity

non-fulfilment of a requirement

[ISO 9000:2005, 3.6.2]

1.145

normative document

document (1.81) that provides rules, guidelines or **characteristics** (1.37) for activities or their results

NOTE The term “normative document” is a generic term that covers such documents as **standards** (1.215), technical **specifications** (1.214), codes of practice and regulations.

Adapted from EN 45020:2004, 3.1.

1.146

normative reference

reference which incorporates **provisions** (1.170) from a cited publication into a **normative document** (1.145)

Adapted from EN 13701:2001, 3.92.

1.147
off-the-shelf
OTS

existing item that has been developed for a specific application and is intended for use in another application

1.148
operating cycles

cumulative number of times an **item** (1.121) completes a sequence of activation and returns to its initial state

1.149
operating life

maximum operating time or cycles that an **item** (1.121) can accrue before replacement or refurbishment without risk of degradation of performance beyond acceptable limits

1.150
organization

group of people and facilities with an arrangement of responsibilities, authorities and relationships

EXAMPLES Company, corporation, firm, enterprise, institution, charity, sole trader, association, **project** (1.167) or **parts** (1.153), or combination thereof.

NOTE 1 The arrangement is generally orderly.

NOTE 2 An organization can be public or private.

NOTE 3 This definition is valid for the purposes of quality management system standards. The term "organization" is defined differently in ISO/IEC Guide 2.

[ISO 9000:2005, 3.3.1]

1.151
organizational structure

arrangement of responsibilities, authorities and relationships between people

Adapted from ISO 9000:2005, 3.3.2.

1.152
original budget

budget established at, or near, the time the **contract** (1.60) was signed, based on the negotiated contract cost

1.153
part

See **component** (1.43).

1.154
payload
P/L

set of space segment elements (parts of a space system, placed in space, to fulfil the space mission objectives)

NOTE 1 A spacecraft payload is a set of instruments or equipment that performs the user mission.

NOTE 2 A launcher payload is a set of space segment elements carried into space in accordance with agreed position, time and environmental conditions.

1.155

performance

aspects of an **item** (1.121) observed or measured from its operation or **function** (1.102)

NOTE These aspects are generally quantified.

Adapted from EN 13701:2001, 3.95.

1.156

preliminary design review

review performed prior to critical design but after preliminary design

NOTE The review shall confirm that the **products** (1.162), the results of the preliminary design that satisfy the system or development specifications, can be materialized and transferred to the critical design phase.

1.157

preliminary hazard analysis

PHA

analysis technique for performing an initial risk assessment of a concept of a system to identify safety-critical areas, evaluate hazards, and to identify the safety design requirements required in the project

1.158

preventive action

action to eliminate the cause of a potential **nonconformity** (1.144), or other undesirable potential situation

NOTE 1 There can be more than one cause for a potential nonconformity.

NOTE 2 Preventive action is taken to prevent occurrence whereas **corrective action** (1.63) is taken to prevent recurrence.

[ISO 9000:2005, 3.6.4]

1.159

procedure

specified way to carry out an activity or **process** (1.160)

NOTE 1 Procedures can be documented or not.

NOTE 2 When a procedure is documented, the term "written procedure" or "documented procedure" is frequently used. The **document** (1.81) that contains a procedure can be called a "procedure document".

[ISO 9000:2005, 3.4.5]

1.160

process

set of interrelated or interacting activities that transform inputs into outputs

NOTE 1 Inputs to a process are generally outputs of other processes.

NOTE 2 Processes in an **organization** (1.150) are generally planned and carried out under controlled conditions to add value.

NOTE 3 A process where the **conformity** (1.55) of the resulting **product** (1.162) cannot be readily or economically verified is frequently referred to as a "special process".

[ISO 9000:2005, 3.4.1]

1.161

procurement document

document such as a purchase order, subcontract, statement of work, technical specifications, and interoperate work order required to define articles, materials and services being procured and the terms and conditions imposed

1.162**product**

result of a **process** (1.160)

NOTE 1 There are four generic product categories, as follows:

- services (e.g. transport);
- software (e.g. computer program, dictionary);
- hardware [e.g. engine **mechanical part** (1.139)];
- processed **materials** (1.135) (e.g. lubricant).

Many products are comprised of elements belonging to different generic product categories. Whether the product is then called service, software, hardware or processed material depends on the dominant element.

EXAMPLE The offered product “automobile” consists of hardware (e.g. tyres), processed materials (e.g. fuel, cooling liquid), software (e.g. engine control software, driver’s manual), and service (e.g. operating explanations given by the salesman).

NOTE 2 Service is the result of at least one activity necessarily performed at the interface between the **supplier** (1.219) and **customer** (1.71) and is generally intangible. Provision of a service can involve, for example,

- an activity performed on a customer-supplied tangible product (e.g. automobile to be repaired);
- an activity performed on a customer-supplied intangible product (e.g. the income statement required to prepare a tax return);
- the delivery of an intangible product (e.g. the delivery of information in the context of knowledge transmission);
- the creation of ambience for the customer (e.g. in hotels and restaurants).

Software consists of information, is generally intangible and can be in the form of approaches, transactions or **procedures** (1.159). Hardware is generally tangible and its amount is a countable **characteristic** (1.37). Processed materials are generally tangible and their amount is a continuous characteristic. Hardware and processed materials often are referred to as goods.

NOTE 3 **Quality assurance** (1.177) is mainly focused on intended product.

[ISO 9000:2005, 3.4.2]

1.163**product assurance**

discipline devoted to the study, planning and implementation of activities intended to assure that the **design** (1.75), controls, methods, and techniques in a **project** (1.167) result in a satisfactory degree of **quality** (1.176) in a **product** (1.162)

[EN 13701:2001, 3.102]

1.164**product state**

particular **configuration** (1.45) of the **product** (1.162) related to the current **configuration baseline** (1.46)

[EN 13701:2001, 3.103]

1.165**product tree**

hierarchical structure depicting the **product** (1.162) orientated breakdown of the **project** (1.167) into successive levels of detail down to the configuration items necessary to deliver the required functions

1.166

programme

group of **projects** (1.167) managed in a coordinated way to obtain benefits not available from managing them individually

[PMI Institute]

1.167

project

set of coordinated and controlled activities with start and finish dates, undertaken to achieve an objective conforming to specific **requirements** (1.190), including constraints of time, cost, and resources

NOTE 1 An individual project can form part of a larger project structure.

NOTE 2 In some projects, the objectives are refined and the product **characteristics** (1.37) defined progressively as the project proceeds.

NOTE 3 The outcome of a project may be one or several units of a **product** (1.162).

[ISO 9000:2005, 3.4.3, as adapted from ISO 10006:2003, 3.5]

1.168

project phase

part of a total **project** (1.167) during which activities are performed to attain a designated objective as one of a series of distinct steps in carrying out a project that together constitute the project **life cycle** (1.128)

1.169

project requirements document

document (1.81), including all **normative references** (1.146), that establishes **requirements** (1.190)

NOTE 1 Examples of a project requirements document include **standards** (1.215), management **specifications** (1.214), technical specifications, statements of work and data requirement lists.

NOTE 2 This does not include the **contract** (1.60) and associated terms and conditions.

Adapted from EN 13701:2001, 3.107.

1.170

provision

expression in the context of a **normative document** (1.145) that takes the form of a statement, an instruction, a recommendation or a **requirement** (1.190)

NOTE These types of provision are distinguished by the form of wording employed (e.g. instructions are expressed in the imperative mood, recommendations by the use of the auxiliary "should" and requirements by the use of the auxiliary "shall", and a choice or "permission", by "may").

[EN 45020:2004, 7.1]

1.171

purchaser

customer (1.71) in a contractual situation

NOTE The purchaser is sometimes referred to as the "business second party".

[EN 13701:2001, 3.108]

1.172

qualification

act or conduct by the **supplier** (1.219) to provide evidences to prove that design, manufacturing (including manufacturing process) of hardware/software is adequate to fulfil all **requirements** (1.190) under required environment conditions

NOTE This may be implemented by analysis, test, inspection, or demonstration.

1.173**qualification process**

process (1.160) to demonstrate the ability to fulfil specified **requirements** (1.190)

NOTE 1 The term “qualified” is used to designate the corresponding status.

NOTE 2 Qualification can concern persons, **products** (1.162), **processes** (1.160), or **systems** (1.221).

EXAMPLES Auditor qualification process, **material** (1.135) qualification process.

[ISO 9000:2005, 3.8.6]

1.174**qualification review****QR**

review that aims to

- achieve qualification of the products as well as associated production means,
- authorise the production of the recurring products

NOTE The achievement of technical qualification of the product elements is on the basis of the following documents:

- complete design justification file for the system including ground element;
- qualification reports;
- finalized user's documentation, including installation, utilisation, operations, and maintenance manuals.

1.175**qualification test**

act of qualification which includes a series of environment tests where the **component** (1.43), subsystem or system under test is subject to more strict environment than the flight predicted levels to prove its design

1.176**quality**

degree to which a set of inherent **characteristics** (1.37) fulfils **requirements** (1.190)

NOTE 1 The term “quality” can be used with adjectives such as poor, good, or excellent.

NOTE 2 “Inherent”, as opposed to “assigned”, means existing in something, especially as a permanent characteristic.

[ISO 9000:2005, 3.1.1]

1.177**quality assurance****QA**

part of quality management focused on providing confidence that quality **requirements** (1.190) are fulfilled

[ISO 9000:2005, 3.2.11]

1.178**quality characteristic**

inherent **characteristic** (1.37) of a **product** (1.162), **process** (1.160) or **system** (1.221) related to a **requirement** (1.190)

NOTE 1 “Inherent” means existing in something, especially as a permanent characteristic.

NOTE 2 A characteristic assigned to a **product** (1.162), **process** (1.160), or **system** (1.221) (e.g. the price of a product, the owner of a product) is not a **quality** (1.176) characteristic of that product, process, or system.

[ISO 9000:2005, 3.5.2]

1.179

quality control

part of quality management focused on fulfilling quality **requirements** (1.190)

[ISO 9000:2005, 3.2.10]

1.180

quality improvement

part of quality management focused on increasing the ability to fulfil quality **requirements** (1.190)

NOTE The **requirements** (1.190) can be related to any aspect, such as effectiveness, efficiency or **traceability** (1.225).

[ISO 9000:2005, 3.2.12]

1.181

quality manual

document (1.81) specifying the quality management system of an **organization** (1.150)

NOTE Quality manuals can vary in detail and format to suit the size and complexity of an individual organization.

[ISO 9000:2005, 3.7.4]

1.182

quality plan

document (1.81) specifying which **procedures** (1.159) and associated resources shall be applied by whom and when to a specific **project** (1.167), **product** (1.162), **process** (1.160) or **contract** (1.60)

NOTE 1 These procedures generally include those referring to quality management processes and to product realization processes.

NOTE 2 A quality plan often makes reference to parts of the **quality manual** (1.181) or to procedure documents.

NOTE 3 A quality plan is generally one of the results of **quality planning** (1.183).

[ISO 9000:2005, 3.7.5]

1.183

quality planning

part of quality management focused on setting quality objectives and specifying necessary operational **processes** (1.160) and related resources to fulfil the quality objectives

NOTE Establishing **quality plans** (1.182) can be part of quality planning.

[ISO 9000:2005, 3.2.9]

1.184

record

document (1.81) stating results achieved or providing evidence of activities performed

NOTE 1 Records can be used, for example, to document **traceability** (1.225) and to provide evidence of **verification** (1.229), **preventive action** (1.158), and **corrective action** (1.63).

NOTE 2 It is generally not necessary that records be under revision control.

[ISO 9000:2005, 3.7.6]

1.185

recurrent cost

costs incurred for each additional, identical **item** (1.121) produced

1.186**redundancy**

⟨design property of a system⟩ existence of more than one means for performing a **function** (1.102)

NOTE The additional means of performing the **function** (1.102) may be intentionally different (diverse) to reduce the potential for common mode **failures** (1.91).

1.187**reliability**

⟨of an item⟩ ability to perform as required under given conditions for a given time interval

NOTE 1 The “given conditions” include the provision of necessary external resources.

NOTE 2 It is usually assumed that the **item** (1.121) is in a state to perform as required at the beginning of the time interval.

NOTE 3 Reliability may be quantified using appropriate measures. Probability is one such measure.

1.188**repair**

action on a nonconforming **product** (1.162) to make it acceptable for the intended use

NOTE 1 Repair includes remedial action taken on a previously conforming product to restore it for use, for example as part of **maintenance** (1.132).

NOTE 2 Unlike **rework** (1.193), repair can affect or change **parts** (1.153) of the nonconforming product.

[ISO 9000:2005, definition 3.6.9]

1.189**request for waiver****RFW**

vehicle for requiring and agreeing to the use or the delivery of a product that does not conform to its approved product configuration baseline

1.190**requirement**

requirement or expectation that is stated, generally implied or obligatory

NOTE 1 “Generally implied” means that it is customary or common practice for the **organization** (1.150), its **customers** (1.71) and other interested parties; that the requirement or expectation under consideration is implied.

NOTE 2 A qualifier can be used to denote a specific type of requirement [e.g. **product** (1.162) requirement, quality management requirement, **customer** (1.71) requirement].

NOTE 3 A specified requirement is one that is stated, for example, in a **document** (1.81).

NOTE 4 Requirements can be generated by different interested parties.

[ISO 9000:2005, 3.1.2]

1.191**residual risk**

risk (1.194) remaining after implementation of risk reduction measures

[ISO 17666:2003, 2.1.10]

1.192**review**

activity undertaken to determine the suitability, adequacy and effectiveness of the subject matter to achieve established objectives

NOTE Review can also include the determination of efficiency.

EXAMPLES Management review, **design** (1.75) and **development** (1.78) review, review of **customer** (1.71) requirements, and **non-conformity** (1.144) review.

[ISO 9000:2005, 3.8.7]

1.193

rework

action on a nonconforming **product** (1.162) to make it conform to the **requirements** (1.190)

NOTE Unlike rework, **repair** (1.188) can affect or change **parts** (1.153) of the nonconforming product.

[ISO 9000:2005, 3.6.7]

1.194

risk

undesirable situation or circumstance that has both a likelihood of occurring and a potential negative consequence on a project

NOTE 1 Risks may be quantified by estimation of probabilities.

NOTE 2 Risks arise from uncertainty due to lack of predictability or control of events, and are inherent to any **project** (1.167), and can arise at any time during the project **life cycle** (1.128); reducing these uncertainties reduces the risk.

[ISO 17666:2003, 2.1.12]

1.195

risk assessment

process (1.160) of qualitative risk categorization and/or quantitative risk evaluation

1.196

risk management

organized, systematic decision-making process that efficiently identifies, analyses, plans, tracks, controls, communicates and documents risk and establishes mitigation approaches and plans to increase the likelihood of achieving program/project goals

[ISO 17666:2003, 2.1.5]

1.197

risk management policy

describes the organization's attitude towards risks, how it conducts risk management, the risks it is prepared to accept and defines the main **requirements** (1.190) for the risk management plan

[ISO 17666:2003, 2.1.6]

1.198

safety

system state with acceptable levels of risk for conditions that can cause death, injury, occupational illness, damage to or loss of equipment or property, or damage to the environment

NOTE The term "safety" is defined differently in ISO/IEC Guide 2 as "freedom from unacceptable risk of harm".

1.199

safety analysis

technique used to systematically evaluate and resolve hazards

1.200

safety-critical function

function (1.102) that, if lost or degraded as a result of incorrect or inadvertent operation, can result in catastrophic or critical consequences

[EN 13701:2001, 3.127]

1.201**scrap**

action on a nonconforming **product** (1.162) to preclude its originally intended use

EXAMPLES Recycling, destruction.

NOTE In a nonconforming service situation, use is precluded by discontinuing the service.

[ISO 9000:2005, 3.6.10]

1.202**security**

protection from unauthorized access or uncontrolled losses or effect

1.203**severity**

classification of a **failure** (1.91) or undesired event according to the magnitude of its possible consequences

[EN 13701:2001, 3.133]

1.204**single-point failure**

failure (1.91) of an **item** (1.121) that results in the unrecoverable **failure** (1.91) of the product

1.205**software****S/W**

programs, procedures, rules and any associated documentation pertaining to the operations of a computer system

[ISO/IEC 9126-1:2001, B.28]

1.206**software module**

smallest program unit that is discrete and identifiable with respect to compiling, combining with other units and loading

[EN 13701:2001, 3.135]

1.207**space element**

product (1.162) or a set of products intended for operation in space

Adapted from EN 13701:2001, 3.137.

1.208**space debris**

any man-made space object, including fragments and elements thereof, in Earth orbit or re-entering the Earth's atmosphere that is non-functional

NOTE Potassium-sodium alloy (NaK) and other such constituents are included in "elements".

1.209**space mission**

defined end user's requirements to be achieved by a **space system** (1.210)

1.210**space system**

system (1.221) that contains at least one **space element** (1.207)

[EN 13701:2001, 3.139]