
**Gas cylinders — Design, construction
and testing of refillable composite gas
cylinders and tubes —**

**Part 3:
Fully wrapped fibre reinforced
composite gas cylinders and tubes
up to 450 l with non-load-sharing
metallic or non-metallic liners or
without liners**

AMENDMENT 1

*Bouteilles à gaz — Conception, construction et essais des tubes et
bouteilles à gaz rechargeables en matériau composite —*

*Partie 3: Tubes et bouteilles à gaz entièrement bobinés en matériau
composite renforcés de fibres d'une contenance allant jusqu'à 450 l
avec liners non métalliques ou métalliques non structuraux, ou sans
liners*

AMENDEMENT 1





COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 3, *Cylinder design*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 11119-3:2020/Amd 1:2023

Gas cylinders — Design, construction and testing of refillable composite gas cylinders and tubes —

Part 3:

Fully wrapped fibre reinforced composite gas cylinders and tubes up to 450 l with non-load-sharing metallic or non-metallic liners or without liners

AMENDMENT 1

8.5.9.4.1

Replace the subclause with the following:

Two cylinders shall be fitted with a steel or aluminium plug with diameter no greater than the neck diameter, to protect threads and sealing surfaces.

Both cylinders shall be dropped twice, in each of the five positions shown in Figure 1, from the calculated drop height on to a smooth concrete surface or a protective steel plate of a minimum of 5 mm thickness. The drop surface shall be sufficiently flat so that the difference in level between any two points on the surface is no more than 2 mm.

The drop height, h , shall be calculated as per Formula (3):

$$h = 1,2 + (0,6 * V / m) \quad (3)$$

where

V is the water volume of the cylinder in litres;

m is the mass of the empty cylinder in kilograms.

One cylinder shall then be subjected to the burst test in 8.5.3.

The other cylinder shall be subjected to the pressure cycling test in 8.5.4.

The following parameters that shall be monitored and recorded are:

- a) visual appearance after each drop: record position and dimensions of impact damage;
- b) parameters specified in 8.5.3;
- c) parameters specified in 8.5.4.

8.5.9.4.2

Replace the subclause with the following:

First cylinder: burst pressure, p_b , shall be equal to or greater than 100 % of the minimum burst level required in the burst test (see 8.5.3).

Second cylinder: the cylinder shall satisfy the requirements of the ambient cycle test (see 8.5.4).

8.5.9.5.2, *first paragraph*

Replace the first paragraph with the following:

The cylinders shall withstand 3 000 pressurization cycles to 2/3 of the test pressure, p_h , without failure by burst or leakage. The test shall continue for a further 9 000 cycles, or until the cylinder fails by leakage, whichever is sooner. In either case, the cylinder shall be deemed to have passed the test. However, if failure during this second part of the test is by burst, then the cylinder shall have failed the test.

STANDARDSISO.COM : Click to view the full PDF of ISO 11119-3:2020/Amd 1:2023