

INTERNATIONAL STANDARD

ISO
11687-1

First edition
1995-02-01

Plain bearings — Pedestal plain bearings —

Part 1: Pillow blocks

Paliers lisses — Paliers lisses à chaise sur le sol —

Partie 1: Supports de paliers



Reference number
ISO 11687-1:1995(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 11687-1 was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 3, *Dimensions, tolerances and construction details*.

ISO 11687 consists of the following parts, under the general title *Plain bearings* — *Pedestal plain bearings*:

- Part 1: *Pillow blocks*
- Part 2: *Side flange bearings*
- Part 3: *Centre flange bearings*

© ISO 1995

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Plain bearings — Pedestal plain bearings —

Part 1: Pillow blocks

1 Scope

This part of ISO 11687 specifies design characteristics for pillow blocks for size ranges 9 to 28 and 35 to 71, as well as design characteristics for shafts.

It is applicable to pillow blocks used mainly in electrical and turbo engineering industries.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 11687. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 11687 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 185:1988, *Grey cast iron — Classification*.

ISO 426-1:1983, *Wrought copper-zinc alloys — Chemical composition and forms of wrought products — Part 1: Non-leaded and special copper-zinc alloys*.

ISO 426-2:1983, *Wrought copper-zinc alloys — Chemical composition and forms of wrought products — Part 2: Leaded copper-zinc alloys*.

ISO 630:1980, *Structural steels*.

ISO 683-11:1987, *Heat-treatable steels, alloy steels and free-cutting steels — Part 11: Wrought case-hardening steels*.

ISO 1302:1992, *Technical drawings — Method of indicating surface texture*.

ISO 2768-1:1989, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*.

ISO 2768-2:1989, *General tolerances — Part 2: Geometrical tolerances for features without individual tolerance indications*.

ISO 3755:1991, *Cast carbon steels for general engineering purposes*.

ISO 4381:1991, *Plain bearings — Lead and tin casting alloys for multilayer plain bearings*.

ISO 8062:1994, *Castings — System of dimensional tolerances and machining allowances*.

ISO 12129-1:—¹⁾, *Plain bearings — Part 1: Fits*.

ISO 12129-2:—¹⁾, *Plain bearings — Part 2: Tolerances on form and position and surface roughness for shafts, flanges and thrust collars*.

1) To be published.

3 Types of pillow block

According to their design, pillow blocks can be devised as follows, each characteristic being designated by a letter symbol.

Housing:

- G Pillow block, without cooling fins
- R Pillow block, with cooling fins

Heat dissipation:

- N Natural cooling
- W Water cooling in oil sump
- U Circulation pump and natural cooling
- T Circulation pump and water cooling in oil sump
- Z Recirculating oil lubrication with external cooling of oil

Shape of bore for journal bearing and type of lubrication:

- C Circular cylindrical bore without oil ring
- L Circular cylindrical bore with split oil ring not fixed on a rotating shaft
- Y Lobed bearing with two sliding surfaces without oil ring
- V Lobed bearing with four sliding surfaces without oil ring

Thrust bearing:

- Q Without sliding surfaces [non-locating (free) bearing]
 - B Plain sliding surfaces with oil grooves (guide bearing)
 - K Wedge surfaces
 - A Tilting pads
- (design and dimensions at the manufacturer's discretion)

Seal:

Type and dimensions subject to agreement

Figures 1 and 2 show examples of pillow blocks. These represent pillow blocks, which are ready to be installed, in the size ranges 9 to 28 and 35 to 71, respectively.

The symbols above figures 1 and 2 explain only the type illustrated; the complete type required shall be specified in the above-mentioned sequence when ordering.

For reasons of design (e.g. on account of limited space) and economy, it is only possible to construct the size range 35 to 71 with thrust bearings (A) with the dimensions given in table 3.

4 Dimensions

See figures 1 to 4 and tables 1 to 4.

The pillow blocks are not expected to conform to the designs illustrated in figures 1 and 2; compliance is only required with respect to the dimensions specified.

NOTE 1 All dimensions are given in millimetres

Details which are not specified shall be chosen as appropriate.

5 Shaft design

See figures 3 and 4 and tables 3 and 4.

6 Materials

Housing:

Grade 300 in accordance with ISO 185; other materials subject to agreement

Half-bearing:

Bearing back:

- Fe 360 B in accordance with ISO 630
- C10 or C15 E 4 in accordance with ISO 683-11
- 200 to 400 in accordance with ISO 3755

Type of material at the manufacturer's discretion

Bearing metal:

Lead-tin-alloy in accordance with ISO 4381, or subject to agreement

Seal:

Copper alloy, aluminium alloy or plastic, subject to agreement

Oil ring, not fixed on rotating shaft:

Copper-zinc alloy in accordance with ISO 426, or subject to agreement

7 Design

General tolerances:

For machined surfaces:

ISO 2768-1 and ISO 2768-2 - mH

For unmachined surfaces:

ISO 8062 - CT 9 (for grade 300), or corresponding standards for other materials agreed upon.

Surface roughness in accordance with ISO 1302:

Pillow block:

Mounted surfaces: $R_a = 3,2 \mu\text{m}$

Sliding surfaces: $R_a = 0,8 \mu\text{m}$

Shaft:

See tables 3 and 4, footnote 1.

Housing:

Pillow block housing with lifting eye bolts or means of conveyance at the manufacturer's discretion.

The inner surfaces of the housing shall be clean and shall have a coat of paint resistant to oil and solvents.

The outer surfaces of the housing shall be protected against corrosion.

For the purpose of pressure compensation, the individual oil spaces within the pillow block housing shall be connected to each other by means of appropriate openings above the oil level.

All bearing housing connections on both sides; other connecting dimensions and arrangements than those given in figures 1 and 2 as well as additional connections subject to agreement.

Type of inspection plate at the manufacturer's discretion.

With two pull-off screws at housing base at the manufacturer's discretion.

With bolts and screws for housing parts and seals, at the manufacturer's discretion.

Bolts and screws and dowel pins for the housing base do not form part of the delivery.

General:

Particular agreements shall be made for applications under special conditions (e.g. inclined positions).

Chamfered edges: type of edge chamfering at the manufacturer's discretion.


If the bearing is only applicable to one direction of rotation, a directional arrow shall be provided.

8 Designation

EXAMPLE

Designation of a pillow block of size 14, shaft diameter 125 mm, housing with cooling fins (R), for recirculating oil lubrication with external cooling of oil (Z), circular cylindrical bore with split oil ring not fixed on a rotating shaft for emergency run (L) and thrust bearing with wedge surfaces (K):

Pillow block ISO 11687-1 - 14 - 125 - RZLK

**Key**


- 1 d_5 Oil inlet (recirculating plant, circulation pump)
- 2 Thread G 1/2 Connection for thermoprobe
- 3 d_6 Oil-level indicator or oil drainage for recirculating plant
- 4 Screw plug (connection for radiator, oil-sump thermometer, suction line of circulation pump, finned cooler)

Figure 1 — Examples of pillow blocks — Size range 9 to 28

Table 1 — Pillow blocks — Size range 9 to 28 (see figure 1)

Size	9			11			14			18			22			28		
D H7 ¹⁾	80	90	100	100	110	125	125	140	160	160	180	200	200	225	250	250	280	300
B ²⁾	60			80			105			135			170			215		
b_1	80			100			125			160			200			250		
b_2	145			165			205			245			310			370		
b_3	190			205			255			300			380			450		
b_4	150			170			215			255			320			380		
d_1 (nominal dimension seal)	80			100			125			160			200			250		
	90			110			140			180			225			280		
	100			125			160			200			250			315		
	110			140			180			225			280			355		
d_2	150			180			230			275			340			440		
d_3	22 for M16			26 for M20			30 for M24			40 for M30			46 for M36			55 for M42		
d_4 ³⁾	10,4			10,4			10,4			15,5			15,5			20,6		
d_5 ⁴⁾	G 3/8			G 3/8			G 3/8			G 1/2			G 3/4			G 3/4		
d_6 ⁴⁾	G 1 1/4			G 1 1/4			G 1 1/2			G 1 1/2			G 2			G 2 1/2		
e_1	300			375			450			560			670			800		
e_2	90			100			125			150			200			250		
h_1 ⁰ ^{-0,5}	190			225			265			315			375			450		
h_2	325			380			460			565			680			830		
h_3	35			50			60			70			80			90		
l_1	355			450			540			660			800			950		
l_2	215			280			340			440			540			650		
l_3	28			30			40			50			60			85		
ϕk ⁵⁾ (spherical) h6	190			212			280			335			425			530		

- 1) Applies only to circular cylindrical bores.
- 2) For the design with thrust bearing part (A), dimensions B may slightly deviate in order to obtain (depending on the type of tilting pad) a constant dimension b_1 (interchangeability of the half-bearing shell).
- 3) Rough bore for pinned fitting.
- 4) If larger connections are necessary, this shall be the subject of a special agreement.
- 5) The fit of the half-bearing and housing shall be a transition fit or shall be subject to agreement.



Key

- 1 d_5 Oil inlet for thrust bearing part (A)
- 2 d_5 Oil inlet (recirculating plant, circulation pump)
- 3 Thread G 1/2 Connection for thermoprobe
- 4 d_6 Oil-level indicator or oil drainage for recirculating plant
- 5 Screw plug (connection for radiator, oil-sump thermometer, suction line of circulation pump, finned cooler)

Figure 2 — Examples of pillow blocks — Size range 35 to 71

Table 2 — Pillow blocks — Size range 35 to 71 (see figure 2)

Size		35					45					56					71									
D	H7 1)	300	315	335	355	375	400	375	400	425	450	475	500	475	500	530	560	600	630	670	710	750	800			
B 2)		260										325					415					530				
b ₁		300										375					475					600				
b ₂		440										530					640					780				
b ₄		460										550					660					810				
d ₁ (nominal dimension seal)		300										375					475					600				
		315										400					500					630				
		335										425					530					670				
		355										450					560					710				
		375										475					600					750				
		400										500					630					800				
		425										530					670					850				
												560					710					900				
d ₂		520										660					800					985				
d ₃		55					for M42					62					62					66				
												for M48					for M48					for M56				
d ₄ 3)		20,5										20,5					25,5					25,5				
d ₅ 4)		G 3/4										G 3/4					G 1					G 1				
d ₆ 4)		G 2 1/2										G 2 1/2					G 3					G 3				
e ₁		950										1150					1400					1800				
e ₂ 5)		—										—					150					200				
e ₃ 5)		300										355					450					560				
h ₁	⁰ −0,5	530										600					670					750				
h ₂		940										1135					1280					1515				
h ₃		95										120					130					160				
l		1 100										1 350					1 600					2 000				
φk 6) (spherical)	h6	630										800					950					1180				

1) Applies only to circular cylindrical bores.

2) For the design with thrust bearing part (A), dimension B may slightly deviate in order to obtain (depending on the type of tilting pad) a constant dimension b₁ (interchangeability of the half-bearing shell).

3) Rough bore for pinned fitting.

4) If larger connections are necessary, this shall be the subject of a special agreement.

5) Size range 35 and 45: 6 plate screws; size range 56 and 71: 8 plate screws.

6) The fit of the half-bearing and housing shall be a transition fit or shall be subject to agreement.

1) Applies only to circular cylindrical bores.

2) For the design with thrust bearing part (A), dimension *B* may slightly deviate in order to obtain (depending on the type of tilting pad) a constant dimension *b*₁ (interchangeability of the half-bearing shell).

3) Rough bore for pinned fitting.

4) If larger connections are necessary, this shall be the subject of a special agreement.

5) Size range 35 and 45: 6 plate screws; size range 56 and 71: 8 plate screws.

6) The fit of the half-bearing and housing shall be a transition fit or shall be subject to agreement.




Figure 3 — Shaft design for non-locating (free) bearing (thrust bearing part Q)




Figure 4 — Shaft design for fixed bearing (thrust bearing parts A, B and K)

Table 3 — Shaft dimensions — Size range 9 to 28 (see figures 3 and 4)

Size		9			11			14			18			22			28		
D ¹⁾		80	90	100	100	110	125	125	140	160	160	180	200	200	225	250	250	280	300
b_5 ²⁾ ± 0,1		80,4			100,4			125,4			160,4			200,4			250,4		
b_6		100			120			150			190			240			300		
b_7 ³⁾		90			110			140			180			220			280		
b_8		100			120			150			190			240			300		
b_9 ⁴⁾		5			6			8,5			10			13,5			19		
d_7 Thrust bearing parts	B, K	110	120	130	135	150	160	170	190	200	215	240	250	265	290	315	325	355	375
	A	132	142	143	157	162	168	192	207	217	244	264	273	308	328	339	378	408	408
$d_8 ; d_9$ ⁴⁾ e8		d_8 d_9		d_8 d_9		d_8 d_9		d_8 d_9		d_8 d_9		d_8 d_9		d_8 d_9		d_8 d_9			
		80 80		100 100		125 125		160 160		200 200		250 250							
		90 80		110 100		140 125		180 160		225 200		280 250							
		100 90		125 110		160 140		200 180		250 225		315 280							
		110 100		140 125		180 160		225 200		280 250		355 315							
d_{10}		90	100	110	110	125	140	140	160	180	180	200	225	225	250	280	280	315	315
r_1 ⁵⁾		2,5			2,5			4			4			6			6		
r_2 ⁵⁾		4			4			6			6			10			10		

1) Limit deviations for shafts and tolerances of form and position and surface roughness in accordance with ISO 12129-1 and ISO 12129-2.

2) Normal axial clearance of 0,5 mm is provided for size range 9 to 28 and 0,6 mm for size range 35 to 71. If a change in direction of the axial loads or axial thrusts is to be expected, dimension b_5 may be reduced by 0,2 mm for size range 9 to 28 and by 0,3 mm for size range 35 to 71. If a fixed bearing (thrust bearing parts B, K) is only needed for the test run, dimension b_5 may be increased.

3) If the non-locating (free) bearing (thrust bearing part Q) has to allow major axial movements (e.g. due to thermal expansion or large constitutional axial clearance), dimension b_7 may be increased.

4) The clearance groove d_9 may be omitted if it is equal to or smaller than the shaft diameter D .

5) The radii r_1 and r_2 may be replaced by an undercut.

Table 4 — Shaft dimensions — Size range 35 to 71 (see figures 3 and 4)

Size		35						45						56						71					
D 1)		300	315	335	355	375	400	375	400	425	450	475	500	475	500	530	560	600	630	600	630	670	710	750	800
b ₅ 2)	± 0,1	300,5						375,5						475,5						600,5					
b ₆		360						445						555						690					
b ₇ 3)		315						400						500						630					
b ₈		335						425						530						670					
b ₉ 4)		10						13						16						20					
Thrust bearing parts	B, K A	385 455	400 470	425 490	450 510	470 510	495 —	480 570	505 595	530 620	555 645	580 —	605 —	590 715	615 740	645 770	675 755	715 —	745 —	725 895	755 925	795 965	835 955	875 —	925 —
d ₈ ; d ₉ 4) e8		300 315 335 355 375 400 425	300 300 315 335 355 375 400	300 300 315 335 355 375 400	300 300 315 335 355 375 400	300 300 315 335 355 375 400	375 400 425 450 475 500 530 560	375 400 425 450 475 500 530 560	375 400 425 450 475 500 530 560	375 400 425 450 475 500 530 560	375 400 425 450 475 500 530 560	375 400 425 450 475 500 530 560	375 400 425 450 475 500 530 560	475 500 530 560 600 630 670 710	475 500 530 560 600 630 670 710	475 500 530 560 600 630 670 710	475 500 530 560 600 630 670 710	475 500 530 560 600 630 670 710	600 630 670 710 750 800 850 900	600 630 670 710 750 800 850 900	600 630 670 710 750 800 850 900	600 630 670 710 750 800 850 900	600 630 670 710 750 800 850 900		
d ₁₀		335	355	375	400	425	450	425	450	475	500	530	560	530	560	600	630	670	710	670	710	750	800	850	900
r ₁ 5)		8						10						10						10					
r ₂ 5)		12						16						16						16					

1) Limit deviations for shafts and tolerances of form and position and surface roughness in accordance with ISO 12129-1 and ISO 12129-2.

2) Normal axial clearance of 0,5 mm is provided for size range 9 to 28 and 0,6 mm for size range 35 to 71. If a change in direction of the axial loads or axial thrusts is to be expected, dimension b₅ may be reduced by 0,2 mm for size range 9 to 28 and by 0,3 mm for size range 35 to 71. If a fixed bearing (thrust bearing part B, K) is only needed for the test run, dimension b₅ may be increased.

3) If the non-locating (free) bearing (thrust bearing part Q) has to allow major axial movements (e.g. due to thermal expansion or large constitutional axial clearance), dimension b₇ may be increased.

4) The clearance groove d₉ may be omitted if it is equal to or smaller than the shaft diameter D.

5) The radii r₁ and r₂ may be replaced by an undercut.

1) Limit deviations for shafts and tolerances of form and position and surface roughness in accordance with ISO 12129-1 and ISO 12129-2.

2) Normal axial clearance of 0,5 mm is provided for size range 9 to 28 and 0,6 mm for size range 35 to 71. If a change in direction of the axial loads or axial thrusts is to be expected, dimension b_5 may be reduced by 0,2 mm for size range 9 to 28 and by 0,3 mm for size range 35 to 71. If a fixed bearing (thrust bearing part B, K) is only needed for the test run, dimension b_5 may be increased.

3) If the non-locating (free) bearing (thrust bearing part Q) has to allow major axial movements (e.g. due to thermal expansion or large constitutional axial clearance), dimension b_7 may be increased.

4) The clearance groove d_9 may be omitted if it is equal to or smaller than the shaft diameter D .

5) The radii r_1 and r_2 may be replaced by an undercut.