

Fourth edition
2009-07-01

AMENDMENT 1
2016-04-15

Displacement compressors — Acceptance tests

AMENDMENT 1: Calculation of isentropic efficiency and relationship with specific energy

Compresseurs volumétriques — Essais de réception

*AMENDEMENT 1: Calcul du rendement isentropique et relation avec
l'énergie spécifique*



Reference number
ISO 1217:2009/Amd.1:2016(E)

© ISO 2016

STANDARDSISO.COM : Click to view the full PDF of ISO 1217:2009/Amd 1:2016



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

Amendment 1 to ISO 1217:2009 was prepared by Technical Committee ISO/TC 118, *Compressors and pneumatic tools, machines and equipment*, Subcommittee SC 6, *Air compressors and compressed air systems*.

STANDARDSISO.COM : Click to view the full PDF of ISO 1217:2009/Amd 1:2016

Displacement compressors — Acceptance tests

AMENDMENT 1: Calculation of isentropic efficiency and relationship with specific energy

Page 6, 3.5.1

Replace the term and definition with the following:

isentropic power

power that is theoretically required to compress an ideal gas under constant entropy, from given inlet conditions to a given discharge pressure

Note 1 to entry The term “ideal gas” is used to indicate any gas in a condition or state so that it follows closely the ideal gas law.

Page 6, 3.6.1

Replace the term and definition with the following:

isentropic efficiency

ratio of the required isentropic power to measured power for the same specified boundaries with the same gas and the same inlet conditions and outlet pressure

$$\eta_{\text{isen}} = \frac{P_{\text{isen}}}{P_{\text{real}}}$$

Note 1 to entry Examples of specified boundaries may be shaft power of bare compressor or motor power of the package including inlet and discharge losses or total input power of the package.

Note 2 to entry In many turbo compressor textbooks, the adiabatic stage gas power $P_i = \Delta h \cdot q_m = (h_2 - h_1) \cdot q_m$

is taken as P_{real} . Isentropic efficiency is then defined as $\eta_{\text{isen}} = \frac{P_{\text{isen}}}{\Delta h \cdot q_m} = \frac{\Delta h_{\text{isen}}}{\Delta h}$. In this special case, the most

narrow boundaries are used which are enclosing only the gas volume. In this sense, it corresponds with the formula for isentropic efficiency given in ISO 5389:2005, Formula (E.101).

Add a new Annex H as follows.

Annex H (informative)

Isentropic efficiency and its relation to specific energy requirement

H.1 General

This annex provides general derivation of isentropic power and calculations for the relationship between isentropic efficiency as defined in this annex and specific energy requirement in accordance with this International Standard.

No additional data or measurements are required for the calculation of isentropic power and isentropic efficiency.

This annex also provides calculations for the relative tolerances between specific power and isentropic efficiency.

H.2 Symbols and subscripts

Table H.1 — Symbols

Symbol	Term	SI unit	Other practical units
c_p	specific heat at constant pressure	J/(kg·K)	—
h	specific enthalpy	J/kg	kJ/kg
Δh	specific enthalpy difference	J/kg	kJ/kg
P	power	W	MW, kW
p	pressure	Pa	MPa, bar, mbar
Δp	pressure difference	Pa	MPa, bar, mbar
R	gas constant	J/(kg·K)	
T	absolute temperature	K	
q_m	mass rate of flow	kg/s	kg/h
q_v	volume flow rate	m ³ /s	m ³ /h, m ³ /min, L/s
K	isentropic exponent (ratio of specific heats)		min ⁻¹
L	lower limit		
η	efficiency		
ρ	density	kg/m ³	
U	upper limit		

Table H.2 — Subscripts

Subscript	Term	Remark
isen	isentropic	
η	efficiency	
m	mass	Characterizes the mass-specific rates of flow, energies and volumes
P	power	
real	real	

Table H.2 (continued)

Subscript	Term	Remark
spec	specific	
V	volume	Characterizes the volume-specific rates of flow and energy
1,2	states	

H.3 Derivation of isentropic power

The power required for isentropic compression can be derived from basic relationships:

$$P_{\text{isen}} = \Delta h_{\text{isen}} \cdot q_m \quad \text{with} \quad q_m = q_V \cdot \rho = \frac{p_1}{RT_1} \quad (\text{ideal gas}) \quad (\text{H.1})$$

Isentropic enthalpy difference:

$$\Delta h_{\text{isen}} = c_p \cdot [T_{2,\text{isen}} - T_1] \quad (\text{ideal gas}) \quad (\text{H.2})$$

with

$$c_p = R \cdot \frac{K}{(K-1)} \quad (\text{H.3})$$

follows:

$$\Delta h_{\text{isen}} = \frac{K}{K-1} RT_1 \cdot \left[\frac{T_{2,\text{isen}}}{T_1} - 1 \right] \quad (\text{H.4})$$

With the isentropic relation $\frac{T_{2,\text{isen}}}{T_1} = \left(\frac{p_2}{p_1} \right)^{\frac{K-1}{K}}$ follows

$$\Delta h_{\text{isen}} = \frac{K}{K-1} RT_1 \cdot \left[\left(\frac{p_2}{p_1} \right)^{\frac{K-1}{K}} - 1 \right] \quad (\text{H.5})$$

and for the power required for isentropic compression:

$$\begin{aligned} P_{\text{isen}} &= q_m \Delta h_{\text{isen}} = q_{V1} \cdot \frac{p_1}{RT_1} \Delta h_{\text{isen}} \\ P_{\text{isen}} &= q_{V1} \cdot \frac{p_1}{RT_1} \frac{K}{K-1} RT_1 \cdot \left[\left(\frac{p_2}{p_1} \right)^{\frac{K-1}{K}} - 1 \right] \\ P_{\text{isen}} &= q_{V1} \cdot p_1 \frac{K}{K-1} \cdot \left[\left(\frac{p_2}{p_1} \right)^{\frac{K-1}{K}} - 1 \right] \end{aligned} \quad (\text{H.6})$$

which is the most widely used version of the formula for isentropic power.

The formulae above show that no additional data have to be measured for the calculation of isentropic power and isentropic efficiency.

Where performance guarantee values are to be determined, then the correction factors to be applied shall be done in accordance with C.4.

H.4 Relationship between isentropic efficiency and specific energy requirement

“Specific energy requirement” (SER) or more precisely “specific power requirement” is defined as

$$P_{\text{spec}} = \frac{P_{\text{real}}}{q_{V1}} \quad (\text{H.7})$$

The relation of “isentropic efficiency” to “specific power requirement” can be derived using

$$\frac{1}{\eta_{\text{isen}}} = \frac{P_{\text{real}}}{P_{\text{isen}}} \text{ and } P_{\text{isen}} = q_{V1} \cdot p_1 \frac{K}{K-1} \cdot \left[\left(\frac{p_2}{p_1} \right)^{\frac{K-1}{K}} - 1 \right] \quad (\text{H.8})$$

to build

$$\frac{1}{\eta_{\text{isen}}} = \frac{\left(\frac{P_{\text{real}}}{q_{V1}} \right)}{P_{\text{spec}}} \cdot \frac{1}{p_1 \frac{K}{K-1} \cdot \left[\left(\frac{p_2}{p_1} \right)^{\frac{K-1}{K}} - 1 \right]} \quad (\text{H.9})$$

$$\frac{1}{\eta_{\text{isen}}} = P_{\text{spec}} \cdot \frac{1}{p_1 \frac{K}{K-1} \cdot \left[\left(\frac{p_2}{p_1} \right)^{\frac{K-1}{K}} - 1 \right]} \quad (\text{H.10})$$

or alternatively

$$\eta_{\text{isen}} = \frac{1}{P_{\text{spec}}} \cdot p_1 \frac{K}{K-1} \cdot \left[\left(\frac{p_2}{p_1} \right)^{\frac{K-1}{K}} - 1 \right] \quad (\text{H.11})$$

Therefore, if the operating conditions are known, the calculation of isentropic efficiency from specific energy requirement and vice versa is unambiguous.

H.5 Tolerances

As isentropic efficiency can be calculated from specific power requirement without additional data to be measured and vice versa (see above), their relative tolerances are directly related as well. As isentropic efficiency is proportional to the reciprocal of specific power requirement [see Formulae (H.9) or (H.10)], the algebraic signs of the tolerance values change and the values have to be converted.

Let P_{spec} have a lower limit L_P and an upper limit U_P , both given as relative values in percentage.