

---

---

**Plastics pipes and fittings — Equipment  
for fusion jointing polyethylene  
systems —**

**Part 3:  
Operator's badge**

*Tubes et raccords en matières plastiques — Appareillage pour  
l'assemblage par soudage des systèmes en polyéthylène —*

*Partie 3: Carte d'identification de l'opérateur*



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 12176-3:2006

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

|                                                                                |    |
|--------------------------------------------------------------------------------|----|
| Foreword.....                                                                  | iv |
| 1 Scope .....                                                                  | 1  |
| 2 Normative references .....                                                   | 1  |
| 3 Terms and definitions .....                                                  | 2  |
| 4 Data carrier .....                                                           | 2  |
| 5 Encoding of data.....                                                        | 3  |
| 5.1 General.....                                                               | 3  |
| 5.2 Encoding of characters.....                                                | 3  |
| 5.3 Language codes.....                                                        | 4  |
| 5.4 Code structure .....                                                       | 4  |
| 5.5 Checksum and identifier (only for bar codes) .....                         | 6  |
| 5.6 Examples of codes .....                                                    | 6  |
| Annex A (normative) Interactive interface with fusion-jointing equipment ..... | 7  |
| Bibliography .....                                                             | 8  |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12176-3 was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 4, *Plastics pipes and fittings for the supply of gaseous fuels*.

This second edition cancels and replaces the first edition (ISO 12176-3:2001), which has been technically revised.

ISO 12176 consists of the following parts, under the general title *Plastics pipes and fittings — Equipment for fusion jointing polyethylene systems*:

- *Part 1: Butt fusion*
- *Part 2: Electrofusion*
- *Part 3: Operator's badge*
- *Part 4: Traceability coding*

# Plastics pipes and fittings — Equipment for fusion jointing polyethylene systems —

## Part 3: Operator's badge

### 1 Scope

This part of ISO 12176 describes the format and the contents of a fusion operator's badge, which is used during the construction of polyethylene (PE) piping systems for the supply of gaseous fuels or water to identify the fusion operator and to activate or deactivate the fusion-jointing equipment.

The objective of this part of ISO 12176 is to achieve international interoperability between the operator's badge and the card-reading equipment of fusion-jointing equipment conforming to ISO 12176-1 or ISO 12176-2. The fusion-jointing equipment is required to read either the bar code or the magnetic-stripe code of the badge and to call up the corresponding data within the equipment in a standard format.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3166-1, *Codes for the representation of names of countries and their subdivisions — Part 1: Country codes*

ISO/IEC 7810, *Identification cards — Physical characteristics*

ISO/IEC 7811-2:2001, *Identification cards — Recording technique — Part 2: Magnetic stripe — Low coercivity*

ISO/IEC 7811-6:2001, *Identification cards — Recording technique — Part 6: Magnetic stripe — High coercivity*

ISO/IEC 16390, *Information technology — Automatic identification and data capture techniques — Bar code symbology specifications — Interleaved 2 of 5*

### 3 Terms and definitions

For the purposes of this part of ISO 12176, the following terms and definitions apply.

#### 3.1

##### **fusion operator**

person trained to carry out fusion jointing between polyethylene (PE) pipes and/or fittings based on a written procedure agreed by the pipeline operator

**NOTE** The fusion operator is trained for one or more fusion-jointing procedures, involving the operation of manual and/or automatic fusion-jointing machines.

#### 3.2

##### **competent organization**

company authorized by the national authorities or by the pipeline operator to organize training courses for fusion operators and to issue fusion operators' badges

#### 3.3

##### **digit**

whole number from zero to nine

#### 3.4

##### **character**

whole number from zero to nine or letter or other symbol

**NOTE** Letters and other symbols are represented by a two-digit number as indicated in Table 2.

### 4 Data carrier

The fusion operator's badge shall be designed in the form of a bar code card or a magnetic-stripe card.

In the case of a bar code card, the code shall be the "2 of 5 interleaved" type conforming to ISO/IEC 16390.

In the case of a magnetic card, the card shall conform to the requirements for ID-1 given in ISO/IEC 7810. The characteristics of the magnetic stripe shall conform to the International Standards given in Table 1, depending on stripe coercivity. The data shall be stored on track 1.

The card shall not contain physically embossed characters.

**Table 1 — Magnetic-stripe characteristics**

| Attribute                                                                         | Low coercivity | High coercivity |
|-----------------------------------------------------------------------------------|----------------|-----------------|
| Stripe properties and encoding method                                             | ISO/IEC 7811-2 | ISO/IEC 7811-6  |
| Track location and dimensions                                                     | ISO/IEC 7811-2 | ISO/IEC 7811-6  |
| <b>NOTE</b> The use of high coercivity is recommended, for reasons of durability. |                |                 |

Both bar code and magnetic-stripe cards shall contain the same data.

## 5 Encoding of data

### 5.1 General

Whatever the type of badge, all data stored on the badge shall be arranged in a single sequential series representing a unique code.

The only difference between the magnetic-card and bar code systems is that the magnetic-card code starts with an identifier, whereas the bar code uses an entrance code and has the identifier at the end.

### 5.2 Encoding of characters

For encoding a bar code card, all characters shall be taken from the ASCII series unless otherwise specified. The codes actually used, which are obtained by subtracting 32 from the ASCII code, are given in Table 2.

**Table 2 — Codes used for basic characters**

| Codes used for basic characters (ASCII code minus 32) |        |        |        |              |        |
|-------------------------------------------------------|--------|--------|--------|--------------|--------|
| 0 = 16                                                | 3 = 19 | 6 = 22 | 9 = 25 | "space" = 00 |        |
| 1 = 17                                                | 4 = 20 | 7 = 23 |        | * = 10       |        |
| 2 = 18                                                | 5 = 21 | 8 = 24 |        | ; = 27       |        |
| A = 33                                                | F = 38 | K = 43 | P = 48 | U = 53       | Z = 58 |
| B = 34                                                | G = 39 | L = 44 | Q = 49 | V = 54       |        |
| C = 35                                                | H = 40 | M = 45 | R = 50 | W = 55       |        |
| D = 36                                                | I = 41 | N = 46 | S = 51 | X = 56       |        |
| E = 37                                                | J = 42 | O = 47 | T = 52 | Y = 57       |        |

NOTE The codes from 65 up to and including 90 may be used at a later stage for lower-case letters (a to z), if necessary.

For encoding a magnetic card, the seven-bit ASCII coded character set shall be used rather than the six-bit coded character set specified in Table 4 of ISO/IEC 7811-2:2001 and ISO/IEC 7811-6:2001.

For the code on a magnetic stripe, a separator shall be used as the identifier and to separate fields.

The character “; = 27” shall not be used in bar codes as it is used as the separator on magnetic stripes. Bar codes do not need separators.

### 5.3 Language codes

The language code shall be taken from Table 3.

**Table 3 — Language codes**

| Code                                                                                                                                    | Language     | Code | Language  |
|-----------------------------------------------------------------------------------------------------------------------------------------|--------------|------|-----------|
| 01                                                                                                                                      | English      | 15   | Polish    |
| 02                                                                                                                                      | French       | 16   | Hungarian |
| 03                                                                                                                                      | Spanish      | 17   | Bulgarian |
| 04                                                                                                                                      | German       | 18   | Romanian  |
| 05                                                                                                                                      | Italian      | 19   | Chinese   |
| 06                                                                                                                                      | Portuguese   | 20   | Russian   |
| 07                                                                                                                                      | Dutch        | 21   | Japanese  |
| 08                                                                                                                                      | Danish       | 22   | Korean    |
| 09                                                                                                                                      | Norwegian    | 23   | Arabic    |
| 10                                                                                                                                      | Swedish      | 24   | Hebrew    |
| 11                                                                                                                                      | Finnish      | 25   | Croatian  |
| 12                                                                                                                                      | Greek        | 26   | Slovenian |
| 13                                                                                                                                      | Turkish      | 27   | Catalan   |
| 14                                                                                                                                      | Czech/Slovak |      |           |
| NOTE If there is a need for other languages, additional language codes will be included at the next revision of this part of ISO 12176. |              |      |           |

### 5.4 Code structure

The operator's badge shall have an entrance code or identifier followed by a series of data fields. All fields shall be completely filled with the relevant coding; when no data are available or no check is required, the field shall be completed with the necessary number of "0" (zero) digits.

In the set of codes for the operator's skills, two codes (64 and 128) shall be left unused for further updating of this part of ISO 12176. These unused codes shall not be used for any other purpose.

The number of characters given in Table 4 shall be considered as fixed; this means that the code structure cannot be shortened. Empty spaces in a field shall be filled with zeros in front (i.e. on the left-hand side) of the characters already in the field.

Table 4 — Code structure

| Field                   | Information                                                                                                                                                                                                                                                                                                                             | Code                                                                    |                                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
|                         |                                                                                                                                                                                                                                                                                                                                         | Magnetic card                                                           | Bar code                                                                                              |
| Identifier              | Code indicating that the information concerns an operator's badge                                                                                                                                                                                                                                                                       | Z2,MSA,<br>(at start of code)                                           | One single-digit numeric character, Z<br>Content = checksum + 2 <sup>a</sup><br>(at end of code)      |
| Entrance code           | Code indicating the number of digits used in the next field to identify the operator (for bar codes only)                                                                                                                                                                                                                               |                                                                         | One single-digit numeric character, N<br>Maximum value 6                                              |
| Operator's badge number | Operator's personal identification code                                                                                                                                                                                                                                                                                                 | Six alphanumeric characters, AAAAAA;                                    | Twelve numeric digits representing six alphanumeric characters, AAAAAAAAAA<br>(ASCII figure minus 32) |
| Expiry date             | Expiry date of badge (month and year)                                                                                                                                                                                                                                                                                                   | Two two-digit numeric characters with a separator in the middle, BB;BB; | Two two-digit numeric characters, BBBB                                                                |
| Country                 | Country where badge was issued (country code in accordance with ISO 3166-1)                                                                                                                                                                                                                                                             | One three-digit numeric character, CCC;                                 | One three-digit numeric character, CCC                                                                |
| Competent organization  | Organization that issued the batch (codes to be defined at national level)                                                                                                                                                                                                                                                              | Two alphanumeric characters, DD;                                        | Four numeric digits representing two alphanumeric characters, DDDD<br>(ASCII figure minus 32)         |
| Skills                  | List of authorized tasks (one or more can be indicated by adding the applicable code-numbers together):<br>1: Electrofusion, manual<br>2: Electrofusion, automatic<br>4: Butt fusion, manual<br>8: Butt fusion, automatic<br>16: Socket/saddle fusion<br>32: Induction fusion<br>64: See 5.4<br>128: See 5.4<br>256: Responsible person | Three numeric characters, EEE;                                          | Three numeric characters, EEE                                                                         |
| Language                | Language of operator (language code in accordance with Table 3) (determines language of display on control unit)                                                                                                                                                                                                                        | One two-digit numeric character, FF                                     | One two-digit numeric character, FF                                                                   |

<sup>a</sup> See 5.5 for the calculation of the checksum.

## 5.5 Checksum and identifier (only for bar codes)

The value of the checksum (control character) shall be calculated as follows:

- 1) Addition of the numerical values of the odd positions in the message read from left to right, followed by multiplication of the total thus obtained by a factor of 3;
- 2) Addition of the numerical values of the even positions in the message read from left to right;
- 3) Addition of the odd and even totals of stages 1 and 2;
- 4) Determination of the checksum, i.e. the smallest figure which, when added to the total obtained in stage 3, gives a multiple of 10.

The value of the identifier shall be calculated by adding 2 to the checksum determined in stage 4. If this value is 10 or higher, then subtract 10 from it. This digit is placed in the 30th position of the bar code when read from left to right.

## 5.6 Examples of codes

An example of a bar code is given in Table 5.

**Table 5 — Example of a bar code**

| Structure               | NAAAAAAAAAAAAABBBBCCCDDEEEFFZ<br>Encoding: 2 of 5 interleaved |                                             |
|-------------------------|---------------------------------------------------------------|---------------------------------------------|
| Example                 | 300000041424312017564039002030                                |                                             |
| Entrance code           | 3                                                             | Number of characters used in the next field |
| Operator's badge number | 000000414243 (ASCII figure minus 32)                          | IJK                                         |
| Expiry date             | 1201                                                          | December 2001                               |
| Country                 | 756                                                           | Switzerland                                 |
| Competent organization  | 4039 (ASCII figure minus 32)                                  | HG                                          |
| Skill                   | 002                                                           | Electrofusion jointing, automatic           |
| Language                | 03                                                            | Spanish                                     |
| Identifier              | 0                                                             | Checksum + 2                                |

An example of a code on a magnetic card is given in Table 6.

**Table 6 — Example of a magnetic-card code**

| Structure               | Z2,MSA,AAAAAA;BB;BB;CCC;DD;EEE;FF |                                   |
|-------------------------|-----------------------------------|-----------------------------------|
| Example                 | Z2,MSA,IJKLMN;12;01;756;HG;002;03 |                                   |
| Identifier              | Z2,MSA                            | In accordance with ISO 13950      |
| Operator's badge number | IJKLMN                            | IJK LMN                           |
| Expiry date             | 12;01                             | December 2001                     |
| Country                 | 756                               | Switzerland                       |
| Competent organization  | HG                                | HG                                |
| Skill                   | 002                               | Electrofusion jointing, automatic |
| Language                | 03                                | Spanish                           |

## Annex A (normative)

### Interactive interface with fusion-jointing equipment

**A.1** The fusion-jointing equipment shall be activated by a software programme adaptable to the purchaser's requirements. The programme shall react to data stored in the operator's badge in a predefined way, as follows:

- activation of fusion-jointing equipment;
- activation of language programme;
- storage in memory;
- verification of data;
- blocking of machine;
- setting of alarm (audio or visual);
- filling in fusion-jointing report.

**A.2** If a field contains only zeros, no validation check is necessary for that field; if a field that implements an action contains only zeros, the programme shall identify it with a special sign (which shall be different from the sign for a field indicating that the badge is invalid, because it is beyond the expiry date for instance).

**Identifier:** For activation of the fusion-jointing machine.

**Entrance code:** Information for decoding the bar code.

**Operator:** Stored in the memory of the fusion-jointing machine.

**Date:** Verified and acted on.

**Country:** Stored in the memory of the fusion-jointing machine.

**Organization:** Stored in the memory of the fusion-jointing machine.

**Skill:** Verified and acted on.

**Language:** Determines the language used on the display of the control unit (if the language requested by the badge is not available in the machine, the most recently used language shall remain active).