
Aerospace — Bolts, reduced bihexagonal head, normal or pitch diameter shank, long length MJ threads, metallic material, coated or uncoated, strength classes less than or equal to 1 275 MPa — Dimensions

Aéronautique et espace — Vis à tête bihexagonale réduite, à tige normale ou de diamètre égal au diamètre sur flancs et filetage MJ long, en matériau métallique, revêtues ou non revêtues, des classes de résistance inférieures ou égales à 1 275 MPa — Dimensions



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 12258 was prepared by Technical Committee ISO/TC 20, *Air craft and space vehicles*, Subcommittee SC 4, *Aerospace fastener systems*.

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case postale 56 • CH-1211 Genève 20 • Switzerland
Internet iso@iso.ch

Printed in Switzerland

Aerospace — Bolts, reduced bihexagonal head, normal or pitch diameter shank, long length MJ threads, metallic material, coated or uncoated, strength classes less than or equal to 1 275 MPa — Dimensions

1 Scope

This International Standard specifies the dimensions of reduced bihexagonal head bolts, with normal or pitch diameter shank and long length MJ threads, in metallic material, coated or uncoated, of strength classes less than or equal to 1 275 MPa.

This International Standard is applicable for the compilation of aerospace product standards.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 3353:1992, *Aerospace — Rolled threads for bolts — Lead and runout requirements.*

ISO 4095:1998, *Aerospace — Bi-hexagonal drives — Wrenching configuration — Metric series.*

ISO 5855-2:1988, *Aerospace — MJ threads — Part 2: Limit dimensions for bolts and nuts.*


ISO 7913:1994, *Aerospace — Bolts and screws, metric — Tolerances of form and position.*

3 Configuration and dimensions

See figure 1 and table 1. Dimensions and tolerances are expressed in millimetres. They are applicable after any surface coating, but before the application of any lubricant.

Tolerances of form and position are specified in ISO 7913.

Break sharp edges 0,1 to 0,4



1) Rounded or chamfered

Figure 1

Table 1

Diameter code	Thread ¹⁾	D_1				D_2	D_3	D_4	D_5	D_6	E
		Normal		Pitch diameter		min.	$+ \begin{smallmatrix} 0,5 \\ 0 \end{smallmatrix}$	$\pm 0,5$	min.	max.	h15
050	MJ5 $\times$ 0,8 – 4h6h	5	h12	4,48	$\pm 0,13$	6,8	3,2	3,4	8,3	9,1	5,5
060	MJ6 $\times$ 1 – 4h6h	6		5,35		7,8	4,1	4,2	9,8	10,6	6
070	MJ7 $\times$ 1 – 4h6h	7		6,35		8,8	4,9	5,2	11,3	12,1	6,5
080	MJ8 $\times$ 1 – 4h6h	8		7,35		9,8	5,2	6,2	12,8	13,6	7
100	MJ10 $\times$ 1,25 – 4h6h	10		9,19		11,8	6,7	7,9	15,7	16,7	8
120	MJ12 $\times$ 1,25 – 4h6h	12		11,19		13,7	8	9,8	18,8	19,9	9,2
Diameter code	F $+ \begin{smallmatrix} 0,4 \\ 0 \end{smallmatrix}$	G min.	H min.	L_1 ^{2) 3) 4)} min.	L_2 ^{2) 3) 4)} max.	L_3	L_4 ³⁾ $\pm 0,3$	R nom. tol.		Wrenching dash number ⁵⁾	
050	2,5	2	1	0,5	4	16	20 to 70	0,5	0 $-0,2$	07	
060	2,8	2,3	1,2	0,7		18	22 to 84	0,7		08	
070	3,3	2,6	1,4			20	24 to 98			09	
080	3,7	2,8	1,6			22	26 to 112			10	
100	4,7	3,1	2	0,8	6	26	32 to 140	0,8		12	
120	5,6	3,5	2,4	0,9		30	36 to 168	0,9	0 $-0,3$	14	

1) In accordance with ISO 5855-2.

2) First length corresponding to first L_4 length.3) In order to provide a manufacturing tolerance, the distance L_2 max. – L_1 min. will be greater than the thread runout length specified in ISO 3353.

4) Increments:

2 for $L_4 \leq 100$ 4 for $L_4 > 100$

If greater lengths are necessary, they shall be chosen using these increments.

5) In accordance with ISO 4095 over G min.