
**Road vehicles — Compressed gaseous
hydrogen (CGH₂) and hydrogen/
natural gas blend fuel system
components —**

**Part 1:
General requirements and definitions**

*Véhicules routiers — Composants des circuits d'alimentation pour
hydrogène gazeux comprimé (CGH₂) et mélanges de gaz naturel et
hydrogène.*

Partie 1: Exigences générales et définitions



STANDARDSISO.COM : Click to view the full PDF of ISO 12619-1:2014



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Construction and assembly	4
5 Electrical equipment and wiring	5
6 Instructions	5
7 Marking	6
Bibliography	8

STANDARDSISO.COM : Click to view the full PDF of ISO 12619-1:2014

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 25, *Vehicles using gaseous fuels*.

ISO 12619 consists of the following parts, under the general title *Road vehicles — Compressed gaseous hydrogen (CGH₂) and hydrogen/natural gas blends fuel system components*:

- *Part 1: General requirements and definitions*
- *Part 2: Performance and general test methods*
- *Part 3: Pressure regulator*

Road vehicles — Compressed gaseous hydrogen (CGH₂) and hydrogen/natural gas blend fuel system components —

Part 1: General requirements and definitions

1 Scope

This part of ISO 12619 specifies general requirements and definitions of compressed gaseous hydrogen (CGH₂) and hydrogen/natural gas blends fuel system components, intended for use on the types of motor vehicles defined in ISO 3833. It also provides general design principles and specifies requirements for instructions and markings.

This part of ISO 12619 is applicable to vehicles using CGH₂ in accordance with ISO 14687-1 or ISO 14687-2 and hydrogen/natural gas blends using natural gas in accordance with ISO 15403-1 and ISO/TR 15403-2. It is not applicable to the following:

- liquefied hydrogen (LH₂) fuel system components;
- fuel containers;
- stationary gas engines;
- container mounting hardware;
- electronic fuel management;
- refuelling receptacles.

NOTE 1 It is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this part of ISO 12619 and tested according to the appropriate functional tests.

NOTE 2 All references to pressure in this part of ISO 12619 are to be considered gauge pressures unless otherwise specified.

NOTE 3 This part of ISO 12619 may not apply to fuel cell vehicles in compliance with international regulations.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6722-1, *Road vehicles — 60 V and 600 V single-core cables — Part 1: Dimensions, test methods and requirements for copper conductor cables*

ISO 6722-2, *Road vehicles — 60 V and 600 V single-core cables — Part 2: Dimensions, test methods and requirements for aluminium conductor cables*

ISO 12619-2, *Road vehicles — Compressed gaseous hydrogen (CGH₂) and hydrogen/natural gas blend fuel system components — Part 2: Performance and general test methods*

ISO 14687-1, *Hydrogen fuel — Product specification — Part 1: All applications except proton exchange membrane (PEM) fuel cell for road vehicles*

ISO 14687-2, *Hydrogen fuel — Product specification — Part 2: Proton exchange membrane (PEM) fuel cell applications for road vehicles*

ISO 15403-1, *Natural gas — Natural gas for use as a compressed fuel for vehicles — Part 1: Designation of the quality*

ISO/TR 15403-2, *Natural gas — Natural gas for use as a compressed fuel for vehicles — Part 2: Specification of the quality*

ISO 16380¹⁾, *Road vehicles — Blended fuels refuelling connector*

ISO 17268, *Gaseous hydrogen land vehicle refuelling connection devices*

3 Terms and definitions

3.1

agent

person or organization responsible for holding the compliance certificate

3.2

burst pressure

pressure which causes structural failure of the component and consequential inability of the component to retain hydrogen or hydrogen/natural gas blends

3.3

compressed gaseous hydrogen

CGH2

gaseous hydrogen which has been compressed and stored for use as a vehicle fuel

3.4

filter

component that is intended to remove contaminants from the gas stream

3.5

flexible fuel line

flexible tubing or hose through which gaseous hydrogen or hydrogen/natural gas blend flows

3.6

fitting

connector used in joining a piping, tubing, or hose system

3.7

fuel cell gas injector

device used for introducing gas into the fuel cell

3.8

gas air mixer

device for mixing the gaseous fuel and intake air for the engine

3.9

gas flow adjuster

gas flow restricting device that is installed downstream of a pressure regulator for controlling gas

3.10

gas injector

device for introducing gaseous fuel into the engine or associated intake system

1) To be published.

3.11**gas tight housing**

device which vents gas leakage to outside the vehicle including the gas ventilation hose, the clear opening of which is at least 450 mm²

3.12**hydrogen/natural gas blend**

mixture of natural gas and more than 2 % by volume of hydrogen and not pure hydrogen as per ISO 14687-1 or ISO 14687-2

3.13**pressure indicator**

pressurized device which indicates the gas pressure

3.14**pressure regulator**

device used to control the delivery pressure of gaseous fuel to the engine

3.15**pressure relief device****PRD**

one-time use device that when activated under specified performance conditions, is used to vent the container contents

3.16**rigid fuel line**

tubing which has been designed not to flex in normal operation and through which either gaseous hydrogen or hydrogen/natural gas blend flow

3.17**service pressure**

settled pressure at a uniform gas temperature of 15 °C

3.18**test pressure**

pressure to which a component is taken during acceptance testing

3.19**valve**

device by which the flow of a fluid may be controlled

3.20**manual valve**

valve which is operated manually

3.21**automatic valve**

valve which is not operated manually

3.22**automatic cylinder valve**

automatic valve rigidly fixed to the cylinder which controls the flow of gas to the fuel system

3.23**check valve**

automatic valve which allows gas to flow in only one direction

3.24**excess flow valve**

valve which automatically shuts off, or limits, the gas flow when the flow exceeds a set design value

3.25

manual cylinder valve

manual valve rigidly fixed to the cylinder

3.26

pressure relief valve

PRV

self closing device which opens to prevent a pre-determined upstream pressure being exceeded

3.27

service valve

manual valve which is closed only when servicing the vehicle

3.28

working pressure

maximum pressure to which a component is designed to be subjected to and which is the basis for determining the strength of the component under consideration

4 Construction and assembly

4.1 Materials normally in contact with hydrogen shall be determined to be acceptable in hydrogen service, with particular attention to hydrogen embrittlement and hydrogen accelerated fatigue. Materials and design shall be such that there will be no significant change in the functioning of the device, deformation or mechanical change in the device, and no harmful corrosion, deformation, or deterioration of the materials.

Resistance to chloride stress corrosion cracking shall be taken under consideration if selecting stainless steel materials. Resistance to sustained load cracking shall be taken under consideration if selecting aluminium materials.

NOTE 1 Material performance data in hydrogen environments may be found in the Sandia National Laboratory Technical Reference for Hydrogen Compatibility of Materials or the ANSI/AIAA G-095 Guide to Safety of Hydrogen and Hydrogen Systems and ASME B31.12 Hydrogen Piping and Pipelines.

NOTE 2 Guidance to account for the degradation effects of hydrogen on the mechanical performance of a material can be found in ISO/TR 15916.

4.2 Jointing components shall provide gas tight sealing performance. Where joints are required to be disassembled, it is recommended that any tapered thread fittings be replaced

4.3 Components on board shall be suitable for service within the following temperature ranges:

Table 1 — Temperature ranges for on board components

	Location on board	
	Location a	Location b
Cold	– 40°C to 120°C	– 40°C to 85°C
Moderate	– 20°C to 120°C	– 20°C to 85°C
Location a: Inside the engine compartment in case of internal combustion engine vehicle. Location b: Elsewhere in case of internal combustion engine vehicle. In case of fuel cell vehicle, only location b is considered.		

4.4 Components on board shall be suitable for service in accordance with the following service pressures (as specified for the refuelling connectors in ISO 16380 and ISO 17268):

Table 2 — Hydrogen/natural gas blend fuel system components

Service Pressure	Working Pressure
20 MPa	25 MPa
25 MPa	31,25 MPa
35 MPa	43,75 MPa

Table 3 — Hydrogen fuel system components

Service Pressure	Working Pressure
25 MPa	31,25 MPa
35 MPa	43,75 MPa
70 MPa	87,50 MPa

4.5 All non-metallic materials used in seals and diaphragms shall comply with the oxygen ageing test specified in ISO 12619-2.

4.6 All non-metallic materials in contact with gaseous hydrogen and hydrogen/natural gas blends shall comply with the non-metallic material immersion test, hydrogen compatibility test specified in ISO 12619-2.

4.7 All components subject to weather exposure and other corrosive conditions shall be made of corrosion resistant material or otherwise protected.

4.8 It is recognized that multifunctional components may be made up of several components as defined in ISO 12619-3 and subsequent parts. Such components shall be examined for conformance to this part of ISO 12619 and tested according to the appropriate functional tests.

4.9 Fuel flow shut-off shall be normally closed.

5 Electrical equipment and wiring

5.1 Any openings through which electrical wiring components pass shall be equipped with means to prevent chafing and abrasion of the wire insulation.

5.2 Electrical equipment and circuit wiring in a component shall be of automotive quality with respect to mechanical strength, insulation and current carrying capacity, in accordance with either ISO 6722-1 or ISO 6722-2.

5.3 Materials used for electrical construction shall be suitable for their particular application. When determining the acceptability of an electrical insulating material, consideration shall be given to its mechanical strength, dielectric strength, heat-resistant properties, the degree to which it is enclosed or protected, and any other features influencing fire and accident hazards

6 Instructions

6.1 Clear, concise instructions and diagrams, stated in terms clearly understandable and adequate for proper assembly, installation, maintenance and safe operation, shall be provided by the manufacturer of the component and component package. The information shall also require that intermediate assemblers transmit the component warnings and information to the final installer. The manufacturer shall provide

copies of the instructions in response to requests, including service parts. Critical parts of the component information shall be worded in the imperative.

6.2 Instructions for periodic maintenance of components, as required, shall be provided. Parts which require periodic replacement shall be identified.

6.3 This information shall be in the predominant language(s) of the country of destination.

6.4 Instructions shall at least include:

- working pressure (MPa);
- temperature range;
- rated for use with pre-cooled hydrogen;
- installation torques;
- orientation requirements;
- venting requirements with consideration for water ingress;
- type of fuel (i.e. “hydrogen and hydrogen/natural gas blends” or “pure hydrogen”);
- type of vehicle (e.g. fuel cell vehicle, internal combustion engine vehicle);
- flow ratings of connections if required for safety, such as flow requirements into and out of relief;
- valves;
- requirements for warning labels that might be required as part of the installation.

Instructions shall also include, as appropriate:

- installation instructions, including torques;
- installation orientation requirements;
- service procedures;
- recommendations for service access.

7 Marking

The components shall include the following information as required:

- a) the manufacturer's or agent's name, trademark or symbol;
- b) the model designation (part number);
- c) the working pressure or working pressure and temperature range;
- d) the direction of flow (when necessary for correct installation);
- e) the type of fuel;
- f) electrical ratings (if applicable);
- g) the symbol of the certification agency (if applicable);
- h) the type approval number;

- i) the serial number or date code;
- j) reference to this part of ISO 12619, i.e. ISO 12619-1:2014.

Marking shall remain legible for the life of the component and shall not be removable without destroying or defacing the marking. Permanent adhesive labels are permissible, or markings may be etched, stamped, or moulded into the component.

NOTE 1 Specific information required for each component can be found in ISO 12619-3 and subsequent parts of the ISO 12619 series.

NOTE 2 This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

STANDARDSISO.COM : Click to view the full PDF of ISO 12619-1:2014