
**Principles for selecting and using test
persons for testing anthropometric
aspects of industrial products and
designs**

*Principes de choix et d'utilisation de sujets d'essai pour l'essai des
aspects anthropométriques des produits industriels et leur conception*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 15537:2004

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Types of tests	2
4.1 General	2
4.2 Screening test	3
4.3 Detailed test	3
5 Test with test persons	3
5.1 General requirements and recommendations	3
5.2 Procedure for testing	3
5.3 Selection of test persons within the intended user population for screening test	4
5.4 Selection of test persons within the intended user population for detailed test	4
5.5 Experienced or inexperienced persons	6
5.6 Criteria for acceptance of a product with regard to anthropometric aspects	6
5.7 Documentation of the test procedure and the results	7
Annex A (informative) Example of a test procedure for testing of anthropometric aspects of an elevator	8
Bibliography	11

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15537 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 122, *Ergonomics*, in collaboration with Technical Committee ISO/TC 159, *Ergonomics*, Subcommittee SC 3, *Anthropometry and biomechanics*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

Introduction

An investigation into how far ergonomic requirements are taken into consideration with regard to industrial products and designs is often performed using test equipment, giving possibilities to register only one parameter (for example only the body height) or perhaps a few parameters. With regard to the concurrent multifunctional testing and/or determination of product characteristics for which no technical testing procedures have been laid down, one or several persons are often designated as test persons and are observed and/or questioned while or after using the product under test.

The reliability of any findings established in this way is very much dependent on the extent to which the test persons represent the intended user group in different aspects. How well a product or design is adjusted to the anthropometrics of the intended user population is dealt with in this International Standard.

According to EN 614-1, work equipment, e.g. machinery, has to be designed with proper regard to the body dimensions of the intended user population. One means to verify that a product or a design fulfils this requirement is to set up a panel of test persons and let them test the product in different ways.

An example of the use of this International Standard is given in Annex A (informative).

Principles for selecting and using test persons for testing anthropometric aspects of industrial products and designs

1 Scope

This International Standard establishes methods for determining the composition of groups of persons whose anthropometric characteristics are to be representative of the intended user population of any specific object under test.

This International Standard is applicable to the testing of anthropometric aspects of industrial products and designs having direct contact with the human body or dependent on human body measurements, e.g. machinery, work equipment, personal protective equipment (PPE), consumer goods, working spaces, architectural details or transportation equipment.

This International Standard is also applicable to the testing of such safety aspects of products that are dependent on human body measurements. It does not deal with other aspects of the task or other requirements, such as perception of information (except geometrical arrangement of the viewing targets) and the use of controls (except their geometrical placement).

Although this International Standard deals with selecting test persons from an anthropometric perspective, similar general principles could be applied for other test variables, e.g. biomechanical aspects.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7250:1996, *Basic human body measurements for technological design*

ISO 15534-3:2000, *Ergonomic design for the safety of machinery — Part 3: Anthropometric data*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

critical dimension of a product to be tested

dimension estimated to cause a major limitation for the usage from an anthropometrical point of view, for the whole body or body parts, depending on the function of the product in question

NOTE 1 Critical dimension is related to reach, clearance, posture, contact pressure or other factors which may result in difficulties of use, discomfort or health risks.

NOTE 2 A product to be tested can have more than one critical dimension, for example, a combination of a reach- and a clearance-dimension.

EXAMPLE The critical dimension for an access opening could be the width, or a combination of two dimensions, for example the width and the opening height.

3.2

critical anthropometric measurement

anthropometric measurement which is most affected by the critical dimensions of the product

NOTE For instance, the critical anthropometric measurement for a person entering an opening for whole body access is the one with the greatest constraint (for example, the body height and/or the body width, depending on the form of the access opening).

3.3

worst-case combination of critical dimensions and anthropometric measurements

combination of critical dimensions of the product, additional equipment and the critical anthropometric measurement imposing the biggest restriction on a person who is able to use the product or design as intended

3.4

slim body type

person for whom at least two width measurements (preferably shoulder width and hip breadth) and two depth measurements (preferably chest depth and abdominal depth) are smaller than the figure representing the 25th percentile or, where this figure is not available, the average value of the 5th and the 50th (mean) percentile for the population in question

EXAMPLE For the European shoulder breadth (see Table 1) the figure in question is
$$\frac{395 \text{ mm} + 474 \text{ mm}}{2} = 434,5 \text{ mm}.$$

3.5

corpulent body type

person for whom at least two breadth measurements (preferably shoulder breadth and hip breadth) and two depth measurements (preferably chest depth and abdominal depth) are bigger than the figure representing the 75th percentile or, where this figure is not available, the average value of the 50th percentile (mean) and the 95th percentile for the population in question

EXAMPLE For the European hip breadth, standing (see Table 1) the figure in question is
$$\frac{359 \text{ mm} + 400 \text{ mm}}{2} = 379,5 \text{ mm}.$$

3.6

medium body type

person belonging neither to the slim nor to the corpulent body type

4 Types of tests

4.1 General

Depending on the accuracy of the test results required and the availability of test persons, either a screening or a detailed test can be performed. In addition to critical dimensions of the product, at least the following shall be taken into account as selection criteria:

- the geographical origin of the user population (global, European Union or a specific population);
- the age of the user population (all or specific age groups);
- the gender of the user population (both or specific);
- occupation (if relevant).

4.2 Screening test

The screening test is not as complete or accurate as a detailed test and is used in the preliminary assessment of the usability of products and designs for a defined intended user population.

NOTE Where appropriate, particularly early in the design process, screening tests can also be performed with the help of computer manikins or body templates, representing the variation of the intended user population defined in 4.1. For more information on computer manikins, see ISO 15536-1.

Screening tests are never sufficient for complete assessment of safety aspects.

4.3 Detailed test

The detailed test takes account of all dimensions of a product or design (for example by using a mock-up, prototype or other physical model), in relation to anthropometric dimensions. The selection of anthropometric measurements and percentiles depends on the features of the product or design under test. The duration of a detailed test shall be long enough to give a good representation of the intended use of the product, including foreseeable non-regular or emergency use and maintenance.

5 Test with test persons

5.1 General requirements and recommendations

Test persons shall be selected to represent the anthropometric measurements of the relevant percentile of the intended user population.

The test shall be reproducible, as far as possible.

5.2 Procedure for testing

The following shall be taken into account:

- identify the intended user population (see 4.1);
- identify critical tasks that the user will perform in or with the product design, and the type of clothing and equipment used during these tasks;
- define the critical dimensions of the product under test;
- define worst-case combinations of critical dimensions and anthropometric measurements, including critical measurements with additional equipment;
- define safety margins, absolute (figures) or relative (percentile) to be added to the dimensions;
- select test persons according to 5.3 or 5.4, respectively;
- run the test(s), taking the following into account:
 - the measuring of critical dimensions and corresponding anthropometric measurements of the test persons,
 - registration of the test persons' subjective opinions during and/or after using the product,
 - observation of the test persons' behaviour and ability to perform the task when using the product as intended;
- document the test procedure and the test results (see 5.7).

Any individual test should cover at least one whole utilisation cycle for each element of the object under test (adjustment gear, displays, controls, visibility, etc.). Any deviation from this recommendation shall be documented. The reliability of some tests can be improved by repeating them at least three times. Requirements for specific tests might be found in some product standards.

5.3 Selection of test persons within the intended user population for screening test

For each critical dimension, select at least three persons, representing the part of the user population anticipated to be limiting in this aspect. That is, if it is a clearance-dimension that shall be tested, the persons should as far as possible represent the 95th percentile for that dimension. If it is a reach-dimension to be tested, the persons should as far as possible represent the 5th percentile. The same test person can be used for testing more than one critical dimension (see Table 1 for European human body measurements and Table 2 for world-wide human body measurements, or relevant regional data should be used).

5.4 Selection of test persons within the intended user population for detailed test

The following shall be taken into account.

- For each critical dimension, select at least seven persons, representing the part of the user population anticipated to be limiting in this aspect. That is, if it is a clearance-dimension that shall be tested, the persons should, as far as possible, represent the 95th percentile for that dimension. If a reach-dimension is to be tested, the persons should, as far as possible, represent the 5th percentile.
- If the 95th and/or the 5th percentile for the critical dimensions are not known in the intended user population, then at least seven test persons representing the limiting (95th or 5th) percentile of stature shall be used. Of these seven test persons, at least two should be of slim, medium and corpulent body type, respectively. It is also recommended that at least one person representing the 95th or the 5th percentile of the breadth or depth measurement be included in the test group. A test person can be used for testing more than one critical dimension.
- In a more complicated test situation, for example, where both clearance- and reach-dimensions are of concern, the sample of test persons should be specifically determined for its purpose.
- It is recommended to use the 1st and the 99th percentile, instead of the 5th and the 95th wherever possible.

For safety considerations (for example, for testing the access openings or safety distances), at least one person representing the 1st or the 99th percentile of the relevant body measurement shall be employed in the test.

Table 1 — European human body measurements for persons aged between 18 and 60 years

Human body measurement	Value, mm			Definition, see
	P5	P50	P95	
Stature (body height)	1 530 ^a	1 719 ^a	1 881 ^{b, c}	ISO 7250:1996; 4.1.2
Eye height	1 420 ^a	1 603 ^a	1 750 ^a	ISO 7250:1996; 4.1.3
Shoulder height	1 260 ^a	1 424 ^a	1 570 ^a	ISO 7250:1996; 4.1.4
Elbow height	930 ^b	1 078 ^a	1 195 ^b	ISO 7250:1996; 4.1.5
Crotch height	665 ^b	816 ^a	900 ^b	ISO 7250:1996; 4.1.7
Tibial height	397 ^a	472 ^a	530 ^a	ISO 7250:1996; 4.1.8
Lower leg length (popliteal height)	340 ^b	444 ^a	505 ^b	ISO 7250:1996; 4.2.12
Knee height, sitting	460 ^a	530 ^a	602 ^a	ISO 7250:1996; 4.2.14
Hip breadth, standing	300 ^a	359 ^a	400 ^a	ISO 7250:1996; 4.1.12
Hip breadth, sitting	333 ^a	368 ^a	440 ^{a, b}	ISO 7250:1996; 4.2.11
Elbow-to-elbow breadth	390 ^a	478 ^a	545 ^c	ISO 7250:1996; 4.2.10
Shoulder (bideltoid) breadth	395 ^a	474 ^a	485 ^a	ISO 7250:1996; 4.2.9
Chest depth, standing	170 ^a	215 ^a	250 ^a	ISO 7250:1996; 4.1.9
Abdominal depth, sitting	195 ^a	237 ^a	350 ^a	ISO 7250:1996; 4.2.15
Hand length	152 ^c	182 ^a	202 ^a	ISO 7250:1996; 4.3.1
Hand breadth with thumb	d	d	120 ^c	ISO 15534-3:2000
Hand breadth at metacarpals	72 ^a	81 ^a	97 ^c	ISO 7250:1996; 4.3.3
Foot length	211 ^c	255 ^a	285 ^{b, c}	ISO 7250:1996; 4.3.7
Foot breadth	84 ^a	96 ^a	113 ^c	ISO 7250:1996; 4.3.8
Head length from tip of nose	d	d	240 ^c	ISO 15534-3:2000
NOTE For further information, see ISO 15534-1 to ISO 15534-3.				
^a Source: Jürgens, H.W.; Matzdorff, I. Windberg, J.: <i>International Anthropometric Data for Work-Place and Machinery Design</i> ([13] in the Bibliography). ^b Source: ISO 14738:2002. ^c Source: ISO 15534-3:2000. ^d There are no data available.				

Table 2 — World-wide human body measurements for persons between 25 and 45 years of age, divided into two categories, i.e. “smaller type” and “larger type”

Human body measurement ^a	Smaller type ^b			Larger type ^b	
	Value, mm				
	P5	P50	P95/P5	P50	P95
Stature (body height)	1 390	1 520	1 650	1 780	1 910
Sitting height (erect)	740	800	870	935	1 000
Eye height, sitting	620	690	750	815	880
Forward reach (fingertips)	670	740	810	880	950
Shoulder (bideltoid) breadth	320	365	410	455	500
Shoulder (biacrominal) breadth	285	325	360	395	430
Hip breath, standing	260	300	335	375	410
Knee height	405	455	505	550	600
Lower leg length (popliteal height)	320	365	410	460	505
Elbow-grip length	270	305	340	375	410
Buttock-knee length	450	505	560	615	670
Buttock-heel length	830	920	1 010	1 100	1 190
Hip breadth, sitting	260	305	350	395	440
Hand length	140	155	170	185	200
Hand breadth at metacarpals	65	75	90	100	110
Foot length	200	225	250	275	300
Head circumference	475	505	540	570	600
Head length	160	175	185	195	205
Head breadth	120	135	145	160	170
NOTE For children and elderly populations, separate data sets are sometimes are needed.					
^a Source: Hans W. Jürgens, Ivar A. Aune, Ursula Pieper: <i>International Data on Anthropometry</i> ([12] in the Bibliography).					
^b Both types should be considered when testing products designed for the whole world. “Smaller type” and “Larger type” categories are given if it is not possible to create a product design for the whole world. “Smaller type” data are based on females from “smaller type” populations. “Larger type” data are based on males from “larger type” populations.					

5.5 Experienced or inexperienced persons

In many situations, it is appropriate that persons with different acquaintance with the product in question are engaged for the test, as long as they belong to the intended user population. When analysing the test data, a distinction should be made between experienced and inexperienced (naive) test persons, concerning the use of the product or the design under test. In some cases, it may be useful to have an even finer differentiation concerning acquaintance with the test situation.

5.6 Criteria for acceptance of a product with regard to anthropometric aspects

General criteria for acceptance are defined in certain standards (for example, ISO 14738 and EN 614-1). The set of acceptance criteria for a given product is dependent on the product/design. For some products, acceptance criteria are formulated in specific product standards. For other products, or when specific user groups are intended, the designers may have to formulate their own acceptance criteria, based on applicable anthropometric information.

For safety aspects, negative results concerning one single item shall lead to redesign.

NOTE Additional allowances for safety may be needed to provide protection for the whole population.

5.7 Documentation of the test procedure and the results

Identification of the product/design tested, the intended user population, defined critical dimensions and critical anthropometric measurements, test procedures, acceptance criteria and test results shall be documented and made available on request.

STANDARDSISO.COM : Click to view the full PDF of ISO 15537:2004

Annex A (informative)

Example of a test procedure for testing of anthropometric aspects of an elevator

A.1 Scope

A ten person elevator which is planned for public use in a big five-floor department store in Europe has to be tested. Two parking levels are situated on top of the store (6th and 7th floor).

The test in this example case has to do with comfort, selective aspects of ergonomic-anthropometric relevance, as well as aspects of entry/exit. In particular, this Annex does not address safety issues of elevators. For this purpose, ISO 4190-1, ISO 4190-2 and EN 81 should be consulted.

A.2 Test procedure (see Table A.1)

Step 1: Determine the critical dimensions of the products and equipment and the critical anthropometric measurements of the users (see Table A.1, step 1).

Step 2: Determine the worst case (see Table A.1, step 2).

Step 3: Determination of different types of test

For checking rough anthropometric data (for example for ten persons) a screening test as well as a computer application can be used. As time aspects (duration of transport in the worst case: from basement to the 7th floor with a stop at every floor level) will influence the acceptance of space inside an elevator, a detailed test with persons should be preferred.

Step 4: Selecting of test persons

As the elevator is for use in a European department store, European anthropometric data will normally be sufficient. Although the data represent an average value for both sexes, it is advisable to form a test group by a mixed male and female population to achieve better subjective test results.

The test persons should be experienced in using an elevator.

The test persons can be formed into three groups (see Table A.1, step 4):

- Group 1 (worst case): Ten persons representing the 95th percentile (corpulent), for testing the door width and the space inside the elevator. Probably the seven test persons needed for the press-button size test (big hand/index fingers) can be included in this group.
- Group 2: Seven children (aged 12 years) representing the 5th percentile, for testing the highest push button.
- Group 3 (realistic): Mixed adult group representing the 95th (three persons), the 50th (four persons) and the 5th (three persons) percentile (including one wheel-chaired person or one person with a pram), instead of Group 1.