
**Agricultural and forestry
machinery — Environmental
requirements for sprayers —**

**Part 3:
Sprayers for bush and tree crops**

*Matériel agricole et forestier — Exigences environnementales pour les
pulvérisateurs —*

Partie 3: Pulvérisateurs pour arbustes et arboriculture



STANDARDSISO.COM : Click to view the full PDF of ISO 16119-3:2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 List of significant hazards	2
5 Requirements	3
5.1 General	3
5.2 Volume/hectare adjustment system	8
5.3 Distribution of liquid and air	8
5.4 Cleaning	9
5.5 Cleaning devices	10
5.6 Additional requirements for spray guns and lances	10
6 Verification	10
7 Marking	11
8 Instruction handbook	11
Bibliography	12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16119-3 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 144, *Tractors and machinery for agriculture and forestry*, in collaboration with ISO Technical Committee TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 6, *Equipment for crop protection*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

ISO 16119 consists of the following parts, under the general title *Agricultural and forestry machinery — Environmental requirements and testing for sprayers*:

- Part 1: General
- Part 2: Horizontal boom sprayers
- Part 3: Sprayers for bush and tree crops
- Part 4: Fixed and semi-mobile sprayers

Introduction

The requirements of this part of ISO 16119 are based on the test methods given in ISO 5682-2:1997, which were primarily developed for hydraulic sprayers. For other types of sprayers, other test methods and/or test criteria may be needed and may be the subject of future investigation/revision of this part of ISO 16119.

This document is a type C standard as stated in ISO 12100.

The machinery concerned and the extent to which hazards, hazardous situations and hazardous events are covered are indicated in the scope of this document.

When provisions of this type C standard are different from those which are stated in type A or B standards, the provisions of this type C standard take precedence over the provisions of the other standards, for machines that have been designed and built according to the provisions of this type C standard.

STANDARDSISO.COM : Click to view the full PDF of ISO 16119-3:2013

STANDARDSISO.COM : Click to view the full PDF of ISO 16119-3:2013

Agricultural and forestry machinery — Environmental requirements for sprayers —

Part 3: Sprayers for bush and tree crops

1 Scope

This part of ISO 16119 specifies requirements and the means for their verification for the design and performance of sprayers for bush and tree crops, as defined in 3.1, and similar crops, with regard to minimizing the potential risk of environmental contamination during use, including misuse foreseeable by the manufacturer.

It is not applicable to human-mounted sprayers for bushes or trees.

It is intended to be used with ISO 16119-1, which gives general requirements common to all the sprayer types covered by ISO 16119. When requirements of this part of ISO 16119 are different from those which are stated in ISO 16119-1, the requirements of this part of ISO 16119 take precedence over the requirements of ISO 16119-1 for machines within the scope of this part of ISO 16119. This part of ISO 16119 does not cover safety aspects (see ISO 4254-6).

This part of ISO 16119 is not applicable to sprayers manufactured before the date of its publication.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4102, *Equipment for crop protection — Sprayers — Connection threading*

ISO 4254-6:2009, *Agricultural machinery — Safety — Part 6: Sprayers and liquid fertilizer distributors*

ISO 4288, *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture*

ISO 5681, *Equipment for crop protection — Vocabulary*

ISO 5682-1, *Equipment for crop protection — Spraying equipment — Part 1: Test methods for sprayer nozzles*

ISO 5682-2:1997, *Equipment for crop protection — Spraying equipment — Part 2: Test methods for hydraulic sprayers*

ISO 5682-3:1996, *Equipment for crop protection — Spraying equipment — Part 3: Test method for volume/hectare adjustment systems of agricultural hydraulic pressure sprayers*

ISO 9357, *Equipment for crop protection — Agricultural sprayers — Tank nominal volume and filling hole diameter*

ISO 9898:2000, *Equipment for crop protection — Test methods for air-assisted sprayers for bush and tree crops*

ISO 13440:1996, *Equipment for crop protection — Agricultural sprayers — Determination of the volume of total residual*

ISO 16119-1:2013, *Agricultural and forestry machinery — Environmental requirements for sprayers — Part 1: General*

ISO 21278-1, *Equipment for crop protection — Induction hoppers — Part 1: Test methods*

ISO 21278-2, *Equipment for crop protection — Induction hoppers — Part 2: General requirements and performance limits*

ISO 22368-1, *Crop protection equipment — Test methods for the evaluation of cleaning systems — Part 1: Internal cleaning of complete sprayers*

ISO 22368-3, *Crop protection equipment — Test methods for the evaluation of cleaning systems — Part 3: Internal cleaning of tank*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5681 and the following apply.

3.1

sprayer for bush and tree crops

machine for spraying plant protection products on bush and tree crops such as grapes, fruits or hops (including annual plants/crops), the application being mostly directed sideways and/or upwards to the target

3.2

plant protection product container

collective name for plant protection product packaging

EXAMPLE Can, bottle, bag, sack, box.

3.3

cleaning device

device for cleaning the insides of empty plant protection product containers

Note 1 to entry: The device may be an integral part of the sprayer or an independent installation (e.g. stationary equipment).

4 List of significant hazards

[Table 1](#) specifies the significant hazards, the significant hazardous situations and significant hazardous event(s) covered by this part of ISO 16119 that have been identified by risk assessment as being relevant for this type of machine with regard to environmental contamination, and which require specific action by the designer or manufacturer to eliminate or to reduce environmental contamination.

Attention is drawn to the necessity to verify that the environmental requirements specified in both ISO 16119-1 and this part of ISO 16119 apply to each significant hazard presented by a given machine and to validate that the risk assessment is complete.

Table 1 — List of significant hazards

Hazard		Hazardous situation/ event	Clause/subclause of this part of ISO 16119
4.1	Spillages	Filling	5.1.1.2; 8
		Induction of plant protection products	5.1.1.2; 8
4.2	Contamination of the water supply	Filling	5.1.1.2
4.3	Leakages	Transport and application	5.1.1.2; 5.1.2
		Contact with crop	5.1.4
4.4	Overfilling	Filling	5.1.1.2; 5.1.1.4; 8
4.5	Dispersal of spray mixture residues or plant protection products	Drainage	5.1.1.3.1; 5.1.1.4; 8
		Cleaning and rinsing	5.1.1.1; 5.4; 5.5; 8
4.6	Accidental leakages	Accidental opening of tank outlet	5.1.1.3.2
4.7	Over-dosing	Heterogeneous mixing	5.1.1.5; 8
		Overlapping	5.1.8
		Sprayer adjustment/control	5.1.1.4; 5.1.2; 5.1.5; 5.1.6; 5.1.8; 5.2; 5.3.1; 5.6; 8
		Sprayer maintenance/service	5.1.7; 7; 8
		Unintended deposition	5.1.8; 5.3.1
4.8	Unintended spraying outside the target area	Application	5.3.2
		Spraying stop control	5.1.2; 5.1.8; 5.6
4.9	Drift	Spraying	5.3.2; 5.3.3; 7; 8
4.10	Discharge of spray mixture	Intervention on the sprayer during application or service	5.1.3; 7; 8
4.11	Dripping	Spraying stop control	5.1.4

5 Requirements

5.1 General

5.1.1 Spray tank

5.1.1.1 Surfaces

The depth of roughness, R_z , (see ISO 4287) of the inner and outer walls of the tank shall be such that $R_z \leq 100 \mu\text{m}$, measured according to ISO 4288.

5.1.1.2 Filling

Filling devices shall be designed to avoid any return of liquid from the tank to the filling supply.

The filling hole diameter shall comply with ISO 9357. The opening lid shall seal sufficiently to prevent leakage/spillage when closed.

The total tank volume shall be at least 5 % more than its nominal volume, to prevent spillage as a result of overfilling. Tanks with a nominal volume greater than 200 l shall have a nominal volume which is a multiple of 100 l.

Strainers shall have a minimum depth, d , as given in [Table 2](#) and measured according to [Figure 1](#).

Strainers shall be installed in filling openings and shall have a mesh size less than 2 mm. Any gaps between the tank filling hole and the strainer shall not exceed 2 mm (see [Figure 1](#)).

The filling capacity of the tank with strainer when filled with water shall be at least 100 l/min for tanks with a nominal volume of 100 l or more. For tanks with a nominal volume of less than 100 l, it shall be possible to fill the tank within 1 min.

Induction hoppers shall comply with ISO 21278-2.

Table 2 — Minimum depth of strainers

Nominal tank capacity	Minimum depth ^a
C	d
l	mm
$C \leq 150$	60
$150 < C \leq 400$	100
$400 < C \leq 600$	150
$C > 600$	250
^a Measured from the upper edge of the strainer down to its bottom.	




Figure 1 — Determination of the depth of the strainer and width of gap(s)

5.1.1.3 Emptying

5.1.1.3.1 Residual volume

The volume of total residual as defined in ISO 13440:1996, 2.1 shall not exceed

- 4 % of the nominal tank volume for a tank volume of less than 400 l;
- 3 % of the nominal tank volume for a tank volume of between 400 l (included) and 1 000 l (included);
- 2 % of the nominal tank volume for a tank volume of more than 1 000 l.

The volume of total residual shall be determined in accordance with ISO 13440.

5.1.1.3.2 Tank emptying device

An emptying device in accordance with ISO 4254-6:2009, 5.4.3 shall allow the complete emptying of the residual in the tank when the sprayer is in a horizontal position. Complete emptying of the residual is considered to have been achieved when there are no visible puddles at the bottom of the tank after 5 min drainage.

It shall be possible to collect the liquid at the outlet without contaminating the environment or equipment parts, e.g. stays.

The tank outlet shall be guarded against accidental opening.

5.1.1.4 Tank contents indicator(s)

The indication of contents shall correspond to ISO 9357. It shall be durable and easily readable from the driver's position and from where the tank is filled. Turning of the head and the upper body is acceptable.

The acceptable tolerances of the indication are

- ± 15 % for each graduation mark/read-out value for volumes up to 10 % of the nominal tank volume,
- $\pm 7,5$ % for each graduation mark/read-out value for volumes from 10 % to 20 % of the nominal tank volume, and
- ± 5 % for each graduation mark/read-out value for volumes above 20 % of the nominal tank volume.

The tolerances shall be measured with a maximum error on measurement of ± 1 % with the sprayer in a horizontal position.

5.1.1.5 Mixing

Tanks shall be designed (e.g. including agitators) to ensure an even concentration of mixture. The maximum allowable deviation is ± 15 %, tested in accordance with ISO 5682-2.

5.1.2 Lines (hoses and pipes)

The bending radius of hoses shall be within the limits recommended by the hose manufacturer. Hoses shall not have any deformation which could disturb the liquid flow.

Pressure lines shall be equipped with quick-acting shut-off devices (e.g. tip-over lever valves).

The maximum working pressure of hoses and the maximum working pressure of connecting devices shall be at least equal to the maximum working pressure of the circuit. See also ISO 16119-1:2013, Clause 6 h).

5.1.3 Filter

Sprayers equipped with a positive displacement pump shall have a suction filter.

On the pressure side, the liquid going to the nozzles shall be filtered by means of central filters or filters in the lines of spraying sections. The size of filters shall correspond to the size of nozzles fitted on the sprayer. This applies also to nozzle and pump filters.

The operator shall be able to detect blockages — for example, by an appropriate positioning of the central pressure filters and pressure indicator.

Filters shall be easily accessible and filter inserts shall be removable. For quick cleaning, the filter tissue of the insert shall be easily accessible.

It shall be possible, with the tank filled to its nominal volume, to clean central filters without any spray liquid leaking out except for that which may be present in the filter casing and connected suction or pressure lines.

5.1.4 Nozzles

It shall be possible to fix nozzles in predetermined positions, to ensure that the spray is correctly directed, by appropriate means such as marking, locking systems or mouldings.

When the spraying stop control has been activated, there shall be no dripping. Verification of this requirement is by the following test. When the spraying stop control has been activated, the dripping shall not exceed 2 ml per nozzle during a period of 5 min, starting 8 s after the spraying stop control has been activated.

Nozzles shall be protected to minimize contact with (parts of) crops.

The flow rate of each individual nozzle, measured according to ISO 5682-1, shall not deviate by more than 5 % from the data of the flow rate tables.

5.1.5 Measuring systems

The working pressure, the volume application rate (in litres per hectare), where relevant, the control setting and the tank volume indication shall be clearly readable from the operator's position. Turning of the head and the upper body is acceptable.

Sprayers shall be fitted with a pressure indicator complying with ISO 4254-6:2009, 5.5, the accuracy of which shall be¹⁾

- $\pm 0,2$ bar for working pressures between 0,8 bar (included) and 8 bar (included),
- $\pm 0,5$ bar for working pressures between 8 bar and 20 bar (included), and
- ± 1 bar for working pressures more than 20 bar.

The pressure indicator shall be clearly readable. The pressure indication shall be stable. The scale of the pressure indicator shall be marked as follows:

- every 0,2 bar for working pressures less than 5 bar;
- every 1,0 bar for working pressures between 5 bar (included) and 20 bar (included);
- every 2,0 bar for working pressures more than 20 bar.

Unless otherwise specified in this part of ISO 16119, each measuring system of the sprayer, e.g. for flow rate, forward speed, pressure or air speed shall be measured within a maximum error of ± 5 % of the true value.

5.1.6 Nozzle output

It shall be possible to measure the flow rate of each individual nozzle.

5.1.7 Provisions for connecting test equipment

Means shall be provided to test the pressure indicator

- on the sprayer with a connection having a 1/4 inch or 1/2 inch inner thread according to ISO 4102, or
- it shall be possible to demount the pressure indicator from the sprayer, without need to demount other parts of the sprayer.

Means shall also be provided to connect a flow meter between the pump and the pressure regulator without damaging any hoses or removing the couplers from the hoses.

If the sprayer is equipped with a flow meter, the sprayer shall be equipped with a connecting device allowing the fitting of a test flow meter without the need to dismount the machine flow meter.

5.1.8 Adjustment of liquid and air-flow

When a blower or blowers are present, it shall be possible to switch off the blower(s) independently from other driven parts of the machine.

It shall be possible to switch off the spray at each side of the sprayer independently. For sprayers with multiple rows, this requirement shall be applied to individual rows.

It shall be possible for one person to adjust the sprayer to the type, size and height of the crop in a reproducible way, by appropriate means such as marking, locking systems or mouldings. See also [Clause 8](#).

1) 1 bar = 0,1 MPa = 0,1 N/mm² = 10⁵ N/m².

It shall be possible to switch each nozzle off and to adjust the direction of its spray independently.

In the case of multi-head nozzles, this requirement applies to each individual multi-head nozzle.

5.2 Volume/hectare adjustment system

5.2.1 General

The maximum error for all the measurements specified in 5.2.2 shall be $\pm 2,5$ %.

5.2.2 Measurements

5.2.2.1 Pressure adjustment devices shall maintain a constant working pressure at constant revolutions of the pump. After switching off/on the sprayer and its individual sections during spraying operation, the working pressure shall return to its original value within $\pm 7,5$ %.

5.2.2.2 The following applies to volume/hectare adjustment systems.

- a) 7 s after variations in operating conditions, the measured volume application rate shall be within ± 10 % of the mean volume application rate in the new constant operating condition.

NOTE Changes in operating conditions are effected, for instance, by switching off nozzles, varying the travelling speed or switching off/on sections of the sprayer boom.

- b) During repeated adjustments to the same volume application rate (l/ha), the coefficient of variation calculated from seven measurements shall not exceed 3 %.
- c) While spraying with constant PTO (power take off) rotational speed and at a constant travelling speed, the maximum deviation from the mean volume application rate (l/ha) shall not exceed 5 %.
- d) The acceptable deviation on the measured volume application rate (l/ha) or respective flow rate (l/min) from the values required shall be
- 1) ± 6 % for the mean deviation, and
 - 2) 3 % for the coefficient of variation.

The test of the volume-hectare adjustment system shall be carried out in accordance with ISO 5682-3. Verification of requirement a), above, shall be checked according to ISO 5682-3:1996, 5.1 and 5.2; requirements b), c) and d) shall be checked according to ISO 5682-3:1996, 5.3.

5.2.2.3 The pressure drop between the measuring point for pressure on the sprayer for bush and tree crops and the nozzle (including anti-drip device, if available) or the orifice plate shall not exceed 10 % of the pressure shown on the pressure indicator. This test shall be performed at maximum flow rate as indicated by the manufacturer in the instruction handbook.

5.2.2.4 Appropriate calibration aids — at least a measuring jar with a capacity of 1 l and an accuracy of $\pm 2,5$ % and with a scale marked every 20 ml — shall be supplied together with the sprayer.

5.3 Distribution of liquid and air

5.3.1 Liquid

The flow rate of each nozzle when mounted on the sprayer shall not deviate by more than 10 % from the data given in the flow rate tables provided by the sprayer manufacturer.

The flow rate of each nozzle of the same type and size when mounted on the sprayer shall not deviate by more than 10 % from the mean flow rate of all the same nozzles mounted on the sprayer. ISO 5682-2 shall be used for the measurement.

These requirements for flow rate shall be checked with a measuring error of less than $\pm 2,5$ % of the true value.

5.3.2 Air (if any)

The air flow rate of the fan(s), measured according to ISO 9898, shall not deviate by more than 10 % from the nominal output specified by the sprayer manufacturer.

For air-assisted sprayers intended for symmetrical application, the sprayer shall be designed so that the air flow produced by the fan is symmetrical at the right and left sides with respect to direction, velocity and air volume (according to ISO 9898:2000, 5.2.3). Deviation between left and right shall not be more than 25 % when measured according to ISO 9898:2000, Clause 6, with the sprayer adjusted according to the instructions given in the sprayer manufacturer's handbook (see [Clause 8](#)).

5.3.3 Drift

The sprayer shall be designed considering the need to reduce drift as far as practicable, e.g. switching off or decreasing the air assistance to one side, allowing the fitting of injection nozzles.

5.4 Cleaning

5.4.1 Water tank

A water tank (or tanks) shall be provided for rinsing the spraying equipment, except for mounted sprayers of nominal tank volume less than or equal to 400 l. This tank shall not be combined with the clean water tank for the operator's use (see ISO 4254-6:2009, 5.10).

It shall have a volume of at least 10 % of the nominal spray tank volume or at least 10 times the volume of residual which can be diluted (see ISO 13440:1996, 2.2). In the latter case, the volume of residual of tank shall be specified in the instruction handbook.

Water tanks shall be designed so that they can be connected with the equipment in such a way that the rinsing of the pipes is possible even when the spray tank is filled to its nominal volume (see also [Clause 8](#)). In addition, the dilution of the volume of residual in the tank shall be possible.

5.4.2 Cleaning systems

5.4.2.1 General

Sprayers shall be equipped with a connecting device to allow the connection of external cleaning devices. Sprayers shall be provided with an internal tank cleaning system.

The internal tank cleaning system shall reduce the quantity of plant protection product adhered to the inner surfaces by 70 % when tested in accordance with ISO 22368-3.

These requirements do not apply to mounted sprayers of a nominal tank volume of less than or equal to 400 l.

5.4.2.2 Residue concentration

One or the other of the following requirements, a) or b), applies:

- a) after completion of the cleaning process, the concentration of the residue shall be reduced by a factor of 300 (or 99,67 %), compared with the concentration before starting the cleaning process, tested in accordance with ISO 22368-1;

- b) after completion of the cleaning process as described in the instruction handbook, the concentration of the liquid drained from the main tank outlet shall have been reduced to 2 % of the original concentration in the tank.

NOTE Upon publication of ISO 16236, this part of ISO 16119 is to be amended to include reference to the test method given in ISO 16236 for the evaluation of the drainable volume.

5.5 Cleaning devices

Devices for cleaning plant protection product containers, when provided, shall be designed so that the volume of residue after cleaning is less than 0,01 % of the nominal container volume. This requirement shall be checked according to the test method given in ISO 21278-1.

There shall be means to rinse the containers with clean water and to transfer and collect the rinsing water in the spray tank without spillage resulting in environmental contamination.

5.6 Additional requirements for spray guns and lances

Spray guns and lances shall be provided with a quick acting start/stop valve. A locking device to hold the spraying control on spraying position is not allowed.

If the spray gun or lance flow rate is adjustable, a clear marking indicating the flow rate setting shall be provided.

If the pressure indicator of the sprayer cannot be easily read from the operator position, then a pressure indicator shall be provided on the spray gun or lance.

6 Verification

Verification of the requirements given in [Clauses 5](#) and [6](#) may be made by means of inspection, calculation, or testing as appropriate. The means of verification is either self-evident or specified for particular requirements in [Clauses 5](#) and [6](#), as summarized in [Table 3](#).

Table 3 — List of safety requirements and/or protective measurements and their verification

Subclause of this part of ISO 16119		Verification			
		Inspection	Measurement	Test	Remark
5.1.1	Spray tank				
5.1.1.1	Surfaces		X		ISO 4288
5.1.1.2	Filling	X	X	X	
5.1.1.3	Emptying	X	X	X	ISO 13440 ISO 9357
5.1.1.5	Mixing		X		ISO 5682-2
5.1.2	Lines	X			
5.1.3	Filter	X			
5.1.4	Nozzles	X	X		ISO 5682-1
5.1.5	Measuring systems	X	X		
5.1.6	Nozzle output	X			
5.1.7	Provisions for connecting test equipment	X			
5.1.8	Adjustment of liquid and air flow	X			
5.2	Volume/hectare adjustment system	X	X		ISO 5682-2 ISO 5682-3