
**Road vehicles — M12 x 1,25 spark-plugs
with flat seating and 14 mm hexagon and
their cylinder head housing**

*Véhicules routiers — Bougies d'allumage M12 x 1,25 à siège plat et à
hexagone de 14 mm et leur logement dans la culasse*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO 16246:2005

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 16246 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 1, *Ignition equipment*.

Road vehicles — M12 x 1,25 spark-plugs with flat seating and 14 mm hexagon and their cylinder head housing

1 Scope

This International Standard specifies the characteristics of M12 × 1,25 spark-plugs with flat seating and 14 mm hexagon and their cylinder head housings, used with spark-ignition engines in road vehicles.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 68-1, *ISO general purpose screw threads — Basic profile — Part 1: Metric screw threads*

ISO 261, *ISO general purpose metric screw threads — General plan*

ISO 965-1, *ISO general-purpose metric screw threads — Tolerances — Part 1: Principles and basic data*

ISO 965-3, *ISO general purpose metric screw threads — Tolerances — Part 3: Deviations for constructional screw threads*

ISO 14508, *Road vehicles — Spark-plugs — Terminals*

3 Terminals

The spark-plug terminal may be either a solid post or threaded terminal, as specified in ISO 14508.

A spark-plug with a threaded terminal on which a nut is applied shall have the same dimensions as those shown for spark-plugs with solid post terminals in Figures 1 and 2.

4 Dimensions and threads

4.1 Spark-plug reach

The spark-plug reach shall be in accordance with Table 1 (see Figures 1 to 4).

Table 1 — Spark-plug reach

Dimensions in millimetres

Type of reach	<i>A</i>	<i>E</i> ^a	<i>B</i> max.	<i>Y</i> + 0,3 – 0,8
	Tolerance of <i>A</i> + <i>E</i> : ± 0,2			
Normal	12,7	0	21	11,7
Long	19		27	18
Extended long		1,5 ... 6	31	
Extra-long	26,5	0	34,5	25,5
Extended extra-long		1,5 ... 6	38,5	
^a It is intended that <i>E</i> be specified more definitively in future revisions of this International Standard.				

4.2 Gasket

When the spark-plugs have been tightened with a torque of 25 N · m, on threads that are clean, smooth and dry, the gaskets shall be 1 mm to 1,6 mm thick. If the gasket thicknesses are different, a corresponding adjustment to dimensions *A*, *B* and *Y* shall be made.

Non-captive gaskets may be used in special cases.

4.3 Threads for spark-plugs and cylinder heads

4.3.1 General

The threads of M12 × 1,25 spark-plugs and the corresponding tapped holes in the cylinder head shall conform to ISO 68-1, ISO 261, ISO 965-1 and ISO 965-3.

For their limiting dimensions and tolerance classes, see 4.3.2 and 4.3.3.

4.3.2 Limiting dimensions

The limiting dimensions shall be in accordance with Table 2.

Table 2 — Limiting dimensions

Dimensions in millimetres

Dimension		Plug thread (on finished plug)	Tapped hole in cylinder head
Major diameter	max.	11,937	Not specified
	min.	11,725	12,000
Pitch diameter	max.	11,125	11,368
	min.	10,993	11,188
Minor diameter	max.	10,404	10,912
	min.	10,181 ^a	10,647
^a With a root radius ≥ 0,125 mm (0,1 <i>P</i>).			

4.3.3 Tolerance classes

The thread tolerance classes of finished M12 × 1,25 spark-plugs and of the corresponding tapped holes in the cylinder head are as follows:

- 6e for spark-plugs (see Note 1);
- 6H for tapped holes in the cylinder head.

NOTE 1 In order that spark-plugs complying with this International Standard can also be fitted in existing cylinder heads in extreme cases, the value for the maximum truncation, $C_{\max}$, of the minor diameter of the spark-plug base has been slightly reduced with respect to the ISO value. This maximum value of the minor diameter is calculated from a distance of $H/16$ for the maximum truncation by the following formula (instead of the value for $C_{\max}$ given by the formula in ISO 965-1:1998, Clause 11):

$$\begin{aligned} \text{Minor diameter, maximum} &= d_1 - e_s - 2(H/4 - H/6) \\ &= (10,647 - 0,063 - 0,180) \text{ mm} \\ &= (10,647 - 0,243 = 10,404) \text{ mm} \end{aligned}$$

The value for the *basic profile* remains the same as for the ISO thread ($10,647 - 0,063 = 10,584$ mm).

NOTE 2 The initial clearance $e = 0,063$ mm between the pitch diameters of the thread and of the tapped hole is intended to prevent the possibility of seizure, as a result of combustion deposits on the bare threads, when removing the spark-plugs. This clearance is also intended to enable spark-plugs with threads in accordance with this International Standard to be fitted in existing tapped holes.

5 Other dimensions of spark-plugs and their cylinder head housings

The other dimensions shall be as indicated in Figures 1 to 5.


Dimensions 52,5 mm on spark-plugs with solid post terminal and 49,5 mm on spark-plugs with threaded terminal shall be measured when the spark-plugs have been tightened according to 4.2.

The non-ribbed insulator design is preferred because it provides superior protection to flashover between the spark-plug insulator and the cover.

The Z length of the spark-plug housing in the cylinder head shall be sufficient to ensure that the end of the spark-plug thread does not project into the combustion chamber at any point when the gasket is tightened to maximum compression.

Details not specified are at the manufacturer's discretion.

Dimensions in millimetres



Key

- 1 solid post terminal (ISO 14508)
- 2 captive gasket
- 3 pitch diameter


^a See Clause 5.

b Optional.

c The maximum protrusion of any part of the spark-plug into the combustion chamber, measured from the spark-plug seat, not including the gasket.

Figure 1 — Spark-plug with solid post terminal (preferred design with non-ribbed insulator)


Dimensions in millimetres



a The number and shape of ribs are optional.

Figure 2 — Spark-plug with solid post terminal (traditional design with ribbed insulator)

Dimensions in millimetres



Key

- 1 threaded terminal (ISO 14508)
- 2 captive gasket
- 3 pitch diameter


^a See Clause 5.

^b Optional.

^c The maximum protrusion of any part of the spark-plug into the combustion chamber, measured from the spark-plug seat, not including the gasket.

Figure 3 — Spark-plug with threaded terminal (preferred design with non-ribbed insulator)

Dimensions in millimetres



^a The number and shape of ribs are optional.

Figure 4 — Spark-plug with threaded terminal (traditional design with ribbed insulator)