

---

---

**Plastics — Polyamide (PA) moulding  
and extrusion materials —**

**Part 2:  
Preparation of test specimens and  
determination of properties**

*Plastiques — Matériaux à base de polyamide (PA) pour moulage et  
extrusion —*

*Partie 2: Préparation des éprouvettes et détermination des propriétés*

STANDARDSISO.COM : Click to view the full PDF of ISO 16396-2:2022



STANDARDSISO.COM : Click to view the full PDF of ISO 16396-2:2022



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

|                                                                            | Page      |
|----------------------------------------------------------------------------|-----------|
| Foreword.....                                                              | iv        |
| <b>1 Scope.....</b>                                                        | <b>1</b>  |
| <b>2 Normative references.....</b>                                         | <b>1</b>  |
| <b>3 Terms and definitions.....</b>                                        | <b>2</b>  |
| <b>4 Preparation of test specimens.....</b>                                | <b>2</b>  |
| 4.1 Treatment of the material before moulding or laser sintering.....      | 2         |
| 4.2 Injection moulding.....                                                | 3         |
| 4.3 Laser sintering.....                                                   | 3         |
| <b>5 Conditioning of test specimens.....</b>                               | <b>5</b>  |
| 5.1 Conditioning states of the test specimen.....                          | 5         |
| 5.2 Dry-as-moulded (DAM) state.....                                        | 5         |
| 5.3 Moist state.....                                                       | 6         |
| <b>6 Determination of properties.....</b>                                  | <b>6</b>  |
| <b>Annex A (normative) Specimen preparation using laser sintering.....</b> | <b>9</b>  |
| <b>Bibliography.....</b>                                                   | <b>10</b> |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 9, *Thermoplastic materials*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 249, *Plastics*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 16396-2:2017), which has been technically revised.

The main changes are as follows:

- the normative references clause has been updated;
- a footnote has been added in [Table 1](#).

A list of all parts in the ISO 16396 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

# Plastics — Polyamide (PA) moulding and extrusion materials —

## Part 2: Preparation of test specimens and determination of properties

### 1 Scope

This document specifies the methods of preparation of test specimens and the test methods to be used in determining the properties of polyamide moulding and extrusion materials. It gives the requirements for handling test material and for conditioning both the test material before moulding and the specimens before testing.

This document specifies procedures and conditions for the preparation of test specimens and procedures for measuring properties of the materials from which these specimens are made are given. It lists the properties and test methods that are suitable and necessary to characterize polyamide moulding and extrusion materials.

The properties have been selected from the general test methods in ISO 10350-1. Other test methods in wide use for, or of particular significance to, these moulding and extrusion materials are also included in this document, as are the designatory properties viscosity number and tensile modulus given in ISO 16396-1.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 62, *Plastics — Determination of water absorption*

ISO 75-2, *Plastics — Determination of temperature of deflection under load — Part 2: Plastics and ebonite*

ISO 179-1, *Plastics — Determination of Charpy impact properties — Part 1: Non-instrumented impact test*

ISO 179-2, *Plastics — Determination of Charpy impact properties — Part 2: Instrumented impact test*

ISO 294-1, *Plastics — Injection moulding of test specimens of thermoplastic materials — Part 1: General principles, and moulding of multipurpose and bar test specimens*

ISO 294-4, *Plastics — Injection moulding of test specimens of thermoplastic materials — Part 4: Determination of moulding shrinkage*

ISO 307, *Plastics — Polyamides — Determination of viscosity number*

ISO 527-2, *Plastics — Determination of tensile properties — Part 2: Test conditions for moulding and extrusion plastics*

ISO 1133-2, *Plastics — Determination of the melt mass-flow rate (MFR) and melt volume-flow rate (MVR) of thermoplastics — Part 2: Method for materials sensitive to time-temperature history and/or moisture*

ISO 1183-1, *Plastics — Methods for determining the density of non-cellular plastics — Part 1: Immersion method, liquid pycnometer method and titration method*

ISO 1183-2, *Plastics — Methods for determining the density of non-cellular plastics — Part 2: Density gradient column method*

ISO 1183-3, *Plastics — Methods for determining the density of non-cellular plastics — Part 3: Gas pycnometer method*

ISO 3451-4, *Plastics — Determination of ash — Part 4: Polyamides*

ISO 8256, *Plastics — Determination of tensile-impact strength*

ISO 11357-3, *Plastics — Differential scanning calorimetry (DSC) — Part 3: Determination of temperature and enthalpy of melting and crystallization*

ISO 15512, *Plastics — Determination of water content*

ISO 16396-1, *Plastics — Polyamide (PA) moulding and extrusion materials — Part 1: Designation system, marking of products and basis for specifications*

ISO 20753, *Plastics — Test specimens*

ISO 27547-1, *Plastics — Preparation of test specimens of thermoplastic materials using mouldless technologies — Part 1: General principles, and laser sintering of test specimens*

IEC 60112, *Method for the determination of the proof and the comparative tracking indices of solid insulating materials*

IEC 60243-1, *Electric strength of insulating materials — Test methods — Part 1: Tests at power frequencies*

IEC 62631-2-1, *Dielectric and resistive properties of solid insulating materials — Part 2-1: Relative permittivity and dissipation factor — Technical Frequencies (0,1 Hz - 10 MHz) — AC Methods*

IEC 62631-3-1, *Dielectric and resistive properties of solid insulating materials — Part 3-1: Determination of resistive properties (DC methods) — Volume resistance and volume resistivity — General method*

IEC 62631-3-2, *Dielectric and resistive properties of solid insulating materials — Part 3-2: Determination of resistive properties (DC methods) — Surface resistance and surface resistivity*

IEC 60296, *Fluids for electrotechnical applications — Unused mineral insulating oils for transformers and switchgear*

IEC 60695-11-10, *Fire hazard testing — Part 11-10: Test flames — 50 W horizontal and vertical flame test methods*

### 3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 4 Preparation of test specimens

#### 4.1 Treatment of the material before moulding or laser sintering

Before processing, the material sample shall have reached room temperature. Before processing, the moisture content of the material sample shall not exceed 2 g/kg in the case of PAs having a viscosity number  $\leq 200$  ml/g and not exceed 1 g/kg in the case of PAs having a viscosity number  $> 200$  ml/g. For

PA46, PA6T/66, PA6T/XT, PA6T/6I/66, PA6T/6I, PA6I/6T and PA NDT/INDT, the moisture content shall be less than 1 g/kg.

The moisture content of filled or reinforced materials shall be expressed as a percentage of the total mass of the compound. The moisture content shall be determined in accordance with ISO 15512 and the viscosity number in accordance with ISO 307.

To ensure that the moisture content remains low, it is recommended that the sample material in the feed hopper of the injection-moulding machine be blanketed with a suitable gas (for example, dried air, nitrogen or argon).

Better results can be obtained using a dehumidifier hopper drier.

If test specimens are to be prepared by laser sintering (see [4.3](#) and [Annex A](#)), follow the instructions given in [Annex A](#) for treatment of the material before processing.

## 4.2 Injection moulding

For the acquisition and presentation of comparable data, injection-moulded specimens are used so that valid comparisons between materials can be made. These data represent the most basic approach to the designation of the properties of materials.

Injection-moulded specimens shall be prepared in accordance with ISO 294-1, using the conditions specified in [Table 1](#). Such specimens shall be prepared by injection moulding from dry granules. It is essential that the specimens are always prepared by the same procedure using the same processing conditions. The material shall be kept in sealed, moisture-proof containers until it is required for use.

**NOTE** The ISO 294 series will be revised, defining only the injection-moulding conditions and will refer to ISO 20753 for the dimensions of the specimens. Other International Standards that have hitherto used different designations for the same specimen type will also be revised to bring the designations into line with those in ISO 20753. Many test standards, specifying test specimen or referring to other standards as ISO 3167 and the ISO 294 series, will be revised in due time and also refer to ISO 20753.

Besides injection moulding, other methods are also used to manufacture PA parts, such as extrusion, blow moulding and methods using mouldless technologies. Different methods of manufacture can lead to significantly different properties and it might be useful to measure these properties using test specimens prepared by the same method. For specimen preparation using laser sintering, see [4.3](#).

## 4.3 Laser sintering

Although injection-moulded specimens are the only ones to be used to measure designatory properties, it is sometimes useful to prepare specimens using the same techniques as are used in parts manufacture (see [4.2](#)).

For specimen preparation using laser sintering, [Annex A](#) shall apply.

Table 1 — Conditions for injection moulding of test specimens

| Material <sup>a, b</sup> | Viscosity number <sup>c</sup><br>ml/g | Filler content<br>% | Plasticizer content<br>% | Melt temperature <sup>d</sup><br>°C | Mould temperature <sup>e</sup><br>°C |
|--------------------------|---------------------------------------|---------------------|--------------------------|-------------------------------------|--------------------------------------|
| PA6                      | ≤160                                  | 0                   | 0                        | 250                                 | 80                                   |
|                          | >160 but ≤200                         | 0                   | 0                        | 260                                 | 80                                   |
|                          | >200                                  | 0                   | 0                        | 270                                 | 80                                   |
|                          | ≤120                                  | >0 but ≤70          | 0                        | 270                                 | 80                                   |
|                          | >120 but ≤200                         | >0 but ≤70          | 0                        | 290                                 | 80                                   |
| PA6/66                   | ≤160                                  | 0                   | 0                        | 280                                 | 80                                   |
|                          | >160                                  | 0                   | 0                        | 280                                 | 80                                   |
| PA66                     | ≥100                                  | 0                   | 0                        | 290                                 | 80                                   |
|                          | ≤160                                  | >0 but ≤50          | 0                        | 290                                 | 80                                   |
|                          | ≤160                                  | >50 but ≤70         | 0                        | 300                                 | 100                                  |
| PA66/6                   | ≤200                                  | ≤70                 | 0                        | 290                                 | 80                                   |
| PA46                     | ≤260                                  | ≤70                 | 0                        | 315                                 | 120                                  |
| PA69                     | ≤200                                  | 0                   | 0                        | 270                                 | 80                                   |
| PA610                    | ≤200                                  | 0                   | 0                        | 270                                 | 80                                   |
| PA612                    | ≤250                                  | 0                   | 0                        | 250                                 | 80                                   |
|                          | ≤250                                  | >0 but ≤70          | 0                        | 290                                 | 80                                   |
| PA11                     | ≤150                                  | 0                   | ≥0                       | 210                                 | 80                                   |
|                          | >150 but ≤200                         | 0                   | ≥0                       | 230                                 | 80                                   |
|                          | >200 but ≤240                         | 0                   | ≥0                       | 250                                 | 80                                   |
|                          | ≤130                                  | >0 but ≤30          | 0                        | 220                                 | 80                                   |
|                          | ≤130                                  | >30 but ≤50         | 0                        | 230                                 | 80                                   |
|                          | >130 but ≤240                         | >0 but ≤20          | 0                        | 250                                 | 80                                   |
|                          | >130 but ≤240                         | >20 but ≤50         | 0                        | 260                                 | 80                                   |
|                          | >240                                  | >50                 | 0                        | 270                                 | 80                                   |
| PA12                     | ≤130                                  | ≤10                 | ≤5                       | 200                                 | 80                                   |
|                          | >130 but ≤200                         | ≤10                 | ≤5                       | 220                                 | 80                                   |
|                          | >200                                  | ≤10                 | ≤5                       | 240                                 | 80                                   |
|                          | ≤130                                  | 0                   | >5                       | 200                                 | 60                                   |
|                          | >130 but ≤200                         | 0                   | >5                       | 210                                 | 60                                   |
|                          | ≤200                                  | 0                   | >5                       | 220                                 | 60                                   |
|                          | ≤130                                  | >10 but ≤30         | 0                        | 230                                 | 80                                   |
|                          | ≤130                                  | >30 but ≤70         | 0                        | 250                                 | 80                                   |
|                          | >130 but ≤240                         | >10 but ≤30         | 0                        | 240                                 | 80                                   |
|                          | >130 but ≤240                         | >30 but ≤70         | 0                        | 260                                 | 80                                   |
|                          | >240                                  | >70                 | 0                        | 270                                 | 80                                   |

<sup>a</sup> For the definition of PA and the symbols used to indicate the chemical structure of polyamide materials, see ISO 472 and ISO 16396-1, respectively.

<sup>b</sup> For the polyamides mentioned in this table, with the exception of PA46, PA6T/66, PA6T/XT, PA6T/6I, PA6I/6T, PA6T/6I/66, PA66/6I and PA9T, the injection velocity shall be 200 mm/s ± 100 mm/s. For PA46, PA6T/66, PA6T/XT, PA6T/6I, PA6I/6T, PA6T/6I/66, PA66/6I and PA9T, the injection velocity shall be 300 mm/s ± 100 mm/s.

<sup>c</sup> Preferred reference solvent according to ISO 307.

<sup>d</sup> Or the temperature and range recommended by the supplier.

<sup>e</sup> For low crystalline PA6/66 grades a mould temperature of 80 °C can cause demoulding problems. For these PA grades, a mould temperature of 50 °C, or the temperature recommended by the supplier, is recommended. The mould temperature shall be reported.

Table 1 (continued)

| Material <sup>a, b</sup> | Viscosity number <sup>c</sup><br>ml/g | Filler content<br>% | Plasticizer content<br>% | Melt temperature <sup>d</sup><br>°C | Mould temperature <sup>e</sup><br>°C |
|--------------------------|---------------------------------------|---------------------|--------------------------|-------------------------------------|--------------------------------------|
| PA MXD6                  | ≤130                                  | 0                   | 0                        | 250                                 | 130                                  |
|                          | >130 but ≤160                         | 0                   | 0                        | 260                                 | 130                                  |
|                          | ≤130                                  | >0 but ≤50          | 0                        | 270                                 | 100                                  |
|                          | ≤130                                  | >50 but ≤70         | 0                        | 280                                 | 130                                  |
|                          | >130 but ≤160                         | >0 but ≤50          | 0                        | 280                                 | 130                                  |
|                          | >130 but ≤160                         | >50 but ≤70         | 0                        | 290                                 | 130                                  |
| PA6T/XT                  | ≤160                                  | ≤70                 | 0                        | 325                                 | 150                                  |
| PA6T/66                  | ≤160                                  | ≤70                 | 0                        | 330                                 | 120                                  |
| PA6T/6I                  | ≤200                                  | ≤70                 | 0                        | 340                                 | 140                                  |
| PA6I/6T                  | ≤200                                  | ≤70                 | 0                        | 325                                 | 130                                  |
| PA6T/6I/66               | ≤200                                  | ≤70                 | 0                        | 325                                 | 130                                  |
| PA66/6I                  | ≤160                                  | ≤70                 | 0                        | 290                                 | 90                                   |
| PA9T                     | ≤200                                  | ≤70                 | 0                        | 320                                 | 120                                  |
| PA NDT/INDT              | ≤160                                  | 0                   | 0                        | 280                                 | 80                                   |
|                          | ≤120                                  | >0 but ≤50          | 0                        | 300                                 | 80                                   |

<sup>a</sup> For the definition of PA and the symbols used to indicate the chemical structure of polyamide materials, see ISO 472 and ISO 16396-1, respectively.

<sup>b</sup> For the polyamides mentioned in this table, with the exception of PA46, PA6T/66, PA6T/XT, PA6T/6I, PA6I/6T, PA6T/6I/66, PA66/6I and PA9T, the injection velocity shall be 200 mm/s ± 100 mm/s. For PA46, PA6T/66, PA6T/XT, PA6T/6I, PA6I/6T, PA6T/6I/66, PA66/6I and PA9T, the injection velocity shall be 300 mm/s ± 100 mm/s.

<sup>c</sup> Preferred reference solvent according to ISO 307.

<sup>d</sup> Or the temperature and range recommended by the supplier.

<sup>e</sup> For low crystalline PA6/66 grades a mould temperature of 80 °C can cause demoulding problems. For these PA grades, a mould temperature of 50 °C, or the temperature recommended by the supplier, is recommended. The mould temperature shall be reported.

## 5 Conditioning of test specimens

### 5.1 Conditioning states of the test specimen

Separate sets of test specimens for determination of properties shall be conditioned in two different ways: one set dry-as-moulded and the other in the moist state.

Properties shall be determined on specimens in the dry-as-moulded state, or on specimens in the moist state, or on specimens in both states. The state of the specimens shall be stated in the test report.

### 5.2 Dry-as-moulded (DAM) state

Test specimens are considered to be in the DAM state when they have been placed, immediately after moulding, in a moisture-proof container and stored at 23 °C ± 2 °C for at least 24 h. The moisture content of DAM specimens shall not exceed 2 g/kg. The intentional addition of water to reach this moisture content is not allowed, nor is drying of specimens with moisture contents above this limit.

To maintain absorbed moisture at a low level, DAM specimens shall be tested in as short a time as possible (maximum 15 min) after removal from the moisture-proof container.

Annealing specimens prior to testing is not allowed.

### 5.3 Moist state

Test specimens are considered to be in the moist state when they have been conditioned at 23 °C and 50 % relative humidity until equilibrium has been reached (see ISO 291). The applied standard atmosphere class, or the applied tolerances, shall be stated in the test report.

NOTE The different classes of standard atmosphere correspond to different tolerance levels for the temperature and relative humidity (RH), as mentioned in ISO 291. The standard atmosphere classes for 23 °C/50 % RH are as follows:

- Class 1: (23 ± 1) °C/(50 ± 5) % RH;
- Class 2: (23 ± 2) °C/(50 ± 10) % RH.

The tolerances apply to the specimen-storage space in a test enclosure or conditioning enclosure. The relative-humidity tolerance includes real tolerances on dew points and allowance for the usual errors and drift in control equipment and hygrometers.

Test specimens which have been conditioned by the procedure for accelerated conditioning of polyamides specified in ISO 1110 are also considered to be in the moist state. The moisture content shall be reported.

## 6 Determination of properties

In order to obtain reproducible and comparable test results, the methods of preparation and conditioning, the specimen dimensions and the test procedures specified in this document, and in particular, [Table 2](#) and [Table 3](#), shall be used. Values determined will not necessarily be identical to those obtained using specimens of different dimensions or prepared using different procedures.

For all ISO test methods applied in this document (see [Table 2](#) and [Table 3](#)), and in which is referred to the ISO 294 series and/or ISO 3167 for the designation and dimensions of the test specimen, ISO 20753 shall be used instead.

All tests shall be carried out in the standard atmosphere of 23 °C ± 2 °C and (50 ± 10) % relative humidity unless specifically stated otherwise in [Table 2](#) and [Table 3](#).

[Table 2](#) is compiled from ISO 10350-1, and the properties listed are those which are appropriate to polyamide moulding and extrusion materials. These properties are those considered useful for comparisons of data generated for different thermoplastics.

[Table 3](#) contains those properties, not found specifically in [Table 2](#), which are in wide use or of particular significance in the practical characterization of polyamide moulding and extrusion materials.

**Table 2 — Standard properties and test conditions (selected from ISO 10350-1)**

| Property                             | Unit | Standard  | Specimen type<br>(dimensions in mm) | Specimen<br>preparation | Test conditions and supplementary instructions |
|--------------------------------------|------|-----------|-------------------------------------|-------------------------|------------------------------------------------|
| <b>Rheological properties</b>        |      |           |                                     |                         |                                                |
| Moulding shrinkage of thermoplastics | %    | ISO 294-4 | 60 × 60 × 2                         | M,<br>DAM               | Parallel and normal                            |
| <b>Mechanical properties</b>         |      |           |                                     |                         |                                                |
| Tensile modulus                      | MPa  | ISO 527-2 | ISO 20753<br>Type A1                | M,<br>DAM + Moist       | Test speed 1 mm/min                            |

Table 2 (continued)

| Property                             | Unit              | Standard                  | Specimen type<br>(dimensions in mm)                                              | Specimen<br>preparation | Test conditions and supplementary instructions                                                                                                 |
|--------------------------------------|-------------------|---------------------------|----------------------------------------------------------------------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Charpy unnotched impact strength     | kJ/m <sup>2</sup> | ISO 179-1<br>or ISO 179-2 | 80 × 10 × 4,<br>ISO 20753 Centre<br>Type A1                                      | M,<br>DAM + Moist       | Method 1eU<br>Edgewise impact<br>Also record type of failure                                                                                   |
| Charpy notched impact strength       | kJ/m <sup>2</sup> |                           | 80 × 10 × 4,<br>ISO 20753 Centre<br>Type A1<br>Machined V-notch,<br>r = 0,25     | M,<br>DAM + Moist       | Method 1eA<br>Edgewise impact<br>Also record type of failure                                                                                   |
| Tensile notched impact strength      | kJ/m <sup>2</sup> | ISO 8256                  | 80 × 10 × 4,<br>ISO 20753 Centre<br>Type A1<br>Machined double<br>V-notch, r = 1 | M,<br>DAM + Moist       | Only to be quoted if fracture cannot be obtained with notched Charpy test                                                                      |
| <b>Thermal properties</b>            |                   |                           |                                                                                  |                         |                                                                                                                                                |
| Temperature of deflection under load | °C                | ISO 75-2                  | 80 × 10 × 4,<br>ISO 20753 Centre<br>Type A1                                      | M, DAM                  | 0,45 MPa and 1,80 MPa,<br>Flatwise                                                                                                             |
| Burning behaviour                    |                   | IEC 60695-11-10           | 125 × 13 × 3<br>or alternative thicknesses < 3                                   | M, DAM                  | Record one of the classifications V-0, V-1, V-2, HB40 or HB75                                                                                  |
| Melting temperature                  | °C                | ISO 11357-3               | Moulding compound                                                                | —                       | Record peak melting temperature<br>Use 10 °C/min or 20 °C/min                                                                                  |
| <b>Electrical properties</b>         |                   |                           |                                                                                  |                         |                                                                                                                                                |
| Relative permittivity                | —                 | IEC 62631-2-1             | ≥ 60 × ≥ 60 × 2                                                                  | M,<br>DAM + Moist       | Frequency 100 Hz and 1 MHz (compensate for electrode edge effects)                                                                             |
| Dissipation factor                   | —                 |                           |                                                                                  |                         |                                                                                                                                                |
| Volume resistivity                   | Ω·m               | IEC 62631-3-1             | ≥ 60 × ≥ 60 × 2                                                                  | M,<br>DAM + Moist       | Voltage 500 V                                                                                                                                  |
| Surface resistivity                  | Ω                 | IEC 62631-3-2             |                                                                                  |                         |                                                                                                                                                |
| Electric strength                    | kV/mm             | IEC 60243-1               | ≥ 60 × ≥ 60 × 1<br>and ≥ 60 × ≥ 60 × 2                                           | M,<br>DAM + Moist       | Use 20 mm diameter spherical electrodes<br>Immerse in transformer oil in accordance with IEC 60296<br>Use a voltage application rate of 2 kV/s |
| Comparative tracking index           | —                 | IEC 60112                 | ≥ 15 × ≥ 15 × 4                                                                  | M,<br>DAM               | Use solution A                                                                                                                                 |
| <b>Other properties</b>              |                   |                           |                                                                                  |                         |                                                                                                                                                |
| Water absorption                     | %                 | ISO 62                    | 60 × 60 × 2                                                                      | M,<br>DAM               | 24 h immersion in water at 23 °C                                                                                                               |

Table 2 (continued)

| Property                                                                       | Unit              | Standard                                           | Specimen type<br>(dimensions in mm) | Specimen<br>preparation | Test conditions and supplementary instructions |
|--------------------------------------------------------------------------------|-------------------|----------------------------------------------------|-------------------------------------|-------------------------|------------------------------------------------|
| Density                                                                        | kg/m <sup>3</sup> | ISO 1183-1<br>or<br>ISO 1183-2<br>or<br>ISO 1183-3 | ISO 20753<br>Centre Type A1         | M,<br>DAM               | ISO 1183-1, Immersion method                   |
| M : Injection moulding.<br>DAM : Dry-as-moulded state.<br>Moist : Moist state. |                   |                                                    |                                     |                         |                                                |

Table 3 — Specialized properties and test conditions

| Property                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Unit                                      | Standard   | Specimen type<br>(dimensions in mm) | Specimen preparation | Test conditions and supplementary instructions                                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|------------|-------------------------------------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mechanical properties                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                           |            |                                     |                      |                                                                                                                                                      |
| Yield stress                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | MPa                                       | ISO 527-2  | ISO 20753<br>Type A1                | M,<br>DAM + Moist    | Test speed:<br><br>Unfilled materials: 50 mm/min<br><br>Reinforced/filled materials<br>5 mm/min                                                      |
| Yield strain                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | %                                         |            |                                     |                      |                                                                                                                                                      |
| Nominal strain at break                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | %                                         |            |                                     |                      |                                                                                                                                                      |
| Stress at break                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | MPa                                       |            |                                     |                      |                                                                                                                                                      |
| Strain at break                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | %                                         |            |                                     |                      |                                                                                                                                                      |
| Other properties                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                           |            |                                     |                      |                                                                                                                                                      |
| Ash                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | %                                         | ISO 3451-4 | Moulding compound                   | —                    | Only for filled or reinforced grades                                                                                                                 |
| Moisture content                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | %                                         | ISO 15512  | Moulding compound                   | —                    |                                                                                                                                                      |
| Viscosity number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | ml/g                                      | ISO 307    | Moulding compound                   | —                    | See conditions given in ISO 16396-1                                                                                                                  |
| Melt volume-flow rate (MVR) or melt mass- flow rate (MFR) <sup>a</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | cm <sup>3</sup> /10 min<br>or<br>g/10 min | ISO 1133-2 | Moulding compound                   | —                    | Moisture content ≤0,2 g/kg<br><br>Test temperature:<br>225 °C, 250 °C, 275 °C or 300 °C<br><br>Load (kg):<br>1,2 kg, 2,16 kg, 5 kg, 10 kg or 21,6 kg |
| <sup>a</sup> Drying conditions:<br>— Vacuum oven with N <sub>2</sub> flow: temperature 75 °C to 85 °C, pressure < 20 kPa, time ≤48 h.<br>— Vacuum oven without N <sub>2</sub> flow: temperature < 100 °C, pressure < 5 kPa, time ≤48 h.<br><br>Other drying conditions may be used or might even be necessary to achieve a moisture content ≤0,2 g/kg. Sample storage moisture-proof container or container with a non-hermetically closing lid stored in a desiccator.<br><br>M : Injection moulding.<br>DAM : Dry-as-moulded state.<br>Moist : Moist state. |                                           |            |                                     |                      |                                                                                                                                                      |