



**International
Standard**

ISO 16454

**Space systems — Structural design
— Stress analysis requirements**

*Systèmes spatiaux — Conception des structures — Exigences
relatives à l'analyse des contraintes*

**Second edition
2024-03**

STANDARDSISO.COM : Click to view the full PDF of ISO 16454:2024



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	5
4.1 General	5
4.2 Basic data	5
4.2.1 General	5
4.2.2 Structural configuration, geometry and gauges	5
4.2.3 Structural materials and their properties	6
4.2.4 Loading data	7
4.3 Analysis methodology and software	7
4.3.1 Analysis methodology	7
4.3.2 Software verification	7
4.4 Structural mathematical model	8
4.4.1 General	8
4.4.2 Boundary conditions	8
4.5 Structure mathematical model check	8
4.6 Failure modes	8
4.6.1 General	8
4.6.2 Detrimental yielding	8
4.6.3 Rupture	9
4.6.4 Collapse	9
4.6.5 Local buckling	9
4.7 Critical location analysis	9
4.8 Determination margins of safety	9
4.9 Report	10
Annex A (informative) Structural mathematical model check	11
Bibliography	14

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 14, *Space systems and operations*.

This second edition cancels and replaces the first edition (ISO 16454:2007), which has been technically revised.

The main changes are as follows:

- updated the terms and definitions;
- updated requirements in [Clause 4](#).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

From the beginning of the space age, structural integrity verification has been one of the main fields of activity of experts in the domain of mechanics. Mission failure and potential danger to human life, expensive ground constructions and other public and private properties are the most probable consequences of a space structural integrity failure. Static strength is one of the most important critical conditions for structural integrity analysis. It is usually the main criterion for space structure weight evaluation. If the space structure is too heavy, the mission can be extremely expensive or impossible to achieve. If the space structure is under-designed, it can result in mission failure, structural failure, leading to high risk associated with safety of life, and loss of expensive hardware and other properties. It is therefore necessary to specify unique requirements for static strength analysis in order to provide cost-effective design and light-weight, reliable and low-risk structures for space application.

STANDARDSISO.COM : Click to view the full PDF of ISO 16454:2024

STANDARDSISO.COM : Click to view the full PDF of ISO 16454:2024

Space systems — Structural design — Stress analysis requirements

1 Scope

This document provides requirements for the determination of maximum stress and corresponding margin of safety under loading and defines criteria for static strength failure modes, such as rupture, collapse and detrimental yielding. This document does not cover critical-conditions-induced fatigue, creep and crack growths. Notwithstanding these limitations in scope, the results of stress calculations based on the requirements of this document are applicable to other critical condition analysis.

This document is applicable to the determination of the stress/strain distribution and margins of safety in launch vehicles and spacecraft load-bearing elements design. Liquid propellant engine structures, solid propellant engine nozzles and the solid propellant itself are not covered, but liquid propellant tanks, pressure vessels and solid propellant cases are within the scope of this document.

In accordance with the requirements of this document, the models, methods and procedures for stress calculation can also be applicable to the displacements and deformation calculation, as well as the calculation of loads, applied to substructures and structural elements under consideration. When this document is applied, it is assumed that temperature distribution has been determined and is used as input data.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 14622, *Space systems — Structural design — Loads and induced environment*

ISO 14623, *Space systems - Pressure vessels and pressurized structures — Design and operation*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

A-basis allowable

mechanical strength value above which at least 99 % of the population of values is expected to fall, with a confidence level of 95 %

3.2

allowable load

allowable stress

allowable strain

maximum *load* (3.18) that can be accommodated by a material or *structure* (3.31) without potential *rupture* (3.25), *collapse* (3.5) or *detrimental yielding* (3.12) in a given environment

Note 1 to entry: The load can imply the corresponding stress or strain.

Note 2 to entry: Allowable loads commonly correspond to the statistically based minimum ultimate strength, buckling strength and yield strength, respectively.

Note 3 to entry: The allowable load shall be determined in accordance with the criteria formulated in [4.6](#) and the requirements of [4.2](#).

3.3

basic data

input data required to perform *stress analysis* ([3.30](#)) and to determine margins of safety

3.4

B-basis allowable

mechanical strength value above which at least 90 % of the population of values is expected to fall, with a confidence level of 95 %

3.5

collapse

failure mode induced by quasi-static compression, shear or combined stress, accompanied by very rapid irreversible loss of *load* ([3.18](#)) resistance capability

3.6

composite material

combination of materials different in composition or form on a macro scale

Note 1 to entry: The constituents retain their identities in the composite.

Note 2 to entry: The constituents can normally be physically identified, and there is an interface between them.

3.7

creep

process of a permanent material deformation resulting from long duration under constant or slowly altered *load* ([3.18](#))

Note 1 to entry: The ultimate creep deformation, corresponding to the loss of material integrity, is often much larger than the ultimate deformation in the case of short time loading.

3.8

critical condition

most severe environmental condition in terms of *load* ([3.18](#)) and temperature, or combination thereof, imposed on a *structure* ([3.31](#)), system, subsystem or component during its service life

3.9

critical location

structural point at which *rupture* ([3.25](#)), *local buckling* ([3.20](#)) or *detrimental yielding* ([3.12](#)) first leads to structural failure

3.10

design safety factor

coefficient by which *limit loads* ([3.17](#)) are multiplied in order to account for the statistical variations of *loads* ([3.18](#)) and *structure* ([3.31](#)) resistance, and inaccuracies in the knowledge of their statistical distributions

3.11

destabilizing load

load ([3.18](#)) that produces compressive stress at *critical location* ([3.9](#))

3.12

detrimental yielding

⟨metallic structures⟩ permanent deformation specified at the system level to be detrimental

3.13**development test**

test to provide design information that can be used to check the validity of analytic technique and assumed design parameters, to uncover unexpected system response characteristics, to evaluate design changes, to determine interface compatibility, to prove qualification and acceptance procedures and techniques, to check manufacturing technology, or to establish accept/reject criteria

3.14**flight-type hardware test**

test of a flight *structure* (3.31) article, a protoflight model, a representative special model or a structural element fabricated with the same or close to flight hardware technology

3.15**gauge**

thickness or other *structure* (3.31) dimension that affects stress levels and/or *margin of safety* (3.21) significantly

3.16**knockdown coefficient**

empirical coefficient, other than *design safety factor* (3.10), used to determine analytically actual or *allowable loads* (3.2), as well as allowable stresses or strains, and defined on the basis of test results of flight-type *structures* (3.31), model structures or structural elements as compared with corresponding *stress analysis* (3.30) data

3.17**limit load**

maximum *load* (3.18) that can be expected during life cycle of the *structure* (3.31)

3.18**load**

volume force or moment, concentrated and/or distributed over the *structure* (3.31) surfaces or structure, caused by its interaction with environment and adjacent parts of vehicle, and accelerations

Note 1 to entry: This includes *pressure* (3.23), external load and enforced displacement acted at considered structural element, pretension, inertial load caused by accelerations and thermal gradient.

3.19**loading case**

particular condition described in terms of *loads* (3.18), pressures and temperatures combinations, which can occur for some parts of *structure* (3.31) at the same time during its service life

3.20**local buckling**

failure mode that occurs when an alternative equilibrium mode of a structural element exists and can lead to *detrimental yielding* (3.12) or *rupture* (3.25) of that element

Note 1 to entry: Local buckling is not considered as a *critical condition* (3.8) if the *structure* (3.31) can be operated normally during and after loading.

3.21**margin of safety**

M_S

$$M_S = \left[\frac{L_A}{(f \times L_L)} \right] - 1$$

where

L_A is the *allowable load* (3.2) under specified functional conditions [e.g. yield, *rupture* (3.25), *collapse* (3.5), *local buckling* (3.20)];

L_L is the *limit load* (3.17);

f is the *design safety factor* (3.10)

Note 1 to entry: Load can imply corresponding stress or strain.

3.22

minimum allowable

minimum material mechanical properties warranted by the supplier

3.23

pressure

external *load* (3.18) caused by fluid action on a structural surface

Note 1 to entry: The terms “pressure” and “load” are sometimes referred to simultaneously in this document.

3.24

primary structure

part of a vehicle that carries the main *loads* (3.18) and/or defines the fundamental resonance frequencies

3.25

rupture

loss of integrity by *structure* (3.31) material differed from fatigue and ultimate *creep* (3.7) deformation attainment, which can prevent the structure from withstanding *load* (3.18) combinations

3.26

semi-finished item

product that is used for *structure* (3.31) manufacturing or assembling

EXAMPLE Sheets, plates, profiles, strips.

3.27

stabilizing load

load (3.18) which decreases compressive stresses if applied in conjunction with *destabilizing loads* (3.11)

3.28

static strength

property of a *structure* (3.31), characterized by its capability to withstand *loads* (3.18) and temperature combinations without *rupture* (3.25), *collapse* (3.5), detrimental *local buckling* (3.20) and *detrimental yielding* (3.12)

3.29

strength failure mode

condition of a *structure* (3.31) or a structural element considered as a *critical condition* (3.8) in accordance with *stress analysis* (3.30) results

3.30

stress analysis

analytical procedure to determine structure stress or strain distribution, deformations and margins of safety

3.31

structure

primary structure (3.24), *unit* (3.34) attachments, *pressure* (3.23) or *loads* (3.18) carrying elements of pressure vessels, loads carrying elements of appendages (solar panels and antennas)

3.32

structural mathematical model

analytical or digital representation of the *structure* (3.31), which, as it is considered, could provide an adequate description of structure behavior when *loads* (3.18), *pressure* (3.23) and temperature are applied

Note 1 to entry: The model should provide adequate description of the structure's response under loads/pressures/temperatures.

3.33

ultimate load

limit load (3.17) multiplied by ultimate *design safety factor* (3.10) used for strength verification

3.34

unit

part of a vehicle which is designed mainly to provide vehicle functioning and which differs from a *structure* (3.31)

4 Requirements

4.1 General

For structures used in space systems, such as launch and space vehicles, the stress analysis and corresponding determination of margin of safety for various static strength failure modes shall meet the requirements specified in this document.

Basic data, structural models, methods for stress analysis and strength criteria are considered critical for the successful completion of these procedures.

Unless otherwise noted in 4.2 to 4.9 there are no limitations set out in this document that restrict the use of results from stress calculations for other applications.

4.2 Basic data

4.2.1 General

Basic data used for space structure stress analysis shall meet the requirements included in this subclause.

Basic data shall include all of the following information:

- structural configuration, geometry and gauges;
- structural materials and their properties;
- loading case list, load and temperature combinations, and corresponding design safety factors for every loading case.

4.2.2 Structural configuration, geometry and gauges

4.2.2.1 Structural configuration, geometry and gauge data (with tolerances) used for stress analysis shall correspond to drawings representing a relevant design stage.

4.2.2.2 The following factors shall be taken into account in choosing a particular thickness (minimum or nominal) for stress analysis:

- conservatism of applied safety factors and knockdown coefficients;
- correspondence between applied thickness and procedure for knockdown coefficient determination;
- stress analysis results dependence on and sensitivity to thickness;

- simplification of stress analysis procedure application;
- linear or non-linear behaviour.

4.2.2.3 Structural configuration, geometry and gauge data (with tolerance) shall be provided to develop a substantial analytical model and to perform stress analysis of a structure.

4.2.3 Structural materials and their properties

4.2.3.1 This subclause (4.2.3) refers to individual material properties both for structure and any individual part of it (junctions) for which the stress analysis require allowable values.

4.2.3.2 A list of materials used for the fabrication of the structure and its elements shall correspond to the design and technology documentation. The information about types of materials, semi-finished items and technology processes shall be provided to evaluate possible variations of their properties used for stress analysis and determine margins of safety.

4.2.3.3 Material properties used for stress analysis and determination of margin of safety shall take into account manufacturing processes, temperature and other significant environmental effects, including possible aging during lifetime.

If appropriate data are not available, special development tests shall be conducted to evaluate corresponding properties.

4.2.3.4 Appropriate ultimate and yield strength (for metal only) material properties shall be used for margin of safety calculations. "A-basis allowable" values shall be used where failure of a single load path would result in loss of structural integrity. "B-basis allowable" values may be used for redundant structural elements where failure of one element would result in a safe redistribution of applied loads to other elements.

When it is difficult to obtain "A-basis allowable" and "B-basis allowable" values, the minimum allowable values warranted by the material supplier and approved by the procuring agency may be used.

Nominal modulus of elasticity and Poisson's ratio shall be used for the stress analysis.

4.2.3.5 If inertia loads are applied and corresponding basic data are described in terms of accelerations or gravity constant, inertia material properties and masses of units and appendages data shall be provided to determine those inertia loads adequately.

Nominal material inertia properties and nominal units and appendages masses and parameters of their arrangements shall be used for stress analysis. When an attachment can be used for different types of units or appendages, nominal values for the most unfavourable type of equipment shall be taken into account.

When equipment inertia scattering is considered significant, the most unfavourable combinations of units and appendages masses and parameters of their arrangements shall be used for local stress analysis in areas near corresponding attachments.

4.2.3.6 Temperature effects on material and physical properties and thermal stresses shall be considered.

When appropriate, thermal stresses for materials with high ultimate strain (as compared with thermal expansion) and low yield strength may not be taken into account. Alternatively, for such materials, it is allowed to consider the limit (without the application of safety factor) thermal stress.

4.2.3.7 When loading which exceeds an elastic limit is permitted and loads values are sufficient to cause significant nonlinear material behaviour, then corresponding stress-strain dependencies shall be used for stress analysis.

4.2.4 Loading data

Load data shall include:

- list of loading cases;
- load and temperature combinations for every loading case.

Load data shall include the ranges in which loads and temperatures can vary simultaneously for every loading case and every loading combination. Maximum loads values shall be limit loads.

Unless otherwise specified, load data shall meet the requirements of ISO 14622. Unless otherwise specified, load/pressure data for metallic pressurized systems and overwrapped pressure vessels made of composite materials shall meet the requirements of ISO 14623.

Unless otherwise specified, design safety factors shall meet the requirements of ISO 14622, where only their minimum values are established. Safety coefficients for beryllium structures should be adopted according to ISO 10786. Design safety factors used for stress analysis and determination of margin of safety may be higher. In this case their values shall be specified by a contract, taking into account national industry specifications, relevant experience and other design and verification requirements. Unless otherwise specified, design safety factors for metallic pressurized systems and overwrapped pressure vessels made of composite materials shall meet the requirements of ISO 14623.

Subject to ISO 14622, the following types of external loads shall be taken into account, which can be generally classified as:

- mechanical loads (quasi static or equivalent quasi-static loads for stresses analysis);
- pressure loads (or equivalent quasi-static pressure);
- thermal loads;
- pretension loads.

4.3 Analysis methodology and software

4.3.1 Analysis methodology

4.3.1.1 Either closed form structural analysis techniques or numerical methods, such as finite element, separately or in combination, can be used to perform stress analysis and calculation of margins of safety (e.g. stresses are calculated with a numerical method and margins of safety corresponding to structural element local buckling are determined as closed form solutions).

4.3.1.2 When numerical methods are applied, the required accuracy shall be demonstrated.

4.3.1.3 Commonly used stress analysis methods shall be verified by comparing calculation results and known test data.

4.3.2 Software verification

4.3.2.1 Software used for stress analysis shall be verified by comparing the results of calculation with analytical results and/or results obtained by using another verified software.

NOTE Verification is not required for current international standard software.

4.3.2.2 Verification procedures shall take into account typical structural models, boundary conditions, loading conditions, materials applied, convergence and stability of numerical methods used.

When knockdown coefficients are used as input data for a software application, the software verification shall be conducted without accounting for the comparison with purely analytical results.

4.4 Structural mathematical model

4.4.1 General

When applied for stress analysis, the structural mathematical model shall be developed using appropriate experience based on the results of flight-type hardware tests.

If such experience is not available or considered not applicable to a particular case, special development tests shall be conducted for structural model validation.

The structural mathematical model shall be developed to take into account the structural configuration, materials applied, loading, environmental conditions and type of analysis.

Structural mathematical models shall be checked for correlation with available test data.

4.4.2 Boundary conditions

Boundary conditions are an integral part of the structural analytical model. The adjacent structures which influence load transmission, stress distribution and collapse mode shall be evaluated to provide adequate loading conditions for the structure under consideration. When any applied boundary conditions do not represent the actual stress distribution, the analytical model of the adjacent structure shall be developed and added to the model of the considered structure.

Notwithstanding that requirement, simplification of boundary conditions is permitted, such as reducing to conservative conditions or to effective stiffness; however, it shall be demonstrated that those simplifications provide a conservative result.

In general, the adjacent structure model shall be developed to be the same as the one for the structure under consideration, except that only stiffness and its load transmission should be modelled properly.

4.5 Structure mathematical model check

When computerized numerical methods are used for stress analysis, the structural mathematical model checks shall be conducted. The model in [Annex A](#) should be followed as far as possible.

4.6 Failure modes

4.6.1 General

The strength criteria application shall be based on the appropriate experience, including flight-type hardware testing with accounting for basic data, structural model, knockdown coefficients and fabrication technology. When appropriate experience is not available or in case of doubt, special development tests shall be conducted for criteria validation.

4.6.2 Detrimental yielding

The margin of safety for detrimental yielding failure mode shall be determined for prescribed load combinations presented in loading data. It shall be taken into account that a detrimental yielding failure mode occurs when stress (strain) levels in the prescribed locations are equal to, or exceed, the corresponding yield material properties.

4.6.3 Rupture

Margins of safety for rupture failure mode shall be determined for any load combination presented in the loading data.

It shall be taken into account that a rupture failure mode occurs when stress (strains) levels in any location of the structure are equal to, or exceed, the corresponding ultimate material properties. When relevant and justified, more sophisticated rupture criteria may be used.

4.6.4 Collapse

Margins of safety shall be determined for the collapse failure mode if compressive and/or shear stresses can occur, when loads are varied in specified ranges.

Criterion for this failure mode is the result of an appropriate buckling analysis application that collapse occurs for a given load combination. For collapse analysis, the initial deformations due to manufacturing operations and thermal deformations due to temperature gradients shall be taken into account. They may be taken into account by the application of corresponding knockdown coefficients.

4.6.5 Local buckling

When not detrimental, post buckled structures are acceptable. Local buckling is not considered as a critical condition if the structure can be operated normally during and after loading. Margins of safety for local buckling of all structural parts shall be determined if compressive and/or shear stresses can occur in these parts, when loads are varied within specified ranges. If the margin of safety is below zero for a part (or parts) of the structure and local buckling is not considered as failure mode, and if it is acceptable at system level, margins of safety for other failure modes shall be determined with buckled elements accounted for.

The criterion for this failure mode is the result of an appropriate buckling analysis application, that local buckling occurs for given stresses combination. For local buckling analysis, the initial deformations due to manufacturing shall be taken into account. They may be taken into account by applying corresponding knockdown coefficients.

4.7 Critical location analysis

Loading conditions and stress distribution analysis shall be carried out to define critical locations where material or structural elements are most sensitive to a failure mode attainment.

When margins of safety are determined for every critical location, the most unfavourable combinations of loads, pressures and temperatures in frames of specified ranges shall be accounted for.

4.8 Determination margins of safety

4.8.1 Margins of safety (M_S) shall be calculated according to 3.21, where L_A shall be determined in accordance with the criteria stated in 4.6 and the requirements of 4.2.

The application of design safety factors is based on the integral accounting of many different issues, such as loads statistical distributions, accuracy of loads and stress analysis models, manufactory technology level, capabilities of test methods and facilities to provide adequate loading conditions, etc.

Margins of safety express the margin of the ultimate load (f^*L_L) against the allowed load. Load may mean corresponding stress or strain. In the case of significant influence of residual stress, this stress shall be taken into account when the margin of safety is determined.

4.8.2 For collapse and local buckling, failure mode stabilizing loads shall be accounted for in conjunction with design safety factor of 1,0. If not otherwise specified, minimum values of stabilizing loads (in the prescribed ranges) shall be used instead of maximum ones in these cases.

4.8.3 Margins of safety shall be non-negative for every loading case and loading combination specified in basic data to demonstrate that a structure meets strength requirements.

4.8.4 As an alternative approach, a reserve factor, (η), may be determined according to [Formula \(1\)](#).

$$\eta = \frac{L_A}{(f \times L_L)} = M_S + 1 \quad (1)$$

The requirement $\eta \geq 1,0$ is mathematically equivalent to the requirement formulated in [4.8.3](#).

4.9 Report

As a result of the stress analysis activity, a stress analysis report shall be issued. The report shall consist of:

- basic data, including:
 - status of structure configuration, geometry, gauges, materials;
 - structural configuration, geometry and gauges;
 - structure materials and their properties;
 - limit loads/pressures/temperatures for every loading case considered;
 - safety factors for every loading case and structure elements considered;
- structural mathematical model description, including:
 - rationales for its choice;
 - boundary conditions;
 - structural mathematical model checks and their results;
 - foundation of closed form solutions applied;
 - failure modes considered;
 - strength criteria applied;
 - description or references related to methods and software applied;
- summary of significant analysis results including:
 - information on structural element considered;
 - loading case;
 - failure mode;
 - safety factor corresponding to failure mode;
 - margin of safety (or reserve factor);
 - contribution of main loads in the margin of safety (if applicable).

Any additional margins applied shall be clearly indicated in the report.

Annex A (informative)

Structural mathematical model check

A.1 General

When computerized numerical methods are used for stress analysis, the structural mathematical model checks specified in [A.2](#) to [A.12](#) should be followed as far as possible.

A.2 Mass check

It should be checked that the total mass of the mathematical model does not differ from mass indicated in approved system documentation by more than the value of mass scattering allowed. A difference less than 1,0 % is preferable.

A.3 Centre of gravity check

It should be checked that the centre of gravity of the mathematical model does not differ from that indicated in approved system documentation by more than the value of centre of gravity scattering allowed. A difference less than 1,0 % of a corresponding dimension in an analysed structure, as measured along any Cartesian system axis, is preferable.

A.4 Inertia check

It should be checked that inertia tensor elements values of the mathematical model do not differ from values indicated in approved system documentation by more than values of inertia scattering allowed. A difference less than 3,0 % of corresponding inertia tensor elements value is preferable.

A.5 Free-free check

To conduct this check, lower frequencies of the mathematical model are determined via an unconstrained modal analysis. It should be checked that at least six frequencies are present with absolute values not exceeding 0,005 Hz. More than six quasi-zero frequencies are present when additional mechanisms are used in the structural model. The presence of additional rigid body modes should be explained by specific structure configuration.

A.6 Strain energy check

To conduct this check, rigid body modes corresponding to quasi-zero frequencies (see [Clause A.5](#)) are determined for the mathematical model with free-free boundary conditions. Modes are normalized such that displacements are equal to 1 m and rotations are equal to 1 rad. The strain energy matrix, E , is defined as follows:

$$E = 0,5 \Phi^T \cdot K \cdot \Phi \quad (A.1)$$