
**Geometrical product specifications
(GPS) — Filtration —**

Part 62:

Linear areal filters: spline filters

*Spécification géométrique des produits (GPS) — Filtrage —
Partie 62: Filtres surfaciques linéaires: filtres spline*



STANDARDSISO.COM : Click to view the full PDF of ISO 16610-62:2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Spline areal filter	2
4.1 General	2
4.2 Filter formula for cubic spline filter for topography maps on uniformly sampled grids	2
4.2.1 General	2
4.2.2 Regularization parameter	3
4.2.3 Tension parameter	4
4.2.4 Matrices of differentiation P and Q	4
4.3 Cubic spline filter for topography maps on distorted sampling grids	5
4.3.1 General	5
4.3.2 Filter formula modification for distorted grids	5
4.4 Transmission characteristics	6
5 Filter designation	7
Annex A (informative) Relationship to the filtration matrix model	8
Annex B (informative) Relationship to the GPS matrix model	9
Bibliography	10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 290, *Dimensional and geometrical product specification and verification*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

A list of all parts in the ISO 16610 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO 14638). It influences chain link C on feature properties in the GPS matrix model.

The ISO GPS matrix model given in ISO 14638 gives an overview of the ISO GPS system, of which this document is a part. The fundamental rules of ISO GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this document, unless otherwise indicated.

For more information on the relationship of this document to the filtration matrix model, see [Annex A](#).

For more detailed information of the relation of this document to other standards and the GPS matrix model, see [Annex B](#).

This document specifies the terminology and concepts for linear areal spline filters. It specifies how to separate long- and short-wave components of a surface with a global shape retainment.

STANDARDSISO.COM : Click to view the full PDF of ISO 16610-62:2023

Geometrical product specifications (GPS) — Filtration —

Part 62:

Linear areal filters: spline filters

1 Scope

This document specifies the characteristics of a linear areal spline filter with a global shape retainment.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 16610-1, *Geometrical product specifications (GPS) — Filtration — Part 1: Overview and basic concepts*

ISO 16610-21, *Geometrical product specifications (GPS) — Filtration — Part 21: Linear profile filters: Gaussian filters*

ISO 16610-22:2015, *Geometrical product specifications (GPS) — Filtration — Part 22: Linear profile filters: Spline filters*

ISO 16610-60:2015, *Geometrical product specification (GPS) — Filtration — Part 60: Linear areal filters — Basic concepts*

ISO 16610-61, *Geometrical product specification (GPS) — Filtration — Part 61: Linear areal filters — Gaussian filters*

ISO/IEC Guide 99, *International vocabulary of metrology — Basic and general concepts and associated terms (VIM)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16610-1, ISO 16610-21, ISO 16610-22, ISO 16610-60, ISO 16610-61 and ISO/IEC Guide 99 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

spline

linear combination of piecewise polynomials, with a smooth fit between the pieces

[SOURCE: ISO 16610-22:2015, 3.1, modified — Note 1 to entry removed.]

3.2

spline filter

linear filter based on splines

3.3

linear areal filter

areal filter which separates surfaces into long-wave and short-wave components and is also a linear function

[SOURCE: ISO 16610-60:2015, 3.1, modified — Notes to entry removed.]

3.3.1

linear planar filter

linear areal filter (3.3) which separates planar surfaces into long-wave and short-wave components, which applies to nominal planar surfaces

[SOURCE: ISO 16610-60:2015, 3.1.1, modified — Note 1 to entry removed.]

3.3.2

linear cylindrical filter

linear areal filter (3.3) which separates cylindrical surfaces into long-wave and short-wave components, which applies to nominal cylindrical surfaces

[SOURCE: ISO 16610-60:2015, 3.1.2, modified — Note 1 to entry removed.]

3.4

cut-off wavelength

wavelength of a sinusoidal surface of which 50 % of the amplitude is transmitted by the *linear areal filter* (3.3)

Note 1 to entry: Linear areal filters are identified by the filter type and the cut-off wavelength.

Note 2 to entry: The cut-off value for the spline filter is an example of a nesting index.

Note 3 to entry: The cut-off 50 % value is by convention.

[SOURCE: ISO 16610-60:2015, 3.7, modified — Note 2 to entry revised.]

4 Spline areal filter

4.1 General

The following low-pass filter formula for spline profile filters is based on cubic splines with a regularization parameter depending on the cut-off wavelength for the smoothness of the resultant waviness profile (low-passed signal) and a tension parameter influencing the slope of the transfer function. It is the areal extension of the linear profile spline filter as specified in ISO 16610-22. Two versions of the areal spline filter are specified, one as linear planar filter for open surface areas and another as linear cylindrical filter for closed surface areas, i.e. cylindrical surfaces with periodic continuation.

4.2 Filter formula for cubic spline filter for topography maps on uniformly sampled grids

4.2.1 General

The filter formula is shown in [Formula \(1\)](#):

$$\mathbf{w} = \mathbf{A}_y \mathbf{z} \mathbf{A}_x^T \quad (1)$$

where

$\mathbf{z}$ is the $n \times m$ -dimensional matrix representing the height map of input data, for example the primary surface of $n \times m$ sampling points;

$\mathbf{w}$ is the $n \times m$ -dimensional matrix representing the height map of output data.

The transformation matrices $\mathbf{A}_x$ and $\mathbf{A}_y$ are defined by [Formula \(2\)](#) and [Formula \(3\)](#), respectively:

$$\mathbf{A}_x = \left(\mathbf{E} + \beta \alpha_x^2 \mathbf{P} + (1 - \beta) \alpha_x^4 \mathbf{Q} \right)^{-1} \quad (2)$$

$$\mathbf{A}_y = \left(\mathbf{E} + \beta \alpha_y^2 \mathbf{P} + (1 - \beta) \alpha_y^4 \mathbf{Q} \right)^{-1} \quad (3)$$

where

$\mathbf{E}$ is the unity matrix;

$\mathbf{P}$ and $\mathbf{Q}$ are the matrices for the discretized differentiation;

β is the tension parameter ([4.2.3](#));

α_x and α_y are parameters ([4.2.2](#)), depending on the smoothness, of the cut-off wavelength of the spline.

For $\mathbf{A}_x$, the matrices are all of dimension $m \times m$ according to m sampling points along x-direction; for $\mathbf{A}_y$, the dimension of the matrices is $n \times n$ according to n sampling points along y-direction.

4.2.2 Regularization parameter

The parameter μ specifies the regularization, i.e. the degree of smoothing. The regularization parameter is therefore related to the cut-off wavelength, λ_c , for minimum tension by [Formula \(4\)](#) and [Formula \(5\)](#):

$$\mu = \alpha_r^4 \quad (4)$$

$$\alpha_r = \frac{1}{2 \sin \left(\frac{\pi \Delta r}{\lambda_c} \right)} \quad (5)$$

where either $r = x$ or $r = y$, for each of the lateral axes, respectively, i.e. with sampling interval $\Delta r = \Delta x$ along the x-direction in the case of $\mathbf{A}_x$ and the sampling interval $\Delta r = \Delta y$ along the y-direction in the case of $\mathbf{A}_y$, respectively. See Reference [\[4\]](#).

For non-minimum tension of the spline, i.e. for $\beta > 0$, the regularization depends on both tension and cut-off wavelength, as shown in [Formula \(6\)](#):

$$\mu = (1 - \beta) \alpha_r^4 \quad (6)$$

See Reference [\[5\]](#).

NOTE For sampling intervals $\Delta r \ll \lambda_c$, the regularization parameter tends to infinity, i.e. $\alpha^4 \rightarrow \infty$.

4.2.3 Tension parameter

The product $\beta\alpha^2$ is the tension factor with parameter β lying between 0 and 1. The parameter β controls the degree of following topography curvatures, where with curvature a local property of a curve or a surface is meant, which is defined at every point quantifying second order deviations of a curve from a straight line or a surface from a plane. Following curvatures closely means optimal shape retainment of the low-pass result, the output data w . For $\beta = 0$, the characteristics of the transfer function conform with ISO 16610-22:2015, Formula (1), a minimum tension which is equivalent to the steepest slope of the transfer function and therefore a better shape retainment than for $\beta > 0$. For $\beta = 0,625\ 242$, the characteristics of the transfer function are similar to the Gaussian filter^[5] as specified in ISO 16610-21 and ISO 16610-61.

NOTE The shape retainment by the spline filter for $\beta = 0$ is global, while the shape retainment by the Gaussian regression with a parabolic regression ($p = 2$) is local.

4.2.4 Matrices of differentiation P and Q

4.2.4.1 General

The matrix $P = (P_{i,j})$ represents the discretized first derivations, the gradient operations to evaluate slopes. The matrix $Q = (Q_{i,j})$ represents the discretized second derivations to evaluate curvatures. The indices $j = 1, \dots, K$ denote the column indices and $i = 1, \dots, K$ the row indices using $K = m$ if used for A_x (filtering in x-direction) and using $K = n$ if used for A_y (filtering in y-direction). The following matrix elements are non-zero and the others are zero.

4.2.4.2 The main diagonals

The main diagonal of matrices P and Q have the following elements:

$$P_{i,i} = 2 \text{ for } i = 2, \dots, K-1 \text{ and } Q_{i,i} = 6 \text{ for } i = 3, \dots, K-2.$$

In the case of cylindrical surfaces, these values apply also for $i = 1, 2, K-1, K$ for A_x if the x-direction lies on a circle being the intersection of the cylinder surface and a plane orthogonal to the cylinder axis and for A_y if the y-direction lies on such a circle.

The main diagonal holds $P_{i,i} = 1$ for $i = 1, K$, $Q_{i,i} = 1$ for $i = 1, K$ and $Q_{i,i} = 5$ for $i = 2, K-1$ in the case of plane surfaces as well as for A_x in the case of a cylindrical surface, if the x-direction lies parallel to the cylinder axis, and for A_y if the y-direction lies parallel to the cylinder axis.

4.2.4.3 The two first-off diagonals

$$P_{i,i+1} = P_{i+1,i} = -1 \text{ for } i = 1, \dots, K-1 \text{ and } Q_{i,i+1} = Q_{i+1,i} = -4 \text{ for } i = 2, \dots, K-1.$$

In the case of cylindrical surfaces and for A_x , if the x-direction lies on a circle being the intersection of the cylinder surface and a plane orthogonal to the cylinder axis and for A_y , if the y-direction lies on such a circle, these values are as well filling the matrix elements of all four corners of the matrix:

$$P_{1,K} = P_{K,1} = -1 \text{ and } Q_{1,2} = Q_{2,1} = Q_{1,K} = Q_{K,1} = Q_{K,K-1} = Q_{K-1,K} = -4.$$

In the case of planar surfaces and of the direction parallel to the cylinder axis, matrix P is tri-diagonal with

$$P_{1,K} = P_{K,1} = 0 \text{ and } Q_{1,2} = Q_{2,1} = -2 \text{ and } Q_{1,K} = Q_{K,1} = 0 \text{ and } Q_{K,K-1} = Q_{K-1,K} = -2.$$

4.2.4.4 The two second-off diagonals

The two second-off diagonals of matrix $\mathbf{Q}$ have value one in their elements and it is penta-diagonal for the cases of planar surfaces or the direction parallel to the cylinder axis, with the two second-off diagonals having the following elements:

$$Q_{i,i+2} = Q_{i+2,i} = 1 \text{ for } i=3, \dots, K-2.$$

In the case of cylindrical surfaces and for $\mathbf{A}_x$, if the x-direction lies on a circle being the intersection of the cylinder surface and a plane orthogonal to the cylinder axis and for $\mathbf{A}_y$, if the y-direction lies on such a circle the diagonals wrap around such that

$$Q_{1,K-1} = Q_{2,K} = Q_{K-1,1} = Q_{K,2} = 1.$$

4.3 Cubic spline filter for topography maps on distorted sampling grids

4.3.1 General

[Formula \(1\)](#) holds for uniformly sampled grids with x-coordinates satisfying $x_j = j \Delta x$ and y-coordinates satisfying $y_i = i \Delta y$, with i and j being integer numbers. Coordinate transformations according to form removals that include a shifting of symmetry points (e.g. eccentricity of roundness measurement) can cause a distorted grid such that there exist displacements $\delta_{x,k}$, $\delta_{y,l}$ leading to positions of the data points, as given in [Formula \(7\)](#):

$$\begin{pmatrix} x_k \\ y_l \end{pmatrix} = \begin{pmatrix} k \Delta x + \delta_{x,k} \\ l \Delta y + \delta_{y,l} \end{pmatrix} \quad (7)$$

The lateral positions shall be strictly monotonically increasing for each of the directions, i.e. $x_k < x_{k+1}$ and $y_l < y_{l+1}$.

4.3.2 Filter formula modification for distorted grids

The matrices $\mathbf{A}_x$ and $\mathbf{A}_y$ are extended to tensors with dimensions $m \times m \times n$ and $m \times n \times n$, see Reference [6]. The tensor elements shall be adopted using average sampling intervals to be included in the parameters α_x and α_y as given in [Formulae \(8\)](#) and [\(9\)](#):

$$\Delta x = \frac{1}{n(m-1)} \sum_{l=1}^{n-1} \sum_{k=1}^{m-1} (x_{l,k+1} - x_{l,k}) \quad (8)$$

$$\Delta y = \frac{1}{m(n-1)} \sum_{k=1}^{m-1} \sum_{l=1}^{n-1} (y_{l+1,k} - y_{l,k}) \quad (9)$$

The non-zero elements of the tensors shall be modified using discrete difference operators with samplings intervals $\Delta_{x,k,j} = x_k - x_j$ and $\Delta_{y,l,i} = y_l - y_i$. They are given in [Formulae \(10\)](#) and [\(11\)](#):

$$D_{x,l,(k,j)} = \frac{\Delta x}{\Delta_{x,l,(k,j)}} \quad (10)$$

$$D_{y,(l,i),k} = \frac{\Delta y}{\Delta_{y,(l,i),k}} \quad (11)$$

where

$\Delta_{x,l,(k,j)}$ is the difference between sampling positions $x_{l,k}$ and $x_{l,j}$;

$\Delta_{y,(l,i),k}$ is the difference between sampling positions $y_{l,k}$ and $y_{i,k}$.

The $n \times n \times m$ -dimensional tensor $\mathbf{P}_y$ is constructed of $n \times n$ matrices with non-zero elements, such as the matrix of 4.2.4 hold, for example the main diagonal elements $P_{y,i,i} = D_{y,(i,i-1),k}^2 + D_{y,(i+1,i),k}^2$, stacked to the third dimension with $k=1, \dots, m$ such that filtration takes place along y-directional profiles and stacking is performed in x-direction. The other tensors shall be set up accordingly.

4.4 Transmission characteristics

The transmission characteristics shall be in accordance with ISO 16610-22:2015, 4.4 (see also [Figure 1](#)).

For each direction $r = x, y$ as given by [Formula \(12\)](#):

$$\frac{a_{r,1}(\lambda_r)}{a_{r,0}(\lambda_r)} = \left(1 + 4\beta \left(\alpha_r \sin \frac{\pi \Delta r}{\lambda_r} \right)^2 + 16(1-\beta) \left(\alpha_r \sin \frac{\pi \Delta r}{\lambda_r} \right)^4 \right)^{-1} \quad (12)$$

where

$a_{r,0}(\lambda)$ is the wavelength-dependent amplitude of a sinusoidal component of the Fourier series of a profile before filtering, as shown in [Formula \(13\)](#);


$a_{r,1}(\lambda)$ is the wavelength-dependent amplitude of a sinusoidal component of the Fourier series of a profile after filtering, as shown in [Formula \(13\)](#);

$$z(r) = \sum_v a_r(v \Delta \lambda) \sin \left(\frac{2\pi}{v \Delta \lambda} r + \varphi(v \Delta \lambda) \right) \quad (13)$$

where

$\lambda = v \Delta \lambda$ is the wavelength of the Fourier component;

$\varphi(\lambda)$ is a wavelength-dependent phase.



- a Normalized spatial wavelength for x-direction $\frac{\lambda_x}{\lambda_c}$
- b Normalized spatial wavelength for y- direction $\frac{\lambda_y}{\lambda_c}$.
- c Transmission $t(\lambda_x, \lambda_y)$.

Figure 1 — Transmission characteristics for the long-wave surface components

$$(\beta = 0; \Delta x = \frac{\lambda_c}{200}, \Delta y = \frac{\lambda_c}{200})$$

Due to linear supposition of the transmission functions of a linear filter, the resultant transmission function is the product as given by [Formula \(14\)](#):

$$t(\lambda_x, \lambda_y) = \frac{a_{x,1}(\lambda_x)}{a_{x,0}(\lambda_x)} \frac{a_{y,1}(\lambda_y)}{a_{y,0}(\lambda_y)} \quad (14)$$

5 Filter designation

Areal spline filters according to this document are designated:

FALS

See also ISO 16610-1.

Annex A (informative)

Relationship to the filtration matrix model

A.1 General

For full details about the filtration matrix model, see ISO 16610-1.

A.2 Position in the filtration matrix model

This document influences particular filters in the areal filters, linear column in [Table A.1](#).

[Table A.1](#) includes current and future parts of the ISO 16610 series.

Table A.1 — Relationship to the filtration matrix model

General	Filters: ISO 16610 series					
	Part 1					
Fundamental	Profile filters			Areal filters		
	ISO 16610-11 ^a			ISO 16610-12 ^a		
	Linear	Robust	Morphological	Linear	Robust	Morphological
Basic concepts	ISO 16610-20	ISO 16610-30	ISO 16610-40	ISO 16610-60	ISO 16610-70	ISO 16610-80
Particular filters	ISO 16610-21 to 25	ISO 16610-31 to 35	ISO 16610-41 to 45	ISO 16610-61 to 65	ISO 16610-71 to 75	ISO 16610-81 to 85
How to filter	ISO 16610-26 to 28	ISO 16610-36 to 38	ISO 16610-46 to 48	ISO 16610-66 to 68	ISO 16610-76 to 78	ISO 16610-86 to 88
Multiresolution	ISO 16610-29	ISO 16610-39	ISO 16610-49	ISO 16610-69	ISO 16610-79	ISO 16610-89
^a At present included in ISO 16610-1.						