
**Geotechnical investigation and
testing — Laboratory testing of soil —**

**Part 12:
Determination of liquid and plastic
limits**

AMENDMENT 2

*Reconnaissance et essais géotechniques — Essais de laboratoire sur
les sols —*

Partie 12: Détermination des limites de liquidité et de plasticité

AMENDEMENT 2





COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 182, *Geotechnics*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 341, *Geotechnical Investigation and Testing*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

A list of all parts in the ISO 17892 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 17892-12:2018/Amd 2:2022

Geotechnical investigation and testing — Laboratory testing of soil —

Part 12: Determination of liquid and plastic limits

AMENDMENT 2

4.2.2.2, Table 1

Replace Table 1 with the following:

Table 1 — Set of fall cones — Typical manufacturing specifications for masses and dimensions

Mass of cone plus shaft	g	$60 \pm 0,06$	$80 \pm 0,08$
Tip angle β	°	$60 \pm 0,3$	$30 \pm 0,3$
Height of the cone tip h	mm	≥ 20	≥ 30
The deviation a from the geometrical tip at manufacturing	mm	$< 0,1$	$< 0,2$

4.2.2.4

Replace the text with the following:

The maximum wear b shall be less than 0,3 mm for the 60 g/60° cone and less than 0,6 mm for the 80 g/30° cone (see Figure 2).


A.3.6.1

Replace the text with the following:

Before the first use on each day of use, check the sharpness of the cone tip, the surface finish on the cone and the free fall of the cone.

To ensure that the point remains sufficiently sharp for the purposes of the test, the cone should be replaced if the point can no longer be felt when brushed lightly with the tip of the finger when the tip is pushed through a hole $(1,50 \pm 0,02)$ mm in diameter, drilled through a metal plate $(2,20 \pm 0,02)$ mm thick for a 30° cone or a $(1,00 \pm 0,02)$ mm thick metal plate for a 60° cone. This is shown schematically in Figure A.1.

Other gauge dimensions may be used providing the ratios of its thickness to the diameters of the holes are maintained. The maximum permitted degree of wear of the cone tip (4.2.2) corresponds to the worn tip being flush with the bottom of the metal plate.



Key

- A hole diameter $1,50 \pm 0,02$ mm
- B plate thickness $2,20 \pm 0,02$ mm
for a 30° cone, or
plate thickness $1,00 \pm 0,02$ mm
for a 60° cone
- C maximum tip wear 0,6 mm for a 30° cone, or 0,3 mm for a 60° cone

Figure A.1 — Cone tip sharpness check gauge

The surface finish of the cones shall be visually checked before use on each day of use to ensure no significant scratches or corrosion is visible.

The cone mass, dimensions and total tip wear shall be verified at least annually to ensure the requirements of Table 1 and 4.2.2.4 are met.