
**Photography — Digital cameras —
Shading measurements**

Photographie — Caméras numériques — Mesurages d'ombrage

STANDARDSISO.COM : Click to view the full PDF of ISO 17957:2015



STANDARDSISO.COM : Click to view the full PDF of ISO 17957:2015



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test conditions and methods	1
4.1 General.....	1
4.2 Apparatus and hardware.....	2
4.3 Lighting.....	2
4.4 Test chart.....	2
4.5 Image/camera settings.....	2
5 Analytical approach	3
5.1 General.....	3
5.2 Lightness non-uniformity.....	4
5.3 Luminance non-uniformity.....	4
5.4 Chrominance non-uniformity.....	5
5.5 Total colour non-uniformity.....	5
6 Presentations of results	5
Annex A (normative) Recommended measurement condition	7
Annex B (informative) Example of shading metric calculation	8
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

The committee responsible for this document is ISO/TC 42, *Photography*.

Introduction

One common type of image phenomenon seen in digital cameras is a systematic intensity variation across an image known as luminance shading. There are several causes of luminance shading in a digital camera: pixels having non-uniform sensitivity across a sensor array, illumination non-uniformity, lens shading, pixel geometry, and electronic non-uniformity. Characteristics of lens shading include symmetry about the optical sensor, uniformity across each colour plane, and variation as a function of $\cos^2\theta$. Luminance shading only affects intensity falloff.

Colour variations within the image can be induced by several factors, all of which will cause varying degrees of non-neutrality within an ideal uniform-gray exposure. Some of the primary factors include, (a) a mismatch between the CMOS micro-lens optical acceptance angle and the lens' chief ray angle over the field of view, (b) spatially varying spectral transmittance differences from the infrared rejection filter (usually most significant at the cutoff wavelength), and (c) inherent spectral sensitivity differences across the array. Consistent, systematic variations can be reduced through correction via image processing, but there might remain residual colour variations.

The information that follows defines the recommended approach for creating a test scene to use for the evaluation of luminance shading and colour variations, as well as specifying the conditions for illumination and exposure. The currently proposed analysis approach to quantify the magnitude of colour variations is described. It is important to understand that this specification is related to the degree of colour variations that are apparent in the image, not the specific colour accuracy. Thus, an image that appeared pink but was uniformly pink over the entire image would be equivalent to a perfectly uniform gray field relative to this colour non-uniformity specification.

Some part of this International Standard is based on the work done by the Camera Phone Image Quality group (CPIQ) within the International Imaging Industry Association (I3A), now part of the Institute of Electrical and Electronics Engineers (IEEE), whose contribution is greatly acknowledged.

STANDARDSISO.COM : Click to view the full PDF of ISO 17957:2015

Photography — Digital cameras — Shading measurements

1 Scope

This International Standard defines a method for measuring shading for digital cameras (including camera phones). The method includes procedures for measuring colour and luminance signal components separately.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7589, *Photography — Illuminants for sensitometry — Specifications for daylight, incandescent tungsten and printer*

ISO 11664-2/CIE, S 014-2/E: *Joint ISO/CIE Standard: Colourimetry — Part 2: CIE Standard Illuminants for Colourimetry*

ISO 11664-4/CIE, S 014-4/E: *Joint ISO/CIE Standard: Colourimetry — Part 4: CIE 1976 $L^*a^*b^*$ Colour Space*

ISO 12231, *Photography — Electronic still picture imaging — Vocabulary*

IEC 61966-2-1:1999+A1:2003: *Multimedia systems and equipment — Colour measurement and management — Part 2-1: Colour management – Default RGB colour space — sRGB*

CIE 15:2004, *Colourimetry*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

luminance shading

luminance non-uniformity

gradual variation of the luminance signal components within the image field

3.2

colour shading

colour non-uniformity

gradual variation of the chrominance signal components within the image field

4 Test conditions and methods

4.1 General

The following measurement conditions should be used as nominal conditions when measuring the shading of a digital camera. If it is not possible or appropriate to achieve these nominal operating conditions, the actual operating conditions shall be listed along with the reported results.

4.2 Apparatus and hardware

The following hardware is necessary to control and report the test conditions:

- a uniform field target;
- light source(s);
- luminance meter.

The total uniformity required for the target and for the light source(s) is specified below.

4.3 Lighting

For lightness non-uniformity and luminance non-uniformity measurement, average outdoor daylight (type D) illuminant shall be used. For chrominance non-uniformity measurement and total colour non-uniformity measurement, three standard illuminants shall be used to represent the characteristics of (a) average outdoor daylight (type D), (b) indoor incandescent lighting (type A), and (c) indoor fluorescent lighting (type F). Other illuminants may be used optionally. The type of illuminant shall be reported in any case.

The recommended daylight illuminant is CIE/D55 (5 503K) with a tolerance of 5 000K to 6 504K. The recommended indoor incandescent illuminant is CIE/A (2 856K) with a tolerance of 2 700K to 3 200K. The recommended fluorescent illuminant is type CIE/F2 (4 230K) with a tolerance of 3 900K to 4 600K.

The light source(s) shall be positioned to provide uniform illumination and produce no glare or reflections from the target.

4.4 Test chart

The target shall provide a spectrally neutral, uniform luminance distribution over the entire imaged field of view. Spectral neutrality is achieved if the spectral transmittance or reflectance of the target does not vary by more than 5 % over the range between 420 nm and 750 nm. The construction of the target can be either transmissive or reflective. Total luminance uniformity of the lighting and the test chart is very important for this measurement. The luminance uniformity should be within 2,5 %; (i.e. $[(\text{Max-Ave})/(\text{Ave}) < 0,025 \text{ and } (\text{Min-Ave})/(\text{Ave}) < 0,025]$), and shall be within 5 %; (i.e. $[(\text{Max-Ave})/(\text{Ave}) < 0,05 \text{ and } (\text{Min-Ave})/(\text{Ave}) < 0,05]$) across the entire imaged area, with an average luminance between 50 cd/m² and 120 cd/m². The light flux from the target shall be diffuse and shall not include any specular component.

A target containing patterns may also be used, provided the same results as the uniform chart are obtained by performing a suitable procedure to remove the patterns. When a target containing patterns is used, exposure shall be adjusted to give an average output value of the central measurement block, between 110 and 130 in sRGB encoding values.

4.5 Image/camera settings

Exposure shall be adjusted to give an average output value of the central measurement block, between 110 and 130 in sRGB encoding values, when exposure adjustment is available. When average output values of the peripheral measurement blocks are very low (e.g. in the case of very wide-angle lens), the exposure level may be adjusted higher. The average output value of the central measurement block shall be reported in any case.

White balance should be adjusted to render the centre of the image as neutral as possible. Recommended focus distance is equal to or larger than “(35 mm-equivalent) focal length x 10”. When the focus may manually be adjusted, focus does not have to be on the test chart. F-number, focal length, focus distance, ISO sensitivity, and exposure time shall be reported. Images should be saved at maximum pixel number using the highest quality (i.e. with least compression) setting.

For the recommended measurement conditions, see [Annex A](#).




Figure 1 — Diagram of recommended measurement condition for a reflective target

5 Analytical approach

5.1 General

For non-uniformity calculation, the image is divided into $(2N+1) \times (2N+1)$ non-overlapping rectangular blocks ($N \geq 5$), where N should be determined to include sufficient number of pixels for averaging noise and local disturbance for each measurement block. The sRGB values of pixels within one block are averaged. When precipitous variations in the image are visible, it is desirable to increase the “ N ” value so that the precipitous variations will not be averaged out. Mean values of the data should be preserved as floating point or rational numbers as rounding numbers to the nearest code value could result in significant quantization errors.

CIELAB values are calculated from sRGB values as follows:

- a) First, the sRGB values of the pixels: R_j, G_j, B_j in the i th measurement block will be averaged to $R_{Ave}(i), G_{Ave}(i), B_{Ave}(i)$.

$$R_{Ave}(i) = \frac{1}{n_i} \cdot \sum_{j=1}^{n_i} R_j \quad G_{Ave}(i) = \frac{1}{n_i} \cdot \sum_{j=1}^{n_i} G_j \quad B_{Ave}(i) = \frac{1}{n_i} \cdot \sum_{j=1}^{n_i} B_j \quad (1)$$

where

R_j, G_j, B_j j th pixel value in measurement block ($j=1$ to n_i);

n_i is the number of pixels in i th measurement block.

- b) Convert averaged sRGB values: $R_{Ave}(i), G_{Ave}(i), B_{Ave}(i)$ to linear RGB values in the range of 0 to 1:
 $R_{Lin}(i), G_{Lin}(i), B_{Lin}(i)$

$$R'(i) = R_{Ave}(i) / 255 \quad G'(i) = G_{Ave}(i) / 255 \quad B'(i) = B_{Ave}(i) / 255$$

$$\text{if } R'(i), G'(i), B'(i) \leq 0,04045 \quad (2)$$

$$R_{Lin}(i) = R'(i) / 12,92 \quad G_{Lin}(i) = G'(i) / 12,92 \quad B_{Lin}(i) = B'(i) / 12,92$$

Otherwise

$$R_{Lin}(i) = \left[\frac{(R'(i) + 0,055)}{1,055} \right]^{2,4} \quad G_{Lin}(i) = \left[\frac{(G'(i) + 0,055)}{1,055} \right]^{2,4} \quad B_{Lin}(i) = \left[\frac{(B'(i) + 0,055)}{1,055} \right]^{2,4}$$

c) Tristimulus values: $X(i)$, $Y(i)$, $Z(i)$ of the i th block are calculated as follows:

$$\begin{bmatrix} X(i) \\ Y(i) \\ Z(i) \end{bmatrix} = \begin{bmatrix} 0,4124 & 0,3576 & 0,1805 \\ 0,2126 & 0,7152 & 0,0722 \\ 0,0193 & 0,1192 & 0,9505 \end{bmatrix} \begin{bmatrix} R_{Lin}(i) \\ G_{Lin}(i) \\ B_{Lin}(i) \end{bmatrix} \quad (3)$$

d) Convert CIE/XYZ values to CIELAB values: $[L^*(i), a^*(i), b^*(i)]$ of the i th block as follows (also indicated in IEC 61966-2-1:1999+A1:2003, Annex H). X_n, Y_n, Z_n are the reference display white point coordinate of illuminant D65 with $X_n = 0,9505$, $Y_n = 1,0000$, $Z_n = 1,0890$.

$$L^*(i) = 116 \cdot f(Y(i)/Y_n) - 16$$

$$a^*(i) = 500 \left[f(X(i)/X_n) - f(Y(i)/Y_n) \right]$$

$$b^*(i) = 200 \left[f(Y(i)/Y_n) - f(Z(i)/Z_n) \right]$$

where

$$\begin{aligned} f(X(i)/X_n) &= (X(i)/X_n)^{1/3} & \text{if } X(i)/X_n > 0,008856 \\ f(X(i)/X_n) &= 7,787(X(i)/X_n) + 16/116 & \text{if } X(i)/X_n \leq 0,008856 \\ f(Y(i)/Y_n) &= (Y(i)/Y_n)^{1/3} & \text{if } Y(i)/Y_n > 0,008856 \\ f(Y(i)/Y_n) &= 7,787(Y(i)/Y_n) + 16/116 & \text{if } Y(i)/Y_n \leq 0,008856 \\ f(Z(i)/Z_n) &= (Z(i)/Z_n)^{1/3} & \text{if } Z(i)/Z_n > 0,008856 \\ f(Z(i)/Z_n) &= 7,787(Z(i)/Z_n) + 16/116 & \text{if } Z(i)/Z_n \leq 0,008856 \end{aligned} \quad (4)$$

5.2 Lightness non-uniformity

The lightness non-uniformity, D_L , is defined as:

$$D_L = \max[L^*(i)] - \min[L^*(i)] \quad (5)$$

5.3 Luminance non-uniformity

The luminance non-uniformity, D_Y (%), is defined as:

$$D_Y = \frac{\max[Y(i)] - \min[Y(i)]}{\max[Y(i)]} \times 100 \quad (6)$$

5.4 Chrominance non-uniformity

Analysis of the chrominance non-uniformity is performed by first calculating the overall average $\overline{a^*}$ and $\overline{b^*}$ for the entire image using the block average values: $a^*(i)$ and $b^*(i)$.

$$\overline{a^*} = 1/m \cdot \sum_{i=1}^m a^*(i) \quad \overline{b^*} = 1/m \cdot \sum_{i=1}^m b^*(i) \quad (7)$$

where

m is the number of measurement blocks.

The chrominance deviation of the i th block is calculated by:

$$D_c(i) = \sqrt{[a^*(i) - \overline{a^*}]^2 + [b^*(i) - \overline{b^*}]^2} \quad (8)$$

The chrominance non-uniformity, D_c , is defined as the maximum deviation from the overall average as:

$$D_c = \max[D_c(i)] \quad (9)$$

5.5 Total colour non-uniformity

Analysis of total colour non-uniformity begins by first calculating the overall maximums and minimums of $L^*(i)$, $a^*(i)$, and $b^*(i)$.

$$L_{max}^* = \max[L^*(i)], \quad L_{min}^* = \min[L^*(i)] \quad (10)$$

$$a_{max}^* = \max[a^*(i)], \quad a_{min}^* = \min[a^*(i)] \quad (11)$$

$$b_{max}^* = \max[b^*(i)], \quad b_{min}^* = \min[b^*(i)] \quad (12)$$

The total colour non-uniformity, D_{Total} , is calculated as:

$$D_{Total} = \sqrt{(L_{max}^* - L_{min}^*)^2 + (a_{max}^* - a_{min}^*)^2 + (b_{max}^* - b_{min}^*)^2} \quad (13)$$

6 Presentations of results

The following measurement conditions shall be reported for each model. If a condition is unknown, write "unknown"

- Model name/Number: _____
- F-Number: _____
- Focal length: _____
- Focus distance: _____
- ISO sensitivity: _____
- Exposure time: _____
- Average output level of central measurement block: _____

Following measurement conditions shall be reported for each metric.

- Light source: D/A/F (or other)

STANDARDSISO.COM : Click to view the full PDF of ISO 17957:2015

Annex A (normative)

Recommended measurement condition

The following measurement conditions are recommended when the representative values for the shading property of the camera are necessary. It is recommended to report the metric when the shading properties are most noticeable (i.e. the worst case). However, since it is almost impossible to find the worst value for every shooting condition, the recommended measurement condition in this Annex may alternatively be used.

Aperture stop ^a	at the smallest F-number (i.e. largest aperture)
Focal length ^b	at the shortest focal length (i.e. wide-end)
^a [Informative] The luminance shading property at the smallest F-number tends to be the largest. ^b [Informative] The luminance shading property at the shortest focal length tends to be the largest.	

When the shading properties of several cameras are compared, it is meaningful to conduct measurements with the same F-number, Focal length, and Focus distance.

For the case of settings not mentioned above, refer to the test conditions described in [Clause 4](#). For the camera settings that are not mentioned anywhere in this International Standard, it is recommended to use manufacturer's default setting.

Annex B (informative)

Example of shading metric calculation

B.1 General

The following example is provided to demonstrate the methodology for assessing the shading properties and for computing the lightness, luminance, chrominance, and total non-uniformity metrics of an image.

B.2 Calculation of non-uniformity metrics

The measurement algorithm used in this International Standard assumes an RGB image is acquired of a uniform-field target with materials and methods as defined in 4.3 to 4.5. The following conversions assume the usual case that the image is stored in the sRGB colour space defined in IEC 61966-2-1:1999.

- a) For this example, the image is sub-sectioned into $(2N+1) \times (2N+1)$ blocks per 5.1, with $N = 5$, yielding an image containing 11×11 blocks.
- b) The RGB values are averaged, per channel, to obtain average red, green, and blue values for each of the 11×11 measurement blocks as defined by Formula 1. The results for this step of the calculation are provided in Table B.1. The averaged sRGB values are converted to Linear RGB values per Formula 2.
- c) The tristimulus values $X(i)$, $Y(i)$, and $Z(i)$, are calculated from the linear RGB values per Formula 3. The tristimulus values calculated per Formula 3 are provided in Table B.2.
- d) Next, the values are converted into CIELAB per Formula 4. The calculated $L^*(i)$, $a^*(i)$, and $b^*(i)$ values are provided in Table B.3.

- e) To calculate **lightness non-uniformity** per Formula 5, maximum and minimum values for L^* are calculated.

$$\max[L^*(i)] = 60,52, \quad \min[L^*(i)] = 47,34 \quad (\text{B.1})$$

$$D_L = \max[L^*(i)] - \min[L^*(i)] = 13,18 \quad (\text{B.2})$$

- f) To calculate **luminance non-uniformity** per Formula 6, minimum and maximum Y values are calculated.

$$\max[Y(i)] = 0,287\ 1, \quad \min[Y(i)] = 0,162\ 8 \quad (\text{B.3})$$

$$D_Y = \frac{\max[Y(i)] - \min[Y(i)]}{\max[Y(i)]} \times 100 = 43,29\ \% \quad (\text{B.4})$$

- g) To calculate **chrominance non-uniformity**, the overall average $\overline{a^*}$ and $\overline{b^*}$ are computed overall measurement blocks per Formula 7.

$$\overline{a^*} = 8,35, \quad \overline{b^*} = 1,66 \quad (\text{B.5})$$

The chrominance deviation $D_c(i)$ of the i th measurement block are calculated per Formula 8, and reported in Table B.4.

Finally, the value of the largest deviation $D_c = \max_i D_c(i)$ is calculated per Formula 9 and reported as the chrominance non-uniformity.

$$D_c = \max D_c(i) = 8,658 \quad (\text{B.6})$$

- h) For the **total colour non-uniformity** calculations, the L^* , a^* , and b^* data in Table B.3 are referenced. The maximum and minimum of L^* , a^* , and b^* are calculated per Formula 10 to Formula 12.

$$L_{\max}^* = 60,52, \quad a_{\max}^* = 16,50, \quad b_{\max}^* = 4,60 \quad (\text{B.7})$$

$$L_{\min}^* = 47,34, \quad a_{\min}^* = 1,83, \quad b_{\min}^* = -0,52 \quad (\text{B.8})$$

Finally, the **total non-uniformity** is calculated per Formula 13.

$$D_{\text{Total}} = \sqrt{(L_{\max}^* - L_{\min}^*)^2 + (a_{\max}^* - a_{\min}^*)^2 + (b_{\max}^* - b_{\min}^*)^2} = 20,38 \quad (\text{B.9})$$

Table B.1 — sRGB 11 × 11 average values

$R(i)$										
155,83	161,14	159,42	152,89	143,69	138,17	134,16	132,06	130,85	136,48	152,35
158,45	161,34	155,85	148,04	139,82	135,13	132,30	129,90	129,05	133,19	146,56
160,79	159,36	150,15	142,49	135,48	130,86	128,57	128,44	127,41	130,91	142,99
162,16	155,91	147,58	139,27	132,19	128,23	125,53	125,88	126,55	129,61	141,03
162,91	153,48	144,88	135,83	129,48	125,90	124,27	122,99	125,25	128,52	139,50
163,37	153,17	143,21	134,66	127,75	123,39	122,07	122,17	124,19	127,90	137,27
164,44	153,62	142,65	135,17	127,93	122,92	121,14	122,14	124,65	128,38	137,70
165,77	155,20	145,26	136,75	129,98	124,99	123,60	123,69	126,54	129,13	138,45
167,65	158,84	148,70	140,23	132,86	128,54	126,04	127,33	128,30	131,73	140,55
171,67	164,98	153,59	145,32	138,35	133,57	131,80	131,48	131,63	135,51	143,41
177,47	169,49	160,08	152,34	143,31	138,43	135,76	135,54	136,17	140,09	145,88
$G(i)$										
119,18	127,05	127,55	123,62	119,17	115,46	111,80	109,04	108,25	114,24	129,43
124,52	130,16	127,42	124,02	120,74	116,32	112,57	110,12	108,12	111,66	124,38
127,63	130,05	126,78	123,63	120,62	117,12	112,87	110,28	107,69	109,93	120,13
129,53	130,42	126,65	123,04	120,81	117,76	114,15	110,84	107,96	109,62	117,46
130,43	130,95	126,32	122,86	121,11	117,86	114,53	111,42	108,29	108,62	115,71
130,88	131,38	126,33	122,73	120,97	118,36	114,94	111,57	108,96	108,61	114,71
131,06	131,46	126,44	122,51	120,54	117,87	115,14	111,54	108,54	108,53	114,23
131,62	131,74	126,87	122,68	120,06	117,48	114,38	111,37	108,56	108,96	114,07
132,15	132,78	128,23	122,58	120,01	117,09	114,22	111,12	109,21	110,04	114,75
133,16	134,40	129,41	123,47	120,35	117,03	113,87	111,60	110,70	111,38	115,93
135,46	136,48	130,88	125,32	121,39	117,78	114,61	112,10	111,23	113,24	117,94
$B(i)$										
123,96	132,22	131,60	126,71	121,96	118,34	114,85	112,23	111,09	117,77	133,83
128,67	134,08	130,04	126,12	121,41	117,71	114,34	111,49	109,73	113,45	127,93

Table B.1 (continued)

130,00	134,22	129,48	124,93	121,06	117,35	113,73	111,04	109,13	111,10	123,56
131,42	133,81	129,20	125,11	121,12	118,13	113,94	111,30	109,32	110,37	120,72
132,13	133,46	129,49	125,14	121,74	118,38	114,90	111,57	109,56	109,98	119,55
132,61	133,66	129,72	124,86	121,11	117,88	115,20	112,32	109,53	109,80	118,57
132,94	133,90	130,50	126,70	121,52	117,39	114,98	112,80	109,69	110,09	118,18
133,74	134,56	130,61	126,98	121,53	118,04	115,20	113,16	110,22	110,55	118,93
135,11	136,34	131,30	127,07	122,22	118,76	115,73	113,10	111,29	112,23	120,31
136,15	139,16	133,09	128,37	123,47	119,94	116,24	113,92	113,11	114,24	121,92
138,48	141,56	135,54	129,77	124,25	120,13	117,01	115,17	114,30	116,61	123,74

Table B.2 — Average XYZ values

<i>X(i)</i>										
0,239 3	0,265 0	0,261 8	0,240 9	0,215 7	0,199 8	0,187 2	0,179 4	0,176 0	0,195 3	0,252 1
0,254 0	0,270 8	0,253 6	0,232 0	0,210 7	0,195 5	0,184 8	0,176 8	0,172 4	0,184 7	0,231 0
0,263 6	0,266 8	0,241 6	0,221 0	0,203 2	0,189 5	0,179 0	0,174 5	0,169 1	0,177 9	0,216 7
0,269 8	0,260 2	0,236 6	0,214 9	0,198 2	0,186 6	0,176 0	0,171 4	0,168 2	0,175 2	0,208 4
0,273 0	0,256 0	0,231 5	0,209 0	0,194 7	0,183 4	0,175 2	0,168 0	0,166 8	0,172 2	0,203 1
0,274 9	0,256 2	0,228 8	0,206 8	0,191 6	0,180 1	0,172 7	0,167 4	0,165 9	0,171 2	0,197 6
0,277 5	0,257 3	0,228 5	0,208 5	0,191 6	0,178 5	0,171 4	0,167 6	0,166 2	0,172 0	0,197 6
0,281 6	0,261 1	0,233 7	0,211 5	0,194 1	0,181 5	0,174 2	0,169 8	0,169 3	0,173 8	0,199 1
0,287 3	0,270 9	0,242 1	0,217 2	0,198 9	0,186 7	0,177 9	0,174 9	0,173 2	0,179 9	0,204 2
0,298 0	0,287 7	0,253 9	0,228 0	0,209 0	0,195 1	0,186 5	0,182 2	0,181 0	0,188 5	0,211 4
0,315 9	0,301 9	0,270 2	0,244 0	0,219 2	0,204 0	0,194 1	0,189 9	0,189 4	0,199 5	0,219 3
<i>Y(i)</i>										
0,217 4	0,244 6	0,243 9	0,226 1	0,205 4	0,191 0	0,178 6	0,170 3	0,167 4	0,186 7	0,242 4
0,234 4	0,253 4	0,239 5	0,222 3	0,205 6	0,190 3	0,178 7	0,170 7	0,165 4	0,177 2	0,222 3
0,245 1	0,251 1	0,232 2	0,216 0	0,201 6	0,188 6	0,176 2	0,169 8	0,163 1	0,171 0	0,207 5
0,251 9	0,248 5	0,229 4	0,211 7	0,199 3	0,188 2	0,176 8	0,169 1	0,163 1	0,169 2	0,198 7
0,255 3	0,247 4	0,226 1	0,208 4	0,198 1	0,186 7	0,177 0	0,168 3	0,162 8	0,166 1	0,193 0
0,257 1	0,248 4	0,224 7	0,207 0	0,196 2	0,185 9	0,176 3	0,168 2	0,163 4	0,165 6	0,188 6
0,258 8	0,249 1	0,224 7	0,207 3	0,195 4	0,184 2	0,176 1	0,168 2	0,162 9	0,165 8	0,187 8
0,262 0	0,251 6	0,228 2	0,209 2	0,195 9	0,185 0	0,176 2	0,169 1	0,164 5	0,167 4	0,188 2
0,265 8	0,258 6	0,235 1	0,211 9	0,198 2	0,187 0	0,177 8	0,171 3	0,167 5	0,172 2	0,191 9
0,273 3	0,270 3	0,243 3	0,219 0	0,203 9	0,191 2	0,181 6	0,175 8	0,173 7	0,178 7	0,197 5
0,287 1	0,281 7	0,254 5	0,230 6	0,211 0	0,197 0	0,186 7	0,180 5	0,178 9	0,187 2	0,204 9
<i>Z(i)</i>										
0,219 9	0,252 3	0,250 1	0,230 7	0,212 3	0,198 8	0,186 4	0,177 4	0,173 7	0,196 4	0,258 4
0,238 4	0,260 5	0,244 2	0,228 5	0,210 8	0,196 9	0,185 0	0,175 4	0,169 6	0,182 0	0,234 7
0,244 6	0,260 8	0,241 4	0,223 8	0,209 3	0,195 8	0,183 0	0,174 1	0,167 6	0,174 3	0,217 9
0,250 6	0,259 1	0,240 2	0,223 9	0,209 3	0,198 3	0,183 9	0,174 9	0,168 2	0,172 0	0,207 4
0,253 6	0,257 8	0,240 8	0,223 7	0,211 2	0,198 9	0,186 8	0,175 7	0,168 9	0,170 4	0,202 8
0,255 6	0,258 7	0,241 5	0,222 6	0,209 0	0,197 4	0,187 7	0,177 9	0,169 0	0,169 9	0,199 2