
**Road vehicles — Connection interface
for pyrotechnic devices, two-way and
three-way connections —**

**Part 1:
Pocket interface definition**

*Véhicules routiers — Interface de raccordement pour dispositifs
pyrotechniques, deux voies et trois voies —*

Partie 1: Définition de l'interface du support allumeur



STANDARDSISO.COM : Click to view the full PDF of ISO 19072-1:2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Dimensional features — Squib holder interface including male contacts	2
5 Material characteristics	4
5.1 Material specifications for male contacts	4
5.2 Contacts and short circuit areas of the male contacts specifications	4
Annex A (normative) Sealed variant of the pyrotechnic device/initiator harness connector assembly	5
Annex B (normative) Variant without retainer of the pyrotechnic device/initiator harness connector assembly	6
Annex C (normative) Undercut geometry for the alternative material of the pyrotechnic device/initiator harness connector assembly	7
Bibliography	8

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 32, *Electrical and electronic components and general system aspects*.

This third edition cancels and replaces the second edition (ISO 19072-1:2014), which has been technically revised.

The main changes compared to the previous edition are as follows:

- greater detail has been specified in [5.2](#) regarding the contacts and short circuit areas for the male contacts;
- [Annex C](#) has been added to define an alternative material variant of the pyrotechnic device/initiator harness connector assembly.

A list of all parts in the ISO 19072 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Road vehicles integrate an increasing number of pyrotechnic devices contributing to occupant safety in vehicles (for example, frontal and side air bag, safety belt pretensioner, etc.).

Various pocket definitions currently exist all over the world. This situation appears difficult to manage for the different equipment makers. The goal of this document is to define a common specification.

A sealed option of the pyrotechnic device/initiator harness connector assembly is defined in [Annex A](#).

A variant without retainer of the pyrotechnic device/initiator harness connector assembly is defined in [Annex B](#).

An alternative material variant of the pyrotechnic device/initiator harness connector assembly is defined in [Annex C](#).

STANDARDSISO.COM : Click to view the full PDF of ISO 19072-1:2019

STANDARDSISO.COM : Click to view the full PDF of ISO 19072-1:2019

Road vehicles — Connection interface for pyrotechnic devices, two-way and three-way connections —

Part 1: Pocket interface definition

1 Scope

This document defines the minimum specification of the pyrotechnic device pocket interface.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1302, *Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation*

ISO 8092-2, *Road vehicles — Connections for on-board electrical wiring harnesses — Part 2: Definitions, test methods and general performance requirements*

ASTM B488, *Standard Specification for Electrodeposited Coatings of Gold for Engineering Uses*

ASTM B689, *Standard Specification for Electroplated Engineering Nickel Coatings*

ASTM B735, *Standard Test Method for Porosity in Gold Coatings on Metal Substrates by Nitric Acid Vapor*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8092-2 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 connector

assembly used to connect several conductors together or a single conductor to an appliance

Note 1 to entry: A male (female) connector is a housing containing male (female) contacts and accessory items. A male connector may be permanently fixed to a wiring harness or to an appliance [an electronic control unit (ECU) for example]. A female connector is generally permanently fixed to a wiring harness.

3.2 housing

connector without its contacts

3.3 initiator

part of the pyrotechnical device with two male contacts

3.4

pocket

squib holder inner interface including male contacts

3.5

retainer

ring holding an optional shorting clip (shunt) and providing coding and electrical insulation, generally made of plastic

Note 1 to entry: The shorting clip (shunt) may be omitted by decision between manufacturer and supplier.

3.6

shorting clip

shunt

metallic bar of the retainer providing the electrical connection between two male contacts

3.7

squib holder

part of the pyrotechnic device, holding the initiator and the retainer

4 Dimensional features — Squib holder interface including male contacts

The contact and short-circuit areas when male and female connectors are mated shall comply with [Figure 1](#).



- 7 rounded and burr free
- 8 undercut geometry required to hold the connector and retainer inside the squib holder; the undercut surface does not need to be a continuous 360° surface and shall meet the specified connector and retainer retention requirements and dimensions regardless of material
- 9 for existing tools to produce plastic pockets, the following values are also allowed:
 $R\ 0,15\begin{smallmatrix} 0 \\ -0,1 \end{smallmatrix} - H\ 6,35\begin{smallmatrix} 0,15 \\ -0,05 \end{smallmatrix}$

NOTE Datum C depending on the style of the polarization area (hole or slot).

Figure 1 — Squib holder interface with male contacts

A sealed option of the pyrotechnic device/initiator harness connector assembly shall be as defined in [Annex A](#).

A variant without retainer of the pyrotechnic device/initiator harness connector assembly shall be as defined in [Annex B](#).

An alternative material variant of the pyrotechnic device/initiator harness connector assembly shall be as defined in [Annex C](#).

5 Material characteristics

5.1 Material specifications for male contacts

The male contacts shall be manufactured of solid material (not folded or hollow).

5.2 Contacts and short circuit areas of the male contacts specifications

Male contact plating shall comply with the following characteristics:

- ASTM B488, min. type II (coating purity), code C (hardness) and class (coating thickness) to be agreed between the customer and the supplier but not less than class 0,5;
- ASTM B735, porosity max. 2 pores/mm²; diameter X of pores which are counted $X > 0,05\text{ mm}$;
- Ni under layer according to ASTM B689, type I or II (coating purity) and class (coating thickness) to be agreed between the customer and the supplier but not less than class 2.

Male contact surface shall comply with the following characteristic:

- Surface roughness $R_a\ 0,4\ \mu\text{m}$ according to ISO 1302.


Annex A (normative)

Sealed variant of the pyrotechnic device/initiator harness connector assembly

All contents of the main document are applicable for the sealed design, except key 2 of [Figure 1](#) (see also [Figure A.1](#)).

For sealed connectors, a seal is inserted between the squib holder and the connector. The space to be left free for the seal shall comply with [Figure A.1](#).

Dimensions in millimetres



Key

- A with retainer
- B without retainer (see [Annex B](#))
- 1 all shapes accepted
- 2 surface reserved for sealing as option
- 3 possible sealing surfaces, selection has to be agreed between customer and supplier
- 4 alternative $45^\circ \pm 2^\circ$ and $0,5 \pm 0,1$

Figure A.1 — Sealing


Annex B (normative)

Variant without retainer of the pyrotechnic device/initiator harness connector assembly

All contents of the main document are applicable for the design without retainer.

Without retainer, only the anti-rotational feature can exceed the squib holder bottom. Initiator and connector shall comply with [Figure B.1](#).

Dimensions in millimetres



Key

- A symmetrical option
- B asymmetrical option
- 1 squib holder as defined in [Figure 1](#)
- 2 anti-rotational feature for symmetrical and asymmetrical option

Figure B.1 — Pocket interface with male contacts