
**Space data and information transfer
systems — Operation of CFDP over
encapsulation service**

*Systèmes de transfert des informations et données spatiales —
Exploitation du CFDP lors des services d'encapsulation*

STANDARDSISO.COM : Click to view the full PDF of ISO 20105:2015



STANDARDSISO.COM : Click to view the full PDF of ISO 20105:2015



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 20105 was prepared by the Consultative Committee for Space Data Systems (CCSDS) (as CCSDS 722.1-M-1, March 2014) and was adopted (without modifications except those stated in clause 2 of this International Standard) by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 13, *Space data and information transfer systems*.

STANDARDSISO.COM : Click to view the full PDF of ISO 20105:2015



The Consultative Committee for Space Data Systems

Recommendation for Space Data System Practices

OPERATION OF CFDP OVER ENCAPSULATION SERVICE

RECOMMENDED PRACTICE

CCSDS 722.1-M-1

MAGENTA BOOK

March 2014

AUTHORITY

Issue:	Recommended Practice, Issue 1
Date:	March 2014
Location:	Washington, DC, USA

This document has been approved for publication by the Management Council of the Consultative Committee for Space Data Systems (CCSDS) and represents the consensus technical agreement of the participating CCSDS Member Agencies. The procedure for review and authorization of CCSDS documents is detailed in *Organization and Processes for the Consultative Committee for Space Data Systems* (CCSDS A02.1-Y-3), and the record of Agency participation in the authorization of this document can be obtained from the CCSDS Secretariat at the address below.

This document is published and maintained by:

CCSDS Secretariat
Space Communications and Navigation Office, 7L70
Space Operations Mission Directorate
NASA Headquarters
Washington, DC 20546-0001, USA

STATEMENT OF INTENT

The Consultative Committee for Space Data Systems (CCSDS) is an organization officially established by the management of its members. The Committee meets periodically to address data systems problems that are common to all participants, and to formulate sound technical solutions to these problems. Inasmuch as participation in the CCSDS is completely voluntary, the results of Committee actions are termed **Recommendations** and are not in themselves considered binding on any Agency.

CCSDS Recommendations take two forms: **Recommended Standards** that are prescriptive and are the formal vehicles by which CCSDS Agencies create the standards that specify how elements of their space mission support infrastructure shall operate and interoperate with others; and **Recommended Practices** that are more descriptive in nature and are intended to provide general guidance about how to approach a particular problem associated with space mission support. This **Recommended Practice** is issued by, and represents the consensus of, the CCSDS members. Endorsement of this **Recommended Practice** is entirely voluntary and does not imply a commitment by any Agency or organization to implement its recommendations in a prescriptive sense.

No later than five years from its date of issuance, this **Recommended Practice** will be reviewed by the CCSDS to determine whether it should: (1) remain in effect without change; (2) be changed to reflect the impact of new technologies, new requirements, or new directions; or (3) be retired or canceled.

In those instances when a new version of a **Recommended Practice** is issued, existing CCSDS-related member Practices and implementations are not negated or deemed to be non-CCSDS compatible. It is the responsibility of each member to determine when such Practices or implementations are to be modified. Each member is, however, strongly encouraged to direct planning for its new Practices and implementations towards the later version of the Recommended Practice.

FOREWORD

This document is a technical **Recommended Practice** for use in developing flight and ground systems for space missions and has been prepared by the **Consultative Committee for Space Data Systems** (CCSDS). The **Recommended Practice** described herein is intended for missions that are cross-supported between Agencies of the CCSDS.

This **Recommended Practice** specifies methods for operating the CCSDS File Delivery Protocol (CFDP) over the CCSDS Encapsulation Service.

Through the process of normal evolution, it is expected that expansion, deletion, or modification of this document may occur. This Recommended Practice is therefore subject to CCSDS document management and change control procedures, which are defined in the *Organization and Processes for the Consultative Committee for Space Data Systems* (CCSDS A02.1-Y-3). Current versions of CCSDS documents are maintained at the CCSDS Web site:

<http://www.ccsds.org/>

Questions relating to the contents or status of this document should be addressed to the CCSDS Secretariat at the address indicated on page i.

At time of publication, the active Member and Observer Agencies of the CCSDS were:

Member Agencies

- Agenzia Spaziale Italiana (ASI)/Italy.
- Canadian Space Agency (CSA)/Canada.
- Centre National d'Etudes Spatiales (CNES)/France.
- China National Space Administration (CNSA)/People's Republic of China.
- Deutsches Zentrum für Luft- und Raumfahrt (DLR)/Germany.
- European Space Agency (ESA)/Europe.
- Federal Space Agency (FSA)/Russian Federation.
- Instituto Nacional de Pesquisas Espaciais (INPE)/Brazil.
- Japan Aerospace Exploration Agency (JAXA)/Japan.
- National Aeronautics and Space Administration (NASA)/USA.
- UK Space Agency/United Kingdom.

Observer Agencies

- Austrian Space Agency (ASA)/Austria.
- Belgian Federal Science Policy Office (BFSPPO)/Belgium.
- Central Research Institute of Machine Building (TsNIIMash)/Russian Federation.
- China Satellite Launch and Tracking Control General, Beijing Institute of Tracking and Telecommunications Technology (CLTC/BITTT)/China.
- Chinese Academy of Sciences (CAS)/China.
- Chinese Academy of Space Technology (CAST)/China.
- Commonwealth Scientific and Industrial Research Organization (CSIRO)/Australia.
- Danish National Space Center (DNSC)/Denmark.
- Departamento de Ciência e Tecnologia Aeroespacial (DCTA)/Brazil.
- European Organization for the Exploitation of Meteorological Satellites (EUMETSAT)/Europe.
- European Telecommunications Satellite Organization (EUTELSAT)/Europe.
- Geo-Informatics and Space Technology Development Agency (GISTDA)/Thailand.
- Hellenic National Space Committee (HNSC)/Greece.
- Indian Space Research Organization (ISRO)/India.
- Institute of Space Research (IKI)/Russian Federation.
- KFKI Research Institute for Particle & Nuclear Physics (KFKI)/Hungary.
- Korea Aerospace Research Institute (KARI)/Korea.
- Ministry of Communications (MOC)/Israel.
- National Institute of Information and Communications Technology (NICT)/Japan.
- National Oceanic and Atmospheric Administration (NOAA)/USA.
- National Space Agency of the Republic of Kazakhstan (NSARK)/Kazakhstan.
- National Space Organization (NSPO)/Chinese Taipei.
- Naval Center for Space Technology (NCST)/USA.
- Scientific and Technological Research Council of Turkey (TUBITAK)/Turkey.
- South African National Space Agency (SANSA)/Republic of South Africa.
- Space and Upper Atmosphere Research Commission (SUPARCO)/Pakistan.
- Swedish Space Corporation (SSC)/Sweden.
- Swiss Space Office (SSO)/Switzerland.
- United States Geological Survey (USGS)/USA.

DOCUMENT CONTROL

Document	Title	Date	Status
CCSDS 722.1-M-1	Operation of CFDP over Encapsulation Service, Recommended Practice, Issue 1	March 2014	Original issue

STANDARDSISO.COM : Click to view the full PDF of ISO 20105:2015

CONTENTS

<u>Section</u>	<u>Page</u>
1 INTRODUCTION.....	1-1
1.1 PURPOSE AND SCOPE OF THIS DOCUMENT	1-1
1.2 APPLICABILITY	1-1
1.3 RATIONALE.....	1-1
1.4 DOCUMENT STRUCTURE	1-1
1.5 CONVENTIONS AND DEFINITIONS.....	1-2
1.6 NOMENCLATURE	1-2
1.7 REFERENCES	1-3
2 OVERVIEW	2-1
2.1 GENERAL.....	2-1
2.2 CONTEXT AND GUIDELINES	2-1
3 CFDP-OVER-ENCAPSULATION	3-1
3.1 GENERAL.....	3-1
3.2 DISCUSSION—CFDP REQUIRED SERVICE	3-1
3.3 DISCUSSION—ENCAPSULATION SERVICE	3-1
3.4 EQUIVALENCIES.....	3-2
ANNEX A INFORMATIVE REFERENCES	A-1
ANNEX B CFDP OPERATION OVER CCSDS SPACE LINKS (INFORMATIVE)..	B-1
ANNEX C OPTIONS FOR DEPLOYMENT INTO GROUND STATION	
NETWORKS (INFORMATIVE).....	C-1
ANNEX D ABBREVIATIONS.....	D-1

Figure

2-1 CFDP Communication over Encapsulation.....	2-1
B-1 CFDP Earth/Spacecraft Architecture Example	B-1
B-2 CFDP Communication between Earth and a Spacecraft	B-2
B-3 CFDP Proximity Physical Architecture Example.....	B-3
B-4 CFDP Communication with Landed Element	B-4

Table

B-1 Link Designations.....	B-2
B-2 Link Designations.....	B-4

STANDARDSISO.COM : Click to view the full PDF of ISO 20105:2015

1 INTRODUCTION

1.1 PURPOSE AND SCOPE OF THIS DOCUMENT

The CCSDS File Delivery Protocol (CFDP—reference [1]) has been designed to support the transfer of files in a variety of mission scenarios. CFDP offers different qualities of service ranging from best effort to fully reliable and has been specifically optimized for long delay, noisy, and disjoint links. CFDP requires a simple minimum service from the underlying protocols, operating over any link providing a packet communication service.

The purpose of this document is to specify how to operate CFDP over the CCSDS Encapsulation Service (reference [2]) as provided for Earth-to-spacecraft, spacecraft-to-Earth, and spacecraft-to-spacecraft communications. It sets out the communications architecture for CFDP operating over the Encapsulation Service. It describes the service expected by CFDP of the underlying layers and reconciles this with the service provided by the Encapsulation Service.

1.2 APPLICABILITY

This document applies to any mission or equipment claiming to provide a CCSDS-compliant CFDP capability between two endpoints operating over a single CCSDS space link.

1.3 RATIONALE

This document is needed to clarify how CFDP should be used with the CCSDS Encapsulation Service.

1.4 DOCUMENT STRUCTURE

The document has three major sections and four annexes:

- this section, containing administrative information, definitions, and references;
- section 2, describing the communications architecture of CFDP operating over an underlying transport protocol;
- section 3, reconciling the service required of the underlying layer by CFDP with the service provided by the underlying Encapsulation Service;
- annex A, listing informative references;
- annex B, discussing the operation of CFDP over long-haul and planetary CCSDS space links;
- annex C, discussing options for deployment into ground station networks;
- annex D, expanding abbreviations used in the document.

1.5 CONVENTIONS AND DEFINITIONS

1.5.1 DEFINITIONS

1.5.1.1 General

For the purpose of this document the following definitions apply.

1.5.1.2 Definitions from the Open Systems Interconnection (OSI) Basic Reference Model

This document is defined using the style established by the Open Systems Interconnection (OSI) Basic Reference Model (reference [A1]). This model provides a common framework for the development of standards in the field of systems interconnection.

The following terms, used in this Recommended Practice, are adapted from definitions given in reference [A1]:

layer: Subdivision of the architecture, constituted by subsystems of the same rank.

protocol data unit: Unit of data specified in a protocol and consisting of protocol-control information and possibly user data.

protocol ID: Identifier that specifies the layer- $(N+1)$ protocol (type of service data unit) encapsulated within a protocol data unit at layer N .

service: Capability of a layer (service provider) together with the layers beneath it, provided to the service users.

service data unit, SDU: Set of data that is sent by a user of the services of a given layer and is transmitted to a peer service user semantically unchanged.

1.5.1.3 Definitions of Terms as Used in this Recommended Practice

packet: Delimited, octet-aligned data unit.

1.6 NOMENCLATURE

1.6.1 NORMATIVE TEXT

The following conventions apply for the normative specifications in this Recommended Standard:

- a) the words 'shall' and 'must' imply a binding and verifiable specification;
- b) the word 'should' implies an optional, but desirable, specification;
- c) the word 'may' implies an optional specification;

- d) the words 'is', 'are', and 'will' imply statements of fact.

NOTE – These conventions do not imply constraints on diction in text that is clearly informative in nature.

1.6.2 INFORMATIVE TEXT

In the normative section of this document (section 3), informative text is set off from the normative specifications either in notes or under one of the following subsection headings:

- Overview;
- Background;
- Rationale;
- Discussion.

1.7 REFERENCES

The following publications contain provisions which, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All publications are subject to revision, and users of this document are encouraged to investigate the possibility of applying the most recent editions of the publications indicated below. The CCSDS Secretariat maintains a register of currently valid CCSDS publications.

- [1] *CCSDS File Delivery Protocol (CFDP)*. Issue 4. Recommendation for Space Data System Standards (Blue Book), CCSDS 727.0-B-4. Washington, D.C.: CCSDS, January 2007.
- [2] *Encapsulation Service*. Issue 2. Recommendation for Space Data System Standards (Blue Book), CCSDS 133.1-B-2. Washington, D.C.: CCSDS, October 2009.
- [3] *Proximity-1 Space Link Protocol—Data Link Layer*. Issue 5. Recommendation for Space Data System Standards (Blue Book), CCSDS 211.0-B-5. Washington, D.C.: CCSDS, December 2013.
- [4] *TC Space Data Link Protocol*. Issue 2. Recommendation for Space Data System Standards (Blue Book), CCSDS 232.0-B-2. Washington, D.C.: CCSDS, September 2010.
- [5] *TM Space Data Link Protocol*. Issue 1. Recommendation for Space Data System Standards (Blue Book), CCSDS 132.0-B-1. Washington, D.C.: CCSDS, September 2003.
- [6] *AOS Space Data Link Protocol*. Issue 2. Recommendation for Space Data System Standards (Blue Book), CCSDS 732.0-B-2. Washington, D.C.: CCSDS, July 2006.

2 OVERVIEW

2.1 GENERAL

The specification of CFDP is provided by reference [1]. The standard is supplemented by three informational reports, references [A2], [A3], and [A4], and the reader is directed to these for a more detailed explanation of the protocol and its intended targets.

CFDP is designed to run over an Underlying Transport (UT) service that provides to CFDP the following primitives:

UNITDATA.request (UT_SDU, UT Address)
UNITDATA.indication (UT_SDU, UT Address)

This document maps the primitives that CFDP requires onto those provided by the Encapsulation Service (section 3).

2.2 CONTEXT AND GUIDELINES

The protocol configuration for CFDP communication over a CCSDS space link when using the Encapsulation Service is shown in figure 2-1.




Figure 2-1: CFDP Communication over Encapsulation

In figure 2-1, operation of the CFDP entities is shown over the CCSDS Encapsulation Service (reference [2]).

3 CFDP-OVER-ENCAPSULATION

3.1 GENERAL

3.1.1 CFDP shall operate, via the CCSDS Encapsulation Service, defined in reference [2], over CCSDS space links (references [3], [4], [5], and [6]).

3.1.2 CCSDS space links shall support the Encapsulation Service via the primitives defined in reference [2].

3.2 DISCUSSION—CFDP REQUIRED SERVICE

CFDP defines the service primitives and parameters required to be provided by the underlying layer as:

UNITDATA.request (UT_SDU, UT Address)

UNITDATA.indication (UT_SDU, UT Address)

NOTES:

- 1 The format and contents of the UT Address parameter depend on the addressing capabilities and conventions of the underlying service. Information in the Management Information Base (MIB) must enable translation between CFDP entity names and the corresponding UT addresses.
- 2 The assumed minimum underlying quality of service is:
 - with possible errors in the delivered UT_SDUs;
 - incomplete, with some UT_SDUs missing;

3.3 DISCUSSION—ENCAPSULATION SERVICE

The Encapsulation Service (reference [2]) provides the following service primitives and parameters:

ENCAPSULATION.request (Data Unit, SDLP_Channel, PVN, EPI)

ENCAPSULATION.indication (Data Unit, SDLP_Channel, PVN, EPI,
Data Unit Loss Flag (optional))

Where:

- Data Unit is the SDU to be transferred.
- SDLP_Channel is part of the SAP address of the Encapsulation Service. It uniquely identifies the channel of the underlying Space Data Link Protocol (SDLP) through which the Data Unit is to be transferred. Reference [2] describes the SDLP_Channel semantics; the exact semantics depend on the underlying SDLP services.

RECOMMENDED PRACTICE FOR OPERATION OF CFDP OVER ENCAPSULATION SERVICE

- PVN is part of the SAP address of the Encapsulation Service and is the Packet Version Number (of the Encapsulation Service, either Encapsulation or CCSDS Packet).
- EPI is part of the SAP address of the Encapsulation Service; depending on the protocol used to implement the encapsulation service, the EPI is either an Application Process Identifier (APID) or the Protocol Identifier.
- The Data Unit Loss Flag is an optional parameter that may be used to notify the user at the receiving end of the Encapsulation Service that a sequence discontinuity has been detected and that one or more Data Units have been lost. This flag may be used only if the Space Packet is used for encapsulation. This parameter, if present, is ignored by implementations of this specification.

3.4 EQUIVALENCIES

3.4.1 To reconcile the service required by CFDP and the service provided by the Encapsulation service the following equivalences shall be used:

- CFDP UT_SDU = Encapsulation Data Unit;
- CFDP UT Address = Encapsulation SAP Address
= Encapsulation SDLP_Channel + PVN + EPI.

3.4.2 A CFDP UNITDATA.request shall generate an ENCAPSULATION.request where:

- The CFDP protocol data unit UT_SDU to be transferred shall be the Encapsulation Data Unit.
- The CFDP UT Address shall contain SDLP_Channel, PVN, and EPI.

3.4.3 A ENCAPSULATION.indication shall generate a CFDP UNITDATA.indication where:

- The CFDP protocol data unit UT_SDU shall contain the received Encapsulation Data Unit.
- The CFDP UT Address shall contain the SDLP_Channel, PVN, and EPI.

3.4.4 The EPI value shall be either an APID (if the Space Packet is used) or a Protocol ID (if the Encapsulation Packet is used).

3.4.4.1 The EPI value shall be set to the CCSDS APID for CFDP when the Encapsulation Service uses CCSDS Packets.

3.4.4.2 The EPI value shall be set to the CCSDS Encapsulation Protocol Identifier for CFDP when the Encapsulation Service uses Encapsulation Packets.

3.4.4.3 If Space Packets are used by the Encapsulation Service used by this specification, the optional Data Loss Flag shall be ignored by implementations of this specification.

NOTE – The SDLP_Channel, PVN, and EPI fields used by CFDP for encapsulation are configured as part of the CFDP Remote Entity Configuration Information.

ANNEX A

INFORMATIVE REFERENCES

(INFORMATIVE)

- [A1] *Information Technology—Open Systems Interconnection—Basic Reference Model: The Basic Model*. 2nd ed. International Standard, ISO/IEC 7498-1:1994. Geneva: ISO, 1994.
- [A2] *CCSDS File Delivery Protocol (CFDP)—Part 1: Introduction and Overview*. Issue 3. Report Concerning Space Data System Standards (Green Book), CCSDS 720.1-G-3. Washington, D.C.: CCSDS, April 2007.
- [A3] *CCSDS File Delivery Protocol (CFDP)—Part 2: Implementers Guide*. Issue 3. Report Concerning Space Data System Standards (Green Book), CCSDS 720.2-G-3. Washington, D.C.: CCSDS, April 2007.
- [A4] *CCSDS File Delivery Protocol (CFDP)—Part 3: Interoperability Testing Final Report*. Issue 1. Report Concerning Space Data System Standards (Green Book), CCSDS 720.3-G-1. Washington, D.C.: CCSDS, September 2007.

ANNEX B

CFDP OPERATION OVER CCSDS SPACE LINKS

(INFORMATIVE)

Figure B-1 shows an example of the CFDP Earth/spacecraft scenario.




Figure B-1: CFDP Earth/Spacecraft Architecture Example

The scenario includes two elements:

- the ground segment;
- a spacecraft such as a LEO or geostationary Earth orbiter or a planetary orbiter.


Although the ground segment is more complex than a single control center, it is sufficient for the purposes of this document to assume that the ground station network is transparent to the link services, probably operating at the Space Link Extension (SLE) frame level, and that the Mission Control Centre (MCC) is transparent or it assumes the role of the CFDP end point.

The space data links are designated as in table B-1.

Table B-1: Link Designations

Name	Source	Destination	CCSDS Recommended Standards
Forward Link	Earth	Spacecraft	Telecommand, AOS
Return Link	Orbiter	Earth	Telemetry, AOS

The protocol configuration for direct CFDP transfer between Earth and a spacecraft is shown in figure B-2.

**Figure B-2: CFDP Communication between Earth and a Spacecraft**

In figure B-2, operation of the CFDP entities is shown over CCSDS TC, TM, and AOS (references [4], [5], and [6], respectively). CCSDS standard architecture mandates that CCSDS standard Network Layer (and above) protocols operate over CCSDS space links via the CCSDS Encapsulation Service (reference [2]), which defines protocol identifiers and standard data structures to identify the user protocols and to transfer their protocol data units.

CFDP will operate, via the CCSDS Encapsulation Service, in the Earth-spacecraft link over TC (forward link) and over TM or AOS (return link).

In the forward direction, CFDP Class-2 is more optimized for reliable data transfer over long-delay links than is CCSDS Telecommand COP-1, primarily because of:

RECOMMENDED PRACTICE FOR OPERATION OF CFDP OVER ENCAPSULATION SERVICE

- the use of a negative rather than positive acknowledgement;
- the ability to concatenate multiple fragments of lost data into one retransmission requiring only one retransmission request.

For these reasons it is recommended that CFDP class 2 be used for reliable file transfer in long-haul forward links.

The same advantages apply in the return direction. Furthermore, TM and AOS have no inherent reliability mechanism, and CFDP is easily optimized to operate over unbalanced (high-rate return, low-rate forward) channels.

There is still a case for operating unreliable CFDP in certain circumstances. For instance, for the transmission of highly ephemeral emergency commands in the forward direction and for return of highly redundant data in the return direction.

Figure B-3 shows an example of the CFDP proximity scenario.



Figure B-3: CFDP Proximity Physical Architecture Example

The scenario includes two elements:

- the landed segment;
- a planetary orbiter or free-flying spacecraft.