

First edition
2012-04-15

AMENDMENT 1
2014-09-01

**Mechanical vibration — Measurement
of vibration on ships —**

Part 4:
**Measurement and evaluation of
vibration of the ship propulsion
machinery**

AMENDMENT 1

*Vibrations mécaniques — Mesurage des vibrations à bord des
navires*

*Partie 4: Mesurage et évaluation des vibrations des machines de
propulsion des navires*

AMENDEMENT 1



Reference number
ISO 20283-4:2012/Amd.1:2014(E)

© ISO 2014

STANDARDSISO.COM : Click to view the full PDF of ISO 20283-4:2012/Amd 1:2014



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 2, *Measurement and evaluation of mechanical vibration and shock as applied to machines, vehicles and structures*.

STANDARDSISO.COM : Click to view the full PDF of ISO 20283-4:2012/Amd 1:2014

Mechanical vibration — Measurement of vibration on ships —

Part 4: Measurement and evaluation of vibration of the ship propulsion machinery

AMENDMENT 1

Page 7, 4.5.5.1, last line

Delete “4.5.5.8”, insert “4.5.5.9”.

Page 14, 4.5.5.8

Add 4.5.5.9 after 4.5.5.8.

4.5.5.9 Transverse thrusters driven by vertical electric motors

For transverse thrusters normally in operation for short periods per day, it is not appropriate to apply the same limits as for electric motors in continuous operation and electric motors in the quiet factory. In order to analyse only self-induced vibration, the thruster electric motor bearing housing vibration shall be measured when it is running individually. This permits separation of induced vibration from vibration such as that induced by other thrusters running at the same time.

NOTE Self-induced vibration is vibration having its source in any part of the thruster unit (gearbox, thruster propeller, electric motor, etc.).

For both variable-speed (Fixed Pitch propeller) and constant-speed (Controllable Pitch propeller) transverse thrusters driven by vertical electric motors, running individually at 100 % of power, the limit of self-induced r.m.s. vibration velocity measured on the bearings of the electric motor, and particularly at the highest casing point as indicated in [Figure D.1](#), is 18 mm/s.

For thrusters with CP propeller running individually at zero pitch and nominal rotational speed, the limit of self-induced r.m.s. vibration velocity measured on the bearings of the electric motor, and particularly at the highest casing point as indicated in [Figure D.1](#), is 10 mm/s.

For thrusters of variable speed and with FP propeller, the self-induced r.m.s. vibration velocity should not exceed the limit of 18 mm/s at any operational speed. Additionally for such thrusters, audible load reversal in the gear box is in general to be restricted at any continuous stage of load and rotational speed.

Details of vibration measurements on thruster electric motors are described in [Annex D](#).

Page 20

Add the following [Annex D](#) before the Bibliography.

Annex D (informative)

Measurements on thruster electric motors

D.1 General

The given limit values and measuring procedures are standard procedures for acceptance purposes during initial sea or quay trials. In cases of trouble shooting, operational restrictions due to vibrations or cavitation effects, altered procedures may be applied. The general r.m.s. limit values as defined in 4.5.5.9 apply to each direction of measurement and include the effect of propeller excitation as well as vibration initiated by unbalance of the vertical electric motor rigidly connected to the foundation and the housing, and they refer to the assembled system.

NOTE The acceptable vibration velocity values due to unbalance of the electric motor itself at nominal speed under test bed conditions are much lower, commonly having an r.m.s. value of less than 5 mm/s.

If the limit values for the installed thruster are exceeded, further investigations should be initiated. In the course of such investigations it is necessary to determine the source of each excitation by frequency analysis techniques as well as the amplification effect due to vicinity to structural or thruster's natural frequencies. High response values of vibratory velocities can be caused by excessive excitation of the propeller (cavitation effects, unfavourable torsional vibration behaviour, etc.) or lateral resonances of the thruster excited either by the rotational frequency of the propeller impulses, or a combination of both.

D.2 Procedure for measurement of self-induced vibration

For each thruster running individually at 100 % of power, measurements should be performed in correspondence to the bearings of the electric motor in three directions (vertical, transverse and longitudinal) at the measuring positions shown in [Figure D.1](#). The transverse and longitudinal readings should be taken radially toward the motor shaft, rather than aligned with the global ship coordinate system. The exact location of the transducers as well as the orientation of the two horizontal measurement axes are to be clearly documented in the report.

The thruster should be tested while running in both directions, due to different wake fields caused by the propeller boss.

For reasons of reproducibility, the measurements at transverse thrusters and particularly typical bow thrusters should be carried out at zero ship's speed.

The readings should be taken under steady-state condition with changes less than 30 % over a 2 s period. The measurement duration is defined by the frequency band and resolution (see 4.4.1 and [D.3](#)). Several readings may be averaged.

D.3 Representation of the results

Self-induced vibration values should be expressed as r.m.s. vibration velocity in mm/s from 2 Hz to 500 Hz (narrow-band representation).

NOTE The upper narrow-band limit specified here takes precedence over the guideline of 1 000 Hz in 4.1.

Magnitude versus frequency or harmonic order spectra are recommended for steady runs because they provide diagnostic information for use if the measured vibration amplitudes exceed guidelines established between the involved parties. A resolution of at least 400 spectral lines and a Hanning