



International
Standard

ISO 20957-7

**Stationary training equipment —
Part 7:
Rowing equipment — Additional
specific safety requirements and
test methods**

Appareils d'entraînement fixes —

*Partie 7: Rameurs — Exigences spécifiques de sécurité et
méthodes d'essai supplémentaires*

**Third edition
2024-09**

STANDARDSISO.COM : Click to view the full PDF of ISO 20957-7:2024



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Classification	3
4.1 General	3
4.2 Accuracy classes	3
4.3 Usage classes	4
5 Safety requirements	4
5.1 General	4
5.2 External construction	4
5.2.1 Squeeze and shear points within the accessible area	4
5.2.2 Transmission elements and rotating parts	4
5.2.3 Temperature rise of accessible surfaces	4
5.2.4 Seat	4
5.3 Intrinsic loading	4
5.4 Handles	5
5.5 Load of ropes, belts, chains and their attachment components	5
5.6 Foot strap	5
5.7 Foot support	5
5.8 Endurance	5
5.9 Stability	6
5.10 Additional classified requirements	6
5.11 Additional instructions for use	6
6 Test methods	6
6.1 General	6
6.1.1 Dimensional check	6
6.1.2 Visual examination	6
6.1.3 Tactile examination	6
6.1.4 Performance test	6
6.1.5 Weighing test	6
6.1.6 Load test of ropes, belts, chains and attachment components	7
6.2 Testing of seat	7
6.3 Testing of temperature rise	7
6.4 Testing of intrinsic loading	7
6.5 Testing of foot strap	7
6.6 Testing of foot support	7
6.7 Endurance testing	8
6.8 Testing of stability	8
6.9 Testing of accuracy of the power readouts	8
6.9.1 General	8
6.9.2 Rowing equipment using speed-independent resistance system	9
6.9.3 Rowing equipment using speed-dependent resistance system	9
7 Test report	10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 83, *Sports and other recreational facilities and equipment*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 136, *Sports, playground and other recreational facilities and equipment*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 20957-7:2020), which has been technically revised.

The main changes are as follows:

- referenced standards have been updated with year of publication;
- [Clause 4](#) has been specified and restructured;
- acceptance criteria have been updated for [5.6](#), [5.7](#) and [5.8](#);
- [5.10](#) “Additional classified requirements” has been added;
- [Clause 7](#) has been restructured.

A list of all parts in the ISO 20957 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Stationary training equipment —

Part 7:

Rowing equipment — Additional specific safety requirements and test methods

1 Scope

This document specifies safety requirements for rowing equipment, in addition to the general safety requirements of ISO 20957-1:2013.

This document is applicable to rowing type stationary training equipment, hereinafter referred to as rowing equipment, within the classes H, S and I and classes A, B and C regarding accuracy.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 20957-1:2013, *Stationary training equipment — Part 1: General safety requirements and test methods*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 20957-1:2013 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:


- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

rowing equipment

stationary training equipment with a moving seat simulating a rowing-like motion


Note 1 to entry: See [Figures 1](#) and [2](#).



Key

- | | | | |
|---|-----------------------|----|----------------------------|
| 1 | hand grip | 7 | foot-strap |
| 2 | arm | 8 | display |
| 3 | resistance adjustment | 9 | foot support |
| 4 | seat | 10 | hydraulic/pneumatic piston |
| 5 | rail | 11 | base support |
| 6 | frame | | |

Figure 1 — Example of rowing equipment with hydraulic/pneumatic system



Key

- | | | | |
|---|--------------|----|--------------|
| 1 | handle | 6 | rail |
| 2 | display | 7 | heel support |
| 3 | foot support | 8 | housing |
| 4 | foot-strap | 9 | base support |
| 5 | seat | 10 | hand grip |

Figure 2 — Example of rowing equipment with cable system

4 Classification

4.1 General

The classification given in ISO 20957-1:2013 shall apply.

Equipment shall be classified in accordance with accuracy and usage classes as described in [4.2](#) to [4.3](#).

If the intended use of the equipment is for more than one usage class, it shall fulfil the requirements of each class.

4.2 Accuracy classes

4.2.1 Accuracy classes shall only apply to equipment that display training data.

4.2.2 Class A: high accuracy.

4.2.3 Class B: medium accuracy.

4.2.4 Class C: low accuracy.

4.3 Usage classes

4.3.1 Class S (Studio): professional and/or commercial use.

NOTE Such stationary training equipment is intended for use in training areas of organizations such as sport associations, educational establishments, hotels, clubs and studios, where access and control are specifically regulated by the owner (person who has the legal responsibility).

4.3.2 Class H (Home): domestic use.

NOTE Such stationary training equipment is intended for use in private homes where access to the equipment is regulated by the owner (person who has the legal responsibility).

4.3.3 Class I: professional and/or commercial use provided for inclusive use for people with special needs (e.g. visual, hearing, physical or learning disabilities).

Such equipment shall also be in accordance with class S requirements (see [4.3.1](#)).

NOTE Such stationary training equipment is intended for use in training areas of organizations such as sport associations, educational establishments, hotels, clubs, rehabilitation centres and studios, where access and control are specifically regulated by the owner (person who has the legal responsibility).

5 Safety requirements

5.1 General

Depending on the design of the piece of equipment, the following requirements shall apply, as appropriate.

5.2 External construction

5.2.1 Squeeze and shear points within the accessible area

The squeeze and shear points within the accessible area shall be in accordance with ISO 20957-1:2013.

5.2.2 Transmission elements and rotating parts

Transmission elements (e.g. chains, belts and ropes) and rotating parts (e.g. fans and flywheels) shall be in accordance with ISO 20957-1:2013.

5.2.3 Temperature rise of accessible surfaces

Accessible surfaces of the rowing equipment shall have a temperature of ≤ 65 °C.

Test in accordance with [6.3](#).

5.2.4 Seat

The seat shall not derail when a load of ≥ 100 N is applied to the seat in all directions. The load shall be applied for ≥ 1 min.

Test in accordance with [6.2](#).

5.3 Intrinsic loading

The rowing equipment shall withstand a load of 2,5 times the maximum user's body mass ± 5 % as specified by the manufacturer or 2 500 N, whichever is greater.

After the test, the rowing equipment shall not be broken or have visible signs of fracture or cracking and shall still function as intended by the manufacturer.

Test in accordance with [6.4](#).

5.4 Handles

In rowing equipment where the handle is connected to the rowing equipment by a flexible member (rope, belt or chain), the mass of the handle without a flexible member shall be ≤ 600 g.

The range of movement of the handle shall be more than 1 600 mm measured from the centre line of the foot rest to the centre of the handle.

Test in accordance with [6.1.1](#) and [6.1.5](#).

5.5 Load of ropes, belts, chains and their attachment components

Rowing equipment using ropes, belts, chains and attachment components (e.g. snap links, shackles, carabineers, clamps or similar) shall withstand a static load of $(2\ 100 \pm 30)$ N. The static load is calculated from a load of (350 ± 5) N multiplied with a safety factor of 6.

Test in accordance with [6.1.6](#).

5.6 Foot strap

Provisions shall be made for fastening the foot (foot straps). For classes S and I, the foot support or foot strap shall be adjustable for different foot sizes.

Test in accordance with [6.1.4](#).

Each foot strap shall withstand a pull force of ≥ 500 N perpendicular to the foot support. The load shall be applied for ≥ 1 min.

After the test, the rowing equipment shall not be broken or have visible signs of fracture or cracking and shall still function as intended by the manufacturer.

Test in accordance with [6.5](#).

5.7 Foot support

Each foot support shall withstand a push force of $\geq 1\ 000$ N perpendicular to the foot support. The load shall be applied for ≥ 1 min.

After the test, the rowing equipment shall not be broken or have visible signs of fracture or cracking and shall still function as intended by the manufacturer.

Test in accordance with [6.6](#).

5.8 Endurance

The rowing equipment shall withstand

- 12 000 cycles for class H, and
- 100 000 cycles for classes S and I,

while loaded with the maximum body weight specified by the manufacturer or 100 kg whichever is greater and with the maximum resistance applied.

After the test, the rowing equipment shall not be broken or have visible signs of fracture or cracking and shall still function as intended by the manufacturer.

Test in accordance with [6.7](#).

5.9 Stability

The rowing equipment shall not tip over.

Test in accordance with [6.8](#).

5.10 Additional classified requirements

Classes A, B and C shall fulfil the requirements in accordance with [Table 1](#).

Table 1 — Classified requirements for adjustable systems

Requirement	Class A	Class B	Class C
Power display Test in accordance with 6.1.2 .	Shall display power in watts. Adjustment by steps.	Shall not display power in watts. Adjustment by steps.	Shall not display power in watts.
Accuracy for the power display Test in accordance with 6.1.2 and 6.9 .	The accuracy of the power display shall be within the tolerance of $\pm 10\%$ or $\pm 5\text{ W}$ for values $< 50\text{ W}$.	Not applicable.	Not applicable.

5.11 Additional instructions for use

In addition to the general instructions for use in accordance with ISO 20957-1:2013, at least the following information shall be given:

- for class A, testing parameters: training speed, resistance setting and range of movement;
- handling and storage.

6 Test methods

6.1 General

6.1.1 Dimensional check

The measurement shall be done with appropriate measurement devices.

6.1.2 Visual examination

The visual examination shall be done under proper lighting.

6.1.3 Tactile examination

The tactile examination shall be done without gloves.

6.1.4 Performance test

The tested mechanism shall be actuated as intended by the manufacturer.

6.1.5 Weighing test

The measurement of the weight shall be done with appropriate measurement devices.

6.1.6 Load test of ropes, belts, chains and attachment components

Pull out the rope, belt or chain (80 ± 10) % of the range of motion and clamp it. Apply the test load to the handles to load the ropes, belts, chains and attachment components between the clamp and the handles.

6.2 Testing of seat

Apply the load in accordance with [5.2.4](#) for ≥ 1 min.

Check whether the seat always remains attached to the rail.

6.3 Testing of temperature rise

Measure the temperature with an accuracy of ± 1 °C.

Operate the rowing equipment for (20 ± 1) min with the following values:

- frequency of $(30^{+1}_{-0}) \text{ min}^{-1}$;
- (60^{+5}_{-0}) % of the maximum range of motion of the hand grip;
- at maximum resistance for the rowing equipment.

Within 10 s after the test, measure the temperature of all exposed surfaces.

6.4 Testing of intrinsic loading

Place the rowing equipment freely on a flat floor and clamp the seat in the most onerous position along the rail.

Apply the test force specified in [5.3](#) to the centre of the seat using a $(300 \pm 5) \text{ mm} \times (300 \pm 5) \text{ mm}$ plate for at least 2 min.

The equipment shall not be fixed to the floor during the test.

6.5 Testing of foot strap

Apply the test force specified in [5.6](#) at the centre of the foot-strap using a $(80 \pm 5) \text{ mm}$ wide belt for a period of $(2 \pm 1) \text{ min}$.

6.6 Testing of foot support

Apply the test force specified in [5.7](#) to the foot support by using the test device according to [Figure 3](#) for $(2 \pm 1) \text{ min}$.




Figure 3 — Test device for testing foot supports

6.7 Endurance testing

Perform the endurance test for the number of cycles specified in 5.8 with the following values:

- frequency of $(30^{+1}_{-0}) \text{ min}^{-1}$;
- $(90 \pm 5) \%$ of the maximum range of motion of the seat.

The endurance test may be performed continuously or in intervals of at least 5 % of the required test cycles. Each interval may be followed by a cool down period as per manufacturer's recommendations.

6.8 Testing of stability

Carry out the test in accordance with the stability test in ISO 20957-1:2013.

6.9 Testing of accuracy of the power readouts

6.9.1 General

Compare the mechanical power input to the power display.

The displayed power in watts shall be within the tolerance given in 5.10.

The test apparatus shall be accurate to $\pm 2 \%$.

The stroke travel shall be 60 % of the maximum possible travel of the hand grips.

Measurements can be performed using a dynamometer or by calculating the input force, distance and time.