



**International
Standard**

ISO 21573-1

**Building construction machinery and
equipment — Concrete pumps —**

**Part 1:
Commercial specifications**

**Third edition
2024-08**

STANDARDSISO.COM : Click to view the full PDF of ISO 21573-1:2024

STANDARDSISO.COM : Click to view the full PDF of ISO 21573-1:2024



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Classification of the concrete pumps	2
5 Commercial specifications	4
5.1 General characteristics	4
5.2 Applicable concrete	5
5.3 Drive	5
5.4 Dimensional characteristics	5
5.5 Cleaning system	6
5.6 Distributing boom	6
5.7 Outrigger component	6
5.8 Hydraulic system	7
5.9 Truck chassis	7
5.10 Trailer chassis	8
5.11 Attachments and tools	8
Annex A (informative) Examples of concrete pump designs and their assemblies	9

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 195, *Building construction machinery and equipment*, Subcommittee SC 1, *Machinery and equipment for concrete work*.

This third edition cancels and replaces the second edition (ISO 21573-1:2014), which has been technically revised.

The main changes are as follows:

- in [Clause 3](#):
 - the definition for “maximum theoretical pumping output” has been updated;
 - the definitions for the following terms have been added:
 - maximum delivery pressure;
 - outrigger span;
- in [Table 1](#), the new classification “drive system” with the following sub-items has been added:
 - fuel engine driven;
 - electric power driven;
 - hybrid power driven;
- in [Table 1](#), the new type “crawler” with sub-item “crawler pump” has been added in the “Mode or frequency of transportation” row;
- in [Table 1](#), the new classification “Type of piston-type concrete pump valve system” with the following sub-items has been added:
 - Swing valve;

- Gate valve;
- in [Clause 5](#), the following subclauses have been updated to match the content in ISO 21573-2:
 - general characteristics ([5.1](#));
 - dimensional characteristics ([5.4](#));
 - distributing boom ([5.6](#));
 - outrigger components ([5.7](#));
- in [Annex A](#), [Figure A.15](#) has been added.

A list of all parts in the ISO 21573 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

STANDARDSISO.COM : Click to view the full PDF of ISO 21573-1:2024

Introduction

This document deals with concrete pumps used on building sites for concrete-mix delivery. It defines technical characteristics of the relevant machines. [Annex A](#) provides examples of current structures of concrete pumps and their principles of operation.

STANDARDSISO.COM : Click to view the full PDF of ISO 21573-1:2024

Building construction machinery and equipment — Concrete pumps —

Part 1: Commercial specifications

1 Scope

This document establishes the content for commercial specifications for concrete pumps which are used on building sites for concrete-mix delivery.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11375:1998, *Building construction machinery and equipment — Terms and definitions*

ISO 21573-2:2020, *Building construction machinery and equipment — Concrete pumps — Part 2: Procedure for examination of technical parameters*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11375 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

piston-type concrete pump

pump in which a piston is used to impart energy to the concrete mix, with the intent of transporting the mix to and through the conveying pipe and/or hose

Note 1 to entry: See [Figure A.1](#).

3.2

rotary-type concrete pump

pump in which a peristaltic action is used to impart energy to the concrete mix with the intent of transporting the mix to and through the conveying pipe and/or hose

Note 1 to entry: See [Figures A.6, A.7, A.8](#) and [A.9](#).

3.3

stationary-type concrete pump

skid, rail or wheeled-chassis mounted concrete pump intended for long-term operation on one building site

Note 1 to entry: See [Figure A.13](#).

3.4

piston-type concrete pump valve system

system composed of cut-off valves successively locking and opening concrete mix flow from the hopper to the concrete cylinder and from the latter to the conveying pipe

Note 1 to entry: See [Figures A.2, A.3, A.4](#) and [A.5](#).

Note 2 to entry: The operation of the valves is synchronized so that, when the concrete-mix flow from the hopper to the concrete cylinder is opened, the flow to the conveying pipe is closed. Various types of valve systems are identified.

3.5

distributing boom

folded boom with fixed concrete mix conveying pipe the role of which is to deliver concrete mix to work areas within its reach

Note 1 to entry: See [Figures A.10](#) and [A.14](#).

Note 2 to entry: The boom has the possibility of folding in the vertical plane and slewing around the vertical axis. Typically, a rubber hose is fixed to the end of the conveying pipe to facilitate concrete-mix distribution.

3.6

maximum applicable size of aggregate

largest size of aggregate that can be consistently delivered through the concrete pump without blockage, including any conveying pipe that is normally supplied on the finished product

3.7

minimum applicable slump

minimum value of slump applicable for conveying by concrete pump

3.8

maximum theoretical pumping output

maximum theoretical volume of concrete per hour calculated based on the designed values of the delivery mechanism of the concrete pump

3.9

maximum delivery pressure

maximum pressure in the delivery line system including the case of blockage in the delivery line system

3.10

outrigger span

actual distance between adjacent centrelines of vertical cylinders with outriggers fully extended or projection distance of the actual distance on the reference plane

Note 1 to entry: The outrigger span shall be measured in accordance with ISO 21573-2:2020, Clause 10.

4 Classification of the concrete pumps

In general, concrete pumps are classified by the following five main characteristics (see [Table 1](#)):

- type of pumping unit;
- type of piston-type concrete pump valve system;
- mode or frequency of transportation;
- form of conveying;
- concrete mix delivery with assistance;
- drive system.

Table 1 — Classification of the concrete pumps

Classification	Type	Current examples	Reference figures
Type of pumping unit	Piston	Hydraulic driven	Figure A.1
		Mechanical driven	—
		Single-piston	—
		Multi-piston	Figure A.1
	Rotary	Vacuum	Figure A.6, A.7
		Elastic	Figure A.8, A.9
Type of piston-type concrete pump valve system	Swing valve	S-type	Figure A.1
		C-type	Figure A.4
		Skirt-type	Figure A.5
	Gate valve	Structure and principle of operation of the gate valve system (horizontal type)	Figure A.2
		Structure and principle of operation of the gate-valve system (vertical type)	Figure A.3
Mode or frequency of transportation	Self-propelled mobile	Truck-mounted	Figures A.10, A.11, A.14 and ISO 11375:1998, Figure 41
	Non self-propelled mobile	Trailer-mounted (with tires on highway)	Figure A.12 and ISO 11375:1998, Figure 42
		Trailer-mounted, steel wheels (rides on rails)	—
		Trailer-mounted, track	—
	Stationary	Skid-mounted/Fixed in place	Figure A.13
		Trailer mounted (with tires off-road)	ISO 11375:1998, Figure 42
	Crawler	Crawler pump	Figure A.15
Form of conveying	With integral distributing boom	Truck mounted	Figure A.10, A.14 and ISO 11375:1998, Figure 41
		Trailer-mounted	ISO 11375:1998, Figure 43
	With separate distributing boom	Tower-mounted boom	ISO 11375:1998, Figure 44
		Articulating distribution arm (with support legs)	—
	With connected conveying line	Pipe and/or hose run from pump to placement	—
Concrete-mix delivery with assistance	With pressurized air	Concrete spraying	—

Table 1 (continued)

Classification	Type	Current examples	Reference figures
Drive system	Fuel engine driven	Stationary type (skid mounted/fixed in place)	Figure A.13
		Trailer mounted (with tires off-road)	ISO 11375:1998, Figure 42
		Trailer mounted (with tires on highway)	Figure A.12
		Truck mounted	Figure A.10, A.14 and ISO 11375:1998, Figure 41
	Electric power driven	Stationary type (skid mounted/fixed in place)	Figure A.13
		Trailer mounted (with tires off-road)	ISO 11375:1998, Figure 42
		Trailer mounted (with tires on highway)	Figure A.12
		Truck mounted	Figure A.10, A.14 and ISO 11375:1998, Figure 41
	Hybrid power driven	Truck mounted	Figure A.10, A.14 and ISO 11375:1998, Figure 41

5 Commercial specifications

5.1 General characteristics

The following characteristics shall be specified:

- model and type;
- manufacturer's name;
- maximum theoretical pumping output (m^3/h);
- maximum delivery pressure (MPa);
- diameter of concrete pumping cylinder (mm);
- stroke length of concrete pumping cylinder (mm);
- number of strokes per minute;
- outlet diameter of concrete valve device (mm);
- capacity of hopper (m^3);
- drive system:
 - fuel engine (kW, torque, water/air cooled, RPM, etc.);
 - electric power (kW, torque, RPM, voltage, current, etc.);
 - hybrid power [kW (combined engine and electric motor), torque (combined engine and electric motor), RPM, voltage, current, etc.];
- acceptable leaning angle of the machine during pumping operation (degrees);
- operating mass (kg);

specify the mass of the concrete pump under the following conditions:

- fully operational and all systems functional;
- with or without cab (to be stated);
- including all standard equipment following the manufacturers' specifications;
- with a driver of mass 75 kg;
- with fuel tank full;
- with cleaning water, cooling, lubrication and hydraulic systems full;
- equipment mass (kg): actual mass of the base machine with equipment specified by the manufacturer.

The manufacturer shall provide means for correlating the machine's theoretical maximum concrete line pressure to the theoretical pumping distance capability.

5.2 Applicable concrete

Specify the following:

- maximum applicable size of aggregate (mm);
- minimum applicable slump (cm).

5.3 Drive

Specify the type of the concrete pump's drive:

- by the vehicle engine/electric power/hybrid power and additional gear box for driving the hydraulic system.
- by a separate diesel engine/electric power/hybrid power for driving the hydraulic system.

5.4 Dimensional characteristics

Specify the following:

- overall dimensions:
 - length, L (mm);
 - width, W (mm);
 - height, H (mm);
- wheel base, L_1 (mm);
- feeding height of hopper H_1 (mm);
- maximum reach in vertical (m);
- maximum reach in horizontal (m).

For the maximum reach of the distributing boom, see [Figure A.14](#).

5.5 Cleaning system

- Conveying-pipe cleaning device

Specify the following:

- operation method (water or pneumatic system);
- performance:
 - delivery volume (l/min);
 - delivery pressure (MPa).
- Cleaning device for other parts

Specify the following:

- model;
- cleaning-water tank capacity (l);
- Water pump specifications (pressure, flow rate).

5.6 Distributing boom

Specify the following:

- model;
- maximum unfolding/folding angles α , β , γ , δ , ε (see [Figure A.14](#)) (degrees);
- maximum slewing angle;
- diameter of the conveying pipe on the boom (mm);
- length of end hose (m);
- number of boom sections;
- mass of the distributing boom:
 - with concrete (kg);
 - without concrete (kg).

5.7 Outrigger component

Specify the following:

- outrigger span:
 - front (mm);
 - rear (mm);
 - lateral (mm);
- maximum load capacity of each outrigger.

5.8 Hydraulic system

Specify the following:

- number of hydraulic pumps;
- hydraulic oil-tank capacity (l);
- boom control block (proportional or nominal directional valve).

For each pump, specify the following:

- application (concrete cylinders drive, cutting-off valves drive, distributing boom drive, outriggers drive, hopper agitator drive);
- model;
- maximum working pressure (MPa).
- maximum delivery volume (l/min).

5.9 Truck chassis

Specify the following:

- general data;
- model;
- load capacity (N);
- number of axles;
- maximum permissible load on axles:
 - front (N);
 - rear (N);
- engine characteristics:
 - model;
 - rated output/engine speed (kW/min⁻¹);
 - maximum torque/engine speed (N·m/min⁻¹);
 - displacement (m³);
- fuel tank capacity (l);
- electric motor characteristics:
 - model;
 - rated output/motor speed (kW/min⁻¹);
 - maximum torque/motor speed (N·m/min⁻¹);
- battery/inverter capacity (kWh).

5.10 Trailer chassis

Specify the following:

- model;
- type of trailer;
- single or double axle;
- load capacity (N);
- maximum permissible load on axle (N).

For a double-axle trailer, specify the permissible load on the front and rear axles.

5.11 Attachments and tools

Specify the following:


- remote-control panel (if any);
- operation manual;
- tools;
- spare parts;
- reduction connection for pipeline with clamp.

STANDARDSISO.COM : Click to view the full PDF of ISO 21573-1:2024

Annex A (informative)

Examples of concrete pump designs and their assemblies


See [Figures A.1](#) to [A.15](#).



Key

- 1 hydraulic valve
- 2 concrete piston
- 3 concrete hopper
- 4 swing pipe
- 5 hydraulic cylinder
- 6 concrete cylinder
- 7 hydraulic cylinder (valve)
- 8 wear plate
- 9 wear ring
- 10 outlet port


Figure A.1 — Structure of piston-type concrete pump (S-type valve)



Key

- 1 concrete cylinder
- 2 suction port
- 3 inlet gate valve
- 4 hydraulic cylinder
- 5 casing
- 6 valve rod
- 7 hydraulic piston
- 8 bushing
- 9 packing (hydraulic cylinder)
- 10 lubricate bushing
- 11 packing (gate valve)
- 12 discharge port
- 13 outlet gate valve
- 14 valve housing
- 15 stopper


Figure A.2 — Structure and principle of operation of the gate valve system (horizontal type)



Key

- 1 hydraulic cylinder
- 2 valve rod
- 3 suction port
- 4 valve plate
- 5 discharge port
- 6 valve casing
- 7 concrete cylinder


Figure A.3 — Structure and principle of operation of the gate-valve system (vertical type)



Key

- 1 concrete hopper
- 2 swing valve
- 3 outlet pipe
- 4 intake-outlet port
- 5 concrete cylinder

Figure A.4 — Structure and principle of operation of the C-type valve system




Key

- 1 concrete hopper
- 2 hydraulic cylinder (valve)
- 3 concrete cylinder
- 4 tapered pipe
- 5 bent pipe
- 6 tapered bent pipe

- 7 outlet pipe
- 8 rock-slicer
- 9 swing valve


Figure A.5 — Structure and principle of operation of the Skirt-valve system



Key

- 1 rubber pad
- 2 drive chain
- 3 rubber roller
- 4 pumping tube
- 5 concrete hopper
- 6 suction port
- 7 discharge port


Figure A.6 — Structure and principle of operation of the rotary-type concrete pump



Key

- 1 guide roller
- 2 pump casing
- 3 rotor frame
- 4 hole cover
- 5 boots
- 6 transfer pipe
- 7 transfer hose
- 8 support beam
- 9 rubber pad
- 10 rubber roller
- 11 roller shaft
- 12 pumping tube
- 13 drain port


Figure A.7 — Structure of the rotary concrete pump (vacuum type)



Key

- 1 pump casing
- 2 rubber pad
- 3 pumping tube
- 4 hydraulic motor
- 5 adjusting screw
- 6 rubber roller
- 7 inlet port
- 8 guide roller (A)
- 9 guide roller (B)
- 10 outlet port
- 11 adjust indicator
- 12 direction of rotation


Figure A.8 — Structure of the rotary concrete pump (elastic-restore type)



Key

- 1 pump casing
- 2 hydraulic motor
- 3 guide roller
- 4 pumping tube
- 5 inlet port
- 6 tube guide
- 7 outlet port
- 8 bearing
- 9 press roller
- 10 rotor


Figure A.9 — Structure of the rotary concrete pump with elastic restore (double roller pump)



Key

- 1 truck chassis
- 2 turn-table
- 3 oil cooler
- 4 oil tank
- 5 boom
- 6 control panel
- 7 concrete hopper
- 8 conveying pipe
- 9 concrete valve
- 10 rear outrigger
- 11 concrete cylinder
- 12 water pump
- 13 front outrigger
- L overall length
- L_1 wheel base
- W overall width
- H overall height
- H_1 hopper height

Figure A.10 — Truck-mounted concrete pump with distributing boom



Key

- 1 truck chassis
- 2 water tank
- 3 oil cooler
- 4 accumulator
- 5 oil tank
- 6 hydraulic valve
- 7 control panel
- 8 concrete hopper
- 9 concrete valve
- 10 concrete cylinder
- 11 water pump
- L overall length
- L_1 wheel base
- W overall width
- H overall height
- H_1 hopper height

Figure A.11 — Truck-mounted concrete pump for connection of a conveying pipeline