

First edition
2007-09-01

AMENDMENT 1
2012-12-01

**Gas cylinders — Cylinder valves with
integrated pressure regulators —
Specification and type testing —
Amendment 1**

*Bouteilles à gaz — Robinets de bouteilles avec détendeur intégré —
Spécifications et essais de type — Amendement 1*



Reference number
ISO 22435:2007/Amd.1:2012(E)

© ISO 2012

STANDARDSISO.COM : Click to view the full PDF of ISO 22435:2007/Amd 1:2012



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 22435:2007 was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 2, *Cylinder fittings*.

STANDARDSISO.COM : Click to view the full PDF of ISO 22435:2007/Amd 1:2012

Gas cylinders — Cylinder valves with integrated pressure regulators — Specification and type testing — Amendment 1

Page 9, 5.17.2

Replace the text with the following:

VIPRs for acetylene shall pass the acetylene decomposition test described in 6.17.

Page 26, 6.17


Replace the subclause with the following:

6.17 Decomposition test method for VIPRs for acetylene

Three samples of the VIPR shall be tested under the conditions of a decomposition of acetylene.

If the VIPR has one or more pressure gauge(s), the test shall be performed without removing them. If the VIPR has a pressure relief device, the test shall be performed without removing it.

The test system (see Figure 7) shall be constructed in a way to resist the respective test conditions.



Key

- 1 ignition source
- 2 inlet tube
- 3 outlet tube
- 4 low pressure side
- 5 filling valve
- 6 stop valve
- 7 VIPR filling port
- 8 VIPR inlet connection

Figure 7 — Test system for acetylene decomposition test

The length of the inlet tube connected to the filling connection of the VIPR shall be 5 m. The length of the outlet tube connected to the cylinder connection (at cylinder neck thread) of the VIPR shall be 1 m. The internal diameter of both tubes shall be 12 mm.

The configuration of the test sample including the filling device (if specified by the manufacturer) shall be the same as when a cylinder is being filled according to the manufacturer's filling instruction. Before testing, the whole test assembly shall be leak tested with nitrogen at 25 bar. The completely assembled test system shall be purged with acetylene for 1 min. Thereafter the stop valve shall be closed and then filled with acetylene up to the test pressure of 25 bar. Then the filling valve of the test assembly shall be closed.

The test should be carried out at 20 ± 5 °C. If the temperature at the test assembly is outside this range, the pressure shall be corrected according to the ideal gas law. Consequently the test shall be carried out at low temperatures with a lower initial pressure and at high temperatures with a higher initial pressure. For safety reasons the minimum temperature for carrying out the test is 5 °C.

The acetylene decomposition is then started by means of a fused wire or by melting a wire as part of the ignition source. Afterwards it shall be checked whether a detonation has occurred. If no detonation has occurred, the test procedure has to be re-done.

The test sample shall withstand the test, without permanent visual deformation or rupture. No flame shall exit the test sample. No part shall be ejected. A destruction of inner parts is permitted.

Rename the number of figures as follows:

- Figure 7 *becomes* Figure 8,
- Figure 8 *becomes* Figure 9,
- Figure 9 *becomes* Figure 10, and
- Figure 10 *becomes* Figure 11.