
Energy efficiency of industrial trucks — Test methods —

Part 1: General

*Efficacité énergétique des chariots de manutention — Méthodes
d'essai —*

Partie 1: Généralités

STANDARDSISO.COM : Click to view the full PDF of ISO 23308-1:2020



STANDARDSISO.COM : Click to view the full PDF of ISO 23308-1:2020



COPYRIGHT PROTECTED DOCUMENT

© ISO 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Test conditions	3
4.1 General	3
4.2 Test equipment	3
4.2.1 Test area	3
4.2.2 Test track	3
4.2.3 Test load and / or towing capacity	3
4.3 Truck conditions	3
4.4 Environmental conditions	4
4.5 Truck maintenance	4
4.6 Battery condition	4
5 Measurement procedure	5
5.1 General	5
5.2 Operating sequence	5
5.3 Electric trucks	5
5.3.1 General	5
5.3.2 Truck measurement	5
5.3.3 Battery efficiency	6
5.3.4 Charger efficiency	7
5.4 Internal combustion (IC)-trucks	7
5.5 Hybrid trucks	7
5.6 Measurement accuracy	7
5.7 Calculation	8
6 Documentation	8
6.1 Test report	8
6.2 Declaration	9
6.2.1 Truck energy consumption	9
6.2.2 Battery efficiency	9
6.2.3 Charger efficiency	9
Annex A (normative) Determination of battery efficiency by using the synthetic discharge cycle	10
Annex B (normative) Simplified procedure to calculate the battery and charging efficiency for lead-acid batteries	15
Annex C (informative) Calculation of the carbon dioxide equivalent	17
Bibliography	20

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 110, *Industrial trucks*, Subcommittee SC 5, *Sustainability*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This document is intended to be used in conjunction with ISO 23308-2 and/or ISO 23308-3.

A list of all parts in the ISO 23308 series can be found on the ISO website.

Introduction

The ISO 23308 series deals with the energy efficiency of industrial trucks including batteries and battery chargers.

This document contains the procedures to determine the efficiency of trucks, traction batteries and battery chargers. The other parts provide a specific test cycle for different truck types.

NOTE The test cycles are based on the VDI 2198 guideline. This guideline is widely accepted by industry and is used to measure the energy consumption of electric industrial trucks and internal combustion (IC) industrial trucks. The guideline has been in place since 1996 and it is used broadly. This approach provides for the evaluation of the energy efficiency of trucks by comparison.

The content of this document is of relevance for the following stakeholder groups:

- machine manufacturers (small, medium and large enterprises);
- market surveillance authorities;
- machine users (small, medium and large enterprises);
- service providers, e.g. for consulting activities.

The stakeholder groups above have been given the opportunity to take part in the drafting process of this document. The machines concerned are indicated in the scope of this document.

STANDARDSISO.COM : Click to view the full PDF of ISO 23308-1:2020

Energy efficiency of industrial trucks — Test methods —

Part 1: General

1 Scope

This document specifies general test criteria and requirements to measure the energy consumption for self-propelled industrial trucks (hereinafter referred to as trucks) during operation. For electric trucks, the efficiency of the battery and the battery charger is included.

The truck specific requirements in ISO 23308-2 and ISO 23308-3 take precedence over the respective requirements of ISO 23308-1.

This document is applicable to the in-use phase of the product life cycle.

It applies to the following truck types according to ISO 5053-1:

- counterbalance lift truck;
- articulated counterbalance lift truck;
- reach truck (with retractable mast or fork arm carriage);
- straddle truck;
- pallet-stacking truck;
- pallet truck;
- platform and stillage truck;
- pallet truck end controlled;
- order-picking truck;
- centre-controlled order-picking truck;
- towing, pushing tractor and burden carrier;
- towing and stacking tractor;
- side-loading truck (one side only);
- variable-reach container handler;
- counterbalance container handler;
- lateral-stacking truck (both sides);
- lateral-stacking truck (three sides);
- multi-directional lift truck.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3691-1:2011, *Industrial trucks — Safety requirements and verification — Part 1: Self-propelled industrial trucks, other than driverless trucks, variable-reach trucks and burden-carrier trucks*

ISO 3691-2:2016, *Industrial trucks — Safety requirements and verification — Part 2: Self-propelled variable-reach trucks*

ISO 5053-1, *Industrial trucks — Terminology and classification — Part 1: Types of industrial trucks*

ISO 15500-1, *Road vehicles — Compressed natural gas (CNG) fuel system components — Part 1: General requirements and definitions*

ISO 23308 (all parts), *Energy efficiency of Industrial trucks — Test methods*

IEC 60254-1, *Lead acid traction batteries — Part 1: General requirements and methods of tests*

IEC 62620:2014, *Secondary cells and batteries containing alkaline or other non-acid electrolytes — Secondary lithium cells and batteries for use in industrial applications*

EN 589, *Automotive fuels — LPG — Requirements and test methods*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5053-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

battery

electrical power source consisting of battery cells, connectors of cells, battery controller (if applicable, e.g. controller for Li-Ion batteries) and battery enclosure that is ready to use in a truck

3.2

battery state of charge

measured capacity (in Ampere hours [Ah]) of the battery divided by the maximum rated capacity [Ah], expressed as a percentage

3.3

carbon dioxide equivalent

CDE

quantity that describes, for a given mixture and amount of greenhouse gas, the amount of CO₂ that would have the same global warming potential (GWP)

3.4

charging factor

ratio between amount of Ah recharged into the battery and the prior discharged amount of Ah from the battery

Note 1 to entry: Typically, the charge factor for lead acid batteries is in the range of 1,02 to 1,25.

3.5**power battery factor****PBF**

factor that gives the ratio between the battery capacity and the electrical power taken from the battery

3.6**synthetic discharge cycle**

typical battery discharge profile that mirrors the actual energy consumption of electric trucks during a test cycle

4 Test conditions**4.1 General**

The following test conditions ensure that the measurement of power consumption is performed in a similar and comparable way.

4.2 Test equipment**4.2.1 Test area**

The test area shall be a flat and smooth area with a hard, clean and dry surface made of concrete, asphalt or equivalent. The test course shall have no more than 2 % slope in any direction of travel.

4.2.2 Test track

For truck type specific information, see the relevant part of the ISO 23308 series.

4.2.3 Test load and / or towing capacity

Unless it is otherwise stated in the specific part of the ISO 23308 series, the test load shall be equal to 70 % of the rated load and standard load centre distance of the truck, in accordance with ISO 3691-1:2011, A.2, or ISO 3691-2:2016, A.1 and A.3.

Tractors shall tow with a force according to 70 % of the rated drawbar pull, as defined in ISO 3691-1:2011, A.3.

Burden-carriers shall be laden with 70 % of the maximum payload, as defined by the manufacturer.

4.3 Truck conditions

The truck to be tested shall be a sample that is representative of series production. For all parts of the truck, with effect to the energy consumption, a run-in time of up to 100 h is permissible. The run-in time shall be documented.

The truck to be tested shall be in a safe and functional state. All equipment attached shall be in accordance to the specification of the manufacturer of the truck.

The set-up of the truck (e.g. software parameters) shall be available as per the manufacturer's specification. This requirement means that the truck performance as specified is achievable (e.g. driving and lifting speed, acceleration) and all software settings are commercially available to the customer.

NOTE For instance, the test driver can adapt the maximum driving speed to achieve the number of cycles per hour.

The test truck shall be fitted with new tyres (maximum 10 % of tread wear) which shall comply with the specifications of the manufacturer of the truck. Pneumatic tyres shall be inflated to their correct pressure specified by the truck manufacturer or by default from the tire manufacturer.

The fuel tanks of internal combustion engine trucks shall be filled to the maximum specified level prior to the warm up period. All other tanks shall be filled to their correct operating levels, if applicable.

If the test is to be performed on a sample that is representative for a range of trucks with the same rated capacity but different lift heights, the test shall be carried out on the truck with the specification according to ISO 3691-1:2011, A.2.1. For trucks covered by ISO 3691-2, the specific requirements of the applicable part of the ISO 23308 series shall apply.

For trucks covered by ISO 3691-1, the specified lift height shall be at least the standard lift height according to ISO 3691-1:2011, A.2.2. The truck's specified lift height shall allow the measurement procedures as defined in the specific part of the ISO 23308 series.

If the test is to be performed on a sample that is representative for a range of trucks with the same rated capacity and the lift height is lower than the lift height that is specified in ISO 3691-1:2011, A.2.1 and A.2.2, the test shall be carried out on the truck with the greatest lift height.

If the test is to be performed on a sample representative of a range of electric trucks with the option of different battery capacities, the test shall be carried out on the truck with the standard battery/batteries according to the data sheet of the manufacturer.

4.4 Environmental conditions

The measurement shall be carried out at an environmental temperature range between 5 °C and 35 °C.

The truck in test configuration shall be at operating temperature.

A minimum warm-up period of 10 min is required for the laden truck, before the test starts.

4.5 Truck maintenance

IC-trucks with emissions control systems that can require cleaning or regeneration of the emission control device shall remain within manufacturer recommended parameters throughout the test. It is allowed to block automatic regenerating of the emission control device during the test.

Engines with other emissions control systems utilizing additional reagents/materials shall remain within the parameters recommended by the manufacturer throughout the test.

4.6 Battery condition

Battery efficiencies are influenced by many factors, e.g. cell technology, cell type, cell design and geometry. Therefore, the battery efficiency as stated in [6.2.2](#) is representative for the tested battery type/battery manufacturer.

If the battery technology requires any energy consuming auxiliary device, e.g. battery management system, controller, cooling or heating, this shall be included in the test.

The battery shall be charged to the rated capacity prior to the respective test. When tests require discharging to the rated minimum capacity of the battery, this shall be determined by one of the following methods.

- a) Lead-acid batteries voltage: the battery is discharged if the voltage is less than or equal to 1,6 V/cell (according to IEC 60254-1 for discharge current I₁).
- b) Lead-acid rated capacity: the battery is discharged if 80 % of the rated capacity is taken from the battery during the test. Recuperation may be considered by calculating with 75 % of the recuperated current over time.
- c) Other technologies: discharge criteria are defined by the battery manufacturer. This criterion shall be consistent with all other specification provided with the battery type, e.g. identical life time and

life cycle characteristic based on endurance tests. A discharge value given in energy (Wh) may be used depending on the technology.

5 Measurement procedure

5.1 General

[Subclauses 5.2](#) to [5.7](#) describe the measurement procedure that is applicable for trucks in general. For specific information for different truck types, see the relevant part of the ISO 23308 series.

5.2 Operating sequence

Trucks shall operate according to the manufacturer's instruction handbook and the test specification defined in the specific part of the ISO 23308 series with the load according to [4.2.3](#). Unless otherwise stated in the specific part of the ISO 23308 series, pick- and place-cycles may be simulated without depositing the load.

NOTE The test load can be secured.

The speed shall be so adapted as to obtain the specified number of cycles per hour. Unless otherwise stated in the specific part of the ISO 23308 series, simultaneous operations are not permissible, all load handling and travelling functions shall be operated separately.

For truck types that are not covered exhaustively by a specific part of the ISO 23308 series, an appropriate sequence of operations shall be selected depending on the design in accordance with the intended use of the truck.

5.3 Electric trucks

5.3.1 General

To determine the overall energy consumption of electric trucks the test shall consider:

- the overall efficiency of the truck, including motor (s), controller(s) and electrical installation;
- the efficiency of the battery/batteries;
- the efficiency of the battery charger.

Because the equipment of trucks with batteries and battery chargers is versatile, it is generally necessary to differentiate between these elements.

[Subclauses 5.3.2](#) to [5.3.4](#) define the procedure to determine the elements of the system efficiency.

5.3.2 Truck measurement

The battery of the truck shall be charged to the rated capacity prior to the warm-up period.

The measurement of the energy consumption shall start at the first test cycle. The warm-up period shall be excluded from the measurement.

The energy consumption shall be given in terms of the electrical energy that is required for 1 h performing the operating sequence, in kWh/h. This measurement can be done by continuous measurement of voltage and current during the test [see [Formula \(1\)](#)].

The measurement of voltage and current shall be performed at the connector of the truck and the traction battery.

$$E_{\text{truck}} = \int_0^T U_{\text{batt}}(t) * f * I_{\text{batt}}(t) * dt \quad (1)$$

where

- E_{truck} is the energy taken from the battery during the test in Wh;
- U_{batt} is the battery voltage in V;
- I_{batt} is the battery current in A;
- dt is the differential (measurement over time);
- T is the test duration;
- f is the discharge/charge factor with $f = 1$ for $I_{\text{batt}} \geq 0$; and $f = 0,75$ for $I_{\text{batt}} < 0$.

NOTE 1 $I_{\text{batt}} < 0$ represents recuperation. The factor $f = 0,75$ refers to the majority of traction batteries, namely lead-acid batteries.

NOTE 2 The factor f differs for other battery technologies.

If the power consumption is determined by measuring electric charge in Ah, the power consumption shall be calculated by multiplication with the nominal battery voltage.

If the determination of the battery efficiency should be included in the truck measurement procedure, the measurement cycle shall start with a battery charged to its rated capacity and shall continue until the battery is discharged to the rated minimum capacity (see 4.6).

5.3.3 Battery efficiency

The battery efficiency consists of two elements that generate power loss:

- the energy flow to the truck (energy taken by the truck from the battery);
- the energy flow from the charger to the battery (energy for complete recharging of the discharged battery).

NOTE The efficiency varies depending on the battery charging status, the current when discharging, the current and method when charging, the battery temperature and the battery type.

The overall efficiency of the battery shall be determined by:

- direct measurement of current and voltage during discharging the battery by performing the truck measurement according to 5.3.2 until the battery is discharged to the rated minimum capacity (see last paragraph of 5.3.2 and 4.6), and during recharging the battery (see 5.3.4);
- direct measurement of current and voltage during discharging the battery by performing the synthetic discharge cycle (in accordance with Annex A), until the battery is discharged to the rated minimum capacity (see last paragraph of 5.3.2 and 4.6) and during recharging the battery (see 5.3.4¹⁾); or
- using defined battery specific values that are verified to be suitable to determine the battery efficiency for lead acid traction batteries used in a truck (in accordance with Annex B).

1) The synthetic discharge cycle can be used to determine the efficiency of all kind of batteries.

5.3.4 Charger efficiency

The overall efficiency of the charger shall be determined:

- in combination with the truck measurement according to 5.3.2;
- after the battery efficiency evaluation according to 5.3.3; or
- by taking into account information of the charger efficiency operating at its optimum operating point (see Annex B).

If a test is performed, the current and voltage at the charger's terminals shall be continuously measured against time to allow calculation of the charger efficiency.

From this test, the charger efficiency is calculated with Formula (2):

$$\eta_{\text{ch}} = \frac{E_{\text{ch}}}{E_{\text{grid}}} \quad (2)$$

where

- η_{ch} is the charger efficiency;
- E_{ch} is the energy delivered to the battery in Wh;
- E_{grid} is the energy withdrawn from grid supply in Wh.

In addition to the efficiency value, information regarding the power factor should be given in the data sheet and on the type plate of the charger.

The power factor shall be determined for the rated operating point. If this is not possible, the power factor may be determined at 80 % of the rated power. In this case, information should be given in the data sheet.

5.4 Internal combustion (IC)-trucks

The measurement of the energy consumption shall start at the first test cycle. The warm-up period shall be excluded from the measurement.

The energy consumption of diesel and gasoline driven trucks shall be given in fuel per hour (l/h) or, for trucks powered by gas (LPG) or natural gas (CNG), in gas consumption per hour (kg/h).

The LPG quality shall be in accordance to EN 589.

The CNG quality shall be in accordance to ISO 15500-1.

Diesel fuel shall be determined by weight, calculated for 15 °C. The density of the fuel of 830 kg/m³ shall be used, which corresponds with the average as defined in EN 590.

5.5 Hybrid trucks

Hybrid trucks shall be tested according to 5.4.

After the test, the energy stored in accumulators (e.g. electrical, pneumatic or hydraulic) shall not be less than before starting the test.

NOTE Starter batteries are not subject to this requirement.

5.6 Measurement accuracy

Suitable measurement equipment shall be selected.

The following tolerances or accuracies of the measurement equipment shall be taken into consideration.

All measuring equipment shall have an accuracy of ± 2 % maximum. The time measuring equipment (e.g. stopwatch) shall have an accuracy of $\pm 0,1$ % maximum.

The energy/fuel efficiency test in accordance to the specific part of the ISO 23308 series shall be performed in a way that a tolerance of maximum ± 5 % is ensured for the tested truck.

This shall be verified by:

- evaluation of the test record (e.g. if voltage and current are recorded); or
- repeating the test and calculate a median value and the standard deviation (e.g. if only the electric charge is measured).

Continuous reading of the energy/fuel consumption, e.g. by continuous fuel measurement or electric energy measurement by the controller, can be used for measurement if the accuracy of the system is verified.

The result may be rounded to one decimal place. This test result shall be documented in accordance to [Clause 6](#).

5.7 Calculation

Calculations, computer modelling or other equivalent simulating methods, based on empirical data, are permissible if these methods are producing comparable results.

When comparing calculated and test values, the test values are considered the true measure of power consumption.

6 Documentation

6.1 Test report

The test report shall contain the following details:

- a) a reference to this document (i.e. ISO 23308-1);
- b) specification of the tested truck in respect to its marking;
- c) in case of type testing, a reference to the type series;
- d) specification of truck equipment (e.g. attachment, cabin, specification of filled hydraulic oil, etc.);
- e) specification of tyres (manufacturer, type, material, dimensions, pressure of pneumatic tyres);
- f) operation modes and/or setting of operator assistance devices;
- g) the set-up of the truck (e.g. software parameters);
- h) specification of the traction battery, if applicable;
- i) specification of the battery charger, if applicable;
- j) the power factor of the battery charger;
- k) the efficiency of the battery and the method used, according to [5.3.3](#), if applicable;
- l) the efficiency of the battery charger and the method used, according to [5.3.4](#), if applicable;
- m) a description of the test track (material, slope, smoothness);

- n) the wind speed, if applicable;
- o) specification of the measurement equipment;
- p) a description of the climatic conditions (temperature);
- q) the date and name of the authorized person;
- r) the result of the test including the achieved tolerance of the energy consumption according to [5.6](#).

Where the verification of the truck design is made by other methods, e.g. simulation, the report shall reasonably be adapted to that specific method.

6.2 Declaration

6.2.1 Truck energy consumption

The manufacturer's instruction handbook accompanying the truck and the manufacturer's documentation²⁾ shall include the appropriate version of the following information:

- energy consumption according to the relevant part of the ISO 23308 series in kWh/h at truck set up³⁾;
- fuel consumption according to the relevant part of the ISO 23308 series in l/h at truck set up;
- gas consumption according to the relevant part of the ISO 23308 series in kg/h at truck set up.

Where conversion of values from 5.3.2, 5.4 and 5.5 into carbon dioxide equivalents is desired in order to calculate the related greenhouse gas emissions of different systems, the methods according to [Annex C](#) should be applied.

6.2.2 Battery efficiency

The battery manufacturer's documentation shall include the overall battery efficiency, η_{Batt} , according to Formula (A.7) including the corresponding charging factor.

The manufacturer's instruction handbook accompanying the battery shall refer to the publicly available manufacturer's document (data sheet).

6.2.3 Charger efficiency

The manufacturer's instruction handbook accompanying the charger and the manufacturer's documentation shall include the overall charger efficiency, η_{Ch} , according to [Formula \(2\)](#).

2) For example, type sheet according to VDI 2198.

3) The truck set up that is used for the measurement as defined in [4.3](#).

Annex A **(normative)**

Determination of battery efficiency by using the synthetic discharge cycle

A.1 General

As the synthetic cycle is scaled to the power battery factor (PBF), it is possible to transfer measurement results to batteries of the same design but different sizes if a representative element of the battery is used.

The applied charging method shall ensure that the service life stated by the battery manufacturer is reached.

Lead-acid batteries shall be charged according to IEC 60254-1. Li-Ion batteries shall be charged according to IEC 62620.

The nominal battery capacity and the efficiency for lead acid batteries is typically based on the constant discharge current for 5 h (I_5). Because this procedure does not represent the application in a truck, the use of the synthetic discharge cycle is recommended.

The cycle can be used to determine the efficiency of all kind of batteries.


Typically, the battery efficiency should be determined by the battery manufacturer.

A.2 Definition of the synthetic discharge cycle

The synthetic discharge cycle consists of a number of blocks, defined by the current magnitude and duration approximating to the individual elements of the cycle.

Recharged energy can be taken as negative values into consideration. The cycle is clustered in order to keep the number of elements of the synthetic discharge cycles small.

See [Figure A.1](#) and [Table A.1](#) for a typical discharge cycle using the power battery factor (PBF) (ratio of the electrical power taken from the battery over the battery capacity).

**Key**

- 1 PBF factor
X time in s
Y power/battery capacity in W/Wh

Figure A.1 — Typical discharge cycle**Table A.1 — Description of the synthetic discharge cycle**

Step	Duration s	PBF factor W/Wh	Charge/Discharge
1	4,5	0,10	Discharge
2	6,0	0,83	Discharge
3	4,5	0,03	Discharge
4	2,5	0,70	Discharge
5	1,5	-0,14	Charge
6	3,5	0,75	Discharge
7	5,0	0,60	Discharge
8	2,5	-0,44	Charge
9	4,5	0,10	Discharge
10	6,0	0,83	Discharge
11	4,5	0,03	Discharge
12	2,5	0,70	Discharge
13	1,5	-0,14	Charge
14	3,5	0,75	Discharge
15	5,0	0,60	Discharge
16	2,5	-0,44	Charge

A.3 Testing according to the synthetic cycle

A.3.1 Preconditions

To ensure comparable results the following test conditions shall be observed. If test conditions deviate, this shall be clearly stated in the test report.

- The battery can be connected to the test equipment directly or by using connectors which are suitable to conduct the required current.
- The rate of current change between the blocks shall be not less than 150 A/100 ms.
- Prior to the test the battery shall be charged to the rated capacity according to the battery manufacturer's definition, e.g. acid electrolyte density for lead-acid batteries, charger control system feedback for Li-Ion batteries.

The battery manufacturer shall define the preconditioning of the battery prior to the test. For example, this takes into account the battery temperature.

- The test shall be performed using the specific power value (see [A.3.2](#)).
- The test using the synthetic discharge cycle ends when the battery is discharged to the rated minimum capacity according to [4.6](#).
- The battery temperature at the beginning of the test shall be $(25 \pm 5) ^\circ\text{C}$.
- Using a reduced cell number is permissible, if cell connectors and other components (e.g. battery management systems, if applicable) of the type used for the complete battery assembly are fitted.

A.3.2 Power value

The specific power value depends on the battery voltage and the effective battery capacity. The discharge power value shall be calculated with [Formula \(A.1\)](#):

$$P_{\text{Cycle}} = Q_{\text{batt}} * PBF * U_{\text{battnom}} \quad (\text{A.1})$$

where

- P_{Cycle} is the power value in W;
- PBF is the power/battery capacity factor;
- Q_{batt} is the effective battery capacity in Ah;
- U_{battnom} is the nominal voltage of the battery in V.

The effective battery capacity is calculated with [Formula \(A.2\)](#):

$$Q_{\text{batt}} = Q_{\text{nom}} * f_{\text{eff}} \quad (\text{A.2})$$

where

- Q_{nom} is the nominal battery capacity in Ah;
- Q_{batt} is the effective battery capacity in Ah;
- f_{eff} is the factor between effective and nominal capacity of the battery.

NOTE 1 For lead acid batteries, f_{eff} is typically 0,8. This value is based on a constant discharge current for 5 h I_5 .

NOTE 2 For Li-Ion batteries f_{eff} is typically 1,0. This value is based on a constant discharge current for 5 h I_5 according to the requirements of IEC 62620:2014, 6.3.1.

EXAMPLE Table A.2 shows an example for a standard lead acid battery with a nominal voltage of 80 V with a nominal capacity of 500 Ah. The effective battery capacity is Formula (A.3):

$$Q_{\text{batt}} = 500 \text{ Ah} \cdot 0,8 = 400 \text{ Ah} \quad (\text{A.3})$$

Table A.2 — Example for the calculation of the power value

Step	Time s	PBF W/Wh	P_{Cycle} W
1	4,5	0,10	3 200
2	6,0	0,83	26 560
3	4,5	0,03	960
4	2,5	0,70	22 400
5	1,5	-0,14	-4 480
6	3,5	0,75	24 000
7	5,0	0,60	19 200
8	2,5	-0,44	-14 080
9	4,5	0,10	3 200
10	6,0	0,83	26 560
11	4,5	0,03	960
12	2,5	0,70	22 400
13	1,5	-0,14	-4 480
14	3,5	0,75	24 000
15	5,0	0,60	19 200
16	2,5	-0,44	-14 080

A.3.3 Test procedure and measurements

During this test, current and voltage against time are continuously measured to allow calculation of the discharged energy, E_{batt} [see Formula (A.4)].

$$E_{\text{batt}} = \int_0^T U_{\text{batt}}(t) \cdot I_{\text{batt}}(t) \cdot dt \quad (\text{A.4})$$

where

E_{batt} is the energy taken from the battery during synthetic discharge cycle in Wh;

U_{batt} is the battery voltage in V;

I_{batt} is the battery current in A;

dt is the differential (measurement over time);

T is the total time to discharge the battery.

After the test, the battery shall be recharged to the rated capacity again, using the charging specifications as provided by the battery manufacturer.

NOTE Depending on the battery technology, these charging specifications as provided by the battery manufacturer can include overcharging.

During this part of the test, current and voltage are continuously measured against time to allow calculation of the charged energy [see [Formula \(A.5\)](#)].

$$E_{\text{ch}} = \int_0^T U_{\text{batt}}(t) * I_{\text{batt}}(t) * dt \quad (\text{A.5})$$

where

E_{ch} is the energy to recharge the battery in Wh;

U_{batt} is the battery voltage in V;

I_{batt} is the battery current in A;

dt is the differential (measurement over time);

T total time to discharge the battery.

From these tests, the overall battery efficiency, η_{batt} , is calculated with [Formula \(A.6\)](#):

$$\eta_{\text{batt}} = \frac{E_{\text{batt}}}{E_{\text{ch}}} \quad (\text{A.6})$$

Annex B (normative)

Simplified procedure to calculate the battery and charging efficiency for lead-acid batteries

B.1 General

The efficiency of lead acid batteries can be calculated by taking the ratio of:

- the energy taken from the battery including power loss; and
- the energy required for the recharging of a discharged battery, including power loss. The applied charging method shall ensure that the service life stated by the battery manufacturer according to IEC 60254-1 can be reached.

The battery efficiency depends on various factors, e.g. the battery cell design, the battery state of charge, the discharge current, the battery temperature, the charging current and method (charging curve) and the charging factor.

The charger efficiency is defined as the ratio of the energy delivered to a discharged battery and the energy taken from the public grid. It varies depending on the charging method (charging curves) and the charger technology.

B.2 Formula

B.2.1 Battery efficiency during discharging based on measurement with constant discharge current

In the case that no testing data according to the synthetic cycle according to [Annex A](#) are available, the battery efficiency can be calculated based on a constant current discharge with the rated 1 h current (I_1) to a discharge voltage of 1,6 V per cell or to the value as specified by the battery manufacturer.

In this case the discharged energy shall be calculated with [Formula \(B.1\)](#):

$$E_{\text{batt}} = \int_0^T I_1 * U_{\text{batt}}(t) * dt \quad (\text{B.1})$$

where

E_{batt} is the energy taken from the battery in Wh;

U_{batt} is the battery voltage in V;

I_1 is the battery current rated 1 h in A;

dt is the differential (measurement over time);

T is the total time to discharge the battery.

NOTE The energy efficiency measured by this method results in a lower energy efficiency compared to the measurement with the synthetic cycle, according to [Annex A](#).

B.2.2 Estimation of the battery efficiency based on generally accepted empirical values

If no values resulting from measurements according to [Annex A](#) or [B.2.1](#) are available, the efficiency can be estimated according to [Table B.1](#).

The values stated in [Table B.1](#) are based on empirical values.

The value given for efficiency takes into account the difference between the standardized method to determine the nominal battery capacity (discharge current for 5 h, I_5) and the typical current profile in an industrial truck (see also [Annex A](#)).

NOTE 1 The estimated values result in a lower efficiency of the battery than the measurement according to the synthetic cycle or according to [B.2.1](#).

Table B.1 — Battery and charging technology specific overall battery efficiency

Battery type	Charging method	η_{batt}
Flooded battery	Taper charge based on DIN 41774	0,5
Flooded battery	Charging regime with current pulses for electrolyte mixing	0,6
Flooded battery	Charging regime with electrolyte mixing by air pump	0,63
Valve regulated lead acid (VRLA) battery with immobilized electrolyte	Regulated IU1a charging regime based on DIN 41773-1	0,67

NOTE 2 Charging method and charging curve significantly influence the efficiency of a lead acid battery.

B.2.3 Charger efficiency

Battery chargers are differentiated between 50 Hz and high frequency (HF) chargers. The charger efficiency is dependent on the battery charger technology.

The overall efficiency of the charger is related to the complete charging process, including charging characteristic, the battery type, size, and condition. The efficiency for the complete charging process is typically 1 % to 2 % lower than the efficiency for the optimum operating point.

Where there are no values available from the manufacturer, [Table B.2](#) can be used.

Table B.2 — Approximate values for charger efficiencies

Charger technology	η_{ch}
HF	0,88
50 Hz regulated	0,78
50 Hz taper	0,73