

INTERNATIONAL STANDARD



2748

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Textile machinery and accessories — Linges for Jacquard weaving

Matériel pour l'industrie textile — Fuseaux pour tissage Jacquard

First edition — 1974-10-01

STANDARDSISO.COM : Click to view the full PDF of ISO 2748:1974

UDC 677.054

Ref. No. ISO 2748-1974 (E)

Descriptors : textile machinery, looms, weaving spindles.

Price based on 1 page

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 2748 was drawn up by Technical Committee ISO/TC 72, *Textile machinery and accessories*, and circulated to the Member Bodies in March 1972.

It has been approved by the Member Bodies of the following countries :

Czechoslovakia	Italy	Thailand
Egypt, Arab Rep. of	Poland	Turkey
Finland	Romania	United Kingdom
Germany	Spain	U.S.S.R.
India	Switzerland	

The Member Bodies of the following countries expressed disapproval of the document on technical grounds :

Belgium
France

Textile machinery and accessories — Lingoos for Jacquard weaving

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies the dimensions and mass of lingoos for Jacquard weaving.

2 DIMENSIONS AND MASS



Dimensions in millimetres

Length L		Mass, in grams, with diameter d							
nominal	actual	2	2,24	2,5	2,8	3,15	3,55	4	4,5
300	290			11			22,5		
	300		9			18			37,5
	310	—			14,5			30,5	
350	340			13			26		
	350		10,5			21			—
	360	8,5			17			35,5	
400	390			15			30		
	400		12			24			—
	410	10			19,5			40,5	
450	440			17			—		
	450		14			—			—
	460	11,5			22			—	