
INTERNATIONAL STANDARD



2976

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Abrasive belts — Selection of width/length combinations

First edition — 1973-11-01

STANDARDSISO.COM : Click to view the full PDF of ISO 2976:1973

UDC 621.922.024

Ref. No. ISO 2976-1973 (E)

Descriptors : Tools, abrasives, belts, dimensions, length, width.

Price based on 1 page

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 2976 was drawn up by Technical Committee ISO/TC 29, *Small tools*, and circulated to the Member Bodies in November 1972.

It has been approved by the Member Bodies of the following countries:

Austria	Israel	Sweden
Belgium	Italy	Switzerland
Czechoslovakia	Mexico	Thailand
Egypt, Arab Rep. of	Poland	Turkey
France	Portugal	United Kingdom
Germany	Romania	U.S.S.R.
Hungary	South Africa, Rep. of	
India	Spain	

The Member Body of the following country expressed disapproval of the document on technical grounds:

Japan

Abrasive belts — Selection of width/length combinations

1 SCOPE AND FIELD OF APPLICATION

This International Standard establishes a selection of width //length L combinations for abrasive belts with respect to the dimensions retained in ISO/R 1929, *Abrasive belts — Designation — Dimensions — Tolerances*.

2 SELECTION OF WIDTH //LENGTH L COMBINATIONS

Dimensions in millimetres

Width // Length L	15	20	25	30	40	50	60	75	100	125	150	200	250	300	350	400	450	500	600	700	800	1 000	1 120	1 250	1 400	1 600	1 800	2 000	2 240	2 500
400	x	x	x	x	x	x	x	x	x																					
500	x	x	x	x	x	x	x	x	x	x																				
630	x	x	x	x	x	x	x	x	x	x	x																			
800	x	x	x	x	x	x	x	x	x	x	x	x																		
1 000	x	x	x	x	x	x	x	x	x	x	x	x	x																	
1 250	x	x	x	x	x	x	x	x	x	x	x	x	x	x																
1 600		x	x	x	x	x	x	x	x	x	x	x	x	x	x															
2 000		x	x	x	x	x	x	x	x	x	x	x	x	x	x	x														
2 500			x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
3 150					x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
4 000						x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5 000							x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
6 300								x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
8 000									x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
10 000										x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
12 500											x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x

NOTE — The tolerances specified in ISO/R 1929 also apply to the width/length combinations given in this International Standard.