

Second edition
2013-09-01

AMENDMENT 1
2016-11-01

**Garden equipment — Safety
requirements for combustion-engine-
powered lawnmowers —**

**Part 2:
Pedestrian-controlled lawnmowers**

**AMENDMENT 1: OPC, cutting means,
pressurized hoses**

*Matériel de jardinage — Exigences de sécurité pour les tondeuses à
gazon à moteur à combustion interne —*

Partie 2: Tondeuses à gazon à conducteur à pied

AMENDEMENT 1: OPC, organes de coupe, tuyaux sous pression



Reference number
ISO 5395-2:2013/Amd.1:2016(E)

© ISO 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

Amendment 1 to ISO 5395-2:2013 was prepared by ISO Technical Committee TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 13, *Powered lawn and garden equipment*.

STANDARDSISO.COM : Click to view the full PDF of ISO 5395-2:2013/Amd 1:2016

Garden equipment — Safety requirements for combustion-engine-powered lawnmowers —

Part 2: Pedestrian-controlled lawnmowers

AMENDMENT 1: OPC, cutting means, pressurized hoses

Page 1, Clause 2

Delete the following reference:

ISO 13849-1:2006, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design*

Page 5, 4.3

Replace 4.3 with the following:

4.3 Operator presence control (OPC)

The lawnmower shall be fitted with operator presence control device(s) which:

- conforms to well-trying principles and applies well-trying components; and
- requires activation by the operator before the lawnmower's traction (if so equipped) and cutting means drive systems can be started; these functions of OPC and starting shall be separate; and
- requires sustained activation by the operator to allow continued operation; and
- automatically activates the stopping of the cutting-means rotation and/or traction-drive system, if so equipped, when the operator releases the control device.

The sustained activation and release functions of the traction-drive OPC can be combined with the cutting means OPC or separate.

A “well-trying component” for a safety-related application is a component which has been either

- a) widely used in the past with successful results in similar applications, or
- b) made and verified using principles which demonstrate its suitability and reliability for safety-related applications.

Newly developed components and safety principles may be considered as equivalent to “well-trying” if they fulfil the conditions of b).

NOTE For further information, see ISO 13849-1 [13].

From a complete stop position, restart of the cutting-means rotation shall require two separate and distinct actions. Activation of the OPC shall be one of the actions. If these actions are to be carried out using the same hand, then the actions shall be separate and dissimilar to prevent accidental restarting of the cutting means.

If the OPC is reactivated before the cutting means have stopped, the cutting means can resume operation if there is sufficient kinetic energy to restart the engine.

Automatic or single-action stopping and starting of the cutting means is permissible during continuous operation of the OPC.

Compliance shall be checked by functional test and inspection.

Page 11, 4.11

Replace 4.11 with the following:

4.11 Pressurized hoses of hydraulic systems

Hoses that operate at a maximum working pressure greater than 5 000 kPa and located less than 1 000 mm from the operator control zone shall be located or shielded so that, in the event of a rupture, the fluid cannot be discharged directly onto the operator when in the normal operating position.

The same requirements apply to pressurized hoses with a working pressure of 500 kPa to 5 000 kPa and within 1 000 mm of the operator control zone and where the temperature of the pressurized fluid exceeds 50 °C when operated at an ambient temperature of 20 °C ± 5 °C.

Compliance shall be checked by inspection and measurement.

Page 17, 5.2

Replace 5.2 with the following:

5.2 Impact of the cutting means

The lawnmower shall withstand a sudden impact to the cutting means in accordance with ISO 5395-1:2013, Annex B and any of the following outcomes of the tests shall be regarded as a failure to meet this requirement:

- target penetration by any part of the lawnmower;
- breakage of the cutting means;
- detachment from the lawnmower of the cutting means or cutting-means arm or disc on which it is mounted.

Breakage of a drive shearing device or chipping of the cutting-means cutting edge shall not be considered as test failures.

It is not required that the machine be suitable for use after the test.

Compliance shall be checked by inspection and tested in accordance with ISO 5395-1:2013, Annex B.

Page 34, Bibliography

Add the following reference:

[13] ISO 13849-1:2015, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design*