

Second edition
2013-09-01

AMENDMENT 2
2017-05

**Garden equipment — Safety
requirements for combustion-engine-
powered lawnmowers —**

**Part 2:
Pedestrian-controlled lawnmowers**

**AMENDMENT 2: Cutting-means-
enclosure guards**

*Matériel de jardinage — Exigences de sécurité pour les tondeuses à
gazon à moteur à combustion interne —*

Partie 2: Tondeuses à gazon à conducteur à pied

AMENDEMENT 2: Enceintes de protection des organes de coupe



Reference number
ISO 5395-2:2013/Amd.2:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

Amendment 2 to ISO 5395-2:2013 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 13, *Powered lawn and garden equipment*.

STANDARDSISO.COM : Click to view the full PDF of ISO 5395-2:2013/Amd 2:2017

Garden equipment — Safety requirements for combustion-engine-powered lawnmowers —

Part 2: Pedestrian-controlled lawnmowers

AMENDMENT 2: Cutting-means-enclosure guards

Page 8, 4.5.2

Revise the subclause with the following:

4.5.2 Opening or detaching of guards

NOTE The provisions of this subclause are mandatory only when required by regional regulations.

The opening or detaching of guards shall require the use of a tool except for:

- a) interlocked guards, in accordance with ISO 14119, which shall prevent access before the moving parts have come to a complete stop. While the hazardous part is exposed, it shall not be possible to apply power to it;
- b) automatically closing guards for side located grass discharge openings in the cutting-means enclosure, which shall cover the opening when the side discharge chute is not fitted. Such guards shall be equipped with a locking mechanism to prevent inadvertent access and be in accordance with the following:
 - the opening shall require a distinct action to unlock the guard prior to a second action to open the guard;
 - when released from the position necessary to remove the adapter or discharge chute, the guard shall automatically return to a closed and locked position to prevent access to the cutting means;
 - the automatically closing side discharge guard shall be a part of the cutting-means enclosure.
 - when in the locked position, a force of 20 N applied to the guard at the most unfavourable position shall not result in the release of the guard from its locked state.
- c) automatically closing guards for grass discharge chutes. Such a guard shall remain in its operating position when:
 - the lawnmower is operated on the coconut matting according to ISO 5395-1:2013, E.6,
 - the cutting means are engaged and operated at maximum operating engine speed, and
 - the cutting means are adjusted to the lowest and highest cutting positions.


Compliance shall be checked by inspection, functional test and measurement.

Revise the subclause with the following:

5.3.2.2 Foot protection test

Protection from contact with cutting means shall be verified by applying the foot protection test in accordance with ISO 5395-1:2013, Annex C to the following:


- a) the front opening, if any;
- b) the discharge opening, if any, including:
 - the area below the discharge opening, if the cutting-means enclosure is less than 3 mm below the cutting-means tip circle as measured to the tip circle at the point of insertion;
 - the sides of any discharge opening or chute, if these are less than 3 mm below the cutting-means tip circle.
- c) the rear of pedestrian-controlled lawnmowers between the wheels as shown in [Figure 8](#) and [Figure 9](#).
- d) areas within 60° on either side of any starting position described in the instruction handbook, which is not in the operator control zone for lawnmowers where the cutting means is not disengaged from the engine by a clutch. The 60° angles shall have their vertices at the centre of rotation of the cutting means nearest to the operator.



Key

- 1 side of discharge chute probed if less than 3 mm below plane of blade tip circle
- 2 discharge opening
- 3 side of discharge chute probed if less than 3 mm below plane of blade tip circle
- 4 foot probe (also probe cutting-means enclosure from any designated starting position)
- 5 cutting-means tip circle
- 6 areas to be probed

Figure 8 — Areas of the lawnmower to be probed



Key

- 1 side of discharge chute probed if less than 3 mm below plane of blade tip circle
- 2 discharge opening
- 3 side of discharge chute probed if less than 3 mm below plane of blade tip circle
- 4 foot probe (also probe deck from any designated starting position)
- 5 cutting-means tip circle
- 6 areas to be probed

Figure 9 — Areas of the lawnmower to be probed

Page 27, 7.1.2

Replace the subclause with the following:

7.1.2 Technical data

The instruction handbook shall give at least the following technical information for each lawnmower model, where required to be declared.

NOTE The provision of this information is mandatory only when required by regional regulations.

Nominal power	kW
Maximum operating engine speed (rotational frequency)	min ⁻¹
Machine mass with empty fuel tanks and in normal operating configuration	kg
Cutting width	cm
Equivalent A-weighted emission sound pressure level at the operator position, determined in accordance with ISO 5395-1:2013, Annex F	dB (A)
— together with the measurement uncertainty	dB (A)
A-weighted sound power level, determined in accordance with ISO 5395-1:2013, Annex F	dB (A)
— together with the measurement uncertainty	dB (A)
For hand-arm vibrations, the highest equivalent vibration total value for the handles or hand positions, determined in accordance with ISO 5395-1:2013	m/s ²
— together with uncertainty of stated value, K	m/s ²
For an operator on a sulky (if applicable), for whole body vibrations the highest root mean square value of weighted acceleration, determined in accordance with ISO 5395-1:2013	m/s ²
— together with uncertainty of stated values, K	m/s ²

Sales literature describing the machinery should not contradict the instructions regarding health and safety aspects.

Sales literature describing the performance characteristics of machinery should not contradict the information on noise emissions and vibration values as are contained in the instruction handbook.